

Halo

DESIGN OLEI TEAM

DOWNLIGHT EMPOTRABLE-LED.

Cuerpo de aluminio y difusor de metacrilato.

LED RECESSED DOWNLIGHT.



Aluminium fitting with pmma diffuser.

Supplied with driver.

External IP43 / IP20 behind ceiling.



SISTEMA REGISTRABLE ADAPTABLE SYSTEM



1621

PCB-LED11w ●●●●●
CÁLIDA / WARM
3000 K-890 lm-350 mA.
NEUTRA / NEUTRAL
4000 K-920 lm-350 mA.
EEI: **A+ ... A**



1622

PCB-LED21w ●●●●●
CÁLIDA / WARM
3000 K-1728lm-350 mA.
NEUTRA / NEUTRAL
4000 K-1886lm-350 mA.
EEI: **A+ ... A**

● NO dim ● dim 1-10v ● dim DALI ● dim PUSH



ACABADOS / FINISH

metal / metal

BM blanco mate / matt white

3000K ● CÁLIDA (se indentifica con C delante la de referencia)
WARM (indicate C before the reference number)

4000K ● NEUTRA (se indentifica con N delante la de referencia)
NEUTRAL (indicate N before the reference number)

.LDT
Ficheros fotométricos
Photometric files
www.olebyfm.com

