



- Die-cast aluminium body.
- Mains voltage: 220-240V / 50-60Hz.
- Clever thermal design.
- With 3-phase universal track adaptor.
- 1-10V, DALI and switch dimming options available upon request.
- Clear safety glass.
- Basic colours: white, black, silver, dark silver and special color options.
- Honeycomb filter, colour filter, antiglare screen and visor accessories available.
- Narrow and medium beam angle options available with rotationally symmetric light distribution.

- Alüminyum enjeksiyon gövde.
- 220-240V / 50-60Hz enerji girişi.
- Akıllı soğutma tasarımı.
- 3-Fazlı universal ray adaptörlü.
- 1-10V, DALI ve switch dim seçenekleri bulunmaktadır.
- Tamperli cam.
- Standart renkler: beyaz, siyah, gri, koyu gri ve isteğe bağlı özel renk seçeneği mevcuttur.
- Bal peteği filtre, renk filtresi, kamaşma önleyici ve ışık siperi aksesuar seçenekleri mevcuttur.
- Simetrik ışık çıkışı sağlayan dar ve orta açı reflektör seçenekleri mevcuttur.

Silindir Maxi / I01.MLT.18191

LED	COB LED	
Led Power / Led Gücü	29W	
System Power / Sistem Gücü	32W	
Lumen Output from Fixture / Armatür Çıkış Lümeni CRI>80	2700K	3450
	3000K	3550
	3500K	3660
	4000K	3770
	5000K	3885
Lumen Output from Fixture / Armatür Çıkış Lümeni CRI>90	2700K	3100
	3000K	3200
	3500K	3295
	4000K	3390
	5000K	X
Meat / Et COB	1800K	2000
Food / Gıda COB	2400K	2060
Mains Switch Dim Option / 220V Anahtar Dim Opsiyonu		✓
1-10V Dimming Option / 1-10V Dim Seçeneği		✓
Dali Dimming Option / Dali Dim Seçeneği		✓

Accessories / Aksesuarlar

