MAESTRO

quattro.1

i-LèD

MAESTRO
quattro.1

i-LÈD



FERRING PHARMACEUTICALS
Copenhagen (Denmark)
Fit-out and lighting design: Studio Foster+Partners
Photography: Nigel Young

Indoor

Downlights

Projectors & Track Systems

Ceiling, wall & suspensions

Linear systems

Step lights

Micro spotlights

Flex lights

Flex lights

Outdoor

Downlights

Projectors

Wall & Ceiling

Linear systems

Step lights

Floor grazing lights

Inground

Effect lights

Bollards

Urban lights

Underwater

Industrial

Industrial lights

Electronics

Electronics

Info

Symbols, Finishes, Optics, Index

Indoor range index

Downlights

EVO NEW  40

Modoc NEW  60

Vos  72

Warp  78

Quantum  86

Epitax  90

Loro  94

Rada  100

Cell  104

Giotto NEW  110

Cob40  114

Cob44  116

Woofer NEW  118


Illuminator NEW  122

Optus_EX  126

Projectors & Track Systems

Pound NEW  136

Optus NEW  152

Skylum_R Track NEW  162

Cell NEW  164

Rollip35_T NEW  166

Track System  168


Creek NEW  172

Navata NEW  176

Ceiling, wall & suspensions

Tour Slim NEW  188

Tour_Slim_ Elliptic_PD NEW  194

Tour  198

Skylum NEW  214

Mini_Albatros  224

Cell  226

Baton  228


Pound  234

High Wired  240


Emy NEW  244

Indoor range index

Linear systems

Ink	Node System	Modus	Rollip	Trail	Archicove	Fylo+
NEW	NEW	NEW	NEW			
						
250	268	286	302	324	330	334

Step lights

Vissa	Petit	Quara	Envelope	Step	Ilamt	Optiwall
						NEW
						
342	344	346	350	352	354	356

Micro spotlights

Bibok	Aspho	Picrol	Nitum	Ghilea	Crystals	Eyelet
						NEW
						
362	364	368	370	372	374	378

Flex lights range index

Flex lights

Ribbon	Ribbon Plus	Ribbon CobLed	Ribbon PRO	Silicone	PU_C Plus	Profiles
NEW	NEW	NEW	NEW	NEW	NEW	NEW
						
390	392	393	394	396	397	400

Rubber 2D Mini	Rubber 3D	Rubber 3D Concrete	Rubber 3D Optics	Rubber 3D PIXEL RGBW	Rubber 3D PROtection	Rubber_O
NEW	NEW	NEW	NEW	NEW	NEW	NEW
						
410	412	412	416	417	418	420



NEW ALDEBARAN
LUXURY APARTMENTS
Catania (Italy)

Architectural project:
lineaTstudio - Studio di architettura
e design | Salvatore Terranova

Architect: Giorgia Testa Engineer

Photography: Giorgio Bottitta

Outdoor range index

Downlights

Orma NEW

438

Guardian NEW

448

Projectors

Eyelet65 NEW

458

Periskop NEW

460

Shaker NEW

472

Iris67

476

Clivo

480

Clark316 NEW

482

Vuelta

486

Prolamp NEW

488

Biglamp

492

Wall & Ceiling

Portik NEW

502

Skin_S

508

Stadium


510


Cubit


512

Vedette

524

Nail

530

Cem

532

Skin_W

534

Linear systems

Ice-Cut66

546

Thin66

548

Skin

552

Paseo


558

Xenia NEW

568

Archiline

590

Mini Tube

608

Maxi Tube

612

High Protection

616

D-Wave


624

Dirigo

630

Dirigo_CUT-OFF NEW

636

Fylo+ Out

640

Outdoor range index

Step lights

Clip


646

Quara

648

Cut

654

Sand

656

Orma
NEW

658

Envelope

664

Step66

670

Optiwall
NEW

672

Chim

676

Floor grazing lights

Alcor316
NEW

682

Alcor
NEW

690

Astropek
NEW

698

Footpad

704

Inground

Beret

712

Orma

716

Suelo
NEW

746

Suelo 316
NEW

778

Effect lights

Orma Blade
NEW

788

Xenia Blade
NEW

792

Arcada

796

Myia

798

Loop66

800

Pixie_PIXEL

802

Paseo_PIXEL

804

Xenia_PIXEL

806

Outdoor range index

Bollards

Lino

812

Blum NEW

814

Rolling Sky NEW

818

Bond Pro

824

Buzzer NEW

826

Ryo

836

Apache

838

Peak

840

Urban lights

Stalk

846

Peak

848

Buzzer NEW

850

Parker

852

Ledweg

856

Voyager

858

Arms & fixing accessories

862

Underwater

Sub

872

Suelo

874

MK68 NEW

876

Rubber 3D Protection NEW

898

MK68 Linear

904

Rodix

910

Industrial lights

Multilamp

916

Raptor

918

Alix NEW

922

Alux

924

Atix

928

Electronics

General Index
931

Twil NEW

932

Bluetooth Silvair NEW

935

Casambi NEW

936

Indoor NEW

937

Outdoor NEW

948

Master & controller NEW

954


Emergency

968

INTERNATIONAL GLOBAL SERVICE LIGHT!

Our global presence is the key of our dedication to customer service. With teams operating on every continent, we are ready to respond to requests, whether they are routine in nature or involve more complex challenges. This global structure allows us to offer unique expertise, including the ability to organise site visits with our technical and commercial experts. We are committed to ensuring timely and professional responses at all times. Cultivating a continuous dialogue with lighting professionals, in order to better understand and satisfy their needs, is at the top of our objectives.







01 Linea Light HQ & site production, Treviso, Italy
02 Baltimore, USA site production (ETL)
03 Zhongshan, China site production (CCC)

04 Linea Light Milano, Italy
05 Linea Light North East, Italy
06 Linea Light Rome, Italy
07 Linea Light Spain
08 Athens, Greece (technical & sales contact)
09 Linea Light Deutschland
10 Linea Light France
11 Linea Light UK
12 Dublin, Ireland (technical & sales contact)
13 Doha, Qatar (technical & sales contact)
14 Linea Light GCC
15 Riyadh, Saudi Arabia (technical & sales contact)
16 New Delhi, India (technical & sales contact)
17 Linea Light Singapore
18 Shanghai, China (technical & sales contact)
19 Beijing, China (technical & sales contact)

INTERNATIONAL LIGHTING PROJECT

FERRING
KASTRUP, DENMARK
WORKPLACE



Fit-out and lighting design:
Studio Foster+Partners @fosterandpartners
Products: **Rollip custom, Shaker, Portik custom**

Inside the new Ferring Pharmaceuticals headquarters building, Linea Light Group has designed a special customised solution of Rollip to adapt it to the existing sound-absorbing false ceiling system. Extending for approximately 15 kilometres along corridors and passages, this versatile luminaire guarantees visual comfort and glare control.



SPARK ONE
MILAN, ITALY
WORKPLACE

Architectural design: **Progetto CMR**
Lighting project: **DEERNS**
Products: **Rollip, Cob, Emy**





The Spark One building inaugurates a new commercial area in the Santa Giulia district in Milan, near the Milano Rogoredo train and metro station. The building, with nine floors and a total area of approximately 52,000 square metres, hosts offices, catering and commercial activities. It is the result of an elaborate architectural project signed by the Progetto CMR studio, which created a space capable of characterising the neighbourhood with its own identity, inspired by the concepts of community, efficiency, sustainability and participation. The great protagonist of the building's lighting design is Rollip70, the continuous line system specifically designed to be integrated into the structure's beams. Used with two different power levels for maximum energy efficiency. The Cob down-light used in some of the office areas for its high visual comfort, completes the lighting project.

THE WESTIN LONDON
LONDON, UK
HOSPITALITY & WELLNESS

Project: **Dexter Moren Associates**
Lighting project: **Nulty Lighting**
Products: **Pound, Vos, Archicove, Creek 2.0, Rubber, Ribbon, Ice-Cut, Cell, Ink Systems, Rollip**





Wellness and business in an unprecedented dimension. This is The Westin London City promise, the new hotel of the prestigious Westin Hotels & Resorts chain, overlooking the Thames with a spectacular view of the river. Designed by the British architecture and interior design studio Moren, the building appears as an open and airy environment, capable of ensuring the right amount of privacy to its guests. The lighting project was conceived to be perfectly in line with the general theme of the hotel: wellbeing. To further underline the elegant atmosphere of the hotel, an accurate lighting project was created by the Nulty lighting designers in collaboration with Studio Moren, using various solutions from the Linea Light Group. The final effect is a feeling of calm and peace that pervades the visitor from the moment he/she arrives.

VIDA BEACH RESORT MARASSI AL BAHRAIN
MANAMA, BAHRAIN
HOSPITALITY & WELLNESS

Lighting Supplier: **Huda Lighting**
Lighting Designer: **UMAYA**





In the entrance of this five-star luxury resort, in the heart of Western Asia, between comfort and tranquillity. Our Alcor step light creates a warm and elegant atmosphere, welcoming and guiding guests along a fascinating path of light. A project supported by high technology and passion for the future, a dream that becomes real in this pearl of the desert.

APPLE'S CULVER CITY HEADQUARTERS
CULVER CITY, USA
WORKPLACE

Project: **Apple's Culver City Headquarters**
8777 Washington Blvd
Location: **Culver City, CA**
Architect: **Gensler**
Lighting Designer: **KGM**





Rubber by Inter-lux/Linea Light transforms the exterior of Apple's headquarters in Culver City by adding an eye-catching detail to the sides of the building.
Linea Light offers a wide range of high-performance LED luminaires and systems characterised by functionality, style and design. Architectural applications include recessed and surface options; Rubber is just one of Linea Light's infinite lighting solutions, characterised by a variety of strip solutions with flexible adhesive circuits suitable for humid places and a polyurethane resin diffuser that creates perfectly uniform lines of light. Extremely flexible, it can bend to cover a very narrow radius, adapting perfectly to sinuous profiles.

CLUNY HILL HOUSE
SINGAPORE
RESIDENTIAL

Architect: **Wallflower Architects**
Lighting designer: **Light Collab**





A house mirrored in the swimming pool.
Our lighting concept enhances the lines and reflections of the water.
Uncompromising lighting, like that of the Cluny Hill House project.
With its orthogonal shape, flat roof and raised first floor that seems to "float" above the swimming pool, Cluny Hill House seeks and finds its space in the contemporary era and in the future.
A welcoming home, which never goes unnoticed, neither in sunlight nor at night, illuminated by the unmistakable style of Linea Light: Rubber 3D Optic black finish that illuminates the facade, Blum that illuminates a flower bed, Orma_IJ to illuminate the lower part of the structure and finally Beret, chosen to highlight some niches inside the house.

MONTEFELTRO OFFICE VILLAGE
MILAN, ITALY
LIGHT FACADE



The recently completed restyling project of the Montefeltro Office Village complex in Milan used light as the characterising element of its facades. The ability of the Rubber 3D LED strip to play with three-dimensionality made it possible to give the building an image of robustness.

Project Team:
Stefano Giubileo, Gregg Brodarick, Andrea Bianchi, Fabio Crespi




MAUSOLEUM OF KHOJA
TURKESTAN, KAZAKHSTAN
ARTE E CULTO

Project: **Media Agency Plastdekor LLP**
Lighting Design: **Media agency Plastdekor LLP**
Electrical project, project adaptation, supply:
LLP SOCIETÀ DI INGEGNERIA "KAZGIPRONEFTETRANS", Media Agency Plastdekor LLP

Linea Light took care of the external lighting of the Mausoleum of Khoja Ahmed Yasawi in Kazakhstan, a magnificent Islamic religious monument from the 12th century, included in the list of UNESCO world heritage sites.
For the lighting project, aimed at enhancing different scenarios of the building, over 200 luminaires were used, some of which were customised, from the Arcada, Archiline, Vuelta, Xenia, Prolamp and Orma families, controlled by a remote system capable of programming and controlling the light.










THE FACTORY

THE PRODUCTIVE HEART OF i-LèD



The impressive 21,400 square meter production plant; the company is a point of reference for the design and production of high-tech lighting fixtures. The Technical Department for the Development of Lighting Fixtures and the Technical Electronic Department are at the centre of this innovation hub. Here, the company invests in research and development to ensure its products live up to technological challenges and market expectations. The factory is not only a place of ideas, but also an example of efficiency and modernity. Equipped with the most innovative production and logistics systems, the company is able to guarantee the highest quality and punctual delivery times. The ISO 9001 and 14001 certifications attest to the constant commitment to excellence, confirming the quality of the production processes and the attention towards environmental impact.




With over 20 numerically controlled (CNC) machines at our disposal, we shape materials with precision. This allows us to create a wide range of products, adaptable to different market demands in terms of size and performance. In particular, our 3 cutting lines for aluminium extrusions are the heart of our savoir-faire. These plants allow us to precisely shape aluminium profiles, ensuring consistent quality and production flexibility, confirming us as a reliable partner for our customers.

The autostore warehouse, a latest generation system that houses components and small parts such as lenses, glass and springs, has the purpose of maximising the yield and speed of operations, whilst managing to reduce costs and obtain a total traceability of the operations. The warehouse is made up of 21,000 boxes divided into 1312 stations with 16 stacked boxes. By scanning the barcode, the order signal is transmitted to the 10 robots which, moving in a coordinated manner and through paths optimised by the algorithm, pick the components which will then move on to assembly.




CREATE LIGHTING SOLUTIONS THAT SHINE EVEN IN THE MOST CHALLENGING CIRCUMSTANCES.

The hermetic sealing of lighting fixtures represents a crucial element to ensure durability and efficiency over time. The choice of the watertight solutions must be carefully calibrated based on the intended use of the devices. In outdoor environments, exposed to bad weather and adverse environmental conditions, the presence of an airtight system is essential to protect the luminaire from atmospheric agents, humidity and dust. Adequate sealing not only preserves the luminous performance, but also the structure of the luminaire itself, reducing the risk of damage due to corrosion or infiltration. Furthermore, in industrial or marine contexts, where exposure to corrosive substances is high, the watertight seal becomes crucial for preserving the integrity of the appliance over time.






Sealing with thermo-hardening material:
Area dedicated to processing the flexible linear families such as Ribbon, Pu-C and Rubber: circuit welding, polyurethane resin coating, testing and control. All products pass a control test at each production stage and are subjected to a final test as well as to random tests which re-verify IP and IK requirements.



Numerically controlled silicone coating:
The numerically controlled sealing system implemented on outdoor luminaires such as Archiline, Xenia, Parker, Orma, Skin, etc., ensures a perfect hermetic seal. This technology precisely applies the optimal amount of adhesive to ensure perfect bonding of the glass, eliminating possible air or water infiltration. The automated approach not only improves aesthetics, but also optimises production efficiency.



Ultrasonic sealing:
The Paseo linear system guarantees reliable protection for the circuit and the power supply unit through the ultrasonic closure of the caps. This innovative technology creates an effective barrier against the elements, eliminating the need for glues or other chemical products. Thanks to this advanced solution, production times are significantly reduced, enabling a more efficient and sustainable process.

THE TESTING PROCESS

The tests of i-LèD luminaires are not only a demonstration of resistance, but also a source of inspiration for innovation. Overcoming limits represents fertile ground for developing increasingly advanced and reliable technologies. In light of these challenges, i-Lèd technical department not only aims to meet the minimum requirements, but is committed to exceeding the standards, anticipating future needs and ensuring that lighting remains a constant and reliable element in daily life.



Submerged Wear Testing:
The devices are subjected to controlled pressures in a tank simulating deep conditions. This test evaluates resistance to liquid agents, ensuring that the devices maintain structural and functional integrity in the most extreme conditions.



We carry out tests on the finished product aimed at verifying the following parameters:
- electrical safety
- electromagnetic compatibility
- electrostatic discharges
- surge test
- voltage dips



Impact Test:
The IK value indicates the degree of resistance to mechanical or accidental impacts of the external cases of electrical and electronic devices (with voltages lower than 72.5kV). The test is carried out by generating an ever-increasing impact energy on one or more potentially vulnerable points of the case for a minimum of 3 consecutive impacts. The test can be carried out using approved devices applied to one of the following test instruments: spring hammer, pendulum hammer or free fall hammer. The result of the test can be considered positive if the product maintains all structural and functional characteristics so that it is still compliant from a safety point of view.



Salt spray test:
By reproducing an extreme environment with high salinity by means of a solution formed from sodium chloride and deionised water, the behaviour of the materials is analysed in order to guarantee a product that can be installed in any outdoor environment.



UV Test:
This test verifies the resistance of materials to yellowing and deterioration caused by sunlight and UV radiation. In fact, we reproduce the radiation of sunlight inside a dedicated chamber, inserting finished products or materials such as optics, plastic materials and cables for a period ranging from a few months to two years.



Stress test:
This test defines the robustness of the lamp body by testing its mechanical resistance to ascertain the walkability and driveability requirements. The lamp body is subjected to stress by means of an oil piston which exerts increasingly greater pressures from 200 to 7500 kg. The test lasts 7 days and consists of the alternation of push and release with one minute cycles.

ELECTRONIC DESIGN

Our Electronics Department is constantly evolving, embracing a vision that goes beyond the simple task of powering a LED source. Today, our primary focus is on designing reliable and efficient electronics. We are dedicated to pushing conventional limits, focusing on creating advanced electronic solutions that not only deliver power, but are also designed for reliability and efficiency. This transformation reflects our commitment to anticipating emerging challenges by offering state-of-the-art electronic solutions that meet the growing needs of the market."




NOW THE DRIVER IS **ON BOARD!** ALL THE i-LèD TECHNOLOGY IN THE PALM OF YOUR HAND.

Linea Light Group has created the first minispots with built-in driver. We have studied and created luminaires that, despite being able to fit in the palm of your hand, maintain the performance expected from our products. The new minispots do not require the use of remote power supplies during installation. They are carefully designed and contain the best, and smallest, technology available. The built-in driver, integrated in the body of the luminaire, can be switched to different configurations, such as Up-Light, Path-Markers and Accent Lighting. The new luminaires are extremely compact and have a steel body ideal for outdoor installation thanks to a high protection rating (IP67). Linea Light Group has provided professionals with different fixtures suitable for different uses, even the most demanding. Easy, fast and well-made are the three qualities that define the new technological frontier reached by Linea Light Group.

STANDARD INSTALLATION
SPOT + DRIVER

NEW SPOT LIGHT WITH
BUILT-IN DRIVER



available for

Suelo
Beret
Orma
Periskop
Shaker
Clivo
Quara
Step66
Envelope
Alcor

HIGH EFFICIENCY BECOMES SLIM

The new Slim High Efficiency (Slim HE) power driver features an innovative fundamental concept: we have replaced perishable, inefficient and hardly reusable electronic components with new high-performance technologies that can be recycled faster and more efficiently. This driver, designed to stand the test of time, offers a lifespan of more than 20 years, far exceeding industry standards. Thanks to its advanced structure, HE can power up to 11 watts, ensuring reliable and sustainable performance in the long term. The absence of the converter, a key feature, contributes not only to energy efficiency, but also to a longer operating life without compromising on the power supplied.

An additional advantage of our Slim HE driver is the dimming mode, which operates in direct current rather than PWM (pulse width modulation), making the device completely Flicker-Free. This innovative feature translates into stable and uniform light, eliminating annoying stroboscopic effects.


FLICKER FREE

HE High Efficiency



Scale 1:1

DRIVER SLIM IMPROVEMENT



Minimum efficiency as per regulations

Separate driver and converter, until 2022

Slim
Power out: **6W**
Life: **60000 h**
Weight: **91 g**
Eff MAX: **69%**

Miniaturisation: aggregate converter drivers, evolution 2023

Slim_PRO
Power out: **6W**
Life: **80000 h**
Weight: **46 g**
Eff MAX: **72%**




More power, long life and higher efficiency, innovation 2024

Slim_PRO HE
Power out: **11W**
Life: **101000 h**
Weight: **48 g**
Eff MAX: **90%**




CONSTANTLY ORIENTED TOWARDS SUSTAINABLE LIGHT

Linea Light Group has always paid particular attention to the design of our luminaires, aiming to ensure that they would not be high-performance alone, but also easily repairable and able to be reprocessed. We have always believed in the importance of offering not only quality products, but also a complete service that continues even after the project has ended. Our dedication to providing reliable after-sales support and on-going technical assistance demonstrates our commitment to ensuring maximum customer satisfaction and the durability of our products over time.





All processing waste undergoes a cleaning phase through a centrifuge which separates oil and shavings. The former is filtered and reused in subsequent cycles while the latter is resold as recycled material. For brass processing, instead, the residues are collected by the supplier who in turn returns the semi-finished product ready to be turned again.



The packaging is adapted to the product to be shipped, thanks to special packaging machinery. This generates less impact on paper consumption but also less CO^2 thanks to optimised transport.


SUSTAINABLE DESIGN: CREATING PRODUCTS DESIGNED FOR LONG-TERM SUSTAINABILITY

Our lighting line embraces the **TM66** rating system not only as a tool to evaluate the degree of sustainability of our current products, but also as a fundamental guide for developing future devices. We intend to use the **TM66** method as a basis for the design and creation of innovative light fixtures, aiming not only for environmental sustainability but also for high quality and long-lasting standards. This approach allows us to create not only advanced lighting products, but also to constantly pursue the goal of reducing environmental impact, ensuring a bright future for both our solutions and the environment.



MODOC
TM66 RESULT 2.4
(discover MODOC on page 60)





EVO
TM66 RESULT 2.3
(discover the EVO collection on page 40)

PERFORMANCE & EFFICIENCY

Minimum Energy Performance

All i-LèD luminaires can comply with the prerequisite*

i-LèD

Optimise Energy Performance

The i-Lèd luminaires have been developed to guarantee the energy performance optimisation criteria

Through our range of office lighting fixtures, we are committed to providing solutions that not only meet sustainability standards, but also allow obtaining the essential values for various certifications related to sustainable construction. The flexibility of the countless combinations offered by our products allows precisely adapting to the various requirements, guaranteeing the optimisation of energy efficiency, the quality of the lighting and compliance with environmental regulations. Our range of luminaires is designed to significantly contribute to creating sustainable working environments, providing not only high-quality lighting, but also measurable results that support the achievement of several green building certifications.



Reduction of energy consumption due to lighting:

Room	Lighting density **
Dormitories	6.0 W/m^2
Hotels	10 W/m^2
Libraries	12 W/m^2
Museums	10 W/m^2
Offices	9.0 W/m^2
Car parks/garages	2.5 W/m^2
Retail	14 W/m^2
Schools/Universities	9.0 W/m^2

** ASHRAE 90.1 values

*the final evaluation goes through the global analysis of the system

QUALITY OF LIGHTING FOR INDOOR ENVIRONMENTS

One of the criteria for evaluating the quality of light used in the LEED® certification depends on the quality of the luminaires:


A. Use of lighting equipment characterised by luminance lower than 2500 cd/m^2 and angle between 45° and 90°.
B. Use of light sources with a CRI greater than 80.
C. Use of light sources with a useful life of at least 24,000 hours for at least 75% of the lighting system.
D. Use of exclusively direct ambient light for a maximum of 25% of all regularly occupied spaces.
E. Reaching or exceeding the following average reflectance thresholds per area for at least 90% of the regularly occupied area (85% ceilings - 60% walls - 25% floors).
F. If applicable, selection of finishes for the furniture that allow the light reflectance thresholds for average surfaces to be exceeded (45% work surfaces - 50% movable walls).
G. For at least 75% of the regularly occupied area, guaranteeing a ratio between average luminance on the vertical surface and average luminance of the work area that is less than or equal to 1.10.
H. For at least 75% of the regularly occupied area, guaranteeing a ratio between average luminance on the ceilings and average luminance of the work area that is less than or equal to 1.10.

(**A, B, C** refer to the lighting fixture, the remaining points to the lighting design project)

Interior lighting
The **EVO** collection complies with the envisaged LEED parameters in terms of luminance, CRI and useful life of LEDs (24,000h)

Example:
Vos_EVO
9W - Medium Flood
3000K
UGR <11
CRI90


The **EVO** collection emerges as the main key point for the assignment of the **LEED credit** since it fully embraces the three strategies attributable to the lighting fixture, thus guaranteeing **a satisfactory coverage of all the required specifications**.



CONNECTED WITH THE FUTURE

twil lightconnection


Twil is the innovative wireless technology owned by Linea Light Group that allows the configuration and control of luminaires through smart devices and PCs. In addition to high-efficiency lighting fixtures, a lighting system with Twil technology can also include sensors for automatic presence and brightness control. These interact with the luminaires to intelligently illuminate the different environments, based on the intended use, the illumination to be guaranteed in the visual field area and the availability of natural light. They can also be installed at great heights, up to 11 m, they are compatible with industrial and commercial applications (high bay applications) and contribute to the energy saving of the system. Unlike common control systems, thanks to its compatibility with DALI systems the Twil technology is able to interact with these systems through special converters. With a minimal intervention, it is also possible to update pre-existing systems, both wired and on three-phase track




A SYSTEM AT YOUR FINGERTIPS

Thanks to the TWIL system, developed also to monitor consumption, efficiency, malfunctions or any anomalies in the installed devices, it is possible to meet the LEED® requirements in terms of Advanced energy metering

Management of groups of luminaires on the floor plan via dedicated software interface on PC. Search for Gateways present on the network and broadcast command of all devices connected to them.





General monitoring of the system status
The TWIL system cloud service represents a revolution in the lighting sector. Thanks to this technology, users can access their system information from anywhere in the world and at any time.

Download on the App Store

GET IN ON Google Play




LIGHT FOR IMPROVING NIGHT-TIME VISIBILITY

The BUG Rating system, developed by the Illuminating Engineering Society (IES) and by the International Dark Sky Association, is used to classify lighting products based on their ability to reduce backlight, the light emitted upwards (Up-light) and glare (Glare).




Through careful development and the targeted design of the Buzzer, integrating the BUG-Rating evaluation system right from the start, we have managed to create a series of versions that boast a zero bug rate. These versions of our Buzzer are designed to integrate perfectly into projects that consider the BUG-Rating criterion the essential requirement to ensure optimal visual comfort in outdoor environments. Our attention to BUG-Rating reduction translates into a significant contribution to ensuring effective outdoor lighting, eliminating any unwanted light disturbance and enabling a comfortable, high-quality visual experience in different architectural projects.

In the world of lighting, by "BUG-Rating" we want to refer to the three main factors that contribute to light pollution, namely Backlight, Up-light and Glare. Backlight: refers to the backlight emitted by the device, better known by the English term "Light Trespass", due to the reflection of light generated by the surface of the device, which causes the so-called "halo" effect around the product. Up-light: Refers to light that is emitted upward towards the night sky, rather than downward where it is needed. This light can cause widespread brightness in the night sky, interfering with the observation of stars and astronomical events. The up-light is considered high when the angle of the light emitted upwards varies between 100° and 180°, while it is low when the values are between 90° and 100°. Glare: refers to the glare of the frontal light, causing discomfort or temporary blindness to observers, especially when driving or using devices that require good vision.




WHERE TO LOOK FOR THE SYMBOL

BUG Rating 0




CUSTOM APPROACH





2360 PROJECTS DEVELOPED IN 2023 THAT INCLUDED A CUSTOM PRODUCT

We aim to build an open and continuous dialogue with the designer to fully understand his or her specific needs and to offer customised solutions, called "bespoke". The company, which stands out thanks to its experience, research and development, is committed to understanding and translating the designer's ideas into unique solutions, even beyond the standard catalogue. Flexibility, deriving from a profound knowledge of the sector and a constant desire for innovation, allows creating tailor-made projects, ensuring maximum quality, reliability and compliance with the specific requests of the designer. We go beyond the mere customisation of the standard product, creating real "one-offs", unique projects that fully reflect the vision and needs of the designer. Our payoff "light up your ideas!" is an invitation to always be curious and experiment with new solutions that highlight new ideas.









1 | Cappella Magi, Florence
Multi Optus Tower

2 | Yongding River Bridge
Prolamp custom

3 | Merlata Bloom
Life Style Center Milan
Custom downlight, Illuminator,
Rollip Pro, TU-V pendant
Design: Thomas Gravanis

4 | Athens Airport
Custom Paseo Pixel
Design: Eleftherya Deko

4



Bosco Verticale | Milan, Italy

Architectural design:
Stefano Boeri

Certified building:
LEED GOLD



Spark One | Milan, Italy

Architectural design:
Progetto CMR
Lighting project:
DEERNS

Certified building:
LEED PLATINUM



HOW TO READ THE CATALOG

Pictograms
How to read symbols
see Page 976

Light emission



Orma_C | V2 | arrayLED | 220-240 V AC | 11,5 W AC

Family Name | Upgrade product | LED Type | Electronics Characteristic | Power

Image of the product with relative technical dimension drawing

How to configure a product: guide to the composition of the finished code

	Cct	Im S - Im D	Opt
SA 76181	W	1267 - 821	15 (17°)
	N	1315 - 854	30 (25°)
			60 (53°)

Im-S Lumen Source
Im-D Lumen Delivery

The effective flux **(Im-D)** is detected, taking as a reference the Flood/M.Flood optics and a neutral colour finish. For more in-depth details, please consult the technical data sheets on the website: **linealight.com**

76181 + W + 30 = 76181W30

1st product code | 2nd temperature code | 3rd optics code | Composed finished code

C.C. - 220 mA - 8 W DC

	Fin	Cct	Im S - Im D	Opt
C00362	SA	M	1132 - 720	SP (10°÷ 1
		W	1182 - 751	ML (30°÷ 3
		N	1212 - 770	WF (50°÷ 7

C00362 + SA + W + ML = C00362SAWML


1st product code | 2nd finish code | 3rd temperature code | 4th optics code | Composed finished code

Driver compatibility reference: **BE**

Driver code | Driver characteristics

89421	C-E200006	C-E200004
ON/OFF	ON/OFF	DALI/PUSH
1 art.	2 - 3 art.	2 - 3 art.
74 x 65 x h 27	135 x 26 x h 26	125 x 45 x h 30
	⌀ 35	⌀ 55

Recessed casing dimensional | Recessed casing code



PVC C-C100016

Outer casing for b
be completed with
C-C100015

Legend

Finishes	Cct				Accessories
SA Steel/Aluminium	M	2700	N	4000	HC Honeycomb
	W	3000			DL Darklight

30
60 Optics
SP **Range, code**
ML **and description**
WF **Page 975**

Orma_C | arrayLED-Direct | 220-240 V AC






220-240V

	Cct	lm S - lm D	Opt
11,5W AC			
SA 76181	W	1267 - 821	15 (17°)
	N	1316 - 854	30 (25°)
			60 (53°)

Recessed casings: (pag 446)

Orma_QC | arrayLED





	Fin	Cct	lm S - lm D	Opt
C.C. - 220 mA - 8 W DC				
C00361	SA	M	1132 - 720	SP (10°-19°)
		W	1182 - 751	ML (30°-36°)
		N	1212 - 770	WF (50°-70°)
C.C. - 220 mA - 8 W DC				
C00362 HC	SA	M	1132 - 550	SP (10°-19°)
		W	1182 - 574	ML (30°-36°)
		N	1212 - 588	WF (50°-70°)

Electronics: C.C. BE (pag 446) | Recessed casings: (pag 446)



Electronics

BE

89421	C-E200006	C-E200004
ON/OFF	ON/OFF	DALI/PUSH
1 art.	2 - 3 art.	2 - 3 art.
74 x 65 x h 27	135 x 28 x h 26	125 x 45 x h 30
Ø35	Ø35	Ø55

Recessed casing



PVC C-C100016 Outer casing for brickwork to be completed with accessory C-C100015

suitable for: Orma_QC L85-116 / Orma_QCJ L85-116

Downlights

446

Finishes	Cct	Accessories
SA Steel/Aluminium	M 2700 N 4000	HC Honeycomb
	W 3000	DL Darklight



DOWN LIGHTS

Downlights range index

Evo

Vos_R EVO

46

Vos_R Par16 EVO


46

Vos_RJ EVO


47

Quantum_R EVO

48

Quantum_RJ EVO


49

Warp_R EVO

50

Warp_R Par16 EVO


50

Warp_RJ EVO


51

Warp_Q EVO


52

Warp_QJ EVO


52-53

Epitax_R EVO


54

Epitax_RJ EVO


54-55

Modoc

Modoc_R


66-67

Modoc_R Ww


66


Modoc_RF


68-69

Modoc_RF Ww


68

Vos

Vos_R

73

Vos_Ww

73

Vos_RJ

74

Vos_Q

74-75

Vos_QJ

75

Warp

Warp_R

79-80

Warp_R PRO

80

Warp_RY

81

Warp_RJ

81-82

Warp_Q

82-83

Warp_QY

84

Quantum

Quantum_R

87

Quantum_RJ

88

Epitax

Epitax

91


Epitax_J

92

Loro

Loro_R

95

Loro_RJ

96

Loro_Q

97

Loro_QJ

98

Rada

Rada_R

102

Cell

Cell
NEW

106

Gypsum Cell

107

Cell_Ww

108

Giotto

Giotto_R

112

Giotto_RF

112

Cob

Cob40_R

114

Cob40_RJ

115

Cob44_R

116

Cob44_RJ

116

Cob44_Q

117

Cob44_QJ

117

Woofer

Woofer_R
NEW

119

Woofer_R ECL

121


Illuminator

Illuminator

123

Illuminator

124

Illuminator
NEW

124


Optus_EX

Optus_EX

128

Optus_EX

129



EVO

Aluminium body. Technopolymer diffuser.

EVO
TM66
RESULT 2.3

LIGHT FOR TOMORROW

BUILD BACK BETTER GOLD WINNER

EVO downlights are innovative, interchangeable, fully recyclable and sustainable fixtures. We realize that protecting the environment is a major concern of our time. For this reason, i-LèD has developed a series of luminaires that help reduce environmental impact without compromising quality or functionality.

CIRCULAR PRODUCT:

61% RECYCLED

98% RECYCLABLE

98% REPAIRABLE



INTERCHANGEABLE

Thanks to the extensive range of accessories, it is very easy to replace a specific part without having to buy a completely new product. This not only reduces costs but also the amount of waste produced.



RECYCLABLE

EVO luminaires and all their components are easy to disassemble, this means that they can be recycled or disposed to the dedicated centres at the end of their life. In this way, we help to drastically reduce the amount of waste.




SUSTAINABLE

The EVO collection is designed following our company philosophy, which applies a low environmental impact production process.

A PERFECT INTERLINKING OF ELEMENTS


The technopolymer used to make the parts that compose the EVO fronts is the result of advanced research and latest-generation applications, guaranteeing uncompromising resistance. In the adjustable versions, every single element is designed with the utmost precision and the components fit together like perfect gears, guaranteeing correct and reliable adjustment of the optical compartment, to satisfy a variety of design requirements. All this is possible as a result of the synergy with local suppliers, specialised in injection moulding for the automotive sector.



A NEW ACCESSORY TO ADAPT TO ANY SITUATION

The new Adapter Ring accessory, for Warp_R EVO and Quantum_R EVO models, increase the front diameter of the fixture with the option of installing EVO downlights in pre-existing holes or in situation where a precise hole is not made.

Example:



Installation with the accessory Adapter Ring (for Warp_R EVO and Quantum_R EVO) on larger hole


ELLIPTICAL FILTER ACCESSORY


This accessory allows the angle of opening for the light beam to be adjusted. Quick and easy to position, it makes it possible to create customised lighting effects.



Elliptical filter for Ø60	Vos_R	Quantum_R	Warp_R
Optic 10 + 83368	11°x28°	12°x37°	12°x40°
Optic 15 + 83368	15°x30°	15°x38°	15°x40°
Optic 30 + 83368	29°x36°	33°x41°	30°x45°
Optic 45 + 83368	39°x40°	43°x46°	45°x50°

Elliptical filter for Ø88	Vos_R	Quantum_R	Warp_R
Optic 10 + 83380	11°x36°	11°x37°	12°x42°
Optic 20 + 83380	21°x37°	22°x37°	22°x45°
Optic 30 + 83380	29°x40°	29°x41°	30°x46°
Optic 50 + 83380	45°x45°	46°x47°	48°x52°





i-LED


MODULAR LIGHTING FOR SUSTAINABLE PROJECTS

UGR IP40 IP65

Every single element of the new series of **EVO** downlights has been designed to be assembled and disassembled without using any tools, but just with mechanical movements. This innovative system also allows you to customise your fixture with infinite combinations which span 5 different design aesthetics, 3 optic layouts to increase visual comfort, 5 optics with different openings, 4 colour light temperatures and 3 different powers controlled by On-Off, Dimming 1-10V and DALI protocol with double IP.



WARP | QUANTUM | VOS | EPITAX | WARP Ø99 | VOS Ø85



FIXED | ADJUSTABLE

WHITE | BLACK | GOLD | COPPER

4 W | 9 W | 9 W | 14 W

NARROW SPOT | SPOT (UGR<16) | MEDIUM FLOOD | MEDIUM W.FLOOD | SPOT (UGR<11) | FLOOD (UGR<16) | MEDIUM FLOOD | WIDE FLOOD

2700K 3000K 4000K | 2200K 2700K 3000K 4000K | 2700K 3000K 4000K | 2200K 2700K 3000K 4000K



HONEYCOMB | ELLIPTIC FILTER | AESTHETIC FILTER




ADAPTER RING
Only for Warp_R and Quantum

WHITE | BLACK | GOLD | COPPER

GU10
(not included)
6 W Max
220-240 V

Vos_R EVO





DW Dynamic White 2200K-5700K - 4W (x channel) available on request


		Cct	lm S - lm D	Opt
powerLED - CRI 90 - 350 mA - 4 W DC				
WH	**77332**	**M**	389 - 208	**10** (9° UGR<11)
BB	**77333**	**W**	416 - 223	
AU	**77534**	**N**	449 - 240	
CU	**77535**			
WH	**77356** HC			
BB	**77357** HC			
AU	**77558** HC			
CU	**77559** HC			


Electronics: **D1** (pag 59) | Recessed casings & accessories: (pag 57, 58)
Cct 3500K available on request

arrayLED - CRI 90/80* - 700 mA - 9 W DC				
WH	**77330**	**A***	892 - 562	**15** (14° UGR<11)
BB	**77331**	**M**	1059 - 664	**30** (30° UGR<11)
AU	**77536**	**W**	1119 - 702	**45** (42° UGR<19)
CU	**77537**	**N**	1196 - 749	
WH	**77354** HC			
BB	**77355** HC			
AU	**77560** HC			
CU	**77561** HC			

Electronics: **J1** (pag 59) | Recessed casings & accessories: (pag 57, 58)
Cct 3500K available on request

Vos_R EVO





DW Dynamic White 2200K-5700K - 8W (x channel) available on request


		Cct	lm S - lm D	Opt
arrayLED - CRI 90/80* - 700 mA - 9 W DC				
WH	**77336**	**A***	892 - 592	**10** (10° UGR<11)
BB	**77337**	**M**	1059 - 700	
AU	**77538**	**W**	1119 - 740	
CU	**77539**	**N**	1196 - 790	
WH	**77360** HC			
BB	**77361** HC			
AU	**77562** HC			
CU	**77563** HC			


Electronics: **J1** (pag 59) | Recessed casings & accessories: (pag 57, 58)

arrayLED - CRI 90/80* - 400 mA - 14 W DC				
WH	**77334**	**A***	2007 - 1504	**20** (21° UGR<11)
BB	**77335**	**M**	2214 - 1658	**30** (32° UGR<11)
AU	**77540**	**W**	2318 - 1737	**50** (54° UGR<19)
CU	**77541**	**N**	2411 - 1807	
WH	**77358** HC			
BB	**77359** HC			
AU	**77564** HC			
CU	**77565** HC			

Electronics: **P1** (pag 59) | Recessed casings & accessories: (pag 57, 58)

Vos_R Par16 EVO






		Fin
220-240 V - 6 W Max GU10 - Ø 50 mm (not included)		
C00755	WH	EZZ
	BB	EZZ
	AU	EZZ
	CU	EZZ

Vos_RJ EVO





DW Dynamic White 2200K-5700K - 4W (x channel) available on request

	Fin	Cct	lm S - lm D	Opt
powerLED - CRI 90 - 350 mA - 4 W DC				
C00630	**WH**	**M**	389 - 197	**NS** (9°)
C00631 HC	**BB**	**W**	416 - 211	
	AU	**N**	449 - 228	
	CU			


Electronics: **D1** (pag 59) | Recessed casings & accessories: (pag 57, 58)

arrayLED - CRI 90/80* - 700 mA - 9 W DC				
C00613	**WH**	**A***	892 - 494	**SP** (14°)
	BB	**M**	1059 - 584	**FL** (28°)
	AU	**W**	1119 - 617	**MW** (40°)
	CU	**N**	1196 - 661	
C00624 HC				**SP** (13°)
				FL (25°)
				ML (30°)

Electronics: **J1** (pag 59) | Recessed casings & accessories: (pag 57, 58)

Vos_RJ EVO





DW Dynamic White 2200K-5700K - 8W (x channel) available on request

	Fin	Cct	lm S - lm D	Opt
arrayLED - CRI 90/80* - 700 mA - 9 W DC				
C00642	**WH**	**A***	892 - 612	**SP** (11°)
C00643 HC	**BB**	**M**	1059 -724	
	AU	**W**	1119 - 765	
	CU	**N**	1196 - 819	

Electronics: **J1** (pag 59) | Recessed casings & accessories: (pag 57, 58)

arrayLED - CRI 90/80* - 400 mA - 14 W DC				
C00640	**WH**	**A***	2007 - 1296	**FL** (20°)
	BB	**M**	2214 - 1429	**ML** (32°)
	AU	**W**	2318 - 1496	**WF** (52°)
	CU	**N**	2411 - 1556	
C00641 HC				**FL** (20°)
				ML (30°)
				MW (45°)

Electronics: **P1** (pag 59) | Recessed casings & accessories:w (pag 57, 58)



Narrow Spot (9°)
UGR <11

Spot (14°)
UGR <11

Medium Flood (30°)
UGR <11

Wide Flood (42°)
UGR <19

Installed downlight: **Vos_R EVO 3000K (Ø71)**


Finishes
White
Black
Gold
Copper

Cct
A 2200
M 2700
W 3000
N 4000

Accessories
HC Honeycomb

Quantum_R EVO





DW Dynamic White 2200K-5700K - 4W (x channel) available on request

	Cct	lm S - lm D	Opt
powerLED - CRI 90 - 350 mA - 4 W DC			
WH **77324**	**M**	389 - 238	**10** (10° UGR<11)
BB **77325**	**W**	416 - 254	
AU **77542**	**N**	449 - 274	
CU **77543**			
WH **77348** HC			
BB **77349** HC			
AU **77566** HC			
CU **77567** HC			


Electronics: **D1** (pag 59) | Recessed casings & accessories: (pag 57, 58)

arrayLED - CRI 90/80* - 700 mA - 9 W DC			
WH **77322**	**A***	892 - 637	**15** (14° UGR<16)
BB **77323**	**M**	1059 - 753	**30** (31° UGR<16)
AU **77544**	**W**	1119 - 796	**45** (46° UGR<19)
CU **77545**	**N**	1196 - 849	
WH **77346** HC			
BB **77347** HC			
AU **77568** HC			
CU **77569** HC			

Electronics: **J1** (pag 59) | Recessed casings & accessories: (pag 57, 58)

Quantum_R EVO





DW Dynamic White 2200K-5700K - 8W (x channel) available on request

	Cct	lm S - lm D	Opt
arrayLED - CRI 90/80* - 700 mA - 9 W DC			
WH **77328**	**A***	892 - 629	**10** (10° UGR<11)
BB **77329**	**M**	1059 - 744	
AU **77546**	**W**	1119 - 787	
CU **77547**	**N**	1196 - 839	
WH **77352** HC			
BB **77353** HC			
AU **77570** HC			
CU **77571** HC			


Electronics: **J1** (pag 59) | Recessed casings & accessories: (pag 57, 58)

arrayLED - CRI 90/80* - 400 mA - 14 W DC			
WH **77326**	**A***	2007 - 1632	**20** (21° UGR<16)
BB **77327**	**M**	2214 - 1799	**30** (32° UGR<16)
AU **77548**	**W**	2318 - 1884	**50** (54° UGR<19)
CU **77549**	**N**	2411 - 1913	
WH **77350** HC			
BB **77351** HC			
AU **77572** HC			
CU **77573** HC			

Electronics: **P1** (pag 59) | Recessed casings & accessories: (pag 57, 58)

Quantum_RJ EVO





DW Dynamic White 2200K-5700K - 4W (x channel) available on request


	Fin	Cct	lm S - lm D	Opt
powerLED - CRI 90 - 350 mA - 4 W DC				
C00634	**WH**	**M**	389 - 232	**NS** (10°)
C00635 HC	**BB**	**W**	416 - 248	
	AU	**N**	449 - 267	
	CU			


Electronics: **D1** (pag 59) | Recessed casings & accessories: (pag 57, 58)

	Fin	Cct	lm S - lm D	Opt
arrayLED - CRI 90/80* - 700 mA - 9 W DC				
C00632	**WH**	**A***	892 - 574	**SP** (15°)
	BB	**M**	1059 - 678	**ML** (30°)
	AU	**W**	1119 - 717	**MW** (42°)
	CU	**N**	1196 - 767	
C00633 HC				**SP** (14°)
				FL (27°)
				ML (31°)

Electronics: **J1** (pag 59) | Recessed casings & accessories: (pag 57, 58)

Quantum_RJ EVO





DW Dynamic White 2200K-5700K - 8W (x channel) available on request

	Fin	Cct	lm S - lm D	Opt
arrayLED - CRI 90/80* - 700 mA - 9 W DC				
C00646	**WH**	**A***	892 - 671	**SP** (11°)
C00647 HC	**BB**	**M**	1059 - 794	
	AU	**W**	1119 - 839	
	CU	**N**	1196 - 898	

Electronics: **J1** (pag 59) | Recessed casings & accessories: (pag 57, 58)

	Fin	Cct	lm S - lm D	Opt
arrayLED - CRI 90/80* - 400 mA - 14 W DC				
C00644	**WH**	**A***	2007 - 1424	**FL** (21°)
	BB	**M**	2214 - 1571	**ML** (33°)
	AU	**W**	2318 - 1645	**WF** (54°)
	CU	**N**	2411 - 1710	
C00645 HC				**FL** (20°)
				ML (30°)
				MW (47°)

Electronics: **P1** (pag 59) | Recessed casings & accessories: (pag 57, 58)




Finishes
White, Black, Gold, Copper

Cct
A 2200 **M** 2700 **W** 3000 **N** 4000

Accessories
HC Honeycomb

Warp_R EVO





DW Dynamic White 2200K-5700K - 4W (x channel) available on request

		Cct	lm S - lm D	Opt
powerLED - CRI 90 - 350 mA - 4 W DC				
WH	**77340**	**M**	389 - 242	**10** (10° UGR<11)
BB	**77341**	**W**	416 - 259	
AU	**77550**	**N**	449 - 279	
CU	**77551**			
WH	**77364** HC			
BB	**77365** HC			
AU	**77574** HC			
CU	**77575** HC			


Electronics: **D1** (pag 59) | Recessed casings & accessories: (pag 57, 58)

		Cct	lm S - lm D	Opt
arrayLED - CRI 90/80* - 700 mA - 9 W DC				
WH	**77338**	**A***	892 - 655	**15** (14° UGR<16)
BB	**77339**	**M**	1059 - 775	**30** (31° UGR<16)
AU	**77552**	**W**	1119 - 819	**45** (46° UGR<19)
CU	**77553**	**N**	1196 - 874	
WH	**77362** HC			
BB	**77363** HC			
AU	**77576** HC			
CU	**77577** HC			

Electronics: **J1** (pag 59) | Recessed casings & accessories: (pag 57, 58)

Warp_R EVO





DW Dynamic White 2200K-5700K - 8W (x channel) available on request


		Cct	lm S - lm D	Opt
arrayLED - CRI 90/80* - 700 mA - 9 W DC				
WH	**77344**	**A***	892 - 649	**10** (10° UGR<11)
BB	**77345**	**M**	1059 - 762	
AU	**77554**	**W**	1119 - 811	
CU	**77555**	**N**	1196 - 865	
WH	**77368** HC			
BB	**77369** HC			
AU	**77578** HC			
CU	**77579** HC			


Electronics: **J1** (pag 59) | Recessed casings & accessories: (pag 57, 58)

		Cct	lm S - lm D	Opt
arrayLED - CRI 90/80* - 400 mA - 14 W DC				
WH	**77342**	**A***	2007 - 1700	**20** (21° UGR<16)
BB	**77343**	**M**	2214 - 1874	**30** (32° UGR<16)
AU	**77556**	**W**	2318 - 1963	**50** (55° UGR<19)
CU	**77557**	**N**	2411 - 2043	
WH	**77366** HC			
BB	**77367** HC			
AU	**77580** HC			
CU	**77581** HC			

Electronics: **P1** (pag 59) | Recessed casings & accessories: (pag 57, 58)

Warp_R Par16 EVO






	Fin
220-240 V - 6 W Max GU10 - Ø 50 mm (not included)	
C00754	WH **EZZ**
	BB **EZZ**
	AU **EZZ**
	CU **EZZ**

Warp_RJ EVO





DW Dynamic White 2200K-5700K - 4W (x channel) available on request

	Fin	Cct	lm S - lm D	Opt
powerLED - CRI 90 - 350 mA - 4 W DC				
C00271	**WH**	**M**	389 - 250	**NS** (9°)
C00272 HC	**BB**	**W**	416 - 267	
	AU	**N**	449 - 289	
	CU			


Electronics: **D1** (pag 59) | Recessed casings & accessories: (pag 57, 58)

	Fin	Cct	lm S - lm D	Opt
arrayLED - CRI 90/80* - 700 mA - 9 W DC				
C00258	**WH**	**A***	892 - 505	**SP** (14°)
	BB	**M**	1059 - 597	**ML** (30°)
	AU	**W**	1119 - 631	**MW** (40°)
	CU	**N**	1196 - 676	
C00260 HC				**SP** (14°)
				FL (27°)
				ML (32°)

Electronics: **J1** (pag 59) | Recessed casings & accessories: (pag 57, 58)

Warp_RJ EVO





DW Dynamic White 2200K-5700K - 8W (x channel) available on request

	Fin	Cct	lm S - lm D	Opt
arrayLED - CRI 90/80* - 700 mA - 9 W DC				
C00638	**WH**	**A***	892 - 666	**SP** (11°)
C00639 HC	**BB**	**M**	1059 - 787	
	AU	**W**	1119 - 832	
	CU	**N**	1196 - 890	

Electronics: **J1** (pag 59) | Recessed casings & accessories: (pag 57, 58)

	Fin	Cct	lm S - lm D	Opt
arrayLED - CRI 90/80* - 400 mA - 14 W DC				
C00636	**WH**	**A***	2007 - 1454	**FL** (21°)
	BB	**M**	2214 - 1603	**ML** (33°)
	AU	**W**	2318 - 1678	**WF** (53°)
	CU	**N**	2411 - 1745	
C00637 HC				**FL** (20°)
				ML (30°)
				MW (47°)

Electronics: **P1** (pag 59) | Recessed casings & accessories: (pag 57, 58)


Warp_Q



71 / 99 mm



Warp_R



Finishes

White
Black
Gold
Copper


Cct


A 2200
M 2700
W 3000
N 4000

Accessories

HC Honeycomb

Warp_Q EVO





DW Dynamic White 2200K-5700K - 4W (x channel) available on request


		Fin		Cct	lm S - lm D	Opt
powerLED - CRI 90 - 350 mA - 4 W DC						
C00205		**WH**		**M**	389 - 259	**NS** (9° UGR<11)
C00206	HC	**BB**		**W**	416 - 277	
		AU		**N**	449 - 299	
		CU				


Electronics: **D1** (pag 59) | Recessed casings & accessories: (pag 57, 58)

arrayLED - CRI 90/80* - 700 mA - 9 W DC					
C00199	**WH**		**A***	892 - 649	**SP** (14° UGR<11)
	BB		**M**	1059 - 767	**ML** (30° UGR<16)
	AU		**W**	1119 - 811	**MW** (42° UGR<16)
	CU		**N**	1196 - 868	
C00203	HC				**SP** (13° UGR<11)
					FL (27° UGR<11)
					ML (32° UGR<11)

Electronics: **J1** (pag 59) | Recessed casings & accessories: (pag 57, 58)

Warp_Q EVO





DW Dynamic White 2200K-5700K - 8W (x channel) available on request

		Fin		Cct	lm S - lm D	Opt
arrayLED - CRI 90/80*- 700 mA - 9 W DC						
C00219		**WH**		**A***	892 - 711	**SP** (10° UGR<11)
C00220	HC	**BB**		**M**	1059 - 840	
		AU		**W**	1119 - 888	
		CU		**N**	1196 - 950	


Electronics: **J1** (pag 59) | Recessed casings & accessories: (pag 57, 58)

arrayLED - CRI 90/80* - 400 mA - 14 W DC					
C00217	**WH**		**A***	2007 - 1523	**FL** (21° UGR<16)
	BB		**M**	2214 - 1680	**ML** (33° UGR<16)
	AU		**W**	2318 - 1759	**WF** (54° UGR<16)
	CU		**N**	2411 - 1829	
C00218	HC				**FL** (20° UGR<11)
					ML (30° UGR<11)
					MW (47° UGR<16)

Electronics: **P1** (pag 59) | Recessed casings & accessories: (pag 57, 58)

Warp_QJ EVO





DW Dynamic White 2200K-5700K - 4W (x channel) available on request

		Fin		Cct	lm S - lm D	Opt
powerLED - CRI 90 - 350 mA - 4 W DC						
C00699		**WH**		**M**	389 - 238	**NS** (9°)
C00700	HC	**BB**		**W**	416 - 254	
		AU		**N**	449 - 275	
		CU				


Electronics: **D1** (pag 59) | Recessed casings & accessories: (pag 57, 58)

arrayLED - CRI 90/80* - 700 mA - 9 W DC					
C00697	**WH**		**A***	892 - 582	**SP** (14°)
	BB		**M**	1059 - 688	**ML** (31°)
	AU		**W**	1119 - 727	**MW** (44°)
	CU		**N**	1196 - 778	
C00698	HC				**SP** (14°)
					FL (27°)
					ML (31°)

Electronics: **J1** (pag 59) | Recessed casings & accessories: (pag 57, 58)

Warp_QJ EVO





DW Dynamic White 2200K-5700K - 8W (x channel) available on request

	Fin	Cct	lm S - lm D	Opt
arrayLED - CRI 90/80* - 700 mA - 9 W DC				
C00703	**WH**	**A***	892 - 676	**SP** (11°)
C00704 HC	**BB**	**M**	1059 - 799	
	AU	**W**	1119 - 845	
	CU	**N**	1196 - 904	

Electronics: **J1** (pag 59) | Recessed casings & accessories: (pag 57, 58)


arrayLED - CRI 90/80* - 400 mA - 14 W DC				
C00701	**WH**	**A***	2007 - 1477	**FL** (21°)
	BB	**M**	2214 - 1629	**ML** (33°)
	AU	**W**	2318 - 1705	**WF** (55°)
	CU	**N**	2411 - 1774	
C00702 HC				**FL** (20°)
				ML (30°)
				MW (48°)

Electronics: **P1** (pag 59) | Recessed casings & accessories: (pag 57, 58)



Epitax_R EVO





DW Dynamic White 2200K-5700K - 4W (x channel) available on request
Recessed casing needed: C-C100004

	Fin	Cct	lm S - lm D	Opt
powerLED - CRI 90 - 350 mA - 4 W DC				
C00162	**WH**	**M**	389 - 248	**NS** (9° UGR<11)
C00163 HC	**BB**	**W**	416 - 265	
	AU	**N**	449 - 287	
	CU			


Electronics: **D1** (pag 59) | Recessed casings & accessories: (pag 57, 58)

arrayLED - CRI 90/80* - 700 mA - 9 W DC				
C00144	**WH**	**A***	892 - 627	**SP** (15° UGR<16)
	BB	**M**	1059 - 742	**ML** (30° UGR<16)
	AU	**W**	1119 - 784	**MW** (41° UGR<16)
	CU	**N**	1196 - 839	
C00145 HC				**SP** (14° UGR<11)
				FL (27° UGR<11)
				ML (31° UGR<16)

Electronics: **J1** (pag 59) | Recessed casings & accessories: (pag 57, 58)

Epitax_R EVO





DW Dynamic White 2200K-5700K - 8W (x channel) available on request
Recessed casing needed: C-C100007


	Fin	Cct	lm S - lm D	Opt
arrayLED - CRI 90/80* - 700 mA - 9 W DC				
C00375	**WH**	**A***	892 - 689	**SP** (10° UGR<)
C00376 HC	**BB**	**M**	1059 - 814	
	AU	**W**	1119 - 861	
	CU	**N**	1196 - 921	


Electronics: **J1** (pag 59) | Recessed casings & accessories: (pag 57, 58)

arrayLED - CRI 90/80* - 400 mA - 14 W DC				
C00371	**WH**	**A***	2007 - 1547	**FL** (22° UGR<16)
	BB	**M**	2214 - 1706	**ML** (33° UGR<16)
	AU	**W**	2318 - 1786	**WF** (55° UGR<16)
	CU	**N**	2411 - 1858	
C00372 HC				**FL** (20° UGR<11)
				ML (30°UGR<11)
				MW (48° UGR<16)

Electronics: **P1** (pag 59) | Recessed casings & accessories: (pag 57, 58)

Epitax_RJ EVO





DW Dynamic White 2200K-5700K - 4W (x channel) available on request
Recessed casing needed: C-C100004

	Fin	Cct	lm S - lm D	Opt
powerLED - CRI 90 - 350 mA - 4 W DC				
C00164	**WH**	**M**	389 - 240	**NS** (9°)
C00165 HC	**BB**	**W**	416 - 257	
	AU	**N**	449 - 277	
	CU			


Electronics: **D1** (pag 59) | Recessed casings & accessories: (pag 57, 58)

arrayLED - CRI 90/80* - 700 mA - 9 W DC				
C00146	**WH**	**A***	892 - 604	**SP** (14°)
	BB	**M**	1059 - 714	**ML** (30°)
	AU	**W**	1119 - 754	**MW** (40°)
	CU	**N**	1196 - 807	
C00147 HC				**SP** (14°)
				FL (27°)
				ML (31°)

Electronics: **J1** (pag 59) | Recessed casings & accessories: (pag 57, 58)

Epitax_RJ EVO





DW Dynamic White 2200K-5700K - 8W (x channel) available on request

Recessed casing needed: C-C100007


	Fin	Cct	lm S - lm D	Opt
arrayLED - CRI 90/80* - 700 mA - 9 W DC				
C00377	**WH**	**A***	892 - 681	**SP** (11°)
C00378 HC	**BB**	**M**	1059 - 805	
	AU	**W**	1119 - 851	
	CU	**N**	1196 - 910	

Electronics: **J1** (pag 59) | Recessed casings & accessories: (pag 57, 58)

arrayLED - CRI 90/80* - 400 mA - 14 W DC				
C00373	**WH**	**A***	2007 - 1501	**FL** (21°)
	BB	**M**	2214 - 1655	**ML** (33°)
	AU	**W**	2318 - 1733	**WF** (54°)
	CU	**N**	2411 - 1802	
C00374 HC				**FL** (20°)
				ML (30°)
				MW (48°)

Electronics: **P1** (pag 59) | Recessed casings & accessories: (pag 57, 58)

Epitax_RJ EVO
C00373WHWML
+
Recessed casing
C-C100007



Finishes

White
Black
Gold
Copper

Cct

A 2200
M 2700
W 3000
N 4000

Accessories

HC Honeycomb

EVO FINISHES FOR UNIQUE, DISTINCTIVE SPACES

For EVO front-facing accessories we have developed four exquisitely elegant finishes: White, Black, Gold and Copper. Easy to install thanks to their simplified system, they add a touch of elegance and sophistication to any project, creating inviting, cosy atmospheres.




White (WH)



Black (BB)



Gold (AU)



Copper (CU)



Accessories

Vos EVO front elements for 4W - 9W LED modules Ø60



WH	**83365**	Vos_R front kit Ø71
BB	**83366**	Vos_R front kit Ø71
AU	**C-K400042**	Vos_R front kit Ø71
CU	**C-K400043**	Vos_R front kit Ø71



WH	**C-K400083**	Quantum_RJ front kit Ø71
BB	**C-K400084**	Quantum_RJ front kit Ø71
AU	**C-K400108**	Quantum_RJ front kit Ø71
CU	**C-K400109**	Quantum_RJ front kit Ø71

Vos EVO front elements for 9W - 14W LED modules Ø88



WH	**83377**	Vos_R front kit Ø105
BB	**83378**	Vos_R front kit Ø105
AU	**C-K400050**	Vos_R front kit Ø105
CU	**C-K400051**	Vos_R front kit Ø105



WH	**C-K400085**	Quantum_RJ front kit Ø99
BB	**C-K400086**	Quantum_RJ front kit Ø99
AU	**C-K400102**	Quantum_RJ front kit Ø99
CU	**C-K400103**	Quantum_RJ front kit Ø99

Quantum EVO front elements for 4W - 9W LED modules Ø60



WH	**83361**	Quantum_R front kit Ø71
BB	**83362**	Quantum_R front kit Ø71
AU	**C-K400038**	Quantum_R front kit Ø71
CU	**C-K400039**	Quantum_R front kit Ø71



WH	**C-K400087**	Quantum_RJ front kit Ø71
BB	**C-K400088**	Quantum_RJ front kit Ø71
AU	**C-K400110**	Quantum_RJ front kit Ø71
CU	**C-K400111**	Quantum_RJ front kit Ø71

Quantum EVO front elements for 9W - 14W LED modules Ø88



WH	**83373**	Quantum_R front kit Ø92
BB	**83374**	Quantum_R front kit Ø92
AU	**C-K400046**	Quantum_R front kit Ø92
CU	**C-K400047**	Quantum_R front kit Ø92



WH	**C-K400089**	Quantum_RJ front kit Ø99
BB	**C-K400090**	Quantum_RJ front kit Ø99
AU	**C-K400104**	Quantum_RJ front kit Ø99
CU	**C-K400105**	Quantum_RJ front kit Ø99

Warp EVO front elements for 4W - 9W LED modules Ø60



WH	**83363**	Warp_R front kit Ø71
BB	**83364**	Warp_R front kit Ø71
AU	**C-K400040**	Warp_R front kit Ø71
CU	**C-K400041**	Warp_R front kit Ø71



WH	**C-K400081**	Warp_RJ front kit Ø71
BB	**C-K400082**	Warp_RJ front kit Ø71
AU	**C-K400028**	Warp_RJ front kit Ø71
CU	**C-K400029**	Warp_RJ front kit Ø71



WH	**C-K400032**	Warp_Q front kit 71x71
BB	**C-K400033**	Warp_Q front kit 71x71
AU	**C-K400097**	Warp_Q front kit 71x71
CU	**C-K400098**	Warp_Q front kit 71x71



WH	**C-K400093**	Warp_QJ front kit 71x71
BB	**C-K400094**	Warp_QJ front kit 71x71
AU	**C-K400112**	Warp_QJ front kit 71x71
CU	**C-K400113**	Warp_QJ front kit 71x71

Warp EVO front elements for 9W - 14W LED modules Ø88



WH	**83375**	Warp_R front kit Ø99
BB	**83376**	Warp_R front kit Ø99
AU	**C-K400048**	Warp_R front kit Ø99
CU	**C-K400049**	Warp_R front kit Ø99



WH	**C-K400091**	Warp_RJ front kit Ø99
BB	**C-K400092**	Warp_RJ front kit Ø99
AU	**C-K400114**	Warp_RJ front kit Ø99
CU	**C-K400115**	Warp_RJ front kit Ø99



WH	**C-K400034**	Warp_Q front kit 100x100
BB	**C-K400035**	Warp_Q front kit 100x100
AU	**C-K400099**	Warp_Q front kit 100x100
CU	**C-K400100**	Warp_Q front kit 100x100



WH	**C-K400095**	Warp_QJ front kit 100x100
BB	**C-K400096**	Warp_QJ front kit 100x100
AU	**C-K400106**	Warp_QJ front kit 100x100
CU	**C-K400107**	Warp_QJ front kit 100x100

Epitax EVO front elements for 4W - 9W LED modules Ø60



WH	**C-K400116**	Epitax_R front kit Ø63
BB	**C-K400117**	Epitax_R front kit Ø63
AU	**C-K400118**	Epitax_R front kit Ø63
CU	**C-K400119**	Epitax_R front kit Ø63



WH	**C-K400120**	Epitax_RJ front kit Ø63
BB	**C-K400121**	Epitax_RJ front kit Ø63
AU	**C-K400122**	Epitax_RJ front kit Ø63
CU	**C-K400123**	Epitax_RJ front kit Ø63

Epitax EVO front elements for 9W - 14W LED modules Ø88



WH	**C-K400124**	Epitax_R front kit Ø92
BB	**C-K400125**	Epitax_R front kit Ø92
AU	**C-K400126**	Epitax_R front kit Ø92
CU	**C-K400127**	Epitax_R front kit Ø92



WH	**C-K400128**	Epitax_RJ front kit Ø92
BB	**C-K400129**	Epitax_RJ front kit Ø92
AU	**C-K400130**	Epitax_RJ front kit Ø92
CU	**C-K400131**	Epitax_RJ front kit Ø92

Finishes

WH White AU Gold
BB Black CU Copper

INTERCHANGEABLE COMPONENTS BETWEEN WARP, QUANTUM, VOS, EPITAX EVO:

Optics kit for LED module Ø60



83370	Spot lens kit (15°)
83371	Medium Flood lens kit (30°)
83372	Medium Flood lens kit (45°)

suitable for: 9W

Optics kit for LED module Ø88



83382	Flood lens kit (20°)
83383	Medium Flood lens kit (30°)
83384	Wide Flood lens kit (50°)

suitable for: 14W

Filters for LED module Ø60



83367	Honeycomb
83368	Elliptic filter
83369	Aesthetic filter

suitable for: 4W - 9W


Filters for LED module Ø88



83379	Honeycomb
83380	Elliptic filter
83381	Aesthetic filter


suitable for: 9W - 14W

Adapter Ring Ø81




WH	**83393**	Warp_R Ø 71 - Quantum_R Ø 71
BB	**83394**	Warp_R Ø 71 - Quantum_R Ø 71
AU	**C-K400044**	Warp_R Ø 71 - Quantum_R Ø 71
CU	**C-K400045**	Warp_R Ø 71 - Quantum_R Ø 71

Adapter Ring Ø106



WH	**83391**	Quantum_R Ø92
BB	**83392**	Quantum_R Ø92
AU	**C-K400054**	Quantum_R Ø92
CU	**C-K400055**	Quantum_R Ø92

Adapter Ring Ø109



WH	**83395**	Warp_R Ø99
BB	**83390**	Warp_R Ø99
AU	**C-K400052**	Warp_R Ø99
CU	**C-K400053**	Warp_R Ø99

Recessed casing



PLC **C-C100004** Recessed casing for flush installation

suitable for: Epitax_R Ø63 - Epitax_RJ Ø63




PLC **C-C100007** Recessed casing for flush installation

suitable for: Epitax_R Ø92 - Epitax_RJ Ø92w




PLP **89373** Recessed casing for brick

suitable for: Quantum_R - Warp_R - Vos_ R



PLP **89374** Recessed casing for brick

suitable for: Quantum_R - Warp_R - Vos_ R



AL **99849** Recessed casing for flush installation

suitable for: Vos_R Ø71 - Vos_RJ Ø71



AL **83065** Recessed casing for flush installation

suitable for: Vos_R Ø105 - Vos_RJ Ø105

Finishes

WH White AU Gold PLC Polycarbonate AL Aluminium
BB Black CU Copper PLP Polypropylene

Electronics

D1

89145
ON/OFF
1 art.
138 x 22 x h 21
29

99375
ON/OFF
2 - 3 art.
138 x 22 x h 21
29

C-E100010
0/1-10V
1 art.
138 x 22 x h 22
31

C-E100011
DALI/PUSH
1 art.
138 x 22 x h 22
31

P1

99734
ON/OFF
1 art.
149 x 37 x h 31
48

99732
0/1-10V
1 art.
149 x 37 x h 31
48

83322
DALI/PUSH
1 art.
149 x 37 x h 31
48

J1

99735
ON/OFF
1 art.
134 x 37 x h 31
48

99147
ON/OFF
2 - 3 art.
103 x 58 x h 27
64

99733
0/1-10V
1 art.
134 x 37 x h 31
48

C-E100012
DALI/PUSH
1 art.
134 x 37 x h 31
48

C-E100016
DALI/PUSH
2 - 3 art.
131 x 44 x h 30
54







MODOC

Aluminium body. Technopolymer diffuser.

MODOC
TM66
RESULT 2.4

CREATIVE FLEXIBILITY

IP20
IP65

A complete collection of professional downlights, designed to offer exceptional performance and to ensure maximum visual comfort. The particular compact structure, created with the highest quality materials, enables installations even in situations of limited space due to the innovative heat sink that completely envelops the diffuser, the six different diameters available, powers from 2 W up to 37 W and a wide optical range, including with Wall Washer distribution. The optics, completely interchangeable, are used to create unique light compositions suitable for any design requirement. Each Modoc luminaire, due to a clean and minimal design, is intended to integrate with the others, creating a visual synergy that transforms spaces.

A

7 Different versions and aesthetic uniformity
6 Powers from 2 W to 37 W
2 Installation options
2 Finishes
5 Temperature colour with high colour rendering
7 Light distributions

B

5 Accessory: interchangeable optics

C

1 Accessory: elliptical filter

D


2 Accessory: closing screens. They guarantee IP65 rating in the optical compartment. Transparent and satin white versions.



NO NEED
FIELD
INTERCHANGEABLE

Upgradeable on-site without tools

TWO SOLUTIONS, ONE UNMISTAKABLE DESIGN



Modoc_R
Version with frame, extremely slender, suitable to elegantly conceal any imperfection due to a hole in the plasterboard

Modoc_RF
Frameless version, offers clean and minimal aesthetics, the luminaire blends harmoniously with the ceiling, creating a modern and seamless visual effect. The luminaire must be installed with the appropriate outer casing.


MODOC, A UNIQUE DESIGN FOR A UNIQUE PROJECT




	_R/RF	_R/RF	_R/RF	_R/RF Ww	_R/RF	_R/RF	_R/RF
W	37	26	18	10	10	6	2
mm	**Ø 189/178**	**Ø 138/128**	**Ø 115/105**	**Ø 86/75**	**Ø 86/75**	**Ø 44/35**	**Ø 27/22**
Cct	2200-2700 3000-3500 4000	2200-2700 3000-3500 4000	2200-2700 3000-3500 4000	2200-2700 3000-3500 4000	2200-2700 3000-3500 4000	2200-2700 3000-3500 4000	2200-2700 3000-3500 4000
Opt	**Spot, Flood, M.Flood, W.Flood, Diffused**	**Spot, Flood, M.W.Flood, W.Flood, Diffused**	**Flood, M.Flood, M.W.Flood, W.Flood, Diffused**	**Asymmetric Ww**	**Spot, Flood, M.W.Flood, W.Flood, Diffused**	**Spot, Flood, W.Flood**	**Spot, M.Flood, W.Flood**
Elec.	On/Off 0/1-10V DALI	On/Off 0/1-10V DALI	On/Off 0/1-10V DALI	On/Off 0/1-10V DALI	On/Off 0/1-10V DALI	On/Off 0/1-10V DALI	On/Off 0/1-10V DALI
Col.	WH BB	WH BB	WH BB	WH BB	WH BB	WH BB	WH BB

Modoc Wall Washer


The particular optic with Wall Washer distribution diffuses the light uniformly along the entire wall, eliminating undesirable shadows. Modoc Wall Washer is the ideal solution to accentuate architectural details, to enhance works of art or simply to create a welcoming and uniformly lit environment. The design that characterises the front of the Modoc Ww luminaires has been created to harmoniously integrate with the Modoc models with rotosymmetric optics.






Modoc Ww adjustment system.

EXCEPTIONAL PERFORMANCE AT EVERY HEIGHT




The Modoc collection features an innovative high-performance heat sink, designed to efficiently manage the temperature, guaranteeing reliable performance over time and a prolonged life of the luminaire. The structure that completely envelops the reflector optimises the dimensions to fit perfectly in all ceilings, even those with limited spaces.



INSTALLATION ADAPTABILITY

The outer casing for flush installation, dedicated to the Modoc RF versions, has been designed to adapt to a wide range of false ceilings, easily adjustable using the relevant fixing tabs, with a minimum step of 12mm up to a maximum of 30mm.



Minimum adjustment 12mm

Maximum adjustment 30mm


1
2
3
4
5




CONSISTENT DESIGN FOR DIFFERENT HEIGHTS

Modoc downlights are the ideal solution for multifunctional contexts. The luminaires adapt to the specific needs of the installation height. Thanks to their wide optic range and scalable powers, they ensure optimal light distribution.

1 **Modoc_RF Ww** 10 W - Ø 75
2 **Modoc_RF** 10 W - Ø 75
3 **Modoc_RF** 26 W - Ø 128
4 **Modoc_RF** 37 W - Ø 178
5 **Modoc_RF** 6 W - Ø 35
6 **Modoc_RF** 18 W - Ø 105

Modoc_R | powerLED | 630 mA | 2 W DC






	Fin	Cct	lm S - lm D	Opt
CRI 90/80*				
C00771	**WH**	**A***	199 - 137	**SP** (19° UGR<19)
	BB	**M**	227 - 149	**ML** (37° UGR<19)
		W	242 - 168	**WF** (52°)
		T	240 - 167	
		N	271 - 187	

Electronics: **C1** (pag 71) | Recessed casings & accessories: (pag 67)

Modoc_R | arrayLED | 500 mA | 6 W DC






	Fin	Cct	lm S - lm D	Opt
CRI 90/80*				
C00579	**WH**	**A***	700 - 441	**SP** (19°)
	BB	**M**	814 - 523	**FL** (24°)
		W	860 - 542	**WF** (52°)
		T	897 - 565	
		N	919 - 579	

Electronics: **E1** (pag 71) | Recessed casings & accessories: (pag 67)

Modoc_R | arrayLED | 300 mA | 10 W DC






	Fin	Cct	lm S - lm D	Opt
CRI 90/80*				
C00580	**WH**	**A***	1570 - 1212	**SP** (19° UGR<11)
	BB	**M**	1707 - 1317	**FL** (29° UGR<11)
		W	1787 - 1379	**MW** (43° UGR<16)
		T	1804 - 1393	**WF** (53° UGR<19)
		N	1858 - 1434	**DI** (Diffused)

Electronics: **L1** (pag 71) | Recessed casings & accessories: (pag 67)

DW Dynamic White 2200K-5700K - 8W (x channel) available on request

Modoc_R Ww | arrayLED | 300 mA | 10 W DC






	Fin	Cct	lm S - lm D	Opt
CRI 90/80*				
C00786	**WH**	**A***	1570 - 515	**WW** (Asym. Ww)
	BB	**M**	1707 - 648	
		W	1787 - 689	
		T	1804 - 689	
		N	1858 - 724	

Electronics: **L1** (pag 71) | Recessed casings: (pag 67)

Modoc_R | arrayLED | 550 mA | 18 W DC






	Fin	Cct	lm S - lm D	Opt
CRI 90/80*				
C00581	**WH**	**A***	2789 - 2245	**FL** (25° UGR<16)
	BB	**M**	3090 - 2477	**ML** (31° UGR<16)
		W	3129 - 2528	**MW** (44° UGR<16)
		T	3322 - 2685	**WF** (54° UGR<19)
		N	3252 - 2629	**DI** (Diffused)

Electronics: **FO** (pag 71) | Recessed casings & accessories: (pag 67)

DW Dynamic White 2200K-5700K - 15W (x channel) available on request

Modoc_R | arrayLED | 750 mA | 26 W DC






DW Dynamic White 2200K-5700K - 15W (x channel) available on request

	Fin		Cct	lm S - lm D	Opt
CRI 90/80*					
C00582	**WH**		**A***	3846 - 2890	**SP** (18° UGR<11)
	BB		**M**	4096 - 3081	**FL** (27° UGR<16)
			W	4268 - 3209	**MW** (41° UGR<16)
			T	4412 - 3318	**WF** (51° UGR<19)
			N	4499 - 3382	**DI** (Diffused)

Electronics: **FP** (pag 71) | Recessed casings & accessories: (pag 67)

Modoc_R | arrayLED | 1100 mA | 37 W DC





DW Dynamic White 2200K-5700K - 25W (x channel) available on request

	Fin		Cct	lm S - lm D	Opt
CRI 90/80*					
C00583	**WH**		**A***	5670 - 4533	**SP** (19° UGR<16)
	BB		**M**	6022 - 4818	**FL** (25° UGR<11)
			W	6249 - 4997	**ML** (38° UGR<11)
			T	6428 - 5147	**WF** (56° UGR<19)
			N	6634 - 5297	**DI** (Diffused)


Electronics: **X1** (pag 71) | Recessed casings & accessories: (pag 67)

Recessed casing




PLP 89373 Recessed casing for brick

suitable for: Modoc_R Ø27 / Ø44/ Ø86
Modoc_R Ww Ø86




PLP 89374 Recessed casing for brick

suitable for: Modoc_R Ø27 / Ø44/ Ø86
Modoc_R Ww Ø86



PLP C-C100016 Outer casing for brickwork to be completed with accessory **C-C100020**

suitable for: Modoc_R Ø115 / Ø138 / Ø189



PLP C-C100017 Outer casing for brickwork to be completed with accessory **C-C100020**


suitable for: Modoc_R Ø115 / Ø138 / Ø189




PLP C-C100020 Grille for round hole

suitable for: Modoc_R Ø115 / Ø138 / Ø189

Modoc_RF | powerLED | 630 mA | 2 W DC






	Fin	Cct	lm S - lm D	Opt
CRI 90/80*				
C00783	**WH**	**A***	199 - 137	**SP** (19° UGR<19)
	BB	**M**	227 - 149	**ML** (37° UGR<19)
		W	242 - 168	**WF** (52°)
		T	240 - 167	
		N	271 - 187	

Electronics: **C1** (pag 71) | Recessed casings & accessories: (pag 69, 71)

Modoc_RF | arrayLED | 500 mA | 6 W DC






	Fin	Cct	lm S - lm D	Opt
CRI 90/80*				
C00692	**WH**	**A***	700 - 441	**SP** (19°)
	BB	**M**	814 - 523	**FL** (24°)
		W	860 - 542	**WF** (52°)
		T	897 - 565	
		N	919 - 579	

Electronics: **E1** (pag 71) | Recessed casings & accessories: (pag 69, 71)

Modoc_RF | arrayLED | 300 mA | 10 W DC






	Fin	Cct	lm S - lm D	Opt
CRI 90/80*				
C00693	**WH**	**A***	1570 - 1212	**SP** (19° UGR<11)
	BB	**M**	1707 - 1317	**FL** (29° UGR<11)
		W	1787 - 1379	**MW** (43° UGR<16)
		T	1804 - 1393	**WF** (53° UGR<19)
		N	1858 - 1434	**DI** (Diffused)

Electronics: **L1** (pag 71) | Recessed casings & accessories: (pag 69, 71)

DW Dynamic White 2200K-5700K - 8W (x channel) available on request

Modoc_RF Ww | arrayLED | 300 mA | 10 W DC






	Fin	Cct	lm S - lm D	Opt
CRI 90/80*				
C00787	**WH**	**A***	1570 - 515	**WW** (Asym. Ww)
	BB	**M**	1707 - 648	
		W	1787 - 689	
		T	1804 - 689	
		N	1858 - 724	

Electronics: **L1** (pag 71) | Recessed casings: (pag 69, 71)

Modoc_RF | arrayLED | 550 mA | 18 W DC





	Fin	Cct	lm S - lm D	Opt
CRI 90/80*				
C00694	**WH**	**A***	2789 - 2245	**FL** (25° UGR<16)
	BB	**M**	3090 - 2477	**ML** (31° UGR<16)
		W	3129 - 2528	**MW** (44° UGR<16)
		T	3322 - 2685	**WF** (54° UGR<19)
		N	3252 - 2629	**DI** (Diffused)


Electronics: **FO** (pag 71) | Recessed casings & accessories: (pag 69, 71)

DW Dynamic White 2200K-5700K - 15W (x channel) available on request

The Modoc_RF models must be completed with the appropriate plasterboard outer casing.

Modoc_RF | arrayLED | 750 mA | 26 W DC






DW Dynamic White 2200K-5700K - 15W (x channel) available on request

	Fin	Cct	lm S - lm D	Opt
CRI 90/80*				
C00695	**WH**	**A***	3846 - 2890	**SP** (18° UGR<11)
	BB	**M**	4096 - 3081	**FL** (27° UGR<16)
		W	4268 - 3209	**MW** (41° UGR<16)
		T	4412 - 3318	**WF** (51° UGR<19)
		N	4499 - 3382	**DI** (Diffused)

Electronics: **FP** (pag 71) | Recessed casings & accessories: (pag 69, 71)

Modoc_RF | arrayLED | 1100 mA | 37 W DC






DW Dynamic White 2200K-5700K - 25W (x channel) available on request

	Fin	Cct	lm S - lm D	Opt
CRI 90/80*				
C00696	**WH**	**A***	5670 - 4533	**SP** (19° UGR<16)
	BB	**M**	6022 - 4818	**FL** (25° UGR<11)
		W	6249 - 4997	**ML** (38° UGR<11)
		T	6428 - 5147	**WF** (56° UGR<19)
		N	6634 - 5297	**DI** (Diffused)

Electronics: **X1** (pag 71) | Recessed casings & accessories: (pag 69, 71)


The Modoc_RF models must be completed with the appropriate plasterboard outer casing.

Recessed casings




PLP C-C100009 Recessed casing for flush installation

suitable for: Modoc_RF Ø22




PLP C-C100008 Recessed casing for flush installation

suitable for: Modoc_RF Ø75 (not for Modoc_RF Ww)




PLP C-C100010 Recessed casing for flush installation

suitable for: Modoc_RF Ø105




PLP C-C100012 Recessed casing for flush installation

suitable for: Modoc_RF Ø178




PLP C-C100006 Recessed casing for flush installation

suitable for: Modoc_RF Ø35



PLP C-C100013 Recessed casing for flush installation

suitable for: Modoc_RF Ww Ø75



PLP C-C100011 Recessed casing for flush installation

suitable for: Modoc_RF Ø128

Finishes

White **PLP** Polypropylene
Black

Cct

A 2200 **W** 3000 **N** 4000
M 2700 **T** 3500



Modoc downlights are innovative, interchangeable, totally recyclable and sustainabl. We realise that environmental protection is a major concern these days. For this reason, i-LèD consists of a series of luminaires developed to help reduce environmental impact without compromising quality or functionality.

Accessories

Optics kit for Modoc 10W (not for Modoc Ww)



83382	Spot lens kit (20°)
83383	Flood lens kit (30°)
C-K400132	Medium Wide Flood lens kit (44°)
83384	Wide Flood lens kit (53°)

suitable for: Modoc_R - Modoc_RF

Optics kit for Modoc 18W



C-K400134	Flood lens kit (25°)
C-K400135	Medium Flood lens kit (30°)
C-K400136	Medium Wide Flood lens kit (44°)
C-K400148	Wide Flood lens kit (54°)

suitable for: Modoc_R - Modoc_RF

Optics kit for Modoc 26W



C-K400138	Spot lens kit (19°)
C-K400139	Flood lens kit (27°)
C-K400140	Medium Wide Flood lens kit (40°)
C-K400141	Wide Flood lens kit (50°)

suitable for: Modoc_R - Modoc_RF

Optics kit for Modoc 37W



C-K400144	Spot lens kit (19°)
C-K400145	Flood lens kit (26°)
C-K400146	Medium Flood lens kit (38°)
C-K400147	Wide Flood lens kit (56°)

suitable for: Modoc_R - Modoc_RF

Transparent closing screen (not for Modoc Ww)



C-U300035	TR	Modoc R - Modoc RF 10W
C-U300037	TR	Modoc R - Modoc RF 18W
C-U300039	TR	Modoc R - Modoc RF 26W
C-U300041	TR	Modoc R - Modoc RF 37W

suitable for: Modoc_R - Modoc_RF


Diffused closing screen (not for Modoc Ww)



C-U300036	OP	Modoc R - Modoc RF 10W
C-U300038	OP	Modoc R - Modoc RF 18W
C-U300040	OP	Modoc R - Modoc RF 26W
C-U300042	OP	Modoc R - Modoc RF 37W

suitable for: Modoc_R - Modoc_RF

Elliptic filter for Modoc (not for Modoc Ww)



C-U300019	Modoc R - Modoc RF 10W
C-U300020	Modoc R - Modoc RF 18W
C-U300021	Modoc R - Modoc RF 26W
C-U300022	Modoc R - Modoc RF 37W

suitable for: Modoc_R - Modoc_RF

To ensure the proper functioning of the device with the diffuse screen accessory, the optics must be removed.



Modoc with optics:
SP (Spot) - FL (Flood)
ML (Medium Flood)
MW (Medium Wide Flood)
WF (Wide Flood)



Modoc with optics:
DI (Diffused)

Suction cup for all Modoc (not for 2W/6W)



C-F600002	Suction cup for removal protective screen

suitable for: Modoc_R - Modoc_RF

Electronics

C1

89147	99376	99105	99710	99713	+ driver 24V DC	
					99374 75W	99331 150W
ON/OFF	ON/OFF	ON/OFF	24V DC converter	24V DC converter		
1 - 2 art.	3 - 6 art.	6 - 12 art.	0/1-10V 1 - 6 art.	DALI 1 - 6 art.		
138 x 22 x h 21	138 x 22 x h 21	103 x 58 x h 27	138 x 22 x h 20	138 x 22 x h 20		
29	29	64	29	29	56	70

E1

99377	99106	C-E100004	C-E100005	C-E100001
ON/OFF	ON/OFF	0/1-10V	DALI/PUSH	DALI/PUSH
1 art.	2 - 3 art.	1 art.	1 art.	2 - 3 art.
138 x 22 x h 21	103 x 58 x h 27	124 x 22 x h 22	124 x 22 x h 22	131 x 44 x h 30
29	64	31	31	54

FO

C-E100033	C-E100034
ON/OFF	DALI/PUSH
1 art.	1 art.
138 x 44 x h 23	138 x 44 x h 23
50	50

FP

C-E100033	C-E100034
ON/OFF	DALI/PUSH
1 art.	1 art.
138 x 44 x h 23	138 x 44 x h 23
50	50

L1

99734	99732	83322
ON/OFF	0/1-10V	DALI/PUSH
1 art.	1 art.	1 art.
149 x 37 x h 31	149 x 37 x h 31	149 x 37 x h 31
48	48	48

X1

C-E100048	83008
ON/OFF	0/1-10V, DALI/PUSH
1 art.	1 art.
142 x 43 x h 30	124 x 79 x h 22
53	84

Finishes

TR Transparent
OP Opaline

VOS

Aluminium body. Aluminium flange. Black-painted optics compartment.




	_Ww	_R	_RJ	_Q	_QJ
W	17	2-4,5-6,3-8-15	4,5-6,3-8-15	2-4,5-6,3-8-15	4,5-6,3-8-15
mm	**Ø 135**	**Ø 42-71-105**	**Ø 64-75-100**	**□ 42-71-105**	**□ 64-75-100**
Cct	2700-3000 4000	2700-3000-4000	2700-3000-4000	2700-3000-4000	2700-3000-4000
Opt	**Adj. Ww**	**Ultra Spot-Spot Flood-M.Flood M.W.Flood-W-Flood**	**Spot-Flood M.Flood-W.Flood M.W.Flood**	**Ultra Spot-Spot-Flood W.Flood-M.Flood M.W.Flood**	**Spot-Flood-M.Flood M.W. Flood-W.Flood**
Elec.	On/Off 0/1-10V DALI	On/Off 0/1-10V DALI	On/Off 0/1-10V DALI	On/Off 0/1-10V DALI	On/Off 0/1-10V DALI
Col.	WH BB	WH BB	WH BB	WH BB	WH BB

A complete range of recessed downlights designed for interior lighting in a contemporary style, boasting high performance and minimal aesthetic impact. The Vos luminaires offer high visual comfort due to the optical compartment that uses the pin-hole camera concept, guaranteeing reflectance control. The source is arranged on a plane set back from the opening of the compartment: the photons that compose the primary light beam exit without encountering obstacles, while the more external ones bounce within the compartment, painted black to obtain the maximum degree of absorption.




TILTING VERSION, SHIELDING OF THE OPTICS COMPARTMENT

The Vos_RJ and Vos_QJ range of products come with a 360° mobility on the horizontal axis and a 35° tilt on the vertical axis. The downlight structure was designed to avoid rear light dispersion and for shielding the internal of the dropped ceiling.



Vos_R | powerLED | 630 mA | 2 W DC






	Fin	Cct	lm S - lm D	Opt
CRI 80				
C00064	**WH**	**M**	174 - 120	**US** (5° UGR<11)
	BB	**W**	186 - 129	
		N	198 - 137	

Electronics: **C1** (pag 76) | Recessed casing: (pag 76)

Vos_R | V2 | powerLED | 500 mA 4,5 W DC | 700 mA 6,3 W DC







	Fin	Cct	lm S - lm D 4,5 W	lm S - lm D 6,3 W	Opt
CRI 90					
C00046	**WH**	**M**	544 - 191	715 - 252	**SP** (19° UGR<16)
	BB	**W**	569 - 200	748 - 263	**FL** (24° UGR<16)
		N	612 - 216	805 - 285	**MW** (46°)
CRI 90					
C00047 HC	**WH**	**M**	544 - 136	715 - 179	**SP** (17° UGR<11)
	BB	**W**	569 - 142	748 - 187	**FL** (21° UGR<16)
		N	612 - 154	805 - 203	**ML** (36° UGR<16)

Electronics: 4,5W **FM** - 6,3W **I1** (pag 76) | Recessed casing: (pag 76)

Vos_R | powerLED | 700 mA | 8 W DC







		Cct	lm S - lm D	Opt
CRI 90				
WH **90662**		**M**	689 - 370	**15** (15° UGR<19)
BB **90663**		**W**	738 - 397	**30** (34° UGR<19)
WH **90670**	HC	**N**	796 - 427	**45** (56°)
BB **90671**	HC			

Electronics: **J1** (pag 76) | Recessed casing * & ccessories: (pag 76)

Vos_R | arrayLED | 400 mA | 15 W DC






		Cct	lm S - lm D	Opt
CRI 90				
WH **90674**		**M**	2214 - 1193	**15** (21° UGR<11)
BB **90675**		**W**	2318 - 1249	**30** (33° UGR<11)
WH **90682**	HC	**N**	2411 - 1300	**60** (49° UGR<19)
BB **90683**	HC			

Electronics: **P2** (pag 76) | Recessed casing: (pag 76)

Vos_Ww | powerLED | 500 mA | 17 W DC





		Cct	lm S - lm D	Opt
CRI 90				
WH **82469**		**M**	2026 - 968	**07** (Adj. Ww)
BB **82470**		**W**	2174 - 998	
		N	2520 - 1075	

Electronics: **Q1** (pag 76)

CONTOURED WALL WASHER


The new technology revolutionises the standards established until now for wall washer lighting. The diaphragm positioned on the optics compartment allows the breadth of the light beam to be adjusted, for versatile and high performance wall lighting. The beam always reaches the peak near the edge of the ceiling, usually narrow and difficult to light, whereas, acting on the opening of the diaphragm, the angle of emission can be changed and therefore the beam can be narrowed or widened, allowing Vos_Ww to be positioned at any distance from the wall and maintaining an immediate, precise and perfect wash to emphasise great works exhibited.



Finishes	Cct			Accessories
WH White	**M** 2700	**N** 4000		HC Honeycomb
BB Black	**W** 3000			

Vos_RJ | V2 | powerLED | 500 mA 4,5 W DC | 700 mA 6,3 W DC






	Fin		Cct	lm S - lm D	lm S - lm D	Opt	
CRI 90				4,5 W	6,3 W		
C00934	**WH**		**M**	544 - 228	715 - 302	**SP**	(19°)
	BB		**W**	569 - 238	748 - 315	**FL**	(27°)
			N	612 - 257	805 - 339	**MW**	(43°)
CRI 90							
C00935 HC	**WH**		**M**	544 - 169	715 - 221	**SP**	(18°)
	BB		**W**	569 - 176	748 - 231	**FL**	(24°)
			N	612 - 190	805 - 249	**ML**	(36°)

Electronics: 4,5W **FM** - 6,3W **I1** (pag 76)

Vos_RJ | powerLED | 700 mA | 8 W DC






		Cct	lm S - lm D	Opt	
CRI 90					
WH **81274**		**M**	689 - 260	**15**	(16°)
BB **81275**		**W**	738 - 278	**30**	(32°)
WH **81122**	HC	**N**	796 - 302	**45**	(49°)
BB **81123**	HC				

Electronics: **J1** (pag 76) | Recessed casing: (pag 76)

Vos_RJ | arrayLED | 400 mA | 15 W DC







	Cct	lm S - lm D	Opt	
CRI 90				
WH **81282**	**M**	2214 - 959	**15**	(22°)
BB **81283**	**W**	2318 - 1004	**30**	(34°)
	N	2411 - 1044	**60**	(45°)

Electronics: **P2** (pag 76) | Recessed casing: (pag 76)

Vos_Q | powerLED | 630 mA | 2 W DC







	Fin		Cct	lm S - lm D	Opt	
CRI 80						
C00063	**WH**		**M**	196 - 97	**US**	(5° UGR<11)
	BB		**W**	210 - 104		
			N	223 - 111		

Electronics: **C1** (pag 76)

Vos_Q | V2 | powerLED | 500 mA 4,5 W DC | 700 mA 6,3 W DC







	Fin		Cct	lm S - lm D	lm S - lm D	Opt	
CRI 90				4,5 W	6,3 W		
C00040	**WH**		**M**	544 - 181	715 - 238	**SP**	(19° UGR<16)
	BB		**W**	569 - 187	748 - 247	**FL**	(23° UGR<16)
			N	612 - 225	805 - 268	**MW**	(43°)
CRI 90							
C00045 HC	**WH**		**M**	544 - 133	715 - 176	**SP**	(17° UGR<11)
	BB		**W**	569 - 139	748 - 184	**FL**	(21° UGR<11)
			N	612 - 152	805 - 200	**ML**	(34° UGR<16)

Electronics: 4,5W **FM** - 6,3W **I1** (pag 76)

Vos_Q | powerLED | 700 mA | 8 W DC







C.C. IP44 IP65

		Cct	Im S - Im D	Opt
CRI 90				
WH **90660**		**M**	689 - 369	**15** (15° UGR<16)
BB **90661**		**W**	738 - 396	**30** (30° UGR<19)
WH **90666**	HC	**N**	796 - 427	**45** (52°)
BB **90667**	HC			

Electronics: **J1** (pag 76) | Recessed casing*: (pag 76)

Vos_Q | arrayLED | 400 mA | 15 W DC







C.C. IP44 IP65

		Cct	Im S - Im D	Opt
CRI 90				
WH **90672**		**M**	2214 - 1226	**15** (20° UGR<11)
BB **90673**		**W**	2318 - 1282	**30** (33° UGR<16)
WH **90678**	HC	**N**	2411 - 1336	**60** (49° UGR<19)
BB **90679**	HC			

Electronics: **P2** (pag 76)

Vos_QJ | V2 | powerLED | 500 mA 4,5 W DC | 700 mA 6,3 W DC






C.C. IP44 IP65 NEW

		Fin	Cct	Im S - Im D 4,5 W	Im S - Im D 6,3 W	Opt
CRI 90						
C00938		WH	**M**	544 - 217	715 - 286	**SP** (18°)
		BB	**W**	569 - 227	748 - 299	**FL** (25°)
			N	612 - 244	805 - 322	**MW** (40°)
CRI 90						
C00939	HC	WH	**M**	544 - 162	715 - 212	**SP** (18°)
		BB	**W**	569 - 169	748 - 221	**FL** (23°)
			N	612 - 182	805 - 238	**ML** (34°)

Electronics: 4,5W **FM** - 6,3W **I1** (pag 76)

Vos_QJ | powerLED | 700 mA | 8 W DC






C.C. IP44 IP65

		Cct	Im S - Im D	Opt
CRI 90				
WH **81278**		**M**	689 - 299	**15** (15°)
BB **81279**		**W**	738 - 320	**30** (32°)
WH **80490**	HC	**N**	796 - 347	**45** (45°)
BB **80491**	HC			

Electronics: **J1** (pag 76)

Vos_QJ | arrayLED | 400 mA | 15 W DC





C.C. IP44 IP65

		Cct	Im S - Im D	Opt
CRI 90				
WH **81286**		**M**	2214 - 828	**15** (22°)
BB **81287**		**W**	2318 - 868	**30** (33°)
		N	2411 - 902	**60** (42°)

Electronics: **P2** (pag 76)

Electronics

C1

89147	99376	99105	99710	99713	+ driver 24V DC	
					99374	99331
ON/OFF	ON/OFF	ON/OFF	24V DC converter	24V DC converter	75W	150W
1 - 2 art.	3 - 6 art.	6 - 12 art.	0/1-10V 1 - 6 art.	DALI 1 - 6 art.		
138 x 22 x h 21	138 x 22 x h 21	103 x 58 x h 27	138 x 22 x h 20	138 x 22 x h 20		
29	29	64	29	29	56	70

I1

99735	99147	99733	83323	C-E100016
ON/OFF	ON/OFF	0/1-10V	DALI/PUSH	DALI/PUSH
1 art.	2 - 3 art.	1 art.	1 art.	2 - 4 art.
134 x 37 x h 31	103 x 58 x h 27	134 x 37 x h 31	134 x 37 x h 31	131 x 44 x h 30
48	64	48	48	54

P2

99740	99739	C-E100032
ON/OFF	0/1-10V	DALI/PUSH
1 art.	1 art.	1 art.
134 x 37 x h 31	134 x 37 x h 31	149 x 37 x h 31
48	48	48

FM

89146	99377	C-E100004	C-E100005	C-E100001
ON/OFF	ON/OFF	0/1-10V	DALI/PUSH	DALI/PUSH
1 art.	1 - 2 art.	1 art.	1 art.	1 - 2 art.
138 x 22 x h 21	138 x 22 x h 21	124 x 22 x h 22	124 x 22 x h 22	131 x 44 x h 30
29	64	31	31	54


J1

99735	99147	99733	C-E100012	C-E100016
ON/OFF	ON/OFF	0/1-10V	DALI/PUSH	DALI/PUSH
1 art.	2 - 3 art.	1 art.	1 art.	2 - 3 art.
134 x 37 x h 31	103 x 58 x h 27	134 x 37 x h 31	134 x 37 x h 31	131 x 44 x h 30
48	64	48	48	54

Q1

99106	99115	C-E100001
ON/OFF	0/1-10V	DALI/PUSH
1 art.	1 art.	1 art.
103 x 58 x h 27	210 x 48 x h 28	131 x 44 x h 30
64	56	54

Recessed casing




AL 99848 Recessed casing for flush installation

suitable for: Vos_R 2W - Vos_R 4,5/6,3W



AL 83065 Recessed casing for flush installation

suitable for: Vos_RJ 15W



PLP 89374 Recessed casing *


suitable for: Vos_R 8W - Vos_Q 8W

* with recessed casing for brick power reduction to 6,3W DC 500mA



AL 99849 Recessed casing for flush installation

suitable for: Vos_R 8W



AL 83064 Recessed casing for flush installation

suitable for: Vos_RJ 8W



PLP 89373 Recessed casing *

suitable for: Vos_R 8W - Vos_Q 8W

* with recessed casing for brick power reduction to 6,3W DC 500mA

Finishes

AL Aluminium
PLP Polypropylene

HARD ROCK HOTEL MADRID
Atocha, Madrid (Spain)

Project: Rockwell Group


Lighting Project: BMLD (Birgit Walter, Marcela Carmona, Alice Antonacci)

Photography:
Thestudio.rocks



WARP

Aluminium body.



Warp_RY


Warp_QY

Warp_R
Warp_R PRO
Warp_RJ


Warp_Q


Aesthetic harmony with the false ceiling is achieved with the Warp collection of recessed luminaires. Use of the extremely slim flange means it is possible to maintain visual continuity in the surface. The versions with the integrated Honeycomb set-up are able to further shield the source to ensure optimal visual comfort.

Tilting version
The items of the Warp_RJ series are characterised by mobility of 360° on the horizontal axis and an inclination of 25° on the vertical axis.




Glass Optics
Thanks to the special glass optics, designed specifically to be positioned inside the Warp_R PRO optics compartment, the distribution is significantly improved, guaranteeing uniformity and cleanliness of the light beam.





Warp_R | V2 | powerLED | 630 mA 2 W DC | 1000 mA 3 W DC






	Fin	Cct	lm S - lm D 2 W	lm S - lm D 3 W	Opt
CRI 90					
C01041	**WH**	**M**	199 - 101	358 - 149	**SP** (19°)
C01042 HC	**BB**	**W**	212 - 108	402 - 163	**FL** (25°)
		N	237 - 120	417 - 169	**MW** (46°)

Electronics: 2W **C1** - 3W **FQ** (pag 85)

Warp_R | powerLED | 630 mA | 2 W DC






	Fin	Cct	lm S - lm D	Opt
CRI 80				
C00119	**WH**	**M**	174 - 123	**US** (5° UGR<16)
	BB	**W**	186 - 132	
		N	198 - 140	

Electronics: **C1** (pag 85)

Warp_R | V2 | powerLED | 500 mA 4,5 W DC | 700 mA 6,3 W DC






	Fin	Cct	lm S - lm D 4,5 W	lm S - lm D 6,3 W	Opt
CRI 90					
C00052	**WH**	**M**	544 - 309	715 - 407	**SP** (19° UGR<16)
	BB	**W**	569 - 323	748 - 425	**FL** (28°)
		N	612 - 349	805 - 460	**WF** (50°)
CRI 90					
C00053 HC	**WH**	**M**	544 - 183	715 - 241	**SP** (17° UGR<11)
	BB	**W**	569 - 190	748 - 251	**FL** (25° UGR<19)
		N	612 - 206	805 - 271	**ML** (39°)

Electronics: 4,5W **FM** - 6,3W **I1** (pag 85)

Warp_R | powerLED | 800 mA | 10 W DC






	Cct	lm S - lm D	Opt
CRI 90			
WH **90762**	**M**	960 - 694	**15** (17° UGR<16)
BB **90763**	**W**	1034 - 747	**30** (27° UGR<19)
WH **90766** HC	**N**	1108 - 800	**60** (39°)
BB **90767** HC			

Electronics: **K1** (pag 89)

Warp_R | Dynamic White | powerLED | 700 mA | 4 W DC (x channel)






	Cct	Opt
CRI 90		
WH **84083**	**D** 2700K - 5700K Dynamic White	**15** (17° UGR<16)
BB **84084**		**30** (27° UGR<19)
WH **84085** HC		**60** (39°)
BB **84086** HC		

Electronics: **CL** (pag 85)

Warp_R | arrayLED | 400 mA | 15 W DC





	Cct	lm S - lm D	Opt
CRI 90			
WH **90776**	**M**	2214 - 1616	**15** (22° UGR<16)
BB **90777**	**W**	2318 - 1692	**30** (38° UGR<16)
WH **90780** HC	**N**	2411 - 1760	**60** (52° UGR<19)
BB **90781** HC			

Electronics: **P2** (pag 85)


Finishes
WH White
BB Black

Cct
M 2700 **N** 4000
W 3000 **D** 2700 - 5700

Accessories
HC Honeycomb

Warp_R | Dynamic White | powerLED | 700 mA | 8 W DC (x channel)






		Cct		Opt
CRI 90				
WH 84087		D	2700K - 5700K Dynamic White	15 (22° UGR<16)
BB 84088				30 (38° UGR<16)
WH 84089	HC			60 (52° UGR<19)
BB 84090	HC			

Electronics: **CM** (pag 85)

Warp_R | arrayLED | 700 mA | 25 W DC






		Cct	Im S - Im D	Opt
CRI 90				
WH 90790		M	3967 - 2790	15 (21° UGR<16)
BB 90791		W	4134 - 2944	30 (34°)
WH 90794	HC	N	4192 - 2908	60 (39°)
BB 90795	HC			

Electronics: **T2** (pag 85)

Warp_R | Dynamic White | powerLED | 700 mA | 15 W DC (x channel)






		Cct		Opt
CRI 90				
WH 84091		D	2700K - 5700K Dynamic White	15 (21° UGR<16)
BB 84092				30 (34°)
WH 84093	HC			60 (39°)
BB 84094	HC			

Electronics: **CN** (pag 85)

Warp_R PRO | arrayLED | 300 mA | 11 W DC






	Cct	Im S - Im D	Opt
CRI 90			
WH 83766	M	1487 - 385	15 (20° UGR<11)
BB 83767	W	1578 - 401	30 (30° UGR<16)
	N	1660 - 431	60 (40° UGR<19)

Electronics: **L1** (pag 85)

Warp_R PRO | arrayLED | 400 mA | 15 W DC






	Cct	Im S - Im D	Opt
CRI 90			
WH 83770	M	2214 - 842	15 (23° UGR<11)
BB 83771	W	2318 - 901	30 (32° UGR<11)
	N	2411 - 970	60 (48° UGR<16)

Electronics: **P2** (pag 85)

Warp_R PRO | arrayLED | 700 mA | 25 W DC






	Cct	Im S - Im D	Opt
CRI 90			
WH 83774	M	3967 - 1579	15 (22° UGR<11)
BB 83775	W	4134 - 1699	30 (29° UGR<11)
	N	4192 - 1817	

Electronics: **T2** (pag 85)

Warp_RY | V2 | powerLED | 630 mA 2 W DC | 1000 mA 3 W DC






		Fin		Cct	Im S - Im D 2 W	Im S - Im D 3 W	Opt	
CRI 90								
C01043		**WH**		**M**	199 - 95	358 - 139	**FL**	(20°÷29°)
C01044	HC	**BB**		**W**	212 - 101	402 - 152	**ML**	(30°÷39°)
				N	237 - 113	417 - 158	**MW**	(40°÷49°)

Electronics: 2W **C1** - 3W **FQ** (pag 85)

Warp_RY | powerLED | 350 mA | 4 W DC






		Cct	Im S - Im D	Opt	
CRI 90					
WH 90830		**M**	389 - 218	**15**	(10°÷19°)
BB 90831		**W**	416 - 233	**30**	(30°÷39°)
WH 90834	HC	**N**	449 - 251	**60**	(50°÷70°)
BB 90835	HC				

Electronics: **D1** (pag 85)

Warp_RY | powerLED | 800 mA | 10 W DC






		Cct	Im S - Im D	Opt	
CRI 90					
WH 90846		**M**	960 - 673	**15**	(10°÷19°)
BB 90847		**W**	1034 - 725	**30**	(30°÷39°)
WH 90850	HC	**N**	1108 - 777	**60**	(50°÷70°)
BB 90851	HC				

Electronics: **K1** (pag 85)

Warp_RY | arrayLED | 400 mA | 15 W DC






		Cct	Im S - Im D	Opt	
CRI 90					
WH 90862		**M**	2214 - 1420	**15**	(10°÷19°)
BB 90863		**W**	2318 - 1487	**30**	(30°÷39°)
WH 90866	HC	**N**	2411 - 1547	**60**	(50°÷70°)
BB 90867	HC				

Electronics: **P2** (pag 85)

Warp_RJ | powerLED | 700 mA | 8 W DC






		Cct	Im S - Im D	Opt	
CRI 90					
WH 81258		**M**	689 - 417	**15**	(15°)
BB 81259		**W**	738 - 446	**30**	(31°)
		N	796 - 482	**60**	(60°)

Electronics: **J1** (pag 85)

Warp_RJ | Dynamic White | powerLED | 700 mA | 4 W DC (x channel)






		Cct		Opt	
CRI 90					
WH 84107		**D**	2700K - 5700K Dynamic White	**15**	(15°)
BB 84108				**30**	(31°)
				60	(60°)

Electronics: **CL** (pag 85)

Warp_RJ | arrayLED | 400 mA | 15 W DC






	Cct	lm S - lm D	Opt
CRI 90			
WH **81262**	**M**	2214 - 1497	**15** (23°)
BB **81263**	**W**	2318 - 1567	**30** (36°)
	N	2411 - 1630	**60** (56°)

Electronics: **P2** (pag 85)

Warp_RJ | Dynamic White | powerLED | 700 mA | 8 W DC (x channel)






	Cct		Opt
CRI 90			
WH **84109**	**D**	2700K - 5700K Dynamic White	**15** (23°)
BB **84110**			**30** (36°)
			60 (56°)

Electronics: **CM** (pag 85)

Warp_Q | V2 | powerLED | 630 mA 2 W DC | 1000 mA 3 W DC






		Fin	Cct	lm S - lm D 2 W	lm S - lm D 3 W	Opt
CRI 90						
C01241		WH	**M**	199 - 96	358 - 149	**FL** (20°÷29°)
C01242	HC	BB	**W**	212 - 102	402 - 163	**ML** (30°÷39°)
			N	237 - 114	417 - 169	**MW** (40°÷49°)

Electronics: 2W **C1** - 3W **FQ** (pag 85)

Warp_Q | powerLED | 630 mA | 2 W DC






	Fin	Cct	lm S - lm D	Opt
CRI 80				
C00120	WH	**M**	174 -126	**US** (5° UGR<16)
	BB	**W**	186 - 135	
		N	198 - 143	

Electronics: **C1** (pag 85)

Warp_Q | V2 | powerLED | 500 mA 4,5 W DC | 700 mA 6,3 W DC






		Fin	Cct	lm S - lm D 4,5 W	lm S - lm D 6,3 W	Opt
CRI 90						
C00054		WH	**M**	544 - 316	715 - 416	**SP** (19° UGR<19)
		BB	**W**	569 - 328	748 - 435	**FL** (28°)
			N	612 - 350	805 - 468	**WF** (50°)
CRI 90						
C00055	HC	WH	**M**	544 - 194	715 - 253	**SP** (17° UGR<11)
		BB	**W**	569 - 202	748 - 265	**FL** (24° UGR<19)
			N	612 - 218	805 - 285	**MW** (40° UGR<19)

Electronics: 4,5W **FM** - 6,3W **I1** (pag 85)

Warp_Q | powerLED | 800 mA | 10 W DC






		Cct	lm S - lm D	Opt
CRI 90				
WH **90770**		**M**	960 - 681	**15** (18° UGR<16)
BB **90771**		**W**	1034 - 734	**30** (29° UGR<16)
WH **90774**	HC	**N**	1108 - 785	**60** (46°)
BB **90775**	HC			

Electronics: **K1** (pag 85)

Warp_Q | Dynamic White | powerLED | 700 mA | 4 W DC (x channel)






		Cct		Opt
CRI 90				
WH **84095**		**D**	2700K - 5700K Dynamic White	**15** (18° UGR<16)
BB **84096**				**30** (29° UGR<16)
WH **84097**	HC			**60** (46°)
BB **84098**	HC			

Electronics: **CL** (pag 85)

Warp_Q | arrayLED | 400 mA | 15 W DC







		Cct	lm S - lm D	Opt
CRI 90				
WH **90784**		**M**	2214 - 1620	**15** (22° UGR<16)
BB **90785**		**W**	2318 - 1696	**30** (38° UGR<16)
WH **90788**	HC	**N**	2411 - 1765	**60** (53° UGR<19)
BB **90789**	HC			

Electronics: **P2** (pag 85)

Warp_Q | Dynamic White | powerLED | 700 mA | 8 W DC (x channel)






		Cct		Opt
CRI 90				
WH **84099**		**D**	2700K - 5700K Dynamic White	**15** (22° UGR<16)
BB **84100**				**30** (38° UGR<16)
WH **84101**	HC			**60** (53° UGR<19)
BB **84102**	HC			

Electronics: **CN** (pag 85)

Warp_Q | powerLED | 700 mA | 25 W DC






		Cct	lm S - lm D	Opt
CRI 90				
WH **90798**		**M**	3967 - 2908	**15** (22° UGR<16)
BB **90799**		**W**	4134 - 3030	**30** (38° UGR<16)
WH **90802**	HC	**N**	4192 - 3073	**60** (50° UGR<19)
BB **90803**	HC			

Electronics: **T2** (pag 85)

Warp_Q | Dynamic White | powerLED | 700 mA | 15 W DC (x channel)






		Cct		Opt
CRI 90				
WH **84103**		**D**	2700K - 5700K Dynamic White	**15** (22° UGR<16)
BB **84104**				**30** (38° UGR<16)
WH **84105**	HC			**60** (50° UGR<19)
BB **84106**	HC			

Electronics: **CM** (pag 85)

Warp_QY | V2 | powerLED | 630 mA 2 W DC | 1000 mA 3 W DC






C.C. IP44 IP65 NEW

	Fin		Cct	lm S - lm D 2 W	lm S - lm D 3 W	Opt	
CRI 90							
C01243	**WH**		**M**	199 - 103	358 - 186	**FL**	(20°÷29°)
C01244 HC	**BB**		**W**	212 - 110	402 - 209	**ML**	(30°÷39°)
			N	237 - 123	417 - 217	**MW**	(40°÷49°)

Electronics: 2W **C1** - 3W **FQ** (pag 85)

Warp_QY | powerLED | 350 mA | 4 W DC






C.C. IP44 IP65

		Cct	lm S - lm D	Opt	
CRI 90					
WH **90838**		**M**	389 - 233	**15**	(10°÷19°)
BB **90839**		**W**	416 - 249	**30**	(30°÷39°)
WH **90842**	HC	**N**	449 - 269	**60**	(50°÷70°)
BB **90843**	HC				

Electronics: **D1** (pag 85)

Warp_QY | powerLED | 800 mA | 10 W DC







C.C. IP44 IP65

		Cct	lm S - lm D	Opt	
CRI 90					
WH **90854**		**M**	960 - 674	**15**	(20°÷29°)
BB **90855**		**W**	1034 - 724	**30**	(30°÷39°)
WH **90858**	HC	**N**	1108 - 777	**60**	(40°÷49°)
BB **90859**	HC				

Electronics: **K1** (pag 85)

Warp_QY | arrayLED | 400 mA | 15 W DC





C.C. IP44 IP65

		Cct	lm S - lm D	Opt	
CRI 90					
WH **90870**		**M**	2214 - 1581	**15**	(20°÷29°)
BB **90871**		**W**	2318 - 1655	**30**	(30°÷39°)
WH **90874**	HC	**N**	2411 - 1721	**60**	(40°÷49°)
BB **90875**	HC				

Electronics: **P2** (pag 85)



Asymmetric version
The items of the Warp_RY and Warp_QY families are inclined at 25° and offer asymmetric emission, ideal for uniform light distribution on the lateral surfaces. The inclined shape of the lamp body allows the light source to be hidden from view, eliminating direct glare.

Finishes		Cct			Accessories
WH	White	**M**	2700	**N** 4000	HC Honeycomb
BB	Black	**W**	3000		



Electronics

C1

89147	99376	99105	99710	99713	+ driver 24V DC	
					99374 75W	99331 150W
ON/OFF 1 - 2 art. 138 x 22 x h 21 29	ON/OFF 3 - 6 art. 138 x 22 x h 21 29	ON/OFF 6 - 12 art. 103 x 58 x h 27 64	24V DC converter 0/1-10V 1 - 6 art. 138 x 22 x h 20 29	24V DC converter DALI 1 - 6 art. 138 x 22 x h 20 29	56	70

CL

83159	C-E500003	DMX	Driver CV
DALI DT8 4 - 8 art. 202 x 58 x h 30 66	Dimmer DMX 1 - 10 art. 107 x 96 x h 39	Controllers Pag 963	CV 48V Pag. 950-951

CM

83159	C-E500003	DMX	Driver CV
DALI DT8 2 - 3 art. 202 x 58 x h 30 66	Dimmer DMX 1 - 6 art. 107 x 96 x h 39	Controllers Pag 963	CV 48V Pag. 950-951

CN

83159	C-E500003	DMX	Driver CV
DALI DT8 1 - 2 art. 202 x 58 x h 30 66	Dimmer DMX 1 - 2 art. 107 x 96 x h 39	Controllers Pag 963	CV 48V Pag. 950-951

D1

89145	99375	C-E100010	C-E100011
ON/OFF 1 art. 138 x 22 x h 21 29	ON/OFF 2 - 3 art. 138 x 22 x h 21 29	0/1-10V 1 art. 138 x 22 x h 22 31	DALI/PUSH 1 art. 138 x 22 x h 22 31

FM

89146	99377	C-E100004	C-E100005	C-E100001
ON/OFF 1 art. 138 x 22 x h 21 29	ON/OFF 1 - 2 art. 138 x 22 x h 21 64	0/1-10V 1 art. 124 x 22 x h 22 31	DALI/PUSH 1 art. 124 x 22 x h 22 31	DALI/PUSH 1 - 2 art. 131 x 44 x h 30 54

FQ

C-E100046	C-E100047	C-E100033	C-E100034
ON/OFF 1 - 6 art. 130 x 38 x h 28 48	DALI 1 - 3 art. 140 x 36 x h 20 40	ON/OFF 4 - 12 art. 138 x 44 x h 23 50	DALI/PUSH 4 - 12 art. 138 x 44 x h 23 50

I1

99735	99147	99733	83323	C-E100016
ON/OFF 1 art. 134 x 37 x h 31 48	ON/OFF 2 - 3 art. 103 x 58 x h 27 64	0/1-10V 1 art. 134 x 37 x h 31 48	DALI/PUSH 1 art. 134 x 37 x h 31 48	DALI/PUSH 2 - 4 art. 131 x 44 x h 30 54

J1

99735	99147	99733	C-E100012	C-E100016
ON/OFF 1 art. 134 x 37 x h 31 48	ON/OFF 2 - 3 art. 103 x 58 x h 27 64	0/1-10V 1 art. 134 x 37 x h 31 48	DALI/PUSH 1 art. 134 x 37 x h 31 48	DALI/PUSH 2 - 3 art. 131 x 44 x h 30 54

K1

99735	99135	99733	C-E100013	99345
ON/OFF 1 art. 134 x 37 x h 31 48	ON/OFF 2 - 3 art. 103 x 58 x h 27 64	0/1-10V 1 art. 134 x 37 x h 31 48	DALI/PUSH 1 art. 124 x 22 x h 22 31	DALI/PSUH 1 - 3 art. 210 x 48 x h 25 56

L1

99734	99732	83322
ON/OFF 1 art. 149 x 37 x h 31 48	0/1-10V 1 art. 149 x 37 x h 31 48	DALI/PUSH 1 art. 149 x 37 x h 31 48

P2

99740	99739	C-E100032
ON/OFF 1 art. 134 x 37 x h 31 48	0/1-10V 1 art. 134 x 37 x h 31 48	DALI/PUSH 1 art. 149 x 37 x h 31 48

T2

99112	83066	C-E100031
ON/OFF 1 art. 103 x 58 x h 27 64	0/1-10V, DALI/PUSH 1 art. 124 x 79 x h 22 84	DALI/PUSH 1 art. 131 x 44 x h 30 54

QUANTUM


Aluminium body.



HC IP44 IP65


The performance of Quantum luminaires is combined with soft and refined shapes. This organic design was recognised the prestigious RedDot Award. The versions with HC set-up include the Honeycomb filter, which allows the source to be shielded, offering an almost complete solution to glare.

reddot award 2015
winner





ADJUSTABLE

The Quantum_RJ luminaires allow personalised control of the direction of the light beam due to the possibility of orienting the optical unit by 35° on the vertical axis.



Quantum_R | V2 | powerLED | 630 mA 2 W DC | 1000 mA 3 W DC







	Fin	Cct	lm S - lm D 2 W	lm S - lm D 3 W	Opt
CRI 90					
C01038	**WH**	**M**	213 - 66	358 - 119	**SP** (19° UGR<19)
	BB	**W**	213 - 75	402 - 130	**FL** (25°)
	AU	**N**	237 - 97	417 - 135	**MW** (45°)

Electronics: 2W **C1** - 3W **FQ** (pag 88)

Quantum_R | powerLED | 630 mA | 2 W DC







	Fin	Cct	lm S - lm D	Opt
CRI 80				
C00117	**WH**	**M**	174 - 115	**US** (5° UGR<19)
	BB	**W**	186 - 123	
	AU	**N**	198 - 131	

Electronics: **C1** (pag 88)

Quantum_R | V2 | powerLED | 500 mA 4,5 W DC | 700 mA 6,3 W DC






		Fin	Cct	lm S - lm D 4,5 W	lm S - lm D 6,3 W	Opt
CRI 90						
C00048		**WH**	**M**	544 - 289	715 - 381	**SP** (19° UGR<19)
		BB	**W**	569 - 302	748 - 398	**FL** (26°)
		AU	**N**	612 - 326	805 - 429	**WF** (52°)
CRI 90						
C00049	HC	**WH**	**M**	544 - 181	715 - 239	**SP** (17° UGR<11)
		BB	**W**	569 - 190	748 - 250	**FL** (25° UGR<19)
		AU	**N**	612 - 204	805 - 269	**MW** (40°)

Electronics: 4,5W **FM** - 6,3W **I1** (pag 88)

Quantum_R | powerLED | 800 mA | 10 W DC







		Cct	lm S - lm D	Opt
CRI 90				
WH **80029**		**M**	960 - 657	**15** (20° UGR<19)
BB **80030**		**W**	1034 - 709	**30** (25°)
AU **82877**		**N**	1108 - 762	**45** (47°)
WH **80033**	HC			
BB **80034**	HC			
AU **82878**	HC			

Electronics: **K1** (pag 88)

Quantum_R | arrayLED | 400 mA | 15 W DC






		Cct	lm S - lm D	Opt
CRI 90				
WH **80035**		**M**	2214 - 1242	**15** (20°)
BB **80036**		**W**	2318 - 1300	**30** (30°)
AU **82881**		**N**	2411 - 1353	**45** (40°)
WH **80039**	HC			
BB **80040**	HC			
AU **82882**	HC			

Electronics: **P2** (pag 88)

Quantum_RJ | V2 | powerLED | 630 mA 2 W DC | 1000 mA 3 W DC






	Fin	Cct	Im S - Im D 2 W	Im S - Im D 3 W	Opt
CRI 90					
C01039	**WH**	**M**	196 - 109	358 - 120	**FL** (20°÷29°)
C01040 HC	**BB**	**W**	210 - 116	402 - 131	**ML** (30°÷39°)
		N	223 - 125	417 - 137	**MW** (40°÷49°)

Electronics: 2W **C1** - 3W **FQ** (pag 88)

Quantum_RJ | powerLED | 630 mA | 2 W DC






	Fin	Cct	Im S - Im D	Opt
CRI 80				
C00118	**WH**	**M**	174 - 109	**US** (5°)
	BB	**W**	186 - 116	
		N	198 - 125	

Electronics: **C1** (pag 88)

Quantum_RJ | V2 | powerLED | 500 mA 4,5 W DC | 700 mA 6,3 W DC






	Fin	Cct	Im S - Im D 4,5 W	Im S - Im D 6,3 W	Opt
CRI 90					
C00050	**WH**	**M**	544 - 289	715 - 285	**SP** (19°)
C00051 HC	**BB**	**W**	569 - 302	748 - 298	**FL** (26°)
		N	612 - 326	805 - 321	**WF** (50°)

Electronics: 4,5W **FM** - 6,3W **I1** (pag 88)

Quantum_RJ | powerLED | 800 mA | 10 W DC





	Cct	Im S - Im D	Opt
CRI 90			
WH **80065**	**M**	960 - 668	**15** (20°)
BB **80066**	**W**	1034 - 718	**30** (30°)
WH **80069** HC	**N**	1108 - 770	**45** (40°)
BB **80070** HC			

Electronics: **K1** (pag 88)

Electronics

C1

89147	99376	99105	99710	99713	+ driver 24V DC
ON/OFF	ON/OFF	ON/OFF	24V DC converter	24V DC converter	99374 75W / 99331 150W
1 - 2 art.	3 - 6 art.	6 - 12 art.	0/1-10V 1 - 6 art.	DALI 1 - 6 art.	
138 x 22 x h 21	138 x 22 x h 21	103 x 58 x h 27	138 x 22 x h 20	138 x 22 x h 20	
29	29	64	29	29	56 / 70

FM

89146	99377	C-E100004	C-E100005	C-E100001
ON/OFF	ON/OFF	0/1-10V	DALI/PUSH	DALI/PUSH
1 art.	1 - 2 art.	1 art.	1 art.	1 - 2 art.
138 x 22 x h 21	138 x 22 x h 21	124 x 22 x h 22	124 x 22 x h 22	131 x 44 x h 30
29	64	31	31	54

FQ

C-E100046	C-E100047	C-E100033	C-E100034
ON/OFF	DALI	ON/OFF	DALI/PUSH
1 - 6 art.	1 - 3 art.	4 - 12 art.	4 - 12 art.
130 x 38 x h 28	140 x 36 x h 20	138 x 44 x h 23	138 x 44 x h 23
48	40	50	50

I1

99735	99147	99733	83323	C-E100016
ON/OFF	ON/OFF	0/1-10V	DALI/PUSH	DALI/PUSH
1 art.	2 - 3 art.	1 art.	1 art.	2 - 4 art.
134 x 37 x h 31	103 x 58 x h 27	134 x 37 x h 31	134 x 37 x h 31	131 x 44 x h 30
48	64	48	48	54

K1

99735	99135	99733	C-E100013	99345
ON/OFF	ON/OFF	0/1-10V	DALI/PUSH	DALI/PSUH
1 art.	2 - 3 art.	1 art.	1 art.	1 - 3 art.
134 x 37 x h 31	103 x 58 x h 27	134 x 37 x h 31	124 x 22 x h 22	210 x 48 x h 25
48	64	48	31	56

P2

99740	99739	C-E100032
ON/OFF	0/1-10V	DALI/PUSH
1 art.	1 art.	1 art.
134 x 37 x h 31	134 x 37 x h 31	149 x 37 x h 31
48	48	48

SOFITEL BARCELONA SKIPPER
Barcelona (Spain)


Lighting Designer:
Fantastico Lighting Partners

Photography:
Jordi Anguera



EPITAX

Aluminium body




Trimless
The downlights of the Epitax family can be flush-mounted or extracted in a semi-recessed position even after installation has already been performed: this possibility greatly simplifies the extraction operation and makes Epitax a versatile and easy-to-configure product. System not available for the Epitax_J swivel versions.




Retracted source
The particularly recessed light source enables a defined emission, reducing the incidence of the secondary light beam and significantly reducing glare.

Tilting version
The Epitax_J versions are characterised by mobility of 360° on the horizontal axis and an inclination of 30° on the vertical axis.



Epitax | V2 | powerLED | 630 mA 2 W DC | 1000 mA 3 W DC






	Fin	Cct	Im S - Im D 2 W	Im S - Im D 3 W	Opt
CRI 90					
C01245	**WH**	**M**	199 - 121	358 - 179	**FL** (22°)
	BB	**W**	212 - 129	402 - 195	**ML** (30°)
	AU	**N**	237 - 144	417 - 203	**WF** (52°)

Electronics: 2W **C1** - 3W **FQ** (pag 93) | Recessed casing (pag 93)

Epitax | powerLED | 630 mA | 2 W DC






	Fin	Cct	Im S - Im D	Opt
CRI 80				
C00121	**WH**	**M**	174 - 117	**US** (5° UGR<19)
	BB	**W**	186 - 126	
	AU	**N**	198 - 134	

Electronics: **C1** (pag 93) | Recessed casing: (pag 93)

Epitax | V2 | powerLED | 500 mA 4,5 W DC | 700 mA 6,3 W DC






	Fin	Cct	Im S - Im D 4,5 W	Im S - Im D 6,3 W	Opt
CRI 90					
C00058	**WH**	**M**	544 - 302	715 - 397	**SP** (19° UGR<19)
	BB	**W**	569 - 316	748 - 416	**FL** (28°)
	AU	**N**	612 - 339	805 - 447	**WF** (51°)
CRI 90					
C00059 HC	**WH**	**M**	544 - 184	715 - 243	**SP** (17° UGR<11)
	BB	**W**	569 - 193	748 - 254	**FL** (24° UGR<19)
	AU	**N**	612 - 208	805 - 274	**MW** (40° UGR<19)

Electronics: 4,5W **FM** - 6,3W **I1** (pag 93) | Recessed casing (pag 93)

Epitax | powerLED | 800 mA | 10 W DC






	Cct	Im S - Im D	Opt
CRI 90			
WH **80595**	**M**	960 - 633	**15** (17° UGR<16)
BB **80596**	**W**	1034 - 681	**30** (28° UGR<19)
AU **80751**	**N**	1108 - 732	**45** (42°)

Electronics: **K1** (pag 93) | Recessed casing (pag 93)

Epitax | arrayLED | 400 mA | 15 W DC






	Cct	Im S - Im D	Opt
CRI 90			
WH **80603**	**M**	2214 - 1461	**15** (22° UGR<16)
BB **80604**	**W**	2318 - 1530	**30** (37° UGR<16)
AU **80753**	**N**	2411 - 1591	**60** (50° UGR<19)

Electronics: **P2** (pag 93) | Recessed casing (pag 93)

The Epitax models must be completed with the appropriate plasterboard outer casing.

Epitax_J | powerLED | 700 mA | 8 W DC






	Cct	lm S - lm D	Opt
CRI 90			
WH **80644**	**M**	689 - 411	**15** (15°)
BB **80645**	**W**	738 - 440	**30** (34°)
AU **80758**	**N**	796 - 475	**60** (64°)

Electronics: **J1** (pag 93) | Recessed casing (pag 93)

Epitax_J | powerLED | 400 mA | 15 W DC





	Cct	lm S - lm D	Opt
CRI 90			
WH **80648**	**M**	2214 - 1439	**15** (23°)
BB **80649**	**W**	2318 - 1507	**30** (36°)
AU **80760**	**N**	2411 - 1567	**60** (55°)

Electronics: **P2** (pag 93) | Recessed casing (pag 93)

The Epitax models must be completed with the appropriate plasterboard outer casing.



PRIVATE VILLA
Castelfranco Veneto - Treviso (Italy)

Project: Studio Architetti Associati Giampietro e Stefano Cinel

Electronics

C1

89147	99376	99105	99710	99713	+ driver 24V DC	
ON/OFF	ON/OFF	ON/OFF	24V DC converter	24V DC converter	99374 75W	99331 150W
1 - 2 art.	3 - 6 art.	6 - 12 art.	0/1-10V 1 - 6 art.	DALI 1 - 6 art.		
138 x 22 x h 21	138 x 22 x h 21	103 x 58 x h 27	138 x 22 x h 20	138 x 22 x h 20		
29	29	64	29	29	56	70

FM

89146	99377	C-E100004	C-E100005	C-E100001
ON/OFF	ON/OFF	0/1-10V	DALI/PUSH	DALI/PUSH
1 art.	1 - 2 art.	1 art.	1 art.	1 - 2 art.
138 x 22 x h 21	138 x 22 x h 21	124 x 22 x h 22	124 x 22 x h 22	131 x 44 x h 30
29	64	31	31	54

FQ

C-E100046	C-E100047	C-E100033	C-E100034
ON/OFF	DALI	ON/OFF	DALI/PUSH
1 - 6 art.	1 - 3 art.	4 - 12 art.	4 - 12 art.
130 x 38 x h 28	140 x 36 x h 20	138 x 44 x h 23	138 x 44 x h 23
48	40	50	50

I1

99735	99147	99733	83323	C-E100016
ON/OFF	ON/OFF	0/1-10V	DALI/PUSH	DALI/PUSH
1 art.	2 - 3 art.	1 art.	1 art.	2 - 4 art.
134 x 37 x h 31	103 x 58 x h 27	134 x 37 x h 31	134 x 37 x h 31	131 x 44 x h 30
48	64	48	48	54

J1

99735	99147	99733	C-E100012	C-E100016
ON/OFF	ON/OFF	0/1-10V	DALI/PUSH	DALI/PUSH
1 art.	2 - 3 art.	1 art.	1 art.	2 - 3 art.
134 x 37 x h 31	103 x 58 x h 27	134 x 37 x h 31	134 x 37 x h 31	131 x 44 x h 30
48	64	48	48	54


K1

99735	99135	99733	C-E100013	99345
ON/OFF	ON/OFF	0/1-10V	DALI/PUSH	DALI/PSUH
1 art.	2 - 3 art.	1 art.	1 art.	1 - 3 art.
134 x 37 x h 31	103 x 58 x h 27	134 x 37 x h 31	124 x 22 x h 22	210 x 48 x h 25
48	64	48	31	56

P2


99740	99739	C-E100032
ON/OFF	0/1-10V	DALI/PUSH
1 art.	1 art.	1 art.
134 x 37 x h 31	134 x 37 x h 31	149 x 37 x h 31
48	48	48

Recessed casing




PLC **C-C100005** Recessed casing for flush installation

suitable for: Epitax 2W Ø29




PLC **C-C100006** Recessed casing for flush installation

suitable for: Epitax 2W Ø34, Epitax 4,5/6,3W




ABS **98499** Recessed casing for flush installation

suitable for: Epitax 10W - Epitax_J 8W




ABS **98500** Recessed casing for flush installation

suitable for: Epitax 15W - Epitax_J 15W




WH **98527**
BB **98528**
AU **98529**
Recessed casing with flange

suitable for: Epitax 2W Ø29




WH **98530**
BB **98531**
AU **98532**
Recessed casing with flange

suitable for: Epitax 2W Ø34, Epitax 4,5/6,3W



WH **98533**
BB **98534**
AU **98535**
Recessed casing with flange

suitable for: Epitax 10W - Epitax_J 8W



WH **98536**
BB **98537**
AU **98538**
Recessed casing with flange

suitable for: Epitax 15W - Epitax_J 15W



Warm & chic gold (AU)



Black RAL9005 (BB)



White RAL9003 (WH)

Finishes

WH White
BB Black
AU Gold
PLC Polycarbonate

Cct

M 2700 **N** 4000
W 3000

LORO

Aluminium body.



	_R	_RJ	_Q	_QJ
W	8-12,5-15-18-25	8-12,5-15-18-25	8-12,5-15-18-25	8-12,5-15-18-25
mm	**Ø 76-105**	**Ø 100-139**	**☐ 70-100**	**☐ 100-139**
Cct	2700-3000-4000-DW	2700-3000-4000-DW	2700-3000-4000-DW	2700-3000-4000-DW
Opt	**Spot-Flood**	**Spot-Flood**	**Spot-Flood**	**Spot-Flood**
	M.W.Flood-W.Flood	**M.W.Flood-W.Flood**	**M.W.Flood-W.Flood**	**M.W.Flood-W.Flood**
Elec.	On/Off	On/Off	On/Off	On/Off
	0/1-10V	0/1-10V	0/1-10V	0/1-10V
	DALI	DALI	DALI	DALI
Col.	WH BB GG	WH BB GG	WH BB GG	WH BB GG

Minimal size
Using a curved rear dissipator reduces the recess depth and allows the Loro range of products (except for the 25 W / 15 W DW) versions to adapt to the installation on dropped ceilings with height lesser than 10 cm.


70 mm




UGR<19
The optics group, consisting of a chrome-plated reflector and a transparent polycarbonate diffuser offers an optimal reflectance control and a UGR index below 19, i.e. the threshold value for the correct lighting of offices and environments with video terminals (UNI-EN 12464-1 standard).

IP65 O.C.
The optics gr group offers an IP65 front index of protection, i.e. full protection against entry of dust and extremely fine particles, as well as sprays and water jets.
WARNING the value exclusively refers to the optics section and NOT the lamp body (IP44 index of protection).

IP44
IP65




Aesthetic filter (33)
The new type of optics filter, designed specifically to hide from view the LED positioned inside the product, it allows an aesthetic upgrade and a cleaner style of the downlight, maintaining the same lighting performance.




Product without filter

Product with filter



Loro_R | arrayLED | 220 mA 8 W DC | 350 mA 12,5 W DC






		Cct	lm S - lm D 8 W	lm S - lm D 12,5 W	Opt
CRI 90					
WH **91749**		**M**	1098 - 793	1644 - 1394	**15** (17° UGR<19)
BB **91750**		**W**	1139 - 822	1705 - 1446	**30** (23° UGR<19)
GG **91751**		**N**	1159 - 837	1736 - 1472	**60** (46° UGR<19)
WH **80799**	HC				**33*** (40°)
BB **80800**	HC				
GG **80801**	HC				

Electronics: 8W **G1** - 12,5W **O1** (pag 99)

Loro_R | Dynamic White | powerLED | 700 mA | 8 W DC (x channel)






		Cct		Opt
CRI 90				
WH **84111**		**D**	2700K - 5700K Dynamic White	**15** (17° UGR<19)
BB **84112**				**30** (23° UGR<19)
GG **84113**				**60** (46° UGR<19)
WH **84115**	HC			
BB **84116**	HC			
GG **84117**	HC			

Electronics: **CM** (pag 99)

Loro_R | arrayLED | 500 mA 18 W DC | 700 mA 25 W DC






		Cct	lm S - lm D 18 W	lm S - lm D 25 W	Opt
CRI 90					
WH **80672**		**M**	2964 - 2252	3967 - 2991	**15** (16° UGR<19)
BB **80673**		**W**	3089 - 2347	4134 - 3117	**30** (34° UGR<19)
GG **80704**		**N**	3132 - 2380	4192 - 3161	**60** (56°)
WH **80807**	HC				**33*** (52°)
BB **80808**	HC				
GG **80809**	HC				

Electronics: 18W **Q2** - 25W **T2** (pag 99)

Loro_R | Dynamic White | powerLED | 700 mA | 15 W DC (x channel)





		Cct		Opt
CRI 90				
WH **84119**		**D**	2700K - 5700K Dynamic White	**15** (16° UGR<19)
BB **84120**				**30** (34° UGR<19)
GG **84121**				**60** (56°)
WH **84123**	HC			
BB **84124**	HC			
GG **84125**	HC			

Electronics: **CN** (pag 99)

*** Aesthetic filter**



Loro_R fitted with aesthetic filter (33), available only for codes without Honeycomb and Dynamic White

Finishes

WH White GG Grey
BB Black

Cct


M 2700 **N** 4000
W 3000 **D** 2700 - 5700

Accessories

HC Honeycomb

Loro_RJ | arrayLED | 220 mA 8 W DC | 350 mA 12,5 W DC






		Cct	lm S - lm D	lm S - lm D	Opt
CRI 90			8 W	12,5 W	
WH **93450**		**M**	1098 - 793	1644 - 1394	**15** (18°)
BB **93451**		**W**	1139 - 822	1705 - 1446	**30** (23°)
GG **93452**		**N**	1159 - 837	1736 - 1472	**60** (47°)
WH **80863**	HC				**33*** (40°)
BB **80864**	HC				
GG **80865**	HC				

Electronics: 8W **G1** - 12,5W **O1** (pag 99)

Loro_RJ | Dynamic White | powerLED | 700 mA | 8 W DC (x channel)






	Cct		Opt
CRI 90			
WH **84143**	**D**	2700K - 5700K Dynamic White	**15** (18°)
BB **84144**			**30** (23°)
GG **84145**			**60** (47°)

Electronics: **CM** (pag 99)

Loro_RJ | arrayLED | 500 mA 18W DC | 700 mA 25 W DC






		Cct	lm S - lm D	lm S - lm D	Opt
CRI 90			18 W	25 W	
WH **80370**		**M**	2964 - 2252	3967 - 2991	**15** (15°)
BB **80371**		**W**	3089 - 2347	4134 - 3117	**30** (34°)
GG **80372**		**N**	3132 - 2380	4192 - 3161	**60** (56°)
WH **80871**	HC				**33*** (52°)
BB **80872**	HC				
GG **80873**	HC				

Electronics: 18W **Q2** - 25W **T2** (pag 99)

Loro_RJ | Dynamic White | powerLED | 700 mA | 15 W DC (x channel)





	Cct		Opt
CRI 90			
WH **84147**	**D**	2700K - 5700K Dynamic White	**15** (15°)
BB **84148**			**30** (34°)
GG **84149**			**60** (56°)

Electronics: **CN** (pag 99)


*** Aesthetic filter**



Loro_RJ fitted with aesthetic filter (33), available only for codes without Honeycomb and Dynamic White

Loro_Q | arrayLED | 220 mA 8 W DC | 350 mA 12,5 W DC






		Cct	Im S - Im D	Im S - Im D	Opt
CRI 90			8 W	12,5 W	
WH **91753**		**M**	1098 - 793	1644 - 1394	**15** (17° UGR<16)
BB **91754**		**W**	1139 - 822	1705 - 1446	**30** (23° UGR<19)
GG **91755**		**N**	1159 - 837	1736 - 1472	**60** (46° UGR<19)
WH **80831**	HC				**33***(40°)
BB **80832**	HC				
GG **80833**	HC				

Electronics: 8W **G1** - 12,5W **O1** (pag 99)

Loro_Q | Dynamic White | powerLED | 700 mA | 8 W DC (x channel)






		Cct		Opt
CRI 90				
WH **84127**		**D**	2700K - 5700K Dynamic White	**15** (17° UGR<16)
BB **84128**				**30** (23° UGR<19)
GG **84129**				**60** (46° UGR<19)
WH **84131**	HC			
BB **84132**	HC			
GG **84133**	HC			

Electronics: **CM** (pag 99)

Loro_Q | arrayLED | 500 mA 18 W DC | 700 mA 25 W DC






		Cct	Im S - Im D	Im S - Im D	Opt
CRI 90			18 W	25 W	
WH **80660**		**M**	2964 - 2252	3967 - 2991	**15** (16° UGR<19)
BB **80661**		**W**	3089 - 2347	4134 - 3117	**30** (34° UGR<19)
GG **80690**		**N**	3132 - 2380	4192 - 3161	**60** (56° UGR<19)
WH **80839**	HC				**33***(52°)
BB **80840**	HC				
GG **80841**	HC				

Electronics: 18W **Q2** - 25W **T2** (pag 99)

Loro_Q | Dynamic White | powerLED | 700 mA | 15 W DC (x channel)





		Cct		Opt
CRI 90				
WH **84135**		**D**	2700K - 5700K Dynamic White	**15** (16° UGR<19)
BB **84136**				**30** (34° UGR<19)
GG **84137**				**60** (56° UGR<19)
WH **84139**	HC			
BB **84140**	HC			
GG **84141**	HC			

Electronics: **CN** (pag 99)

*** Aesthetic filter**



Loro_Q fitted with aesthetic filter (33), available only for codes without Honeycomb and Dynamic White

Finishes

WH White GG Grey
BB Black

Cct


M 2700 **N** 4000
W 3000 **D** 2700 - 5700

Accessories

HC Honeycomb

Loro_QJ | arrayLED | 220 mA 8 W DC | 350 mA 12,5 W DC






		Cct	lm S - lm D	lm S - lm D	Opt
CRI 90			8 W	12,5 W	
WH **80354**		**M**	1098 - 793	1644 - 1394	**15** (18°)
BB **80355**		**W**	1139 - 822	1705 - 1446	**30** (23°)
GG **80356**		**N**	1159 - 837	1736 - 1472	**60** (47°)
WH **80895**	HC				**33***(40°)
BB **80896**	HC				
GG **80897**	HC				

Electronics: 8W **G1** - 12,5W **O1** (pag 99)

Loro_QJ | Dynamic White | powerLED | 700 mA | 8 W DC (x channel)






	Cct		Opt
CRI 90			
WH **84151**	**D**	2700K - 5700K Dynamic White	**15** (18°)
BB **84152**			**30** (23°)
GG **84153**			**60** (47°)

Electronics: **CM** (pag 99)

Loro_QJ | arrayLED | 500 mA 18W DC | 700 mA 25 W DC






		Cct	lm S - lm D	lm S - lm D	Opt
CRI 90			18 W	25 W	
WH **80362**		**M**	2964 - 2252	3967 - 2991	**15** (15°)
BB **80363**		**W**	3089 - 2347	4134 - 3117	**30** (34°)
GG **80364**		**N**	3132 - 2380	4192 - 3161	**60** (56°)
WH **80903**	HC				**33***(52°)
BB **80904**	HC				
GG **80905**	HC				

Electronics: 18W **Q2** - 25W **T2** (pag 99)

Loro_QJ | Dynamic White | powerLED | 700 mA | 15 W DC (x channel)





	Cct		Opt
CRI 90			
WH **84155**	**D**	2700K - 5700K Dynamic White	**15** (15°)
BB **84156**			**30** (34°)
GG **84157**			**60** (56°)

Electronics: **CN** (pag 99)

*** Aesthetic filter**



Loro_Q fitted with aesthetic filter (33), available only for codes without Honeycomb and Dynamic White

Electronics

CM

83159
DALI DT8
2 - 3 art.
202 x 58 x h 30
66

C-E500003
Dimmer DMX
1 - 6 art.
107 x 96 x h 39

DMX
Controllers
Pag 963

Driver CV
CV 48V
Pag. 950-951

CN

83159
DALI DT8
1 - 2 art.
202 x 58 x h 30
66

C-E500003
Dimmer DMX
1 - 2 art.
107 x 96 x h 39

DMX
Controllers
Pag 963

Driver CV
CV 48V
Pag. 950-951

G1

99198
ON/OFF
1 art.
149 x 37 x h 31
48

99732
0/1-10V
1 art.
149 x 37 x h 31
48

83322
DALI/PUSH
1 art.
149 x 37 x h 31
48

O1

99375
ON/OFF
1 art.
138 x 22 x h 21
29

99115
0/1-10V
1 art.
210 x 48 x h 25
56

83322
DALI/PUSH
1 art.
149 x 37 x h 31
48

Q2

83219
ON/OFF
1 art.
103 x 58 x h 27
64

99262
0/1-10V
1 art.
210 x 49 x h 25
56

C-E100030
DALI/PUSH
1 art.
131 x 44 x h 30
54

T2

99112
ON/OFF
1 art.
103 x 58 x h 27
64

83066
0/1-10V, DALI/PUSH
1 art.
124 x 79 x h 22
84

C-E100031
DALI/PUSH
1 art.
131 x 44 x h 30
54



White RAL9003 (WH)



Black RAL9005 (BB)




Grey RAL9006 (GG)



RADA

Aluminium body.
Recuperator in Optical white painted aluminium.






Visual comfort
The perimeter LED circuit, placed in the inner part of the circular frame and concealed from view, directs the light upwards; this is collected by the dome reflector made of optical white painted aluminium, which redistributes it in the environment. The final effect corresponds to an indirect and diffused, very soft lighting. The total absence of glare allows direct observation of the product without any discomfort for the eyes.


Oblique diffusion


Due to the specifically studied internal reflections, Rada offers a diffusion almost oblique to the ceiling, distributing the light in the entire surrounding environment.





Rada_R | topLED | 220 mA | 8 W DC






C.C. IK05 IP40

	Fin	Cct	lm S - lm D	Opt
CRI 90				
C00197	**WH**	**M**	1093 - 499	**DI** (Diffused)
		W	1145 - 522	
		N	1217 - 555	

Electronics: **G1** (pag 103) | Accessories (pag 103)

Rada_R | topLED | 350 mA | 12,5 W DC






C.C. IK05 IP40

	Fin	Cct	lm S - lm D	Opt
CRI 90				
C00198	**WH**	**M**	1746 - 1048	**DI** (Diffused)
		W	1828 - 1097	
		N	1943 - 1166	

Electronics: **O1** (pag 103) | Accessories (pag 103)

Rada_R | topLED | 500 mA | 18 W DC






C.C. IK05 IP40

	Fin	Cct	lm S - lm D	Opt
CRI 90				
C00200	**WH**	**M**	2519 - 1147	**DI** (Diffused)
		W	2638 - 1201	
		N	2803 - 1276	

Electronics: **Q1** (pag 103) | Accessories (pag 103)

Rada_R | topLED | 700 mA | 25 W DC






C.C. IK05 IP40

	Fin	Cct	lm S - lm D	Opt
CRI 90				
C00201	**WH**	**M**	3515 - 2433	**DI** (Diffused)
		W	3681 - 2548	
		N	3913 - 2709	

Electronics: **T1** (pag 103) | Accessories (pag 103)

Rada_R | topLED | 1800 mA | 65 W DC






C.C. IK05 IP40

	Fin	Cct	lm S - lm D	Opt
CRI 90				
C00202	**WH**	**M**	8900 - 6180	**DI** (Diffused)
		W	9320 - 6471	
		N	9905 - 6879	

Electronics: **FA** (pag 103) | Accessories (pag 103)

Rada_R | topLED | 2260 mA | 82 W DC





C.C. IK05 IP40

	Fin	Cct	lm S - lm D	Opt
CRI 90				
C00204	**WH**	**M**	11318 - 7679	**DI** (Diffused)
		W	11853 - 8041	
		N	12597 - 8547	

Electronics: **FB** (pag 103) | Accessories (pag 103)

Electronics

FA

99717
ON/OFF
1 art.
208 x 89 x h 40
98

99726
0/1-10V
1 art.
180 x 63 x h 36
79

99727
DALI
1 art.
171 x 68 x h 39
79

G1

99198
ON/OFF
1 art.
149 x 37 x h 31
48

99732
0/1-10V
1 art.
149 x 37 x h 31
48

83322
DALI/PUSH
1 art.
149 x 37 x h 31
48

Q1

99106
ON/OFF
1 art.
103 x 58 x h 27
64

99115
0/1-10V
1 art.
210 x 48 x h 28
56

C-E100001
DALI/PUSH
1 art.
131 x 44 x h 30
54

FB

99718
ON/OFF
1 art.
208 x 89 x h 40
98

99728
0/1-10V
1 art.
199 x 63 x h 36
79

99729
DALI
1 art.
220 x 68 x h 39
79

O1

99375
ON/OFF
1 art.
138 x 22 x h 21
29

99115
0/1-10V
1 art.
210 x 48 x h 25
56

83322
DALI/PUSH
1 art.
149 x 37 x h 31
48

T1

99147
ON/OFF
1 art.
103 x 58 x h 27
64

83008
0/1-10V, DALI/PUSH
1 art.
124 x 79 x h 22
84

C-E100016
DALI/PUSH
1 art.
131 x 44 x h 30
54

Accessories



WH **98436**

Easy-plug cable and connector
Length 300 mm

suitable for: Rada_R




CELL

Aluminium body. The Gypsum_Cell comes with a recessed casing with plaster frame.

Cell family

Cell_Ww track	Cell_S
	
164	226



_Cell

W 2-4-6-12-18
mm ☐ **50x50-119-221**
☐ **119x119**
Cct 2700-3000-4000
Opt **Spot**
Medium Flood
Medium Wide Flood
Elec. On/Off
0/1-10V
DALI
Col. WH BB

_Ww

W 9,5-18-32,5
mm ☐ **50x120-227-439**
Cct 2700
3000
4000
Opt **Asymm**
Elec. On/Off
0/1-10V
DALI
Col. WH BB

_Gypsum

W 2-4-6-12-18
mm ☐ **36x36-110-220**
☐ **110x110**
Cct 2700-3000-4000
Opt **Spot**
Medium Flood
Medium Wide Flood
Elec. On/Off
0/1-10V
DALI
Col. WH BB



WB | White / Black




WH | White

Total Black: even more impressive
The visual effect of the black optics combines perfectly with the black finish of the device, creating a coherent and refined look. The black flange further adds a touch of sophistication, creating a clean and discreet boundary between Cell and its surroundings.




BB | Black


Vast range
The Cell and Gypsum_Cell range of products now come with new versions, conceived to meet several lighting technology needs. The new one-cell single recessed casing joins the three and six-cell options arranged linearly and squared with nine modules. The innovation is the introduction of the Cell_Ww asymmetric versions, designed for wall lighting, available in linear configurations of 3, 6 and 12 cells.




Micro-Optics CELL
The particular wire mesh with convex faces that characterises the surface of the micro reflectors is capable of controlling each light beam defining an emission available in Spot, Medium Flood, Medium Wide Flood.



Quick installation
The Gypsum_Cell comes with a recessed casing with plaster frame, conceived for installation on dropped ceiling. The magnet-equipped quick coupling system allows to easily position the light units that can be painted, for full integration with the architecture.




New Wall washer Optics
The Cell_Ww Optics compartment is designed to guarantee clean and precise wall washer lighting. The cut-off cells are structured to channel the wall light, starting from the peak, lighting it with a sharp-edged and defined beam that gradually washes the entire surface. The opening of the beam reaches 90 degrees, also lighting the walking area adjacent to the wall. A specific fixed eyelid, slightly raised to eliminate the luminance of the cells, partially covers the Optics compartment, defines the angle of emission and eliminates any smudging of stray light.



Cell | powerLED | 630 mA | 2 W DC






	Fin	Cct	lm S - lm D	Opt
CRI 90				
C00148	**WH**	**M**	199 - 172	**SP** (13° UGR<16)
	BB	**W**	213 - 184	**ML** (32° UGR<16)
	WB	**N**	237 - 206	**MW** (48° UGR<19)

Electronics: **C1** (pag 108)

Cell | powerLED | 350 mA | 4 W DC






	Fin	Cct	lm S - lm D	Opt
CRI 90				
C00149	**WH**	**M**	389 - 308	**SP** (15° UGR<16)
	BB	**W**	416 - 329	**ML** (33° UGR<16)
	WB	**N**	449 - 355	**MW** (47° UGR<16)

Electronics: **D1** (pag 108)

Cell | powerLED | 630 mA | 6 W DC






	Fin	Cct	lm S - lm D	Opt
CRI 90				
C00150	**WH**	**M**	597 - 520	**SP** (12° UGR<11)
	BB	**W**	639 - 557	**ML** (33° UGR<11)
	WB	**N**	711 - 624	**MW** (49° UGR<16)

Electronics: **F1** (pag 108)

Cell | powerLED | 350 mA | 12 W DC






	Fin	Cct	lm S - lm D	Opt
CRI 90				
C00151	**WH**	**M**	1167 - 892	**SP** (16° UGR<11)
	BB	**W**	1248 - 955	**ML** (35° UGR<11)
	WB	**N**	1347 - 1030	**MW** (47° UGR<16)

Electronics: **O1** (pag 108)

Cell | powerLED | 630 mA | 12 W DC






	Fin	Cct	lm S - lm D	Opt
CRI 90				
C00152	**WH**	**M**	1194 - 1080	**SP** (14° UGR<11)
	BB	**W**	1278 - 1157	**ML** (34° UGR<11)
	WB	**N**	1422 - 1296	**MW** (49° UGR<16)

Electronics: **M1** (pag 108)

Cell | powerLED | 630 mA | 18 W DC







	Fin	Cct	lm S - lm D	Opt
CRI 90				
C00153	**WH**	**M**	1791 - 1704	**SP** (12° UGR<11)
	BB	**W**	1917 - 1823	**ML** (31° UGR<11)
	WB	**N**	2133 - 2042	**MW** (49° UGR<16)

Electronics: **R1** (pag 108)

Gypsum Cell | powerLED | 630 mA | 2 W DC







C.C. IP20

	Cct	lm S - lm D	Opt
CRI 90			
WH **64630**	**M**	199 - 135	**15** (13° UGR<16)
BB **64631**	**W**	213 - 155	**30** (32° UGR<16)
	N	237 - 201	**45** (48° UGR<19)

Electronics: **C1** (pag 108)

Gypsum Cell | powerLED | 350 mA | 4 W DC







C.C. IP20 NEW

	Fin	Cct	lm S - lm D	Opt
CRI 90				
C00207	WH	**M**	389 - 308	**SP** (15° UGR<16)
	BB	**W**	416 - 329	**ML** (33° UGR<16)
		N	449 - 355	**MW** (47° UGR<16)

Electronics: **D1** (pag 108)

Gypsum Cell | powerLED | 630 mA | 6 W DC







C.C. IP20

	Cct	lm S - lm D	Opt
CRI 90			
WH **64547**	**M**	597 - 507	**15** (12° UGR<11)
BB **64546**	**W**	636 - 540	**30** (33° UGR<11)
	N	711 - 603	**45** (49° UGR<16)

Electronics: **F1** (pag 108)

Gypsum Cell | powerLED | 350 mA | 12 W DC






C.C. IP20 NEW

	Fin	Cct	lm S - lm D	Opt
CRI 90				
C00208	WH	**M**	1167 - 892	**SP** (16° UGR<11)
	BB	**W**	1248 - 955	**ML** (35° UGR<11)
		N	1347 - 1030	**MW** (47° UGR<16)

Electronics: **O1** (pag 108)

Gypsum Cell | powerLED | 630 mA | 12 W DC







C.C. IP20

	Cct	lm S - lm D	Opt
CRI 90			
WH **64549**	**M**	1194 - 1014	**15** (14° UGR<11)
BB **64548**	**W**	1272 - 1080	**30** (34° UGR<11)
	N	1422 - 1206	**45** (49° UGR<16)

Electronics: **M1** (pag 108)

Gypsum Cell | powerLED | 630 mA | 18 W DC






C.C. IP20

	Cct	lm S - lm D	Opt
CRI 90			
WH **64551**	**M**	1791 - 1521	**15** (12° UGR<11)
BB **64550**	**W**	1908 - 1620	**30** (31° UGR<11)
	N	2133 - 1809	**45** (49° UGR<16)

Electronics: **R1** (pag 108)

Accessories



AL **60830** Spacer 100x19 mm

suitable for: Gypsum Cell

Finishes


WH White
BB Black
AL Aluminium

Cct

M 2700
W 3000
N 4000

Cell_Ww | powerLED | 350 mA | 9,5 W DC







C.C. IP20

	Cct	lm S - lm D	Opt
CRI 90			
WH **82600**	**M**	1099 - 481	**07** (Asym. Ww)
BB **82940**	**W**	1152 - 517	
	N	1426 - 558	

Electronics: **FC** (pag 108)

Cell_Ww | powerLED | 630 mA | 18 W DC







C.C. IP20

	Cct	lm S - lm D	Opt
CRI 90			
WH **82601**	**M**	2198 - 926	**07** (Asym. Ww)
BB **82941**	**W**	2304 - 993	
	N	2852 - 1073	

Electronics: **FD** (pag 108)

Cell_Ww | powerLED | 1200 mA | 32,5 W DC





C.C. IP20

	Cct	lm S - lm D	Opt
CRI 90			
WH **82602**	**M**	3740 - 1838	**07** (Asym. Ww)
BB **82942**	**W**	3912 - 1972	
	N	4848 - 2130	

Electronics: **FE** (pag 108)

Electronics

C1

89147 ON/OFF 1 - 2 art. 138 x 22 x h 21 — 29
99376 ON/OFF 3 - 6 art. 138 x 22 x h 21 — 29
99105 ON/OFF 6 - 12 art. 103 x 58 x h 27 — 64
99710 24V DC converter 0/1-10V 1 - 6 art. 138 x 22 x h 20 — 29
99713 24V DC converter DALI 1 - 6 art. 138 x 22 x h 20 — 29
+ driver 24V DC **99374** 75W — 56
99331 150W — 70

D1

89145 ON/OFF 1 art. 138 x 22 x h 21 — 29
99375 ON/OFF 2 - 3 art. 138 x 22 x h 21 — 29
C-E100010 0/1-10V 1 art. 138 x 22 x h 22 — 31
C-E100011 DALI/PUSH 1 art. 138 x 22 x h 22 — 31

F1

99376 ON/OFF 1 - 2 art. 138 x 22 x h 21 — 29
99105 ON/OFF 2 - 4 art. 103 x 58 x h 27 — 64
99115 0/1-10V 1 - 3 art. 210 x 48 x h 25 — 56
C-E100001 DALI/PUSH 2 - 4 art. 131 x 44 x h 30 — 54

FC

99126 ON/OFF 1 art. 206 x 89 x h 40 — 48
99115 0/1-10V 1 art. 210 x 48 x h 25 — 56
C-E100001 DALI/PUSH 1 art. 131 x 44 x h 30 — 54

FD

99105 ON/OFF 1 art. 103 x 58 x h 27 — 64
83008 0/1-10V, DALI/PUSH 1 art. 124 x 79 x h 22 — 84
C-E100001 DALI/PUSH 1 art. 131 x 44 x h 30 — 54

FE

83008 ON/OFF, 0/1-10V, DALI 1 art. 124 x 79 x h 22 — 84

M1

99129 ON/OFF 1 art. 134 x 37 x h 31 — 48
99105 ON/OFF 1 - 2 art. 103 x 58 x h 27 — 64
99115 0/1-10V 1 art. 210 x 48 x h 25 — 56
C-E100001 DALI/PUSH 1 - 2 art. 131 x 44 x h 30 — 54

O1

99375 ON/OFF 1 art. 138 x 22 x h 21 — 29
99115 0/1-10V 1 art. 210 x 48 x h 25 — 56
83322 DALI/PUSH 1 art. 149 x 37 x h 31 — 48

R1

99105 ON/OFF 1 art. 103 x 58 x h 27 — 64
99115 0/1-10V 1 art. 210 x 48 x h 28 — 56
C-E100001 DALI/PUSH 1 art. 131 x 44 x h 30 — 54

SOFITEL BARCELONA SKIPPER
Barcelona (Spain)

Lighting Designer:
Fantastico Lighting Partners


Photography:
Jordi Anguera




GIOTTO

PATENTED


Aluminium body.






Scale 1:1

In a class of its own
Due to the 9 millimetres of source and the surprising controlled diffusion in three optical variants: Spot, Medium Flood, Wide Flood. Giotto ushers an innovative solution in the lighting industry, unrivalled for its ratio between the slim diameter of the beam output hole and the super efficient lighting technique.



Cross Optics Technology ™
This patented technology uses the positioning of two convex lenses place across from one another: the first gathers the light on the surface of the second, channelling it into a small point for perfect definition. The second lens reopens the beam, now deprived of the secondary component, creating a crisp and clean ring of light on the lit surface.





Giotto Frameless
Giotto_RF adapts to any ceiling and disappears entirely from view thanks to the plaster white body that allows the product to be painted. The recessed casing allows easy screw installation and just as easy removal of the item, which can be replaced with another from the Giotto family.





Giotto_R | powerLED | 350 mA | 4 W DC






	Cct	lm S - lm D	Opt
CRI 90			
WH **84199**	**M**	389 - 95	**10** (14° UGR<11)
BB **84200**	**W**	416 - 103	**30** (35° UGR<11)
	N	456 - 111	**60** (54° UGR<11)

Electronics: **D1** (pag 112)

Giotto_R | powerLED | 500 mA | 6 W DC







	Cct	lm S - lm D	Opt
CRI 90			
WH **84203**	**M**	532 - 129	**10** (14° UGR<11)
BB **84204**	**W**	569 - 139	**30** (35° UGR<11)
	N	614 - 150	**60** (54° UGR<11)

Electronics: **E1** (pag 112)

Giotto_RF | powerLED | 350 mA | 4 W DC







	Cct	lm S - lm D	Opt
CRI 90			
WH **82075**	**M**	389 - 95	**10** (14° UGR<11)
	W	416 - 103	**30** (35° UGR<11)
	N	456 - 111	**60** (54° UGR<11)

Electronics: **D1** (pag 112) | Recessed casing (pag 112)

Giotto_RF | powerLED | 500 mA | 6 W DC





	Cct	lm S - lm D	Opt
CRI 90			
WH **82077**	**M**	532 - 129	**10** (14° UGR<11)
	W	569 - 139	**30** (35° UGR<11)
	N	614 - 150	**60** (54° UGR<11)

Electronics: **E1** (pag 112) | Recessed casing (pag 112)

The Giotto_RF models must be completed with the appropriate plasterboard outer casing.

Electronics


D1

89145	**99375**	**C-E100010**	**C-E100011**
ON/OFF	ON/OFF	0/1-10V	DALI/PUSH
1 art.	2 - 3 art.	1 art.	1 art.
138 x 22 x h 21	138 x 22 x h 21	138 x 22 x h 22	138 x 22 x h 22
29	29	31	31

E1

99377	**99106**	**C-E100004**	**C-E100005**	**C-E100001**
ON/OFF	ON/OFF	0/1-10V	DALI/PUSH	DALI/PUSH
1 art.	2 - 3 art.	1 art.	1 art.	2 - 3 art.
138 x 22 x h 21	103 x 58 x h 27	124 x 22 x h 22	124 x 22 x h 22	131 x 44 x h 30
29	64	31	31	54

Recessed casing



PLC **C-C100006** Recessed casing for flush installation

suitable for: Giotto_RF 4W / Giotto_RF 6W


LINEA LIGHT GROUP
Treviso (Italy)

Lighting Designer:
Linea Light Group




COB40

Cob40 is a recessed mount with reduced dimensions and high efficiency. Available in two versions, fixed or tilting, in three power versions - 6.5W, 15W and 18W. Thanks to the new accessories, Cob 40 can change the colour of the inner ring to adapt and match the surrounding environment. Aluminium body.



Cob40_R | arrayLED | 700 mA | 6,5 W DC






	Fin	Cct	lm S - lm D	Opt
CRI 90				
C00174	**WH**	**M**	715 - 580	**SP** (19° UGR<16)
	BB	**W**	748 - 606	**FL** (21° UGR<16)
		N	805 - 653	**WF** (54°)

Electronics: **I1** (pag 115) | Recessed casings & accessories (pag 115)

Cob40_R | arrayLED | 400 mA | 15 W DC






	Fin	Cct	lm S - lm D	Opt
CRI 90				
C00175	**WH**	**M**	1837 - 1333	**FL** (22° UGR<19)
	BB	**W**	1906 - 1383	**ML** (31° UGR<19)
		N	1940 - 1411	**WF** (58°)

Electronics: **P1** (pag 115) | Recessed casings & accessories (pag 115)

Cob40_R | arrayLED | 500 mA | 18 W DC






	Cct	lm S - lm D	Opt
CRI 90			
WH **82473**	**M**	2692 - 2323	**15** (16° UGR<16)
BB **82474**	**W**	2818 - 2395	**30** (34° UGR<16)
	N	2930 - 2491	**60** (58°)

Electronics: **Q1** (pag 115) | Recessed casings & accessories (pag 115)

Cob40_RJ | arrayLED | 700 mA | 6,5 W DC






	Fin	Cct	lm S - lm D	Opt
CRI 90				
C00176	**WH**	**M**	715 - 580	**SP** (19°)
	BB	**W**	748 - 606	**FL** (21°)
		N	805 - 653	**WF** (54°)

Electronics: **I1** (pag 115) | Recessed casings & accessories (pag 115)

Cob40_RJ | arrayLED | 500 mA | 18 W DC





	Cct	lm S - lm D	Opt
CRI 90			
WH 82477	**M**	2692 - 2323	**15** (16°)
BB 82478	**W**	2818 - 2395	**30** (34°)
	N	2930 - 2491	**60** (58°)

Electronics: **Q1** (pag 115) | Recessed casings & accessories (pag 115)

Electronics

I1

99735
ON/OFF
1 art.
134 x 37 x h 31
48

99147
ON/OFF
2 - 3 art.
103 x 58 x h 27
64

99733
0/1-10V
1 art.
134 x 37 x h 31
48

83323
DALI/PUSH
1 art.
134 x 37 x h 31
48

C-E100016
DALI/PUSH
2 - 4 art.
131 x 44 x h 30
54

Q1

99106
ON/OFF
1 art.
103 x 58 x h 27
64

99115
0/1-10V
1 art.
210 x 48 x h 28
56

C-E100001
DALI/PUSH
1 art.
131 x 44 x h 30
54


P1

99734
ON/OFF
1 art.
149 x 37 x h 31
48

99732
0/1-10V
1 art.
149 x 37 x h 31
48

83322
DALI/PUSH
1 art.
149 x 37 x h 31
48

Recessed casings & Accessories



PLP **89374** Recessed casing

suitable for: Cob40_R 6,5W - Cob40_R 15W
Cob40_R 18W - Cob40_RJ 6,5W



WH **99888** Accessories
AU **99889**
CU **99890**
CH **99899**
suitable for: Cob40_R 6,5W - Cob40_RJ 6,5W



PLP **89373** Recessed casing *

suitable for: Cob40_R 6,5W - Cob40_R 15W
Cob40_R 18W - Cob40_RJ 6,5W




WH **99891** Accessories
AU **99892**
CU **99893**
CH **99900**
suitable for: Cob40_R 15W




WH **99901** Accessories
AU **99902**
CU **99903**
CH **99904**
suitable for: Cob40_R 18W - Cob40_RJ 18W


COB44

Aluminium body. Polycarbonate flange.



Cob44_R | arrayLED | 700 mA | 6,5 W DC






	Fin	Cct	lm S - lm D	Opt
CRI 90				
C00177	**WH**	**M**	715 - 580	**SP** (10° UGR<16)
	BB	**W**	748 - 607	**FL** (20° UGR<16)
		N	805 - 653	**WF** (52° UGR<16)

Electronics: **I1** (pag 117)

Cob44_R | arrayLED | 300 mA | 11 W DC






	Fin	Cct	lm S - lm D	Opt
CRI 90				
C00178	**WH**	**M**	1487 - 909	**SP** (13° UGR<19)
	BB	**W**	1578 - 965	**FL** (21° UGR<19)
		N	1660 - 1015	**WF** (52° UGR<19)

Electronics: **L1** (pag 117)

Cob44_RJ | arrayLED | 700 mA | 6,5 W DC






	Fin	Cct	lm S - lm D	Opt
CRI 90				
C00179	**WH**	**M**	715 - 580	**SP** (10°)
	BB	**W**	748 - 607	**FL** (20°)
		N	805 - 653	**WF** (52°)

Electronics: **I1** (pag 117)

Cob44_RJ | arrayLED | 300 mA | 11 W DC







	Fin	Cct	lm S - lm D	Opt
CRI 90				
C00180	**WH**	**M**	1487 - 909	**SP** (13°)
	BB	**W**	1578 - 965	**FL** (21°)
		N	1660 - 1015	**WF** (52°)

Electronics: **L1** (pag 117)

Cob44_Q | arrayLED | 700 mA | 6,5 W DC







	Fin	Cct	lm S - lm D	Opt
CRI 90				
C00181	**WH**	**M**	715 - 580	**SP** (10° UGR<16)
	BB	**W**	748 - 607	**FL** (20° UGR<16)
		N	805 - 653	**WF** (52° UGR<16)

Electronics: **I1** (pag 117)

Cob44_Q | arrayLED | 300 mA | 11 W DC






	Fin	Cct	lm S - lm D	Opt
CRI 90				
C00182	**WH**	**M**	1487 - 909	**SP** (13° UGR<16)
	BB	**W**	1578 - 965	**FL** (21° UGR<16)
		N	1660 - 1015	**WF** (52° UGR<16)

Electronics: **L1** (pag 117)

Cob44_QJ | arrayLED | 700 mA | 6,5 W DC






	Fin	Cct	lm S - lm D	Opt
CRI 90				
C00183	**WH**	**M**	715 - 580	**SP** (10°)
	BB	**W**	748 - 607	**FL** (20°)
		N	805 - 653	**WF** (52°)

Electronics: **I1** (pag 117)

Cob44_QJ | arrayLED | 300 mA | 11 W DC





	Fin	Cct	lm S - lm D	Opt
CRI 90				
C00184	**WH**	**M**	1487 - 909	**SP** (13°)
	BB	**W**	1578 - 965	**FL** (21°)
		N	1660 - 1015	**WF** (52°)

Electronics: **L1** (pag 117)

Electronics

I1

99735	99147	99733	83323	C-E100016
ON/OFF	ON/OFF	0/1-10V	DALI/PUSH	DALI/PUSH
1 art.	2 - 3 art.	1 art.	1 art.	2 - 4 art.
134 x 37 x h 31	103 x 58 x h 27	134 x 37 x h 31	134 x 37 x h 31	131 x 44 x h 30
48	64	48	48	54

L1

99734	99732	83322
ON/OFF	0/1-10V	DALI/PUSH
1 art.	1 art.	1 art.
149 x 37 x h 31	149 x 37 x h 31	149 x 37 x h 31
48	48	48

Finishes

White
Black

Cct

M 2700 **N** 4000
W 3000

WOOFER

Aluminium body.



High Efficiency

PREVIOUS VERSION **Woofer_R**		NEW VERSION **Woofer_R V2**	
old 13 W 3000K **1385 lm S**	→	new 12,5 W 3000K **2235 lm S**	**+850 lm**
old 25 W 3000K **2941 lm S**	→	new 25 W 3000K **4007 lm S**	**+1066 lm**

Spot (SP)
Wide Flood (WF)
Extra Wide Flood (XF)



Asymmetric Wallwasher (WW)




Diffused (00)
ECL version



Woofer_R | V2 | arrayLED | 220 mA | 8 W DC







C.C. IK08 IP44 NEW

	Fin	Cct	lm S - lm D	Opt
CRI 90				
C00405	**WH**	**M**	1278 - 938	**SP** (16° UGR<16)
		W	1338 - 982	**WF** (64° UGR<16)
		N	1392 - 1017	**XF** (96°)
				WW (Asym Ww)

Electronics: **G1** (pag 119)

Woofer_R | V2 | arrayLED | 350 mA | 12,5 W DC






C.C. IK08 IP44 NEW

	Fin	Cct	lm S - lm D	Opt
CRI 90				
C00406	**WH**	**M**	2145 - 1488	**SP** (21° UGR<19)
		W	2235 - 1620	**WF** (62° UGR<19)
		N	2266 - 1665	**XF** (96°)
				WW (Asym Ww)

Electronics: **O1** (pag 119)

Woofer_R | V2 | arrayLED | 500 mA | 18 W DC






C.C. IK08 IP44 NEW

	Fin	Cct	lm S - lm D	Opt
CRI 90				
C00407	**WH**	**M**	2834 - 2060	**SP** (21° UGR<19)
		W	2869 - 2082	**WF** (60° UGR<19)
		N	2982 - 2173	**XF** (96°)
				WW (Asym Ww)

Electronics: **Q1** (pag 119)

Woofer_R | V2 | arrayLED | 500 mA | 18 W DC






C.C. IK08 IP44 NEW

	Fin	Cct	lm S - lm D	Opt
CRI 90				
C00408	**WH**	**M**	2834 - 2060	**SP** (21° UGR<19)
		W	2869 - 2082	**WF** (60° UGR<19)
		N	2982 - 2173	**XF** (96°)
				WW (Asym Ww)

Electronics: **Q1** (pag 119)

Woofer_R | V2 | arrayLED | 700 mA | 25 W DC





C.C. IK08 IP44 NEW

	Fin	Cct	lm S - lm D	Opt
CRI 90				
C00409	**WH**	**M**	3846 - 2757	**SP** (27° UGR<19)
		W	4007 - 2869	**WF** (57° UGR<19)
		N	4225 - 3029	**XF** (99°)
				WW (Asym Ww)

Electronics: **T1** (pag 119)

Electronics

T1

99147
ON/OFF
1 art.
103 x 58 x h 27
64

83008
0/1-10V, DALI/PUSH
1 art.
124 x 79 x h 22
84

C-E100016
DALI/PUSH
1 art.
131 x 44 x h 30
54

Q1

99106
ON/OFF
1 art.
103 x 58 x h 27
64

99115
0/1-10V
1 art.
210 x 48 x h 28
56

C-E100001
DALI/PUSH
1 art.
131 x 44 x h 30
54

O1

99375
ON/OFF
1 art.
138 x 22 x h 21
29

99115
0/1-10V
1 art.
210 x 48 x h 25
56

83322
DALI/PUSH
1 art.
149 x 37 x h 31
48

G1

99198
ON/OFF
1 art.
149 x 37 x h 31
48

99732
0/1-10V
1 art.
149 x 37 x h 31
48

83322
DALI/PUSH
1 art.
149 x 37 x h 31
48


Finishes
White

Cct
M 2700
W 3000
N 4000

Environment Care Lighting


In collaboration with University of Strathclyde Glasgow

Linea Light Group introduces Environment Care Lighting, a technology developed in collaboration with the University of Strathclyde in Glasgow which, thanks to a wavelength of light of 405 nm, sanitises surfaces, preventing the onset of infections, guaranteeing renewed wellbeing in the environment in which it is used and reducing the bacterial load by up to 70%. It was found that after a 10-hour test, the reduction of the bacterial load already reaches 35%.
Environment Care Lighting involves the use of a blue-dominant LED source combined with a white powerLED, thus achieving a dual functionality: lighting and disinfecting the environment at the same time. The use of high colour rendering LEDs makes it possible to illuminate the room by emphasising colours and surfaces.



Woofer_R ECL | topLED | 220-240 V AC | 15 W DC - 16,5 W AC | 405 nm






Driver Downl. C.V. IK08 IP44 KIT

	Cct	lm S - lm D	Opt
Efficiency - CRI 90			
WH **84023**	**T**	1000 - 748	**00** (Diffused)

Woofer_R ECL | topLED | 220-240 V AC | 24 W DC - 26,5 W AC | 405 nm





Driver Downl. C.V. IK08 IP44 KIT

	Cct	lm S - lm D	Opt
Efficiency - CRI 90			
WH **84024**	**T**	1770 - 1377	**00** (Diffused)

Dual independent lighting:




Day: White light + λ 405 Nm light




Night: λ 405 Nm light

Woofer_R ECL 24W:

Example of use on volumes
of 3 m x 3 m x h 2.7 m.
Effective area 9 sqm.





Finishes **Cct**

WH White **T** 3500

ILLUMINATOR

Aluminium body.



High Efficiency

PREVIOUS VERSION **Illuminator**		NEW VERSION **Illuminator V2**	
old 15 W 3000K **1677 lm S**	→	new 12,5 W 3000K **1950 lm S**	**+273 lm**
old 25 W 3000K **2794 lm S**	→	new 23 W 3000K **3384 lm S**	**+590 lm**







Illuminator | arrayLED | 700 mA | 6,5 W DC






	Cct	lm S - lm D	Opt
CRI 90			
AM **80338**	**M**	715 - 647	**15** (15°)
	W	748 - 677	**30** (26°)
	N	805 - 729	**60** (52°)

Electronics: **I1** (pag 124)

Illuminator | Adjustable recessed casing






1 x lamp

WH **99485**
BB **99488**

Accessories (pag 125)

Illuminator | Adjustable recessed casing






2 x lamp

WH **99486**
BB **99489**

Accessories (pag 125)

Illuminator | Adjustable recessed casing





3 x lamp

WH **99487**
BB **99490**

Accessories (pag 125)

Finishes


WH White AM Anodised Aluminium
BB Black

Cct

M 2700 **N** 4000
W 3000

Illuminator | V2 | arrayLED | 350 mA 12,5 W DC | 630 mA 23 W DC






	Fin	Cct	lm S - lm D 12,5 W DC	lm S - lm D 23 W DC	Opt
CRI 90					
C00400	**WH**	**M**	1815 - 1470	3342 - 2717	**SP** (19°)
	BB	**W**	1837 - 1488	3384 - 2750	**ML** (39°)
		N	1950 - 1580	3517 - 2860	**WF** (50°)

Electronics: 12,5W **O1** - 23W **R1** (pag 124) | Optics & Accessories (pag 125)

Illuminator | Adjustable recessed casing






1 x lamp

WH **99497**
BB **99500**

Accessories (pag 125)

Illuminator | Adjustable recessed casing






2 x lamp

WH **99498**
BB **99501**

Accessories (pag 125)

Illuminator | Adjustable recessed casing





3 x lamp

WH **99499**
BB **99502**

Accessories (pag 125)

Electronics

I1

99735
ON/OFF
1 art.
134 x 37 x h 31
48

99147
ON/OFF
2 - 3 art.
103 x 58 x h 27
64

99733
0/1-10V
1 art.
134 x 37 x h 31
48

83323
DALI/PUSH
1 art.
134 x 37 x h 31
48

C-E100016
DALI/PUSH
2 - 4 art.
131 x 44 x h 30
54

R1

99105
ON/OFF
1 art.
103 x 58 x h 27
64

99115
0/1-10V
1 art.
210 x 48 x h 28
56

C-E100001
DALI/PUSH
1 art.
131 x 44 x h 30
54

O1

99375
ON/OFF
1 art.
138 x 22 x h 21
29

99115
0/1-10V
1 art.
210 x 48 x h 25
56

83322
DALI/PUSH
1 art.
149 x 37 x h 31
48

Finishes **Cct**

WH White **M** 2700 **N** 4000
BB Black **W** 3000

ADJUSTABLE RECESSED CASING



ELECTRONICS


ON/OFF


1-10 V


DALI

LAMP


Illuminator 6,5 W


Illuminator 12,5 W


Illuminator 23 W

ACCESSORIES

Illuminator


Honeycomb


Elliptical filter


Cross louvre


Cylindrical screen



45° Cylindrical screen

Optics & Accessories



C-U300009 Spot lens kit (15°)
C-U300010 Medium Flood lens kit (30°)
C-U300011 Wide Flood lens kit (45°)

suitable for: Illuminator 12,5W/23W



TR **99552** Elliptical filter
suitable for: Illuminator 6,5W


TR **C-U300007** Elliptical filter
suitable for: Illuminator 12,5W/23W



BB **C-U300031** Cross louvre
suitable for: Illuminator 12,5W/23W



BB **C-U300030** 45° Cylindrical screen
suitable for: Illuminator 12,5W/23W




BB **99554** Cylindrical screen
suitable for: Illuminator 6,5W



BB **99550** Honeycomb
suitable for: Illuminator 6,5W

BB **C-U300008** Honeycomb
suitable for: Illuminator 12,5W/23W



BB **C-U300029** Cylindrical screen
suitable for: Illuminator 12,5W/23W

Finishes

TR Transparent
BB Black

OPTUS_EX

Aluminium body.



Optus family

Optus_T	Optus_Ww	Optus W2/W3	Creek Optus	Navata Optus
				
155-156	158	160	172	178



	_EX
W	1,5
mm	**Ø 55**
Cct	2700-3000
Opt	**Flood** **M.Flood**
Elec.	On/Off 1/10V-DALI
Col.	WH BB


	_EX
W	4
mm	**Ø 75**
Cct	2700-3000-4000
Opt	**Spot-M.Flood** **W. Flood-Focus**
Elec.	On/Off 1/10V-DALI
Col.	WH BB

	_EX
W	12-18-(8 DW)
mm	**Ø 138**
Cct	2700-3000-4000-DW
Opt	**Spot-Flood** **W.Flood**
Elec.	On/Off-1/10V DALI
Col.	WH BB

	_EX
W	25-35-(15-25 DW)
mm	**Ø 173**
Cct	2700-3000-4000-5000-DW
Opt	**Spot-Flood** **W.Flood**
Elec.	On/Off-1/10V DALI
Col.	WH BB


SMALL SIZE

Optux_EX comes with an extremely compact-size die cast aluminium single block, just 50 mm high. This particular shape allows installation in plasterboards as well as low and narrow surfaces.



EXTRACTABLE TILTING SYSTEM

Optux_EX downlights come with a 350° mobility on the horizontal axis and an inclination on the vertical axis that allows a max 20° recess or an up to 45° extraction of the spotlight.





Optics 85 Focus
A spotlight with variable optics from 10° to 20° used to adjust the light beam according to requirements. The variable optics can be adjusted manually and this versatility means being able to adapt the lighting to a variety of needs, offering the flexibility to concentrate or diffuse the light, depending on the circumstances.



85 Focus | 10° - 20°

Optus_EX | powerLED | 500 mA | 1,5 W DC






	Cct	lm S - lm D	Opt
CRI 90			
WH **82737**	**M**	170 - 123	**20** (22°)
BB **82738**	**W**	181 - 131	**35** (32°)
	N	203 - 147	

Electronics: **B1** (pag 131)

Optus_EX | powerLED | 350 mA | 4 W DC






	Cct	lm S - lm D	Opt
CRI 90			
WH **82739**	**M**	389 - 276	**15** (15°)
BB **82740**	**W**	419 - 295	**30** (33°)
	N	449 - 318	**60** (61°)
			85 (10°-20°)

Electronics: **D1** (pag 131)

Optus_EX | arrayLED | 350 mA 12W DC | 500 mA 18 W DC






	Cct	lm S - lm D	lm S - lm D	Opt
CRI 98 - Specialty		12W	18W	
WH **81665**	**W**	1719 - 1238	2356 - 1696	**15** (18°)
BB **81666**				**30** (38°)
				60 (48°)
CRI 98 - Fidelity		12W	18W	
WH **81663**	**M**	1768 - 1274	2423 - 1745	**15** (18°)
BB **81664**	**W**	1810 - 1303	2480 - 1785	**30** (38°)
	N	1924 - 1385	2637 - 1898	**60** (48°)
CRI 90 - Balance		12W	18W	
WH **81661**	**M**	1964 - 1420	2692 - 1945	**15** (18°)
BB **81662**	**W**	2056 - 1487	2818 - 2037	**30** (38°)
	N	2138 - 1548	2930 - 2121	**60** (48°)

Electronics: 12W **O1** - 18W **Q1** (pag 131) | Optics & Accessories (pag 130)

Optus_EX | Dynamic White | powerLED | 700 mA | 8 W DC (x channel)





	Cct		Opt
CRI 90			
WH **84159**	**D**	2700K - 5700K Dynamic White	**30** (38°)
BB **84160**			**60** (48°)


Electronics: **CM** (pag 131) | Optics & Accessories (pag 130)

Diode varieties

The Optus_EX range of products offers the highest combination-source degree, given that it is fit for LED Balance - CRI 90 , Specialty - CRI 98 and Fidelity - CRI 98 diodes. This allows obtaining maximum versatility of use, given that Optus_EX can be installed in various environments ranging from museums to retail, depending on the specific type of source chosen.









Finishes **Cct**

WH White **M** 2700 **N** 4000
BB Black **W** 3000 **D** 2700-5700

Optus_EX | arrayLED | 700 mA 25W DC | 950 mA 35 W DC







	Cct	lm S - lm D	lm S - lm D	Opt
CRI 98 - Specialty		25W	35W	
WH **81671**	**W**	3242 - 2589	4196 - 3350	**15** (17°)
BB **81672**				**30** (26°)
				60 (48°)
CRI 98 - Fidelity		25W	35W	
WH **81669**	**M**	3446 - 2754	4460 - 3563	**15** (17°)
BB **81670**	**W**	3412 - 2727	4416 - 3528	**30** (26°)
	N	3627 - 2899	4695 - 3751	**60** (48°)
CRI 90 - Balance		25W	35W	
WH **81667**	**M**	3829 - 3054	4956 - 3951	**15** (17°)
BB **81668**	**W**	3877 - 3100	5019 - 4011	**30** (26°)
	N	4030 - 3224	5216 - 4172	**60** (48°)
	C	3909 - 3131	5059 - 4051	

Electronics: 25W **T1** - 35W **V1** (pag 131) | Optics & Accessories (pag 130)

Optus_EX | Dynamic White | powerLED | 700 mA | 15 W DC (x channel)







	Cct		Opt
CRI 90			
WH **84161**	**D**	2700K - 5700K Dynamic White	**15** (17°)
BB **84162**			**30** (26°)

Electronics: **CN** (pag 131) | Optics & Accessories (pag 130)

Optus_EX | Dynamic White | powerLED | 700 mA | 25 W DC (x channel)





	Cct		Opt
CRI 90			
WH **84163**	**D**	2700K - 5700K Dynamic White	**15** (17°)
BB **84164**			**30** (26°)

Electronics: **CO** (pag 131) | Optics & Accessories (pag 130)

Smart lighting
The Dynamic White modules, combined with the new, specifically developed management systems, allow the mixture of whites from Warm White and Cold White. With a single product, it is therefore possible to reproduce all the colour temperatures from 2700K to 5700K, maintaining the same luminous flow. Recent studies on the circadian cycles have shown how the temperature variations of natural light, from dawn to dusk, influence the well-being of humans.



2700K 5700K

Finishes
WH White
BB Black

Cct
M 2700 **N** 4000 **D** 2700-5700
W 3000 **C** 5000

Optics & Accessories



TR **99827** Spot
TR **99828** Flood
TR **99829** W. Flood
suitable for: Optus_EX 12W / 18W
Optus_EX 8W Dynamic White

TR **99808** Spot
TR **99809** Flood
TR **99810** W. Flood
suitable for: Optus_EX 15W Dynamic White /
25W Dynamic White


TR **C-U300015** Spot
TR **C-U300016** Flood
TR **C-U300017** W. Flood
suitable for: Optus_EX 25W(not for Dynamic White) / 35W



TR **99844** Focal Kit
(min 16° / max 50°)
suitable for: Optus_EX 12W / 18W
Optus_EX 8W Dynamic White

TR **99843** Focal Kit
(min 16° / max 42°)
suitable for: Optus_EX 15W Dynamic White /
25W Dynamic White

TR **C-U300034** Focal Kit
(min 16° / max 42°)
suitable for: Optus_EX 25W(not for Dynamic White) / 35W



BB **99841** Honeycomb (a)
with fixing ring (b)
suitable for: Focal kit **99844**

BB **99842** Honeycomb (a)
with fixing ring (b)
suitable for: Focal kit **99843**


BB **C-U300014** Honeycomb (a)
without fixing ring (b)
suitable for: Focal kit **C-U300034**



BB **99779** Cross louvre
suitable for: Optus_EX 12W / 18W
Optus_EX 8W Dynamic White

BB **99799** Cross louvre
suitable for: Optus_EX 15W Dynamic White /
25W Dynamic White


BB **C-U300031** Cross louvre
suitable for: Optus_EX 25W(not for Dynamic White) / 35W



TR **99781** Elliptical filter (a)
suitable for: Optus_EX 12W / 18W
Optus_EX 8W Dynamic White

TR **99797** Elliptical filter (a)
suitable for: Optus_EX 15W Dynamic White /
25W Dynamic White


TR **C-U300013** Elliptical filter (b)
Not compatible with optics 60
suitable for: Optus_EX 25W(not for Dynamic White) / 35W



BB **99780** Honeycomb (a)
suitable for: Optus_EX 12W / 18W
Optus_EX 8W Dynamic White

BB **99798** Honeycomb (b)
suitable for: Optus_EX 15W Dynamic White /
25W Dynamic White

BB **C-U300014** Honeycomb (a)
suitable for: Optus_EX 25W (not for Dynamic White) / 35W



BB **99783** Cylindrical screen
suitable for: Optus_EX 12W / 18W
Optus_EX 8W Dynamic White

BB **99796** Cylindrical screen
suitable for: Optus_EX 15W Dynamic White /
25W Dynamic White

BB **C-U300029** Cylindrical screen
suitable for: Optus_EX 25W(not for Dynamic White) / 35W



BB **99510** Kicker
suitable for: Optus_EX 12W / 18W
Optus_EX 8W Dynamic White

BB **99479** Kicker
suitable for: Optus_EX 15W / 25W / 35W



BB **99782** 45° Cylindrical screen
suitable for: Optus_EX 12W / 18W
Optus_EX 8W Dynamic White

BB **99795** 45° Cylindrical screen
suitable for: Optus_EX 15W Dynamic White /
25W Dynamic White

BB **C-U300030** 45° Cylindrical screen
suitable for: Optus_EX 25W(not for Dynamic White) / 35W

Electronics

B1

99195
ON/OFF
1 - 2 art.
138 x 22 x h 21
29

89146
ON/OFF
2 - 3 art.
138 x 22 x h 21
29

99377
ON/OFF
3 - 6 art.
138 x 22 x h 21
64

C-E100004
0/1-10V
3 - 4 art.
124 x 22 x h 22
31

C-E100005
DALI/PUSH
3 - 4 art.
124 x 22 x h 22
31

CN

83159
DALI DT8
1 - 2 art.
202 x 58 x h 30
66

C-E500003
Dimmer DMX
1 - 2 art.
107 x 96 x h 39

DMX
Controllers
Pag 963

Driver CV
CV 48V
Pag. 950-951

D1

89145
ON/OFF
1 art.
138 x 22 x h 21
29

99375
ON/OFF
2 - 3 art.
138 x 22 x h 21
29

C-E100010
0/1-10V
1 art.
138 x 22 x h 22
31

C-E100011
DALI/PUSH
1 art.
138 x 22 x h 22
31

Q1

99106
ON/OFF
1 art.
103 x 58 x h 27
64

99115
0/1-10V
1 art.
210 x 48 x h 28
56

C-E100001
DALI/PUSH
1 art.
131 x 44 x h 30
54

V1

99239
ON/OFF
1 art.
103 x 58 x h 27
64

83008
0/1-10V, DALI/PUSH
1 art.
124 x 79 x h 22
84

99345
DALI/PUSH
1 art.
210 x 48 x h 28
56

CM

83159
DALI DT8
2 - 3 art.
202 x 58 x h 30
66

C-E500003
Dimmer DMX
1 - 6 art.
107 x 96 x h 39

DMX
Controllers
Pag 963

Driver CV
CV 48V
Pag. 950-951

CO

83159
DALI DT8
1 art.
202 x 58 x h 30
66

C-E500003
Dimmer DMX
1 art.
107 x 96 x h 39

DMX
Controllers
Pag 963

Driver CV
CV 48V
Pag. 950-951

O1

99375
ON/OFF
1 art.
138 x 22 x h 21
29

99115
0/1-10V
1 art.
210 x 48 x h 25
56

83322
DALI/PUSH
1 art.
149 x 37 x h 31
48

T1

99147
ON/OFF
1 art.
103 x 58 x h 27
64

83008
0/1-10V, DALI/PUSH
1 art.
124 x 79 x h 22
84

C-E100016
DALI/PUSH
1 art.
131 x 44 x h 30
54





PROJECTORS & TRACK SYSTEMS



FRANTOIO CENTUMBRIE
Agello - Perugia (Italy)

Project: Architect Gianmarco Balucani

System and Lighting Designer:
Prait, Simone Suriani

Designer: Miriam Cinaglia

Photography: Matteo Canestraro

Projectors & Track systems range index

Pound

Pound_T Super Spot

138

Pound_T

138-142

Pound Focus

143-144

Pound Shaper


146-147

Optus

Optus_T


155-156

Optus_Ww

160

Optus_W2

160

Optus_W3

160

Skylum

Skylum_R Track



163

Cell

Cell_Ww track


165

Rollip35_T

Rollip35_T


167

Track system

Track system

170

Creek


Creek Optus


172

Linear Profiles

173

Navata

Navata_Optus


178

Navata Pound Shaper


180

Base

181

POUND

Aluminium body





_Shaper

W	11-27
mm	**Ø 48-85**
Cct	2700-3000-4000
Opt	**Shaper short medium-distance**
Elec.	D.O.B-DALI 2-Push Bluetooth
Col.	WH BB

_T

W	8-13-15-23-26-32,5-34
mm	**Ø 48-65-85**
Cct	2700-3000-4000-DW
Opt	**Spot-Flood-M.Flood M.W.Flood-W.Flood**
Elec.	On/Off-DALI 2-Push D.O.B-Bluetooth
Col.	WH BB

_Focus

W	13-23-32,5
mm	**Ø 48-65-85**
Cct	2700-3000-4000
Opt	**Focus**
Elec.	DALI 2-Push D.O.B Bluetooth
Col.	WH BB

_T Super Spot

W	7,2
mm	**Ø 48**
Cct	2700 3000 4000
Opt	**Narrow Spot**
Elec.	DALI 2-Push
Col.	WH BB


Pound family

Pound_BS	Pound_BC	Pound_S	Pound_Wall
			
236	236	237	237


Shaper

Pound shaper is the professional profiler in the i-LèD projector range. It was developed to highlight and emphasise museum works of different shapes and sizes thanks to the shaping system that minimises the outflow of reflections from the optical compartment. It is easy to use and available in 2 powers, 11 or 27 watts, with two different lenses designed to adapt to any distance. The track-mounted projectors make the most of technology Shaper are perfect for meeting the countless needs of any field, from retail spaces to museums.






Acro Optic Technology®




Conventional Optic Shaper

Pound Super spot

The Pound range offers a special version with an extremely small opening angle (8°). Thanks to a Fresnel lens, pound can reach small objects over long distances and accentuate details in museum or retail environments.








Pound_T | arrayLED | 220-240 V AC | 13 W DC - 15,5 W AC






IP20

	Cct	lm S - lm D	Opt
CRI 98 - Specialty			
WH **81629**	**W**	1482 - 1039	**15** (17°)
BB **81630**			**30** (25°)
			60 (45°)
CRI 98 - Fidelity			
WH **81627**	**M**	1502 - 1052	**15** (17°)
BB **81628**	**W**	1559 - 1092	**30** (25°)
	N	1676 - 1175	**60** (45°)
CRI 90 - Balance			
WH **81625**	**M**	1669 - 1169	**15** (17°)
BB **81626**	**W**	1771 - 1241	**30** (25°)
	N	1863 - 1305	**60** (45°)

Optics & accessories: (pag 150)

Pound_T Super Spot | powerLED | 220-240 V AC | 7,2 W DC - 9 W AC






IP20 DALI 2 DALI PUSH

	Cct	lm S - lm D	Opt
CRI 90 - Balance			
WH **81954**	**M**	614 - 260	**08** (8°)
BB **81955**	**W**	657 - 278	
	N	709 - 300	

Pound_T | arrayLED | 220-240 V AC | 13 W DC - 15,5 W AC






IP20 DALI 2 DALI PUSH

	Cct	lm S - lm D	Opt
CRI 98 - Specialty			
WH **82611**	**W**	1482 - 1039	**15** (17°)
BB **82612**			**30** (25°)
			60 (45°)
CRI 98 - Fidelity			
WH **82609**	**M**	1502 - 1052	**15** (17°)
BB **82610**	**W**	1559 - 1092	**30** (25°)
	N	1676 - 1175	**60** (45°)
CRI 90 - Balance			
WH **82607**	**M**	1669 - 1169	**15** (17°)
BB **82608**	**W**	1771 - 1241	**30** (25°)
	N	1863 - 1305	**60** (45°)

Optics & accessories: (pag 150)

Pound_T | Dynamic White | powerLED | 220-240 V AC | 8 W DC - 9 W AC (x channel)





IP20 DALI 2 DW DT8

	Cct		Opt
CRI 90			
WH **84165**	**D**	2700K - 5700K Dynamic White	**30** (26°)
BB **84166**			**60** (57°)


Optics: (pag 150)

Colors
WH White
BB Black

Cct
M 2700 **N** 4000
W 3000 **D** 2700 - 5700

Pound_T | arrayLED | 220-240 V AC | 13 W DC - 15,5 W AC





IP20


Technology Partner SILVAIR

	Cct	lm S - lm D	Opt
CRI 98 - Specialty			
WH **83799**	**W**	1482 - 1039	**15** (17°)
BB **83800**			**30** (25°)
			60 (45°)
CRI 98 - Fidelity			
WH **83801**	**M**	1502 - 1052	**15** (17°)
BB **83802**	**W**	1559 - 1092	**30** (25°)
	N	1676 - 1175	**60** (45°)
CRI 90 - Balance			
WH **83803**	**M**	1669 - 1169	**15** (17°)
BB **83804**	**W**	1771 - 1241	**30** (25°)
	N	1863 - 1305	**60** (45°)

Optics & accessories: (pag 150)

Pound_T | arrayLED | 220-240 V AC | 13 W DC - 15,5 W AC





IP20


D.O.B.

	Cct	lm S - lm D	Opt
CRI 98 - Specialty			
WH **82408**	**W**	1320 - 925	**15** (17°)
BB **82409**			**30** (25°)
			60 (45°)
CRI 98 - Fidelity			
WH **82406**	**M**	1338 - 936	**15** (17°)
BB **82407**	**W**	1389 - 972	**30** (25°)
	N	1493 - 1046	**60** (45°)
CRI 90 - Balance			
WH **82227**	**M**	1487 - 1042	**15** (17°)
BB **82228**	**W**	1578 - 1106	**30** (25°)
	N	1660 - 1163	**60** (45°)

Optics & accessories: (pag 150)

Pound_T | arrayLED | 220-240 V AC | 26 W DC - 29 W AC






IP20

	Cct	lm S - lm D	Opt
CRI 98 - Specialty			
WH **81635**	**W**	3315 - 2256	**15** (19°)
BB **81636**			**30** (35°)
			60 (56°)
CRI 98 - Fidelity			
WH **81633**	**M**	3204 - 2179	**15** (19°)
BB **81634**	**W**	3278 - 2231	**30** (35°)
	N	3485 - 2372	**60** (56°)
CRI 90 - Balance			
WH **81631**	**M**	3558 - 2420	**15** (19°)
BB **81632**	**W**	3725 - 2534	**30** (35°)
	N	3874 - 2636	**60** (56°)

Optics & accessories: (pag 150)

Pound_T | arrayLED | 220-240 V AC | 26 W DC - 29 W AC






IP20 DALI 2 DALI PUSH

	Cct	lm S - lm D	Opt
CRI 98 - Specialty			
WH **81812**	**W**	3315 - 2256	**15** (19°)
BB **81813**			**30** (35°)
			60 (56°)
CRI 98 - Fidelity			
WH **81810**	**M**	3204 - 2179	**15** (19°)
BB **81811**	**W**	3278 - 2231	**30** (35°)
	N	3485 - 2372	**60** (56°)
CRI 90 - Balance			
WH **81808**	**M**	3558 - 2420	**15** (19°)
BB **81809**	**W**	3725 - 2534	**30** (35°)
	N	3874 - 2636	**60** (56°)

Optics & accessories: (pag 150)

Pound_T|DynamicWhite|powerLED|220-240VAC|15WDC-17,5WAC(xchannel)






IP20 DALI 2 DW DT8

	Cct		Opt
CRI 90			
WH **84167**	**D**	2700K - 5700K Dynamic White	**15** (19°)
BB **84168**			**30** (37°)
			60 (63°)

Optics: (pag 150)

Pound_T | arrayLED | 220-240 V AC | 23 W DC - 26 W AC





IP20 Technology Partner SILVAIR

	Cct	lm S - lm D	Opt
CRI 98 - Specialty			
WH **83805**	**W**	2748 - 1985	**15** (19°)
BB **83806**			**30** (35°)
			60 (56°)
CRI 98 - Fidelity			
WH **83807**	**M**	2827 - 1917	**15** (19°)
BB **83808**	**W**	2892 - 1963	**30** (35°)
	N	3075 - 2088	**60** (56°)
CRI 90 - Balance			
WH **83809**	**M**	3139 - 2130	**15** (19°)
BB **83810**	**W**	3287 - 2231	**30** (35°)
	N	3418 - 2319	**60** (56°)


Optics & accessories: (pag 150)

Colors **Cct**

WH White **M** 2700 **N** 4000
BB Black **W** 3000 **D** 2700 - 5700

Pound_T | arrayLED | 220-240 V AC | 23 W DC - 26 W AC






IP20

D.O.B.


	Cct	lm S - lm D	Opt
CRI 98 - Specialty			
WH **82412**	**W**	2748 - 1985	**15** (19°)
BB **82413**			**30** (35°)
			60 (56°)
CRI 98 - Fidelity			
WH **82410**	**M**	2827 - 1917	**15** (19°)
BB **82411**	**W**	2892 - 1963	**30** (35°)
	N	3075 - 2088	**60** (56°)
CRI 90 - Balance			
WH **82229**	**M**	3139 - 2130	**15** (19°)
BB **82230**	**W**	3287 - 2231	**30** (35°)
	N	3418 - 2319	**60** (56°)

Optics & accessories: (pag 150)



Pound_T | arrayLED | 220-240 V AC | 34 W DC - 39 W AC






IP20

	Cct	lm S - lm D	Opt
CRI 98 - Specialty			
WH **81641**	**W**	4196 - 3165	**15** (17°)
BB **81642**			**30** (24°)
			60 (47°)
CRI 98 - Fidelity			
WH **81639**	**M**	4460 - 3271	**15** (17°)
BB **81640**	**W**	4416 - 3332	**30** (24°)
	N	4695 - 3476	**60** (47°)
CRI 90 - Balance			
WH **81637**	**M**	4956 - 3635	**15** (17°)
BB **81638**	**W**	5019 - 3786	**30** (24°)
	N	5216 - 3861	**60** (47°)

Optics & accessories: (pag 150)

Pound_T | arrayLED | 220-240 V AC | 34 W DC - 39 W AC






IP20 DALI DALI 2 PUSH

	Cct	lm S - lm D	Opt
CRI 98 - Specialty			
WH **81756**	**W**	4196 - 3165	**15** (17°)
BB **81757**			**30** (24°)
			60 (47°)
CRI 98 - Fidelity			
WH **81754**	**M**	4460 - 3271	**15** (17°)
BB **81755**	**W**	4416 - 3332	**30** (24°)
	N	4695 - 3476	**60** (47°)
CRI 90 - Balance			
WH **81752**	**M**	4956 - 3635	**15** (17°)
BB **81753**	**W**	5019 - 3786	**30** (24°)
	N	5216 - 3861	**60** (47°)

Optics & accessories: (pag 150)

Pound_T | arrayLED | 220-240 V AC | 32,5 W DC - 37,5 W AC






IP20 Technology Partner SILVAIR

	Cct	lm S - lm D	Opt
CRI 98 - Specialty			
WH **83811**	**W**	4014 - 3029	**15** (17°)
BB **83812**			**30** (24°)
			60 (47°)
CRI 98 - Fidelity			
WH **83823**	**M**	4266 - 3130	**15** (17°)
BB **83824**	**W**	4225 - 3188	**30** (24°)
	N	4491 - 3326	**60** (47°)
CRI 90 - Balance			
WH **83825**	**M**	4741 - 3478	**15** (17°)
BB **83826**	**W**	4801 - 3623	**30** (24°)
	N	4990 - 3696	**60** (47°)

Optics & accessories: (pag 150)

Pound_T | arrayLED | 220-240 V AC | 32,5 W DC - 37,5 W AC





IP20 D.O.B.

	Cct	lm S - lm D	Opt
CRI 98 - Specialty			
WH **82416**	**W**	4014 - 3029	**15** (17°)
BB **82417**			**30** (24°)
			60 (47°)
CRI 98 - Fidelity			
WH **82414**	**M**	4266 - 3130	**15** (17°)
BB **82415**	**W**	4225 - 3188	**30** (24°)
	N	4491 - 3326	**60** (47°)
CRI 90 - Balance			
WH **82231**	**M**	4741 - 3478	**15** (17°)
BB **82232**	**W**	4801 - 3623	**30** (24°)
	N	4990 - 3696	**60** (47°)

Optics & accessories: (pag 150)

Colors


WH White
BB Black

Cct

M 2700 **N** 4000
W 3000

Pound Focus | arrayLED | 220-240 V AC | 13 W DC - 15,5 W AC






IP20 — DALI 2 PUSH

	Cct	lm S - lm D	Opt
CRI 98 - Fidelity			
WH **82422**	**M**	1502 - On req	**85** (14°-47°)
BB **82423**	**W**	1559 - On req	
	N	1676 - On req	
CRI 90 - Balance			
WH **81987**	**M**	1669 - On req	**85** (14°-47°)
BB **81988**	**W**	1771 - On req	
	N	1863 - On req	

Accessories: (pag 150)

Pound Focus | arrayLED | 220-240 V AC | 13 W DC - 15,5 W AC






IP20 — Technology Partner SILVAIR

	Cct	lm S - lm D	Opt
CRI 98 - Fidelity			
WH **83827**	**M**	1502 - On req	**85** (14°-47°)
BB **83828**	**W**	1559 - On req	
	N	1676 - On req	
CRI 90 - Balance			
WH **83829**	**M**	1669 - On req	**85** (14°-47°)
BB **83830**	**W**	1771 - On req	
	N	1863 - On req	

Accessories: (pag 150)

Pound Focus | arrayLED | 220-240 V AC | 13 W DC - 15,5 W AC






IP20 — D.O.B.

	Cct	lm S - lm D	Opt
CRI 98 - Fidelity			
WH **82444**	**M**	1338 - On req	**85** (14°-47°)
BB **82445**	**W**	1389 - On req	
	N	1493 - On req	
CRI 90 - Balance			
WH **82105**	**M**	1487 - On req	**85** (14°-47°)
BB **82106**	**W**	1578 - On req	
	N	1660 - On req	

Accessories: (pag 150)

Pound Focus | arrayLED | 220-240 V AC | 23 W DC - 26 W AC






IP20 — DALI 2 PUSH

	Cct	lm S - lm D	Opt
CRI 98 - Fidelity			
WH **82438**	**M**	2827 - On req	**85** (16°-65°)
BB **82439**	**W**	2892 - On req	
	N	3075 - On req	
CRI 90 - Balance			
WH **81989**	**M**	3139 - On req	**85** (16°-65°)
BB **81990**	**W**	3287 - On req	
	N	3418 - On req	

Accessories: (pag 150)

Pound Focus | arrayLED | 220-240 V AC | 23 W DC - 26 W AC





IP20 — Technology Partner SILVAIR

	Cct	lm S - lm D	Opt
CRI 98 - Fidelity			
WH **83831**	**M**	2827 - On req	**85** (16°-65°)
BB **83832**	**W**	2892 - On req	
	N	3075 - On req	
CRI 90 - Balance			
WH **83833**	**M**	3139 - On req	**85** (16°-65°)
BB **83834**	**W**	3287 - On req	
	N	3418 - On req	

Accessories: (pag 150)

Colors


WH White
BB Black

Cct

M 2700 **N** 4000
W 3000

Pound Focus | arrayLED | 220-240 V AC | 23 W DC - 29 W AC






IP20 D.Q.B.

	Cct	lm S - lm D	Opt
CRI 98 - Fidelity			
WH **82446**	**M**	2827 - On req	**85** (16°-65°)
BB **82447**	**W**	2892 - On req	
	N	3075 - On req	
CRI 90 - Balance			
WH **82107**	**M**	3139 - On req	**85** (16°-65°)
BB **82108**	**W**	3287 - On req	
	N	3418 - On req	

Accessories: (pag 150)

Pound Focus | arrayLED | 220-240 V AC | 32,5 W DC - 37 W AC






IP20 DALI 2 DALI PUSH

	Cct	lm S - lm D	Opt
CRI 98 - Fidelity			
WH **82440**	**M**	4266 - On req	**85** (17°-60°)
BB **82441**	**W**	4225 - On req	
	N	4491 - On req	
CRI 90 - Balance			
WH **81991**	**M**	4741 - On req	**85** (17°-60°)
BB **81992**	**W**	4801 - On req	
	N	4990 - On req	

Accessories: (pag 150)

Pound Focus | arrayLED | 220-240 V AC | 32,5 W DC - 37 W AC






IP20 Technology Partner SILVAIR

	Cct	lm S - lm D	Opt
CRI 98 - Fidelity			
WH **83835**	**M**	4266 - On req	**85** (17°-60°)
BB **83836**	**W**	4225 - On req	
	N	4491 - On req	
CRI 90 - Balance			
WH **83839**	**M**	4741 - On req	**85** (17°-60°)
BB **83840**	**W**	4801 - On req	
	N	4990 - On req	

Accessories: (pag 150)

Pound Focus | arrayLED | 220-240 V AC | 32,5 W DC - 37 W AC





IP20 D.Q.B.

	Cct	lm S - lm D	Opt
CRI 98 - Fidelity			
WH **82448**	**M**	4266 - On req	**85** (17°-60°)
BB **82449**	**W**	4225 - On req	
	N	4491 - On req	
CRI 90 - Balance			
WH **82109**	**M**	4741 - On req	**85** (17°-60°)
BB **82110**	**W**	4801 - On req	
	N	4990 - On req	

Accessories: (pag 150)

Colors **Cct**

WH White **M** 2700 **N** 4000
BB Black **W** 3000


CARIVERONA FOUNDATION
Verona (Italy)

Photography:
Francesca Parolin



Pound Shaper_medium | arrayLED | 220-240 V AC | 11 W DC - 13 W AC






IP20 DALI 2 DALI PUSH

	Cct	lm S - lm D	Opt
CRI 98 - Fidelity			
WH **76661**	**M**	1338 - On req	**66** (Shaper Medium)
BB **76662**	**W**	1389 - On req	
	N	1493 - On req	

Accessories: (pag 150)

Pound Shaper_medium | arrayLED | 220-240 V AC | 11 W DC - 13 W AC






IP20 Technology Partner SILVAIR

	Cct	lm S - lm D	Opt
CRI 98 - Fidelity			
WH **76665**	**M**	1338 - On req	**66** (Shaper Medium)
BB **76666**	**W**	1389 - On req	
	N	1493 - On req	

Accessories: (pag 150)

Pound Shaper_medium | arrayLED | 220-240 V AC | 11 W DC - 13 W AC






IP20 D.O.B.

	Cct	lm S - lm D	Opt
CRI 98 - Fidelity			
WH **76669**	**M**	1338 - On req	**66** (Shaper Medium)
BB **76670**	**W**	1389 - On req	
	N	1493 - On req	

Accessories: (pag 150)

Pound Shaper_distance | arrayLED | 220-240 V AC | 11 W DC - 13 W AC






IP20 DALI 2 DALI PUSH

	Cct	lm S - lm D	Opt
CRI 98 - Fidelity			
WH **76659**	**M**	1338 - On req	**66** (Shaper Long)
BB **76660**	**W**	1389 - On req	
	N	1493 - On req	

Accessories: (pag 150)

Pound Shaper_distance | arrayLED | 220-240 V AC | 11 W DC - 13 W AC






IP20 Technology Partner SILVAIR

	Cct	lm S - lm D	Opt
CRI 98 - Fidelity			
WH **76663**	**M**	1338 - On req	**66** (Shaper Long)
BB **76664**	**W**	1389 - On req	
	N	1493 - On req	

Accessories: (pag 150)

Pound Shaper_distance | arrayLED | 220-240 V AC | 11 W DC - 13 W AC





IP20 D.O.B.

	Cct	lm S - lm D	Opt
CRI 98 - Fidelity			
WH **76667**	**M**	1338 - On req	**66** (Shaper Long)
BB **76668**	**W**	1389 - On req	
	N	1493 - On req	


Accessories: (pag 150)

Colors **Cct**

WH White **M** 2700 **N** 4000
BB Black **W** 3000

Pound Shaper_short | arrayLED | 220-240 V AC | 27 W DC - 30 W AC






IP20 NEW — DALI 2 DALI PUSH

	Cct	lm S - lm D	Opt
CRI 98 - Fidelity			
WH **76052**	**M**	3658 - On req	**66** (Shaper Short)
BB **76053**	**W**	3622 - On req	
	N	3851 - On req	

Accessories: (pag 150)

Pound Shaper_short | arrayLED | 220-240 V AC | 27 W DC - 30 W AC






IP20 NEW — Technology Partner SILVAIR

	Cct	lm S - lm D	Opt
CRI 98 - Fidelity			
WH **76054**	**M**	3658 - On req	**66** (Shaper Short)
BB **76055**	**W**	3622 - On req	
	N	3851 - On req	

Accessories: (pag 150)

Pound Shaper_short | arrayLED | 220-240 V AC | 27 W DC - 30 W AC






IP20 NEW — D.O.B.

	Cct	lm S - lm D	Opt
CRI 98 - Fidelity			
WH **76056**	**M**	3658 - On req	**66** (Shaper Short)
BB **76057**	**W**	3622 - On req	
	N	3851 - On req	

Accessories: (pag 150)

Pound Shaper_distance | arrayLED | 220-240 V AC | 27 W DC - 30 W AC






IP20 — DALI 2 DALI PUSH

	Cct	lm S - lm D	Opt
CRI 98 - Fidelity			
WH **82072**	**M**	3658 - On req	**66** (Shaper Long)
BB **82114**	**W**	3622 - On req	
	N	3851 - On req	

Accessories: (pag 150)

Pound Shaper_distance | arrayLED | 220-240 V AC | 27 W DC - 30 W AC






IP20 — Technology Partner SILVAIR

	Cct	lm S - lm D	Opt
CRI 98 - Fidelity			
WH **83899**	**M**	3658 - On req	**66** (Shaper Long)
BB **83900**	**W**	3622 - On req	
	N	3851 - On req	

Accessories: (pag 150)

Pound Shaper_distance | arrayLED | 220-240 V AC | 27 W DC - 30 W AC






IP20 — D.O.B.

	Cct	lm S - lm D	Opt
CRI 98 - Fidelity			
WH **82121**	**M**	3658 - On req	**66** (Shaper Long)
BB **82122**	**W**	3622 - On req	
	N	3851 - On req	


Accessories: (pag 150)



Profiling Report




Pound Shaper_medium 11W





Pound Shaper_distance 11W



Colors **Cct**

WH White **M** 2700 **N** 4000
BB Black **W** 3000

POLITTICO DI SAN MARTINO
Treviglio, Bergamo (Italy)

Lighting designer:
Studio Switch

Photography:
Andrea Martiradonna



Optics



TR **99805** Spot
TR **99806** Flood
TR **99807** W.Flood
suitable for: Pound_T 13W



TR **C-U300015** Spot
TR **C-U300016** Flood
TR **C-U300017** W.Flood
suitable for: Pound_T 32,5W - 34W



TR **99827** Spot
TR **99828** Flood
TR **99829** W.Flood
suitable for: Pound_T 23W / 26W / 8W (Dynamic White)



TR **99808** Spot
TR **99809** Flood
TR **99810** W.Flood
suitable for: Pound_T 15W (Dynamic White)


Accessories

Adamus-T



WH **C-E700031** Controller DALI-TWIL
BB **C-E700008**


suitable for: Pound DALI2
Pag. 932



TR **99775** Elliptical filter (a)
suitable for: Pound_T 13W

TR **99781** Elliptical filter (a)
suitable for: Pound_T 23W / 26W

TR **C-U300013** Elliptical filter (b)
Not compatible with optics 60
suitable for: Pound_T 32,5W / 34W



BB **99776** Honeycomb (b)
suitable for: Pound_T 13W

BB **99780** Honeycomb (b)
suitable for: Pound_T 23W / 26W


BB **C-U300014** Honeycomb (a)
suitable for: Pound_T 32,5W / 34W



BB **99777** Cross louvre
suitable for: Pound_T 13W

BB **99779** Cross louvre
suitable for: Pound_T 23W / 26W

BB **C-U300031** Cross louvre
suitable for: Pound_T 32,5W / 34W



BB **99774** Cylindrical screen
suitable for: Pound_T 13W

BB **99783** Cylindrical screen
suitable for: Pound_T 23W / 26W

BB **C-U300029** Cylindrical screen
suitable for: Pound_T 32,5W / 34W



BB **99773** 45° Cylindrical screen
suitable for: Pound_T 13W

BB **99782** 45° Cylindrical screen
suitable for: Pound_T 23W / 26W

BB **C-U300030** 45° Cylindrical screen
suitable for: Pound_T 32,5W / 34W



BB **99853** Gobo accessory
suitable for: Pound Shaper 27W

Colors
BB Black
TR Transparent

BHARTIYA
Milan (Italy)

Project: Architect
Cristina Broggi

Photography:
Andrea Badoni Initial content



OPTUS

Aluminium body



Extensive range of products
The Optus range of products comes in three different application: recessed (Optus_EX), wall-mounted (Optus_W) and track-mounted projector (Optus_T). Given its unmistakable design, it becomes an effective tool when working in spaces with several applications while maintaining the same product design.

High Efficiency





Optus_W2
Optus_W3
Page 160

	_T
W	8,5-10
mm	**Ø 75**
Cct	2700-3000-4000
Opt	**Ulta Spot, Spot** **Medium Flood** **Wide Flood**
Elec.	On/Off-DALI 2-Push
Col.	WH BB

	_T
W	16-24
mm	**Ø 95**
Cct	2700-3000-4000
Opt	**Spot** **Flood** **Wide Flood**
Elec.	On/Off-DALI 2-Push
Col.	WH BB

	_Ww
W	17-27
mm	**Ø 90-105**
Cct	2700-3000-4000
Opt	**Adjustable Wall Washer**
Elec.	On/Off DALI 2 - D.O.B Bluetooth
Col.	WH BB

Optus family

Optus_EX



125

The Optus_T collection is updated with a new generation of high-efficiency LEDs, designed to offer maximum illumination and versatility. Thanks to the easy interchangeability of the optics and accessories, you can customize the lighting by creating extremely precise and targeted light effects, ensuring maximum comfort. The ultra-compact and minimalist design makes it perfect for a wide range of settings, from retail to museums.




Optics: Spot


Optics: Flood/M.Flood


Optics: W.Flood

Interchangeable accessories and optics


Focal Kit
(min 16° / max 42°)


Honeycomb



Cross louvre



Elliptical filter



45° Cylindrical screen


Cylindrical screen

Diode varieties
The Optus_T range of products offers the highest combination-source degree, given that it is fit for LED Balance - CRI 90, Specialty - CRI 98 and Fidelity - CRI 98 diodes. This allows obtaining maximum versatility of use, given that Optus_T can be installed in various environments ranging from museums to retail, depending on the specific type of source chosen.








5000 K on request

Optus_Ww
Optus_Ww is equipped with the new technology for light control through the mechanical Sliding Kickers and Sliding Hood systems located in the body of the projector. The technology developed by the i-LèD technical offices rewrites the technical lighting rules and allows precise shaping at any distance. Optus_Ww is adaptive to the space and to the object being lit.





EUROSPAR - La Cooperativa di Cortina
Cortina d'Ampezzo - Belluno (Italy)


Project: Franco Bolzonello, Technical Director of the affiliated Aspiag Service division

Executive Project:
Carlo Saccardo, BS89 Architetti

Photography:
Studio De Sandre

Optus_T | V2 | powerLED | 220-240 V AC | 8,5 W DC - 10 W AC






IP20 NEW

	Fin	Cct	lm S - lm D	Opt
CRI 90 - Balance				
C00993	**WH**	**M**	683 - 514	**US** (6°)
	BB	**W**	731 - 551	
		N	788 - 594	

Optics & accessories: (pag 161)

Optus_T | V2 | arrayLED | 220-240 V AC | 10 W DC - 12 W AC






IP20 NEW

	Fin	Cct	lm S - lm D	Opt
CRI 98 - Specialty				
C00995	**WH**	**W**	1718 - 1200	**SP** (17°)
	BB			**ML** (35°)
				WF (52°)
CRI 98 - Fidelity				
C00996	**WH**	**M**	1735 - 1211	**SP** (17°)
	BB	**W**	1824 - 1273	**ML** (35°)
		N	1822 - 1270	**WF** (52°)
CRI 90 - Balance				
C00997	**WH**	**M**	1817 - 1268	**SP** (17°)
	BB	**W**	1892 - 1321	**ML** (35°)
		N	1920 - 1347	**WF** (52°)

Optics & accessories: (pag 161)

Optus_T | V2 | powerLED | 220-240 V AC | 8,5 W DC - 10 W AC






IP20 NEW **DALI 2 DALI PUSH**

	Fin	Cct	lm S - lm D	Opt
CRI 90 - Balance				
C00994	**WH**	**M**	683 - 514	**US** (6°)
	BB	**W**	731 - 551	
		N	788 - 594	

Optics & accessories: (pag 161)

Optus_T | V2 | arrayLED | 220-240 V AC | 10 W DC - 12 W AC






IP20 NEW **DALI 2 DALI PUSH**

	Fin	Cct	lm S - lm D	Opt
CRI 98 - Specialty				
C00998	**WH**	**W**	1718 - 1200	**SP** (17°)
	BB			**ML** (35°)
				WF (52°)
CRI 98 - Fidelity				
C00999	**WH**	**M**	1735 - 1211	**SP** (17°)
	BB	**W**	1824 - 1273	**ML** (35°)
		N	1822 - 1270	**WF** (52°)
CRI 90 - Balance				
C01000	**WH**	**M**	1817 - 1268	**SP** (17°)
	BB	**W**	1892 - 1321	**ML** (35°)
		N	1920 - 1347	**WF** (52°)

Optics & accessories: (pag 161)

Optus_T | V2 | arrayLED | 220-240 V AC | 16 W DC - 18 W AC






IP20 NEW

	Fin		Cct	lm S - lm D	Opt	
CRI 98 - Specialty						
C00434	**WH**		**W**	2723 - 2037	**SP**	(15°)
	BB				**FL**	(24°)
					WF	(51°)
CRI 98 - Fidelity						
C00433	**WH**		**M**	2750 - 2057	**SP**	(15°)
	BB		**W**	2891 - 2163	**FL**	(24°)
			N	2888 - 2163	**WF**	(51°)
CRI 90 - Balance						
C00432	**WH**		**M**	2692 - 2154	**SP**	(15°)
	BB		**W**	2818 - 2245	**FL**	(24°)
			N	2930 - 2267	**WF**	(51°)

Optics & accessories: (pag 161)

Optus_T | V2 | arrayLED | 220-240 V AC | 16 W DC - 18 W AC






IP20 NEW DALI 2 DALI PUSH

	Fin		Cct	lm S - lm D	Opt	
CRI 98 - Specialty						
C00438	**WH**		**W**	2723 - 2037	**SP**	(15°)
	BB				**FL**	(24°)
					WF	(51°)
CRI 98 - Fidelity						
C00436	**WH**		**M**	2750 - 2057	**SP**	(15°)
	BB		**W**	2891 - 2163	**FL**	(24°)
			N	2888 - 2163	**WF**	(51°)
CRI 90 - Balance						
C00435	**WH**		**M**	2692 - 2154	**SP**	(15°)
	BB		**W**	2818 - 2245	**FL**	(24°)
			N	2930 - 2267	**WF**	(51°)

Optics & accessories: (pag 161)

Optus_T | V2 | arrayLED | 220-240 V AC | 24 W DC - 27 W AC






IP20 NEW

	Fin		Cct	lm S - lm D	Opt	
CRI 98 - Specialty						
C00443	**WH**		**W**	3749 - 3051	**SP**	(17°)
	BB				**FL**	(24°)
					WF	(48°)
CRI 98 - Fidelity						
C00441	**WH**		**M**	3790 - 3090	**SP**	(17°)
	BB		**W**	3978 - 3237	**FL**	(24°)
			N	3974 - 3237	**WF**	(48°)
CRI 90 - Balance						
C00440	**WH**		**M**	3829 - 3226	**SP**	(17°)
	BB		**W**	3877 - 3361	**FL**	(24°)
			N	4030 - 3429	**WF**	(48°)

Optics & accessories: (pag 161)

Optus_T | V2 | arrayLED | 220-240 V AC | 24 W DC - 27 W AC





IP20 NEW DALI 2 DALI PUSH

	Fin		Cct	lm S - lm D	Opt	
CRI 98 - Specialty						
C00449	**WH**		**W**	3749 - 3051	**SP**	(17°)
	BB				**FL**	(24°)
					WF	(48°)
CRI 98 - Fidelity						
C00448	**WH**		**M**	3790 - 3090	**SP**	(17°)
	BB		**W**	3978 - 3237	**FL**	(24°)
			N	3974 - 3237	**WF**	(48°)
CRI 90 - Balance						
C00446	**WH**		**M**	3829 - 3226	**SP**	(17°)
	BB		**W**	3877 - 3361	**FL**	(24°)
			N	4030 - 3429	**WF**	(48°)

Optics & accessories: (pag 161)

Colors

White
Black

Cct

M 2700 **N** 4000
W 3000



CAP Holding
Milan (Italy)


Project: Studio Claudio Lucchin & Architetti Associati

Interior design, furnishings and lamps: Alterstudio Partners

Photography: Margherita Nardi

Optus_Ww | arrayLED | 220-240 V AC | 17 W DC - 19 W AC






IP20

	Fin	Cct	lm S - lm D	Opt
L 158 mm - CRI 90 - Balance - On-Off				
C00473	**WH**	**M**	2026 - 1244	**AW** (Adj Ww)
	BB	**W**	2174 - 1280	
		N	2520 - 1383	
L 250 mm - CRI 90 - Balance - DALI				**DALI** 2
C00474	**WH**	**M**	2026 - 1244	**AW** (Adj Ww)
	BB	**W**	2174 - 1280	
		N	2520 - 1383	

Accessories: (pag 161)

Optus_Ww | arrayLED | 220-240 V AC | 17 W DC - 19 W AC






IP20 SILVAIR

	Cct	lm S - lm D	Opt
CRI 90 - Balance - Bluetooth			
WH 83921	**M**	2026 - 1244	**07** (Adj Ww)
BB 83922	**W**	2174 - 1280	
	N	2520 - 1383	

Optics & accessories: (pag 161)

Optus_Ww | arrayLED | 220-240 V AC | 17 W DC - 19 W AC






IP20 D.O.B.

	Cct	lm S - lm D	Opt
CRI 90 - Balance - D.O.B.			
WH 82251	**M**	2026 - 1244	**07** (Adj Ww)
BB 82252	**W**	2174 - 1280	
	N	2520 - 1383	

Accessories: (pag 161)

Optus_Ww | arrayLED | 220-240 V AC | 27 W DC - 30 W AC






IP20

	Fin	Cct	lm S - lm D	Opt
L 158 mm - CRI 90 - Balance - On-Off				
C00475	**WH**	**M**	3299 - 1945	**AW** (Adj Ww)
	BB	**W**	3540 - 2087	
		N	4103 - 2253	
L 250 mm - CRI 90 - Balance - DALI				**DALI** 2
C00476	**WH**	**M**	3299 - 1945	**AW** (Adj Ww)
	BB	**W**	3540 - 2087	
		N	4103 - 2253	

Accessories: (pag 161)

Optus_Ww | arrayLED | 220-240 V AC | 27 W DC - 30 W AC






IP20 SILVAIR

	Cct	lm S - lm D	Opt
CRI 90 - Balance - Bluetooth			
WH 83923	**M**	3299 - 1945	**07** (Adj Ww)
BB 83924	**W**	3540 - 2087	
	N	4103 - 2253	

Accessories: (pag 161)

Optus_Ww | arrayLED | 220-240 V AC | 27 W DC - 30 W AC





IP20 D.O.B.

	Cct	lm S - lm D	Opt
CRI 90 - Balance - D.O.B.			
WH 82253	**M**	3299 - 1945	**07** (Adj Ww)
BB 82254	**W**	3540 - 2087	
	N	4103 - 2253	

Accessories: (pag 161)

Colors **Cct**

WH White **M** 2700 **N** 4000
BB Black **W** 3000




STUDIO GUASTALLA
Milan (Italy)

Project: Gregorio Pecorelli

Photography:
Marco Reggi

Optus_W2 | arrayLED | 840 mA | 30 W DC







	Cct	lm S - lm D	Opt
CRI 98 - Specialty			
WH **77072**	**W**	2x 2150 - 1556	**15** (18°)
BB **77073**			**30** (38°)
			60 (50°)
CRI 98 - Fidelity			
WH **77074**	**W**	2x 2263 - 1638	**15** (18°)
BB **77075**	**N**	2x 2406 - 1741	**30** (38°)
			60 (50°)
CRI 90 - Balance			
WH **77076**	**M**	2x 2457 - 1784	**15** (18°)
BB **77077**	**W**	2x 2757 - 1869	**30** (38°)
	N	2x 2675 - 1946	**60** (50°)

Electronics: **U1** (pag 160) | Optics & accessories: (pag 161)

Optus_W3 | arrayLED | 1250 mA | 45 W DC





	Cct	lm S - lm D	Opt
CRI 98 - Specialty			
WH **77078**	**W**	3x 2150 - 1556	**15** (18°)
BB **77079**			**30** (38°)
			60 (50°)
CRI 98 - Fidelity			
WH **77080**	**W**	3x 2263 - 1638	**15** (18°)
BB **77081**	**N**	3x 2406 - 1741	**30** (38°)
			60 (50°)
CRI 90 - Balance			
WH **77082**	**M**	3x 2457 - 1784	**15** (18°)
BB **77083**	**W**	3x 2757 - 1869	**30** (38°)
	N	3x 2675 - 1946	**60** (50°)

Electronics: **W1** (pag 160) | Optics & accessories: (pag 161)

Electronics

U1 | Electronics

99135
ON/OFF
1 art.
103 x 58 x h 27
64

83008
0/1-10V, DALI/PUSH
1 art.
124 x 79 x h 22
84

99345
DALI/PUSH
1 art.
210 x 48 x h 28
56

W1 | Electronics

C-E100048
ON/OFF
1 art.
142 x 43 x h 30
53

83008
0/1-10V, DALI/PUSH
1 art.
124 x 79 x h 22
84

Accessories

Adamus-T



WH **C-E700031**
BB **C-E700008**

Controller DALI-TWIL for track

suitable for: Optus DALI2

Optics & Accessories



TR **83348** Spot
TR **83349** Flood
TR **83350** W.Flood
suitable for: Optus_W2 - Optus_W3

TR **C-U100002** Spot
TR **C-U100003** M.Flood
TR **C-U100004** W.Flood
suitable for: Optus_T V2 10W


TR **C-U300009** Spot
TR **C-U300012** Flood
TR **C-U300010** W.Flood
suitable for: Optus_T V2 16W

TR **C-U300015** Spot
TR **C-U300016** Flood
TR **C-U300017** W.Flood
suitable for: Optus_T V2 24W



TR **83347** Focal Kit (min 16° / max 42°)
suitable for: Optus_T V2 10W - Optus_W2 - Optus_W3

TR **C-U300034** Focal Kit (min 16° / max 42°)
suitable for: Optus_T V2 16W - Optus_T V2 24W



BB **99841** Honeycomb (a)
with fixing ring (b)
suitable for: Focal kit **83347**

BB **C-U300014** Honeycomb (a)
without fixing ring (b)
suitable for: Focal kit **C-U300034**



BB **83344** Cross louvre
suitable for: Optus_W2 - Optus_W3

BB **C-U300047** Cross louvre
suitable for: Optus_T V2 10W


BB **C-U300031** Cross louvre
suitable for: Optus_T V2 16W - Optus_T V2 24W



BB **83343** 45° Cylindrical screen
suitable for: Optus_W2 - Optus_W3

BB **C-U300046** 45° Cylindrical screen
suitable for: Optus_T V2 10W

BB **C-U300030** 45° Cylindrical screen
suitable for: Optus_T V2 16W - Optus_T V2 24W



TR **83345** Elliptical filter (a)
suitable for: Optus_W2 - Optus_W3

TR **C-U300044** Elliptical filter (a)
suitable for: Optus_T V2 10W

TR **C-U300007** Elliptical filter (a)
suitable for: Optus_T V2 16W


TR **C-U300013** Elliptical filter (b)
Not compatible with optics WF
suitable for: Optus_T V2 24W



BB **C-U300043** Honeycomb
suitable for: Optus_T V2 10W

BB **C-U300008** Honeycomb
suitable for: Optus_T V2 16W

BB **C-U300014** Honeycomb
suitable for: Optus_T V2 24W




BB **83342** Cylindrical screen
suitable for: Optus_W2 - Optus_W3

BB **C-U300045** Cylindrical screen
suitable for: Optus_T V2 10W

BB **C-U300029** Cylindrical screen
suitable for: Optus_T V2 16W - Optus_T V2 24W

Variable dynamic optics
A unique focal accessory on the market which allows the focus and/or zoom of the light beam to be adjusted using two specific rings. The plug and play installation allows for dynamic and versatile light in any situation.





Focal Kit (min 16° / max 42°)

Colors
BB Black
TR Transparent

SKYLUM_R
TRACK

Body in aluminium. Diffuser in micro-prismatic PMMA (Comfort)



Skylum family

Skylum_R



218

Skylum_Q



222


Track System family


Track System



168


Skylum_R Track Comfort | topLED | UGR<19 | 220-240 V AC | 19 W DC - 22 W AC





IP40 NEW

	Fin	Cct	lm S - lm D	Opt
CRI 90				
C00904	**WH**	**M**	2988 - 2168	**DI** (Diffused UGR<19)
	BB	**W**	3129 - 2270	
DALI 2		**N**	3326 - 2408	
C00905				



Skylum_R Track is a minimalist-shaped lighting fixture with an adapter for electrified tracks. Designed to mark spaces, the light emission is perfectly uniform. Skylum_R Track can diffusely illuminate a work surface below or environments in the office or retail sector, guaranteeing an extraordinary visual comfort.



UGR

Micro-prismatic diffuser Comfort **(UGR<19)**



Colors **Cct**

White **M** 2700 **N** 4000
Black **W** 3000



CELL_WW
TRACK

Aluminium body


Cell family

Cell / Cell_Ww Gypsum Cell	Cell_S
104	226



Cell_Ww Track | powerLED | 220-240 V AC | 19 W DC - 21 W AC





	Fin	Cct	lm S - lm D	Opt
L 158 - CRI 90				
C00470	**WH**	**M**	2198 - 927	**AW** (Adj Ww)
	BB	**W**	2304 - 994	
		N	2852 - 1074	
L 250 - CRI 90 - DALI				
C00472	**WH**	**M**	2198 - 927	**AW** (Adj Ww)
	BB	**W**	2304 - 994	
		N	2852 - 1074	

Accessories

Adamus-T



WH **C-E700031** Controller DALI-TWIL
BB **C-E700008**

suitable for: Cell_Ww track DALI (C00472)


Colors **Cct**

White **M** 2700 **N** 4000
Black **W** 3000

ROLLIP35_T
TRACK


Aluminium profile, polycarbonate diffuser.


Rollip35_Track is a system for continuous line track application with adapter for electrified tracks, designed to mark spaces, without interruptions, with perfectly uniform light emission. Rollip35_Track is able to diffusely light a corridor, a floor below or be used for areas in retail or museum settings.



Rollip family	Rollip_PRO	Rollip_MC	Rollip_MF	Rollip_MS	Rollip_MP
					
	305	306-308	311-313	316-317	320-321

Rollip35_Track | topLED | 220-240 V AC






EL


* The driver contained in the device complies with IEC 61347-2-13 annex J, and can therefore be powered by centralized power supply systems.

IP40 NEW

	Fin	Cct	lm S - lm D	Opt
CRI 90 - 13 W DC - 16 W AC				
C00878	**WH**	**M**	1993 - 1496	**DI** Diffused
	BB	**W**	2101 - 1575	
DALI 2*		**N**	2244 - 1682	
C00879				
CRI 90 - 25 W DC - 27,5 W AC				
C00880	**WH**	**M**	3607 - 2708	**DI** Diffused
	BB	**W**	3802 - 2850	
DALI 2*		**N**	4062 - 3044	
C00881				

HORIZONTAL BALANCING





If the appliance is not aligned, the adjustment system can be used to restore it perfectly to the horizontal axis



Colors White, Black

Cct **M** 2700 **N** 4000 **W** 3000


TRACK SYSTEM

Aluminium body


Earthing continuity
For proper earthing of all accessories that contribute to form a three-phase track system, the continuity of the earthing line between each element is crucial. As shown by the track section herebeside, the position of the earthing line (red) is asymmetric to the central axis of the track; based on this structural difference one can distinguish the right part (including the earthing line) which binds the introduction of all accessories. The positioning of the earth conductor, must be consequential between the accessory and the electrified track structure.

Configuration
For a correct design, we suggest to create the structure with top plan view, as shown in the drawing below:


Axonometric view




Plan view




Track system
Three-phase track +
DALI | Ceiling/Suspension




Track system
Three-phase track +
DALI | Recessed




PLAN VIEW FROM ABOVE







Land line



The “H”, “I” and “L” accessories can be used in both directions.




Track system | Three-phase track + DALI



	1 M	2 M	3 M
WH	83336	83337	83338
BB	83339	83340	83341

Track system | Recessed three-phase track + DALI




	1 M	2 M	3 M
WH	80990	80991	80992
BB	80993	80994	80995

Head power supply




	Power DX	Power Sx
WH	81033	81036
BB	81034	81037

Internal electrical joint




WH	81039
BB	81040

Central joint



WH	81042
BB	81043

L-shaped joint




	INT	EXT
WH	81045	81048
BB	81046	81049

Flexible joint



WH	81066
BB	81067

X-shaped joint



WH	81063
BB	81064

T-shaped joint




	EXT/SX	EXT/DX
WH	81051	81054
BB	81052	81055

T-shaped joint




	INT/SX	INT/DX
WH	81057	81060
BB	81058	81061

Sealing cap | Ceiling/Suspension



WH	80999
BB	81000

Sealing cap | Recessed




WH	81002
BB	81003

Suspension



	1.5 M	5 M
WH	81012	81013
BB	81014	81015

Suspension with adjustment devices



	1.5 M	5 M
WH	81006	81007
BB	81008	81009

Rigid suspension




	1 M
WH	81021
BB	81022

Tensioner clip for rigid suspension




WH	81018
BB	81019

Ceiling-mounted fixing bracket




AM	81086
WH	81087
BB	81088

Stiffening bracket




AM	81024
WH	81025
BB	81026

Power supply head cover




WH	81069
BB	81070

Central joint cover




WH	81072
BB	81073

L-shaped joint cover




WH	81075
BB	81076

T-shaped joint cover



WH	81078
BB	81079

X-shaped joint cover




WH	81081
BB	81082

Colors


WH White AM Anodised Aluminium
BB Black

Three-phase track cover



WH **83249**
BB **83250**

Three-phase track adaptor *



WH **81091**
BB **81093**

*Use for tapping line voltage only.

Power supply head gasket




WH **81084**
BB **81085**

Conductor cutting pliers




AM **81005**

Three-phase track adaptor + DALI *




WH **81094**
BB **81095**
* Use for tapping line voltage and/or DALI signal only.

RUBBER 3D, **NOW ALSO ON TRACK SYSTEM**




Track System power supply for Rubber 3D



WH **C-E300007** On/Off - Max 50W DC - IP20
BB **C-E300008** On/Off - Max 50W DC - IP20
suitable for: Rubber 3D

Input 220-240V DC - Output 24V DC - Class 2


Rubber 3D fixing profile for Track System



TR **C-K100022** 100 mm - 27 mm - 15 mm

suitable for: Rubber 3D

Rubber 3D fixing profile for Track System



TR **C-K100021** 2000 mm - 27 mm - 15 mm

suitable for: Rubber 3D

Colors

WH White AM Anodised Aluminium
BB Black TR Transparent

CREEK

Structure in EPS
Aluminium projector

Optus family **Optus_EX**




126



Creek Optus | powerLED | 700 mA | 8,5 W DC






	Fin	Cct	lm S - lm D	Opt
CRI 90 - Balance				
C01133	**WH**	**M**	683 - 514	**US** (6°)
	BB	**W**	731 - 551	
		N	788 - 594	

Electronics: **J1** (pag 174) | Accessories: (pag 174)

Creek Optus | arrayLED | 400 mA | 15 W DC






	Cct	lm S - lm D	Opt
CRI 90 - Balance			
WH 82731	**M**	2214 - 1677	**15** (18°)
BB 82732	**W**	2318 - 1757	**30** (38°)
	N	2411 - 1829	**60** (50°)

Electronics: **P1** (pag 174) | Optics & accessories: (pag 174)

Creek Optus | arrayLED | 700 mA | 24 W DC






	Cct	lm S - lm D	Opt
CRI 90 - Balance			
WH 82733	**M**	3829 - 3013	**15** (17°)
BB 82734	**W**	3877 - 3106	**30** (25°)
	N	4030 - 3300	**60** (53°)

Electronics: **T1** (pag 174) | Optics & accessories: (pag 174)

Creek Optus | arrayLED | 950 mA | 34 W DC





	Cct	lm S - lm D	Opt
CRI 90 - Balance			
WH 82735	**M**	4956 - 3951	**15** (17°)
BB 82736	**W**	5019 - 4011	**30** (24°)
	N	5216 - 4172	**60** (48°)

Electronics: **V1** (pag 174) | Optics & accessories: (pag 174)

Colors


WH White
BB Black

Cct

M 2700 **N** 4000
W 3000

Upper cover guard






	L mm
BB 99927	500
BB 99928	1000


Sealing head






BB 99929

Linear Profiles _P (pair)






	L mm
WH 82728	500
WH 82729	1000
WH 82730	1500

Integrated architecture solutions

1 | Linear profiles (500 mm)
2 | Linear profiles (1000 mm)
3 | Linear profiles (1500 mm)
4 | Mechanical joint*
5 | Final guard
6 | Linear guard (500 mm)
7 | Linear guard (1000 mm)
8 | Duct Tape

*item supplied by the installer, or available from any building material retailer.



Product installation phase

PHASE 1
Once the structure has been set up in the false ceiling, the lighting body is positioned in the linear casing.





PHASE 2
The fixing is done by interlocking, inserting the end of the base in the internal seat of the profile.



PHASE 3
The process is completed by pressing down on the base near the point where the articulated arm starts.

Colors

WH White
BB Black

Electronics

J1

99735	99147	99733	C-E100012	C-E100016
ON/OFF 1 art. 134 x 37 x h 31 48	ON/OFF 2 - 3 art. 103 x 58 x h 27 64	0/1-10V 1 art. 134 x 37 x h 31 48	DALI/PUSH 1 art. 134 x 37 x h 31 48	DALI/PUSH 2 - 3 art. 131 x 44 x h 30 54

T1

99147	83008	C-E100016
ON/OFF 1 art. 103 x 58 x h 27 64	0/1-10V, DALI/PUSH 1 art. 124 x 79 x h 22 84	DALI/PUSH 1 art. 131 x 44 x h 30 54

P1

99734	99732	83322
ON/OFF 1 art. 149 x 37 x h 31 48	0/1-10V 1 art. 149 x 37 x h 31 48	DALI/PUSH 1 art. 149 x 37 x h 31 48

V1

99239	83008	99345
ON/OFF 1 art. 103 x 58 x h 27 64	0/1-10V, DALI/PUSH 1 art. 124 x 79 x h 22 84	DALI/PUSH 1 art. 210 x 48 x h 28 56

Optics



TR **99827** Spot
TR **99828** Flood
TR **99829** W.Flood
suitable for: Creek Optus 15W

TR **99808** Spot
TR **99809** Flood
TR **99810** W.Flood
suitable for: Creek Optus 24W


TR **C-U300015** Spot
TR **C-U300016** Flood
TR **C-U300017** W.Flood
suitable for: Creek Optus 34W



TR **99844** Focal Kit (min 16° / max 50°)
suitable for: Creek Optus 15W

TR **99843** Focal Kit (min 16° / max 42°)
suitable for: Creek Optus 24W

TR **C-U300034** Focal Kit (min 16° / max 42°)
suitable for: Creek Optus 34W



BB **99841** Honeycomb (a) with fixing ring (b)
suitable for: Focal kit **99844**


BB **99842** Honeycomb (a) with fixing ring (b)
suitable for: Focal kit **99843**

BB **C-U300014** Honeycomb (a) without fixing ring (b)
suitable for: Focal kit **C-U300034**

Accessories




TR **99781** Elliptical filter
suitable for: Creek Optus 15W



BB **99780** Honeycomb (b)
suitable for: Creek Optus 15W

BB **99798** Honeycomb (b)
suitable for: Creek Optus 24W


BB **C-U300014** Honeycomb (a)
suitable for: Creek Optus 34W



BB **99783** Cylindrical screen
suitable for: Creek Optus 15W

BB **99796** Cylindrical screen
suitable for: Creek Optus 24W

BB **C-U300029** Cylindrical screen
suitable for: Creek Optus 34W



TR **99797** Elliptical filter
suitable for: Creek Optus 24W

TR **C-U300013** Elliptical filter
Not compatible with optics 60
suitable for: Creek Optus 34W



BB **99779** Cross louvre
suitable for: Creek Optus 15W

BB **99799** Cross louvre
suitable for: Creek Optus 24W

BB **C-U300031** Cross louvre
suitable for: Creek Optus 34W



BB **99782** 45° Cylindrical screen
suitable for: Creek Optus 1W

BB **99795** 45° Cylindrical screen
suitable for: Creek Optus 24W

BB **C-U300030** 45° Cylindrical screen
suitable for: Creek Optus 34W

Colors

BB Black
TR Transparent



aDoc MEDICAL CLINIC
Gualdo Tadino - Perugia (Italy)

Project: A25

Photography:
Mattia Micheli



NAVATA

Structure in aluminium

Optus family

Optus_EX



126

Pound family

Pound_BS



236

Pound_BC



236

Pound_S



237

Pound_Wall



237

MAXIMUM VERSATILITY IN EVERY SPACE

The Navata system expands its range of accessories with new, extremely compact bases to offer designers all the benefits of the flexibility making Navata unique to its kind.




INTEGRATED CONTROL SYSTEMS FOR FLEXIBLE LIGHT

The new base with integrated power pack has been designed to allow light fixtures in the Navata collection to be positioned in all restricted architectural contexts, for example cornices, mouldings or nooks. Despite its compact size, the base of the projector houses On/Off, DALI and DALI PUSH configurations.



Base | 198 - 264 V AC | 300mA | 1050mA | Code **99948**



Base | 198 - 264 V AC | 300mA | 1050mA | Code **99938**

NEW MICRO BASE


The new base with remote power pack has been designed to allow light fixtures in the Navata collection to be positioned in all restricted architectural contexts, for example cornices or narrow overhangs. It measures a mere 52x32 mm with a height of 20 mm, and is available in three different finishes, white, black and sand, to be completed with dedicated electronics with On/Off, DALI2 and DALI PUSH control.



Base | Code **98588**

Navata_Optus | powerLED | 700 mA | 8,5 W DC






	Fin	Cct	lm S - lm D	Opt
CRI 90 - Balance				
C01134	**WH**	**M**	683 - 514	**US** (6°)
	BB	**W**	731 - 551	
	SN	**N**	788 - 594	

Base for installation: (pag 181) | Accessories: (pag 183)

Navata_Optus | arrayLED | 450 mA | 16 W DC






	Cct	lm S - lm D	Opt
CRI 98 - Fidelity			
WH **82385**	**M**	2212 - 1601	**15** (18°)
BB **82386**	**W**	2263 - 1638	**30** (38°)
SN **82902**	**N**	2406 - 1741	**60** (50°)
CRI 90 - Balance			
WH **82383**	**M**	2457 - 1784	**15** (18°)
BB **82384**	**W**	2572 - 1869	**30** (38°)
SN **82903**	**N**	2675 - 1946	**60** (50°)

Base for installation: (pag 181) | Optics & accessories: (pag 183)

Navata_Optus | arrayLED | 700 mA | 24 W DC






	Cct	lm S - lm D	Opt
CRI 98 - Fidelity			
WH **82391**	**M**	3446 - 2750	**15** (17°)
BB **82392**	**W**	3412 - 2723	**30** (25°)
SN **82905**	**N**	3627 - 2895	**60** (53°)
CRI 90 - Balance			
WH **82389**	**M**	3829 - 3013	**15** (17°)
BB **82390**	**W**	3877 - 3106	**30** (25°)
SN **82906**	**N**	4030 - 3300	**60** (53°)

Base for installation: (pag 181) | Optics & accessories: (pag 183)

Navata_Optus | arrayLED | 950 mA | 34 W DC





	Cct	lm S - lm D	Opt
CRI 98 - Fidelity			
WH **82397**	**M**	4460 - 3563	**15** (17°)
BB **82398**	**W**	4416 - 3528	**30** (24°)
SN **82908**	**N**	4695 - 3751	**60** (48°)
CRI 90 - Balance			
WH **82395**	**M**	4956 - 3951	**15** (17°)
BB **82396**	**W**	5019 - 4011	**30** (24°)
SN **82909**	**N**	5216 - 4172	**60** (48°)
	C	5059 - 4051	

Base for installation: (pag 181) | Optics & accessories: (pag 183)


CAPPELLA DEL SANTISSIMO
Asolo (Italy)

Photography:
TheStudio

NAVATA OPTUS


The Navata Optus range offers an updated optical range that allows you to enhance the architecture of, for example, a place of worship while respecting its context.
The reduced dimensions of the structure seem to almost disappear and the correctly oriented beams will enhance: domes, vaults, walls, or they will create real paths of light





Navata Pound Shaper medium | arrayLED | 300 mA | 11 W DC






C.C. IP20

	Cct	lm S - lm D	Opt
CRI 98 - Fidelity			
WH **76742**	**M**	1019 - On req	**66** (Shaper Medium)
BB **76743**	**W**	1076 - On req	
SN **76744**	**N**	1182 - On req	

Base for installation: (pag 181)

Navata Pound Shaper distance | arrayLED | 300 mA | 11 W DC






C.C. IP20

	Cct	lm S - lm D	Opt
CRI 98 - Fidelity			
WH **76739**	**M**	1019 - On req	**66** (Shaper Long)
BB **76740**	**W**	1076 - On req	
SN **76741**	**N**	1182 - On req	

Base for installation: (pag 181)

Navata Pound Shaper short | arrayLED | 700 mA | 27 W DC






C.C. IP20 NEW

	Cct	lm S - lm D	Opt
CRI 98 - Fidelity			
WH **77619**	**M**	2636 - On req	**66** (Shaper Short)
BB **77620**	**W**	2785 - On req	
SN **77621**	**N**	3059 - On req	

Base for installation: (pag 181)

Navata Pound Shaper distance | arrayLED | 700 mA | 27 W DC





C.C. IP20


	Cct	lm S - lm D	Opt
CRI 98 - Fidelity			
WH **82631**	**M**	2636 - On req	**66** (Shaper Long)
BB **82632**	**W**	2785 - On req	
SN **82912**	**N**	3059 - On req	

Base for installation: (pag 181)

Profiling report




Pound Shaper_medium 11W





Pound Shaper_distance 11W




Colors


WH White
BB Black
SN Sand

Cct

M 2700 **N** 4000
W 3000

Base | 220-240 V AC | 300 mA | 1050 mA






C.C. IP20 *


WH	**99938**	From 8,5 to 38 W DC
BB	**99943**	From 8,5 to 38 W DC
SN	**83055**	From 8,5 to 38 W DC

C.C. IP20 * DALI 2 DALI PUSH

WH	**99936**	From 8,5 to 38 W DC
BB	**99941**	From 8,5 to 38 W DC
SN	**83054**	From 8,5 to 38 W DC

Base | 220-240 V AC | 300 mA | 1050 mA






C.C. IP20 *


WH	**99948**	From 8,5 to 38 W DC
BB	**99953**	From 8,5 to 38 W DC
SN	**83052**	From 8,5 to 38 W DC

C.C. IP20 * DALI 2 DALI PUSH

WH	**99946**	From 8,5 to 38 W DC
BB	**99951**	From 8,5 to 38 W DC
SN	**83051**	From 8,5 to 38 W DC

Base





WH	**98588**	
BB	**98589**	
SN	**83242**	

To be completed with remote power pack

Electronic: **J1** (8,5W) - **FI** (11W) - **FJ** (16W) - **FK** (24/27W) - **FL** (34W) (pag 183)

EL

* The driver contained in the device complies with IEC 61347-2-13 annex J, and can therefore be powered by centralized power supply systems.

Colors

WH White SN Sand
BB Black



AUSTRIAN NATIONAL LIBRARY
Vienna (Austria)

Project: Mr. Ing. Wolfgang Zellermayer

Lighting Designer:
Helmut Regvart, Lighting Design Austria

Photography:
We Feel

Optics & Accessories



TR **99827** Spot
TR **99828** Flood
TR **99829** W.Flood
suitable for: Navata_Optus 16W

TR **99808** Spot
TR **99809** Flood
TR **99810** W.Flood
suitable for: Navata_Optus 24W


TR **C-U300015** Spot
TR **C-U300016** Flood
TR **C-U300017** W.Flood
suitable for: Navata_Optus 34W



TR **99844** Focal Kit (min 16° / max 50°)
suitable for: Navata_Optus 16W

TR **99843** Focal Kit (min 16° / max 42°)
suitable for: Navata_Optus 24W


TR **C-U300034** Focal Kit (min 16° / max 42°)
suitable for: Navata_Optus 34W



BB **99841** Honeycomb (a)
with fixing ring (b)
suitable for: Focal kit **99844**

BB **99842** Honeycomb (a)
with fixing ring (b)
suitable for: Focal kit **99843**

BB **C-U300014** Honeycomb (a)
without fixing ring (b)
suitable for: Focal kit **C-U300034**



TR **99781** Elliptical filter (a)
suitable for: Navata_Optus 16W

TR **99797** Elliptical filter (a)
suitable for: Navata_Optus 24W

TR **C-U300013** Elliptical filter (b)
Not compatible with optics 60
suitable for: Navata_Optus 34W



BB **99779** Cross louvre
suitable for: Navata_Optus 16W

BB **99799** Cross louvre
suitable for: Navata_Optus 24W


BB **C-U300031** Cross louvre
suitable for: Navata_Optus 34W



BB **99782** 45° Cylindrical screen
suitable for: Navata_Optus 16W

BB **99795** 45° Cylindrical screen
suitable for: Navata_Optus 24W


BB **C-U300030** 45° Cylindrical screen
suitable for: Navata_Optus 34W



BB **99783** Cylindrical screen
suitable for: Navata_Optus 16W

BB **99796** Cylindrical screen
suitable for: Navata_Optus 24W

BB **C-U300029** Cylindrical screen
suitable for: Navata_Optus 34W



BB **99780** Honeycomb (b)
suitable for: Navata_Optus 16W

BB **99798** Honeycomb (b)
suitable for: Navata_Optus 24W

BB **C-U300014** Honeycomb (a)
suitable for: Navata_Optus 34W

Electronics

FI | Electronics 300 mA (for 11 W)

99734	**83322**	**C-E100006**
ON/OFF	DALI/PUSH	TWIL
1 art.	1 art.	1 art.
149 x 37 x h 31	149 x 37 x h 31	210 x 49 x h 25
48	48	56

FJ | Electronics 400 mA (Recommended for Navata 450 mA - 16 W)

99734	**C-E100001**	**C-E100007**
ON/OFF	DALI/PUSH	TWIL
1 art.	1 art.	1 art.
149 x 37 x h 31	131 x 44 x h 30	210 x 49 x h 25
48	54	44

FL | Electronics 950 mA (for 34 W)

99146	**99330**	**C-E100009**
ON/OFF	DALI/PUSH	TWIL
1 art.	1 art.	1 art.
103 x 58 x h 27	210 x 49 x h 25	210 x 49 x h 25
64	56	56

FK | Electronics 700 mA (for 24/27 W)


99112	**C-E100016**	**C-E100008**
ON/OFF	DALI/PUSH	TWIL
1 art.	1 art.	1 art.
103 x 58 x h 27	131 x 44 x h 30	210 x 49 x h 25
64	54	56


J1 | Electronics 700 mA (for 8,5 W)

99735	**99147**	**99733**	**C-E100012**	**C-E100016**
ON/OFF	ON/OFF	0/1-10V	DALI/PUSH	DALI/PUSH
1 art.	2 - 3 art.	1 art.	1 art.	2 - 3 art.
134 x 37 x h 31	103 x 58 x h 27	134 x 37 x h 31	134 x 37 x h 31	131 x 44 x h 30
48	64	48	48	54

Colors

BB Black
TR Transparent





CEILING WALL SUSPENSIONS

Ceiling / Wall / Suspensions range index

Tour Slim

Tour_Slim_PD Complete

191

Tour_Slim_PD

192

Tour_Slim_D
NEW

193

Tour_Slim_ Elliptic_PD
NEW

194


Ceiling rose


196


Tour

Tour_R

201

Tour_Cell_C

201

Tour_CD

203

Tour_PI

203

Tour_PD

204

Tour_PU

206

Tour_D

207

Tour_Cell_P

208

Tour_Track

209

Tour_Projectors

209

Ceiling rose

210-211

Skylum

Skylum_R
NEW

218

Skylum_R Comfort
NEW

218

Skylum_RP
NEW

221

Skylum_Q

222

Skylum_Q PRO

222

Mini_Albatros

Mini_Albatros

225

Cell

Cell_S

227


Cell_S Ww

227

Baton

Baton_P

232

Baton_R
NEW

232-233

Baton_Q
NEW

233

Pound

Pound_BS



236

Pound_BC



236

Pound_S



237

Pound_Wall



237

High Wired

High Wired



242


High Wired IP44



242

Emy

Emy



245



TOUR SLIM

Structure in aluminium.


DIMENSIONS AND COLOURS FOR UNEXPECTED LAYOUTS

Thanks to its slimline profile, Tour Slim fits discretely into any living space. Only a soft, well-defined light is perceived thus ensuring excellent visual comfort. The collection features two suspension methods: a central ceiling rose and fastening kit. The central ceiling rose, including the power source, supports the three cables. The kit includes three ceiling nipples with a remote driver for greater visual appeal. This solution makes it easier to create layouts with multiple lights. Tour Slim is available in three temperature colours: 2700K, 3000K and 4000K which meet a variety of design and installation requirements. The combination of all these elements makes the collection extremely flexible and versatile, and easily adaptable to different settings.




TOUR_SLIM_D
DUAL EMISSION

Tour_Slim_D
Ø 550 mm / Ø 700 mm / Ø 900 mm
Ø 1150 mm / Ø 1450 mm



TOUR_SLIM_PD
TOUR_SLIM_PD COMPLETE
DIRECT EMISSION

Tour_Slim_PD Complete
Ø 550 mm / Ø 700 mm
Tour_Slim_PD
Ø 550 mm / Ø 700 mm / Ø 900 mm
Ø 1150 mm / Ø 1450 mm



TOUR_SLIM_ELLIPTIC_PD
DIRECT EMISSION

Tour_Slim_Elliptic_PD
880x1350 mm
1030x1800 mm

We have come up with four elegant, understated finishes: white and embossed black, brushed gold and copper. Tour Slim is also characterized by a strong technical component, such as the perfectly flush and homogeneous opal diffuser made of silicone, which gives the collection a high visual comfort, without glare or lateral dispersion. The timely management of the devices completes the technological potential of the family. Thanks to DALI, DALI2 digital and 1-10v analogue protocols, Push-Dimm, Phase-Cut it is possible to control each pendant light, its function and manage the production of specific lighting scenes.



White **(WH)**



Text Black **(BB)**




Brushed Copper **(HC)**




Brushed Gold **(HG)**

Tour Slim offers the designer a wide range of installation possibilities. With a central canopy complete with power supply and a special fixing kit, consisting of three ceiling nipples that fix the support and power cables, the driver must be positioned remotely. These solutions allow a great deal of freedom of expression, with room for a wide variety of combinations of heights, angles and diameters with the finishes.




Here are some examples of the creative design of Tour Slim among the many that have been invented by you. Symmetrical or asymmetrical, concentrically converging or diverging cascades. Why not have a go!



Tour_Slim_PD Complete | topLED | 220-240 V AC | 33 W DC - 40 W AC







	Fin	Cct	lm S - lm D	Opt
On/Off - Phase Cut - Push Dim - CRI 90				
C01055	**WH**	**M**	3432 - 1848	**DI** (Diffused)
	BB	**W**	3612 - 1945	
	HG	**N**	3854 - 2075	
	HC			
DALI - CRI 90				
C01056	**WH**	**M**	3432 - 1848	**DI** (Diffused)
	BB	**W**	3612 - 1945	
	HG	**N**	3854 - 2075	
	HC			

Tour_Slim_PD Complete | topLED | 220-240 V AC | 41 W DC - 50 W AC





	Fin	Cct	lm S - lm D	Opt
On/Off - Phase Cut - Push Dim - CRI 90				
C01057	**WH**	**M**	4314 - 2448	**DI** (Diffused)
	BB	**W**	4541 - 2577	
	HG	**N**	4844 - 2750	
	HC			
DALI - CRI 90				
C01058	**WH**	**M**	4314 - 2448	**DI** (Diffused)
	BB	**W**	4541 - 2577	
	HG	**N**	4844 - 2750	
	HC			





Finishes


White
Black
Brushed Gold
Brushed Copper

Cct

M 2700 **N** 4000
W 3000

Tour_Slim_PD | V2 | single-emission | topLED | 24 V DC | 33 W DC






	Fin	Cct	lm S - lm D	Opt
CRI 90				
C01059	**WH**	**M**	3432 - 1848	**DI** (Diffused)
	BB	**W**	3612 - 1945	
	HG	**N**	3854 - 2075	
	HC			

Electronics: **ER** (pag 197) | Accessories & Ceiling rose (pag 196-197)

Tour_Slim_PD | V2 | single-emission | topLED | 24 V DC | 41 W DC







	Fin	Cct	lm S - lm D	Opt
CRI 90				
C01060	**WH**	**M**	4314 - 2448	**DI** (Diffused)
	BB	**W**	4541 - 2577	
	HG	**N**	4844 - 2750	
	HC			

Electronics: **AC** (pag 197) | Accessories & Ceiling rose (pag 196-197)

Tour_Slim_PD | V2 | single-emission | topLED | 24 V DC | 52 W DC







	Fin	Cct	lm S - lm D	Opt
CRI 90				
C01061	**WH**	**M**	5491 - 3123	**DI** (Diffused)
	BB	**W**	5779 - 3288	
	HG	**N**	6166 - 3507	
	HC			

Electronics: **AD** (pag 197) | Accessories & Ceiling rose (pag 196-197)

Tour_Slim_PD | V2 | single-emission | topLED | 24 V DC | 65 W DC







	Fin	Cct	lm S - lm D	Opt
CRI 90				
C01062	**WH**	**M**	7060 - 3916	**DI** (Diffused UGR<19)
	BB	**W**	7430 - 4123	
	HG	**N**	7927 - 4398	
	HC			

Electronics: **AE** (pag 197) | Accessories & Ceiling rose (pag 196-197)

Tour_Slim_PD | V2 | single-emission | topLED | 24 V DC | 78 W DC






	Fin	Cct	lm S - lm D	Opt
CRI 90				
C01063	**WH**	**M**	8923 - 4923	**DI** (Diffused UGR<19)
	BB	**W**	9391 - 5128	
	HG	**N**	10019 - 5529	
	HC			

Electronics: **ES** (pag 197) | Accessories & Ceiling rose (pag 196-197)

Tour_Slim_D | double-emission | topLED | 24 V DC | 60 W DC





Fin | Cct | lm S - lm D | Opt


CRI 90

	Fin	Cct	lm S - lm D	Opt
C00663	**WH**	**M**	6118 - 3830	**DD** (Diff.+ Diff. UGR<19)
	BB	**W**	6558 - 4110	
	HG	**N**	6954 - 4357	
	HC			

Electronics: **AD** (pag 197) | Accessories & Ceiling rose (pag 196-197)

Tour_Slim_D | double-emission | topLED | 24 V DC | 74 W DC





Fin | Cct | lm S - lm D | Opt


CRI 90

	Fin	Cct	lm S - lm D	Opt
C00664	**WH**	**M**	7722 - 4634	**DD** (Diff.+ Diff. UGR<19)
	BB	**W**	8278 - 4973	
	HG	**N**	8778 - 5272	
	HC			

Electronics: **AE** (pag 197) | Accessories & Ceiling rose (pag 196-197)

Tour_Slim_D | double-emission | topLED | 24 V DC | 90 W DC






Fin | Cct | lm S - lm D | Opt


CRI 90

	Fin	Cct	lm S - lm D	Opt
C00665	**WH**	**M**	9906 - 5786	**DD** (Diff.+ Diff. UGR<19)
	BB	**W**	10620 - 6207	
	HG	**N**	11260 - 6579	
	HC			

Electronics: **AF** (pag 197) | Accessories & Ceiling rose (pag 196-197)

Tour_Slim_D | double-emission | topLED | 24 V DC | 108 W DC






Fin | Cct | lm S - lm D | Opt


CRI 90

	Fin	Cct	lm S - lm D	Opt
C00666	**WH**	**M**	12672 - 7186	**DD** (Diff.+ Diff. UGR<19)
	BB	**W**	13586 - 7711	
	HG	**N**	14406 - 8173	
	HC			

Electronics: **AF** (pag 197) | Accessories & Ceiling rose (pag 196-197)

Tour_Slim_D | double-emission | topLED | 24 V DC | 126 W DC





Fin | Cct | lm S - lm D | Opt


CRI 90


	Fin	Cct	lm S - lm D	Opt
C00667	**WH**	**M**	15880 - 8570	**DD** (Diff.+ Diff. UGR<19)
	BB	**W**	17026 - 9199	
	HG	**N**	18052 - 9750	
	HC			

Electronics: **AG** (pag 197) | Accessories & Ceiling rose (pag 196-197)

Use 2 drivers to have the separate dual UP & DOWN switching on/off.

Tour_Slim_Elliptic_PD | single-emission | topLED | 24 V DC | 65 W DC







	Fin	Cct	lm S - lm D	Opt
CRI 90				
C00738	**WH**	**M**	6765 - 4121	**DI** (Diffused)
	BB	**W**	7120 - 4422	
	HG	**N**	7597 - 4687	
	HC			

Electronics: **AE** (pag 197) | Accessories & Ceiling rose (pag 196-197)

Tour_Slim_Elliptic_PD | single-emission | topLED | 24 V DC | 75 W DC





	Fin	Cct	lm S - lm D	Opt
CRI 90				
C00739	**WH**	**M**	8824 - 5206	**DI** (Diffused)
	BB	**W**	9288 - 5586	
	HG	**N**	9909 - 5921	
	HC			

Electronics: **AE** (pag 197) | Accessories & Ceiling rose (pag 196-197)

Black **(BB)**

White **(WH)**



Brushed Gold **(HG)**




Brushed Copper **(HC)**

Ceiling rose

3-cables coupling ceiling rose | 220-240 V AC






IP20

On-Off - Phase Cut - Push Dim Max 50 W
WH **64010**
BB **64011**
HG **64013**
HC **64012**

DALI - 1-10V Max 70 W
WH **64020**
BB **64021**
HG **64023**
HC **64022**

3-cables coupling ceiling rose | 220-240 V AC





IP20

On-Off Max 90 W
WH **64578**
BB **65142**
HG **64039**
HC **64038**

On-Off Max 75 W + 75 W
WH **65324**
BB **65326**
HG **C-F300011**
HC **C-F300012**

Phase-Cut Max 100 W
WH **64030**
BB **64031**
HG **64033**
HC **64032**


DALI Push Max 75 W + 75 W
WH **C-F300017**
BB **C-F300018**
HG **C-F300019**
HC **C-F300020**

DALI Push Max 75 W
WH **C-F300013**
BB **C-F300014**
HG **C-F300015**
HC **C-F300016**

DALI2 Push Max 150 W
WH **C-F300054**
BB **C-F300055**
HG **C-F300056**
HC **C-F300057**

6-cables coupling ceiling rose | 220-240 V AC





IP20

On-Off Max 150 W
WH **64066**
BB **64067**
HG **64069**
HC **64068**


On-Off Max 150 W + 150 W
WH **65336**
BB **65338**
HG **C-F300021**
HC **C-F300022**

Phase-Cut Max 100 W
WH **64060**
BB **64061**
HG **64063**
HC **64062**

DALI Push Max 150 W
WH **C-F300027**
BB **C-F300029**
HG **C-F300030**
HC **C-F300031**

6-cables ceiling rose for 2/3 Tour fixing | 220-240 V AC





IP20

On-Off Max 150 W + 150 W + 150 W
WH **65412**
BB **65413**
HG **C-F300032**
HC **C-F300033**


DALI Push Max 75 W + 100 W + 150 W
WH **C-F300038**
BB **C-F300039**
HG **C-F300040**
HC **C-F300041**

DALI Push Max 150 W + 150 W
WH **C-F300034**
BB **C-F300035**
HG **C-F300036**
HC **C-F300037**

Finishes
WH White
BB Black
HG Brushed Gold
HC Brushed Copper

Accessories

Fixing kit for Tour Slim (3 pcs)



WH **64575**
BB **64670**
HG **64189**
HC **64179**

suitable for diameter: Tour Slim / Elliptic / Double

Remote driver



Electronics

AC

99374	99332	99722	83333	C-E400002
ON/OFF	0/1-10V	DALI	DALI/PUSH	DALI/PUSH
1 art.	1 - 3 art.	1 - 2 art.	1 - 3 art.	1 - 5 art.
210 x 49 x h 25	158 x 60 x h 35	191 x 63 x h 38	188 x 68 x h 34	188 x 68 x h 34
56	70	73	77	77

AD

99374	99332	99722	83333	C-E400002
ON/OFF	0/1-10V	DALI	DALI/PUSH	DALI/PUSH
1 art.	1 - 2 art.	1 - 2 art.	1 - 2 art.	1 - 4 art.
210 x 49 x h 25	158 x 60 x h 35	191 x 63 x h 38	188 x 68 x h 34	188 x 68 x h 34
56	70	73	77	77

AE

99374	99332	99722	83333	C-E400002
ON/OFF	0/1-10V	DALI	DALI/PUSH	DALI/PUSH
1 art.	1 - 2 art.	1 art.	1 - 2 art.	1 - 4 art.
210 x 49 x h 25	158 x 60 x h 35	191 x 63 x h 38	188 x 68 x h 34	188 x 68 x h 34
56	70	73	77	77

AF

99331	99332	99722	83333	C-E400002
ON/OFF	0/1-10V	DALI	DALI/PUSH	DALI/PUSH
1 art.	1 art.	1 art.	1 art.	1 - 2 art.
158 x 60 x h 35	158 x 60 x h 35	191 x 63 x h 38	188 x 68 x h 34	188 x 68 x h 34
70	70	73	77	77

AG

99331	99332	99722	83333
ON/OFF	0/1-10V	DALI	DALI/PUSH
1 art.	1 art.	1 art.	1 art.
158 x 60 x h 35	158 x 60 x h 35	191 x 63 x h 38	188 x 68 x h 34
70	70	73	77

ER

99374	99332	99722	83333	C-E400002
ON/OFF	0/1-10V	DALI	DALI/PUSH	DALI/PUSH
1 - 2 art.	1 - 4 art.	1 - 3 art.	1 - 4 art.	1 - 7 art.
210 x 49 x h 25	158 x 60 x h 35	191 x 63 x h 38	188 x 68 x h 34	188 x 68 x h 34
56	70	73	77	77

ES


99331	99332	99722	83333	C-E400002
ON/OFF	0/1-10V	DALI	DALI/PUSH	DALI/PUSH
1 art.	1 art.	1 art.	1 art.	1 - 3 art.
158 x 60 x h 35	158 x 60 x h 35	191 x 63 x h 38	188 x 68 x h 34	188 x 68 x h 34
70	70	73	77	77

Finishes

WH White
BB Black
HG Brushed Gold
HC Brushed Copper

TOUR

Structure in aluminium.



Recessed




	_R	_Cell_C
W	37,5-45-70	38-46-68
mm	**Ø 745-915-1435**	**Ø 745-915-1435**
Cct	2700-3000-4000	2700-3000-4000
Opt	**Diffused**	**M.Flood-W.Flood**
Elec.	On/Off 0/1-10V DALI	On/Off 0/1-10V DALI
Col.	WH BB	WH

Surface




	_CD
W	37,5-45-70
mm	**Ø 740-910-1430**
Cct	2700-3000-4000
Opt	**Diffused**
Elec.	On/Off 0/1-10V DALI
Col.	WH BB

Suspension
Single emission



	_PI	_PD	_PU	_Cell_P
W	29-36,5-57,5	37,5-45-70-114	37,5-45-70-114	38-46-68
mm	**Ø 750-945-1475**	**Ø 740-910-1430-2450**	**Ø 740-910-1430-2450**	**Ø 740-910-1430**
Cct	2700-3000-4000	2700-3000-4000	2700-3000-4000	2700-3000-4000
Opt	**Diffused**	**Diffused**	**Diffused**	**M.Flood-M.W.Flood**
Elec.	On/Off 0/1-10V DALI	On/Off 0/1-10V DALI	On/Off 0/1-10V DALI	On/Off 0/1-10V DALI
Col.	WH BB HG HC	WH BB HG HC	WH BB HG HC	WH BB

Suspension
Double emission



	_D
	75-90-140-224
	Ø 740-910-1430-2450
	2700-3000-4000
	Diffused
	On/Off 0/1-10V DALI
	WH BB HG HC

Suspension
Projector



	_Track
V	48
W	15-22
mm	**Ø 945-1475**
Cct	2700-3000-4000
Opt	**Spot-Flood-M.Flood W.Flood**
Elec.	On/Off
Col.	WH BB



White **(WH)**



Text Black **(BB)**




Brushed Copper **(HC)**




Brushed Gold **(HG)**


Emission range
Tour_Cell adopts cut-off microcells for punctual emission with zero glare and very high visual comfort; Tour_Projector, by attaching specific projectors, allows you to obtain a highly versatile accent emission. The family is completed with versions that offer diffuse, direct, indirect, internal lateral, and double emission light distribution: four light effects that can be combined in countless combinations to transform environments with a minimalist and contemporary light signature.




Microcell emission
(Tour Cell_C)




Direct emission
(Tour R)




Direct emission
(Tour CD)




Microcell emission
(Tour Cell_P)




Accent emission
(Tour Projector)




Direct emission
(Tour PD)




Indirect emission
(Tour PU)



Internal lateral emission
(Tour PI)





Dual emission
(Tour D)



Cell Optics
Small and round, the convex-faced micro reflectors that make up the Tour_Cell optics effectively control the luminance and, combined with the recessed source and the black cell, guarantee almost total glare control. In fact, the light source is impossible to see unless you are in the zenith position with respect to the lamp. This guarantees extremely high visual comfort, with uniform general lighting without shadowy areas or discolouring. Tour_Cell is available in the hanging version, essential and elegant, or for recessed installation for maximum conservation of clean aesthetics and architecture.


Tour_projector
Tour_projector guarantees high performance thanks to the projectors available in two sizes: 15W Ø65 mm and 22W Ø85 mm. The characteristics of the two projectors allow Tour_projector to work at its best level in a Retail setting, but also in a Museum setting, providing top-level dynamic performance, allowing the projectors to be positioned in any area of the Tour_track without affecting the final balance of the suspension.






Emission control accessories
Tour_projector is compatible with a wide range of light beam control accessories: standard cylindrical screen and at 45 degrees, fully or partly eliminating the secondary beam and reducing the light cone; cross-like and honeycomb diffuser, for controlling and reducing glaring more or less markedly; directional fins and elliptical filter, for shaping the light or creating ovalized projections.

Easy Plug Connection
Thanks to the particular connection system, can be positioned on the entire circumference of Tour_track. Using the new mechanical locking system, Tour_projector guarantees maximum safety and stability in the directing phase.



Tour_R | topLED | 24 V DC | 37,5 W DC






	Fin	Cct	lm S - lm D	Opt
CRI 90				
C00221	**WH**	**M**	4001 - 2242	**DI** (Diffused)
	BB	**W**	4176 - 2340	
		N	4432 - 2483	

Electronics: **AB** (pag 213)

Tour_R | topLED | 24 V DC | 45 W DC






	Fin	Cct	lm S - lm D	Opt
CRI 90				
C00223	**WH**	**M**	5001 - 2710	**DI** (Diffused)
	BB	**W**	5220 - 2837	
		N	5540 - 3010	

Electronics: **AC** (pag 213)

Tour_R | topLED | 24 V DC | 70 W DC







	Fin	Cct	lm S - lm D	Opt
CRI 90				
C00224	**WH**	**M**	8001 - 4230	**DI** (Diffused)
	BB	**W**	8352 - 4416	
		N	8864 - 4686	

Electronics: **AE** (pag 213)

Tour_Cell_C | powerLED | 600 mA | 38 W DC






	Fin	Cct	lm S - lm D	Opt
CRI 90				
C00225	**WH**	**M**	3980 - 2812	**MW** (52° UGR<11)
		W	4240 - 2992	**ML** (64° UGR<11)
		N	4740 - 3344	

Electronics: **Y1** (pag 213)

Tour_Cell_C | powerLED | 600 mA | 46 W DC







	Fin	Cct	lm S - lm D	Opt
CRI 90				
C00403	**WH**	**M**	4776 - 3372	**MW** (52° UGR<11)
		W	5088 - 3589	**ML** (64° UGR<11)
		N	5688 - 4013	

Electronics: **Y1** (pag 213)

Tour_Cell_C | powerLED | 550 mA | 68 W DC





	Fin	Cct	lm S - lm D	Opt
CRI 90				
C00404	**WH**	**M**	7164 - 5065	**MW** (52° UGR<11)
		W	7632 - 5389	**ML** (64° UGR<11)
		N	8532 - 6023	

Electronics: **Z1** (pag 213)







1 **ARIA RETREAT & Spa** | Cima di Porlezza - Como (Italy)

Project: R4M Engineering
Lighting Designer: Architect Giorgio Colombo, Light+Arch Consultancy
Photography: Andrea Martiradonna


2 **IRI headquarters** | Milan (Italy)


Lighting Designer: Garibaldi Architects
Photography: Giacomo Albo

3 **UNIVERSITÄT WR. NEUSTADT** | (Austria)

Project: Arch. Alexander Magyar
Photography: Alexander Magyar

Tour_CD | single-emission | topLED | 24 V DC | 37,5 W DC







	Fin	Cct	lm S - lm D	Opt
CRI 90				
C00410	**WH**	**M**	4001 - 2242	**DI** (Diffused)
	BB	**W**	4176 - 2340	
		N	4432 - 2483	

Electronics: **AB** (pag 213)

Tour_CD | single-emission | topLED | 24 V DC | 45 W DC







	Fin	Cct	lm S - lm D	Opt
CRI 90				
C00411	**WH**	**M**	5001 - 2710	**DI** (Diffused)
	BB	**W**	5220 - 2837	
		N	5540 - 3010	

Electronics: **AC** (pag 213)

Tour_CD | single-emission | topLED | 24 V DC | 70 W DC






	Fin	Cct	lm S - lm D	Opt
CRI 90				
C00412	**WH**	**M**	8001 - 4230	**DI** (Diffused)
	BB	**W**	8352 - 4416	
		N	8864 - 4686	

Electronics: **AE** (pag 213)

Tour_PI | internal-emission | topLED | 24 V DC | 29 W DC






	Fin	Cct	lm S - lm D	Opt
CRI 90				
C00854	**WH**	**M**	3515 - 1162	**DI** (Diffused)
	BB	**W**	3669 - 1212	
	HG	**N**	3933 - 1298	
	HC			

Electronics: **AA** (pag 213) | Accessories & Ceiling rose (pag 210-212)

Tour_PI | internal-emission | topLED | 24 V DC | 36,5 W DC







	Fin	Cct	lm S - lm D	Opt
CRI 90				
C00855	**WH**	**M**	4432 - 1503	**DI** (Diffused)
	BB	**W**	4626 - 1568	
	HG	**N**	4959 - 1683	
	HC			

Electronics: **AB** (pag 213) | Accessories & Ceiling rose (pag 210-212)

Tour_PI | internal-emission | topLED | 24 V DC | 57,5 W DC






	Fin	Cct	lm S - lm D	Opt
CRI 90				
C00856	**WH**	**M**	7029 - 2270	**DI** (Diffused)
	BB	**W**	7337 - 2369	
	HG	**N**	7866 - 2543	
	HC			

Electronics: **AD** (pag 213) | Accessories & Ceiling rose (pag 210-212)

Tour_PD | single-emission | topLED | 24 V DC | 37,5 W DC






	Fin	Cct	lm S - lm D	Opt
CRI 90				
C00413	**WH**	**M**	4001 - 2242	**DI** (Diffused)
	BB	**W**	4176 - 2340	
	HG	**N**	4432 - 2483	
	HC			

Electronics: **AB** (pag 213) | Accessories & Ceiling rose (pag 210-212)

Tour_PD | single-emission | topLED | 24 V DC | 45 W DC







	Fin	Cct	lm S - lm D	Opt
CRI 90				
C00414	**WH**	**M**	5001 - 2710	**DI** (Diffused)
	BB	**W**	5220 - 2837	
	HG	**N**	5540 - 3010	
	HC			

Electronics: **AC** (pag 213) | Accessories & Ceiling rose (pag 210-212)

Tour_PD | single-emission | topLED | 24 V DC | 70 W DC






	Fin	Cct	lm S - lm D	Opt
CRI 90				
C00415	**WH**	**M**	8001 - 4231	**DI** (Diffused)
	BB	**W**	8352 - 4416	
	HG	**N**	8864 - 4686	
	HC			

Electronics: **AE** (pag 213) | Accessories & Ceiling rose (pag 210-212)

Tour_PD | single-emission | topLED | 24 V DC | 114 W DC





	Fin	Cct	lm S - lm D	Opt
CRI 90				
C00416	**WH**	**M**	13502 - 7228	**DI** (Diffused UGR<19)
	BB	**W**	14094 - 7545	
	HG	**N**	14958 - 8007	
	HC			

Electronics: **AF** (pag 213) | Accessories & Ceiling rose (pag 210-212)

For single-emission Tour_PD, the following diameters are available on request: 3500, 5000, 7000, and 9800 mm.



ARIA RETREAT & Spa
Cima di Porlezza - Como (Italy)


Project: R4M Engineering

Lighting Designer: Architect Giorgio Colombo, Light+Arch Consultancy

Photography:
Andrea Martiradonna

Tour_PU | indirect-emission | topLED | 24 V DC | 37,5 W DC






	Fin	Cct	lm S - lm D	Opt
CRI 90				
C00424	**WH**	**M**	4001 - 2242	**DI** (Diffused)
	BB	**W**	4176 - 2340	
	HG	**N**	4432 - 2483	
	HC			

Electronics: **AB** (pag 213) | Accessories & Ceiling rose (pag 210-212)

Tour_PU | indirect-emission | topLED | 24 V DC | 45 W DC






	Fin	Cct	lm S - lm D	Opt
CRI 90				
C00425	**WH**	**M**	5001 - 2802	**DI** (Diffused)
	BB	**W**	5220 - 2837	
	HG	**N**	5540 - 3010	
	HC			

Electronics: **AC** (pag 213) | Accessories & Ceiling rose (pag 210-212)

Tour_PU | indirect-emission | topLED | 24 V DC | 70 W DC







	Fin	Cct	lm S - lm D	Opt
CRI 90				
C00426	**WH**	**M**	8001 - 4230	**DI** (Diffused)
	BB	**W**	8352 - 4416	
	HG	**N**	8864 - 4686	
	HC			

Electronics: **AE** (pag 213) | Accessories & Ceiling rose (pag 210-212)

Tour_PU | indirect-emission | topLED | 24 V DC | 114 W DC






	Fin	Cct	lm S - lm D	Opt
CRI 90				
C00427	**WH**	**M**	13502 - 7728	**DI** (Diffused)
	BB	**W**	14094 - 7545	
	HG	**N**	14958 - 8007	
	HC			

Electronics: **AF** (pag 213) | Accessories & Ceiling rose (pag 210-212)

Tour_D | double-emission | topLED | 24 V DC | 75 W DC






	Fin	Cct	lm S - lm D	Opt
CRI 90				
C00428	**WH**	**M**	8001 - 4230	**DD** (Diff.+ Diff. UGR<19)
	BB	**W**	8352 - 4416	
	HG	**N**	8864 - 4686	
	HC			

Electronics: **AE** (pag 213) | Accessories & Ceiling rose (pag 210-212)

Tour_D | double-emission | topLED | 24 V DC | 90 W DC







	Fin	Cct	lm S - lm D	Opt
CRI 90				
C00429	**WH**	**M**	10001 - 5443	**DD** (Diff.+ Diff. UGR<19)
	BB	**W**	10440 - 5673	
	HG	**N**	11080 - 6021	
	HC			

Electronics: **AF** (pag 213) | Accessories & Ceiling rose (pag 210-212)

Tour_D | double-emission | topLED | 24 V DC | 140 W DC







	Fin	Cct	lm S - lm D	Opt
CRI 90				
C00430	**WH**	**M**	16002 - 8459	**DD** (Diff.+ Diff. UGR<19)
	BB	**W**	16704 - 8831	
	HG	**N**	17728 - 9373	
	HC			

Electronics: **AG** (pag 213) | Accessories & Ceiling rose (pag 210-212)

Tour_D | double-emission | topLED | 24 V DC | 224 W DC






	Fin	Cct	lm S - lm D	Opt
CRI 90				
C00431	**WH**	**M**	27004 - 14452	**DD** (Diff.+ Diff. UGR<19)
	BB	**W**	28188 - 15089	
	HG	**N**	29916 - 16014	
	HC			

Electronics: **AH** (pag 213) | Accessories & Ceiling rose (pag 210-212)

Use 2 drivers to have the separate dual UP & DOWN switching on/off.

Tour_Cell_P | powerLED | 600 mA | 38 W DC






	Fin	Cct	lm S - lm D	Opt
CRI 90				
C00437	**WH**	**M**	3980 -2812	**MW** (52° UGR<11)
	BB	**W**	4240 - 2992	**ML** (64° UGR<11)
		N	4740 - 3344	

Electronics: **Y1** (pag 213) | Accessories (pag 212) | Ceiling rose (pag 208)

Tour_Cell_P | powerLED | 600 mA | 46 W DC







	Fin	Cct	lm S - lm D	Opt
CRI 90				
C00439	**WH**	**M**	4776 - 3372	**MW** (52° UGR<11)
	BB	**W**	5088 - 3558	**ML** (64° UGR<11)
		N	5688 - 4013	

Electronics: **Y1** (pag 213) | Accessories (pag 212) | Ceiling rose (pag 208)

Tour_Cell_P | powerLED | 550 mA | 68 W DC






	Fin	Cct	lm S - lm D	Opt
CRI 90				
C00442	**WH**	**M**	7164 - 5065	**MW** (52° UGR<11)
	BB	**W**	7632 - 5389	**ML** (64° UGR<11)
		N	8532 - 6023	

Electronics: **Z1** (pag 213) | Accessories (pag 212) | Ceiling rose (pag 208)

Coupling ceiling rose Tour_Cell_P | 220-240 V AC





On-Off Max 75 W

WH	**63778**	**suitable for:**
BB	**63779**	**Tour_Cell_P** Ø 740-910-1430

DALI2/PUSH Max 75 W


WH	**C-F300042**	**suitable for:**
BB	**C-F300043**	**Tour_Cell_P** Ø 740-910

DALI2/PUSH Max 75 W

WH	**C-F300044**	**suitable for:**
BB	**C-F300045**	**Tour_Cell_P** Ø 1430

Tour_Track | 48 V DC








WH **82753**
BB **82755**

Accessories (pag 212) | Ceiling rose (pag 209)

Tour_Track | 48 V DC








WH **82754**
BB **82756**

Accessories (pag 212) | Ceiling rose (pag 209)

Tour_Projectors | arrayLED | 48 V DC | 15 W DC








	Cct	lm S - lm D	Opt
Balance - CRI 90			
WH **82757**	**M**	2214 - 1510	**15** (19°)
BB **82758**	**W**	2318 - 1581	**30** (35°)
	N	2411 - 1645	**60** (56°)

Optics & Accessories (pag 212)

Tour_Projectors | arrayLED | 48 V DC | 22 W DC








	Cct	lm S - lm D	Opt
Balance - CRI 90			
WH **82759**	**M**	3588 - 2610	**15** (17°)
BB **82760**	**W**	3633 - 2718	**30** (24°)
	N	3776 - 2773	**60** (47°)

Optics & Accessories (pag 212)

Coupling ceiling rose Tour_Track | 220-240 V AC








On-Off Max 75 W

WH **63782** **suitable for:**
BB **63783** **Tour_Track** Ø 945-1475

Coupling ceiling rose Tour_Track | 220-240 V AC








On-Off Max 200 W

WH **63772** **suitable for:**
BB **63773** **Tour_Track** Ø 945-1475

Ceiling rose

3-cables coupling ceiling rose | 220-240 V AC






IP20

On-Off - Phase Cut - Push Dim Max 50 W
- WH **64010**
- BB **64011**
- HG **64013**
- HC **64012**

DALI - 1-10V Max 70 W
- WH **64020**
- BB **64021**
- HG **64023**
- HC **64022**

3-cables coupling ceiling rose | 220-240 V AC





IP20

On-Off Max 90 W
- WH **64578**
- BB **65142**
- HG **64039**
- HC **64038**

Phase-Cut Max 100 W
- WH **64030**
- BB **64031**
- HG **64033**
- HC **64032**

DALI Push Max 75 W
- WH **C-F300013**
- BB **C-F300014**
- HG **C-F300015**
- HC **C-F300016**

On-Off Max 75 W + 75 W
- WH **65324**
- BB **65326**
- HG **C-F300011**
- HC **C-F300012**

DALI Push Max 75 W + 75 W
- WH **C-F300017**
- BB **C-F300018**
- HG **C-F300019**
- HC **C-F300020**

DALI2 Push Max 150 W
- WH **C-F300054**
- BB **C-F300055**
- HG **C-F300056**
- HC **C-F300057**


Finishes

WH White HG Brushed Gold
BB Black HC Brushed Copper

Ceiling rose

6-cables coupling ceiling rose | 220-240 V AC





IP20

On-Off Max 150 W
WH **64066**
BB **64067**
HG **64069**
HC **64068**


Phase-Cut Max 100 W
WH **64060**
BB **64061**
HG **64063**
HC **64062**

On-Off Max 150 W + 150 W
WH **65336**
BB **65338**
HG **C-F300021**
HC **C-F300022**

DALI Push Max 150 W
WH **C-F300027**
BB **C-F300029**
HG **C-F300030**
HC **C-F300031**

6-cables ceiling rose for 2/3 Tour fixing | 220-240 V AC





IP20


On-Off Max 150 W + 150 W + 150 W
WH **65412**
BB **65413**
HG **C-F300032**
HC **C-F300033**

DALI Push Max 75 W + 100 W + 150 W
WH **C-F300038**
BB **C-F300039**
HG **C-F300040**
HC **C-F300041**

DALI Push Max 150 W + 150 W
WH **C-F300034**
BB **C-F300035**
HG **C-F300036**
HC **C-F300037**


Accessories

Fixing kit for Tour PD - PI - PU - D (3 pcs)



WH **64575**
BB **64670**
HG **64189**
HC **64179**

For version Ø 2450 requires 2x fixing kit with 3 cones each



BB **99781** Elliptical filter (a)
suitable for: Tour_Projectors 15W

BB **C-U300007** Elliptical filter (b)
suitable for: Tour_Projectors 22W




BB **99780** Honeycomb
suitable for: Tour_Projectors 15W

BB **C-U300008** Honeycomb
suitable for: Tour_Projectors 22W



BB **99779** Cross louvre
suitable for: Tour_Projectors 15W

BB **C-U300031** Cross louvre
suitable for: Tour_Projectors 22W



BB **99783** Cylindrical screen
suitable for: Tour_Projectors 15W

BB **C-U300029** Cylindrical screen
suitable for: Tour_Projectors 22W



BB **99782** 45° Cylindrical screen
suitable for: Tour_Projectors 15W

BB **C-U300030** 45° Cylindrical screen
suitable for: Tour_Projectors 22W

Optics



TR **99827** Spot
TR **99828** Flood
TR **99829** W. Flood
suitable for: Tour_Projectors 15W

TR **C-U300015** Spot
TR **C-U300016** Flood
TR **C-U300017** W. Flood
suitable for: Tour_Projectors 22W

Finishes
WH White HG Brushed Gold TR Transparent
BB Black HC Brushed Copper

Electronics

AA

99374	99332	99722	83333	C-E400002
ON/OFF	0/1-10V	DALI	DALI/PUSH	DALI/PUSH
1 - 2 art.	1 - 5 art.	1 - 4 art.	1 - 5 art.	1 - 8 art.
210 x 49 x h 25	158 x 60 x h 35	191 x 63 x h 38	188 x 68 x h 34	188 x 68 x h 34
56	70	73	77	77

AB

99374	99332	99722	83333	C-E400002
ON/OFF	0/1-10V	DALI	DALI/PUSH	DALI/PUSH
1 - 2 art.	1 - 4 art.	1 - 3 art.	1 - 4 art.	1 - 6 art.
210 x 49 x h 25	158 x 60 x h 35	191 x 63 x h 38	188 x 68 x h 34	188 x 68 x h 34
56	70	73	77	77

AC

99374	99332	99722	83333	C-E400002
ON/OFF	0/1-10V	DALI	DALI/PUSH	DALI/PUSH
1 art.	1 - 3 art.	1 - 2 art.	1 - 3 art.	1 - 5 art.
210 x 49 x h 25	158 x 60 x h 35	191 x 63 x h 38	188 x 68 x h 34	188 x 68 x h 34
56	70	73	77	77

AD

99374	99332	99722	83333	C-E400002
ON/OFF	0/1-10V	DALI	DALI/PUSH	DALI/PUSH
1 art.	1 - 2 art.	1 - 2 art.	1 - 2 art.	1 - 4 art.
210 x 49 x h 25	158 x 60 x h 35	191 x 63 x h 38	188 x 68 x h 34	188 x 68 x h 34
56	70	73	77	77

AE

99374	99332	99722	83333	C-E400002
ON/OFF	0/1-10V	DALI	DALI/PUSH	DALI/PUSH
1 art.	1 - 2 art.	1 art.	1 - 2 art.	1 - 4 art.
210 x 49 x h 25	158 x 60 x h 35	191 x 63 x h 38	188 x 68 x h 34	188 x 68 x h 34
56	70	73	77	77

AF

99331	99332	99722	83333	C-E400002
ON/OFF	0/1-10V	DALI	DALI/PUSH	DALI/PUSH
1 art.	1 art.	1 art.	1 art.	1 - 2 art.
158 x 60 x h 35	158 x 60 x h 35	191 x 63 x h 38	188 x 68 x h 34	188 x 68 x h 34
70	70	73	77	77

AG

99331	99332	99722	83333
ON/OFF	0/1-10V	DALI	DALI/PUSH
1 art.	1 art.	1 art.	1 art.
158 x 60 x h 35	158 x 60 x h 35	191 x 63 x h 38	188 x 68 x h 34
70	70	73	77

AH

99786	C-E400002
ON/OFF	DALI/PUSH
1 art.	1 art.
244 x 71 x h 38	188 x 68 x h 34
81	77

Y1

83122	83120
ON/OFF	0/1-10V, DALI/PUSH
1 art.	1 art.
129 x 76 x h 30	124 x 79 x h 22
90	84

Z1

83143	83121
ON/OFF, PUSH, 0/1-10V	DALI
1 art.	1 art.
124 x 79 x h 22	150 x 90 x h 38
84	97



GRAND HOTEL TREMEZZO
Como (Italy)

Project: Arch. Silvia Perego

Photography: Stefano Anzani

Skylum_R Track




162

SKYLUM

Body in aluminium. Diffuser in white polyester fabric or micro-prismatic PMMA (Comfort versions)

SKYLUM SIMPLICITY WITH VERY HIGH PERFORMANCE.

Light technology meets design precision. Visual comfort finds its most rational form, exploiting the simplicity of pure geometry to create a scenographic effect.




LIGHT EVOLUTION THAT TRANSFORMS THE SPACE.
4 SIZES, 3 INSTALLATION POSSIBILITIES, ONE SINGLE DESIGN.




SKYLUM_Q IS PURE DIFFUSED LIGHT

Skylum is the diffused lighting system available in two versions: Standard and PRO, with multiple possibilities of combinations and configurations. In default or custom dimensions, Skylum is the ideal lighting for retail and contract environments or large open spaces such as airports and hotels. The system guarantees the perfect uniformity of the light, cancelling out shadows on the ground and increasing environmental comfort.




82260
7 m x 7 m x 3 h
value calculated with
reflection coefficients:
20 floor
50 wall
70 ceiling



Floor plan

NO SHADOWS





High light diffusion
Skylum is a high definition system, with the large surface lit in an entirely uniform way in every part without drop-offs or blind corners, perfectly vertical on the ground surface, it completely cancels out horizontal shadows and is characterised by a B1 grade fire-resistant polyester diffuser which complies with the DIN 4102-1 standard, easily removable.




Standard version
The Standard version is made up of a thin aluminium frame, just 56,5 mm thick, available in three sizes: 620x620, 935x935, 1250x1250 mm, with LED circuits distributed inside, where each individual diode is mounted on special micro-optics that guarantee uniformity, despite the reduced height of the reflection chamber



PRO version
In the PRO version, the frame is 100 mm thick and has two fixed sizes: 1500x500 and 1500x1500; both models contain modular LED sources that are easily customised in terms of size up to two limit shapes: (max. 1940x1940 mm) and rectangular (max. 5780x1460 mm), the frame of the structure with its extremely thin edges makes the side-by-side placement of the module imperceptible, guaranteeing original lighting structures every time.






Mod. A
480 mm x 480 mm
4000 K: **3298 lm S**




Mod. B
120 mm x 160 mm
4000 K: **275 lm S**




Frame
12 mm

Example:


2 Mod. A + 12 Mod. B
(frame included)
4000 K: **9896 lm S**




1 Mod. A + 18 Mod. B
(frame included)
4000 K: **8248 lm S**



1 Mod. A + 13 Mod. B
(frame included)
4000 K: **6873 lm S**




1 Mod. A + 8 Mod. B
(frame included)
4000 K: **5498 lm S**




Example maximum sizes:

12 Mod. A + 3 Mod. A
(frame included) | 4000 K: **118728 lm S**




4 Mod. A + 4 Mod. A
(frame included) | 4000 K: **52768 lm S**



Skylum_R | topLED






IP40 NEW *

	Fin	Cct	lm S - lm D	Opt
Ø 410 mm - CRI 90 - 24 W DC - 27 W AC				
C00730	**WH**	**M**	3741 - 2782	**DI** (Diffused)
		W	3918 - 2913	
DALI 2/PUSH		**N**	4164 - 3097	
C00731				
Ø 605 mm - CRI 90 - 47 W DC - 52 W AC				
C00732	**WH**	**M**	7249 - 5545	**DI** (Diffused)
		W	7591 - 5806	
DALI 2/PUSH		**N**	8068 - 6172	
C00733				
Ø 910 mm - CRI 90 - 89 W DC - 99 W AC				
C00734	**WH**	**M**	13842 - 10736	**DI** (Diffused)
		W	14495 - 11242	
DALI 2/PUSH		**N**	15405 - 11950	
C00735				
Ø 1150 mm - CRI 90 - 146 W DC - 162 W AC				
C00736	**WH**	**M**	22950 - 17355	**DI** (Diffused)
		W	24033 - 18172	
DALI 2/PUSH		**N**	25119 - 19317	
C00737				

Skylum_R Comfort | topLED | UGR<19 | 220-240 V AC





IP40 UGR NEW *

	Fin	Cct	lm S - lm D	Opt
Ø 410 mm - CRI 90 - 19 W DC - 22 W AC				
C00740	**WH**	**M**	2988 - 2168	**DI** (Diffused UGR<19)
		W	3129 - 2270	
DALI 2/PUSH		**N**	3326 - 2408	
C00741				
Ø 605 mm - CRI 90 - 38 W DC - 42 W AC				
C00742	**WH**	**M**	5932 - 4418	**DI** (Diffused UGR<19)
		W	6212 - 4626	
DALI 2/PUSH		**N**	6602 - 4907	
C00743				
Ø 910 mm - CRI 90 - 75 W DC - 83 W AC				
C00744	**WH**	**M**	11667 - 8780	**DI** (Diffused UGR<19)
		W	12218 - 9193	
DALI 2/PUSH		**N**	12985 - 9749	
C00745				

EL


* The driver contained in the device complies with IEC 61347-2-13 annex J, and can therefore be powered by centralized power supply systems.

Finishes White

Cct **M** 2700 **N** 4000 **W** 3000



Skylum_R
with fabric diffuser



Skylum_R Comfort
with micro-prismatic diffuser
(UGR<19)


UGR





Skylum_RP | double-emission | topLED | 220-240 V AC






IP40 NEW *

	Fin	Cct	lm S - lm D	Opt
Ø 410 mm - CRI 90 - 33 W DC - 37 W AC				
C00821	**WH**	**M**	4835 - 3258	**DD** (Diffused + diffused)
		W	5064 - 3412	
DALI 2/PUSH		**N**	5382 - 3627	
C00822				
Ø 605 mm - CRI 90 - 58 W DC - 68 W AC				
C00823	**WH**	**M**	8950 - 6428	**DD** (Diffused + diffused)
		W	9373 - 6731	
DALI 2/PUSH		**N**	9962 - 7155	
C00824				
Ø 910 mm - CRI 90 - 116 W DC - 130 W AC				
C00825	**WH**	**M**	17973 - 12907	**DD** (Diffused + diffused)
		W	18821 - 13515	
DALI 2/PUSH		**N**	20003 - 14366	
C00826				

EL

* The driver contained in the device complies with IEC 61347-2-13 annex J, and can therefore be powered by centralized power supply systems.



Finishes


White

Cct

M 2700 **N** 4000
W 3000

Skylum_Q | topLED | 220-240 V AC






IP40 *

	Cct	lm S - lm D	Opt
L 620 - CRI 80 - 38 W DC - 43 W AC			
WH **82258**	**M**	6450 - 4778	**00** (Diffused)
BB **84273**	**W**	6737 - 4993	
	N	7023 - 5192	
L 620 - CRI 80 - DALI2 / PUSH - 38 W DC - 43 W AC			
WH **82261**	**M**	6450 - 4778	**00** (Diffused)
BB **84276**	**W**	6737 - 4993	
	N	7023 - 5192	
L 935 - CRI 80 - 96 W DC - 104 W AC			
WH **82259**	**M**	15093 - 12043	**00** (Diffused)
BB **84274**	**W**	15763 - 12581	
	N	16434 - 13087	
L 935 - CRI 80 - DALI2 / PUSH - 96 W DC - 104 W AC			
WH **82262**	**M**	15093 - 12043	**00** (Diffused)
BB **84277**	**W**	15763 - 12581	
	N	16434 - 13087	
L 1250 - CRI 80 - 160 W DC - 172 W AC			
WH **82260**	**M**	27882 - 19666	**00** (Diffused)
BB **84275**	**W**	29059 - 20546	
	N	30295 - 21371	
L 1250 - CRI 80 - DALI2 / PUSH - 160 W DC - 172 W AC			
WH **82263**	**M**	27882 - 19666	**00** (Diffused)
BB **84278**	**W**	29059 - 20546	
	N	30295 - 21371	

Skylum_Q PRO | topLED





C.C. IP40

	Cct	lm S - lm D	Opt
CRI 80 - 2100 mA - 78 W DC			
WH **84170**	**M**	13083 - 7785	**00** (Diffused)
BB **84271**	**W**	13665 - 8135	
	N	14246 - 8419	


Electronics: **FF** (pag 222)

CRI 80 - 4350 mA - 157 W DC			
WH **84171**	**M**	25446 - 15864	**00** (Diffused)
BB **84272**	**W**	26577 - 16577	
	N	27708 - 17157	

Electronics: **FG** (pag 222)

Skylum_Q PRO | topLED





C.C. IP40

	Cct	lm S - lm D	Opt
CRI 80 - 1450mA - 52 W DC			
WH **84169**	**M**	8482 - 5288	**00** (Diffused)
BB **84270**	**W**	8859 - 5526	
	N	9236 - 5719	

Electronics: **FH** (pag 222)

Electronics

FF

83195
DALI
1 art.
180 x 63 x h 36
79

FG

83196
DALI
1 art.
244 x 71 x h 38
79

FH

83194
DALI
1 art.
180 x 63 x h 36
79

EL

Drivers 83195, 83196, and 83194 comply with IEC 61347-2-13 annex J, and can therefore be powered by centralized power supply systems.

Finishes **Cct**

WH White **M** 2700 **N** 4000
BB Black **W** 3000

SALUBER
Calcinato - Brescia (Italy)

Project:
Architects Borgognoni and Sisti

Photography:
Marco Reggi




MINI_ALBATROS

Aluminium body
PMMA diffuser




OptiLight Technology
The transparent PMMA surface has a special pattern consisting of laser micro-engravings which divert the photons emitted by the lateral source, conveying the emission downwards and upwards. The lined engraving of the edge avoids glare and improves the performance of the lamp. A Linea Light Group's technology, that keeps the product fully transparent when not lit; it emits a soft glare-free light when lit, for full visual comfort.

Direct and indirect emission
The double emission solution is conceived to guarantee the correct light distribution in both directions: 55% of the emission is conveyed uniformly in the underlying plane, while the remaining 45% of indirect light allows to obtain good environmental lighting.




Albatros modular | Example of installation



Mini_Albatros | Complete | double-emission | topLED | 220-240 V AC






IK08 IP40

	Cct	lm S - lm D	Opt
L 1125 mm - CRI 90 - 37 W DC - 44 W AC			
WH **82834**	**W**	4356 - 3976	**00** (Diffused + diffused)
	N	4572 - 4181	
L 1125 mm - CRI 90 - DALI - 37 W DC - 44 W AC			
WH **82749**	**W**	4356 - 3976	**00** (Diffused + diffused)
	N	4572 - 4181	
L 1414 mm - CRI 90 - 46 W DC - 55 W AC			
WH **82836**	**W**	5445 - 4970	**00** (Diffused + diffused)
	N	5715 - 5228	
L 1414 mm - CRI 90 - DALI - 46 W DC - 55 W AC			
WH **82751**	**W**	5445 - 4970	**00** (Diffused + diffused)
	N	5715 - 5228	

Mini_Albatros Cct W = 3500 K

Mini_Albatros_M Master | double-emission | topLED | 220-240 V AC






IK08 IP40

	Cct	lm S - lm D	Opt
L 1125 mm - CRI 90 - 37 W DC - 44 W AC			
WH **82838**	**W**	4356 - 3976	**00** (Diffused + diffused)
	N	4572 - 4181	
L 1125 mm - CRI 90 - DALI - 37 W DC - 44 W AC			
WH **82823**	**W**	4356 - 3976	**00** (Diffused + diffused)
	N	4572 - 4181	
L 1414 mm - CRI 90 - 46 W DC - 55 W AC			
WH **82840**	**W**	5445 - 4970	**00** (Diffused + diffused)
	N	5715 - 5228	
L 1414 mm - CRI 90 - DALI - 46 W DC - 55 W AC			
WH **82825**	**W**	5445 - 4970	**00** (Diffused + diffused)
	N	5715 - 5228	

Mini_Albatros Cct W = 3500 K

Mini_Albatros_M Slave | double-emission | topLED | 220-240 V AC





IK08 IP40

	Cct	lm S - lm D	Opt
L 1125 mm - CRI 90 - 37 W DC - 44 W AC			
WH **82842**	**W**	4356 - 3976	**00** (Diffused + diffused)
	N	4572 - 4181	
L 1125 mm - CRI 90 - DALI - 37 W DC - 44 W AC			
WH **82827**	**W**	4356 - 3976	**00** (Diffused + diffused)
	N	4572 - 4181	
L 1414 mm - CRI 90 - 46 W DC - 55 W AC			
WH **82844**	**W**	5445 - 4970	**00** (Diffused + diffused)
	N	5715 - 5228	
L 1414 mm - CRI 90 - DALI - 46 W DC - 55 W AC			
WH **82829**	**W**	5445 - 4970	**00** (Diffused + diffused)
	N	5715 - 5228	

Mini_Albatros Cct W = 3500 K

Accessories

Mini_Albatros | Fixing for false ceilings



WH **98428**

Finishes

WH White

Cct

W 3500
N 4000

CELL

Aluminium body.



Cell family

Cell / Cell_Ww Gypsum Cell



104


Cell_Ww track



164

Cell_S | 3 x powerLED | 220-240 V AC | 5 W DC - 6 W AC






	Cct	lm S - lm D	Opt
CRI 90			
WB **65190**	**M**	510 - 413	**15** (12° UGR<11)
BB **65191**	**W**	543 - 440	**30** (33° UGR<11)
	N	609 - 493	**45** (49° UGR<16)

Cell_S | 6 x powerLED | 220-240 V AC | 9 W DC - 11 W AC






	Cct	lm S - lm D	Opt
CRI 90			
WB **65192**	**M**	1020 - 826	**15** (13° UGR<11)
BB **65193**	**W**	1086 - 880	**30** (34° UGR<11)
	N	1218 - 986	**45** (49° UGR<11)

Cell_S Ww | 3 x powerLED | 220-240 V AC | 9,5 W DC - 10,5 W AC






	Cct	lm S - lm D	Opt
CRI 90			
WH **82603**	**M**	1026 - 481	**07** (Asym. Ww)
BB **82604**	**W**	1101 - 518	
	N	1188 - 559	

Cell_S Ww | 6 x powerLED | 220-240 V AC | 19 W DC - 21 W AC





	Cct	lm S - lm D	Opt
CRI 90			
WH **82605**	**M**	2052 - 927	**07** (Asym. Ww)
BB **82606**	**W**	2202 - 994	
	N	2376 - 1074	



Finishes

WH White WB White/Black
BB Black

Cct

M 2700 **N** 4000
W 3000



Cob44_R
For additional
information: pag 106

BATON

The fixtures are made in aluminium and powder coated in either matt white or matt black, perfectly blending into the architectural space. The optics compartment is characterised by a reflector ensuring the high visual comfort of Baton.

NEW OPTICS GROUP FOR GREATER DESIGN VERSATILITY

The Baton family introduces new high-performing LEDs CRI 90 and a new optics group consisting of a reflector in aluminium with three different angles of light distribution. Baton is aimed at designers, offering lighting performance and high visual comfort thanks to the rearward position of the LED circuit, ensuring glare control with UGR ≤11.



	_Baton_P	_Baton_P	_Baton_Q	_Baton_R	_Baton_R/_Q
W	8,2W AC	5W AC	7,3	9W AC	2W DC
mm	**Ø 60 H 250/400**	**Ø 32 H 350/500**	**☐ 80 H 120-200**	**Ø 80 H 120**	**☐ Ø 30 H 30**
Cct	2700-3000-4000	3000-4000	2700-3000-4000	2700-3000-4000	3000-4000
Opt	**Spot-Flood** **M.W.Flood**	**W.Flood**	**Spot** **W.Flood**	**Spot-Flood** **W.Flood**	**M.Flood-W.Flood** **E.W.Flood**
Elec.	On/Off	On/Off	On/Off - DALI DALI Push	On/Off - DALI DALI Push	On/Off 0/1-10V - DALI
Col.	WB WA BB BD	WB WA BD	WH WB WA BB BD	WH WB WA BB BD	WH



Finishes
The lighting bodies, painted with white matt or black matt finish powders, perfectly merge with the architectural space. The internal of the optical unit characterises the product with a slight colour accent, declined in matt black and gold black.



Baton_Q: 76089W10
Worktop dimensions: (L x P x H) 1000 x 1000 x 1000 mm
Ceiling height: 2800 mm
Lamp height from worktop: 1600 mm
Average illuminance: 435 lx
UGR: ≤16

Controlled emission
Baton creates high contrast light effects. The lens integrated in the body creates a light beam characterised by clear-cut edges capable of casting any lit subject. The receded position of the LED makes this suspension extremely comfortable to view, perfect, for example, for, lighting cafeteria tables and counters.



Baton_P: 84576W45
Worktop dimensions: (L x P x H) 1800 x 900 x 800 mm
Ceiling height: 2800 mm
Lamp height from worktop: 1000 mm
Average illuminance: 350 lx
UGR: ≤16



CAP HOLDING
Milan (Italy)


Customer: CAP Holding S.p.A.


Architectural design: Studio Claudio Lucchin & Architetti Associati

Interior design, furnishings and lamps: Alterstudio Partners

Photos: Margherita Nardi

Baton_P | arrayLED | 220-240 V AC | 3 W DC - 5 W AC






IP40 UGR

	Fin	Cct	lm S - lm D	Opt
L 350 mm - CRI 90				
C00317	**WB**	**W**	321 - 256	**WF** (59° UGR<19)
	WA	**N**	345 - 275	
	BD			

Baton_P | arrayLED | 220-240 V AC | 3 W DC - 5 W AC






IP40 UGR

	Fin	Cct	lm S - lm D	Opt
L 500 mm - CRI 90				
C00318	**WB**	**W**	321 - 256	**WF** (59° UGR<19)
	WA	**N**	345 - 275	
	BD			

Baton_P | arrayLED | 220-240 V AC | 6,3 W DC - 8,2 W AC






IP40 UGR

	Fin	Cct	lm S - lm D	Opt
L 250 mm - CRI 90				
84575	**WB**	**M**	715 - 467	**10** (12° UGR<11)
84576	**WA**	**W**	748 - 512	**20** (20° UGR<11)
76102	**BB**	**N**	805 - 478	**45** (42° UGR<16)
84577	**BD**			

Baton_P | arrayLED | 220-240 V AC | 6,3 W DC - 8,2 W AC






IP40 UGR

	Fin	Cct	lm S - lm D	Opt
L 400 mm - CRI 90				
84578	**WB**	**M**	715 - 467	**10** (12° UGR<11)
84579	**WA**	**W**	748 - 512	**20** (20° UGR<11)
76103	**BB**	**N**	805 - 478	**45** (42° UGR<16)
84580	**BD**			

Baton_R | powerLED | 630 mA | 2 W DC






III C.C. IP52

	Fin	Cct	lm S - lm D	Opt
L 30 mm - CRI 90				
C00320	**WH**	**W**	212 - 189	**ML** (31°)
		N	237 - 210	**MW** (36°)
				WF (70°)
				XF (112°)

Electronics: **C1** (pag 233)

Baton_Q | powerLED | 630 mA | 2 W DC




III C.C. IP52

	Fin	Cct	lm S - lm D	Opt
L 30 mm - CRI 90				
C00321	**WH**	**W**	212 - 189	**ML** (31°)
		N	237 - 210	**MW** (36°)
				WF (70°)
				XF (112°)

Electronics: **C1** (pag 233)

Baton_R | arrayLED | 220-240 V AC | 7,3 W DC - 9 W AC






IP40 IP65 UGR NEW

	Fin	Cct	lm S - lm D	Opt
L 120 mm - CRI 90				
84581	WH	**M**	1067 - 779	**10** (12° UGR<16)
84582	WB	**W**	1133 - 827	**20** (20° UGR<16)
84583	WA	**N**	1191 - 869	**50** (55° UGR<16)
76084	BB			
76085	BD			

L 120 mm - CRI 90 - DALI				DALI 2	DALI PUSH
C01029	**WH**	**M**	1060 - 778	**SP**	(12° UGR<16)
	WB	**W**	1107 - 826	**FL**	(20° UGR<16)
	WA	**N**	1135 - 868	**WF**	(55° UGR<16)
	BB				
	BD				

Baton_Q | arrayLED | 220-240 V AC | 7,3 W DC - 9 W AC





IP40 IP65 UGR NEW


	Fin	Cct	lm S - lm D	Opt
L 120 mm - CRI 90				
84584	WH	**M**	1067 - 779	**10** (12° UGR<16)
84585	WB	**W**	1133 - 827	**20** (20° UGR<16)
84586	WA	**N**	1191 - 869	**50** (55° UGR<16)
76086	BB			
76087	BD			

L 120 mm - CRI 90 - DALI				DALI 2	DALI PUSH
C01030	**WH**	**M**	1060 - 778	**SP**	(12° UGR<16)
	WB	**W**	1107 - 826	**FL**	(20° UGR<16)
	WA	**N**	1135 - 868	**WF**	(55° UGR<16)
	BB				
	BD				

L 200 mm - CRI 90					
84587	WH	**M**	1067 - 779	**10**	(12° UGR<16)
84588	WB	**W**	1133 - 827	**20**	(20° UGR<16)
84589	WA	**N**	1191 - 869	**50**	(55° UGR<16)
76088	BB				
76089	BD				

L 200 mm - CRI 90 - DALI				DALI 2	DALI PUSH
C01031	**WH**	**M**	1060 - 778	**SP**	(12° UGR<16)
	WB	**W**	1107 - 826	**FL**	(20° UGR<16)
	WA	**N**	1135 - 868	**WF**	(55° UGR<16)
	BB				
	BD				

TECHNOLOGICAL CORE
Technology dressed up in a sober and understated design, in one word, Baton.



Electronics

C1

89147	99376	99105	99710	99713	+ driver 24V DC	
ON/OFF	ON/OFF	ON/OFF	24V DC converter	24V DC converter	**99374**	**99331**
1 - 2 art.	3 - 6 art.	6 - 12 art.	0/1-10V 1 - 6 art.	DALI 1 - 6 art.	75W	150W
138 x 22 x h 21	138 x 22 x h 21	103 x 58 x h 27	138 x 22 x h 20	138 x 22 x h 20		
29	29	64	29	29	56	70

Finishes
WH White WB White/Black BD Black/Gold
BB Black WA White/Gold

Cct
M 2700 **N** 4000
W 3000

POUND

Aluminium body.



Vast range

Four versions, available in white and black finishes, the Pound BC, BS, S, Wall models free you from the track system whilst maintaining the advantages of the Pound range.



Pound_BC
Semi-recessed



Pound_BS
Surface
Driver on board





Pound_S
Surface
Driver on board



Pound_Wall
Surface
Driver on board

The Pound_Wall collection is designed to fit any type of situation. It makes use of the new joint that allows the product to be rotated on the vertical axis by 90° and on the horizontal axis by 350°.







Pound family

Pound_T



138-142

Pound_T Super Spot



138

Pound Focus



143-144


Pound Shaper



146-147

Pound_BS | arrayLED | 220-240 V AC | 13 W DC - 15,5 W AC






IP20

	Cct	lm S - lm D	Opt
CRI 90			
WH **82359**	**M**	1669 - 1169	**15** (17°)
BB **82360**	**W**	1771 - 1241	**30** (25°)
CRI 92 - DALI	**N**	1363 - 1305	**60** (45°)
WH **82365**			
BB **82366**			

Optic & accessories: (pag 238)

Pound_BS | arrayLED | 220-240 V AC | 25 W DC - 29 W AC






IP20

	Cct	lm S - lm D	Opt
CRI 90			
WH **82361**	**M**	3558 - 2420	**15** (19°)
BB **82362**	**W**	3725 - 2534	**30** (35°)
CRI 92 - DALI	**N**	3874 - 2636	**60** (56°)
WH **82367**			
BB **82368**			

Optic & accessories: (pag 238)

Pound_BS | arrayLED | 220-240 V AC | 34 W DC - 39 W AC






IP20

	Cct	lm S - lm D	Opt
CRI 90			
WH **82363**	**M**	4956 - 3635	**15** (17°)
BB **82364**	**W**	5019 - 3786	**30** (24°)
CRI 92 - DALI	**N**	5216 - 3861	**60** (47°)
WH **82369**			
BB **82370**			

Optic & accessories: (pag 238)

Pound_BC | arrayLED | 350 mA | 13 W DC






C.C. IP20

	Cct	lm S - lm D	Opt
CRI 90			
WH **82353**	**M**	1669 - 1169	**15** (17°)
BB **82354**	**W**	1771 - 1241	**30** (25°)
	N	1363 - 1305	**60** (45°)

Electronic: **O1** (pag 238) | Optic & accessories: (pag 238)

Pound_BC | arrayLED | 700 mA | 25 W DC






C.C. IP20

	Cct	lm S - lm D	Opt
CRI 90			
WH **82355**	**M**	3558 - 2420	**15** (19°)
BB **82356**	**W**	3725 - 2534	**30** (35°)
	N	3874 - 2636	**60** (56°)

Electronic: **T1** (pag 238) | Optic & accessories: (pag 238)

Pound_BC | arrayLED | 950 mA | 34 W DC






C.C. IP20

	Cct	lm S - lm D	Opt
CRI 90			
WH **82357**	**M**	4956 - 3635	**15** (17°)
BB **82358**	**W**	5019 - 3786	**30** (24°)
	N	5216 - 3861	**60** (47°)

Electronic: **V1** (pag 238) | Optic & accessories: (pag 238)

Pound_S | arrayLED | 220-240 V AC | 6,5 W DC - 8,5 W AC






IP40 UGR

	Cct	lm S - lm D	Opt	
Balance - CRI 90				
WH **82003**	**M**	715 - 562	**15**	(15° UGR<16)
BB **82004**	**W**	748 - 588	**30**	(22° UGR<16)
	N	805 - 630	**60**	(44°)

Optic & accessories: (pag 238)

Pound_S | arrayLED | 220-240 V AC | 17,5 W DC - 19,5 W AC






IP40 UGR

	Cct	lm S - lm D	Opt	
Balance - CRI 90				
WH **82005**	**M**	2692 - 1832	**15**	(19° UGR<16)
BB **82006**	**W**	2818 - 1919	**30**	(35° UGR<19)
	N	2930 - 1996	**60**	(56°)

Optic & accessories: (pag 238)

Pound_S | arrayLED | 220-240 V AC | 26 W DC - 29 W AC






IP40 UGR

	Cct	lm S - lm D	Opt	
Balance - CRI 90				
WH **82007**	**M**	4295 - 3126	**15**	(17° UGR<19)
BB **82008**	**W**	4349 - 3256	**30**	(24° UGR<19)
	N	4520 - 3321	**60**	(47°)

Optic & accessories: (pag 238)

Pound_Wall | arrayLED | 220-240 V AC | 6,5 W DC - 8,5 W AC






IP20

	Cct	lm S - lm D	Opt	
Balance - CRI 90				
WH **81995**	**M**	715 - 562	**15**	(15°)
BB **81996**	**W**	748 - 588	**30**	(22°)
	N	805 - 630	**60**	(44°)

Optic & accessories: (pag 238)

Pound_Wall | arrayLED | 220-240 V AC | 17,5 W DC - 19,5 W AC






IP20

	Cct	lm S - lm D	Opt	
Balance - CRI 90				
WH **81997**	**M**	2692 - 1832	**15**	(19°)
BB **81998**	**W**	2818 - 1919	**30**	(35°)
	N	2930 - 1996	**60**	(56°)

Optic & accessories: (pag 238)

Pound_Wall | arrayLED | 220-240 V AC | 26 W DC - 29 W AC






IP20

	Cct	lm S - lm D	Opt	
Balance - CRI 90				
WH **81999**	**M**	4295 - 3126	**15**	(17°)
BB **82000**	**W**	4349 - 3256	**30**	(24°)
	N	4520 - 3321	**60**	(47°)

Optic & accessories: (pag 238)

Accessories



BB **99775** Elliptical filter (a)
suitable for: Pound_BS 13W - Pound_BC 13W Pound_S 6,5W - Pound_Wall 6,5W

BB **99781** Elliptical filter (a)
suitable for: Pound_BS 25W - Pound_BC 25W Pound_S 17,5W - Pound_Wall 17,5W

BB **C-U300007** Elliptical filter (b)
suitable for: Pound_BS 34W - Pound_BC 34W Pound_S 26W - Pound_Wall 26W



BB **99777** Cross louvre
suitable for: Pound_BS 13W - Pound_BC 13W Pound_S 6,5W - Pound_Wall 6,5W

BB **99779** Cross louvre
suitable for: Pound_BS 25W - Pound_BC 25W Pound_S 17,5W - Pound_Wall 17,5W


BB **C-U300031** Cross louvre
suitable for: Pound_BS 34W - Pound_BC 34W Pound_S 26W - Pound_Wall 26W



BB **99773** 45° Cylindrical screen
suitable for: Pound_BS 13W - Pound_BC 13W Pound_S 6,5W - Pound_Wall 6,5W

BB **99782** 45° Cylindrical screen
suitable for: Pound_BS 25W - Pound_BC 25W Pound_S 17,5W - Pound_Wall 17,5W


BB **C-U300030** 45° Cylindrical screen
suitable for: Pound_BS 34W - Pound_BC 34W Pound_S 26W - Pound_Wall 26W



BB **99776** Honeycomb (b)
suitable for: Pound_BS 13W - Pound_BC 13W Pound_S 6,5W - Pound_Wall 6,5W

BB **99780** Honeycomb (b)
suitable for: Pound_BS 25W - Pound_BC 25W Pound_S 17,5W - Pound_Wall 17,5W

BB **C-U300008** Honeycomb (a)
suitable for: Pound_BS 34W - Pound_BC 34W Pound_S 26W - Pound_Wall 26W



BB **99774** Cylindrical screen
suitable for: Pound_BS 13W - Pound_BC 13W Pound_S 6,5W - Pound_Wall 6,5W

BB **99783** Cylindrical screen
suitable for: Pound_BS 25W - Pound_BC 25W Pound_S 17,5W - Pound_Wall 17,5W

BB **C-U300029** Cylindrical screen
suitable for: Pound_BS 34W - Pound_BC 34W Pound_S 26W - Pound_Wall 26W

Optics



TR **99805** Spot
TR **99806** Flood
TR **99807** W. Flood
suitable for: Pound_BS 13W - Pound_BC 13W Pound_S 6,5W - Pound_Wall 6,5W

TR **99827** Spot
TR **99828** Flood
TR **99829** W. Flood
suitable for: Pound_BS 25W - Pound_BC 25W Pound_S 17,5W - Pound_Wall 17,5W

TR **C-U300015** Spot
TR **C-U300016** Flood
TR **C-U300017** W. Flood
suitable for: Pound_BS 34W - Pound_BC 34W Pound_S 26W - Pound_Wall 26W

Electronics

O1 | Electronics

99375	**99115**	**83322**
ON/OFF	0/1-10V	DALI/PUSH
1 art.	1 art.	1 art.
138 x 22 x h 21	210 x 48 x h 25	149 x 37 x h 31
29	56	48

V1 | Electronics

99239	**83008**	**99345**
ON/OFF	0/1-10V, DALI/PUSH	DALI/PUSH
1 art.	1 art.	1 art.
103 x 58 x h 27	124 x 79 x h 22	210 x 48 x h 28
64	84	56

T1 | Electronics

99147	**83008**	**C-E100016**
ON/OFF	0/1-10V, DALI/PUSH	DALI/PUSH
1 art.	1 art.	1 art.
103 x 58 x h 27	124 x 79 x h 22	131 x 44 x h 30
64	84	54

Finishes
BB Black
TR Transparent



RESIDENTIAL HOME
Empordà (Spain)

Interior Design: A&P Interiorismo
(Loles Armengol y Eva Pallarés)

Project:
Studio Gama

Lighting Designer:
Vié II·Luminació
(@vieluxbcn) Anna Vié

Photography:
Jordi Anguera

HIGH WIRED

Body in 6060 aluminium.
Diffuser in polycarbonate.

Construction details
Profile in 6060 anodised aluminium with cover in embossed. In the version with IP44 protection grade, the insulating cable gland is built in, absent in the IP40 version.



High Wired IP40
Opaline

High Wired IP44
Embossed

Surface installation
High Wired can be surface installed on the desired surface or on busbar, using specific fixing accessories.



Surface installation on busbar




Surface installation



High Wired | topLED | 220-240 V AC | 13 W DC - 14,5 W AC






IK08 IP40

	Cct	lm S - lm D	Opt
CRI 90			
EB **94908**	**W**	1440 - 1141	**30** (101°x 90°)
DALI - CRI 90	**N**	1501 - 1216	**12** (111°x 112°)
EB **84382**			

Accessories (pag 243)

High Wired | topLED | 220-240 V AC | 20 W DC - 24 W AC






IK08 IP40

	Cct	lm S - lm D	Opt
CRI 90			
EB **94909**	**W**	2318 - 1883	**30** (101°x 90°)
DALI - CRI 90	**N**	2478 - 2005	**12** (111°x 122°)
EB **84385**			

Accessories (pag 243)

High Wired | topLED | 220-240 V AC






IK08 IP40

	Cct	lm S - lm D	lm S - lm D	Opt
CRI 90		37W	20W	
37W DC - 40,5W AC	**W**	3974 - 3195	2479 - 1985	**30** (101°x 90°)
EB **94910**	**N**	4248 - 3403	2699 - 2159	**12** (111°x 112°)
DALI - CRI 90				
20W DC - 22W AC				
EB **84388**				

Accessories (pag 243)

High Wired IP44 | topLED | 220-240 V AC | 13 W DC - 14,5 W AC






IK08 IP44

	Cct	lm S - lm D	Opt
CRI 90			
EB **94911**	**W**	1440 - 1141	**30** (101°x 90°)
DALI - CRI 90	**N**	1501 - 1216	**12** (111°x 112°)
EB **84393**			

Accessories (pag 243)

High Wired IP44 | topLED | 220-240 V AC | 20 W DC - 24 W AC






IK08 IP44

	Cct	lm S - lm D	Opt
CRI 90			
EB **94912**	**W**	2318 - 1883	**30** (101°x 90°)
DALI - CRI 90	**N**	2478 - 2005	**12** (111°x 122°)
EB **84396**			

Accessories (pag 243)

High Wired IP44 | topLED | 220-240 V AC





IK08 IP44

	Cct	lm S - lm D	lm S - lm D	Opt
CRI 90		37W	20W	
37W DC - 40,5W AC	**W**	3974 - 3195	2479 - 1985	**30** (101°x 90°)
EB **94913**	**N**	4248 - 3403	2699 - 2159	**12** (111°x 112°)
DALI - CRI 90				
20W DC - 22W AC				
EB **84399**				

Accessories (pag 243)

Finishes **Cct**

EB Embossed **W** 3000
N 4000

Accessories



99226
Fastening kit with steel clips.
Two fastening kits are required for installation.

suitable for: High Wired / High Wired IP44



99227
Fastening kit with steel clips and connector.
Two fastening kits are required for installation.

suitable for: High Wired / High Wired IP44



99228
Fastening kit with safety clasp.
Two fastening kits are required for installation.

suitable for: High Wired / High Wired IP44



99225
IP66 ON-OFF connection box.

suitable for: High Wired / High Wired IP44



99229 per meter
Extension cable in neoprene 2x1 mm^2 ON-OFF.
Example: 99229 x 3 pz = 3 m.

83213 per meter
Extension cable in neoprene 4x1 mm^2 DALI.
Example: 83213 x 3 pz = 3 m.

suitable for: High Wired / High Wired IP44



98729
Quick connector IP68 socket/plug.
2 poles ON-OFF.

99768
Quick connector IP68 socket/plug.
5 poles DALI.

suitable for: High Wired / High Wired IP44




EMY

Aluminium body. Diffuser in microprismatic PMMA.

Emy | V2 | topLED | 1200 mA | 40 W DC






	Fin	Cct	lm S - lm D	Opt
CRI 90				
C01130	**WS**	**W**	4400 - 3569	**DI** (Diffused UGR<19)
		N	4400 - 4007	

Electronics: **FN** (pag 245) | Accessories (pag 245)

Emy | V2 | topLED | 1200 mA | 40 W DC






	Fin	Cct	lm S - lm D	Opt
CRI 90				
C01131	**WS**	**W**	4400 - 4021	**DI** (Diffused)
		N	4400 - 4024	

Electronics: **FN** (pag 245) | Accessories (pag 245)

Emy | V2 | topLED | 220-240 V AC | 40W AC






	Fin	Cct	lm S - lm D	Opt
CRI 90				
C01132	**WS**	**N**	4400 - On req	**DI** (Diffused)

Accessories (pag 245)

Quick installation



Connection of the Driver to the electrical mains.



Surface installation on the modular false ceiling frame

Accessories



99584 Suspension cables 4 pz.

suitable for: Emy C01130 - C01131*

*installation over 2.80 meters is recommended.
Not suitable for Emy C01132.



99556 Surface frame 600x600x50

suitable for: Emy 595x595



99898 Surface frame 1200x300x70

suitable for: Emy 1195x295


Electronics

FN

C-E100045	**99971.02**
ON/OFF	DALI/PUSH
1 art.	1 art.
100 x 47 x h 27	145 x 46 x h 28
55	56

Surface Installation





Finishes

Smooth white

Cct

W 3000
N 4000



LINEAR SYSTEMS

Linear systems range index

Ink

Ink system Cable NEW  256, 263

Ink system Components NEW  256

Ink system LED Strip  259

Ink system_L NEW  260


Ink system_L UGR NEW  260, 264

Ink system_L NEW  260, 264

Ink system_LP NEW  261, 264

Ink system_P NEW  261, 264


Ink system_SP NEW  262, 265

Ink system Recessed  263

Ink system Electronics NEW  266


Node system

Node System_L NEW  276-277

Node System_SP NEW  278

Node System_P NEW  278

Rubber_O NEW  278

Node System Component NEW  280-281

Node System Electronics NEW  282

Rubber_O Accessories NEW  284-285

Modus

Modus_MC NEW  294

Modus_MS NEW  295

Modus_MP  296-297

Modus Microprismatic  298

Modus Optus_EX Modus Cell  298

Modus Projectors  298

Modus Sensor NEW  299

Rollip

Rollip_PRO  305

Rollip35_MC NEW  306


Rollip60_MC NEW  307


Rollip100_MC NEW  308

Rollip35_MF NEW  311


Rollip60_MF NEW  312

Rollip100_MF NEW  313

Rollip35_MS NEW  316

Rollip60_MS NEW  317

Rollip35_MP NEW  320

Rollip60_MP NEW  321

Trail

Trunking System



327

Trunking System



328

Trunking System



329

Archicove

Archicove 24V



331

Archicove 240V



331

Fylo+

Fylo+ Direct_1



336

Fylo+ Recessed_1



336

Fylo+ Recessed_2



336

Fylo+ Recessed_3



336

Fylo+ Recessed_4



336

Fylo+ Recessed_5



336

Fylo+ Surface_1



337

Fylo+ Surface_2



337

Fylo+ Surface_3



337

Fylo+ Surface_4




337

INK

PATENTED

Rubber conductor cable
Aluminium accessories



ELEGANT, NOW ALSO WHITE!

Ink revises the concept of the luminaire, disassembling and reassembling it, until it discovers new forms. The light becomes reworked, a thin strip with indirect emission allows you to cover and illuminate large distances, the same components, combined with the special extruded wall/ceiling or with the new recessed profile, become light paths that furnish the rooms. The cable also acts as a conductor on which it is possible to hook, in the lower part, various lighting elements: with diffuse emission or UGR<19, adjustable projectors also with focus optics and suspended lamps.



Ink is fully equipped
Four projectors: 6W, 10W, 12W Focus, 22W designed to meet all accent lighting needs. To complete the linear elements, a horizontal cylindrical diffuser has been inserted for all-around diffused lighting. A new recess-mounted electrified track solution comes alongside the existing system, letting you combine indirect lighting with detail lighting.

Recessed



Ink system_SP 22W | Ink system_SP Focus 12W | Ink system_SP 10W | Ink system_SP 6W

Surface



Ink system_SP 22W | Ink system_SP Focus 12W | Ink system_SP 10W | Ink system_SP 6W

Recessed Ink system


The recessed profile in three different sizes:

- 84012 1000 mm
- 84013 2000 mm
- 84014 3000 mm

the cable should be positioned inside the profile. available in the usual sizes and a new version on request:

- 81410 5000 mm
- 81411 1000 0mm
- 84016* on request

***** E.g. **84016** x 13 pieces: cable on spool with total length of 13 metres
Only for surface or recessed mounting (not suspension).






Ink is a complete linear system
Installation possibilities know no limits with INK, thanks to the wide range of acessories.



Ink is movement
To meet particular composition needs, small wall or ceiling brackets have been introduced which allow the cable to bend and, with the anchoring of the included LED strip, alternative lighting effects can be created.



84017 Clip for curves

Ink is all light
The INK system introduces a new modular element that enhances the vast range that has made it famous. A new, cylindrical shape in opal polycarbonate that alternates on/off and Dali point-point versions, available for recessed, the luce 360 module lets you create multiple solution, thanks in part to the different lengths of the profile.



83943 Ink system_L
linear module 360°



TENSIONED SYSTEM ON SLOPING BEAMED CEILING



Walls with exposed brick and sloping beamed ceilings require effective but discreet lighting, especially in the evening. The INK tensioned systems allow you to reach the desired inclination (max 45 degrees) to adapt to the ceiling, illuminating it indirectly. At the same time, the cables serve as the basis for adding projectors and pendants that complement ambient lighting where more light is needed. The driver with cover allows you to power the systems while preserving the integrity of the wall and avoiding the need to make ducts for ad hoc systems. To maintain stylistic continuity, INK is also available in the wall-mounted system with headboard projectors.

Components for Standard Ink

Ink system | Cable






IP20 NEW

WH	**83412**	5+1 m
BB	**81410**	5+1 m
WH	**83413**	10+1 m
BB	**81411**	10+1 m
WH	**83414**	1 m *
BB	**84016**	1 m *

* E.g. **84016** x 13 pieces: cable on spool with total length of 13 metres
Only for surface or recessed mounting (not suspension).

Ink system | Wall / ceiling extruded






BB	**81430**	Kit 2 x
BB	**81426**	Kit 5 x

Ink system | Cross fitting







IP20 NEW

WH	**83418**	
BB	**81418**	

Ink system | L-shaped fitting






IP20 NEW

WH	**83419**	
BB	**81419**	

Ink system | T-shaped fitting





IP20 NEW

WH	**83420**	
BB	**81420**	

Ink system | Wall / ceiling sealing cap






IP20 NEW

WH	**83421**	
BB	**81421**	

Ink system | 60x60 mounting bracket





IP20


		Kit
BB	**84010**	3 brackets x 2 profiles
BB	**84011**	3 brackets x 5 profiles

Finishes

WH White
BB Black

Ink system | Clips for curves






IP20 NEW

WH **83422** 2 x kit
BB **84017** 2 x kit

Ink system | Cardboard fixing






IP20 NEW

WH **83423** 2 x kit
BB **81422** 2 x kit

Ink system | Swivel wall fixing






IP20 NEW

WH **83424** 2 x kit
BB **81423** 2 x kit

Ink system | Steel support and cable






NEW

WH **83425**
BB **81425**

Ink system | Steel support and cable





NEW

WH **83427**
BB **83426**

The pass-through support allows the continuity of the strip module.

Accessories

Ink system | Cable shear



81427

Finishes


WH White
BB Black



Light modules

Ink system | 24 V DC | LED Strip






	Cct	Im S - Im D	Opt
CRI 90 - Basic 3,2 W/m DC			
L 1000			
TW **82946**	**M**	380 - 257	**00** (Diffused)
	W	404 - 271	
L 2500			
TW **82947**	**M**	960 - 643	
	W	1011 - 677	
L 5000			
TW **82948**	**M**	1919 - 1286	
	W	2022 - 1354	
CRI 90 - Hi-Flux 12,6 W/m DC			
L 1000			
TW **82949**	**M**	1435 - 1081	**00** (Diffused)
	W	1510 - 1138	
L 2500			
TW **82950**	**M**	3588 - 2703	
	W	3777 - 2845	
L 5000			
TW **82951**	**M**	7166 - 5405	
	W	7544 - 5690	

Ink system | 24 V DC | LED Strip





PTP DALI

	Cct	Im S - Im D	Opt
CRI 90 - DALI - Basic 3,2 W/m DC			
L 1000			
TW **83990**	**W**	404 - 271	**00** (Diffused)
L 2500			
TW **83991**	**W**	1011 - 677	
L 5000			
TW **83992**	**W**	2022 - 1354	
CRI 90 - DALI - Hi-Flux 12,6 W/m DC			
L 1000			
TW **83987**	**W**	1510 - 1138	**00** (Diffused)
L 2500			
TW **83988**	**W**	3777 - 2845	
L 5000			
TW **83989**	**W**	7544 - 5690	

Finishes


TW Transparent White

Cct

M 2700
W 3000


Ink system | 24 V DC | Linear module diffused






Cct		Im S - Im D	Opt
L 320 mm - CRI 90 - 11 W DC			
WH 77582	M	988 - 619	00 (Diffused)
BB 83943	W	1040 - 652	
L 620 mm - CRI 90 - 22 W DC			
WH 77583	M	1976 - 1283	
BB 83944	W	2081 - 1350	
L 920 mm - CRI 90 - 33 W DC			
WH 77584	M	2964 - 1886	
BB 83945	W	3120 - 1985	
L 486 mm - CRI 90 - DALI - 11 W DC			
BB 83972	W	1040 - 652	00 (Diffused)
L 786 mm - CRI 90 - DALI - 22 W DC			
BB 83973	W	2081 - 1350	
L 1086 mm - CRI 90 - DALI - 33 W DC			
BB 83974	W	3120 - 1985	


Ink system_L UGR | 24 V DC | Anti-glaring linear module






Cct		Im S - Im D	Opt
L 300 mm - CRI 90 - 7 W DC			
WH 77585	M	609 - 247	30 (33°x 37°
BB 82918	W	641 - 260	UGR<11)
L 600 mm - CRI 90 - 14 W DC			
WH 77586	M	1217 - 494	
BB 82920	W	1282 - 520	
L 465 mm - CRI 90 - DALI - 7 W DC			
BB 83970	W	641 - 260	30 (33°x 37°
L 765 mm - CRI 90 - DALI - 14 W DC			UGR<11)
BB 83971	W	1282 - 520	


Ink system_L | 24 V DC | Linear module





Cct		Im S - Im D	Opt
L 300 mm - CRI 90 - 11 W DC			
WH 77587	M	988 - 376	00 (Diffused)
BB 82914	W	1040 - 396	
L 600 mm - CRI 90 - 22 W DC			
WH 77588	M	1976 - 751	
BB 82916	W	2081 - 791	
L 465 mm - CRI 90 - DALI - 11 W DC			
BB 83968	W	1040 - 396	00 (Diffused)
L 765 mm - CRI 90 - DALI - 22 W DC			
BB 83969	W	2081 - 791	


Point to Point
DALI DIMM.




ON/OFF
DALI DIMM.



Ink system_LP UGR | 24 V DC | Anti-glaring linear Suspension






C.V. IP40 UGR NEW

	Cct	lm S - lm D	Opt
L 900 mm - CRI 90 - 9 W DC			
WH **77589**	**M**	742 - 260	**30** (33°x 58°
BB **82932**	**W**	781 - 274	UGR<16)
L 1200 mm - CRI 90 - 12 W DC			
WH **77590**	**M**	990 - 334	
BB **82944**	**W**	1041 - 352	
L 900 mm - CRI 90 - DALI - 9 W DC			PTP DALI
BB **83982**	**W**	781 - 274	**30** (33°x58°
L 1200 mm - CRI 90 - DALI - 12 W DC			UGR<16)
BB **83983**	**W**	1041 - 352	

Ink system_LP | 24 V DC | Linear Suspension






C.V. IP40 NEW

	Cct	lm S - lm D	Opt
L 900 mm - CRI 90 - 22 W DC			
WH **77591**	**M**	1978 - 702	**00** (Diffused)
BB **82928**	**W**	2081 - 738	
L 1200 mm - CRI 90 - 29 W DC			
WH **77592**	**M**	2607 - 902	
BB **82930**	**W**	2744 - 950	
L 900 mm - CRI 90 - DALI - 22 W DC			PTP DALI
BB **83980**	**W**	2081 - 738	**00** (Diffused)
L 1200 mm - CRI 90 - DALI - 29 W DC			
BB **83981**	**W**	2744 - 950	

Ink system_P | 24 V DC | Suspension







C.V. IP40 NEW

	Cct	lm S - lm D	Opt
L 104 mm - CRI 90 - 6 W DC			
WH **77593** HC	**M**	674 - 445	**45** (47°)
BB **82926** HC	**W**	709 - 468	
L 225 mm - CRI 90 - DALI - 6 W DC			PTP DALI
BB **83979** HC	**W**	709 - 468	**45** (47°)

Ink system_SP | 24 V DC | Projector






C.V. IP40 NEW

	Cct	lm S - lm D	Opt
L 104 mm - CRI 90 - 6 W DC			
WH **77594**	HC	**M** 674 - 418	**10** (21°)
BB **82922**	HC	**W** 709 - 440	**30** (31°)
			45 (42°)
L 225 mm - CRI 90 - DALI - 6 W DC			
BB **83975**	HC	**W** 709 - 440	**10** (21°)
			30 (31°)
			45 (42°)

Ink system_SP | 24 V DC | Projector






C.V. IP40 NEW

	Cct	lm S - lm D	Opt
L 104 mm - CRI 90 - 10 W DC			
WH **77595**	HC	**M** 1015 - 655	**30** (31°)
BB **83946**	HC	**W** 1068 - 690	**45** (42°)
L 225 mm - CRI 90 - DALI - 10 W DC			
BB **83976**	HC	**W** 1068 - 690	**30** (31°)
			45 (42°)

Ink system_SP Focus | 24 V DC | Projector






C.V. IP40 NEW

	Cct	lm S - lm D	Opt
L 104 mm - CRI 90 - 12 W DC			
WH **77596**		**M** 1173 - On req	**85** (16°-35°)
BB **83947**		**W** 1234 - On req	
L 225 mm - CRI 90 - DALI - 12 W DC			
BB **83977**		**W** 1234 - On req	**85** (16°-35°)

Ink system_SP | 24 V DC | Projector







C.V. IP40 NEW

	Cct	lm S - lm D	Opt
L 114 mm - CRI 90 - 22 W DC			
WH **77597**	HC	**M** 2407 - 1877	**20** (20°)
BB **83948**	HC	**W** 2534 - 1976	**35** (36°)
			60 (62°)
L 225 mm - CRI 90 - DALI - 22 W DC			
BB **83978**	HC	**W** 2534 - 1976	**20** (20°)
			35 (36°)
			60 (62°)

Components for recessed Ink


Ink system | Wall / ceiling Recessed profile






BB	**84012**	1 m
BB	**84013**	2 m
BB	**84014**	3 m

Ink system | Recessed corner







BB	**84015**	



81419 L-shaped fitting included

Ink system | Recessed corner-IN






BB	**84073**	

Ink system | Recessed corner-OUT






BB	**84074**	

Ink system | Closing plug







BB	**83153**	2x



81421 Wall / ceiling sealing cap included

Ink system | Cable





WH	**83412**	5+1 m
BB	**81410**	5+1 m
WH	**83413**	10+1 m
BB	**81411**	10+1 m
WH	**83414**	1 m *
BB	**84016**	1 m *


* E.g. **84016** x 13 pieces: cable on spool with total length of 13 metres
Only for surface or recessed mounting (not suspension).


Finishes

WH White
BB Black

Light modules for recessed Ink


Ink system_L UGR | 24 V DC | Recessed anti-glaring linear module






	Cct	lm S - lm D	Opt
L 342 mm - CRI 90 - 7 W DC			
BB **83954**	**W**	641 - 260	**30** (33°x 37° UGR<11)
L 642 mm - CRI 90 - 14 W DC			
BB **83955**	**W**	1282 - 520	
L 502 mm - CRI 90 - DALI - 7 W DC			PTP DALI
BB **83995**	**W**	641 - 260	**30** (34°x 37° UGR<11)
L 802 mm - CRI 90- DALI - 14 W DC			
BB **83996**	**W**	1282 - 520	

Ink system_L | 24 V DC | Recessed linear module






	Cct	lm S - lm D	Opt
L 342 mm - CRI 90 - 11 W DC			
BB **83952**	**W**	1040 - 396	**00** (Diffused)
L 642 mm - CRI 90 - 22 W DC			
BB **83953**	**W**	2081 - 791	
L 502 mm - CRI 90 - DALI - 11 W DC			PTP DALI
BB **83993**	**W**	1040 - 396	**00** (Diffused)
L 802 mm - CRI 90- DALI - 22 W DC			
BB **83994**	**W**	2081 - 791	

Ink system_LP UGR | 24 V DC | Recessed Anti-glaring linear suspension






	Cct	lm S - lm D	Opt
L 963 mm - CRI 90 - 9 W DC			
BB **83963**	**W**	781 - 274	**30** (33°x 58° UGR<16)
L 1264 mm - CRI 90 - 12 W DC			
BB **83964**	**W**	1041 - 352	
L 963 mm - CRI 90 - DALI - 9 W DC			PTP DALI
BB **84004**	**W**	781 - 274	**30** (33°x 58° UGR<16)
L 1264 mm - CRI 90 - DALI - 12 W DC			
BB **84005**	**W**	1041 - 352	

Ink system_LP | 24 V DC | Recessed linear suspension






	Cct	lm S - lm D	Opt
L 963 mm - CRI 90 - 22 W DC			
BB **83961**	**W**	2081 - 738	**00** (Diffused)
L 1264 mm - CRI 90 - 29 W DC			
BB **83962**	**W**	2744 - 950	
L 963 mm - CRI 90 - DALI - 22 W DC			PTP DALI
BB **84002**	**W**	2081 - 738	**00** (Diffused)
L 1264 mm - CRI 90 - DALI - 29 W DC			
BB **84003**	**W**	2744 - 950	

Ink system_P | 24 V DC | Recessed suspension







	Cct	lm S - lm D	Opt
L 141 mm - CRI 90 - 6 W DC			
BB **83960** HC	**W**	709 - 468	**45** (47°)
L 262 mm - CRI 90 - DALI - 6 W DC			PTP DALI
BB **84001** HC	**W**	709 - 468	**45** (47°)

Ink system_SP | 24 V DC | Recessed projector











Ink system_SP Focus | 24 V DC | Recessed projector





Ink system_SP | 24 V DC | Recessed projector






	Cct	Im S - Im D	Opt
L 141 mm - CRI 90 - 6 W DC			
BB **83956** HC	**W**	709 - 440	**10** (21°) **30** (31°) **45** (42°)
L 262 mm - CRI 90 - DALI - 6 W DC			
BB **83997** HC	**W**	709 - 440	**10** (21°) **30** (31°) **45** (42°)

	Cct	Im S - Im D	Opt
L 141 mm - CRI 90 - 10 W DC			
BB **83957** HC	**W**	1068 - 690	**30** (31°) **45** (42°)
L 262 mm - CRI 90 - DALI - 10 W DC			
BB **83998** HC	**W**	1068 - 690	**30** (31°) **45** (42°)

	Cct	Im S - Im D	Opt
L 141 mm - CRI 90 - 12 W DC			
BB **83958**	**W**	1234 - On req	**85** (16°-35°)
L 262 mm - CRI 90 - DALI - 12 W DC			
BB **83999**	**W**	1234 - On req	**85** (16°-35°)

	Cct	Im S - Im D	Opt
L 141 mm - CRI 90 - 22 W DC			
BB **83959** HC	**W**	2534 - 1976	**20** (20°) **35** (36°) **60** (62°)
L 262 mm - CRI 90 - DALI - 22 W DC			
BB **84000** HC	**W**	2534 - 1976	**20** (20°) **35** (36°) **60** (62°)


Recessed connection modules
The new recessed modules are designed with a new connection system that guarantees stability and safety. Using the included hex wrench, lodging the fixture in the recessed mount becomes extremely simple.





Accessories

Ink system | Template



83186 1100 x 80


Finishes
BB Black

Cct
W 3000

Electronics

Ink system | ON/OFF driver with cover | 220-240 V AC





C.V. IP20 NEW

WH	**83415**	120 W	Canopy for wall or ceiling installation
BB	**81413**	120 W	
WH	**83416**	180 W	
BB	**81414**	180 W	

The canopy allows for the possibility to feed Ink from both sides.

Ink system | ON/OFF driver with cover | 220-240 V AC






C.V. IP20 NEW

WH	**83429**	120 W	L 465	Ceiling power supply for overhead installation. * 2m cable included
BB	**83428**	120 W	L 465	
WH	**83431**	180 W	L 510	
BB	**83430**	180 W	L 510	

Ink system | Junction box






IP20 NEW

WH	**83417**	Junction box
BB	**81424**	

Ink system | Remote ON/OFF driver | 220-240 V AC






C.V. IP20

WH	**81416**	300 mm	120 W - Output 24 V DC
WH	**81417**	345 mm	180 W - Output 24 V DC

Ink system | Dimmer converter | DALI PUSH | 0/1-10V






C.V. DALI PUSH DALI 1-10V C.V. IP20

WH	**83042**	288 W Max - Input 24 V DC

To be completed with driver 24 V DC

Ink system | Remote converter | DALI 2 PointToPoint





C.V. DALI2 PTP DALI IP20

WH	**84018**	180 W Max - Input 24 V DC

To be completed with driver 24 V DC






NODE SYSTEM

Aluminium profile
Polycarbonate diffuser
Aluminium accessories

BEYOND ALL LIMITS. MODULAR LIGHT WITHOUT BORDERS.

Node System is the new i-LèD linear system, designed to overcome any architectural obstacle, allowing you to shape unique and exclusive compositions. Single or bi-emission light modules are available in different lengths, with diffused light or with controlled UGR thanks to the special optical cells that guarantee an UGR <19, projectors and directional suspensions for total design creativity. The distinctive feature of the Node System lies in the absolute freedom of movement, with the ability to rotate 360 degrees and orient itself in any direction, without any constraints. This versatility makes it an ideal lighting system for any context, it plays with the surrounding architecture and creates original and evocative atmospheres.

360° ROTATION



The Node System simplifies installation with an ultra-fast connection system.
The light modules can rotate 360° without interruption.



NODE SYSTEM DESIGNED TO MEET
EVERY ARCHITECTURAL CHALLENGE.
IN ANY CONTEXT.



LIGHT MODULES

48V



Diffused light linear module from
11W DC to 32W DC
L 629 mm / L 1188 mm / L 1748 mm



Comfort micro-cell module UGR<19
12W DC - 33W DC
L 629 mm / L 1188 mm / L 1748 mm




Comfort micro-cell module UGR<19
+ indirect diffused light.
From 48W DC to 64W DC
L 1188 mm / L 1748 mm




Pendant projector module
6W DC - Ø 70 mm



Pendant projector module
11W DC - Ø 80 mm




Projector module
6W DC - Ø 70 mm



Projector module
11W DC - Ø 80 mm

ELECTRIFIED TRACK MODULE



Rubber_O flexible module from 30W DC to 120W DC.
L 2500 mm / L 5000 mm / L 10000 mm

The fixture only allows the electrical connection on one side and must be completed with the relevant Rubber_O accessories.




Electrified track module for projectors. It can be used as an electrified blind module (to be combined with the Track Cover accessory).
L 629 mm max 2 luminaires
L 1188 mm max 4 luminaires
L 1748 mm max 6 luminaires




Accessory cover for track module. It can be cut according to the number of luminaires installed.
L 1119 mm / L 1679 mm


JUNCTION & CONNECTION ACCESSORIES




Suspended blanking cap.




Suspended linear joint.




Suspended adjustable joint (horizontal axis).




Suspended T-shaped joint.




Suspended line power supply plug.




Suspended central power supply joint.




Power supply on suspended adjustable joint (horizontal axis).




Suspended T-shaped power supply joint.




Wall/ceiling blanking cap.




Wall/ceiling linear joint.




Connector, for power supply for driver with wall/ceiling cover.




Connector for power supply from multiple rosette.



Wall/ceiling adjustable joint (horizontal axis).



Wall/ceiling adjustable joint (vertical axis).



Wall/ceiling T-shaped joint.



Multiple rose max 8 connections.



ON/OFF driver with cover - wall/ceiling.



ON/OFF driver with cover - suspension.


The connectors allow electrical continuity between the linear modules, however, it is possible to interrupt the line from one of the two poles with the accessory provided.





Node System_L | 48V DC | Diffused light linear module






	Cct	Im S - Im D	Opt
L 629 mm - CRI 90 - 11 W DC			
WH 76372	M	1812 - 1054	00 (Diffused)
BB 76373	W	1923 - 1098	
L 1188 mm - CRI 90 - 23 W DC			
WH 76374	M	3624 - 2108	
BB 76375	W	3826 - 2197	
L 1748 mm - CRI 90 - 31 W DC			
WH 76376	M	5436 - 2810	
BB 76377	W	5739 - 2928	

DALI 2

L 629 mm - CRI 90 - DALI2 - 12 W DC			
WH 76396	M	1812 - 1054	00 (Diffused)
BB 76397	W	1923 - 1098	
L 1188 mm - CRI 90 - DALI2 - 24 W DC			
WH 76398	M	3624 - 2108	
BB 76399	W	3826 - 2197	
L 1748 mm - CRI 90 - DALI2 - 32 W DC			
WH 76400	M	5436 - 2810	
BB 76401	W	5739 - 2928	

Node System_L Comfort | 48V DC | Anti-glaring linear module






	Cct	Im S - Im D	Opt
L 629 mm - CRI 90 - 12 W DC			
WH 76378	M	1778 - 1047	50 (49° UGR<19)
BB 76379	W	1887 - 1090	
L 1188 mm - CRI 90 - 24 W DC			
WH 76380	M	3556 - 2093	
BB 76381	W	3754 - 2180	
L 1748 mm - CRI 90 - 32 W DC			
WH 76382	M	5334 - 2766	
BB 76383	W	5631 - 2881	

DALI 2

L 629 mm - CRI 90 - DALI2 - 12 W DC			
WH 76402	M	1778 - 1047	50 (49° UGR<19)
BB 76403	W	1887 - 1090	
L 1188 mm - CRI 90 - DALI2 - 25 W DC			
WH 76404	M	3556 - 2093	
BB 76405	W	3754 - 2180	
L 1748 mm - CRI 90 - DALI2 - 33 W DC			
WH 76406	M	5334 - 2766	
BB 76407	W	5631 - 2881	

Node System_L Comfort | 48V DC | Double emission linear module





	Cct	Im S - Im D	Opt
L 1188 mm - CRI 90 - 48 W DC			
WH 76384	M	7142 - 4640	61 (49° UGR<19+Diff)
BB 76385	W	7540 - 4833	
L 1748 mm - CRI 90 - 63 W DC			
WH 76386	M	10713 - 6132	
BB 76387	W	11310 - 6387	

DALI 2


L 1188 mm - CRI 90 - DALI2- 49 W DC			
WH 76408	M	7142 - 4640	61 (49° UGR<19 +Diff)
BB 76409	W	7540 - 4833	
L 1748 mm - CRI 90 - DALI2 - 64 W DC			
WH 76410	M	10713 - 6132	
BB 76411	W	11310 - 6387	

Finishes
WH White
BB Black

Cct
M 2700
W 3000

Node System_L | 48V DC | Electrified track module





C.V. IP40 NEW

WH	**83309**	L 629 mm	max 2 x spotlights or suspension spotlights
BB	**83310**	L 629 mm	max 2 x spotlights or suspension spotlights
WH	**83311**	L 1188 mm	max 4 x spotlights or suspension spotlights
BB	**83312**	L 1188 mm	max 4 x spotlights or suspension spotlights
WH	**83313**	L 1748 mm	max 6 x spotlights or suspension spotlights
BB	**83314**	L 1748 mm	max 6 x spotlights or suspension spotlights

Node System_L | Track cover





NEW

WH	**83316**	L 1119 mm
BB	**83317**	L 1119 mm
WH	**83318**	L 1679 mm
BB	**83319**	L 1679 mm




The 76385W61 double emission linear module is ideal for office applications, ensuring correct illuminance on the worktop with values above 500lx while the Comfort optical cells guarantee an UGR value of <19.

Finishes

WH White
BB Black

Node System_SP | 48V DC | Projector






C.V. IP40 NEW

	Cct	lm S - lm D	Opt	
CRI 90 - 5 W DC				
WH **76420**	**M**	603 - 543	**15**	(17°)
BB **76421**	**W**	621 - 559	**35**	(34°)
			60	(63°)
CRI 90 - DALI2 - 6 W DC				DALI 2
WH **76424**	**M**	603 - 543	**15**	(17°)
BB **76425**	**W**	621 - 559	**35**	(34°)
			60	(63°)

Node System_SP | 48V DC | Projector







C.V. IP40 NEW

	Cct	lm S - lm D	Opt	
CRI 90 - 10 W DC				
WH **76422**	**M**	959 - 863	**15**	(16°)
BB **76423**	**W**	988 - 889	**35**	(34°)
			60	(58°)
CRI 90 - DALI2- 11 W DC				DALI 2
WH **76426**	**M**	959 - 863	**15**	(16°)
BB **76427**	**W**	988 - 889	**35**	(34°)
			60	(58°)

Node System_P | 48V DC | Suspended projector







C.V. IP40 NEW

	Cct	lm S - lm D	Opt	
CRI 90 - 5 W DC				
WH **76428**	**M**	603 - 543	**15**	(17°)
BB **76429**	**W**	621 - 559	**35**	(34°)
			60	(63°)
CRI 90 - DALI2- 6 W DC				DALI 2
WH **76432**	**M**	603 - 543	**15**	(17°)
BB **76433**	**W**	621 - 559	**35**	(34°)
			60	(63°)

Node System_P | 48V DC | Suspended projector






C.V. IP40 NEW

	Cct	lm S - lm D	Opt	
CRI 90 - 10 W DC				
WH **76430**	**M**	959 - 863	**15**	(16°)
BB **76431**	**W**	988 - 889	**35**	(34°)
			60	(58°)
CRI 90 - DALI2 - 11 W DC				DALI 2
WH **76434**	**M**	959 - 863	**15**	(16°)
BB **76435**	**W**	988 - 889	**35**	(34°)
			60	(58°)

Rubber_O | topLED | 48 V DC | 12 W/m





C.V. R9 >50 IP65 NEW

		Cct	lm S/m - lm D/m	Opt	L	
CRI 90						
C0020		**M**	3845 - On req	**DI**	**02517**	(2,5 m - 30 W)
		W	4135 - On req		**05017**	(5 m - 60 W)
		N	4425 - On req		**10017**	(10 m - 120 W)

Electronics: **EK** (pag 285) | Accessories (pag. 284/285)

The Rubber_O module can be only be used in the wall/ceiling installations (it cannot be installed on pendant configurations). Use the following connection accessories to join Rubber_O to the system: 83297,83298 (On-Off) or 83305,83306 (DALI2).

Finishes

WH White
BB Black

Cct

M 2700
W 3000



350° head rotation




330° rotation of the cable


ROTATION ON EVERY AXIS


The head of the Node System projectors can be easily adjusted on all the axes, obtaining extremely precise points of light. The intuitive orientation on every axis ensures optimal customisation of the lighting, adapting it to the specific needs of every environment.





Node System | Suspended blanking cap







IP20 NEW

WH **83281**
BB **83282**

Node System | Suspended linear joint







IP20 NEW

WH **83275**
BB **83276**

With the special accessory included, it is possible to stop the line from one of the two poles.

Node System | Suspended adjustable joint (horizontal axis)






IP20 NEW

WH **83271**
BB **83272**

With the special accessory included, it is possible to stop the line from one of the two poles.

Node System | Suspended T-shaped joint







IP20 NEW

WH **C-U500010**
BB **C-U500011**

With the special accessory included, it is possible to stop the line from one of the two poles.

Node System | Suspended plug with power supply cable






IP20 NEW

WH **83279**
BB **83280**

To be completed with: driver with cover - pendant (pag. 282).

Node System | Suspended joint with power supply cable






IP20 NEW

WH **83277** Input 48V DC
BB **83278** Input 48V DC

With the special accessory included, it is possible to stop the line from one of the two poles.
To be completed with: driver with cover - pendant (pag. 282).

Node System | Suspended joint with power supply cable






IP20 NEW

WH **83273** Input 48V DC
BB **83274** Input 48V DC

With the special accessory included, it is possible to stop the line from one of the two poles.
To be completed with: driver with cover - pendant (pag. 282).

Node System | Suspended T-shaped joint with power supply cable






IP20 NEW

WH **C-U500012**
BB **C-U500013**

With the special accessory included, it is possible to stop the line from one of the two poles.
To be completed with: driver with cover - pendant (pag. 282).

Node System | Wall/ceiling blanking cap



IP20 NEW

WH **83287**
BB **83288**

Node System | Wall/ceiling linear joint




IP20 NEW

WH **83291**
BB **83292**

With the special accessory included, it is possible to stop the line from one of the two poles.

Node System | Wall/ceiling adjustable joint (horizontal axis)




IP20 NEW

WH **83283**
BB **83284**

With the special accessory included, it is possible to stop the line from one of the two poles.

Node System | Wall/ceiling adjustable joint (vertical axis)




IP20 NEW

WH **83285**
BB **83286**

With the special accessory included, it is possible to stop the line from one of the two poles.

Node System | Wall/ceiling T-shaped joint



IP20 NEW

WH **C-U500008**
BB **C-U500009**

With the special accessory included, it is possible to stop the line from one of the two poles.

Node System | Connector for multiple rose




IP20 NEW

WH **83295**
BB **83296**

The line can be interrupted with the relevant accessory included.
To be completed with: multiple rose.


Node System | Multiple rose max 8 connections



IP20 NEW

WH **83254** Input 48V DC
BB **83255** Input 48V DC

Node System | Connector for Driver with wall/ceiling cover



IP20 NEW


WH **83293**
BB **83294**


To be completed with: driver with cover - wall/ceiling (pag. 282).

Finishes

WH White
BB Black

Node System | ON/OFF driver with cover - wall/ceiling






C.V. IP20 NEW

WH	**83256**	100W - Output 48V DC - Input 220-240V AC
BB	**83257**	100W - Output 48V DC - Input 220-240V AC

Node System | ON/OFF driver with cover - wall/ceiling







C.V. IP20 NEW

WH	**83260**	150W - Output 48V DC - Input 220-240V AC
BB	**83261**	150W - Output 48V DC - Input 220-240V AC
WH	**83264**	240W - Output 48V DC - Input 220-240V AC
BB	**83265**	240W - Output 48V DC - Input 220-240V AC

Node System | ON/OFF driver with cover - suspension






C.V. IP20 NEW

WH	**83258**	100W - Output 48V DC - Input 220-240V AC
BB	**83259**	100W - Output 48V DC - Input 220-240V AC

Node System | ON/OFF driver with cover - suspension






C.V. IP20 NEW

WH	**83262**	150W - Output 48V DC - Input 220-240V AC
BB	**83263**	150W - Output 48V DC - Input 220-240V AC
WH	**83266**	240W - Output 48V DC - Input 220-240V AC
BB	**83267**	240W - Output 48V DC - Input 220-240V AC

Node System | Remote ON/OFF driver






C.V. IP67

WH	**99784**	219 mm	150W - Output 48V DC - Input 220-240V AC
WH	**99785**	244 mm	240W - Output 48V DC - Input 220-240V AC

Node System | Dimmer converter | DALI | DALI PUSH | 0/1-10V






C.V. IP20 DALI PUSH DALI 1-10V

WH	**83042**	288 W Max - Input 48 V DC

To be completed with driver 48 V DC

Node System | DALI Signal Optoisolator






C.V. IP20

WH	**83270**	Input 48V DC DALI In - Out Opto-Isolated

Protection device to be installed after the driver, electrically isolates the digital input line from the output line. DALI2 compatible.

Node System | Template for suspended installation



NEW

BB	**83269**	


The accessory facilitates the installation of suspension joints and related linear modules, ensuring that the spacing is maintained even in configurations that require different angles on the installation surface.


Finishes

WH White
BB Black



Rubber_O | Wall/ceiling connector







IP20 NEW

WH **83297**
BB **83298**

Accessory for electrical connection (On-Off) + Node System mechanical connection for Rubber_O modules.

Rubber_O | DALI2 wall/ceiling connector






IP20 DALI NEW


DALI 2

WH **83305**
BB **83306**

Accessory for electrical connection (DALI2) + Node System mechanical connection for Rubber_O modules.

Rubber_O | Suspension kit






NEW

WH **C-W500001** 1 x ring + steel cable

Accessory for the suspended mounting of Rubber_O modules.

Rubber_O | Fixing clip wall/ceiling






NEW

TR **C-F400005** 1 x wall clip + 3 x screws

Clip for wall/ceiling mounting of Rubber_O modules.

Rubber_O | 1/2-way connector






IP20 NEW

WH **C-F300001**
BB **C-F300002**

Accessory for wall/ceiling mounting or power supply (with remote driver) of Rubber_O modules.

Rubber_O | 1/2-way connector with on/off driver







C.V. IP20 NEW

WH **C-F300003** 48 V DC - 60W max
BB **C-F300004** 48 V DC - 60W max

Accessory for wall/ceiling mounting and power supply of Rubber_O modules.

Rubber_O | 1/2-way connector with on/off driver






C.V. IP20 NEW

WH **C-F300009** 48 V DC - 120W max
BB **C-F300010** 48 V DC - 120W max

Accessory for wall/ceiling mounting and power supply of Rubber_O modules.

Rubber_O | Ceiling connector






IP20 NEW

WH **C-F300005**
BB **C-F300006**

Accessory for ceiling fixing or power supply (with remote driver) of Rubber_O modules.

Rubber_O | Ceiling connector with on/off driver





C.V. IP20 NEW

WH **C-F300007** 48 V DC - 60W max
BB **C-F300008** 48 V DC - 60W max

Accessory for ceiling mounting and power supply of Rubber_O modules.

Electronics

EK

99784	99785	C-E400003	Switching	83177
ON/OFF	ON/OFF	DALI/PUSH	CV 48V	Dimmer DMX
150W CV 48V	240W CV 48V	150W CV 48V		312W
219 x 63 x h 35	244 x 71 x h 38	188 x 68 x h 34	Pag. 945-946	97 x 36 x h 62
80	81	77		



Finishes

WH White
BB Black

MODUS

Aluminium profile, polycarbonate diffuser,
aluminium accessories


SUSPENSION, CEILING, RECESS: EXTENDED AND VERSATILE SYSTEM


Modus is a modular system, consisting of an aluminum profile that houses a 24 V electrified track inside, available in three neutral finishes white, black and burnished and with a wide range of modules that offer great freedom of composition. The system includes different elements and numerous accessories, each dedicated to a specific lighting scenario or a precise operating environment. The great ease of use is joined by the speed of integration and variation of the elements, all easily press-fitted into the track. The extreme versatility of Modus makes it suitable for various spaces such as offices, retail environments, museums or even modern residential settings. Modus is a system conceived and designed to simplify and streamline any technical lighting creation, no matter how complex.



WIDE RANGE OF ACCESSORIES

Modus is a linear system made up of various lighting elements such as adjustable spotlights and projectors, modules with UGR<19 anti-glare cells, wall-washers (a single module lets you direct the asymmetric beam to the right or left) and linear modules with UGR<19. The vast range and the quick connection system facilitate the operations of replacing the fixtures or changing the lighting scenery. You can change accessories and scenery with a simple gesture, plus the system has the latest generation DALI protocol.





Asymmetric Module

The system is fitted with a microcells asymmetric diffuser. Equipped with high performance LEDs, the module guarantees wide uniformity of the illuminated walls, increasing the perception of the spaces lit by the system.





Adjustable Spotlights Module

Equipped with adjustable spotlights, the system defines not only office environments, but also multi-function areas that require accent lighting. In addition to the 2 different 7 and 12 watt protectors, the system also includes the optus_EX microprojectors that disappear inside the extruded profile thanks to the extremely reduced dimensions.



Light-PIR Sensor Module


The Light-PIR sensor module allows light to be precisely and reliably adapted to the needs of workers in every work environment. This means that the lighting can be adapted based on the quantity of natural light available, the type of work being carried out, and personal preference.

Maximum power connectable on a 10-metre line (accessories).
Master 1200 - 1500 mm, 90 W max | **Master** 2400 - 3000 mm, 140 W max



Modus_MP


Modus_MC





Air Quality Sensor Module

The AQS sensor constantly monitors the air by defining the VOC index. Through DALI management, it is possible to interact with home automation systems such as KNX to control the ventilation of rooms (e.g. automatic opening of windows). The module is equipped with a signal LED that changes colour to define the level of air quality.




Indirect emission

The indirect component of Modus is characterised by a high performance circuit with an opening angle of 150° through the use of micro-optics distributed in the upper part of the chassis. Available with white light or with Dynamic white technology, Modus distributes the light in a uniform way over the entire surface of the ceiling, increasing visual comfort in the entire environment.



Microcells Module

The microcells direct light system with set-back optics (darklight) was designed to distribute the light beam in a clear and uniform way on the lit surface, ensuring significant comfort (UGR<19) without invading the surrounding work areas.



Microprismatic linear module

The module is available in 3 different dimensions to cover multiple design needs. It has a high performance LED circuit and guarantees a light distribution in a uniform way and with low glare levels (UGR<19) thanks to an optics system made up of the overlapping of microcells, batwing filter and microprismatic refractor.



MIONETTO
Valdobbiadene - Treviso (Italy)

Architect: QUIET ARCHITECTURE di Treviso Arch. Alberto Salvadori e Arch. Moris Valeri

Designed by: Gisela Steiger, founder of Autentico Architectural Lighting Design, during her time at Fantastico studio

Photos:
Marco Zanta




VISUAL COMFORT AND WELLNESS





Modus is a system optimised for Human Centric Lighting, conceived to improve time spent in work and study spaces based on the principles of the Circadian rhythm. The product was conceived and designed to provide extremely high visual and dwelling comfort for the residents, increasing wellness and improving productivity. On the upper part of the profile, a particular optics system was designed that allows a 150° opening of the light beam. The two mono-chromatic colour temperatures (3500°K or 4000K°) are joined by the Dynamic White technology (from 2700°K to 5000°K) for indirect ambient lighting intended to favour a long stay in the operational spaces. It is a flexible and completely adaptive system.



White **(WH)** + White **(WH)**



White **(WH)** + Black **(BB)**



Black **(BB)** + White **(WH)**





Black **(BB)** + Black **(BB)**





Modus_MC | 24 V DC





	Fin		
L 1200 mm **C00170**	**WH**	**EZZ**	45x1200
	BB		
L 1500 mm **C00171**			45x1500
L 2400 mm **C00172**			45x2400
L 3000 mm **C00173**			45x3000

EZZ = Without light unit


Electronics: **AL** (pag 294)


Electronics

AL

99374	**99331**	**99332**	**83333**	**C-E400002**
ON/OFF	ON/OFF	0/1-10V	DALI/PUSH	DALI/PUSH
75W	150W	150W	150W	240W
210 x 49 x h 25	158 x 60 x h 35	158 x 60 x h 35	188 x 68 x h 34	188 x 68 x h 34
56	70	70	77	77


Modus_MC | L-shaped fitting






WH **C-K400027**
BB **C-K400026**


Modus_MC | T-shaped fitting






WH **C-K400037**
BB **C-K400036**

Modus_MC | Cross fitting






WH **C-K400031**
BB **C-K400030**

Modus_MC | Caps kit







2 x
WH **C-K400056**
BB **C-K400057**

Finishes

WH White
BB Black

Modus_MS Master | 220-240 V AC





DALI

Fin

L 1200 mm - 90 W DC - 96 W AC - DALI
C00065 WH EZZ
BB


L 1500 mm - 90 W DC - 96 W AC - DALI
C00066 WH EZZ
BB


L 2400 mm - 140 W DC - 150 W AC - DALI
C00067 WH EZZ
BB

L 3000 mm - 140 W DC - 150 W AC - DALI
C00068 WH EZZ
BB

EZZ = Without light unit

Modus_MS Slave





DALI

Fin

L 1200 mm
C00069 WH EZZ
BB

L 1500 mm
C00070

L 2400 mm
C00071


L 3000 mm
C00072


EZZ = Without light unit

Maximum power connectable on a 10-metre line (accessories).
Master 1200 - 1500 mm, 90 W max | **Master** 2400 - 3000 mm, 140 W max




Modus_MS | L-shaped fitting






WH **C-K400001**
BB **C-K400002**
WB **C-K400016**
BH **C-K400017**


Modus_MS | T-shaped fitting






WH **C-K400005**
BB **C-K400004**
WB **C-K400018**
BH **C-K400019**

Modus_MS | Cross fitting






WH **C-K400008**
BB **C-K400007**
WB **C-K400020**
BH **C-K400021**

Modus_MS | Caps kit







2 x
WH **83108**
BB **83109**

Finishes

WH White WB White/Black
BB Black BH Black/White

Modus_MP Master | topLED | 220-240 V AC







C.V. IP40 **DALI**

	Cct	lm S - lm D	Opt
L 1200 mm - CRI 90 - 22 W DC - 24 W AC			
WH **83712**	**W**	3020 - 2421	**00** (Diffused Indirect)
BB **83736**	**N**	3175 - 2542	
L 1500 mm - CRI 90 - 29 W DC - 31 W AC			
WH **83713**	**W**	4027 - 3328	**00** (Diffused Indirect)
BB **83737**	**N**	4234 - 3389	
L 2400 mm - CRI 90 - 47 W DC - 51 W AC			
WH **83714**	**W**	6544 - 5259	**00** (Diffused Indirect)
BB **83738**	**N**	6880 - 5525	
L 3000 mm - CRI 90 - 62 W DC - 67 W AC			
WH **83715**	**W**	8558 - 6876	**00** (Diffused Indirect)
BB **83739**	**N**	8996 - 7220	

Modus Cct W = 3500 K

Modus_MP Slave | topLED | 220-240 V AC





C.V. IP40 **DALI**


	Cct	lm S - lm D	Opt
L 1200 mm - CRI 90 - 22 W DC - 24 W AC			
WH **83716**	**W**	3020 - 2421	**00** (Diffused Indirect)
BB **83740**	**N**	3175 - 2542	
L 1500 mm - CRI 90 - 29 W DC - 31 W AC			
WH **83717**	**W**	4027 - 3328	**00** (Diffused Indirect)
BB **83741**	**N**	4234 - 3389	
L 2400 mm - CRI 90 - 47 W DC - 51 W AC			
WH **83718**	**W**	6544 - 5259	**00** (Diffused Indirect)
BB **83742**	**N**	6880 - 5525	
L 3000 mm - CRI 90 - 62 W DC - 67 W AC			
WH **83719**	**W**	8558 - 6876	**00** (Diffused Indirect)
BB **83743**	**N**	8996 - 7220	


Modus Cct W = 3500 K

Maximum power connectable on a 10-metre line (accessories).
Master 1200 - 1500 mm, 90 W max | **Master** 2400 - 3000 mm, 140 W max



Modus_M | L-shaped fitting







IP40

WH **83733**
BB **83757**
WB **83221**
BH **83222**

Modus_M | T-shaped fitting







IP40 NEW

WH **C-K400011**
BB **C-K400010**
WB **C-K400022**
BH **C-K400023**

Modus_M | Cross fitting






IP40 NEW

WH **C-K400014**
BB **C-K400013**
WB **C-K400024**
BH **C-K400025**

Modus_M | Caps kit







2 x
WH **83108**
BB **83109**

Finishes
WH White WB White/Black
BB Black BH Black/White

Cct
W 3500
N 4000

Modus_MP Master Dynamic-White | topLED | 220-240 V AC







C.V. IP40 DW DALI

	Cct	Opt
L 1200 mm - CRI 80 - 20 W DC - 23 W AC		
WH **83791** / BB **83815**	**D** 2700K - 5000K Dynamic White	**00** (Diffused Indirect)
L 1500 mm - CRI 80 - 27 W DC - 30 W AC		
WH **83792** / BB **83816**	**D** 2700K - 5000K Dynamic White	**00** (Diffused Indirect)
L 2400 mm - CRI 80 - 43 W DC - 48 W AC		
WH **83793** / BB **83817**	**D** 2700K - 5000K Dynamic White	**00** (Diffused Indirect)
L 3000 mm - CRI 80 - 55 W DC - 60 W AC		
WH **83794** / BB **83818**	**D** 2700K - 5000K Dynamic White	**00** (Diffused Indirect)

Modus_MP Slave Dynamic-White | topLED | 220-240 V AC






C.V. IP40 DW DALI


	Cct	Opt
L 1200 mm - CRI 80 - 20 W DC - 23 W AC		
WH **83795** / BB **83819**	**D** 2700K - 5000K Dynamic White	**00** (Diffused Indirect)
L 1500 mm - CRI 80 - 27 W DC - 30 W AC		
WH **83796** / BB **83820**	**D** 2700K - 5000K Dynamic White	**00** (Diffused Indirect)
L 2400 mm - CRI 80 - 43 W DC - 48 W AC		
WH **83797** / BB **83821**	**D** 2700K - 5000K Dynamic White	**00** (Diffused Indirect)
L 3000 mm - CRI 80 - 55 W DC - 60 W AC		
WH **83798** / BB **83822**	**D** 2700K - 5000K Dynamic White	**00** (Diffused Indirect)

Maximum power connectable on a 10-metre line (accessories).
Master 1200 - 1500 mm, 90 W max | **Master** 2400 - 3000 mm, 140 W max



Modus_M | L-shaped fitting







IP40

WH **83733**
BB **83757**
WB **83221**
BH **83222**

Modus_M | T-shaped fitting







IP40 NEW

WH **C-K400011**
BB **C-K400010**
WB **C-K400022**
BH **C-K400023**

Modus_M | Cross fitting






IP40 NEW

WH **C-K400014**
BB **C-K400013**
WB **C-K400024**
BH **C-K400025**

Modus_M | Caps kit






2 x
WH **83108**
BB **83109**

Finishes
WH White WB White/Black
BB Black BH Black/White

Cct
D 2700 - 5000

Modus Microprismatic | topLED | 24 V DC






DALI

	Cct	lm S - lm D	Opt
L 900 mm - CRI 90 - 19 W DC			
WH **83722**	**W**	2362 - 1522	**96** (Batwing UGR<19)
BB **83746**	**N**	2484 - 1600	
L 1200 mm - CRI 90 - 24 W DC			
WH **83723**	**W**	3150 - 2029	**96** (Batwing UGR<19)
BB **83747**	**N**	3311 - 2133	
L 1500 mm - CRI 90 - 30 W DC			
WH **83724**	**W**	3937 - 2535	**96** (Batwing UGR<19)
BB **83748**	**N**	4139 - 2665	

Modus Cct W = 3500 K

Modus Optus_EX | powerLED | 24 V DC | 5 W DC






DALI

	Cct	lm S - lm D	Opt
CRI 90			
WH **83732**	**W**	522 - 378	**20** (22°)
BB **83756**	**N**	561 - 406	**35** (32°)

Modus Cct W = 3500 K

Modus Projectors | powerLED | 24 V DC | 7 W DC






DALI

	Cct	lm S - lm D	Opt
CRI 90			
WH **83731**	**W**	569 - 478	**10** (20°)
BB **83755**	**N**	614 - 515	**30** (32°)
			45 (47°)

Modus Cct W = 3500 K

Modus Projectors | arrayLED | 24 V DC | 13 W DC






DALI

	Cct	lm S - lm D	Opt
CRI 90			
WH **83730**	**W**	1597 - 967	**15** (17°)
BB **83754**	**N**	1660 - 994	**30** (25°)
			60 (42°)

Modus Cct W = 3500 K

Modus Cell_WW | powerLED | 24 V DC | 12 W DC






DALI

	Cct	lm S - lm D	Opt
CRI 90			
WH **83721**	**W**	1281 - 586	**07** (Asym. Ww)
BB **83745**	**N**	1383 - 633	

Modus Cct W = 3500 K

Modus Cell | powerLED | 24 V DC | 12 W DC





DALI


	Cct	lm S - lm D	Opt
CRI 90			
WH **83720**	**W**	1281 - 1085	**60** (56° UGR<19)
BB **83744**	**N**	1383 - 1172	

Modus Cct W = 3500 K

Finishes **Cct**

WH White **W** 3500
BB Black **N** 4000


Modus | Air Quality Sensor | 24 V DC



III C.V. IP40 NEW

WH **C-E900004**
BB **C-E900003**


Modus | Light PIR Sensor | 24 V DC



III C.V. IP40 NEW

WH **C-E900002**
BB **C-E900001**


Modus_M | Lower buffer



L 150 mm	L 300 mm	L 600 mm
WH **83725**	WH **83729**	WH **83726**
BB **83749**	BB **83753**	BB **83750**
L 900 mm	**L 1200 mm**	
WH **83727**	WH **83728**	
BB **83751**	BB **83752**	



The air quality sensor monitors the VOC index via the Twil web app. VOCs (volatile organic compounds) are chemical compounds made up of molecules of different nature, all characterised by high volatility, i.e. their ability to evaporate easily into the air at room temperature. THROUGH DALI management, it is possible to interact with home automation systems such as KNX to control the ventilation of rooms (e.g. automatic opening of windows). The module is equipped with a signal LED that changes colour to define the level of air quality.



Using the Light-PIR sensor module in the Modus system in an office setting helps to create a comfortable and productive working environment while reducing energy consumption and costs. You can manage the light automatically, programming it to turn on, for example, when a person enters a room, or to turn off, when the person leaves the workstation.
Maximum installation height 5 metres.
Bluetooth Mesh technology
Presence detector (with or without daylight).
Brightness detector.

Finishes

WH White
BB Black

OMB SALERI
Brescia (Italy)

Project: Studio Paterlini Brescia
Engineer Marco Paterlini

Photography:
Margherita Nardi






The large waiting room welcomes users in an enveloping and natural, albeit artificial, light. The soft colours, together with the lighting of the wide waiting and distribution corridors, contribute to emotional well-being, using light as an essential tool for humanising the environments. The theme of the humanisation of medical environments is a key topic of design in the medical field, as the paradigm through which the vision of white and grey environments was a guarantee of cleanliness and care has changed.



aDoc MEDICAL CLINIC
Gualdo Tadino - Perugia (Italy)

Project: A25

Photography:
Mattia Micheli



ROLLIP

Aluminium profile
Polycarbonate diffuser

A COMPLETE SYSTEM FOR ARCHITECTURE

Rollip allows you to express maximum design creativity with even more efficient lighting performance thanks to a completely updated system. The structure has been redesigned using less aluminium in favour of greater sustainability, two embossed black and white finishes are available, obtained through powder coating. Rollip is available in three different widths and three installation options, recessed with frame or frameless, surface-mounted or suspended. The latter with the possibility of selecting single-emission and double emission modules.



Rollip_PRO
Recessed frame



Rollip35_MC
Recessed frame



Rolli60_MC
Recessed frame



Rollip100_MC
Recessed frame

-40%
COMPONENTS

+30%
EFFICIENCY
COMPARED TO THE PREVIOUS VERSION



Rollip35_MF
Recessed frameless



Rollip60_MF
Recessed frameless



Rollip100_MF
Recessed frameless



Rollip35_MS
Surface



Rollip60_MS
Surface



Rollip35_MP
Suspension
mono-emission
double-emission




Rollip60_MP
Suspension
mono-emission
double-emission



The easy installation of the ROLL DIFFUSER allows to obtain continuous lines measuring up to 20 metres in a single, simple assembly operation within drastically reduced times.

The **Rollip_MP** suspended system is equipped with a system for adjusting the support cable and the power cable, up to 8 cm. This technical solution guarantees maximum versatility in installation, allowing you to overcome obstacles with extreme ease.

In the double emission version of **Rollip_MP**, the distribution of indirect light is controlled by a special optic with an opening angle of 150° that guarantees a clean and high-performance illuminance. In addition, direct emission and indirect emission can be managed independently.



Rollip PRO
The PRO version is the maximum engineering evolution of the Rollip range of products, by applying the OptiLight™ technology, with the typical pattern of laser micro-engravings to redistribute the light projecting from the PMMA diffuser, and the ensuing full control of the UGR for applications in work environments with video terminals. The minimal size, just 13 millimetres, allows to recess the product on the dropped ceiling without exceeding the plasterboard, given that the thickness of Rollip PRO is smaller: a major advantage lies in the presence of possible uprights or hindrances in the dropped ceiling.

NGC Medical Headquarters
Como (Italy)


Project: Giuseppe
Tortato Architetti Firm

Photography:
Carola Merello



Rollip_PRO_C | complete | topLED | 24 V DC






	Cct	Im S - Im D	
L 1199 mm - CRI 90 - 24 W DC			
WH **77466**	**M**	2839 - 1472	67x1188
	W	2940 - 1561	
	N	3146 - 1635	
L 1519 mm - CRI 90 - 30 W DC			
WH **77468**	**M**	3604 - 1869	67x1508
	W	3733 - 1983	
	N	4000 - 2076	

Electronics: **AL** (pag 323)

Rollip_PRO | topLED | 24 V DC






	Cct	Im S - Im D	
L 595 mm - CRI 90 - 12 W DC			
WH **65438**	**M**	1419 - 736	67x595
	W	1470 - 780	
	N	1573 - 817	
L 1185 mm - CRI 90 - 24 W DC			
WH **65439**	**M**	2838 - 1471	67x1185
	W	2940 - 1561	
	N	3146 - 1634	
L 1505 mm - CRI 90 - 30 W DC			
WH **65440**	**M**	3602 - 1868	67x1505
	W	3733 - 1982	
	N	4000 - 2076	

Rollip_PRO | Corner | topLED | 24 V DC





	Cct	Im S - Im D	
Corner L 512x512 mm - CRI 90 - 20 W DC			
WH **65441**	**M**	2402 - 1132	67 512x512
	W	2531 - 1202	
	N	2705 - 1258	

Electronics: **AL** (pag 323)

Delivered lumens measured with opal diffuser.


Even more performance and a Total White visual effect for this new Rollip_Pro diffuser. Two versions, opal or with full UGR control, which guarantees up to 30% more luminous flux, for application in working environments with video terminals.

Rollip_PRO | Roller diffuser




UGR<19 anti-glaring
OP **83356** 5 m
OP **83357** 10 m
Opaline
OP **83407** 5 m
OP **83408** 10 m
OP **83409** 20 m

Rollip_PRO | Caps kit



WH **62460** 2 x




Finishes
WH White
OP Opaline

Cct
M 2700
W 3000
N 4000


Rollip35_MC | V2 | topLED | 48 V DC





Rollip35_MC | V2 | Corner | topLED | 48 V DC





	Fin	Cct	lm S - lm D	Opt	
L 1000 mm - CRI 90 - 13 W DC					
C00187	**WH**	**M**	1670 - 1298	**ZZ**	41x1000
		W	1759 - 1367		
		T	1789 - 1390		
		N	1880 - 1461		
L 1500 mm - CRI 90 - 19,5 W DC					
C00188	**WH**	**M**	2505 - 1946	**ZZ**	41x1500
		W	2639 - 2050		
		T	2684 - 2085		
		N	2820 - 2191		
L 2000 mm - CRI 90 - 26 W DC					
C00189	**WH**	**M**	3340 - 2595	**ZZ**	41x2000
		W	3518 - 2733		
		T	3578 - 2780		
		N	3760 - 2922		
L 3000 mm - CRI 90 - 39 W DC					
C00190	**WH**	**M**	5010 - 3893	**ZZ**	41x3000
		W	5277 - 4100		
		T	5367 - 4169		
		N	5640 - 4382		

Joining kit included


Corner L 530x530 mm - CRI 90 - 13 W DC					
C00191	**WH**	**M**	1670 - 1298	**ZZ**	41 530x530
		W	1759 - 1367		
		T	1789 - 1390		
		N	1880 - 1461		

The composition with the angular module does not guarantee the IP54 index of protection.

Electronics: **EP** (pag 323)

Delivered lumens measured with opal diffuser.

Rollip35_MC | Roller diffuser



Asymmetric

OP **C-U200006** 5 m

OP **C-U200007** 10 m


Opaline

OP **C-U200002** 5 m

OP **C-U200003** 10 m

OP **C-U200004** 20 m


Rollip35_MC | Caps kit



WH **C-V400004** 2 x

To use the plugs, the length of the installation hole must be increased by 8 mm.

Rollip35_MC | Template



WH **C-V200001** 2 x

Finishes

WH White

OP Opaline


Cct

M 2700 **T** 3500

W 3000 **N** 4000


Rollip60_MC | V2 | topLED | 48 V DC





Rollip60_MC | V2 | Corner | topLED | 48 V DC





	Fin	Cct	lm S - lm D	Opt	
L 1000 mm - CRI 90 - 13 W DC					
C00247	**WH**	**M**	1670 - 1491	**ZZ**	64x1000
		W	1759 - 1570		
		T	1789 - 1596		
		N	1880 - 1678		
L 1500 mm - CRI 90 - 19,5 W DC					
C00248	**WH**	**M**	2505 - 2236	**ZZ**	64x1500
		W	2639 - 2355		
		T	2684 - 2395		
		N	2820 - 2517		
L 2000 mm - CRI 90 - 26 W DC					
C00249	**WH**	**M**	3340 - 2981	**ZZ**	64x2000
		W	3518 - 3140		
		T	3578 - 3193		
		N	3760 - 3356		
L 3000 mm - CRI 90 - 39 W DC					
C00250	**WH**	**M**	5010 - 4471	**ZZ**	64x3000
		W	5277 - 4710		
		T	5367 - 4790		
		N	5640 - 5034		

Joining kit included


Corner L 542x542 mm - CRI 90 - 13 W DC					
C00251	**WH**	**M**	1670 - 1491	**ZZ**	64 542x542
		W	1759 - 1570		
		T	1789 - 1596		
		N	1880 - 1678		

The composition with the angular module does not guarantee the IP54 index of protection.

Electronics: **EP** (pag 323)

Delivered lumens measured with opal diffuser.

Rollip60_MC | Roller diffuser




Asymmetric
- OP **C-U200012** 5 m
- OP **C-U200013** 10 m

Opaline
- OP **C-U200008** 5 m
- OP **C-U200009** 10 m
- OP **C-U200010** 20 m

UGR<19 anti-glaring
- OP **C-U200014** 5 m
- OP **C-U200015** 10 m


Rollip60_MC | Caps kit



WH **C-V400008** 2 x

To use the plugs, the length of the installation hole must be increased by 8 mm.

Rollip60_MC | Template




WH **C-V200003** 2 x

Finishes
- WH White
- OP Opaline

Cct
M 2700 **T** 3500
W 3000 **N** 4000

Rollip100_MC | V2 | topLED | 48 V DC





	Fin	Cct	lm S - lm D	Opt	
L 1000 mm - CRI 90 - 20 W DC					
C00336	**WH**	**M**	2780 - 2119	**ZZ**	102x1000
		W	2912 - 2219		
		T	3010 - 2292		
		N	3094 - 2359		
L 1500 mm - CRI 90 - 30 W DC					
C00337	**WH**	**M**	4170 - 3179	**ZZ**	102x1500
		W	4368 - 3329		
		T	4515 - 3438		
		N	4641 - 3539		
L 2000 mm - CRI 90 - 40 W DC					
C00338	**WH**	**M**	5560 - 4238	**ZZ**	102x2000
		W	5824 - 4438		
		T	6020 - 4584		
		N	6188 - 4718		
L 3000 mm - CRI 90 - 60 W DC					
C00339	**WH**	**M**	8340 - 6357	**ZZ**	102x3000
		W	8736 - 6657		
		T	9030 - 6867		
		N	9282 - 7077		

Joining kit included

	Fin	Cct	lm S - lm D	Opt	
Corner L 580x580 mm - CRI 90 - 21,5 W DC					
C00340	**WH**	**M**	2955 - 2246	**ZZ**	102 580x580
		W	3096 - 2352		
		T	3200 - 2430		
		N	3289 - 2500		


The composition with the angular module does not guarantee the IP54 index of protection.

Electronics: **EP** (pag 323)

Delivered lumens measured with opal diffuser.

Rollip100_MC | V2 | Corner | topLED | 48 V DC





Rollip100_MC | Roller diffuser



Opaline

OP **C-U200016** 5 m
OP **C-U200017** 10 m
OP **C-U200018** 20 m


UGR<19 anti-glaring

OP **C-U200022** 5 m
OP **C-U200023** 10 m

Asymmetric

OP **C-U200020** 5 m
OP **C-U200021** 10 m


Rollip100_MC | Caps kit



WH **C-V400012** 2 x

To use the plugs, the length of the installation hole must be increased by 8 mm.

Rollip100_MC | Template



WH **C-V200004** 2 x

Finishes

WH White
OP Opaline

Cct

M 2700 **T** 3500
W 3000 **N** 4000


THE WESTIN LONDON CITY
London (United Kingdom)

Project: Dexter Moren Associates

Lighting Designer:
Nulty Lighting


Photography:
Matteo Barro






ROLLIP MF: SIMPLE, FAST, PERFECT.


The mounting system for MF frameless recessed profiles makes installation a precise and easy operation. Rollip_MF is designed to simplify every step of the installation, ensuring a professional and long-lasting result.






Rollip35_MF | V2 | topLED | 48 V DC





Rollip35_MF | V2 | Corner | topLED | 48 V DC





	Fin	Cct	lm S - lm D	Opt
L 1000 mm - CRI 90 - 13 W DC				
C00331	**WH**	**M**	1670 - 1298	**ZZ** With C-C600001: 45,5x1000 Without C-C600001: 38,5x1000
		W	1759 - 1367	
		T	1789 - 1390	
		N	1880 - 1461	
L 1500 mm - CRI 90 - 19,5 W DC				
C00332	**WH**	**M**	2505 - 1946	**ZZ** With C-C600001: 45,5x1500 Without C-C600001: 38,5x1500
		W	2639 - 2050	
		T	2684 - 2085	
		N	2820 - 2191	
L 2000 mm - CRI 90 - 26 W DC				
C00333	**WH**	**M**	3340 - 2595	**ZZ** With C-C600001: 45,5x2000 Without C-C600001: 38,5x2000
		W	3518 - 2733	
		T	3578 - 2780	
		N	3760 - 2922	
L 3000 mm - CRI 90 - 39 W DC				
C00334	**WH**	**M**	5010 - 3893	**ZZ** With C-C600001: 45,5x3000 Without C-C600001: 38,5x3000
		W	5277 - 4100	
		T	5367 - 4169	
		N	5640 - 4382	

Joining kit included


Corner L 530x530 mm - CRI 90 - 13 W DC				
C00335	**WH**	**M**	1670 - 1298	**ZZ** With C-C600001: 45,5 Without C-C600001: 38,5 530x530
		W	1759 - 1367	
		T	1789 - 1390	
		N	1880 - 1461	

The composition with the angular module does not guarantee the IP54 index of protection.

Electronics: **EP** (pag 323)

Delivered lumens measured with opal diffuser.

Rollip35_MF | Roller diffuser




Asymmetric

OP	**C-U200006**	5 m
OP	**C-U200007**	10 m

Opaline

OP	**C-U200002**	5 m
OP	**C-U200003**	10 m
OP	**C-U200004**	20 m


Rollip35_MF | Caps kit



WH **C-V400006** 2 x

To use the plugs, the length of the installation hole must be increased by 8 mm.


Rollip35_MF | Template



WH **C-V200006** 2 x

Jig for installation with corner guards

Rollip35_MF | Corner guards



WH **C-C600001** 2 x 2 m

Corner guards required for installation on plasterboard


Finishes


WH White
OP Opaline

Cct

M 2700 **T** 3500
W 3000 **N** 4000


Rollip60_MF | V2 | topLED | 48 V DC





Rollip60_MF | V2 | Corner | topLED | 48 V DC





	Fin	Cct	lm S - lm D	Opt
L 1000 mm - CRI 90 - 13 W DC				
C00341	**WH**	**M**	1670 - 1491	**ZZ**
		W	1759 - 1570	With C-C600001: 68,5x1000 Without C-C600001: 61x1000
		T	1789 - 1596	
		N	1880 - 1678	
L 1500 mm - CRI 90 - 19,5 W DC				
C00342	**WH**	**M**	2505 - 2236	**ZZ**
		W	2639 - 2355	With C-C600001: 68,5x1500 Without C-C600001: 61x1500
		T	2684 - 2395	
		N	2820 - 2517	
L 2000 mm - CRI 90 - 26 W DC				
C00343	**WH**	**M**	3340 - 2981	**ZZ**
		W	3518 - 3140	With C-C600001: 68,5x2000 Without C-C600001: 61x2000
		T	3578 - 3193	
		N	3760 - 3356	
L 3000 mm - CRI 90 - 39 W DC				
C00344	**WH**	**M**	5010 - 4471	**ZZ**
		W	5277 - 4710	With C-C600001: 68,5x3000 Without C-C600001: 61x3000
		T	5367 - 4790	
		N	5640 - 5034	

Joining kit included


Corner L 538x538 mm - CRI 90 - 13 W DC				
C00345	**WH**	**M**	1670 - 1491	**ZZ**
		W	1759 - 1570	With C-C600001: 68,5 Without C-C600001: 61
		T	1789 - 1596	
		N	1880 - 1678	538x538

The composition with the angular module does not guarantee the IP54 index of protection.

Electronics: **EP** (pag 323)

Delivered lumens measured with opal diffuser.

Rollip60_MF | Roller diffuser




Asymmetric
- OP **C-U200012** 5 m
- OP **C-U200013** 10 m

Opaline
- OP **C-U200008** 5 m
- OP **C-U200009** 10 m
- OP **C-U200010** 20 m

UGR<19 anti-glaring
- OP **C-U200014** 5 m
- OP **C-U200015** 10 m


Rollip60_MF | Caps kit



WH **C-V400010** 2 x

To use the plugs, the length of the installation hole must be increased by 8 mm.


Rollip60_MF | Template



WH **C-V200007** 2 x

Jig for installation with corner guards

Rollip60_MF | Corner guards



WH **C-C600001** 2 x 2 m

Corner guard required for installation on drywall

Finishes


WH White
OP Opaline

Cct

M 2700 **T** 3500
W 3000 **N** 4000


Rollip100_MF | V2 | topLED | 48 V DC





Rollip100_MF | V2 | Corner | topLED | 48 V DC





	Fin	Cct	lm S - lm D	Opt
L 1000 mm - CRI 90 - 20 W DC				
C00346	**WH**	**M**	2780 - 2119	**ZZ** With C-C600001: 107,5x1000 Without C-C600001: 100x1000
		W	2912 - 2219	
		T	3010 - 2292	
		N	3094 - 2359	
L 1500 mm - CRI 90 - 30 W DC				
C00347	**WH**	**M**	4170 - 3179	**ZZ** With C-C600001: 107,5x1500 Without C-C600001: 100x1500
		W	4368 - 3329	
		T	4515 - 3438	
		N	4641 - 3539	
L 2000 mm - CRI 90 - 40 W DC				
C00348	**WH**	**M**	5560 - 4238	**ZZ** With C-C600001: 107,5x2000 Without C-C600001: 100x2000
		W	5824 - 4438	
		T	6020 - 4584	
		N	6188 - 4718	
L 3000 mm - CRI 90 - 60 W DC				
C00349	**WH**	**M**	8340 - 6357	**ZZ** With C-C600001: 107,5x3000 Without C-C600001: 100x3000
		W	8736 - 6657	
		T	9030 - 6867	
		N	9282 - 7077	

Joining kit included

Corner L 576x576 mm - CRI 90 - 21,5 W DC				
C00350	**WH**	**M**	2955 - 2246	**ZZ** With C-C600001: 107,5 Without C-C600001: 100 576x576
		W	3096 - 2352	
		T	3200 - 2430	
		N	3289 - 2500	

The composition with the angular module does not guarantee the IP54 index of protection.

Electronics: **EP** (pag 323)

Delivered lumens measured with opal diffuser.

Rollip100_MF | Roller diffuser




Opaline
- **OP** **C-U200016** 5 m
- **OP** **C-U200017** 10 m
- **OP** **C-U200018** 20 m

UGR<19 anti-glaring
- **OP** **C-U200022** 5 m
- **OP** **C-U200023** 10 m

Asymmetric
- **OP** **C-U200020** 5 m
- **OP** **C-U200021** 10 m


Rollip100_MF | Caps kit



WH **C-V400014** 2 x

To use the plugs, the length of the installation hole must be increased by 8 mm.


Rollip100_MF | Template



WH **C-V200008** 2 x

Jig for installation with corner guards

Rollip100_MF | Corner guards



WH **C-C600001** 2 x 2 m

Corner guard required for installation on drywall

Finishes

WH White
OP Opaline

Cct

M 2700 **T** 3500
W 3000 **N** 4000

CANTINA BOTTENAGO
Polpenazze del Garda - Brescia (Italy)

Architectural Project & Interior Design:
Architect Massimiliano Cirani

Lighting Designer:
Viola Elettrotecnica


Photography:
Marco Reggi






Rollip35_MS | V2 | topLED | 220-240 V AC





Rollip35_MS | V2 | Corner | topLED | 220-240 V AC





Non-electrifiable module

EL * The driver contained in the device complies with IEC 61347-2-13 annex J, and can therefore be powered by centralized power supply systems.

IP40 IP54 NEW *

	Fin	Cct	lm S - lm D	Opt
L 1000 mm - CRI 90 - 13 W DC - 14,5 W AC				
C00794	**WH**	**M**	1984 - 1489	**ZZ**
DALI *	**BB**	**W**	2078 - 1559	
C00835		**N**	2228 - 1671	
L 1500 mm - CRI 90 - 19,5 W DC - 22 W AC				
C00795	**WH**	**M**	2976 - 2234	**ZZ**
DALI *	**BB**	**W**	3117 - 2339	
C00836		**N**	3342 - 2509	
L 2000 mm - CRI 90 - 26 W DC - 29 W AC				
C00796	**WH**	**M**	3968 - 2978	**ZZ**
DALI *	**BB**	**W**	4156 - 3118	
C00837		**N**	4456 - 3342	


Joining kit included

Corner L 528x528 mm - CRI 90 - 13 W DC - 14,5 W AC				
C00808	**WH**	**M**	1984 - 1489	**ZZ**
DALI *	**BB**	**W**	2078 - 1559	
C00838		**N**	2228 - 1671	

To be completed with accessory **C-F400007.**

Delivered lumens measured with opal diffuser.

Rollip35_MS | Roller diffuser



Asymmetric

OP **C-U200006** 5 m

OP **C-U200007** 10 m


Opaline

OP **C-U200002** 5 m

OP **C-U200003** 10 m

OP **C-U200004** 20 m


Rollip35_MS | Caps kit



WH **C-V400015** 2 x

BB **C-V400016** 2 x


Rollip35_MS | Fixing bracket



IS **C-F400007** 2 x


Rollip60_MS | V2 | topLED | 220-240 V AC





Rollip60_MS | V2 | Corner | topLED | 220-240 V AC





Non-electrifiable module

EL * The driver contained in the device complies with IEC 61347-2-13 annex J, and can therefore be powered by centralized power supply systems.

	Fin	Cct	lm S - lm D	Opt
L 1000 mm - CRI 90 - 13 W DC - 14,5 W AC				
C00803	**WH**	**M**	1984 - 1508	**ZZ**
DALI *	**BB**	**W**	2078 - 1579	
C00847		**N**	2228 - 1693	
L 1500 mm - CRI 90 - 19,5 W DC - 22 W AC				
C00804	**WH**	**M**	2976 - 2262	**ZZ**
DALI *	**BB**	**W**	3117 - 2368	
C00848		**N**	3342 - 2539	
L 2000 mm - CRI 90 - 26 W DC - 29 W AC				
C00805	**WH**	**M**	3968 - 3016	**ZZ**
DALI *	**BB**	**W**	4156 - 3158	
C00850		**N**	4456 - 3385	

Joining kit included

Corner L 540x540 mm - CRI 90 - 13 W DC - 14,5 W AC				
C00811	**WH**	**M**	1984 - 1508	**ZZ**
DALI *	**BB**	**W**	2078 - 1578	
C00853		**N**	2228 - 1692	

To be completed with accessory **C-F400007.**

Delivered lumens measured with opal diffuser.

Rollip60_MS | Roller diffuser




Asymmetric
- OP **C-U200012** 5 m
- OP **C-U200013** 10 m

Opaline
- OP **C-U200008** 5 m
- OP **C-U200009** 10 m
- OP **C-U200010** 20 m

UGR<19 anti-glaring
- OP **C-U200014** 5 m
- OP **C-U200015** 10 m

Rollip60_MS | Caps kit



- WH **C-V400017** 2 x
- BB **C-V400018** 2 x

Rollip60_MS | Fixing bracket



- IS **C-F400007** 2 x

Finishes

WH White OP Opaline
BB Black IS Steel

Cct

M 2700 **N** 4000
W 3000




COMFORT LIGHT FOR BETTER LIFE




Rollip35_MP | V2 | mono-emission | topLED | 220-240 V AC





Rollip35_MP | V2 | Corner | mono-emission | topLED | 220-240 V AC






EL * The driver contained in the device complies with IEC 61347-2-13 annex J, and can therefore be powered by centralized power supply systems.

** First module always to be integrated with the power supply kit. All the linear modules are to be completed with at least one suspension kit, to be installed at one of the ends.


Rollip35_MP | V2 | double-emission | topLED | 220-240 V AC





Rollip35_MP | V2 | Corner | double-emission | topLED | 220-240 V AC





EL * The driver contained in the device complies with IEC 61347-2-13 annex J, and can therefore be powered by centralized power supply systems.

** First module always to be integrated with the power supply kit. All the linear modules are to be completed with at least one suspension kit, to be installed at one of the ends.

IP20 NEW *

	Fin		Cct	lm S - lm D	Opt
L 1000 mm - CRI 90 - 13 W DC - 14,5 W AC **					
C00788	**WH**		**M**	1984 - 1489	**ZZ**
DALI *	**BB**		**W**	2078 - 1559	
C00827			**N**	2228 - 1671	
L 1500 mm - CRI 90 - 19,5 W DC - 22 W AC **					
C00789	**WH**		**M**	2976 - 2234	**ZZ**
DALI *	**BB**		**W**	3117 - 2339	
C00828			**N**	3342 - 2507	
L 2000 mm - CRI 90 - 26 W DC - 29 W AC **					
C00790	**WH**		**M**	3968 - 2978	**ZZ**
DALI *	**BB**		**W**	4156 - 3118	
C00829			**N**	4456 - 3342	

Joining kit included

L 528x528 mm - CRI 90 - 13 W DC - 14,5 W AC					
C00806	**WH**		**M**	1984 - 1489	**ZZ**
DALI *	**BB**		**W**	2078 - 1559	
C00830			**N**	2228 - 1671	

Delivered lumens measured with opal diffuser.

IP20 NEW *


	Fin		Cct	lm S - lm D	Opt
L 1000 mm - CRI 90 - 23 W DC - 25 W AC **					
C00791	**WH**		**M**	3471 - 2784	**DZ**
DALI *	**BB**		**W**	3635 - 2915	
C00831			**N**	3883 - 3125	
L 1500 mm - CRI 90 - 34,5 W DC - 38 W AC **					
C00792	**WH**		**M**	5207 - 4176	**DZ**
DALI *	**BB**		**W**	5453 - 4372	
C00832			**N**	5824 - 4687	
L 2000 mm - CRI 90 - 46 W DC - 50 W AC **					
C00793	**WH**		**M**	6942 - 5567	**DZ**
DALI *	**BB**		**W**	7270 - 5830	
C00833			**N**	7766 - 6250	

Joining kit included

Corner L 528x528 mm - CRI 90 - 23 W DC - 25 W AC					
C00807	**WH**		**M**	3471 - 2796	**DZ**
DALI *	**BB**		**W**	3635 - 2914	
C00834			**N**	3883 - 2954	

Delivered lumens measured with opal diffuser.

Rollip35_MP | Roller diffuser



Asymmetric

OP **C-U200006** 5 m

OP **C-U200007** 10 m

Opaline

OP **C-U200002** 5 m

OP **C-U200003** 10 m


OP **C-U200004** 20 m

UGR<19 anti-glaring

OP **C-U200026** 5 m Only for double-emission


OP **C-U200027** 10 m Only for double-emission

Rollip35_MP | Suspension kit



WH **C-F100003** It includes a single cable. It is necessary to purchase 2 suspension kits for the starting module and 1 suspension kit for each individual module of the system. It is already included in the corner element.


Rollip35_MP | Caps kit



WH **C-V400015** 2 x

BB **C-V400016** 2 x

Rollip35_MP | Power supply kit



WH **64639** Single emission

BB **63300** Single emission

WH **64649** Double emission

BB **63302** Double emission


DALI 2 - DALI PUSH

WH **64660** Single / Double emission


BB **63301** Single / Double emission


Rollip60_MP | V2 | mono-emission | topLED | 220-240 V AC





Rollip60_MP | V2 | Corner | mono-emission | topLED | 220-240 V AC






Non-electrifiable module

EL * The driver contained in the device complies with IEC 61347-2-13 annex J, and can therefore be powered by centralized power supply systems.


** First module always to be integrated with the power supply kit. All the linear modules are to be completed with at least one suspension kit, to be installed at one of the ends.


Rollip60_MP | V2 | double-emission | topLED | 220-240 V AC





Rollip60_MP | V2 | Corner | double-emission | topLED | 220-240 V AC





Non-electrifiable module

EL * The driver contained in the device complies with IEC 61347-2-13 annex J, and can therefore be powered by centralized power supply systems.

** First module always to be integrated with the power supply kit. All the linear modules are to be completed with at least one suspension kit, to be installed at one of the ends.

IP20 NEW *

	Fin	Cct	lm S - lm D	Opt
L 1000 mm - CRI 90 - 13 W DC - 14,5 W AC **				
C00797	**WH**	**M**	1984 - 1508	**ZZ**
DALI *	**BB**	**W**	2078 - 1579	
C00839		**N**	2228 - 1693	
L 1500 mm - CRI 90 - 19,5 W DC - 22 W AC **				
C00798	**WH**	**M**	2976 - 2262	**ZZ**
DALI *	**BB**	**W**	3117 - 2368	
C00840		**N**	3342 - 2539	
L 2000 mm - CRI 90 - 26 W DC - 29 W AC **				
C00799	**WH**	**M**	3968 - 3016	**ZZ**
DALI *	**BB**	**W**	4156 - 3158	
C00841		**N**	4456 - 3385	
Joining kit included				
L 540x540 mm - CRI 90 - 13 W DC - 14,5 W AC				
C00809	**WH**	**M**	1984 - 1508	**ZZ**
DALI *	**BB**	**W**	2078 - 1578	
C00842		**N**	2228 - 1692	


Delivered lumens measured with opal diffuser.

IP20 NEW *

	Fin	Cct	lm S - lm D	Opt
L 1000 mm - CRI 90 - 23 W DC - 25 W AC **				
C00800	**WH**	**M**	3471 - 2869	**DZ**
DALI *	**BB**	**W**	3635 - 3004	
C00843		**N**	3883 - 3220	
L 1500 mm - CRI 90 - 34,5 W DC - 38 W AC **				
C00801	**WH**	**M**	5207 - 4303	**DZ**
DALI *	**BB**	**W**	5453 - 4506	
C00844		**N**	5824 - 4830	
L 2000 mm - CRI 90 - 46 W DC - 50 W AC **				
C00802	**WH**	**M**	6942 - 5737	**DZ**
DALI *	**BB**	**W**	7270 - 6008	
C00845		**N**	7766 - 6440	
Joining kit included				
Corner L 528x528 mm - CRI 90 - 23 W DC - 25 W AC				
C00810	**WH**	**M**	3471 - 2868	**DZ**
DALI *	**BB**	**W**	3635 - 3004	
C00846		**N**	3883 - 3220	

Delivered lumens measured with opal diffuser.

Rollip60_MP | Roller diffuser




Asymmetric
- OP **C-U200012** 5 m
- OP **C-U200013** 10 m

Opaline
- OP **C-U200008** 5 m
- OP **C-U200009** 10 m
- OP **C-U200010** 20 m


UGR<19 anti-glaring
- OP **C-U200014** 5 m
- OP **C-U200015** 10 m

Rollip60_MP | Suspension kit




WH **C-F100003** It includes a single cable. It is necessary to purchase 2 suspension kits for the starting module and 1 suspension kit for each individual module of the system. It is already included in the corner element.

Rollip60_MP | Caps kit



- WH **C-V400017** 2 x
- BB **C-V400018** 2 x

Rollip60_MP | Power supply kit



- WH **64639** Single emission
- BB **63300** Single emission
- WH **64649** Double emission
- BB **63302** Double emission

DALI 2 - DALI PUSH
- WH **64660** Single / Double emission
- BB **63301** Single / Double emission

Finishes


WH White OP Opaline
BB Black

Cct

M 2700 **N** 4000
W 3000







IRI headquarters
Milan (Italy)

Lighting Designer:
Garibaldi Architects

Photography:
Giacomo Albo

Electronics

AL

99374	99331	99332	83333	C-E400002
ON/OFF	ON/OFF	0/1-10V	DALI/PUSH	DALI/PUSH
75W	150W	150W	150W	240W
210 x 49 x h 25	158 x 60 x h 35	158 x 60 x h 35	188 x 68 x h 34	188 x 68 x h 34
56	70	70	77	77

EP

C-E300009	C-E300010	99784	99785	C-E400003
ON/OFF	ON/OFF	ON/OFF	ON/OFF	DALI/PUSH
75W CV 48V	150W CV 48V	150W CV 48V	240W CV 48V	150W CV 48V
280 x 41 x h 29	280 x 41 x h 29	219 x 63 x h 35	244 x 71 x h 38	188 x 68 x h 34
49	49	80	81	77


TRAIL

Steel chassis
Aluminium body



High efficiency versatile system
Trail offers homogeneous and contrast-free lighting, a long-lasting and quality light capable of adapting to any environment of use: as a matter of fact, the modularity of the system allows to create customised configurations. The great energy efficiency and low maintenance allow to reduce the operating costs as compared to conventional fluorescence systems.







Quick installation
Continuous Trail lines are easy and quick to install: the new lock and quick release system of the guards allows the technician to operate totally freely, without needing any tools. Upon mounting the bearing structure, the quick-coupling system allows to position the single lighting bodies at will to obtain the most appropriate lighting and follow the arrangement of the elements in the environment.






Trunking system | Trail_chassis | Power module







Trunking system | Trail_chassis | UPS backbone





Trunking system | Trail_chassis | Auxiliary power supply





IP20

WH	**90911**	L 1135 mm	ON/OFF	3 pin
WH	**90915**	L 2270 mm	ON/OFF	3 pin
WH	**90913**	L 1135 mm	ON/OFF / DALI	7 pin
BB	**83651**	L 1135 mm	ON/OFF / DALI	7 pin
WH	**90917**	L 2270 mm	ON/OFF / DALI	7 pin
BB	**83652**	L 2270 mm	ON/OFF / DALI	7 pin

IP20

WH	**90903**	L 1135 mm	ON/OFF	3 pin
WH	**90907**	L 2270 mm	ON/OFF	3 pin
WH	**90905**	L 1135 mm	ON/OFF / DALI	7 pin
BB	**83653**	L 1135 mm	ON/OFF / DALI	7 pin
WH	**90909**	L 2270 mm	ON/OFF / DALI	7 pin
BB	**83654**	L 2270 mm	ON/OFF / DALI	7 pin

IP20

WH	**90905E**	L 1135 mm	ON/OFF / DALI	7 pin
BB	**83655**	L 1135 mm	ON/OFF / DALI	7 pin

White





Black

Finishes

WH White
BB Black

Trunking system | topLED | 220-240 V AC | 34 W DC - 35 W AC







IP20

	Cct	lm S - lm D	Opt
3 pin - CRI 80			
WH **90919**	**N**	4557 - 4518	**60** (70°x94°)
7 pin - CRI 80			**00** (Diffused)
WH **90921**			**07** (Asym. Ww)
7 pin - DALI - CRI 80			**69** (Double Asym.)
WH **90923**			

Trunking system | topLED | 220-240 V AC | 46 W DC - 47 W AC







IP20

	Cct	lm S - lm D	Opt
3 pin - CRI 80			
WH **90925**	**N**	6186 - 5768	**60** (70°x94°)
7 pin - CRI 80			**00** (Diffused)
WH **90927**			**07** (Asym. Ww)
7 pin - DALI - CRI 80			**69** (Double Asym.)
WH **90929**			

Trunking system | topLED | 220-240 V AC | 58 W DC - 60 W AC






IP20

	Cct	lm S - lm D	Opt
3 pin - CRI 80			
WH **90931**	**N**	7522 - 6958	**60** (70°x94°)
7 pin - CRI 80			**00** (Diffused)
WH **90933**			**07** (Asym. Ww)
7 pin - DALI - CRI 80			**69** (Double Asym.)
WH **90935**			
BB **83656**			

Trunking system | Three-phase adaptor







IP20

WH **90952**
BB **83067**

Module for track projectors.
Maximum load 3kg.
Sustained maximum power 60 W.

Trunking system | Cover





WH **90950**
BB **83069**


Blind cover module.

Finishes
WH White
BB Black

Cct
N 4000

Trunking system | Suspension kit





CH **90944** L 1500 mm
CH **90943** L 3000 mm

Steel cable adjustable at the base, required for the suspension installation and available in two versions, 1.5 m and 3 m versions.
Fixing interline 1.5 m

Trunking system | Ceiling-mounted fixing kit






AL **90945**

1x Steel bracket required for ceiling installation. Providing at least 1 bracket every 1.5 m of Trail_chassis module installed.

Trunking system | Sealing cap






WH **90946**
BB **83068**


Line neutral sealing cap.

Extensive range of products
Trail is an extremely versatile system, with various available solutions. Three powers, that can be combined with optics of choice among the available four: diffused emission; E. W. Flood for high heights and applications not strictly bound to the supermarket sector; single or double Asymmetric emission, for light directed on one or two categories of displayed products, conceived for visually enhancing the quality of the goods.


Asymmetric **(07)**




D. Asymmetric **(69)**



Diffused **(00)**



E. W. Flood **(60)**



Finishes

WH White CH Chrome
BB Black AL Aluminium


ARCHICOVE

Aluminium body
Polycarbonate diffuser



Archicove | topLED | 24 V DC






	Cct	lm S - lm D	Opt	
L 342 mm - 9 W DC				
BB **94110**	**M**	979 - 700	**30**	(34°x90°)
	W	1044 - 730	**60**	(60°x112°)
	N	1092 - 761	**00**	(Diffused)
			07	(Asym. Ww)
L 1022 mm - 27 W DC				
BB **94115**	**M**	2925 - 2098	**30**	(34°x90°)
	W	3132 - 2190	**60**	(60°x112°)
	N	3276 - 2283	**00**	(Diffused)
			07	(Asym. Ww)

Electronics: **AL** (pag 332) | Cables and accessories (pag 332)


Archicove On/Off | topLED | 220-240 V AC






	Cct	lm S - lm D	Opt	
L 342 mm - 9 W DC - 10 W AC				
BB **92023**	**M**	979 - 700	**30**	(34°x90°)
	W	1044 - 730	**60**	(65°x112°)
	N	1092 - 761	**00**	(Diffused)
			07	(Asym. Ww)
L 1022 mm - 27 W DC - 30 W AC				
BB **92025**	**M**	2925 - 2098	**30**	(34°x90°)
	W	3132 - 2190	**60**	(65°x112°)
	N	3276 - 2283	**00**	(Diffused)
			07	(Asym. Ww)

The extensive variety of optics offers a wide choice of solutions. Above all, it allows to redefine the cove lighting concept: not only softly diffused indirect light, but also a tool to be used to enhance the architecture with more or less narrow dimensions.






Finishes

BB Black

Cct

M 2700 **N** 4000
W 3000

MAXIMUM VERSATILITY IN EVERY SPACE



Equipment equipped with male and female connectors, conceived for quick installation of a continuous row.


Precise light beam adjustment option by setting the rotation angle of the LED profile.

Electronics and accessories

AL

99374	99331	99332	83333	C-E400002
ON/OFF 75W 210 x 49 x h 25 56	ON/OFF 150W 158 x 60 x h 35 70	0/1-10V 150W 158 x 60 x h 35 70	DALI/PUSH 150W 188 x 68 x h 34 77	DALI/PUSH 240W 188 x 68 x h 34 77

Archicove | Steel support plate



IS **98699** L 342 mm
IS **98781** L 1022 mm

suitable for: Archicove / Archicove On/Off

Cables



BB **98879** Supply 24V

suitable for: Archicove




BB **98713** Supply 190~250V

suitable for: Archicove On/Off



BB **98878** Extension 24V

suitable for: Archicove



BB **98716** Extension 190~250V

suitable for: Archicove On/Off



LA ROTONDA Coffee Shop/Pizzeria
Magliano di Tenna - Fermo (Italy)

Project: Nazzareno Senzacqua

Lighting Designer:
Lighting (Matteo Ercoli + Simona Braconi)

Photography:
Giuseppe Saluzzi

FYLO+

Aluminium profile
Quartz powder resin and mixed construction site material

PATENTED

reddot award winner

Installation process Fylo+
Once installed, the profiles are concealed fully camouflaging with the surrounding architecture; the integrated light concept allows to customise the spaces with unique and precious light details.




Continuous line
The ROLL DIFFUSER was designed to create continuous light lines. Once coupled at the ends, the special polycarbonate reel unwinds following the profile along its entire length: this solution allows avoiding complex installation operations, replaced by a single, simple assembly operations with drastically reduced times. With the equipment lit, the diffuser screens and harmonises the light emitted by the source, reducing glaring drastically even when observed directly.



Quick installation
The profiles are snap-coupled on a dedicated bracket. Special plastic elements were introduced into the rear of the profiles, in the linear guides where they slide. Fixing is not bound to a pre-established point and so it can be installed as the installation technician wishes.


Fylo+ Surface



Bring the profile closer to the bracket


Push the product firmly against the bracke

Fylo+ Recessed



Fylo+ Recessed is provided for cardboard wall-mounted installation. For installation on existing walls is sufficient to remove the lateral flaps included in the profile.

Fylo+ Aluminium



More light, more efficiency
The choice of aluminium, lightened due to the specific design developed for the profiles section, allows to exploit the surface of the module as a diffuser enhancing the light performance available for the range of products.

Fylo_Direct



65180 - 65181

Fylo_Recessed



65006 - 65007 | 65003 - 65004 | 65027 - 65028 | 65009 - 65010 | 65012 - 65013


Fylo_Surface



65015 - 65016 | 65018 - 65019 | 65021 - 65022 | 65024 - 65025

Fylo+ Direct_1 | Reel diffuser | Recessed linear light






	L mm
WH **65180**	1000
WH **65181**	2000

Accessories: (pag 337) | Light source and power supply: (pag 337)

65184 Opaline diffuser L roller 5 m
65183 Opaline diffuser L roller 10 m
65182 Opaline diffuser L roller 20 m
62900 Outer casing for dropped ceiling

Fylo+ Recessed_1 | Recessed linear light body






	L mm
WH **65027**	1000
WH **65028**	2000

Accessories: (pag 337) | Light source and power supply: (pag 337)

65054 Opaline diffuser 1pcs L 1 m
65055 Opaline diffuser 5pcs L 1 m
62900 Outer casing for dropped ceiling

Fylo+ Recessed_2 | Recessed linear light body






	L mm
WH **65006**	1000
WH **65007**	2000

Accessories: (pag 337) | Light source and power supply: (pag 337)

65054 Opaline diffuser 1pcs L 1 m
65055 Opaline diffuser 5pcs L 1 m
62900 Outer casing for dropped ceiling

Fylo+ Recessed_3 | Recessed linear light body






	L mm
WH **65003**	1000
WH **65004**	2000

Accessories: (pag 337) | Light source and power supply: (pag 337)

65054 Opaline diffuser 1pcs L 1 m
65055 Opaline diffuser 5pcs L 1 m
62900 Outer casing for dropped ceiling

Fylo+ Recessed_4 | Recessed linear light body







	L mm
WH **65009**	1000
WH **65010**	2000

Accessories: (pag 337) | Light source and power supply: (pag 337)

65054 Opaline diffuser 1pcs L 1 m
65055 Opaline diffuser 5pcs L 1 m
62900 Outer casing for dropped ceiling

Fylo+ Recessed_5 | Recessed linear light body






	L mm
WH **65012**	1000
WH **65013**	2000

Accessories: (pag 337) | Light source and power supply: (pag 337)

65054 Opaline diffuser 1pcs L 1 m
65055 Opaline diffuser 5pcs L 1 m
62900 Outer casing for dropped ceiling

Fylo+ Surface_1 | Surface light body






	L mm
WH **65015**	1000
WH **65016**	2000

Accessories: (pag 337) | Light source and power supply: (pag 337)

65054 Opaline diffuser 1pcs L 1 m
65055 Opaline diffuser 5pcs L 1 m
62900 Outer casing for dropped ceiling
65008 Sealing caps 2 pcs

Fylo+ Surface_2 | Surface light body






	L mm
WH **65018**	1000
WH **65019**	2000

Accessories: (pag 337) | Light source and power supply: (pag 337)

65054 Opaline diffuser 1pcs L 1 m
65055 Opaline diffuser 5pcs L 1 m
62900 Outer casing for dropped ceiling
65011 Sealing caps 2 pcs

Fylo+ Surface_3 | Surface light body






	L mm
WH **65021**	1000
WH **65022**	2000

Accessories: (pag 337) | Light source and power supply: (pag 337)

65054 Opaline diffuser 1pcs L 1 m
65055 Opaline diffuser 5pcs L 1 m
62900 Outer casing for dropped ceiling
65014 Sealing caps 2 pcs

Fylo+ Surface_4 | Angular light body





	L mm
WH **65024**	1000
WH **65025**	2000

Accessories: (pag 337) | Light source and power supply: (pag 337)

65054 Opaline diffuser 1pcs L 1 m
65055 Opaline diffuser 5pcs L 1 m
62900 Outer casing for dropped ceiling
65097 Sealing caps 2 pcs

Accessories

Fylo+ | Light units - LED Strip



Ribbon Pro pag. 394
Ribbon Plus pag. 392-393
Ribbon pag. 390-391

Fylo+ | Opaline diffuser




OP **65184** 5 m
OP **65183** 10 m
OP **65182** 20 m
suitable for: Direct_1

Fylo+ | Outer casing



62900
suitable for: Direct_1 - Recessed_1 - Recessed_2
Recessed_3 - Recessed_4 - Recessed_5
Surface_1 - Surface_2 - Surface_3 - Surface_4

Fylo+ | Opaline diffuser



OP **65054** 1 m
OP **65055** 1 m x 5pz
suitable for: Recessed_1 - Recessed_2 - Recessed_3
Recessed_4 - Recessed_5 - Surface_1 - Surface_2
Surface_3 - Surface_4

Fylo+ | Sealing caps



WH **65008** 2 x
suitable for:
Surface_1

Fylo+ | Sealing caps




WH **65011** 2 x
suitable for:
Surface_2

Fylo+ | Sealing caps



WH **65014** 2 x
suitable for:
Surface_3


Fylo+ | Sealing caps



WH **65097** 2 x
suitable for:
Surface_4

Finishes

WH White
OP Opaline



STEP LIGHTS

SOFITEL BARCELONA SKIPPER
Barcelona (Spain)


Lighting Designer:
Fantastico Lighting Partners

Photography:
Jordi Anguera



Step lights range index

Vissa

Vissa_R

343

Vissa_Q

343

Petit

Petit_R

345

Petit_Q

345

Quara

Quara_R

347

Quara_Q

347

Envelope

Envelope_1

351

Envelope_2

351

Envelope_4

351

Step

Step

353

Ilamt

Ilamt

355

Ilamt66

355

Optiwall

Optiwall



357




VISSA

Brass body.

Vissa_R | powerLED







	Fin	Cct	lm S - lm D	Opt
CRI 90 - 220 mA - 0,7 W DC				
C00477	**CH**	**M**	88 - 44	**XF** (91°)
	NK	**W**	92 - 46	
		N	98 - 49	

Electronics: **A2** (pag 343) | Accessories: (pag 343)

Vissa_Q | powerLED





	Fin	Cct	lm S - lm D	Opt
CRI 90 - 220 mA - 0,7 W DC				
C00478	**CH**	**M**	88 - 44	**XF** (91°)
	NK	**W**	92 - 46	
		N	98 - 49	

Electronics: **A2** (pag 343) | Accessories: (pag 343)

Recessed casings & Accessories



PVC **84995** Recessed casing



PVC **84952** Washer for installation on moquette

Electronics

A2

99307	**83007**	**99198**	**99361**	**83322**
ON/OFF	ON/OFF	ON/OFF	0/1-10V	DALI/PUSH
1 - 2 art.	3 - 6 art.	6 - 12 art.	4 - 12 art.	4 - 12 art.
138 x 22 x h 21	138 x 22 x h 21	149 x 37 x h 30	150 x 43 x h 29	149 x 37 x h 31
29	29	48	56	48

Finishes

Chrome
Nickel

Cct


M 2700 **N** 4000
W 3000


PETIT

Brass or aluminium body.



Petit_R | powerLED






C.C. IP20

	Fin	Cct	lm S - lm D	Opt
CRI 90 - 350 mA - 1 W DC				
C00230	**WH**	**M**	124 - On req	**US** (6°)
	NK	**W**	132 - On req	
		N	147 - On req	

Electronics: **A1** (pag 345) | Accessories: (pag 345)

Petit_Q | powerLED






C.C. IP20

	Fin	Cct	lm S - lm D	Opt
CRI 90 - 350 mA - 1 W DC				
C00231	**WH**	**M**	124 - On req	**US** (6°)
	NK	**W**	132 - On req	
		N	147 - On req	

Electronics: **A1** (pag 345) | Accessories: (pag 345)

Petit_R | powerLED







C.C. IP44

	Fin	Cct	lm S - lm D	Opt
CRI 90 - 350 mA - 1 W DC				
C00232	**WH**	**M**	124 - On req	**US** (6°)
	NK	**W**	132 - On req	
		N	147 - On req	

Electronics: **A1** (pag 345) | Accessories: (pag 345)

Petit_Q | powerLED






C.C. IP44

	Fin	Cct	lm S - lm D	Opt
CRI 90 - 350 mA - 1 W DC				
C00233	**WH**	**M**	124 - On req	**US** (6°)
	NK	**W**	132 - On req	
		N	147 - On req	


Electronics: **A1** (pag 345) | Accessories: (pag 345)

Recessed casings




ABS 84335 Recessed casing

suitable for: Petit_R 1W 20 mm - Q 1W 20 mm



ABS 84915 Recessed casing

suitable for: Petit_R 1W 40 mm - Q 1W 40 mm



ABS 84336 Recessed casing

suitable for: Petit_R 1W 40 mm - Q 1W 40 mm

Electronics

A1

89144	89145	99375	C-E100010	C-E100011
ON/OFF	ON/OFF	ON/OFF	0/1-10V	DALI/PUSH
1 - 2 art.	3 - 6 art.	6 - 12 art.	3 - 4 art.	3 - 4 art.
138 x 22 x h 21	138 x 22 x h 21	138 x 22 x h 21	124 x 22 x h 22	124 x 22 x h 22
29	29	29	31	31

Finishes

White
Nickel

Cct


M 2700 **N** 4000
W 3000





QUARA


Aluminium or steel body.

Quara_R | powerLED












Quara_R | powerLED





Quara_Q | powerLED





IP65

	Fin	Cct	lm S - lm D	Opt
CRI 90 - 350 mA - 1 W DC				
C00236	**WH**	**M**	145 - 14	**WW** (Asym. Ww)
	GG	**W**	154 - 14	
	DB	**N**	165 - 16	
	IS			

Electronics: **A1** (pag 348) | Accessories: (pag 348)

IP65

	Fin	Cct	lm S - lm D	Opt
CRI 90 - 350 mA - 1 W DC				
C00237	**WH**	**M**	145 - 14	**WW** (Asym. Ww)
	GG	**W**	154 - 14	
	DB	**N**	165 - 16	
	IS			

Electronics: **A1** (pag 348) | Accessories: (pag 348)

IP44

	Fin	Cct	lm S - lm D	Opt
CRI 90 - 630 mA - 2 W DC				
C00238	**NK**	**M**	199 - 73	**WW** (Asym. Ww)
		W	212 - 78	
		N	237 - 87	

Electronics: **C1** (pag 348) | Accessories: (pag 348)

IP44 ID

	Fin	Cct	lm S - lm D	Opt
CRI 90 - 220-240 V AC - 2 W DC - 2,7 W AC				
C00240	**NK**	**M**	199 - 69	**WW** (Asym. Ww)
		W	212 - 73	
		N	237 - 82	

IP44

	Fin	Cct	lm S - lm D	Opt
CRI 90 - 630 mA - 2 W DC				
C00239	**NK**	**M**	199 - 73	**WW** (Asym. Ww)
		W	212 - 78	
		N	237 - 87	

Electronics: **C1** (pag 348) | Accessories: (pag 348)

IP44 ID

	Fin	Cct	lm S - lm D	Opt
CRI 90 - 220-240 V AC - 2 W DC - 2,7 W AC				
C00241	**NK**	**M**	199 - 69	**WW** (Asym. Ww)
		W	212 - 73	
		N	237 - 82	

Quara family

Quara_R _RO _RI



650-651

Quara_F



651

Quara_Q _QI



652

Finishes

White, Dark Brown, Nickel, Grey, Steel

Cct


M 2700 **N** 4000
W 3000

Recessed casing



ABS **98950** Recessed casing

suitable for: Quara_R 1W 25 mm - Q 1W 25 mm



ABS **84338** Recessed casing

suitable for: Quara_R 2W 65 mm - Q 2W 70 mm

Electronics

A1

89144	89145	99375	C-E100010	C-E100011
ON/OFF 1 - 2 art. 138 x 22 x h 21 29	ON/OFF 3 - 6 art. 138 x 22 x h 21 29	ON/OFF 6 - 12 art. 138 x 22 x h 21 29	0/1-10V 3 - 4 art. 124 x 22 x h 22 31	DALI/PUSH 3 - 4 art. 124 x 22 x h 22 31

C1

89147	99376	99105	99710	99713	+ driver 24V DC	
ON/OFF 1 - 2 art. 138 x 22 x h 21 29	ON/OFF 3 - 6 art. 138 x 22 x h 21 29	ON/OFF 6 - 12 art. 103 x 58 x h 27 64	24V DC converter 0/1-10V 1 - 6 art. 138 x 22 x h 20 29	24V DC converter DALI 1 - 6 art. 138 x 22 x h 20 29	99374 75W 56	99331 150W 70








ENVELOPE

Aluminium body.

Envelope_1 | powerLED







C.C. IP66

	Fin	Cct	lm S - lm D	Opt
CRI 90 - 350 mA - 1 W DC				
C00227	**WH**	**M**	124 - 25	**WW** (Asym. Ww)
	GG	**W**	132 - 26	
	DB	**N**	147 - 29	

Electronics: **A1** (pag 351) | Accessories: (pag 351)

Envelope_2 | powerLED






C.C. IP20

	Fin	Cct	lm S - lm D	Opt
CRI 90 - 350 mA - 1 W DC				
C00228	**WH**	**M**	124 - 20	**RB** (Radial Bi-direc.)
	GG	**W**	132 - 21	
	DB	**N**	147 - 23	

Electronics: **A1** (pag 351) | Accessories: (pag 351)

Envelope_4 | powerLED





C.C. IP20

	Fin	Cct	lm S - lm D	Opt
CRI 90 - 350 mA - 1 W DC				
C00229	**WH**	**M**	124 - 30	**RM** (Radial Multi direc.)
	GG	**W**	132 - 33	
	DB	**N**	147 - 36	

Electronics: **A1** (pag 351) | Accessories: (pag 351)

Envelope family

Envelope_R _RW



666

Envelope_Q _QW




668

Envelope_W



668

Recessed casings



ABS 84336 Recessed casing

suitable for: Envelope_1 - Envelope_2 - Envelope_4

Electronics

A1

89144	89145	99375	C-E100010	C-E100011
ON/OFF	ON/OFF	ON/OFF	0/1-10V	DALI/PUSH
1 - 2 art.	3 - 6 art.	6 - 12 art.	3 - 4 art.	3 - 4 art.
138 x 22 x h 21	138 x 22 x h 21	138 x 22 x h 21	124 x 22 x h 22	124 x 22 x h 22
29	29	29	31	31

Finishes

White
Grey
Dark Brown

Cct

M 2700
W 3000
N 4000


STEP

Aluminium body.



Step | powerLED





	Fin	Cct	lm S - lm D	Opt
CRI 90 - 350 mA - 1 W DC				
C00943	**WH**	**A**	111 - 47	**WW** (Asym. Ww)
	BB	**M**	124 - 52	
	CH	**W**	132 - 56	
	NK	**N**	147 - 63	
	BS			

Electronics: **A1** (pag 353) | Accessories: (pag 353)



Step family


Step66



670

Accessories

Step | Template



POL **99850**

Electronics

A1

89144	**89145**	**99375**	**C-E100010**	**C-E100011**
ON/OFF	ON/OFF	ON/OFF	0/1-10V	DALI/PUSH
1 - 2 art.	3 - 6 art.	6 - 12 art.	3 - 4 art.	3 - 4 art.
138 x 22 x h 21	138 x 22 x h 21	138 x 22 x h 21	124 x 22 x h 22	124 x 22 x h 22
29	29	29	31	31

Finishes

White, Black, Chrome, Nickel, Brass, POL Polystyrene

Cct

A 2200 **M** 2700 **W** 3000 **N** 4000




ILAMT

Brass body.

Ilamt | powerLED






C.C. IP44

	Fin	Cct	lm S - lm D	Opt
CRI 90 - 350 mA - 1 W DC				
C00244	**WH**	**M**	124 - 87	**SP** (19°)
	NK	**W**	132 - 92	**FL** (27°)
		N	147 - 103	**WF** (57°)

Electronics: **A1** (pag 355) | Accessories: (pag 355)

Ilamt | powerLED






C.C. IP44

	Fin	Cct	lm S - lm D	Opt
CRI 90 - 630 mA - 2 W DC				
C00245	**WH**	**M**	199 - 127	**FL** (24°)
	NK	**W**	212 - 135	**MW** (31°)
		N	237 - 150	**WF** (54°)

Electronics: **C1** (pag 355) | Accessories: (pag 355)

Ilamt66 | powerLED






C.C. IP66

	Fin	Cct	lm S - lm D	Opt
CRI 90 - 630 mA - 2 W DC				
C00246	**WH**	**M**	199 - 130	**NS** (13°)
	NK	**W**	212 - 138	**ML** (25°)
		N	237 - 153	**MW** (31°)
				WF (54°)


Electronics: **C1** (pag 355) | Accessories: (pag 355)

Recessed casings



ABS 84337 Recessed casing

suitable for: Ilamt 1W 22 mm



ABS 84349 Recessed casing

suitable for: Ilamt 2W 30 mm - Ilamt66 2W 30 mm

Electronics

A1

89144	89145	99375	C-E100010	C-E100011
ON/OFF	ON/OFF	ON/OFF	0/1-10V	DALI/PUSH
1 - 2 art.	3 - 6 art.	6 - 12 art.	3 - 4 art.	3 - 4 art.
138 x 22 x h 21	138 x 22 x h 21	138 x 22 x h 21	124 x 22 x h 22	124 x 22 x h 22
29	29	29	31	31

C1

89147	99376	99105	99710	99713	+ driver 24V DC	
ON/OFF	ON/OFF	ON/OFF	24V DC converter	24V DC converter	99374	99331
1 - 2 art.	3 - 6 art.	6 - 12 art.	0/1-10V 1 - 6 art.	DALI 1 - 6 art.	75W	150W
138 x 22 x h 21	138 x 22 x h 21	103 x 58 x h 27	138 x 22 x h 20	138 x 22 x h 20		
29	29	64	29	29	56	70

Finishes

White
Nickel


Cct


M 2700 **N** 4000
W 3000

Step lights



OPTIWALL





	Fin	Cct	lm S - lm D	Opt
CRI 80 - 24 V DC - 1,2 W DC				
C01032	**WH**	**A**	126 - 68	**WW** (Asym. Ww)
	GG	**M**	151 - 81	
	DB	**W**	158 - 85	
	BG	**N**	167 - 90	
	AU			
	CU			

Electronics: **EQ** (pag 357)

*** Optiwall with AU and CU finishes can only be installed indoors.**

A CASCADE OF LIGHT IN A FEW MILLIMETRES OF THICKNESS

OPTIWALL is an innovative step light without outer casing and with a thickness reduced to the bare minimum: just 18 mm to house the light sources. Easy to install, ideal for marking corridors, pathways, and stairs. The recessed light sources, thanks to the flat diffuser underneath, diffuse a copious cascade of light both horizontally and vertically.





Grey (GG)



Dark Brown (DB)



Black Grey (BG)



Gold (AU)



Copper (CU)

Materials
Aluminium body.
PMMA diffuser.

Optiwall family Outdoor

Optiwall



674

Optiwall_Pro

674-675


Electronics

EQ

89488	**89179**	**89359**	**99332**	**83333**
ON/OFF 1 - 8 art. 100 x 80 x h 31	ON/OFF 1 - 14 art. 117 x 92 x h 38	ON/OFF 1 - 28 art. 140 x 115 x h 50	0/1-10V 1 - 90 art. 158 x 60 x h 35 70	DALI/PUSH 1 - 90 art. 188 x 68 x h 34 77

Finishes
White, Grey, Dark Brown, Black Grey, Gold, Copper

Cct
A 2200 **M** 2700 **W** 3000 **N** 4000



MICRO SPOT LIGHTS



THE RIVER
New York City, USA

Project: Bentel & Bentel

Photography: Arcphoto

Micro Spotlights range index

Bibok

Bibok



363

Aspho

Aspho_R



365

Aspho_Q



365

Picrol

Picrol



369

Nitum

Nitum_R



370

Nitum_Q



371

Ghilea

Ghilea



373

Crystals

Beriel



375

Elin



375

Ture



375-376

Gude



376

Eyelet

Eyelet_R



379

Eyelet_Q



379

Eyelet_R

NEW



379

Eyelet_Q


NEW



379


BIBOK

Brass body.



Bibok | 5mmLED | 24 V DC | 0,5 W DC







C.V. IP44

	Cct	Im S - Im D	Opt
CRI 80			
WH **91366**	**W**	42 - 6	**30** (45°)
CH **85335**	**C**	58 - 8	

Electronics: **AV** (pag 363) | Recessed casing: (pag 363)

Bibok | powerLED | 350 mA | 1 W DC






C.C. IP44

	Fin	Cct	Im S - Im D	Opt
CRI 90				
C00259	WH	**W**	132 - 39	**MW** (32°)
	CH	**N**	147 - 43	**WF** (66°)

Electronics: **A1** (pag 363) | Recessed casing: (pag 363)

Bibok | powerLED | 500 mA | 1,5 W DC





C.C. IP44

	Fin	Cct	Im S - Im D	Opt
CRI 90				
C00261	WH	**W**	181 - 53	**MW** (32°)
	CH	**N**	203 - 59	

Electronics: **B1** (pag 363) | Recessed casing: (pag 363)

Recessed casings



ABS **84916** Recessed casings

suitable for: Bibok 1W 13 mm



ABS **84917** Recessed casings

suitable for: Bibok 1,5W 13 mm

Electronics

A1

89144	89145	99375	C-E100010	C-E100011
ON/OFF	ON/OFF	ON/OFF	0/1-10V	DALI/PUSH
1 - 2 art.	3 - 6 art.	6 - 12 art.	3 - 4 art.	3 - 4 art.
138 x 22 x h 21	138 x 22 x h 21	138 x 22 x h 21	124 x 22 x h 22	124 x 22 x h 22
29	29	29	31	31

B1

99195	89146	99377	C-E100004	C-E100005
ON/OFF	ON/OFF	ON/OFF	0/1-10V	DALI/PUSH
1 - 2 art.	2 - 3 art.	3 - 6 art.	3 - 4 art.	3 - 4 art.
138 x 22 x h 21	138 x 22 x h 21	138 x 22 x h 21	124 x 22 x h 22	124 x 22 x h 22
29	29	64	31	31

AV

89408	99374	99332	83333	99722
ON/OFF	ON/OFF	0/1-10V	DALI/PUSH	DALI
1 - 10 art.	1 - 135 art.	1 - 270 art.	1 - 270 art.	1 - 220 art.
138 x 22 x h 20	210 x 49 x h 25	158 x 60 x h 35	188 x 68 x h 34	191 x 63 x h 38
29	56	70	77	73

Finishes

WH White
CH Chrome

Cct


W 3000 **C** 5000
N 4000


ASPHO

Brass or steel body.



Aspho_R | 5mmLED | 24 V DC | 0,5 W DC







C.V. IP44

	Cct	Im S - Im D	Opt
CRI 80			
WH 88417	W	45 - 6	30 (45°)
CH 85001	C	58 - 8	
NK 85002			

Electronics: **AV** (pag 367) | Recessed casing: (pag 367)

Aspho_R | 5mmLED | 24 V DC | 1,5 W DC







C.V. IP44

	Cct	Opt
WH 91352	Z RGB	30 (45°)
CH 86707		
NK 86708		

Electronics: **AM6** (pag 367) | Recessed casing: (pag 367)

Aspho_R | powerLED | 350 mA | 1 W DC






C.C. IP44

	Fin	Cct	Im S - Im D	Opt
CRI 90				
C00263	WH	M	124 - 36	MW (32°)
	CH	W	132 - 39	WF (66°)
	NK	N	147 - 43	
	BS			

Electronics: **A1** (pag 367) | Recessed casing: (pag 367)

Aspho_R | powerLED | 500 mA | 1,5 W DC






C.C. IP44

	Fin	Cct	Im S - Im D	Opt
CRI 90				
C00264	WH	M	170 - 50	MW (32°)
	CH	W	181 - 53	WF (66°)
	NK	N	203 - 59	

Electronics: **B1** (pag 367) | Recessed casing: (pag 367)

Aspho_Q | powerLED | 350 mA | 1 W DC






C.C. IP44

	Fin	Cct	Im S - Im D	Opt
CRI 90				
C00267	WH	M	124 - 37	MW (32°)
	CH	W	132 - 40	WF (66°)
	NK	N	147 - 44	

Electronics: **A1** (pag 367) | Recessed casing: (pag 367)

Aspho_Q | powerLED | 500 mA | 1,5 W DC





C.C. IP44

	Fin	Cct	Im S - Im D	Opt
CRI 90				
C00268	WH	M	170 - 51	MW (32°)
	CH	W	180 - 54	WF (66°)
	NK	N	203 - 60	

Electronics: **B1** (pag 367) | Recessed casing: (pag 367)



PADOVA CONGRESS
Padua (Italy)

Project: Architect Kengo Kuma

Lighting Designer:
Cogevi

Photography:
TheStudio

Recessed casings



ABS 84916 Recessed casings

suitable for: Aspho_R 0,5W H23 / Aspho_R 1W H23 / Aspho_Q 1W H23 / Aspho_R 1,5W(RGB) H23



ABS 84335 Recessed casings

suitable for: Aspho_R 0,5W H23 / Aspho_R 1W H23 / Aspho_Q 1W H23



ABS 84917 Recessed casings

suitable for: Aspho_R 1,5W H70 / Aspho_Q 1,5W H70

Electronics

A1

89144	89145	99375	C-E100010	C-E100011
ON/OFF	ON/OFF	ON/OFF	0/1-10V	DALI/PUSH
1 - 2 art.	3 - 6 art.	6 - 12 art.	3 - 4 art.	3 - 4 art.
138 x 22 x h 21	138 x 22 x h 21	138 x 22 x h 21	124 x 22 x h 22	124 x 22 x h 22
29	29	29	31	31

AV

89408	99374	99332	83333	99722
ON/OFF	ON/OFF	0/1-10V	DALI/PUSH	DALI
1 - 10 art.	1 - 135 art.	1 - 270 art.	1 - 270 art.	1 - 220 art.
138 x 22 x h 20	210 x 49 x h 25	158 x 60 x h 35	188 x 68 x h 34	191 x 63 x h 38
29	56	70	77	73

AM6

C-E700002+C-W600001	99331	C-E700005	DMX	99331
Dimmer RF	CV 24V	Dimmer DMX	Controllers	CV 24V
1 - 140 art.	150 W	1 - 140 art.		150 W
52 x 52 x h 26	158 x 60 x h 35		Pag. 963	158 x 60 x h 35
53	70			70

B1

99195	89146	99377	C-E100004	C-E100005
ON/OFF	ON/OFF	ON/OFF	0/1-10V	DALI/PUSH
1 - 2 art.	2 - 3 art.	3 - 6 art.	3 - 4 art.	3 - 4 art.
138 x 22 x h 21	138 x 22 x h 21	138 x 22 x h 21	124 x 22 x h 22	124 x 22 x h 22
29	29	64	31	31


PICROL

Brass or polyamide body.



Picrol | powerLED | 350 mA | 1 W DC






C.C. IP20

	Fin	Cct	lm S - lm D	Opt
CRI 90				
C00278	**WH**	**M**	124 - 91	**MW** (45°)
	BB	**W**	132 - 96	**WF** (61°)
	CH	**N**	147 - 107	**XF** (73°)

Electronics: **A1** (pag 369) | Recessed casing: (pag 369)

Picrol | powerLED | 350 mA | 1 W DC





C.C. IP44


	Fin	Cct	lm S - lm D	Opt
CRI 90				
C00280	**WH**	**M**	124 - 105	**ML** (35°)
	CH	**W**	132 - 112	**MW** (47°)
		N	147 - 126	**WF** (68°)
				XF (115°)

Installable only with its specific outer casing.

Electronics: **A1** (pag 369) | Recessed casing: (pag 369)

Picrol | powerLED | 500 mA | 1,5 W DC





C.C. IP44

	Fin	Cct	lm S - lm D	Opt
CRI 90				
C00281	**WH**	**M**	170 - 144	**ML** (35°)
	CH	**W**	181 - 154	**MW** (47°)
		N	203 - 173	**WF** (68°)
				XF (115°)

Installable only with its specific outer casing.

Electronics: **B1** (pag 369) | Recessed casing: (pag 369)

Recessed casings



ABS 98049 Recessed casings

suitable for: Picrol 1W H34



ABS 84336 Recessed casings

suitable for: Picrol 1W H26




ABS 84956 Recessed casings

suitable for: Picrol 1,5W H50



ABS 84901 Recessed casings

suitable for: Picrol 1,5W H50



ABS 84955 Recessed casings

suitable for: Picrol 1W H26

Electronics

A1

89144	89145	99375	C-E100010	C-E100011
ON/OFF	ON/OFF	ON/OFF	0/1-10V	DALI/PUSH
1 - 2 art.	3 - 6 art.	6 - 12 art.	3 - 4 art.	3 - 4 art.
138 x 22 x h 21	138 x 22 x h 21	138 x 22 x h 21	124 x 22 x h 22	124 x 22 x h 22
29	29	29	31	31

B1

99195	89146	99377	C-E100004	C-E100005
ON/OFF	ON/OFF	ON/OFF	0/1-10V	DALI/PUSH
1 - 2 art.	2 - 3 art.	3 - 6 art.	3 - 4 art.	3 - 4 art.
138 x 22 x h 21	138 x 22 x h 21	138 x 22 x h 21	124 x 22 x h 22	124 x 22 x h 22
29	29	64	31	31

Finishes

White
Black
Chrome

Cct

M 2700 **N** 4000
W 3000

NITUM


Brass or steel body.





Nitum_R | powerLED | 350 mA | 1 W DC







C.C. IP44

	Fin	Cct	lm S - lm D	Opt
CRI 90				
C00269	**WH**	**M**	124 - 105	**ML** (35°)
	CH	**W**	132 - 112	**MW** (47°)
	NK	**N**	147 - 126	**WF** (68°)
	IS			**XF** (115°)

Electronics: **A1** (pag 371) | Recessed casing: (pag 371)

Nitum_R | powerLED | 630 mA | 2 W DC






C.C. IP44

	Fin	Cct	lm S - lm D	Opt
CRI 90				
C00273	**WH**	**M**	199 - 169	**ML** (35°)
	CH	**W**	212 - 180	**MW** (47°)
	NK	**N**	237 - 202	**WF** (68°)
	IS			**XF** (115°)

Electronics: **C1** (pag 371) | Recessed casing: (pag 371)

Nitum_R | powerLED | 220 mA | 2,1 W DC





C.C. IP44 RGB

	Cct	Opt
WH **88568**	**Z** RGB	**15** (21°)
CH **86612**		**30** (27°)
NK **86613**		**60** (50°)
IS **86674**		**00** (Diffused)

Electronics: **CC** (pag 371) | Recessed casing: (pag 371) | Cables: (pag 970)



For Nitum_R RGB 2,1W


Finishes


WH White
CH Chrome
NK Nickel
IS Steel

Cct

M 2700 **N** 4000
W 3000 **Z** RGB

Nitum_Q | powerLED | 350 mA | 1 W DC






	Fin	Cct	lm S - lm D	Opt
CRI 90				
C00275	**WH**	**M**	124 - 105	**ML** (35°)
	CH	**W**	132 - 112	**MW** (47°)
	NK	**N**	147 - 126	**WF** (68°)
	IS			**XF** (115°)

Electronics: **A1** (pag 371) | Recessed casing: (pag 371)

Nitum_Q | powerLED | 630 mA | 2 W DC






	Fin	Cct	lm S - lm D	Opt
CRI 90				
C00276	**WH**	**M**	199 - 169	**ML** (35°)
	CH	**W**	212 - 180	**MW** (47°)
	NK	**N**	237 - 202	**WF** (68°)
	IS			**XF** (115°)

Electronics: **C1** (pag 371) | Recessed casing: (pag 371)

Nitum_Q | powerLED | 220 mA | 2,1 W DC





	Cct	Opt
WH **88569**	**Z** RGB	**15** (21°)
CH **86614**		**30** (27°)
NK **86615**		**60** (50°)
IS **86675**		**00** (Diffused)

Electronics: **CC** (pag 371) | Recessed casing: (pag 371) | Cables: (pag 970)



For Nitum_Q RGB 2,1W

Recessed casings




ABS **84336** Recessed casings

suitable for: Nitum_R 1W / Nitum_Q 1W H24,5



ABS **84915** Recessed casings

suitable for: Nitum_R 1W / Nitum_Q 1W H24,5



ABS **84901** Recessed casings

suitable for: Nitum_R 2W / Nitum_R 2,1W H45
Nitum_Q 2W / Nitum_Q 2,1W H45

Electronics

A1

89144	89145	99375	C-E100010	C-E100011
ON/OFF	ON/OFF	ON/OFF	0/1-10V	DALI/PUSH
1 - 2 art.	3 - 6 art.	6 - 12 art.	3 - 4 art.	3 - 4 art.
138 x 22 x h 21	138 x 22 x h 21	138 x 22 x h 21	124 x 22 x h 22	124 x 22 x h 22
29	29	29	31	31

C1

89147	99376	99105	99710	99713	+ driver 24V DC	
ON/OFF	ON/OFF	ON/OFF	24V DC converter	24V DC converter	99374	99331
1 - 2 art.	3 - 6 art.	6 - 12 art.	0/1-10V 1 - 6 art.	DALI 1 - 6 art.	75W	150W
138 x 22 x h 21	138 x 22 x h 21	103 x 58 x h 27	138 x 22 x h 20	138 x 22 x h 20		
29	29	64	29	29	56	70

CC

C-E700003+C-W600001	C-E500015	DMX	Driver CV	Switching
Dimmer RF	Dimmer DMX	Controllers	CV 48V	CV 48V
6 - 12 art.	6 - 12 art.			
175 x 45 x h 27	107 x 96 x h 39	Pag. 963	Pag. 950-951	Pag. 945-946
52				


GHILEA

Aluminium body.



Ghilea | powerLED | 630 mA | 2 W DC






	Fin	Cct	lm S - lm D	Opt
CRI 90				
C00282	**WH**	**M**	199 - 133	**FL** (21°)
	BB	**W**	212 - 142	**ML** (32°)
	NK	**N**	237 - 159	
	CH			

Electronics: **C1** (pag 373) | Recessed casing: (pag 373)



Eos Hotel
Lecce (Italy)

Recessed casings



ABS **84902** Recessed casings

suitable for: Ghilea

Electronics

C1

89147	**99376**	**99105**	**99710**	**99713**	**+ driver 24V DC**	
ON/OFF	ON/OFF	ON/OFF	24V DC converter	24V DC converter	**99374**	**99331**
1 - 2 art.	3 - 6 art.	6 - 12 art.	0/1-10V 1 - 6 art.	DALI 1 - 6 art.	75W	150W
138 x 22 x h 21	138 x 22 x h 21	103 x 58 x h 27	138 x 22 x h 20	138 x 22 x h 20		
29	29	64	29	29	56	70

Finishes

White Nickel
Black Chrome

Cct

M 2700 **N** 4000
W 3000


CRYSTALS

Brass body. Transparent prismatic ground crystal diffuser.



Beriel | powerLED | 350 mA | 1 W DC






	Fin	Cct	lm S - lm D	Opt
CRI 90				
C00283	**CH**	**M**	124 - On req	**DI** (Diffused)
		W	132 - On req	
		N	147 - On req	

Electronics: **A1** (pag 376) | Recessed casing: (pag 379)

Beriel | powerLED | 500 mA | 1,5 W DC






	Fin	Cct	lm S - lm D	Opt
CRI 90				
C00284	**CH**	**M**	170 - On req	**DI** (Diffused)
		W	181 - On req	
		N	203 - On req	

Electronics: **B1** (pag 376) | Recessed casing: (pag 377)

Elin | 5mmLED | 24 V DC | 0,5 W DC






	Cct	Opt
87340	**Z** RGB	**00** (Diffused)

Electronics: **AM6** (pag 376) | Recessed casing: (pag 377)

Elin | powerLED | 350 mA | 1 W DC






	Fin	Cct	lm S - lm D	Opt
CRI 90				
C00292	**CH**	**M**	124 - On req	**DI** (Diffused)
		W	132 - On req	
		N	147 - On req	

Electronics: **A1** (pag 376) | Recessed casing: (pag 377)

Elin | powerLED | 500 mA | 1,5 W DC






	Fin	Cct	lm S - lm D	Opt
CRI 90				
C00293	**CH**	**M**	170 - On req	**DI** (Diffused)
		W	181 - On req	
		N	203 - On req	

Electronics: **B1** (pag 376) | Recessed casing: (pag 377)

Ture | powerLED | 500 mA | 1,5 W DC





	Fin	Cct	lm S - lm D	Opt
CRI 90				
C00294	**CH**	**M**	170 - On req	**DI** (Diffused)
		W	181 - On req	
		N	203 - On req	

Electronics: **B1** (pag 376) | Recessed casing: (pag 377)



For Elin RGB 0,5W

Finishes


CH Chrome

Cct

M 2700 **N** 4000
W 3000 **Z** RGB

Ture | powerLED | 500 mA | 1,5 W DC






	Fin	Cct	lm S - lm D	Opt
CRI 90				
C00295	**CH**	**M**	170 - On req	**DI** (Diffused)
		W	181 - On req	
		N	203 - On req	

Electronics: **B1** (pag 376) | Recessed casing: (pag 377)

Ture | powerLED | 500 mA | 1,5 W DC






	Fin	Cct	lm S - lm D	Opt
CRI 90				
C00296	**CH**	**M**	170 - On req	**DI** (Diffused)
		W	181 - On req	
		N	203 - On req	

Electronics: **B1** (pag 376) | Recessed casing: (pag 377)

Gude | powerLED | 500 mA | 1,5 W DC






	Fin	Cct	lm S - lm D	Opt
CRI 90				
C00297	**CH**	**M**	170 - On req	**XF** (99°)
		W	181 - On req	
		N	203 - On req	

Electronics: **B1** (pag 376) | Recessed casing: (pag 377)

Gude | powerLED | 500 mA | 1,5 W DC






	Fin	Cct	lm S - lm D	Opt
CRI 90				
C00298	**CH**	**M**	170 - On req	**XF** (99°)
		W	181 - On req	
		N	203 - On req	

Electronics: **B1** (pag 376) | Recessed casing: (pag 377)

Gude | powerLED | 500 mA | 1,5 W DC





	Fin	Cct	lm S - lm D	Opt
CRI 90				
C00299	**CH**	**M**	170 - On req	**XF** (99°)
		W	181 - On req	
		N	203 - On req	

Electronics: **B1** (pag 376) | Recessed casing: (pag 377)

Electronics

A1

89144	89145	99375	C-E100010	C-E100011
ON/OFF	ON/OFF	ON/OFF	0/1-10V	DALI/PUSH
1 - 2 art.	3 - 6 art.	6 - 12 art.	3 - 4 art.	3 - 4 art.
138 x 22 x h 21	138 x 22 x h 21	138 x 22 x h 21	124 x 22 x h 22	124 x 22 x h 22
29	29	29	31	31

B1

99195	89146	99377	C-E100004	C-E100005
ON/OFF	ON/OFF	ON/OFF	0/1-10V	DALI/PUSH
1 - 2 art.	2 - 3 art.	3 - 6 art.	3 - 4 art.	3 - 4 art.
138 x 22 x h 21	138 x 22 x h 21	138 x 22 x h 21	124 x 22 x h 22	124 x 22 x h 22
29	29	64	31	31

AM6

C-E700002+C-W600001	99331	C-E700005	DMX	99331
Dimmer RF	CV 24V	Dimmer DMX	Controllers	CV 24V
1 - 140 art.	150 W	1 - 140 art.		150 W
52 x 52 x h 26	158 x 60 x h 35		Pag. 963	158 x 60 x h 35
53	70			70

Recessed casings



ABS 84335 Recessed casings

suitable for: Beriel 1W / Elin 0,5W / Elin 1W



ABS 84917 Recessed casings

suitable for: Beriel 1,5W / Elin 1,5W /
Ture 1,5W Ø21 mm / Gude 1,5W L 20 mm



ABS 84901 Recessed casings

suitable for: Ture 1,5W Ø41 mm / Gude 1,5W L 40 mm



ABS 84916 Recessed casings

suitable for: Elin 0,5W / Elin 1W



ABS 84954 Recessed casings

suitable for: Ture 1,5W Ø31 mm / Gude 1,5W L 30 mm



ALMAR HOTEL
Jesolo (Italy)

Photography:
Studio Pointer


EYELET

Aluminium body.



Eyelet_R | powerLED | 350 mA | 1 W DC







C.C. IK03 IP40

	Fin	Cct	lm S - lm D	Opt
CRI 90				
C00301	**WH**	**M**	124 - 64	**FL** (20°)
	BB	**W**	132 - 68	**ML** (34°)
	GG	**N**	147 - 76	
	DB			

Electronics: **A1** (pag 379)

Eyelet_Q | powerLED | 350 mA | 1 W DC






C.C. IK03 IP40

	Fin	Cct	lm S - lm D	Opt
CRI 90				
C00303	**WH**	**M**	124 - 64	**FL** (20°)
	BB	**W**	132 - 68	**ML** (34°)
	GG	**N**	147 - 76	
	DB			

Electronics: **A1** (pag 379)

Eyelet_R | powerLED | 630 mA 2 W DC | 1000 mA 3 W DC






C.C. IK03 IP40 NEW

	Fin	Cct	lm S - lm D 2 W	lm S - lm D 3 W	Opt
CRI 90					
C01045	**WH**	**M**	199 - 154	358 - 278	**FL** (24°)
	BB	**W**	212 - 164	402 - 312	**ML** (31°)
	GG	**N**	237 - 183	417 - 327	**WF** (54°)
	DB				

Electronics: 2W **C1** - 3W **FQ** (pag 379)

Eyelet_Q | powerLED | 630 mA 2 W DC | 1000 mA 3 W DC





C.C. IK03 IP40 NEW

	Fin	Cct	lm S - lm D 2 W	lm S - lm D 3 W	Opt
CRI 90					
C01046	**WH**	**M**	199 - 154	358 - 278	**FL** (24°)
	BB	**W**	212 - 164	402 - 312	**ML** (31°)
	GG	**N**	237 - 183	417 - 327	**WF** (54°)
	DB				

Electronics: 2W **C1** - 3W **FQ** (pag 379)



Electronics

A1

89144	89145	99375	C-E100010	C-E100011
ON/OFF	ON/OFF	ON/OFF	0/1-10V	DALI/PUSH
1 - 2 art.	3 - 6 art.	6 - 12 art.	3 - 4 art.	3 - 4 art.
138 x 22 x h 21	138 x 22 x h 21	138 x 22 x h 21	124 x 22 x h 22	124 x 22 x h 22
29	29	29	31	31

C1

89147	99376	99105	99710	99713	+ driver 24V DC	
ON/OFF	ON/OFF	ON/OFF	24V DC converter	24V DC converter	99374	99331
1 - 2 art.	3 - 6 art.	6 - 12 art.	0/1-10V 1 - 6 art.	DALI 1 - 6 art.	75W	150W
138 x 22 x h 21	138 x 22 x h 21	103 x 58 x h 27	138 x 22 x h 20	138 x 22 x h 20		
29	29	64	29	29	56	70

FQ


C-E100046	C-E100047	C-E100033	C-E100034
ON/OFF	DALI	ON/OFF	DALI/PUSH
1 - 6 art.	1 - 3 art.	4 - 12 art.	4 - 12 art.
130 x 38 x h 28	140 x 36 x h 20	138 x 44 x h 23	138 x 44 x h 23
48	40	50	50

Finishes

White
Black
Grey
Dark Brown

Cct

M 2700 **N** 4000
W 3000



FLEX LIGHTS & PROFILES

LUFTSCHIFFHANGAR MÜLHEIM
Mülheim an der Ruhr (Germany)

Project: WDL-Gruppe, Luftschiffhangar Mülheim, Luftschiff Theo, Elomechgruppe

Photography:
Stefan Lamberty



Flex lights & Profiles range index


LED Strips

Ribbon NEW  390-391

Ribbon Plus NEW  392-393


Ribbon (cobLED) NEW  393

Ribbon PRO NEW  394

Silicone NEW  396

PU_C Plus NEW  397

Profiles

 404-407

Rubber 2D mini

Rubber 2D_mini NEW  411

Rubber 3D

Rubber 3D NEW  412-413

Rubber 3D Concrete NEW  412

Rubber 3D Optics NEW  416

Rubber 3D PIXEL RGBW NEW  417


Rubber 3D PROtection NEW  418

Rubber_O

Rubber_O NEW  424


How to configure a product

guide to the composition of the finished code



QUALITY, MATERIAL, SECURITY MEASURE, TEST AND CONTROL SPEAK ONLY ONE LANGUAGE

Made in Italy



Guaranteed quality


All Made in Italy strips are certified and guaranteed for 3 years. The company is ISO 9001 certified. The materials and components used, for the construction of our products, are guaranteed by international certifying bodies such as IMQ and UL, and are marked and tested according to CE standards.

ICS regulators

Specific integrated circuits guarantee luminous uniformity over the entire length of the product and intervene when voltage drops occur (typical in long stretches), preventing drops in luminous flux. Thanks to these innovations, perfectly identical lumen values are maintained from the beginning to the end of the circuit. In addition, the ICS chips are able to automatically detect polarity reversal and activate safe protection, preventing the entire circuit from being compromised.

LED STRIPS COLLECTIONS COMPARISON

Ribbon Pro



The Ribbon Pro series has been designed to deliver superior performance in advanced lighting designs. Completely Made in Italy, created to guarantee high efficiency and performance of the highest level, selected LEDs instead allow true colour accuracy with a high Colour Rendering Index; the R9 value is above 50 and ensures bright reds, ideal when the highest quality of light is required. The circuit is made of RA copper and guarantees high flexibility and better thermal and electrical conductivity, while special ICS chips prevent voltage drops, keeping the brightness uniform along the entire length of the Ribbon Pro strips.
ICS chips also offer robust protection against reverse polarity due to incorrect connection. Ribbon Pro installation contexts: Museums and art galleries, places of worship, photographic studios, film sets, theatres, offices, boutiques, doctors' surgeries, public buildings, green buildings.

Ribbon Plus & PU_C Plus



The Ribbon Plus (IP20) and PU_C Plus (IP66) series represent the excellent compromise between performance and price. Completely Made in Italy and designed with high standards using high quality components, thus ensuring long life and reliable performance over time. A collection suitable for versatile and efficient installation solutions, designed to create welcoming atmospheres or emphasise architectural details without compromising the budget.
Ribbon Plus and PU_C Plus installation contexts: offices, meeting rooms, hotels, wellness centres, shops, shopping malls, building façades, landscape.

Ribbon & Silicone



The Ribbon (IP20) and Silicone (IP67) series are made with a standardised production process, have basic technological features and represent an excellent entry point for those looking for LED strips at an affordable level. Ideal for decorative or secondary lighting.
Ribbon and Silicone installation contexts: cove lighting, residential, restaurants and bars, warehouses, gardens.

LED STRIPS OPERATIVE INDEX

IP20

MONOCHROME		See	Electronic information	Brightness lm/m at 3000K			CRI	R9	ICS	PP	Guarantee years		Page
24V	**SLIM (5MM WIDTH)**												
	Ribbon	09	9,6 W/m - 120 LED/m		843 Lm/m	5m	90	-	-	-	2		391
	Ribbon	10	10,5 W/m - 160 LED/m		1209 Lm/m	5m	90	-	-	-	2		391
	LOW POWER (FROM 3 TO 10 W/m)												
	Ribbon Plus	13	4,8 W/m - 70 LED/m		543 Lm/m	5m	90	-	ICS	√	3	Made in Italy	392
		14	9,6 W/m - 70 LED/m		1150 Lm/m	5m	90	-	ICS	√	3	Made in Italy	392
		15	9,6 W/m - 140 LED/m		1176 Lm/m	5m	90	-	ICS	√	3	Made in Italy	392
	Ribbon	01	4,8 W/m - 60 LED/m		491 Lm/m	5m	90	-	-	-	2		390
		02	9,6 W/m - 120 LED/m		1011 Lm/m	5m	90	-	-	-	2		390
	MEDIUM POWER (FROM 11 TO 18 W/m)												
	Ribbon Plus	16	14,4 W/m - 140 LED/m		1870 Lm/m	5m	90	-	ICS	√	3	Made in Italy	392
	Ribbon	07	12 W/m - 160 LED/m		1396 Lm/m	5m	95	-	-	-	2		391
		03	14,4 W/m - 168 LED/m		1613 Lm/m	5m	90	-	-	-	2		390
		21	10 W/m - CobLED		978 Lm/m	5m	90	-	-	-	2		393
	HIGH POWER (OVER 19 W/m)												
	Ribbon Plus	17	19,2 W/m - 140 LED/m		2306 Lm/m	5m	90	-	ICS	√	3	Made in Italy	392
	Ribbon	08	21,6 W/m - 160 LED/m		2341 Lm/m	5m	95	-	-	-	2		391
		04	19,6 W/m - 238 LED/m		2216 Lm/m	5m	90	-	-	-	2		390
	HIGH EFFICIENCY												
	Ribbon PRO	22	3,6 W/m - 80 LED/m		518 Lm/m	5m	90	>50	ICS	√	3	Made in Italy	394
		23	6,7 W/m - 128 LED/m		958 Lm/m	5m	90	>50	ICS	√	3	Made in Italy	394
		24	9,6 W/m - 80 LED/m		1418 Lm/m	5m	90	>50	ICS	√	3	Made in Italy	394
		25	13,6 W/m - 128 LED/m		1961 Lm/m	5m	90	>50	ICS	√	3	Made in Italy	394
		26	16,8 W/m - 160 LED/m		2420 Lm/m	5m	90	>50	ICS	√	3	Made in Italy	394
	Ribbon	05	12 W/m - 160 LED/m		1538 Lm/m	5m	85	-	-	-	2		390
		06	21,6 W/m - 160 LED/m		2901 Lm/m	5m	85	-	-	-	2		390
48V	**LOW POWER (FROM 3 TO 10 W/m)**												
	Ribbon PRO	27	8,6 W/m - 136 LED/m		1504 Lm/m	5m	90	>50	ICS	√	3	Made in Italy	394
	Ribbon	11	9,6 W/m - 130 LED/m		1041 Lm/m	20m	90	-	-	-	2		391
	MEDIUM POWER (FROM 11 TO 18) W/m)												
	Ribbon	12	13,8 W/m - 130 LED/m		1446 Lm/m	15m	90	-	-	-	2		391

COLOR		See	Electronic information	Brightness lm/m at 3000K			CRI	R9	ICS	PP	Guarantee years		Page
24V	**RGBW**												
	Ribbon Plus RGBW	18	19,2 W/m - 60+60 LED/m		-	5m	90	-	ICS	√	3	Made in Italy	393
	WARM TUNE												
	Ribbon Plus WT	19	13 W/m - 70+70 LED/m		-	5m	90	-	ICS	√	3	Made in Italy	393
	DYNAMIC WHITE												
	Ribbon Plus DW	20	12,5 W/m - 70+70 LED/m		-	5m	90	-	ICS	√	3	Made in Italy	393

IP66/IP67

MONOCHROME		See	Electronic information	Brightness Lm/m at 3000K			CRI	R9	ICS	PP	Guarantee years		Page
24V	**LOW POWER (FROM 3 TO 10 W/m)**												
	PU_C Plus (IP66)	33	3,2 W/m - 70 LED/m		310 Lm/m	5m	90	-	ICS	√	3	Made in Italy	397
		34	7,2 W/m - 140 LED/m		663 Lm/m	5m	90	-	ICS	√	3	Made in Italy	397
	Silicone (IP67)	28	4,8 W/m - 60 LED/m		415 Lm/m	5m	90	-	-	-	2		396
		29	9,6 W/m - 120 LED/m		864 Lm/m	5m	90	-	-	-	2		396
	MEDIUM POWER (FROM 11 TO 18 W/m)												
	PU_C Plus (IP66)	35	12,5 W/m - 70 LED/m		1267 Lm/m	5m	90	-	ICS	√	3	Made in Italy	397
	Silicone (IP67)	30	14,4 W/m - 168 LED/m		1425 Lm/m	5m	90	-	-	-	2		396
	HIGH POWER (OVER 19 W/m)												
	PU_C Plus (IP66)	36	25 W/m - 140 LED/m		2346 Lm/m	5m	90	-	ICS	√	3	Made in Italy	397
	HIGH EFFICIENCY												
	Silicone (IP67)	31	12 W/m - 160 LED/m		1556 Lm/m	5m	85	-	-	-	2		396
48V	**MEDIUM POWER (FROM 11 TO 18) W/m)**												
	Silicone (IP67)	32	13,8 W/m - 130 LED/m		1320 Lm/m	15m	90	-	-	-	2		396
COLOR													
24V	**RGBW** (IP66)												
	PU_C Plus RGBW	37	19,2 W/m - 60+60 LED/m		-	5m	90	-	ICS	√	3	Made in Italy	397

Legend:

- Roll strip length
- **CRI** Colour Rendering Index
- **R9** R9 value
- **ICS** ICS Regulators
- **PP** Reverse polarity protection







LUXEMBOURG PAVILION
ARCHITECTURE
BIENNALE 2018
Venice (Italy)

Photography:
Diego Fava - Studio Pointer

IP20

Ribbon | 60 LED/m | topLED | 24 V DC | 4,8 W/m







C.V. CRI 90 IP20 NEW

	Cct	lm S - lm D	Opt	L
CRI 90				
C0033	**M**	2331 - 2331	**DI**	**05000** (5 m - 24 W)
	W	2457 - 2457		
	N	2612 - 2612		

Electronics: **AL** (pag 399) | Accessories (pag 398) | Linear profile (pag 400)

Ribbon | 120 LED/m | topLED | 24 V DC | 9,6 W/m







C.V. CRI 90 IP20 NEW

	Cct	lm S - lm D	Opt	L
CRI 90				
C0036	**M**	4662 - 4662	**DI**	**05000** (5 m - 48 W)
	W	5057 - 5057		
	N	5247 - 5247		

Electronics: **AL** (pag 399) | Accessories (pag 398) | Linear profile (pag 400)

Ribbon | 168 LED/m | topLED | 24 V DC | 14,4 W/m







C.V. CRI 90 IP20 NEW

	Cct	lm S - lm D	Opt	L
CRI 90				
C0041	**M**	7725 - 7725	**DI**	**05000** (5 m - 72 W)
	W	8067 - 8067		
	N	8650 - 8650		

Electronics: **AL** (pag 399) | Accessories (pag 398) | Linear profile (pag 400)

Ribbon | 238 LED/m | topLED | 24 V DC | 19,6 W/m







C.V. CRI 90 IP20 NEW

	Cct	lm S - lm D	Opt	L
CRI 90				
C0042	**M**	10628 - 10628	**DI**	**05000** (5 m - 98 W)
	W	11080 - 11080		
	N	11750 - 11750		

Electronics: **AL** (pag 399) | Accessories (pag 398) | Linear profile (pag 400)

Ribbon | 160 LED/m | topLED | 24 V DC | 12 W/m







C.V. IP20 NEW

	Cct	lm S - lm D	Opt	L
CRI 85				
C0043	**M**	7339 - 7339	**DI**	**05000** (5 m - 60 W)
	W	7689 - 7689		
	N	8200 - 8200		

Electronics: **AL** (pag 399) | Accessories (pag 398) | Linear profile (pag 400)

Ribbon | 160 LED/m | topLED | 24 V DC | 21,6 W/m





C.V. IP20 NEW

	Cct	lm S - lm D	Opt	L
CRI 85				
C0044	**M**	13838 - 13838	**DI**	**05000** (5 m - 108 W)
	W	14506 - 14506		
	N	15187 - 15187		

Electronics: **AL** (pag 399) | Accessories (pag 398) | Linear profile (pag 400)

Finishes


WH White

Cct

M 2700 **N** 4000
W 3000

IP20

Ribbon | 160 LED/m | topLED | 24 V DC | 12 W/m




C.V. IP20 NEW CRI 95

	Cct	lm S - lm D	Opt	L
CRI 95				
C0045	**M**	6394 - 6394	**DI**	**05000** (5 m - 60 W)
	W	6982 - 6982		
	N	7174 - 7174		

Electronics: **AL** (pag 399) | Accessories (pag 398) | Linear profile (pag 400)

Ribbon | 160 LED/m | topLED | 24 V DC | 21,6 W/m




C.V. IP20 NEW CRI 95

	Cct	lm S - lm D	Opt	L
CRI 95				
C0046	**M**	11403 - 11403	**DI**	**05000** (5 m - 108 W)
	W	11705 - 11705		
	N	12643 - 12643		

Electronics: **AL** (pag 399) | Accessories (pag 398) | Linear profile (pag 400)

Ribbon | Slim | 120 LED/m | topLED | 24 V DC | 9,6 W/m




C.V. CRI 90 IP20 NEW 5 mm

	Cct	lm S - lm D	Opt	L
CRI 90				
C0047	**M**	4029 - 4029	**DI**	**05000** (5 m - 48 W)
	W	4214 - 4214		
	N	4653 - 4653		

Electronics: **AL** (pag 399) | Accessories (pag 398) | Linear profile (pag 400)

Ribbon | Slim | 160 LED/m | topLED | 24 V DC | 10,5 W/m




C.V. IP20 NEW 5 mm

	Cct	lm S - lm D	Opt	L
CRI 90				
C0048	**M**	5661 - 5661	**DI**	**05000** (5 m - 52,5 W)
	W	6048 - 6048		
	N	6632 - 6632		

Electronics: **AL** (pag 399) | Accessories (pag 398) | Linear profile (pag 400)

Ribbon | 130 LED/m | topLED | 48 V DC | 9,6 W/m




C.V. IP20 NEW 20 m 48V

	Cct	lm S - lm D	Opt	L
CRI 90				
C0049	**M**	19862 - 19862	**DI**	**20000** (20 m - 192 W)
	W	20812 - 20812		
	N	21647 - 21647		

Electronics: **EK** (pag 399) | Accessories (pag 398) | Linear profile (pag 400)

Ribbon | 130 LED/m | topLED | 48 V DC | 13,8 W/m




C.V. IP20 NEW 15 m 48V


	Cct	lm S - lm D	Opt	L
CRI 90				
C0050	**M**	20868 - 20868	**DI**	**15000** (15 m - 207 W)
	W	21688 - 21688		
	N	23132 - 23132		

Electronics: **EK** (pag 399) | Accessories (pag 398) | Linear profile (pag 400)

IP20

Ribbon Plus | 70 LED/m | topLED | 24 V DC | 4,8 W/m







		Cct	lm S - lm D	Opt	L
CRI 90					
C0021		**M**	2522 - 2522	**DI**	**05000** (5 m - 24 W)
		W	2712 - 2712		
		N	2880 - 2880		

Electronics: **AL** (pag 399) | Accessories (pag 398) | Linear profile (pag 400)

Ribbon Plus | 70 LED/m | topLED | 24 V DC | 9,6 W/m







		Cct	lm S - lm D	Opt	L
CRI 90					
C0027		**M**	5580 - 5580	**DI**	**05000** (5 m - 48 W)
		W	5750 - 5750		
		N	6300 - 6300		

Electronics: **AL** (pag 399) | Accessories (pag 398) | Linear profile (pag 400)

Ribbon Plus | 140 LED/m | topLED | 24 V DC | 9,6 W/m







		Cct	lm S - lm D	Opt	L
CRI 90					
C0022		**M**	5610 - 5610	**DI**	**05000** (5 m - 48 W)
		W	5880 - 5880		
		N	6260 - 6260		

Electronics: **AL** (pag 399) | Accessories (pag 398) | Linear profile (pag 400)

Ribbon Plus | 140 LED/m | topLED | 24 V DC | 14,4 W/m







		Cct	lm S - lm D	Opt	L
CRI 90					
C0029		**M**	8810 - 8810	**DI**	**05000** (5 m - 72 W)
		W	9350 - 9350		
		N	10110 - 10110		

Electronics: **AL** (pag 399) | Accessories (pag 398) | Linear profile (pag 400)

Ribbon Plus | 140 LED/m | topLED | 24 V DC | 19,2 W/m






		Cct	lm S - lm D	Opt	L
CRI 90					
C0039		**M**	11110 - 11110	**DI**	**05000** (5 m - 96 W)
		W	11530 - 11530		
		N	12010 - 12010		

Electronics: **AL** (pag 399) | Accessories (pag 398) | Linear profile (pag 400)

IP20


Ribbon Plus RGBW | 60+60 LED/m | topLED | 24 V DC | 19,2 W/m



Cct	lm S - lm D	Opt	L
CRI 90			
C0027 ▭ **V**	RGBW (3000 K)	**DI**	**05000** (5 m - 96 W)

Electronics: **AM7** (pag 399) | Accessories (pag 398) | Linear profile (pag 400)


Ribbon Plus WT | 70+70 LED/m | topLED | 24 V DC | 13 W/m



Cct	lm S - lm D	Opt	L
CRI 90			
C0027 ▭ **S**	Warm tune 1800-3000 K	**DI**	**05000** (5 m - 65 W)

Electronics: **AM7** (pag 399) | Accessories (pag 398) | Linear profile (pag 400)

Ribbon Plus DW | 70+70 LED/m | topLED | 24 V DC | 12,5 W/m



Cct	lm S - lm D	Opt	L
CRI 90			
C0027 ▭ **D**	Dynamic White 1800-4000 K	**DI**	**05000** (5 m - 62,5 W)


Electronics: **AM7** (pag 399) | Accessories (pag 398) | Linear profile (pag 400)

WT

Warm Tune

Warm Tune rekindles lovely memories of the incandescence lamps: the light becomes progressively warmer and dimmer as the intensity reduces until reaches the candle effect.

Ribbon | cobLED | 24 V DC | 10 W/m




Cct	lm S - lm D	Opt	L
CRI 90			
C0037 ▭ **M**	4779 - 4779	**DI**	**05000** (5 m - 50 W)
W	4892 - 4892		
N	5690 - 5690		

Electronics: **AL** (pag 399) | Accessories (pag 398) | Linear profile (pag 400)

IP20


Ribbon PRO | 80 LED/m | topLED | 24 V DC | 3,6 W/m



		Cct	lm S - lm D	Opt	L
CRI 90					
C0023		**M**	2558 - 2558	**DI**	**05000** (5 m - 18 W)
		W	2590 - 2590		
		N	2754 - 2754		

Electronics: **AL** (pag 399) | Accessories (pag 398) | Linear profile (pag 400)


Ribbon PRO | 128 LED/m | topLED | 24 V DC | 6,7 W/m



		Cct	lm S - lm D	Opt	L
CRI 90					
C0024		**M**	4638 - 4638	**DI**	**05000** (5 m - 33,5 W)
		W	4791 - 4791		
		N	5115 - 5115		

Electronics: **AL** (pag 399) | Accessories (pag 398) | Linear profile (pag 400)


Ribbon PRO | 80 LED/m | topLED | 24 V DC | 9,6 W/m



		Cct	lm S - lm D	Opt	L
CRI 90					
C0028		**M**	6835 - 6835	**DI**	**05000** (5 m - 48 W)
		W	7088 - 7088		
		N	7519 - 7519		

Electronics: **AL** (pag 399) | Accessories (pag 398) | Linear profile (pag 400)


Ribbon PRO | 128 LED/m | topLED | 24 V DC | 13,6 W/m



		Cct	lm S - lm D	Opt	L
CRI 90					
C0030		**M**	9447 - 9447	**DI**	**05000** (5 m - 68 W)
		W	9806 - 9806		
		N	10489 - 10489		

Electronics: **AL** (pag 399) | Accessories (pag 398) | Linear profile (pag 400)


Ribbon PRO | 160 LED/m | topLED | 24 V DC | 16,8 W/m



		Cct	lm S - lm D	Opt	L
CRI 90					
C0031		**M**	11857 - 11857	**DI**	**05000** (5 m - 84 W)
		W	12098 - 12098		
		N	13013 - 13013		

Electronics: **AL** (pag 399) | Accessories (pag 398) | Linear profile (pag 400)

Ribbon PRO | 136 LED/m | topLED | 48 V DC | 8,6 W/m



		Cct	lm S - lm D	Opt	L
CRI 90					
C0040		**M**	6482 - 6482	**DI**	**05000** (5 m - 43 W)
		W	7519 - 7519		
		N	7792 - 7792		

Electronics: **AL** (pag 399) | Accessories (pag 398) | Linear profile (pag 400)


Finishes White


Cct **M** 2700 **N** 4000 **W** 3000



IP67

Silicone | 60 LED/m | topLED | 24 V DC | 4,8 W/m







	Cct	lm S - lm D	Opt	L
CRI 90				
C0051	**M**	1996 - 1996	**DI**	**05019** (5 m - 24 W)
	W	2077 - 2077		
	N	2189 - 2189		

Electronics: **AL** (pag 399) | Accessories (pag 398) | Linear profile (pag 400)

Silicone | 120 LED/m | topLED | 24 V DC | 9,6 W/m







	Cct	lm S - lm D	Opt	L
CRI 90				
C0052	**M**	4040 - 4040	**DI**	**05019** (5 m - 48 W)
	W	4323 - 4323		
	N	4490 - 4490		

Electronics: **AL** (pag 399) | Accessories (pag 398) | Linear profile (pag 400)

Silicone | 168 LED/m | topLED | 24 V DC | 14,4 W/m







	Cct	lm S - lm D	Opt	L
CRI 90				
C0053	**M**	6786 - 6786	**DI**	**05019** (5 m - 72 W)
	W	7127 - 7127		
	N	7189 - 7189		

Electronics: **AL** (pag 399) | Accessories (pag 398) | Linear profile (pag 400)

Silicone | 160 LED/m | topLED | 24 V DC | 12 W/m







	Cct	lm S - lm D	Opt	L
CRI 85				
C0054	**M**	7320 - 7320	**DI**	**05019** (5 m - 60 W)
	W	7782 - 7782		
	N	8266 - 8266		

Electronics: **AL** (pag 399) | Accessories (pag 398) | Linear profile (pag 400)

Silicone | 130 LED/m | topLED | 48 V DC | 13,8 W/m





	Cct	lm S - lm D	Opt	L
CRI 90				
C0055	**M**	18596 - 18596	**DI**	**15030** (15 m - 207 W)
	W	19796 - 19796		
	N	21440 - 21440		


Electronics: **EK** (pag 399) | Accessories (pag 398) | Linear profile (pag 400)


Finishes White

Cct **M** 2700 **N** 4000 **W** 3000

IP66

PU_C Plus | 70 LED/m | topLED | 24 V DC | 3,2 W/m







		Cct	lm S - lm D	Opt	L
CRI 90					
C0018		**M**	1424 - 1424	**DI**	**05019** (5 m - 16 W)
		W	1550 - 1550		
		N	1628 - 1628		

Electronics: **AL** (pag 399) | Accessories (pag 398) | Linear profile (pag 400)

PU_C Plus | 140 LED/m | topLED | 24 V DC | 7,2 W/m







		Cct	lm S - lm D	Opt	L
CRI 90					
C0019		**M**	3040 - 3040	**DI**	**05019** (5 m - 36 W)
		W	3314 - 3314		
		N	3458 - 3458		

Electronics: **AL** (pag 399) | Accessories (pag 398) | Linear profile (pag 400)

PU_C Plus | 70 LED/m | topLED | 24 V DC | 12,5 W/m







		Cct	lm S - lm D	Opt	L
CRI 90					
C0025		**M**	5941 - 5941	**DI**	**05019** (5 m - 62,5 W)
		W	6334 - 6334		
		N	6873 - 6873		

Electronics: **AL** (pag 399) | Accessories (pag 398) | Linear profile (pag 400)

PU_C Plus | 140 LED/m | topLED | 24 V DC | 25 W/m







		Cct	lm S - lm D	Opt	L
CRI 90					
C0026		**M**	11942 - 11942	**DI**	**05019** (5 m - 125 W)
		W	11731 - 11731		
		N	12264 - 12264		

Electronics: **AL** (pag 399) | Accessories (pag 398) | Linear profile (pag 400)

PU_C Plus RGBW | 60+60 LED/m | topLED | 24 V DC | 19,2 W/m






		Cct	lm S - lm D	Opt	L
CRI 90					
C0025		**V**	RBGW (3000 K)	**DI**	**05019** (5 m - 96 W)

Electronics: **AM7** (pag 399) | Accessories (pag 398) | Linear profile (pag 400)

Cables and connectors

Connector | Strip-strip connector 8mm




TR **83396**

connector: 2 poles
protection: IP20

suitable for: Ribbon Plus 70, 140 LED/m
Ribbon 60, 120, 160 LED/m

Connector | Strip-strip connector 10mm




TR **83398**

connector: 2 poles
protection: IP20

suitable for: Ribbon Pro 80,128, 136, 160 LED/m
Ribbon Plus Warm Tune - Ribbon 160 LED/m

Connector | Strip-strip connector 10mm




TR **83400**

connector: 3 poles
protection: IP20

suitable for: Ribbon Plus Dynamic White

Connector | Strip-strip connector 10mm



TR **83402**

connector: 5 poles
protection: IP20

suitable for: Ribbon Plus RGBW

Connector | Strip-strip connector 10mm




TR **C-W400001**

connector: 2 poles
protection: IP20

suitable for: Ribbon 168, 238 LED/m

Connector | Strip-strip or cable-strip connector 8mm Cob



TR **C-W400003**
(cables not included)

connector: 2 poles
protection: IP20

suitable for: Ribbon Cob

Connector | Cable-strip connector 8mm



TR **83397**
(cables not included)

connector: 2 poles
protection: IP20

suitable for: Ribbon Plus 70, 140 LED/m
Ribbon 60, 120, 160 LED/m

Connector | Cable-strip connector 10mm




TR **83399**
(cables not included)

connector: 2 poles
protection: IP20

suitable for: Ribbon Pro 80,128, 136, 160 LED/m
Ribbon Plus Warm Tune - Ribbon 160 LED/m

Connector | Cable-strip connector 10mm




TR **83401**
(cables not included)

connector: 3 poles
protection: IP20

suitable for: Ribbon Plus Dynamic White

Connector | Cable-strip connector 10mm




TR **83403**
(cables not included)

connector: 5 poles
protection: IP20

suitable for: Ribbon Plus RGBW

Connector | Cable-strip connector 10mm




TR **C-W400002**

connector: 2 poles
protection: IP20

suitable for: Ribbon 168, 238 LED/m

Accessories

PU_C Plus | Fixing kit




TR **98964**

1 x glue
20 x brackets
40 x M3x25 screws
10 x caps

suitable for: 5 m PU_C Plus

Silicone | Fixing kit




TR **C-V400002**

1 x glue
10 x caps

suitable for: 5 m Silicone

PU_C Plus - Silicone | Fixing brackets



TR **89223**

10 x brackets
20 x M3x25 screws

suitable for: 5 m PU_C Plus, Silicone

Electronics

AL

99374
ON/OFF
75W
210 x 49 x h 25
56

99331
ON/OFF
150W
158 x 60 x h 35
70

99332
0/1-10V
150W
158 x 60 x h 35
70

83333
DALI/PUSH
150W
188 x 68 x h 34
77

C-E400002
DALI/PUSH
240W
188 x 68 x h 34
77

EK

99784
ON/OFF
150W CV 48V
219 x 63 x h 35
80

99785
ON/OFF
240W CV 48V
244 x 71 x h 38
81

C-E400003
DALI/PUSH
150W CV 48V
188 x 68 x h 34
77

Switching
CV 48V
Pag. 945-946

83177
Dimmer DMX
312W
97 x 36 x h 62

AM7

C-E700002+C-W600001
Dimmer RF
52 x 52 x h 26
53

99331
CV 24V
150 W
158 x 60 x h 35
70

C-E700005
Dimmer DMX

DMX
Controllers
Pag. 963

99331
CV 24V
150 W
158 x 60 x h 35
70



FABIO CARS SRL
Caltagirone - Sicily (Italy)

Project:
Studio3000 Architettura e Design

Designer:
Arch. Marco Scebba

Design collaborator:
Arch. Nunzio Andrea Zago

Photography:
Davide e Umberto Di Pasquale & figli Fotografi


Finishes

TR Transparent

PROFILE RANGE


Surface

Svik_00/00
pag 407



Finishes profile
- AM Aluminium


Alise_10/10
pag 407



Finishes profile
- AM Aluminium

Finishes diffuser
- OP Opaline


Fonis_06/11
pag 407



Finishes profile
- AM Aluminium

Finishes diffuser
- TR Transparent
- TN Satinized
- OP Opaline


Rive_17/16
pag 405



Finishes profile
- AM Aluminium
- BB Black

Finishes diffuser
- TR Transparent
- TN Satinized
- OP Opaline
- BB Black

Vojo_17/08
pag 404




Finishes profile
- AM Aluminium
- BB Black

Finishes diffuser
- TR Transparent
- TN Satinized
- OP Opaline
- BB Black

Recessed
Tiles

Tabulo_35/14
pag 406




Finishes profile
- AM Aluminium

Finishes diffuser
- OP Opaline

Recessed
Bricks

Armita_58/15
pag 406




Finishes profile
- AM Aluminium

Finishes diffuser
- OP Opaline

Recessed
Wood


Roko_33/15
pag 406



Finishes profile
- AM Aluminium

Finishes diffuser
- TR Transparent
- TN Satinized
- OP Opaline


Vojo_17/08
pag 404



Finishes profile
- AM Aluminium

Finishes diffuser
- TN Satinized


Ozner_25/10
pag 407



Finishes profile
- AM Aluminium

Finishes diffuser
- TR Transparent


Luno_20/27
pag 404



Finishes profile
- AM Aluminium
- BB Black

Finishes diffuser
- OP Opaline
- BB Black


Luno_20/27
pag 405



Finishes profile
- AM Aluminium
- BB Black

Finishes diffuser
- OP Opaline
- BB Black

Cela_18/18
pag 407




Finishes profile
- AM Aluminium
- BB Black

Finishes diffuser
- TR Transparent
- TN Satinized
- OP Opaline
- BB Black

Recessed
Plasterboard


Sageto_24/08
pag 405



Finishes profile
- AM Aluminium

Finishes diffuser
- TR Transparent
- TN Satinized
- OP Opaline


Ghost_64/14
pag 406



Finishes profile
- AM Aluminium

Finishes diffuser
- TR Transparent
- TN Satinized
- OP Opaline

Rialt_55/70
pag 406



Finishes profile
- AM Aluminium

Finishes diffuser
- OP Opaline


ON REQUEST

Tailor-made lighting: precision cuts for unique projects.

Linea Light Group introduces a new custom cutting service dedicated to the i-LèD profiles from the Flex Light section, designed to offer highly customized lighting solutions, perfectly calibrated for every design need. Customization becomes simple: after choosing the profile model, diffuser, and ideal length, you can combine the lighting units from the Ribbon, Ribbon PRO, and Ribbon Plus collections to create unique, ready-to-use linear solutions. Each fixture is made with quality materials and technologies, ensuring extraordinary lighting performance and maximum installation versatility.



1.
Select the profile and accessories



2.
Select the strip



3.
Specify the dimensions and cable position



4.
The fixture is ready for installation




Waste optimization for efficient sustainability.

Why choose the custom service?

- Maximum customization and adaptability for any type of project.
- Tailor-made, complete, and ready-to-use fixtures.
- Reduced costs and faster installation.

To create your custom project, contact your local Linea Light Group representative.



Profiles: where is the difference





TR Transparent polycarbonate


TN Satinized polycarbonate

OP Opaline polycarbonate

Vojo_17/08 | Low surface profile









AM	**98891**	1 x	Profile
BB	**83129**	1 x	Profile
TR	**98941**	1 x	Diffuser
TN	**98942**	1 x	Diffuser
OP	**98943**	1 x	Diffuser
BB	**83132**	1 x	Diffuser
TR	**C-U100001**	1 x	Diffuser (Optic 30/50°)
OP	**C-K200005**	1 x	Diffuser 3D square
OP	**C-K200007**	1 x	Diffuser 3D round
GG	**98892**	2 x	Caps
BB	**83133**	2 x	Caps
GG	**C-V400023**	2 x	Caps (for diffuser optic 30/50°)
BB	**C-V400024**	2 x	Caps (for diffuser optic 30/50°)
GG	**C-V400027**	2 x	Caps (for diffuser 3D square)
GG	**C-V400029**	2 x	Caps (for diffuser 3D round)
	98944	5 x	Brackets
KIT composition			
	98954	1 x	98891-98943-98892-98944
KIT composition Black			
	84446	1 x	83129-83132-83133-98944

Compatible with: Ribbon PRO - Ribbon Plus - Ribbon (not for 48V) - Silicone (only 10mm)

Vojo_17/08 | Low surface profile







AM	**98891**	1 x	Profile
TN	**98925**	1 x	Diffuser (Optic 90°)
GG	**98928**	2 x	Caps
	98944	5 x	Brackets
KIT composition			
	99983	1 x	98891-98925-98928-98944

Compatible with: Ribbon PRO - Ribbon Plus - Ribbon (not for 48V) - Silicone (only 10mm)

Luno_20/27 | High square surface profile






AM	**C-K100017**	1 x	Profile
BB	**C-K100018**	1 x	Profile
OP	**C-K200001**	1 x	Diffuser
BB	**C-K200002**	1 x	Diffuser
GG	**C-V400019**	2 x	Caps
BB	**C-V400020**	2 x	Caps
	98931	5 x	Brackets

Compatible with: Ribbon PRO - Ribbon Plus - Ribbon - PU_C Plus - Silicone

Luno_20/27 | High round surface profile








AM	**C-K100017**	1 x	Profile
BB	**C-K100018**	1 x	Profile
OP	**C-K200003**	1 x	Diffuser
BB	**C-K200004**	1 x	Diffuser
GG	**C-V400021**	2 x	Caps
BB	**C-V400022**	2 x	Caps
	98931	5 x	Brackets

Compatible with: Ribbon PRO - Ribbon Plus - Ribbon - PU_C Plus - Silicone

Rive_17/16 | High surface profile









AM	**C-K100015**	1 x	Profile
BB	**C-K100016**	1 x	Profile
TR	**98941**	1 x	Diffuser
TN	**98942**	1 x	Diffuser
OP	**98943**	1 x	Diffuser
BB	**83132**	1 x	Diffuser
TR	**C-U100001**	1 x	Diffuser (Optic 30/50°)
OP	**C-K200005**	1 x	Diffuser 3D square
OP	**C-K200007**	1 x	Diffuser 3D round
GG	**C-V400035**	2 x	Caps
BB	**C-V400036**	2 x	Caps
GG	**C-V400025**	2 x	Caps (for diffuser optic 30/50°)
BB	**C-V400026**	2 x	Caps (for diffuser optic 30/50°)
GG	**C-V400031**	2 x	Caps (for diffuser 3D square)
GG	**C-V400033**	2 x	Caps (for diffuser 3D round)
	98944	5 x	Brackets
KIT composition			
	C-K100026	1 x	C-K100015 -98943- C-V400035 -98944
KIT composition Black			
	C-K100027	1 x	C-K100016 -83132- C-V400036 -98944

Compatible with: Ribbon PRO - Ribbon Plus - Ribbon (not for 48V) - Silicone (only 10mm)

Sageto_24/08 | Low recessed profile








AM	**98895**	1 x	Profile
TR	**98941**	1 x	Diffuser
TN	**98942**	1 x	Diffuser
OP	**98943**	1 x	Diffuser
TR	**C-U100001**	1 x	Diffuser (Optic 30/50°)
GG	**98896**	2 x	Caps
GG	**C-V400023**	2 x	Caps (for diffuser optic 30/50°)
	98944	5 x	Brackets
KIT composition			
	98965	1 x	98895-98943-98896-98944


Compatible with: Ribbon PRO - Ribbon Plus - Ribbon (not for 48V)

Finishes

BB Black
AM Anodised Aluminium
GG Grey
OP Opaline
TR Transparent
TN Satinized

Roko_33/15 | Low recessed profile







AM	98897	1 x	Profile
TR	98898	1 x	Diffuser
TN	98899	1 x	Diffuser
OP	98900	1 x	Diffuser
GG	98902	2 x	Caps
	98901	5 x	Brackets

Compatible with: Ribbon PRO - Ribbon Plus - Ribbon - PU_C Plus - Silicone

Ghost_64/14 | Low recessed profile







AM	98906	1 x	Profile
TR	98898	1 x	Diffuser
TN	98899	1 x	Diffuser
OP	98900	1 x	Diffuser
GG	98907	2 x	Caps

Compatible with: Ribbon PRO - Ribbon Plus - Ribbon - PU_C Plus - Silicone

Armita_58/15 | Integrated linear profile






AM	98916	1 x	Profile
OP	98917	1 x	Diffuser
GG	98918	2 x	Caps

Compatible with: Ribbon PRO - Ribbon Plus - Ribbon (not for 48V) - Silicone (only 10mm)

Tabulo_35/14 | Integrated side profile







AM	98921	1 x	Profile
OP	98917	1 x	Diffuser
GG	98922	2 x	Caps

Compatible with: Ribbon PRO - Ribbon Plus - Ribbon (not for 48V)

Rialt_55/70 | Integrated side profile






AM	C-K100025	1 x	Profile
OP	C-K200009	1 x	Diffuser
GG	C-V400041	2 x	Caps


Compatible with: Ribbon PRO - Ribbon Plus - Ribbon - PU_C Plus - Silicone

Finishes

AM Anodised Aluminium
GG Grey
TR Transparent
OP Opaline
TN Satinized

Alise_10/10 | Square slim surface profile






AM	**98912**	1 x	Profile
OP	**98913**	1 x	Diffuser
GG	**98915**	2 x	Caps
	98914	5 x	Brackets

Compatible with: Ribbon Slim

Fonis_06/11 | Low slim surface profile






AM	**98885**	1 x	Profile
TR	**98886**	1 x	Diffuser
TN	**98887**	1 x	Diffuser
OP	**98888**	1 x	Diffuser
GG	**98890**	2 x	Caps
	83224	5 x	Brackets

Compatible with: Ribbon Slim

Ozner_25/10 | Low surface profile







AM	**98419**	1 x	Profile
OP	**98395**	1 x	Diffuser
GG	**98418**	2 x	Caps
	98420	5 x	Brackets

Compatible with: Ribbon Pro - Ribbon Plus - Ribbon - PU_C Plus - Silicone

Svik_00/00 | Heat sink







AM	**98956**	1 x	Heat sink

Compatible with: Ribbon Pro - Ribbon Plus - Ribbon - PU_C Plus - Silicone (not for 48V)

Cela_18/18 | Corner profile






AM	**C-K100019**	1 x	Profile
BB	**C-K100020**	1 x	Profile
TR	**98941**	1 x	Diffuser
TN	**98942**	1 x	Diffuser
OP	**98943**	1 x	Diffuser
BB	**83132**	1 x	Diffuser
GG	**C-V400037**	2 x	Caps
BB	**C-V400038**	2 x	Caps
	98904	5 x	Brackets
KIT composition			
	C-K100028	1 x	C-K100019-98943- C-V400037 -98904
KIT composition Black			
	C-K100029	1 x	C-K100020-83132- C-V400038 -98904

Compatible with: Ribbon PRO - Ribbon Plus - Ribbon (not for 48V) - Silicone (only 10mm)

RUBBER RANGE

Made in Italy

3 years warranty



Rubber_O 48V	
White finish	
pag 424	
W/m	12
Lm/m	1538 → 1770
m	2,5-5-10
CRI	90
R9	>50
Cct (K)	2700-3000 4000
IP	65
Opt	Diffused

Rubber 3D **Rubber 3D** 48V	
White finish	
pag 412-413	
W/m	5 → 16
Lm/m	412 → 1736
m	1-5-10
CRI	90
R9	>50
Cct (K)	2200-2700-3000 3500-4000 DW 2000 → 6000
IP	67
Opt	Diffused

Rubber 3D Concrete	
Concrete finish	
pag 412	
W/m	9,6
Lm/m	274
m	1-5-10
CRI	90
R9	-
Cct (K)	3000
IP	67
Opt	Diffused

Rubber 3D **RGBW** **RGBW** 48V	
White finish	
pag 412-413	
W/m	15
Lm/m	-
m	1-5-10
CRI	90
R9	-
Cct (K)	RGBW
IP	67
Opt	Diffused

Rubber 3D **PIXEL** **RGBW**	
White finish	
pag 417	
W/m	13,2
Lm/m	-
m	0,5-1-5
CRI	90
R9	>50
Cct (K)	RGBW
IP	67
Opt	Diffused



RUBBER
TM66
RESULT 1.9

Rubber 3D PROtection

White finish
pag 418

W/m	9,6
Lm/m	627 → 715
m	1-5-10
CRI	90
R9	>50
Cct (K)	2700-3000 3500-4000
IP	68
Opt	Diffused

Rubber 3D PROtection RGBW

White finish
pag 418

W/m	15
Lm/m	-
m	1-5
CRI	90
R9	-
Cct (K)	RGBW
IP	68
Opt	Diffused

Rubber 3D Optics

White finish
pag 416

W/m	19,5
Lm/m	1576 → 1854
m	1-3-5
CRI	90
UGR	-
Cct (K)	2200-2700 3000-3500 4000
IP	67
Opt	Flood-M.Flood

Rubber 3D Optics


Black finish
pag 416

W/m	19,5
Lm/m	1345 → 1576
m	1-3-5
CRI	90
UGR	-
Cct (K)	2200-2700 3000-3500 4000
IP	67
Opt	Flood-M.Flood

Rubber 2D Mini

White finish
pag 411

W/m	6
Lm/m	157 → 226
m	1-5-10
CRI	90
R9	>50
Cct (K)	2200-2700 3000-3500 4000
IP	67
Opt	Diffused



RUBBER 2D MINI

Minimum curvature radius: 150 mm


RUBBER 3D

Minimum curvature radius: 250 mm


2D | 6mm | R9 >50


Rubber 2D_mini

Like the standard 14 mm model, the Mini version is also an ideal solution for curves and reverse curves that demand bending on a single axis, combining flexible installation with high performance. IP67 certified, it differs from any other Rubber with its extremely reduced dimensions. Rubber 2D Mini packs in just 6mm a custom designed circuit that allows extremely high performance to be achieved with very thin light for discrete and elegant linear effects. Just like the internal electronics, the accessories, clips and profiles are also specifically designed for the minimum bulk of the strip.



Rubber 2D_mini | V3 | LED strip | 24 V DC





Made in Italy | C.V. | R9 >50 | IP67 | NEW

		Cct	lm S/m - lm D/m	Opt	L
CRI 90 - 6W/m					
C0057		**A**	515 - On req	**DI**	**01004** (1 m - 6 W)
		M	624 - On req		**05004** (5 m - 30 W)
		W	685 - On req		**10004** (10 m - 60 W)
		T	724 - On req		
		N	754 - On req		

Electronics: **AL** (pag 411) | Accessories and cables (pag 430-433)



Electronics


AL


99374	**99331**	**99332**	**83333**	**C-E400002**
ON/OFF	ON/OFF	0/1-10V	DALI/PUSH	DALI/PUSH
75W	150W	150W	150W	240W
210 x 49 x h 25	158 x 60 x h 35	158 x 60 x h 35	188 x 68 x h 34	188 x 68 x h 34
56	70	70	77	77

Finishes White

Cct **A** 2200 **M** 2700 **W** 3000 **T** 3500 **N** 4000

Rubber 3D | V3 | LED strip | 24 V DC





Cct		Im S/m - Im D/m	Opt	L
CRI 90 - 5 W/m				
C0013	**A**	412 - On req	**DI**	**01004** (1 m - 5 W)
	M	499 - On req		**05004** (5 m - 25 W)
	W	530 - On req		**10004** (10 m - 50 W)
	T	579 - On req		
	N	603 - On req		

Electronics: **AL** (pag 413) | Accessories and cables (pag 430-433)

Cct		Im S/m - Im D/m	Opt	L
CRI 90 - 9,6 W/m				
C0014	**A**	824 - On req	**DI**	**01004** (1 m - 9,6 W)
	M	998 - On req		**05004** (5 m - 48 W)
	W	1096 - On req		**10004** (10 m - 96 W)
	T	1158 - On req		
	N	1206 - On req		

Electronics: **AL** (pag 413) | Accessories and cables (pag 430-433)

Cct		Im S/m - Im D/m	Opt	L
CRI 90 - 14,4 W/m				
C0015	**A**	1186 - On req	**DI**	**01004** (1 m - 14,4 W)
	M	1437 - On req		**05004** (5 m - 72 W)
	W	1526 - On req		**10004** (10 m - 144 W)
	T	1667 - On req		
	N	1736 - On req		

Electronics: **AL** (pag 413) | Accessories and cables (pag 430-433)

Cct			Opt	L
CRI 90 - 16 W/m				
C0014	**D**	Dynamic White 2000-6000 K	**DI**	**01004** (1 m - 16 W)
				05004 (5 m - 80 W)

For power supply/control contact
Linea Light support service


Electronics: **AM7** (pag 413) | Accessories and cables (pag 430-433)


Cct			Opt	L
CRI 90 - 15 W/m				
C0014	**V**	RBGW (3000 K)	**DI**	**01004** (1 m - 15 W)
				05004 (5 m - 75 W)

For power supply/control contact
Linea Light support service

Electronics: **AM7** (pag 413) | Accessories and cables (pag 430-433)

Rubber 3D | Concrete | V3 | LED strip | 24 V DC







Cct		Im S/m - Im D/m	Opt	L
CRI 90 - 9,6 W/m				
C0017	**W**	274 - On req	**DI**	**01004** (1 m - 9,6 W)
				05004 (5 m - 48 W)
				10004 (10 m - 96 W)

Electronics: **AL** (pag 413) | Accessories and cables (pag 430-433)

Rubber 3D | V3 | LED strip | 48 V DC





Made in Italy | C.V. | R9 >50 | IP67 | NEW | 48V

	Cct	lm S/m - lm D/m	Opt	L
CRI 90 - 9,6 W/m				
C0016	**A**	858 - On req	**DI**	**01004** (1 m - 10 W)
	M	1040 - On req		**05004** (5 m - 50 W)
	W	1142 - On req		**10004** (10 m - 100 W)
	T	1206 - On req		
	N	1256 - On req		

Electronics: **EK** (pag 413) | Accessories and cables (pag 430-433)

Made in Italy | C.V. | IP67 | NEW | 48V +RGBW

	Cct		Opt	L
CRI 90 - 15 W/m				
C0016	**V**	RBGW (3000 K)	**DI**	**01004** (1 m - 15 W)
				05004 (5 m - 75 W)
				10004 (10 m - 150 W)

For power supply/control contact
Linea Light support service

Electronics: **EH** (pag 413) | Accessories and cables (pag 430-433)

48V

The main characteristic that Linea Light Group introduces through the Rubber 3D 48V units is the ability to increase the usable section even on projects where significant lengths are foreseen. Thereby simplifying planning and installation.

Electronics

AL

99374	**99331**	**99332**	**83333**	**C-E400002**
ON/OFF	ON/OFF	0/1-10V	DALI/PUSH	DALI/PUSH
75W	150W	150W	150W	240W
210 x 49 x h 25	158 x 60 x h 35	158 x 60 x h 35	188 x 68 x h 34	188 x 68 x h 34
56	70	70	77	77

AM7

C-E700002+C-W600001	**99331**	**C-E700005**	**DMX**	**99331**
Dimmer RF	CV 24V	Dimmer DMX	Controllers	CV 24V
	150 W			150 W
52 x 52 x h 26	158 x 60 x h 35		Pag. 963	158 x 60 x h 35
53	70			70


EH

99784	**99785**	**C-E700002+C-W600001**	**Switching**	**83178**
ON/OFF	ON/OFF	Dimmer RF	CV 48V	Dimmer DMX
150W CV 48V	240W CV 48V	CV 48V		384W
219 x 63 x h 35	244 x 71 x h 38	52 x 52 x h 26	Pag. 945-946	97 x 71 x h 62
80	81	53		

EK

99784	**99785**	**C-E400003**	**Switching**	**83177**
ON/OFF	ON/OFF	DALI/PUSH	CV 48V	Dimmer DMX
150W CV 48V	240W CV 48V	150W CV 48V		312W
219 x 63 x h 35	244 x 71 x h 38	188 x 68 x h 34	Pag. 945-946	97 x 36 x h 62
80	81	77		








The restyling project of the Montefeltro Office Village complex in Milan used light as a characterising element of its façades. The ability of the Rubber 3D LED strip to play with three-dimensionality has made it possible to give the building an image of robustness.


MONTEFELTRO OFFICE VILLAGE
Milan (Italy)

Project: Stefano Giubileo, Gregg Brodarick, Andrea Bianchi, Fabio Crespi

Photography:
Marco Reggi

Rubber 3D Optics | V2 | LED strip | 24 V DC






	Cct	lm S/m - lm D/m	Opt	L
CRI 90 - 19,5W/m				
C0010	**A**	1691 - 1576	**FL**	**01004** (1,004 m - 19,5W)
C0011	**M**	1799 - 1677	**ML**	**03004** (3,004 m - 58,5W)
	W	1874 - 1747		**05004** (5,004 m - 97,5 W)
	T	1817 - 1694		
	N	1989 - 1854		

FL Flood (24°) | **ML** M. Flood (37°)

Electronics: **AL** (pag 416) | Accessories and cables (pag 430-433)





Electronics

AL

99374	**99331**	**99332**	**83333**	**C-E400002**
ON/OFF	ON/OFF	0/1-10V	DALI/PUSH	DALI/PUSH
75W	150W	150W	150W	240W
210 x 49 x h 25	158 x 60 x h 35	158 x 60 x h 35	188 x 68 x h 34	188 x 68 x h 34
56	70	70	77	77


Finishes


WH White
BB Black

Cct

A 2200 **W** 3000 **N** 4000
M 2700 **T** 3500

Rubber 3D PIXEL RGBW | LED strip | 24 V DC





Cct			Opt	L	
CRI 90 - 13,2W/m					
C0056	**V**	RBGW (3000 K)	**DI**	**00504**	(0,5 m - 6,6 W)
				01004	(1 m - 13,2 W)
				05004	(5 m - 66 W)

Two connectors for 500 mm length

For power supply/control contact
Linea Light support service

Electronics: **AM11** (pag 417) | Accessories and cables (pag 417, 430-433)

Accessories and cables

Cable with connector



PVC **99688** Conn. F 2x 0,25 - 2000 mm
PVC **99689** Conn. M 2x 0,25 - 2000 mm
suitable for: Rubber 3D PIXEL RGBW

Cable SPI with connector PIXEL



GG **82850** Conn. F 2x 0,5 - 2000 mm
GG **82851** Conn. M 2x 0,5 - 2000 mm
suitable for: Rubber 3D PIXEL RGBW

PIXEL Transmitter Box with SPI male cable



GG **82857**

suitable for: Rubber 3D PIXEL RGBW

PIXEL Receiver Box with SPI female cable



GG **99519**

suitable for: Rubber 3D PIXEL RGBW

T-cable with connectors



BB **83387**

suitable for: Rubber 3D PIXEL RGBW

Electronics


AM11


99786	**82852/82853**	**82856**	**99519**	**C-E700004**
ON/OFF 240W 244 x 71 x h 38 81	ARTNET/SPI Controllers	Transmitter	Receiver	Easy Pixel Controller + TLC

Finishes
WH White
GG Grey
BB Black

Cct
V RGBW (3000)

Rubber 3D PROtection | V3 | LED strip | 24 V DC





10 m | max 3 m

	Cct	lm S/m - lm D/m	Opt	L
CRI 90 - 9,6 W/m				
C0012	**M**	998 - On req	**DI**	**01004** (1 m - 9,6 W)
	W	1096 - On req		**05004** (5 m - 48 W)
	T	1158 - On req		**10004** (10 m - 96 W)
	N	1206 - On req		

Electronics: **AL** (pag 418) | Accessories (pag 432-433)

10 m | max 3 m

	Cct		Opt	L
CRI 90 - 15 W/m				
C0012	**V**	RBGW (3000 K)	**DI**	**01004** (1 m - 15 W)
				05004 (5 m - 75 W)

For power supply/control contact
Linea Light support service

Electronics: **AM7** (pag 418) | Accessories (pag 432-433)



Electronics

AL

99374	**99331**	**99332**	**83333**	**C-E400002**
ON/OFF	ON/OFF	0/1-10V	DALI/PUSH	DALI/PUSH
75W	150W	150W	150W	240W
210 x 49 x h 25	158 x 60 x h 35	158 x 60 x h 35	188 x 68 x h 34	188 x 68 x h 34
56	70	70	77	77

AM7

C-E700002+C-W600001	**99331**	**C-E700005**	**DMX**	**99331**
Dimmer RF	CV 24V	Dimmer DMX	Controllers	CV 24V
	150 W			150 W
52 x 52 x h 26	158 x 60 x h 35		Pag. 963	158 x 60 x h 35
53	70			70

Finishes White

Cct **M** 2700 **T** 3500 **V** RGBW (3000) **W** 3000 **N** 4000



HOTEL SOFITEL BARCELONA
Barcelona (Spain)

Lighting design:
Fantastico Lighting Partners + Autentico Architectural Lighting Design

Photography:
Jordi Anguera





RUBBER_O


360° OF TOTAL BRIGHTNESS AND FLEXIBILITY.

NEW | 3D | R9 >50 | 48V


Rubber_O redefines the lighting experience. Mouldable in any direction, it offers a homogeneous 360-degree diffused light. Made with a special highly flexible material, this device allows the creation of unique and scenographic installations. Its versatility allows you to shape the light according to your creative vision, ensuring a stunning impact. With Rubber_O, form meets function to integrate into any type of project, in any type of architecture. The extraordinary ability to adapt to surfaces of any geometry and size represents a unique opportunity to create dynamic and engaging light compositions.








To express the creative potential of Rubber_O to the fullest, we have created a wide range of accessories. The great ease of installation allows scenographic compositions with wall, ceiling and suspension fixings.








Rubber_O | topLED | 48 V DC





48V

	Cct	Im S/m - Im D/m	Opt	L
CRI 90 - 12W/m				
C0020	**M**	1538 - 1150	**DI**	**02517** (2,5 m - 30 W)
	W	1654 - 1256		**05017** (5 m - 60 W)
	N	1770 - 1284		**10017** (10 m - 120 W)


Electronics: **EK** (pag 424) | Accessories (pag 424-426)

48V

The main characteristic that Linea Light Group introduces through the Rubber_O (48V) units is the ability to increase the usable section even on projects where significant lengths are foreseen. Thereby simplifying planning and installation.

Accessories


Rubber_O | End cap kit



WH **C-K400076** Kit 5 round Rubber_O caps Ø 30 mm

suitable for: Rubber_O

Rubber_O | End cap + cable kit



WH **C-K400077** Kit 1 round Rubber_O cap Ø 30 mm + cable 2 poles

suitable for: Rubber_O

Rubber_O | Fixing kit



TR **C-K400080** Silicone glue for sealing

suitable for: Rubber_O


Electronics


EK

99784	**99785**	**C-E400003**	**Switching**	**83177**
ON/OFF	ON/OFF	DALI/PUSH	CV 48V	Dimmer DMX
150W CV 48V	240W CV 48V	150W CV 48V		312W
219 x 63 x h 35	244 x 71 x h 38	188 x 68 x h 34	Pag. 945-946	97 x 36 x h 62
80	81	77		



Rubber_O | Suspension accessory






NEW

WH **C-W500001** 1 x ring + steel cable

Rubber_O | Wall clip






NEW

TR **C-F400005** 1 x wall clip + 3 x screws

Rubber_O | 1/2-way connector






NEW

WH **C-F300001**
BB **C-F300002**

Rubber_O | 1/2-way connector + on/off driver






C.V. IP20 NEW

WH **C-F300003** 48 V DC - 60W max
BB **C-F300004** 48 V DC - 60W max

Rubber_O | 1/2-way connector + on/off driver






C.V. IP20 NEW

WH **C-F300009** 48 V DC - 120W max
BB **C-F300010** 48 V DC - 120W max

Rubber_O | Ceiling connector






NEW

WH **C-F300005**
BB **C-F300006**

Rubber_O | Ceiling connector + on/off driver






C.V. IP20 NEW

WH **C-F300007** 48 V DC - 60W max
BB **C-F300008** 48 V DC - 60W max

Finishes


WH White TR Transparent
BB Black

With Rubber_O accessories, connections become quick and easy.




Application examples


Symmetrical or asymmetrical, concentrically converging or diverging cascades.
Discover some installation examples with Rubber_O and dedicated accessories.




01 C-F300003 x 1 pz
02 C-F400005 x 2 pz
03 C-F300001 x 1 pz
04 C-F300005 x 1 pz



02 C-F400005 x 6 pz
04 C-F300005 x 6 pz
06 Driver remote



01 C-F300001 x 2 pz
02 C-F400005 x 2 pz
04 C-F300005 x 1 pz
05 C-W500001 x 3 pz
06 Driver remote



01 C-F300007 x 5 pz
04 C-F300005 x 5 pz


MAX 5 m
Maximum length allowed for "U" configurations.



Flexible antiglare shade (C-K100032)
+ Clip (C-F400002)
+ Rubber 3D

Spike with bracket (83351)
+ Clip (C-F400002)
+ Rubber 3D






Tilting bracket

It allows an accurate adjustment, ensuring maximum flexibility in directing the light according to specific needs. To be combined with the appropriate clips or Rubber 3D linear profiles.


Spike with bracket

The spike on allows you to anchor clips and Rubber 3D linear profiles, allowing the creation of appealing lighting effects grazing the ground or engaging uplight effects.





Installation examples




Grazing light installation



Uplight installation


Accessories: Rubber 2D Mini

Linear profile



AM **82846** 1000 mm - 20 mm - 10 mm
AM **82202** 2000 mm - 20 mm - 10 mm
suitable for: Rubber 2D Mini


Clip with toothed spring



AM **82847** 50 mm - 20 mm - 10 mm
suitable for: Rubber 2D Mini


Accessories: Rubber 3D

Linear profile




AM **99549** 1000 mm - 18 mm - 19 mm
AM **82198** 2000 mm - 18 mm - 19 mm
AK **C-K100007** 1000 mm - 18 mm - 19 mm
AK **C-K100008** 2000 mm - 18 mm - 19 mm
suitable for: Rubber 3D (Not for 3D PROtection)

Linear profile with cable run




AM **83034** 1000 mm - 39 mm - 19 mm
AM **82199** 2000 mm - 39 mm - 19 mm
AK **C-K100009** 1000 mm - 39 mm - 19 mm
AK **C-K100010** 2000 mm - 39 mm - 19 mm
suitable for: Rubber 3D (Not for 3D PROtection)

Clip with toothed spring




AM **C-F400001** 50 mm - 23 mm - 21 mm
AK **C-F400002**
suitable for: Rubber 3D (Not for 3D PROtection)

Clip with toothed spring with cable run



AM **C-F400003** 50 mm - 41 mm - 21 mm
AK **C-F400004**
suitable for: Rubber 3D (Not for 3D PROtection)


Flexible profile



IS **C-K100011** 1007 mm - 13 mm - 16 mm

suitable for: Rubber 3D

Flexible antiglare shade




IS **C-K100032** 2035 mm - 80 mm - 34 mm

suitable for: Rubber 3D

To be completed with linear profile or clip.

Tilting bracket




TR **83352**

suitable for: Rubber 3D (Not for 3D PROtection)

To be completed with linear profile or clip.


Steel tilting bracket



IS **C-K400168** L 50 mm - 42 mm - 28 mm
IS **C-K400169** L 100 mm - 42 mm - 28 mm
suitable for: Rubber 3D

To be completed with linear profile or clip.

Spike with bracket



IS **83351**

suitable for: Rubber 3D (Not for 3D PROtection)

To be completed with linear profile or clip.

Peg with steel tilting bracket



IS **C-F500004** L 50 mm
IS **C-F500005** L 100 mm
suitable for: Rubber 3D (Not for 3D PROtection)


To be completed with linear profile or clip.

Cap kits



TR **99539** Rubber (not for Rubber_O, Rubber 2D Mini).
TR **99538** Rubber 2D Mini

Rubber profile drilling template




AM **C-V200005** 25 mm - 20 mm - 34 mm hole Ø 13,2
suitable for: Linear profile Rubber 3D

Finishes

AM Anodised Aluminium
AK Anodised Black Aluminium
IS Steel
TR Transparent


Rubber 3D fixing profile for Track System



TR **C-K100022** 100 mm - 27 mm - 15 mm

suitable for: Rubber 3D


Rubber 3D fixing profile for Track System



TR **C-K100021** 2000 mm - 27 mm - 15 mm

suitable for: Rubber 3D

Track System power supply for Rubber 3D




WH **C-E300007** On/Off - Max 50W DC - IP20

BB **C-E300008** On/Off - Max 50W DC - IP20

suitable for: Rubber 3D (Not for 3D PROtection)

Input 220-240V DC - Output 24V DC - Class 2

RUBBER 3D, NOW ALSO ON TRACK SYSTEM



Finishes


WH White

AK Anodised Black Aluminium

TR Transparent


Accessories: Rubber 3D PROtection

Linear profile




ASA **C-K100002** 1000 mm - 18 mm - 19 mm
ASA **C-K100001** 2000 mm - 18 mm - 19 mm
suitable for: Rubber 3D PROtection

Linear profile with cable run




ASA **C-K100005** 1000 mm - 39 mm - 19 mm
ASA **C-K100004** 2000 mm - 39 mm - 19 mm
suitable for: Rubber 3D PROtection

Clip



ASA **C-K100003** 50 mm - 18 mm - 19 mm
suitable for: Rubber 3D PROtection

Clip with cable run




ASA **C-K100006** 50 mm - 39 mm - 19 mm
suitable for: Rubber 3D PROtection

Recessed casing + cable gland




PVC **C-C300001** 300 mm - Ø36 mm
suitable for: Rubber 3D PROtection

Rubber profile drilling template




AM **C-V200005** 25 mm - 20 mm - 34 mm
hole Ø 13,2
suitable for: Linear profile Rubber 3D PROtection

Rubber preparation kit




WH **99521** 1100 mm - 40 mm - 22 mm
Niche template
suitable for: Rubber 3D PROtection

Accessory for corrugated preparation




WH **C-K400165** 50 mm - 40 mm - 22 mm
To be combined with Rubber preparation kit 99521
suitable for: Rubber 3D PROtection

Rubber preparation kit




WH **C-K400170** 1010 mm - 40 mm - 27 mm
Niche template
suitable for: Rubber 3D PROtection

Accessory for corrugated preparation or C-C300001



WH **C-K400171** 50 mm - 40 mm - 27 mm
To be combined with Rubber preparation kit C-K400170
suitable for: Rubber 3D PROtection



ASA: Acrylonitrile Styrene Acrylate (thermoplastic material)

Finishes
WH White
AM Anodised Aluminium

Accessories


Connector 2 ways



ABS **98990** IP68
min. 2x0,25 max. 2x1,0 mm²

suitable for: Rubber 3D PROtection (not suitable RGBW) Rubber 3D (not suitable RGBW) - Rubber 3D Optics V2

Connector



PVC **89548** IP68 with GEL
max. 4x1,5 mm2

suitable for: Rubber 3D PROtection (not suitable RGBW) Rubber 3D (not suitable RGBW) - Rubber 3D Optics V2 Rubber 2D Mini


Connector 2 ways



PVC **C-W300001** IP68 with GEL
max. 5x1.5 mm2

suitable for: Rubber 3D PROtection RGBW Rubber 3D RGBW

Double-sided tape



PVC **99520** 33 m

suitable for: Rubber (not for Rubber_O)

IP68 connector C-W300001



Cables

Cable with connector



BB **99688** Conn. F 2x 0,25 - 2000 mm
BB **99689** Conn. M 2x 0,25 - 2000 mm

suitable for: Rubber 3D Pixel

Cable SPI with connector PIXEL



GG **82850** Conn. F 2x 0,5 - 2000 mm
GG **82851** Conn. M 2x 0,5 - 2000 mm

suitable for: Rubber 3D PIXEL RGBW

Cable with connector Dynamic White



BB **C-W200003** Conn. M 3x 0,5 - 2000 mm
BB **C-W200004** Conn. F 3x 0,5 - 2000 mm

suitable for: Rubber 3D Dynamic White

Cable with connector M+F



BB **C-W200009** Conn. M/F 3x 0,5 - 5000 mm

suitable for: Rubber 3D Dynamic White

Cable with connector



BB **C-W200001** Conn. M 2x 0,5 - 2000 mm
BB **C-W200002** Conn. F 2x 0,5 - 2000 mm

suitable for: Rubber 3D - Rubber 3D concrete Rubber 3D Optics V2 - Rubber 2D Mini

Cable with connector RGB**W**



BB **C-W200005** Conn. M 5x 0,5 - 2000 mm
BB **C-W200006** Conn. F 5x 0,5 - 2000 mm

suitable for: Rubber 3D RGBW
(not for Rubber PROtection RGBW)

Cable with connector M+F



BB **C-W200007** Conn. M/F 2x 0,5 - 5000 mm

suitable for: Rubber 3D - Rubber 3D concrete Rubber 3D Optics V2 - Rubber 2D Mini

Cable with connector M+F



BB **C-W200011** Conn. M/F 5x 0,5 - 5000 mm

suitable for: Rubber 3D RGBW
(not for Rubber PROtection RGBW)



With high profile, integrated connection.



New miniaturised IP67 connector for Rubber 3D, made of technopolymer that guarantees greater chemical and UV resistance. (not for Rubber Optics 22W/m and Rubber Pixel). The cable sizes are equivalent for both monochrome and colour-changing versions.

Finishes

GG Grey
BB Black



DOWN LIGHTS





PADOVA CONGRESS
Padua (Italy)

Project: Architect Kengo Kuma

Lighting Designer:
Cogevi

Photography:
TheStudio

Downlights range index

Orma

Orma_C



440-442

Orma_CJ



440-442

Orma_QC



444-445

Orma_QCJ



444-445

Guardian

Guardian



449-453

Guardian_J



449-453



ORMA

Aluminium body.
AISI 316L stainless steel flange.

ORMA ROUND OR SQUARE:
FREE TO CHOOSE.

IP68 IK10




Small overall dimensions

A small-footprint downlight, from 46 to barely 66 mm, with a small flange and Optics designed to fit inside the body. This smart solution makes the product easier to install.

Breadth of range

A complete family, with various lighting solutions to choose from: Spot, Flood, Medium Flood, Wide Flood, Elliptic Spot optics. Two shapes and three sizes, with constant current or constant voltage versions. Finally, the range of Orma downlights includes the _J tilting versions, which can be easily adjusted by acting with a slotted screwdriver on the appropriate screw, without having to open the lamp body.





Visual comfort

Depending on how the light is positioned, its beam can be optimised using the appropriate accessory. The honeycomb filter screens secondary light and reduces direct glare, while maintaining the same high and diffuse quality.



Orma
standard




Orma
+ honeycomb

Orma family

Orma_AJ_IJ	Orma_Q _QF	Orma_I	Orma_A	Orma_F	Orma_Q _QF	Orma Blade
						
659	660	719-723	724-727	730-734	735-741	793

Orma_C | powerLED





C.V. version with converter integrated in the lamp body

		Cct	lm S - lm D	Opt	
C.C. - 350 mA - 4W DC					
SA **81223**		**M**	490 - 270	**15** (22°)	
		W	490 - 270	**30** (29°)	
		N	529 - 292	**60** (49°)	
				25 (16°x 39°)	
C.C. - 350 mA - 4W DC					**HONEYCOMB**
SA **81224**	HC	**M**	490 - 186	**15** (20°)	
		W	490 - 186	**30** (25°)	
		N	529 - 201	**60** (37°)	


Electronics: **BE** (pag 446) | Recessed casings: (pag 446)

C.V. - 24 V DC - 5W DC					
SA **81226**		**M**	490 - 270	**15** (22°)	
		W	490 - 270	**30** (29°)	
		N	529 - 292	**60** (49°)	
				25 (16°x 39°)	
C.V. - 24 V DC - 5W DC					**HONEYCOMB**
SA **81227**	HC	**M**	490 - 186	**15** (20°)	
		W	490 - 186	**30** (25°)	
		N	529 - 201	**60** (37°)	

Electronics: **DB** (pag 446) | Recessed casings: (pag 446)

Orma_CJ | powerLED






C.V. version with converter integrated in the lamp body

		Cct	lm S - lm D	Opt
C.C. - 350 mA - 4W DC				
SA **81241**		**M**	490 - 270	**15** (22°)
		W	490 - 270	**30** (29°)
		N	529 - 292	**60** (49°)

Electronics: **BE** (pag 446) | Recessed casings: (pag 446)

C.V. - 24 V DC - 5W DC				
SA **81242**		**M**	490 - 270	**15** (22°)
		W	490 - 270	**30** (29°)
		N	529 - 292	**60** (49°)


Electronics: **DB** (pag 446) | Recessed casings: (pag 446)



CJ tilting versions

Orma_C | arrayLED





C.V. version with converter integrated in the lamp body

		Cct	Im S - Im D	Opt	
C.C. - 220 mA - 8W DC					
SA **81229**		**M**	1132 - 903	**15**	(15°)
		W	1182 - 943	**30**	(32°)
		N	1212 - 967	**60**	(61°)
C.C. - 220 mA - 8W DC					**HONEYCOMB**
SA **81230**	HC	**M**	1132 - 644	**15**	(15°)
		W	1182 - 673	**30**	(27°)
		N	1212 - 690	**60**	(49°)

Electronics: **BF** (pag 446) | Recessed casings: (pag 446)


C.V. - 24 V DC - 9W DC					
SA **81232**		**M**	1265 - 998	**15**	(15°)
		W	1320 - 1041	**30**	(32°)
		N	1354 - 1068	**60**	(61°)
C.V. - 24 V DC - 9W DC					**HONEYCOMB**
SA **81233**	HC	**M**	1265 - 719	**15**	(15°)
		W	1320 - 750	**30**	(27°)
		N	1354 - 769	**60**	(49°)

Electronics: **DC** (pag 446) | Recessed casings: (pag 446)

Orma_C | arrayLED-Direct | 220-240 V AC

220-240V






		Cct	Im S - Im D	Opt	
7W AC					
SA **76180**		**W**	865 - 560	**15**	(18°)
		N	870 - 560	**30**	(33°)
				60	(56°)

Recessed casings: (pag 446)

Orma_CJ | arrayLED





C.V. version with converter integrated in the lamp body

		Cct	Im S - Im D	Opt	
C.C. - 220 mA - 8W DC					
SA **81243**		**M**	1132 - 903	**15**	(15°)
		W	1182 - 943	**30**	(32°)
		N	1212 - 967	**60**	(61°)
C.C. - 220 mA - 8W DC					**HONEYCOMB**
SA **82452**	HC	**M**	1132 - 644	**15**	(15°)
		W	1182 - 673	**30**	(27°)
		N	1212 - 690	**60**	(49°)


Electronics: **BF** (pag 446) | Recessed casings: (pag 446)

C.V. - 24 V DC - 9W DC					
SA **81244**		**M**	1265 - 998	**15**	(15°)
		W	1320 - 1041	**30**	(32°)
		N	1354 - 1068	**60**	(61°)
C.V. - 24 V DC - 9W DC					**HONEYCOMB**
SA **82453**	HC	**M**	1265 - 719	**15**	(15°)
		W	1320 - 750	**30**	(27°)
		N	1354 - 769	**60**	(49°)

Electronics: **DC** (pag 446) | Recessed casings: (pag 446)

Orma_C | arrayLED





C.V. version with converter integrated in the lamp body

		Cct	lm S - lm D	Opt	
C.C. - 350 mA - 12W DC					
SA **81235**		**M**	2015 - 1612	**15** (14°)	
		W	2100 - 1680	**30** (31°)	
		N	2156 - 1725	**60** (61°)	
C.C. - 350 mA - 12W DC					**HONEYCOMB**
SA **81236**	HC	**M**	2015 - 1147	**15** (13°)	
		W	2100 - 1195	**30** (28°)	
		N	2156 - 1227	**60** (49°)	

Electronics: **BG** (pag 446) | Recessed casings: (pag 446)


C.V. - 24 V DC - 13 W DC					
SA **81238**		**M**	1876 - 1501	**15** (14°)	
		W	1959 - 1567	**30** (31°)	
		N	2010 - 1608	**60** (61°)	
C.V. - 24 V DC - 13 W DC					**HONEYCOMB**
SA **81239**	HC	**M**	1876 - 1067	**15** (13°)	
		W	1959 - 1115	**30** (28°)	
		N	2010 - 1144	**60** (49°)	

Electronics: **DD** (pag 446) | Recessed casings: (pag 446)

Orma_C | arrayLED-Direct | 220-240 V AC

220-240V






		Cct	lm S - lm D	Opt
11,5W AC				
SA **76181**		**W**	1267 - 821	**15** (17°)
		N	1316 - 854	**30** (25°)
				60 (53°)

Recessed casings: (pag 446)

Orma_CJ | arrayLED





C.V. version with converter integrated in the lamp body

		Cct	lm S - lm D	Opt	
C.C. - 350 mA - 12W DC					
SA **81245**		**M**	2015 - 1540	**15** (22°)	
		W	2100 - 1607	**30** (34°)	
		N	2156 - 1650	**60** (61°)	
C.C. - 350 mA - 12W DC					**HONEYCOMB**
SA **82454**	HC	**M**	2015 - 1093	**15** (20°)	
		W	2100 - 1141	**30** (27°)	
		N	2156 - 1171	**60** (48°)	

Electronics: **BG** (pag 446) | Recessed casings: (pag 446)

C.V. - 24 V DC - 13 W DC					
SA **81246**		**M**	1876 - 1432	**15** (22°)	
		W	1959 - 1495	**30** (34°)	
		N	2010 - 1535	**60** (61°)	
C.V. - 24 V DC - 13 W DC					**HONEYCOMB**
SA **82455**	HC	**M**	1876 - 1017	**15** (20°)	
		W	1959 - 1062	**30** (27°)	
		N	2010 - 1089	**60** (48°)	

Electronics: **DD** (pag 446) | Recessed casings: (pag 446)



CANTINA BOTTENAGO
Polpenazze del Garda - Brescia (Italy)


Architectural Project & Interior Design:
Architect Massimiliano Cirani

Lighting Designer:
Viola Elettrotecnica

Photography:
Marco Reggi

Orma_QC | powerLED






	Fin	Cct	Im S - Im D	Opt
C.C. - 350 mA - 4 W DC				
C00351	**SA**	**M**	596 - 299	**SP** (19°)
		W	624 - 313	**ML** (30°)
		N	660 - 330	**WF** (52°)
				EF (26°x 50°)
C.C. - 350 mA - 4 W DC				**HONEYCOMB**
C00352 HC	**SA**	**M**	596 - 232	**SP** (18°)
		W	624 - 232	**FL** (25°)
		N	660 - 245	**MW** (40°)
				1F (23°x 40°)
C.V. - 24 V DC - 5 W DC				
C00354	**SA**	**M**	596 - 299	**SP** (19°)
		W	624 - 313	**ML** (30°)
		N	660 - 330	**WF** (52°)
				EF (26°x 50°)
C.V. - 24 V DC - 5 W DC				**HONEYCOMB**
C00355 HC	**SA**	**M**	596 - 232	**SP** (18°)
		W	624 - 232	**FL** (25°)
		N	660 - 245	**MW** (40°)
				1F (23°x 40°)

Electronics: C.C. **BE** - C.V. **DB** (pag 446) | Recessed casings: (pag 446)

Orma_QCJ | powerLED







	Fin	Cct	Im S - Im D	Opt
C.C. - 350mA - 4 W DC				
C00357	**SA**	**M**	596 - 299	**SP** (19°)
		W	624 - 313	**ML** (30°)
		N	660 - 330	**WF** (52°)
C.C. - 350mA - 4 W DC				**HONEYCOMB**
C00358 HC	**SA**	**M**	596 - 232	**SP** (18°)
		W	624 - 232	**FL** (25°)
		N	660 - 245	**MW** (40°)
C.V. - 24 V DC - 5 W DC				
C00359	**SA**	**M**	596 - 299	**SP** (19°)
		W	624 - 313	**ML** (30°)
		N	660 - 330	**WF** (52°)
C.V. - 24 V DC - 5 W DC				**HONEYCOMB**
C00360 HC	**SA**	**M**	596 - 232	**SP** (18°)
		W	624 - 232	**FL** (25°)
		N	660 - 245	**MW** (40°)

Electronics: C.C. **BE** - C.V. **DB** (pag 446) | Recessed casings: (pag 446)

Orma_QC | arrayLED







	Fin	Cct	lm S - lm D	Opt
C.C. - 220 mA - 8 W DC				
C00361	**SA**	**M**	1132 - 720	**SP** (18°)
		W	1182 - 751	**FL** (26°)
		N	1212 - 770	**WF** (58°)
C.C. - 220 mA - 8 W DC				**HONEYCOMB**
C00362 HC	**SA**	**M**	1132 - 550	**SP** (17°)
		W	1182 - 574	**FL** (23°)
		N	1212 - 588	**MW** (48°)
C.V. - 24 V DC - 9 W DC				
C00364	**SA**	**M**	1265 - 804	**SP** (18°)
		W	1320 - 839	**FL** (26°)
		N	1354 - 860	**WF** (58°)
C.V. - 24 V DC - 9 W DC				**HONEYCOMB**
C00365 HC	**SA**	**M**	1265 - 614	**SP** (17°)
		W	1320 - 641	**FL** (23°)
		N	1354 - 657	**MW** (48°)

Electronics: C.C. **BF** - C.V. **DC** (pag 446) | Recessed casings: (pag 446)

Orma_QC | arrayLED-Direct | 220-240 V AC







220-240V

	Fin	Cct	lm S - lm D	Opt
7 W AC				
C00972	**SA**	**W**	865 - 315	**SP** (18°)
		N	870 - 316	**FL** (26°)
				MW (44°)

Recessed casings: (pag 446)

Orma_QCJ | arrayLED





	Fin	Cct	lm S - lm D	Opt
C.C. - 220 mA - 8 W DC				
C00367	**SA**	**M**	1132 - 720	**SP** (18°)
		W	1182 - 751	**FL** (26°)
		N	1212 - 770	**WF** (58°)
C.C. - 220 mA - 8 W DC				**HONEYCOMB**
C00368 HC	**SA**	**M**	1132 - 550	**SP** (17°)
		W	1182 - 574	**FL** (23°)
		N	1212 - 588	**MW** (48°)
C.V. - 24 V DC - 9 W DC				
C00369	**SA**	**M**	1265 - 804	**SP** (18°)
		W	1320 - 839	**FL** (26°)
		N	1354 - 860	**WF** (58°)
C.V. - 24 V DC - 9 W DC				**HONEYCOMB**
C00370 HC	**SA**	**M**	1265 - 614	**SP** (17°)
		W	1320 - 641	**FL** (23°)
		N	1354 - 657	**MW** (48°)

Electronics: C.C. **BF** - C.V. **DC** (pag 446) | Recessed casings: (pag 446)

Electronics

BE

89421	C-E200006	C-E200004
ON/OFF 1 art. 74 x 65 x h 27	ON/OFF 2 - 3 art. 135 x 26 x h 26 35	DALI/PUSH 2 - 3 art. 125 x 45 x h 30 55

BF

99342	C-E200005
ON/OFF 1 art. 100 x 80 x h 31	DALI/PUSH 1 art. 125 x 45 x h 30 55

BG

C-E200006	C-E200004
ON/OFF 1 art. 135 x 26 x h 26 35	DALI/PUSH 1 art. 125 x 45 x h 30 55

DB

89488	89179	89359	99660	83042	+ driver 24V DC	
					99331 150W	99786 240W
ON/OFF 1 - 2 art. 80 x 100 x h 31	ON/OFF 1 - 4 art. 92 x 117 x h 38	ON/OFF 1 - 9 art. 115 x 140 x h 50	Dimmer DALI - 0/1-10V 149 x 37 x h 31 48	Dimmer DALI/PUSH 0/1-10V 164 x 38 x h 25 45	1-21 art. 70	1-33 art. 81

DC

89179	89359	99331	99660	83042	+ driver 24V DC	
					99331 150W	99786 240W
ON/OFF 1 - 2 art. 92 x 117 x h 38	ON/OFF 1 - 5 art. 115 x 140 x h 50	ON/OFF 1 - 15 art. 158 x 60 x h 35	Dimmer DALI - 0/1-10V 149 x 37 x h 31 48	Dimmer DALI/PUSH 0/1-10V 164 x 38 x h 25 45	1-11 art. 70	1-18 art. 81

DD

89179	89359	99331	99660	83042	+ driver 24V DC	
					99331 150W	99786 240W
ON/OFF 1 art. 92 x 117 x h 38	ON/OFF 1 - 3 art. 115 x 140 x h 50	ON/OFF 1 - 10 art. 158 x 60 x h 35	Dimmer DALI - 0/1-10V 149 x 37 x h 31 48	Dimmer DALI/PUSH 0/1-10V 164 x 38 x h 25 45	1-8 art. 70	1-12 art. 81

Recessed casing




PLP **89373** Recessed casing for brickwork

suitable for: Orma_C Ø64 / Orma_CJ Ø64
Orma_C Ø97 / Orma_CJ Ø97



PLP **89374** Recessed casing for brickwork

suitable for: Orma_C Ø64 / Orma_CJ Ø64
Orma_C Ø97 / Orma_CJ Ø97




PLP **99749** Recessed casing (to be completed with universal grille **99750**)

suitable for: Orma_C Ø138 / Orma_CJ Ø138




PVC **99750** Universal grille for recessed light casing **99749**

suitable for: Orma_C Ø138 / Orma_CJ Ø138



PLP **C-C100016** Recessed casing for brickwork to be completed with accessory **C-C100015**

suitable for: Orma_QC L85-116 / Orma_QCJ L85-116



PLP **C-C100017** Recessed casing for brickwork to be completed with accessory **C-C100015**

suitable for: Orma_QC L85-116 / Orma_QCJ L85-116



PVC **C-C100015** Universal grid for outer casing **C-C100016 - C-C100017**

suitable for: Orma_QC L85-116 / Orma_QCJ L85-116

Finishes

PLP Polypropylene




GUARDIAN

Aluminium body.
Anodised aluminium flange.



Guardian | powerLED | 220-240 V AC | 7,2 W DC - 8,5 W AC






IK10 IP67

		Cct	lm S - lm D	Opt
WH **81893**		**M**	1041 - 568	**15** (17°)
BB **81916**		**W**	1087 - 592	**30** (26°)
GG **81838**		**N**	1114 - 613	**60** (51°)
				07 (Asym. Ww)
WH **81894**	HC	**M**	1041 - 453	**15** (14°)
BB **81917**	HC	**W**	1087 - 473	**30** (24°)
GG **81839**	HC	**N**	1114 - 489	**60** (42°)

Recessed casings: (pag 453)

Guardian_J | powerLED | 220-240 V AC | 7,2 W DC - 8,5 W AC





IK10 IP67

	Cct	lm S - lm D	Opt
WH **81895**	**M**	1041 - 558	**20** (20°)
BB **81918**	**W**	1087 - 565	**30** (30°)
GG **81840**	**N**	1114 - 572	**60** (60°)

Recessed casings: (pag 453)



White (WH)





Gray (GG)



Black (BB)

Guardian_J (7,2 W)
Which can be easily adjusted using a slotted screwdriver on the relevant screw, the optic group can be angled from -20°/+20°.





Finishes
WH White GG Grey
BB Black

Cct
M 2700 **N** 4000
W 3000

Accessories
HC Honeycomb




PADOVA CONGRESS
Padua (Italy)


Project: Architect Kengo Kuma

Lighting Designer:
Cogevi

Photography:
TheStudio

Guardian | powerLED | 220-240 V AC | 13 W DC - 15 W AC






IK10 IP67 NEW

		Cct	lm S - lm D	Opt	
WH **76778**		**M**	1676 - 1325	**10** (10°)	
BB **76808**		**W**	1750 - 1380		
GG **76838**		**N**	1794 - 1421		
DALI					
WH **76787**					
BB **76817**					
GG **76847**					
WH **76779**	HC	**M**	1676 - 1054	**10** (10°)	**HONEYCOMB**
BB **76809**	HC	**W**	1750 - 1098		
GG **76839**	HC	**N**	1794 - 1131		
DALI					
WH **76788**	HC				
BB **76818**	HC				
GG **76848**	HC				

Recessed casings: (pag 453)

Guardian_J | powerLED | 220-240 V AC | 13 W DC - 15 W AC






IK10 IP67 NEW

		Cct	lm S - lm D	Opt	
WH **76794**		**M**	1676 - 1289	**10** (10°)	
BB **76824**		**W**	1750 - 1344		
GG **76854**		**N**	1794 - 1383		
DALI					
WH **76800**					
BB **76830**					
GG **76860**					
WH **76795**	HC	**M**	1676 - 1098	**10** (10°)	**HONEYCOMB**
BB **76825**	HC	**W**	1750 - 1144		
GG **76855**	HC	**N**	1794 - 1178		
DALI					
WH **76801**	HC				
BB **76831**	HC				
GG **76861**	HC				

Recessed casings: (pag 453)

Guardian_J (13 W)
Which can be easily adjusted using a slotted screwdriver on the relevant screw, the optic group can be angled from -25°/+25°.





Finishes
WH White GG Grey
BB Black

Cct
M 2700 **N** 4000
W 3000

Accessories
HC Honeycomb

Guardian | powerLED | 220-240 V AC | 16 W DC - 18 W AC






IK10 IP67 NEW

		Cct	Im S - Im D	Opt	
WH **76775**		**M**	2528 - 1718	**15** (16°)	
BB **76805**		**W**	2634 - 1790	**30** (37°)	
GG **76835**		**N**	2704 - 1671	**50** (53°)	
DALI					
WH **76784**					
BB **76814**					
GG **76844**					
WH **76776**	HC	**M**	2528 - 1275	**15** (15°)	**HONEYCOMB**
BB **76806**	HC	**W**	2634 - 1321	**30** (33°)	
GG **76836**	HC	**N**	2704 - 1368	**50** (46°)	
DALI					
WH **76785**	HC				
BB **76815**	HC				
GG **76845**	HC				

Recessed casings: (pag 453)

Guardian_J | powerLED | 220-240 V AC | 16 W DC - 18 W AC






IK10 IP67 NEW


		Cct	Im S - Im D	Opt	
WH **76792**		**M**	2528 - 1633	**15** (16°)	
BB **76822**		**W**	2634 - 1702	**30** (37°)	
GG **76852**		**N**	2704 - 1753	**50** (52°)	
DALI					
WH **76798**					
BB **76828**					
GG **76858**					
WH **76793**	HC	**M**	2528 - 1162	**15** (15°)	**HONEYCOMB**
BB **76823**	HC	**W**	2634 - 1210	**30** (32°)	
GG **76853**	HC	**N**	2704 - 1246	**50** (45°)	
DALI					
WH **76799**	HC				
BB **76829**	HC				
GG **76859**	HC				


Recessed casings: (pag 453)

Guardian_J (16 W / 19 W)
Which can be easily adjusted using a slotted screwdriver on the relevant screw, the optic group can be angled from -25°/+25°.



Guardian | powerLED | 220-240 V AC | 19 W DC - 22 W AC






IK10 IP67 NEW

		Cct	lm S - lm D	Opt	
WH **76772**		**M**	2773 - On req	**15** (16°)	
BB **76802**		**W**	2889 - On req	**30** (37°)	
GG **76832**		**N**	2966 - On req	**50** (53°)	
DALI					
WH **76781**					
BB **76811**					
GG **76841**					
WH **76773**	HC	**M**	2773 - On req	**15** (15°)	**HONEYCOMB**
BB **76803**	HC	**W**	2889 - On req	**30** (33°)	
GG **76833**	HC	**N**	2966 - On req	**50** (46°)	
DALI					
WH **76782**	HC				
BB **76812**	HC				
GG **76842**	HC				

Recessed casings: (pag 453)

Guardian_J | powerLED | 220-240 V AC | 19 W DC - 22 W AC






IK10 IP67 NEW

		Cct	lm S - lm D	Opt	
WH **76790**		**M**	2773 - On req	**15** (16°)	
BB **76820**		**W**	2889 - On req	**30** (37°)	
GG **76850**		**N**	2966 - On req	**50** (52°)	
DALI					
WH **76796**					
BB **76826**					
GG **76856**					
WH **76791**	HC	**M**	2773 - On req	**15** (15°)	**HONEYCOMB**
BB **76821**	HC	**W**	2889 - On req	**30** (32°)	
GG **76851**	HC	**N**	2966 - On req	**50** (45°)	
DALI					
WH **76797**	HC				
BB **76827**	HC				
GG **76857**	HC				


Recessed casings: (pag 453)

Recessed casings




ABS **99673** Recessed casing for brick or concrete-mounted installation

suitable for: Guardian Ø110 7,2W
Guardian_J Ø110 7,2W




POL **83331** Template for cementing in polystyrene foam

suitable for: Guardian Ø200 13W - 16W - 19W
Guardian_J Ø200 13W - 16W - 19W



ABS **83328** Recessed casing for brick or concrete-mounted installation

suitable for: Guardian Ø200 13W - 16W - 19W
Guardian_J Ø200 13W - 16W - 19W



ZN **83330** Case back for outer casing closure 83328

suitable for: Guardian Ø200 13W - 16W - 19W
Guardian_J Ø200 13W - 16W - 19W

Finishes

WH White GG Grey POL Polystyrene
BB Black ZN Galvanised Steel

Cct

M 2700 **N** 4000
W 3000

Accessories

HC Honeycomb



PRO JECTORS

H-FARM - Tenuta Ca' Tron
Roncade - Treviso (Italy)

Project:
Studio Zanon Architetti Associati

Photography:
TheStudio



Projectors range index

Eyelet65

Eyelet65_R


459


Eyelet65_Q


459

Periskop

Periskop45

464

Periskop60

464

Periskop80


466

Periskop110


468

Periskop160


469

Shaker

Shaker


473

Iris67

Iris67

477

Iris67 Elliptic

478

Clivo

Clivo_2

481

Clivo_SL

481

Clark316

Clark316



484

Vuelta

Vuelta_Y

487

Prolamp

Prolamp


489-490

Biglamp

Biglamp

493

Biglamp Pro

494-495


EYELET65

Aluminium body.



Eyelet65_R | V2 | powerLED | 630 mA 2 W DC | 1000 mA 3 W DC






	Fin	Cct	Im S - Im D 2 W	Im S - Im D 3 W	Opt
C01047	**WH**	**M**	219 - 151	417 - 322	**FL** (24°)
	BB	**W**	233 - 171	432 - 335	**ML** (31°)
	GG	**N**	249 - 183	642 - 343	**WF** (54°)
	GR				
	DB				

Electronics: 2W IP67 **BD** - 3W IP40 **FQ** (pag 459) | Accessories: (pag 459)


Eyelet65_Q | V2 | powerLED | 630 mA 2 W DC | 1000 mA 3 W DC





	Fin	Cct	Im S - Im D 2 W	Im S - Im D 3 W	Opt
C01048	**WH**	**M**	219 - 151	417 - 322	**FL** (24°)
	BB	**W**	233 - 171	432 - 335	**ML** (31°)
	GG	**N**	249 - 183	642 - 343	**WF** (54°)
	GR				
	DB				

Electronics: 2W IP67 **BD** - 3W IP40 **FQ** (pag 459) | Accessories: (pag 459)



Scale 1:1

Electronics

BD IP67


89420	**C-E200008**	**99186**	**C-E200002**
ON/OFF	ON/OFF	ON/OFF	DALI/PUSH
1 - 2 art.	3 - 6 art.	6 - 12 art.	5 - 12 art.
74 x 65 x h 27	135 x 26 x h 26	117 x 92 x h 38	125 x 45 x h 30
	35		55

FQ IP40

C-E100046	**C-E100047**	**C-E100033**	**C-E100034**
ON/OFF	DALI	ON/OFF	DALI/PUSH
1 - 6 art.	1 - 3 art.	4 - 12 art.	4 - 12 art.
130 x 38 x h 28	140 x 36 x h 20	138 x 44 x h 23	138 x 44 x h 23
48	40	50	50

Accessories


IS **98624** Steel peg Ø10x160 mm
IS **C-F500002** Steel peg Ø10x700 mm
IS **C-F500003** Steel peg Ø10x1000 mm
suitable for: Eyelet65_R - Eyelet65_Q



BB **83359** Snoot
suitable for: Eyelet65_R



IS **98669** Steel peg 101 mm
suitable for: Eyelet65_R - Eyelet65_Q



BB **W-U300001** Snoot
suitable for: Eyelet65_Q

Finishes

WH White
BB Black
GG Grey
GR Green
DB Dark Brown
IS Steel

Cct

M 2700
W 3000
N 4000

PERISKOP

Aluminium body.
Extra-clear tempered
glass diffuser.



A NEW OPTICS GROUP

The new Periskop frame is made of die-cast aluminum with epoxy powder coated finish: white, black, grey, dark brown and green; the front is characterised by clear tempered glass with a black screen-printed edge; inside we find a new optics group with beam angles: Hyper Spot, Ultra Spot, Spot, Flood, Medium Flood, Wide Flood, Elliptic.
The anti-glare accessories help further reduce the glare for significantly enhanced visual comfort.



☐ **45** ☐ **60** ☐ **80** ☐ **110** ☐ **160**

PERISKOP**45** (4,5W-6W)



08 Spot (11°)
15 Spot (14°)
30 Flood (28°)
60 W.Flood (50°)

PERISKOP**60** (6W-6,7W)



10 Spot (11°)
15 Spot (16°)
30 M.Flood (32°)
45 M.Flood (40°)

PERISKOP**80** (2W-9,5W)



HS Hyper Spot (3°)
US Ultra Spot (5°)
SP Spot (15°)
ML M.Flood (38°)
WF W.Flood (50°)
1S Elliptic Spot (15°x41°)
OH Elliptic M.W.Flood (41°x15°)
EM Elliptic M.Flood (33°x43°)
1H Elliptic M.W.Flood (43°x33°)

PERISKOP**110** (8,4W-18W)



HS Hyper Spot (3°)
US Ultra Spot (5°)
SP Spot (15°)
ML M.Flood (37°)
WF W.Flood (52°)
1S Elliptic Spot (16°x40°)
OH Elliptic M.W.Flood (40°x16°)
EM Elliptic M.Flood (33°x42°)
1H Elliptic M.W.Flood (42°x33°)

PERISKOP**160** (19W-44W)





HS Hyper Spot (3°)
US Ultra Spot (5°)
FL Flood (23°)
ML M.Flood (38°)
WF W.Flood (55°)
EF Elliptic Flood (23°x42°)
1H Elliptic M.W.Flood (42°x23°)

In the optical representations, the lighting fixture is to be considered as wall-mounted with a front view.











HD8 HOTEL
Milan (Italy)

Project: arch. Marco Guido Savorelli,
arch. Daniela Bernabei - Sa Architecture

Photography:
Marco Reggi

Periskop45 | powerLED






C.C. IK05 IP66

	Cct	Im S - Im D	Opt
500 mA - 6 W DC			
WH **81788**	**M**	659 - 487	**08** (11°)
BB **81789**	**W**	659 - 487	
GG **81790**	**N**	711 - 524	
DB **81791**			
GR **77605**			

Electronics: **BO** (pag 470) | Accessories: (pag 470-471)

Periskop45 | powerLED







C.C. IK05 IP66

	Cct	Im S - Im D	Opt
500 mA - 6 W DC			
WH **90519**	**M**	659 - 396	**15** (14°)
BB **90520**	**W**	659 - 396	**30** (28°)
GG **90521**	**N**	711 - 427	**60** (50°)
DB **90522**			
GR **77604**			

Electronics: **BO** (pag 470) | Accessories: (pag 470-471)

Periskop45 RGB | powerLED






C.C. IK05 IP66

	Cct		Opt
500 mA - 4,5 W DC			
WH **95068**	**Z**	RGB	**15** (14°)
BB **95126**			**60** (50°)
GG **95141**			
DB **95330**			
GR **77606**			

Electronics: **CE** (pag 470) | Accessories: (pag 470-471)

Periskop60 | powerLED







IK08 IP66 ID

	Cct	Im S - Im D	Opt
220-240 V AC - 6 W DC - 7,5 W AC			
WH **84237**	**M**	659 - 468	**10** (11°)
BB **84238**	**W**	659 - 468	
GG **84239**	**N**	711 - 506	
DB **84240**			
GR **77608**			

Accessories: (pag 470-471)

Periskop60 | powerLED






IK05 IP66 ID

	Cct	Im S - Im D	Opt
220-240 V AC - 6,7 W DC - 8,7 W AC			
WH **84233**	**M**	849 - 632	**15** (16°)
BB **84234**	**W**	886 - 660	**30** (32°)
GG **84235**	**N**	935 - 696	**45** (40°)
DB **84236**			
GR **77607**			

Accessories: (pag 470-471)

ID
Driver
on board





THE CO99 ART BUILDING & OPR GALLERY
Milan (Italy)


Project: Architect Federico Regazzoni

Lighting Designer:
Light+Arch Consultancy,
Architect Giorgio Colombo

Photography:
Marco Reggi

Periskop80 | V2 | powerLED





IP66 NEW

	Fin	Cct	lm S - lm D	Opt
630 mA - 2 W DC				
C00778	**WH**	**A**	128 - 114	**HS** (1°÷ 3°)
	BB	**M**	174 - 151	
	GG	**W**	186 - 162	
	DB	**N**	201 - 172	
	GR			

Electronics: **BD** (pag 470) | Accessories: (pag 470-471)


IK08 IP66 NEW

	Fin	Cct	lm S - lm D	Opt
220-240 V AC - 2 W DC - 3,7 W AC				
C00777	**WH**	**A**	128 - 114	**HS** (1°÷ 3°)
	BB	**M**	174 - 151	
	GG	**W**	186 - 162	
	DB	**N**	201 - 172	
	GR			

Accessories: (pag 470-471)

Periskop80 | V2 | powerLED





IP66 NEW

	Fin	Cct	lm S - lm D	Opt
630 mA - 8 W DC				
C00780	**WH**	**A**	512 - 369	**US** (5°)
	BB	**M**	696 - 497	
	GG	**W**	744 - 533	
	DB	**N**	792 - 566	
	GR			


Electronics: **BU** (pag 470) | Accessories: (pag 470-471)


IK08 IP66 NEW

	Fin	Cct	lm S - lm D	Opt
220-240 V AC - 8,4 W DC - 11,5 W AC				
C00779	**WH**	**A**	580 - 419	**US** (5°)
	BB	**M**	784 - 559	
	GG	**W**	840 - 599	
	DB	**N**	892 - 636	
	GR			

Accessories: (pag 470-471)

Periskop80 | V2 | arrayLED





IP66 NEW

	Fin	Cct	lm S - lm D	Opt
500 mA - 9,5 W DC				
C00489	**WH**	**A**	1011 - 766	**SP** (15°)
	BB	**M**	1265 - 958	**ML** (38°)
	GG	**W**	1320 - 1000	**WF** (50°)
	DB	**N**	1354 - 1026	**1S** (15°x 41°)
	GR			**OH** (41°x 15°)
				EM (33°x 43°)
				1H (43°x 33°)


HONEYCOMB


		Fin	Cct	lm S - lm D	Opt
C00490	HC	**WH**	**A**	1011 - 550	**SP** (14°)
		BB	**M**	1265 - 688	**ML** (33°)
		GG	**W**	1320 - 718	**MW** (44°)
		DB	**N**	1354 - 731	
		GR			

Electronics: **IA** (pag 470) | Accessories: (pag 470-471)

DW Dynamic White 4 W available on request

Periskop80 | V2 | arrayLED





IK08 IP66 NEW


	Fin	Cct	lm S - lm D	Opt
220-240 V AC - 9,5 W DC - 11,5 W AC				
C00487	**WH**	**A**	1011 - 766	**SP** (15°)
	BB	**M**	1265 - 958	**ML** (38°)
	GG	**W**	1320 - 1000	**WF** (50°)
	DB	**N**	1354 - 1026	**1S** (15°x 41°)
	GR			**OH** (41°x 15°)
				EM (33°x 43°)
				1H (43°x 33°)


HONEYCOMB

C00488 HC	**WH**	**A**	1011 - 550	**SP** (14°)
	BB	**M**	1265 - 688	**ML** (33°)
	GG	**W**	1320 - 718	**MW** (44°)
	DB	**N**	1354 - 731	
	GR			

Accessories: (pag 470-471)

Periskop80 RGBW | V2 | arrayLED





C.C. IK08 IP66 NEW

	Fin	Cct		Opt
600 mA - 8 W DC				
C00781	**WH**	**V**	RGBW (3000 K)	**US** (5°)
	BB	**Q**	RGBW (4000 K)	**SP** (15°)
	GG			**MW** (44°)
	DB			
	GR			

Electronics: **CF** (pag 470) | Accessories: (pag 470-471)



New finish Green (RAL 6031)

Finishes

White Grey Green
Black Dark Brown

Cct


A 2200 **W** 3000 **V** RGBW (3000 K)
M 2700 **N** 4000 **Q** RGBW (4000 K)

Accessories

HC Honeycomb

Periskop110 | V2 | powerLED





IK08 IP66 NEW


*

	Fin	Cct	lm S - lm D	Opt
220-240 V AC - 8,4 W DC - 10 W AC				
C00817	**WH**	**A**	579 - 386	**HS** (3°)
DALI *	**BB**	**M**	784 - 515	
C00818	**GG**	**W**	840 - 552	
	DB	**N**	892 - 586	
	GR			

Accessories: (pag 470-471)

Periskop110 | V2 | powerLED






IK08 IP66 NEW

	Fin	Cct	lm S - lm D	Opt
220-240 V AC - 18 W DC - 21 W AC				
C00819	**WH**	**A**	1155 - 892	**US** (5°)
DALI	**BB**	**M**	1566 - 1188	
C00820	**GG**	**W**	1593 - 1273	
	DB	**N**	1809 - 1352	
	GR			

Accessories: (pag 470-471)

Periskop110 | V2 | arrayLED





IK08 IP66 NEW

	Fin	Cct	lm S - lm D	Opt
220-240 V AC - 18 W DC - 21 W AC				
C00812	**WH**	**A**	2446 - 1746	**SP** (15°)
DALI	**BB**	**M**	2773 - 1979	**ML** (37°)
C00814	**GG**	**W**	2889 - 2062	**WF** (52°)
	DB	**N**	2996 - 2138	**1S** (16°x 40°)
	GR			**OH** (40°x 16°)
				EM (33°x 42°)
				1H (42°x 33°)

HONEYCOMB


C00813	HC	**WH**	**A**	2446 - 1283	**SP** (15°)
DALI		**BB**	**M**	2773 - 1454	**ML** (33°)
C00815	HC	**GG**	**W**	2889 - 1515	**MW** (46°)
		DB	**N**	2996 - 1571	
		GR			

Accessories: (pag 470-471)

DW Dynamic White 15 W available on request - Driver not included

Periskop110 RGBW | V2 | arrayLED






C.C. IK08 IP66 NEW RGBW


	Fin	Cct	lm S - lm D	Opt
500 mA - 18 W DC				
C00816	**WH**	**V**	RGBW (3000 K)	**FL** (20°÷ 29°)
	BB			**ML** (30°÷ 39°)
	GG			**WF** (50°÷ 70°)
	DB			
	GR			

Electronics: **CT** (pag 470) | Accessories: (pag 470-471)

EL * The driver contained in the device complies with IEC 61347-2-13 annex J, and can therefore be powered by centralized power supply systems.

Periskop160 | powerLED






IK08 IP66 NEW

	Fin	Cct	lm S - lm D	Opt
220-240 V AC - 19 W DC - 22 W AC				
C00874	**WH**	**A**	1303 - 945	**HS** (3°)
DALI	**BB**	**M**	1764 - 1260	
C00875	**GG**	**W**	1890 - 1350	
	DB	**N**	2007 - 1434	
	GR			

Accessories: (pag 470-471)

Periskop160 | V2 | powerLED






IK08 IP66 NEW

	Fin	Cct	lm S - lm D	Opt
220-240 V AC - 34 W DC - 38 W AC				
C00876	**WH**	**A**	2317 - 1526	**US** (5°)
DALI	**BB**	**M**	3136 - 2034	
C00877	**GG**	**W**	3360 - 2180	
	DB	**N**	3568 - 2315	
	GR			

Accessories: (pag 470-471)

Periskop160 | V2 | arrayLED





IK08 IP66 NEW

	Fin	Cct	lm S - lm D	Opt
220-240 V AC - 44 W DC - 48 W AC				
C00857	**WH**	**A**	6452 - 4533	**FL** (23°)
DALI	**BB**	**M**	7328 - 5156	**ML** (38°)
C00859	**GG**	**W**	7642 - 5371	**WF** (55°)
	DB	**N**	7837 - 5510	**1H** (42°x 23°)
	GR			**EF** (23°x 42°)

HONEYCOMB


C00858	HC	**WH**	**A**	6452 - 3365	**FL** (22°)
DALI		**BB**	**M**	7328 - 3828	**ML** (34°)
C00860	HC	**GG**	**W**	7642 - 3987	**MW** (47°)
		DB	**N**	7837 - 4091	
		GR			

Accessories: (pag 470-471)

DW Dynamic White 25 W available on request

Periskop160 RGBW | arrayLED





IK08 IP66 DMX RDM RGBW

	Cct	Opt
220-240 V AC - 37 W DC - 40 W AC		
WH **81784**	**V** RGBW (3000 K)	**20** (20°)
BB **81785**		**30** (27°)
GG **81786**		**60** (51°)
DB **81787**		
GR **77618**		

Electronics: **AM4** (pag 470) | Accessories: (pag 470-471)



RGBW Connector

Finishes

WH White GG Grey GR Green
BB Black DB Dark Brown

Cct

A 2200 **W** 3000 **V** RGBW (3000 K)
M 2700 **N** 4000

Electronics

AM4

DMX
Controllers
Pag. 963

C-E700026
DMX/RDM addresser

98986
120 Ohm DMX line closure

98985/99390
Splitter ALLinONE Start & Continuity
Pag. 972

BO

C-E200007
ON/OFF
1 art.
135 x 26 x h 26
35

99185
ON/OFF
2 - 3 art.
117 x 92 x h 38

C-E200003
DALI/PUSH
2 - 3 art.
125 x 45 x h 30
55

CE

C-E700003+C-W600001
Dimmer RF
6 - 12 art.
175 x 45 x h 27
52

C-E500012
Dimmer DMX
6 - 12 art.
107 x 96 x h 39

DMX
Controllers
Pag. 963

Driver CV
CV 48V
Pag. 950-951

Switching
CV 48V
Pag. 945-946

CT

C-E700003+C-W600001
Dimmer RF
2 - 4 art.
175 x 45 x h 27
52

C-E500012
Dimmer DMX
2 - 4 art.
107 x 96 x h 39

DMX
Controllers
Pag. 963

Driver CV
CV 48V
Pag. 950-951

Switching
CV 48V
Pag. 945-946

BD

89420
ON/OFF
1 - 2 art.
74 x 65 x h 27

C-E200008
ON/OFF
3 - 6 art.
135 x 26 x h 26
35

99186
ON/OFF
6 - 12 art.
117 x 92 x h 38

C-E200002
DALI/PUSH
5 - 12 art.
125 x 45 x h 30
55

BU

C-E200008
ON/OFF
1 art.
135 x 26 x h 26
35

99186
ON/OFF
2 - 3 art.
117 x 92 x h 38

C-E200002
DALI/PUSH
2 - 3 art.
125 x 45 x h 30
55

CF

C-E700003+C-W600001
Dimmer RF
6 - 12 art.
175 x 45 x h 27
52

C-E500011
Dimmer DMX
6 - 12 art.
107 x 96 x h 39

DMX
Controllers
Pag. 963

Driver CV
CV 48V
Pag. 950-951

Switching
CV 48V
Pag. 945-946

IA

C-E200007
ON/OFF
1 art.
135 x 26 x h 26
35

99185
ON/OFF
1 - 2 art.
117 x 92 x h 38

C-E200003
DALI/PUSH
1 - 2 art.
125 x 45 x h 30
55

Cables & accessories

AllinOne DMX 190-250V AC | Extension cables



BB **98662** M. / F. 6 pin (L 1m)
BB **98663** M. / F. 6 pin (L 5m)

suitable for: Periskop RGBW 40W



98986 ALLinONE splitter power/DMX_DMX line closure adapter

Pag. 972



98985 ALLinONE splitter power/DMX_Start splitter


Pag. 972



99390 ALLinONE splitter power/DMX_Continuity splitter

Pag. 972

Accessories



BB **83245** Anti-glare screen
suitable for: Periskop60 (not for optic 10)

BB **C-U300023** Anti-glare screen
suitable for: Periskop80

BB **C-U300024** Anti-glare screen
suitable for: Periskop110

BB **C-U300025** Anti-glare screen
suitable for: Periskop160



BB **C-U300026** Anti-glare pipe
suitable for: Periskop80

BB **C-U300027** Anti-glare pipe
suitable for: Periskop110

BB **C-U300028** Anti-glare pipe
suitable for: Periskop160



BB **C-U300032** Flaps

suitable for: Periskop160



TR **C-U300033** Elliptical filter

suitable for: Periskop160
To be combined with the Flaps code **C-U300032**

IS **98624** Steel peg Ø10x160 mm
IS **C-F500002** Steel peg Ø10x700 mm
IS **C-F500003** Steel peg Ø10x1000 mm
suitable for: Periskop45 - Periskop60



IS **98550** Peg L152 mm
suitable for: Periskop45



PLC **89371** Peg L204 mm
suitable for: Periskop60



PLC **98549** Peg L204 mm
suitable for: Periskop80 - Periskop110 - Periskop160



BB **99802** Tree belt
suitable for: Periskop80 - Periskop110 - Periskop160

OUTDOOR ACCESSORIES ANTI-GLARE

Anti-glare accessories are conceived to reduce light glare. These accessories are made of black painted aluminium.



Finishes

BB Black TR Transparent
IS Steel PLC Polycarbonate

SHAKER

Aluminium body.
Extra-clear tempered glass diffuser.




PRIVATE HOUSE
Madrid (Spain)

Lighting Designer:
Oscar Abril Revuelta

Photography:
Marek Jarosz

Shaker | powerLED






IK10 IP66 ID

	Cct	lm S - lm D	Opt
220-240 V AC - 2 W DC - 3 W AC			
WH **84241**	**A**	128 - 98	**15** (15°)
BB **84242**	**M**	233 - 176	**30** (30°)
GG **84243**	**W**	249 - 189	**60** (60°)
DB **84244**	**N**	266 - 202	
GR **77611**			

Accessories: (pag 474)

Shaker | arrayLED





IK07 IP66 NEW

	Fin	Cct	lm S - lm D	Opt
220-240 V AC - 6,3 W DC - 8 W AC				
C00709	**WH**	**A**	715 - 533	**SP** (14°)
	BB	**M**	849 - 632	**ML** (31°)
	GG	**W**	886 - 660	**MW** (43°)
	DB	**N**	935 - 696	
	GR			
				HONEYCOMB
C00710 HC	**WH**	**A**	715 - 317	**SP** (14°)
	BB	**M**	849 - 376	**ML** (31°)
	GG	**W**	886 - 392	
	DB	**N**	935 - 414	
	GR			

Accessories: (pag 474)


III IK07 IP66 NEW

	Fin	Cct	lm S - lm D	Opt
630 mA - 6 W DC				
C00711	**WH**	**A**	715 - 533	**SP** (14°)
	BB	**M**	849 - 632	**ML** (31°)
	GG	**W**	886 - 660	**MW** (43°)
	DB	**N**	935 - 696	
	GR			
				HONEYCOMB
C00712 HC	**WH**	**A**	715 - 317	**SP** (14°)
	BB	**M**	849 - 376	**ML** (31°)
	GG	**W**	886 - 392	
	DB	**N**	935 - 414	
	GR			

Electronics: **BV** (pag 474) | Accessories: (pag 474)

Shaker | arrayLED





IK10 IP66

	Cct	lm S - lm D	Opt
220-240 V AC - 14 W DC - 15 W AC			
WH **84527**	**A**	2033 - 1118	**15** (13°)
BB **84528**	**M**	2304 - 1262	**30** (26°)
GG **84529**	**W**	2452 - 1349	**60** (53°)
DB **84530**	**N**	2463 - 1350	
GR **77609**			

IK10 IP66


	Cct	lm S - lm D	Opt
220-240 V AC - Led-Direct 11,5 W AC			
WH **76182**	**W**	1267 - 827	**15** (12°)
BB **76183**	**N**	1316 - 860	**30** (29°)
GG **76184**			**50** (43°)
DB **76185**			
GR **77612**			

Accessories: (pag 474)

DESIGNING OUTDOOR SPACES WITHOUT LIMITS AND CONSTRAINTS

A versatile and technological outdoor projector with IP66 protection rating. The fixture is made from epoxy powder-coated die-cast aluminium in the finishes: white, black, grey, dark brown, green. Shaker is designed for wall, ceiling and ground applications with the relative stake accessory.





220-240 V

Electronics

BV

C-E200008	99186	C-E200002
ON/OFF	ON/OFF	DALI/PUSH
1 - 2 art.	2 - 4 art.	2 - 4 art.
135 x 26 x h 26	117 x 92 x h 38	125 x 45 x h 30
35		55

Accessories



IS **98669** Steel peg L 101 mm
suitable for: Shaker Ø43 mm



PLC **89371** Peg L204 mm
suitable for: Shaker Ø62 mm / Shaker Ø99 mm

IS **98624** Steel peg Ø10x160 mm
IS **C-F500002** Steel peg Ø10x700 mm
IS **C-F500003** Steel peg Ø10x1000 mm
suitable for: Shaker Ø43 mm / Shaker Ø62 mm



BB **83246** Anti-glare Ø49x40 mm
suitable for: Shaker Ø43 mm



BB **C-U300018** Anti-glare Ø70x50 mm
suitable for: Shaker Ø62 mm



BB **99819** Anti-glare Ø106x75 mm
suitable for: Shaker Ø99 mm

Finishes
IS Steel
PLC Polycarbonate







IRIS67

Aluminium body.

Iris67 | arrayLED | 630 mA | 6 W DC






	Cct	lm S - lm D	Opt
WH 84537	M	751 - On req	85 (15°-45°)
BB 84538	W	783 - On req	
GG 84539	N	826 - On req	

Electronics: **BI** (pag 478) | Accessories: (pag 478)

Iris67 | arrayLED | 350 mA | 13 W DC






	Cct	lm S - lm D	Opt
WH 84540	M	2015 - On req	85 (15°- 62°)
BB 84541	W	2100 - On req	
GG 84542	N	2156 - On req	

Electronics: **BG** (pag 478) | Accessories: (pag 478)

Iris67 | arrayLED | 630 mA | 22 W DC






	Cct	lm S - lm D	Opt
WH 84543	M	3378 - On req	85 (16°- 52°)
BB 84544	W	3593 - On req	
GG 84545	N	3610 - On req	

Electronics: **BR** (pag 478) | Accessories: (pag 478)

Iris67 | arrayLED | 840 mA | 30 W DC





	Cct	lm S - lm D	Opt
WH 84546	M	4452 - On req	85 (15°- 56°)
BB 84547	W	4741 - On req	
GG 84548	N	4865 - On req	

Electronics: **BT** (pag 478) | Accessories: (pag 478)



Adjustable Focus Optics (85)

Iris67 allows the beam to be adapted to the targeting requirements in outdoor environments. The adjustable ring nut makes it possible to calibrate the beam width, which varies according to the model chosen, making targeting easy and accurate. The simplified focus clamping system allows for a beam width that exactly matches the gradient marked along the bezel.

Elliptic Optics

The Iris67 Elliptic allows the beam width to be adjusted accurately by rotating a specially designed ring nut. A second ring nut moves a filter, which is located at the end of the luminaire. By increasing or decreasing the distance of the filter from the main lens, the shape of the light beam can be altered, resulting in elliptical lighting. This is ideal for highlighting architectural and urban features, or accentuating details in gardens and outdoor spaces.

Finishes


WH White GG Grey
BB Black

Cct

M 2700 **N** 4000
W 3000

Iris67 Elliptic | arrayLED | 630 mA | 6 W DC






C.C. IK10 IP67

	Cct	lm S - lm D	Opt
WH 84549	M	751 - On req	88 (15°-45°)
BB 84550	W	783 - On req	
GG 84551	N	826 - On req	

Electronics: **BI** (pag 478) | Accessories: (pag 478)

Iris67 Elliptic | arrayLED | 350 mA | 13 W DC






C.C. IK10 IP67

	Cct	lm S - lm D	Opt
WH 84552	M	2015 - On req	88 (15°- 62°)
BB 84553	W	2100 - On req	
GG 84554	N	2156 - On req	

Electronics: **BG** (pag 478) | Accessories: (pag 478)

Iris67 Elliptic | arrayLED | 630 mA | 22 W DC






C.C. IK10 IP67

	Cct	lm S - lm D	Opt
WH 84555	M	3378 - On req	88 (16°- 52°)
BB 84556	W	3593 - On req	
GG 84557	N	3610 - On req	

Electronics: **BR** (pag 478) | Accessories: (pag 478)

Iris67 Elliptic | arrayLED | 840 mA | 30 W DC





C.C. IK10 IP67

	Cct	lm S - lm D	Opt
WH 84558	M	4452 - On req	88 (15°- 56°)
BB 84559	W	4741 - On req	
GG 84560	N	4865 - On req	

Electronics: **BT** (pag 478) | Accessories: (pag 478)

Electronics

BI

C-E200008
ON/OFF
1 - 2 art.
135 x 26 x h 26
35

99186
ON/OFF
2 - 4 art.
117 x 92 x h 38

C-E200002
DALI/PUSH
2 - 4 art.
125 x 45 x h 30
55

BG

C-E200006
ON/OFF
1 art.
135 x 26 x h 26
35

C-E200004
DALI/PUSH
1 art.
125 x 45 x h 30
55

BR

99186
ON/OFF
1 art.
117 x 92 x h 38

C-E200002
DALI/PUSH
1 art.
125 x 45 x h 30
55

BT

99269
ON/OFF
1 art.
117 x 92 x h 38

Accessories

IS **84890** Steel peg Ø17x250 mm
IS **98112** Steel peg Ø17x700 mm
IS **C-F500001** Steel peg Ø17x1000 mm
suitable for: Iris67 - Iris67 Elliptic



KRUJË CASTLE
Rruga Kala, Krujë (Albania)

Lighting Designer:
Fulvio Baldeschi

Photography:
Pietro Savorelli

CLIVO

Brass or AISI 316L stainless steel body.
Extra-clear tempered glass diffuser.




ID

Driver on board

Brass




White Black Chrome Nickel Dark Brown Steel Green



By turning the built-in ring nut, it is possible to adjust the width of the light beam, from a 10° angle up to a 60° angle.

Clivo | powerLED | 220-240 V AC | 1,6 W DC - 3 W AC






IP66 ID

		Cct	Im S - Im D	Opt
WH	83571	M	233 - On req	85 (10°-60°)
BB	83572	W	249 - On req	
CH	83575	N	266 - On req	
NK	83574			
DB	83573			
BS	83576			
IS	83577			
GR	77615			

Steel version (IS): body made of AISI 316 L steel

Clivo | powerLED | 630 mA | 2 W DC





III C.C. IP66


		Cct	Im S - Im D	Opt
WH	84561	M	233 - On req	85 (10°- 66°)
BB	84562	W	249 - On req	
CH	97072	N	266 - On req	
NK	97071			
DB	84563			
BS	81473			
IS	97073			
GR	77613			

Steel version (IS): body made of AISI 316 L steel

Electronics: **BD** (pag 481) | Accessories: (pag 481)

Clivo_SL | powerLED | 350 mA | 4 W DC





III C.C. IP66

		Cct	Im S - Im D	Opt
WH	84564	M	490 - On req	85 (10°- 60°)
BB	84565	W	490 - On req	
CH	90404	N	529 - On req	
NK	90403			
DB	84566			
BS	81474			
GR	77614			

Electronics: **BE** (pag 481) | Accessories: (pag 481)

Accessories

IS **84890** Steel peg Ø17x250 mm
IS **98112** Steel peg Ø17x700 mm
IS **C-F500001** Steel peg Ø17x1000 mm
suitable for: Clivo / Clivo_SL



BB **98513** Anti-glare
suitable for: Clivo

Electronics

BD

89420	C-E200008	99186	C-E200002
ON/OFF	ON/OFF	ON/OFF	DALI/PUSH
1 - 2 art.	3 - 6 art.	6 - 12 art.	5 - 12 art.
74 x 65 x h 27	135 x 26 x h 26	117 x 92 x h 38	125 x 45 x h 30
	35		55

BE

89421	C-E200006	C-E200004
ON/OFF	ON/OFF	DALI/PUSH
1 art.	2 - 3 art.	2 - 3 art.
74 x 65 x h 27	135 x 26 x h 26	125 x 45 x h 30
	35	55

Finishes
WH White CH Chrome DB Dark Brown IS Steel
BB Black NK Nickel BS Brass GR Green

Cct
M 2700 N 4000
W 3000

CLARK316

AISI 316L stainless steel body.
Extra-clear tempered glass diffuser.



PROJECTOR FULL STEEL: DESIGNED FOR CHALLENGING CONDITIONS

IP68

Clark_316 is an outdoor projector/floodlight constructed entirely of AISI 316 stainless steel, which provides reliable performance, even in highly saline environments. Strong and durable, it is ideal for outdoor spaces that are exposed to the elements. It provides effective, long-lasting illumination, helping to enhance outdoor environments.





Clark316
Honeycomb version



Clark316
4,3 W AC - Ø 73



Clark316
13,3 W AC - Ø 112




Clark316
17,5 W AC - Ø 147



Clark316
26,5 W AC - Ø 190

Clark316 | arrayLED





	Fin	Cct	lm S - lm D	Opt
220-240 V AC - 3,2 W DC - 4,3 W AC				
C00140	**SE**	**M**	482 - 365	**SP** (11°)
		W	500 - 379	**ML** (30°)
		N	526 - 398	**MW** (45°)
C00141 HC	**SE**	**M**	482 - 269	**SP** (11°)
		W	500 - 279	**FL** (27°)
		N	526 - 294	**ML** (37°)


Accessories: (pag 485)

	Fin	Cct	lm S - lm D	Opt
C.C. 350 mA - 3,2 W DC				
C00156	**SE**	**M**	482 - 365	**SP** (11°)
		W	500 - 379	**ML** (30°)
		N	526 - 398	**MW** (45°)
C00157 HC	**SE**	**M**	482 - 269	**SP** (11°)
		W	500 - 279	**FL** (27°)
		N	526 - 294	**ML** (37°)

Electronics: **BN** (pag 485) | Accessories: (pag 485)

Clark316 | arrayLED | 220-240 V AC







	Fin	Cct	lm S - lm D	Opt
11 W DC - 13,3 W AC				
C00142	**SE**	**M**	1477 - 1133	**SP** (10°)
C00143 HC		**W**	1541 - 1181	**FL** (22°)
		N	1581 - 1216	**ML** (36°)
DALI 9 W DC - 13 W AC				
C00158	**SE**	**M**	1265 - 970	**SP** (10°)
C00159 HC		**W**	1320 - 1011	**FL** (22°)
		N	1354 - 1041	**ML** (36°)

Accessories: (pag 485)

Clark316 | arrayLED | 220-240 V AC







	Fin	Cct	lm S - lm D	Opt
15,5 W DC - 17,5 W AC				
C00154	**SE**	**M**	2427 - 1863	**SP** (16°)
DALI		**W**	2529 - 1978	**ML** (32°)
C00160		**N**	2670 - 2089	**WF** (54°)
C00155 HC	**SE**	**M**	2427 - 1418	**SP** (15°)
DALI		**W**	2529 - 1478	**FL** (29°)
C00161 HC		**N**	2670 - 1561	**MW** (45°)

Accessories: (pag 485)

Clark316 | arrayLED | 220-240 V AC





	Fin	Cct	lm S - lm D	Opt
25 W DC - 26,5 W AC				
C00773	**SE**	**M**	3851 - 2976	**SP** (15°)
DALI		**W**	4011 - 3099	**FL** (26°)
C00775		**N**	4116 - 3193	**ML** (34°)
C00774 HC	**SE**	**M**	3851 - 2326	**SP** (14°)
DALI		**W**	4011 - 2415	**FL** (24°)
C00776 HC		**N**	4116 - 2496	**ML** (30°)

Accessories: (pag 485)



Electronics

BN

89421	**C-E200006**	**C-E200004**
ON/OFF	ON/OFF	DALI/PUSH
1 - 2 art.	2 - 4 art.	2 - 4 art.
74 x 65 x h 27	135 x 26 x h 26	125 x 45 x h 30
	35	55

Accessories

IS **84890**	Steel peg Ø17x250 mm
IS **98112**	Steel peg Ø17x700 mm
IS **C-F500001**	Steel peg Ø17x1000 mm

suitable for: Clark316



PLC **98549** Peg L204 mm

suitable for: Clark316

Finishes	Cct				Accessories	Projectors
IS Stainless Steel	**M**	2700	**N**	4000	HC Honeycomb	485
	W	3000				


VUELTA

Aluminium body.
Transparent glass diffuser.



Vuelta_Y | arrayLED | 220-240 V AC | 13,5 W DC - 16 W AC






IK09 IP65

	Cct	lm S - lm D	Opt
GG **64522**	**M**	1676 - 994	**07** (Asym. Ww)
BG **64523**	**W**	1750 - 1038	
	N	1794 - 1064	

Accessories: (pag 487)

Vuelta_Y | arrayLED | 220-240 V AC | 30 W DC - 32 W AC





IK09 IP65

	Cct	lm S - lm D	Opt
GG **64530**	**M**	4323 - 3316	**07** (Asym. Ww)
BG **64531**	**W**	4520 - 3453	
	N	4620 - 3544	

Accessories: (pag 487)



Peg



Angular bracket



Grid




Pole




Pole kit


Accessories




PLC **14931** Peg
suitable for: Vuelta_Y




BB **64534** Grid
suitable for: Vuelta_Y



GG **64532** Pole kit
BG **64533** Pole kit
suitable for: Vuelta_Y



GG **64538** Angular bracket
BG **64539** Angular bracket
suitable for: Vuelta_Y



GG **64536** Pole
BG **64537** Pole
suitable for: Vuelta_Y

Finishes


GG Grey
BG Black/Grey
PLC Polycarbonate

Cct

M 2700 **N** 4000
W 3000


PROLAMP

Body in die-cast aluminium, tempered glass.



Prolamp | powerLED | 220-240 V AC - 59 W DC - 64 W AC





IK08 IP67

	Cct	Im S - Im D	Opt	
BB **81946**	**W**	6416 - 4566	**06**	(12°)
	N	6926 - 4927	**25**	(15°x 44°)

Accessories and cables: (pag 491)

C.V. IK08 IP67 DMX RDM +RGBW


	Cct		Opt	
RGBW - 59 W DC 48V				
BB **81949**	**V**	RGBW (3000 K)	**06**	(12°)
	Q	RGBW (4000 K)	**15**	(20°÷ 29°)
			30	(30°÷ 39°)
			25	(15°x 44°)

In-out cable included

Electronics: **AM8** (pag 491) | Accessories and cables: (pag 491)

Prolamp | V2 | powerLED | 220-240 V AC | 133 W DC - 150 W AC





IK08 IP66 NEW

	Fin	Cct	Im S - Im D	Opt	
C00975	BB	**M**	13518 - 10595	**SP**	(12°)
		W	13518 - 10595	**ES**	(14°x 46°)
		N	14598 - 11445		

Accessories and cables: (pag 491)

IK08 IP66 NEW DMX RDM +RGBW

	Fin	Cct	Im S - Im D	Opt	
C00974	BB	**V**	RGBW (3000 K)	**SP**	(12°)
		Q	RGBW (4000 K)	**ES**	(14°x 46°)

In-out cable included

Electronics: **AM4** (pag 491) | Accessories and cables: (pag 491)




Finishes


BB Black

Cct

M 2700 **N** 4000 **V** RGBW (3000 K)
W 3000 **Q** RGBW (4000 K)

Prolamp | arrayLED | 220-240 V AC | 35 W DC - 40 W AC







IK08 IP66

	Cct	lm S - lm D	Opt
BB **82270**	**W**	5206 - 3820	**30** (21°)
	N	5343 - 3909	**60** (54°)
DALI	**C**	5405 - 4045	**90** (93°)
BB **82271**			**12** (65°x 89°)
			07 (Asym. Ww)

Accessories: (pag 491)

Prolamp | arrayLED | 220-240 V AC | 71 W DC - 80 W AC







IK08 IP66

	Cct	lm S - lm D	Opt
BB **82272**	**W**	10257 - 7837	**30** (27°)
	N	10519 - 8044	**60** (57°)
DALI	**C**	10643 - 8312	**90** (91°)
BB **82273**			**12** (75°x 80°)
			07 (Asym. Ww)

Accessories: (pag 491)

Prolamp | arrayLED | 220-240 V AC | 90 W DC - 100 W AC







IK08 IP66

	Cct	lm S - lm D	Opt
BB **84068**	**W**	14768 - 12410	**30** (22°)
	N	15146 - 12737	**60** (55°)
DALI	**C**	15322 - 12989	**90** (90°)
BB **84441**			**12** (89°x 95°)
			07 (Asym. Ww)

Accessories: (pag 491)

Prolamp | arrayLED | 220-240 V AC







IK08 IP66

	Cct	lm S - lm D	Opt
110 W DC - 120 W AC			
BB **82274**	**W**	18110 - 14278	**30** (27°)
	N	18572 - 14624	**60** (59°)
DALI	**C**	18792 - 15108	**90** (91°)
BB **82275**			**12** (105°)
			07 (Asym. Ww)
144 W DC - 150 W AC			
BB **84069**	**W**	22338 - 17804	**30** (27°)
	N	22908 - 18180	**60** (60°)
DALI	**C**	23178 - 18600	**90** (90°)
BB **84442**			**12** (108°)
			07 (Asym. Ww)

Accessories: (pag 491)

Prolamp | arrayLED | 220-240 V AC





IK08 IP66

	Cct	lm S - lm D	Opt
170 W DC - 180 W AC			
BB **82286**	**W**	25248 - 19824	**30** (22°)
	N	26178 - 20491	**60** (53°)
DALI	**C**	26481 - 20991	**90** (92°)
BB **82287**			**12** (95°x 110°)
			07 (Asym. Ww)
185 W DC - 200 W AC			
BB **84070**	**W**	30771 - 23580	**30** (28°)
	N	31557 - 24075	**60** (61°)
DALI	**C**	31929 - 24637	**90** (90°)
BB **84443**			**12** (97°x 110°)
			07 (Asym. Ww)

Accessories: (pag 491)

Electronics

AM4

DMX
Controllers
Pag. 963

C-E700026
DMX/RDM addresser

98986
120 Ohm DMX line closure

98985/99390
Splitter ALLinONE Start & Continuity
Pag. 972

AM8

99785
ON/OFF
240W CV 48V
244 x 71 x h 38

DMX
Controllers
Pag. 963

C-E700026
DMX/RDM addresser

98986
120 Ohm DMX line closure

98985/99390
Splitter ALLinONE Start & Continuity
Pag. 972

Cables

On/Off 190-250V AC | Cables



BB **99057** Conn. F.3 pin (L 2m)

suitable for: Prolamp 59 W - 133 W

On/Off 190-250V AC | Extension cables



BB **98147** Conn. M. / F. 3 pin (L 5m)
BB **98146** Conn. M. / F. 3 pin (L 10m)

suitable for: Prolamp 59 W - 133 W



PVC **99390** ALLinONE splitter power/DMX_Continuity splitter
PVC **98985** ALLinONE splitter power/DMX_Start splitter

Pag. 972

AllinOne DMX cable 190-250V AC | Cables



BB **98660** F. 6 pin (L 1m)
BB **98661** F. 6 pin (L 5m)

suitable for: Prolamp RGBW

AllinOne DMX 190-250V AC | Extension cables



BB **98662** M. / F. 6 pin (L 1m)
BB **98663** M. / F. 6 pin (L 5m)

suitable for: Prolamp RGBW



BB **98986** ALLinONE splitter power/DMX_DMX line closure adapter

Pag. 972

Accessories



IS **99391** 35W
IS **99392** 71/90W
IS **99574** 110/144W
IS **83035** 133/170/185W

Protective cage in steel wire, ideal for increasing the impact resistance of the fixture.

suitable for: Prolamp



On request Directional flaps - shaper

suitable for: Prolamp 59W - 133W / Prolamp RGBW



Prolamp optic 30 - 60 - 90



Prolamp optic 07



Prolamp optic 12

Finishes

BB Black


BIGLAMP

Body in die-cast aluminium, tempered glass,
EPD treated iron bracket, power-coated in.



Biglamp | powerLED | 220-240 V AC | 280 W DC - 300 W






0,6 m | OVP | ESD | IP66 | IK08 | 0,01 | 0,13

	Cct	lm S - lm D	Opt
AL 82424	W	42795 - 31198	15 (25°)
	N	46155 - 33654	30 (38°)
	C	46155 - 33654	60 (62°)
			07 (Asym. Ww)

Biglamp | powerLED | 220-240 V AC | 2 x 280 W DC - 2 x 300 W AC






0,6 m | OVP | ESD | IP66 | IK08 | 0,04 | 0,32

	Cct	lm S - lm D	Opt
AL 82425	W	85590 - 62534	15 (25°)
	N	92310 - 67327	30 (38°)
	C	92310 - 67327	60 (62°)
			07 (Asym. Ww)

Biglamp | powerLED | 220-240 V AC | 3 x 280 W DC - 3 x 300 W AC






0,6 m | OVP | ESD | IP66 | IK08 | 0,05 | 0,40

	Cct	lm S - lm D	Opt
AL 82426	W	128385 - 93613	15 (25°)
	N	138465 - 100991	30 (38°)
	C	138465 - 100991	60 (62°)
			07 (Asym. Ww)

Construction details

The body of the LED module is made of EN AB 46100 die-cast untreated aluminium while the fastening bracket is in EPD treated iron with a final RAL9006 grey powder coating. All the light fixture's screws are in AISI 316 stainless steel. The optics are in high yield transparent polycarbonate with anti UV ray protection in six different versions: Spot, Flood, Medium Flood, Wide Flood, Elliptic e Asymmetrical. The fixture's IP66 protection grade and the IK08 seal are ensured by an anti-UV silicone gasket and retaining springs in black galvanised stainless steel designed to compensate for the item's thermal expansion and to guarantee the integrity of the glass over time. The front protective glass is 4 mm thick.

0/1-10V | DMX RDM | DALI



Finishes


AL Aluminium

Cct

W 3000 **C** 5700
N 4000

Biglamp Pro | powerLED | 450 W DC





1 m | 0,01 | 0,13

	Cct	lm S - lm D	Opt	
C.C. - 3600 mA				
AL **84432**	**N**	78781 - 53385	**15**	(19°x 23°)
	C	78781 - 53385	**20**	(21°x 26°)
			35	(35°x 43°)
			60	(61°x 66°)
			23	(28°x 40°)
			26	(22°x 26°)

Electronics: **HA** (pag 495)

C.C. - 2700 mA				
AL **84435**	**N**	76720 - 56684	**10**	(12°)
	C	76720 - 56684	**15**	(15°x 21°)
			30	(28°x 39°)
			60	(56°x 63°)
			23	(22°x 38°)
			26	(19°x 26°)


Electronics: **HB** (pag 495)

C.C. - 2500 mA				
AL **84438**	**N**	66666 - 46324	**07**	(Asym. Ww)
	C	66666 - 46324		

Electronics: **HC** (pag 495)

Biglamp Pro | powerLED | 2 x 450 W DC





1 m | 0,04 | 0,32

	Cct	lm S - lm D	Opt	
C.C. - 3600 mA/module				
AL **84433**	**N**	157562 - 106769	**15**	(19°x 23°)
	C	157562 - 106769	**20**	(21°x 26°)
			35	(35°x 43°)
			60	(61°x 66°)
			23	(28°x 40°)
			26	(22°x 26°)

Electronics for single module: **HA** (pag 495)


C.C. - 2700 mA/module				
AL **84436**	**N**	153440 - 113344	**10**	(12°)
	C	153440 - 113344	**15**	(15°x 21°)
			30	(28°x 39°)
			60	(56°x 63°)
			23	(22°x 38°)
			26	(19°x 26°)

Electronics for single module: **HB** (pag 495)

C.C. - 2500 mA/module				
AL **84439**	**N**	133332 - 92648	**07**	(Asym. Ww)
	C	133332 - 92648		

Electronics for single module: **HC** (pag 495)

The Driver and Control equipment is to be considered for each individual module (2x)



Installation on light tower


The Biglamp protector design was conceived to make installation and directing of the light beam as easy as possible. Considering the possibility of swivelling the projector and the individual modules, Biglamp is ideal for applications on any type of light tower.


Aiming

Projector aiming service is available on request.

LASER Guide

Biglamp Pro | powerLED | 3 x 450 W DC





1 m | 0,05 | 0,40

	Cct	lm S - lm D	Opt	
C.C. - 3600 mA/module				
AL **84434**	**N**	236343 - 160159	**15**	(19°x 23°)
	C	236343 - 160159	**20**	(21°x 26°)
			35	(35°x 43°)
			60	(61°x 66°)
			23	(28°x 40°)
			26	(22°x 26°)

Electronics for single module: **HA** (pag 495)

C.C. - 2700 mA/module				
AL **84437**	**N**	230160 - 170044	**10**	(12°)
	C	230160 - 170044	**15**	(15°x 21°)
			30	(28°x 39°)
			60	(56°x 63°)
			23	(22°x 38°)
			26	(19°x 26°)

Electronics for single module: **HB** (pag 495)

C.C. - 2500 mA/module				
AL **84440**	**N**	199998 - 138971	**07**	(Asym. Ww)
	C	199998 - 138971		

Electronics for single module: **HC** (pag 495)

The Driver and Control equipment is to be considered for each individual module (3x)

Electronics

HA

83212	83211	83030	83031	Controller
Input 220 V AC ON/OFF, 0/1-10V 262 x 125 x h 44	Input 380 V AC ON/OFF, 0/1-10V 262 x 125 x h 44	Signal converter DALI to 0/1-10V 53 x 27 x h 22	Signal converter DMX to 0/1-10V 90 x 38 x h 27	DALI pag 954-955 DMX pag 963

HB

83216	83215	83030	83031	Controller
Input 220 V AC ON/OFF, 0/1-10V 262 x 125 x h 44	Input 380 V AC ON/OFF, 0/1-10V 262 x 125 x h 44	Signal converter DALI to 0/1-10V 53 x 27 x h 22	Signal converter DMX to 0/1-10V 90 x 38 x h 27	DALI pag 954-955 DMX pag 963

HC

83218	83217	83030	83031	Controller
Input 220 V AC ON/OFF, 0/1-10V 262 x 125 x h 44	Input 380 V AC ON/OFF, 0/1-10V 262 x 125 x h 44	Signal converter DALI to 0/1-10V 53 x 27 x h 22	Signal converter DMX to 0/1-10V 90 x 38 x h 27	DALI pag 954-955 DMX pag 963

Installation applications



Biglamp:

- Industry
- Gyms and sports centres
- Indoor sports activities and under tensile structures
- Tennis courts
- Basketball courts
- Volleyball courts
- Ice hockey rinks
- Large areas requiring continuous lighting

Biglamp Pro:

- Stadiums
- Medium-large football pitches
- Racecourses
- Race tracks
- Rugby pitches
- Baseball diamonds
- Golf courses
- Sports clubs with outdoor activities
- Ski slopes

Finishes

AL Aluminium

Cct


N 4000
C 5700

H-FARM
Treviso (Italy)

Project: Zanon Architetti Associati

Lighting Designer:
Linea Light Group

Photography:
Thestudio











TELEVISION LIGHTING CONSISTENCY INDEX

On request, the fixtures are available with a colour rendering index of ≥90 and colour temperature of 5700K. With these characteristics, the light fixtures are in compliance with TV broadcasting requirements with filming in HDTV and super slow motion quality.



WALL & CEILING

PRIVATE HOME
Madrid (Spain)

Lighting Designer:
Oscar Abril Revuelta

Photography:
Marek Jarosz



Wall & Ceiling range index

Portik

Portik_R
NEW

503-504

Portik_Q
NEW

504-505

Skin_S

Skin_S

509

Stadium

Stadium

511

Cubit

Cubit

516-520

Cubit Pro

516-521

Vedette

Vedette_R

525

Vedette_Q


526-529


Nail

Nail_W

531

Cem

Cem_C

533

Cem_W

533

Cem_WF

533

Skin_W

Skin_WF

537-540

Skin_WL

537-540

Skin_WY

541


PORTIK

Aluminium body.



Portik_R | V2 | arrayLED





IP65 IK08 NEW

	Fin	Cct	lm S - lm D	Opt
220-240 V AC - 6,5 W DC - 7,5 W AC				
C00467	**WH**	**M**	925 - 679	**SP** (15° UGR<16)
	BB	**W**	965 - 709	**ML** (37° UGR<16)
	GG	**N**	990 - 727	**WF** (50° UGR<19)
	DB			
				HONEYCOMB
C00480 HC	**WH**	**M**	925 - 493	**SP** (14° UGR<16)
	BB	**W**	965 - 515	**ML** (33° UGR<16)
	GG	**N**	990 - 528	**MW** (44° UGR<16)
	DB			


C.C. IP65 IK08 NEW

	Fin	Cct	lm S - lm D	Opt
350mA - 6,5 W DC				
C00468	**WH**	**M**	925 - 679	**SP** (15° UGR<16)
	BB	**W**	965 - 709	**ML** (37° UGR<16)
	GG	**N**	990 - 727	**WF** (50° UGR<19)
	DB			
				HONEYCOMB
C00481 HC	**WH**	**M**	925 - 493	**SP** (14° UGR<16)
	BB	**W**	965 - 515	**ML** (33° UGR<16)
	GG	**N**	990 - 528	**MW** (44° UGR<16)
	DB			

Electronics: **BZ** (pag 507)

Portik_R | V2 | arrayLED





IP65 IK08 NEW

	Fin	Cct	lm S - lm D	Opt
220-240 V AC - 14 W DC - 15,8 W AC				
C00471	**WH**	**M**	2275 - 1668	**SP** (16° UGR<16)
	BB	**W**	2371 - 1741	**ML** (36° UGR<16)
	GG	**N**	2434 - 1787	**WF** (51° UGR<19)
	DB			
				HONEYCOMB
C00482 HC	**WH**	**M**	2275 - 1228	**SP** (15° UGR<11)
	BB	**W**	2371 - 1281	**ML** (32° UGR<11)
	GG	**N**	2434 - 1315	**MW** (45° UGR<16)
	DB			

Accessories: (pag 507)


IP65 IK08 NEW **DALI**

	Fin	Cct	lm S - lm D	Opt
DALI - 220-240 V AC - 14 W DC - 15,8 W AC				
C00483	**WH**	**M**	2275 - 1668	**SP** (16° UGR<16)
	BB	**W**	2371 - 1741	**ML** (36° UGR<16)
	GG	**N**	2434 - 1787	**WF** (51° UGR<19)
	DB			
				HONEYCOMB
C00484 HC	**WH**	**M**	2275 - 1228	**SP** (15° UGR<11)
	BB	**W**	2371 - 1281	**ML** (32° UGR<11)
	GG	**N**	2434 - 1315	**MW** (45° UGR<16)
	DB			

Accessories: (pag 507)

Portik_R | arrayLED







IP65 IK08

	Cct	lm S - lm D	Opt
220-240 V AC - 25 W DC - 28 W AC			
WH **81877**	**M**	3851 - 2753	**15** (18° UGR<16)
BB **81878**	**W**	4011 - 2868	**30** (26° UGR<16)
GG **81879**	**N**	4116 - 2943	**60** (56°)
DB **81880**			
220-240 V AC - 34 W DC - 39 W AC			
WH **81371**	**M**	4998 - 3169	**15** (18° UGR<19)
BB **81372**	**W**	5206 - 3301	**30** (26° UGR<19)
GG **81373**	**N**	5342 - 3387	**60** (56°)
DB **81374**			
DALI - 220-240 V AC - 33 W DC - 36 W AC			**DALI**
WH **81885**	**M**	4777 - 3654	**15** (18° UGR<19)
BB **81886**	**W**	4976 - 3807	**30** (26° UGR<19)
GG **81887**	**N**	5106 - 3906	**60** (56°)
DB **81888**			

Portik_Q | V2 | arrayLED





IP65 IK07 NEW

	Fin	Cct	lm S - lm D	Opt
220-240 V AC - 7 W DC - 8,5 W AC				
C00726	**WH**	**M**	1041 - 789	**SP** (15° UGR<16)
	BB	**W**	1087 - 823	**ML** (38° UGR<16)
	GG	**N**	1114 - 844	**WF** (50° UGR<16)
	DB			
				HONEYCOMB
C00727 HC	**WH**	**M**	1041 - 567	**SP** (14° UGR<11)
	BB	**W**	1087 - 591	**ML** (33° UGR<11)
	GG	**N**	1114 - 606	**MW** (43° UGR<11)
	DB			

III C.C. IP65 IK07 NEW

	Fin	Cct	lm S - lm D	Opt
200 mA - 6,5 W DC				
C00728	**WH**	**M**	1041 - 789	**SP** (15° UGR<16)
	BB	**W**	1087 - 823	**ML** (38° UGR<16)
	GG	**N**	1114 - 844	**WF** (50° UGR<16)
	DB			
				HONEYCOMB
C00729 HC	**WH**	**M**	1041 - 567	**SP** (14° UGR<11)
	BB	**W**	1087 - 591	**ML** (33° UGR<11)
	GG	**N**	1114 - 606	**MW** (43° UGR<11)
	DB			

Electronics: **BF** (pag 507)


HOUSE DG
Rossano Veneto – Vicenza (Italy)

Project: and Lighting Designer:
Didonè Comacchio Architects (Arch. Paolo Didonè, Arch. Devvy Comacchio)



Portik_Q | V2 | arrayLED





IP65 IK07 NEW

	Fin	Cct	lm S - lm D	Opt
220-240 V AC - 14 W DC - 15,8 W AC				
C00746	**WH**	**M**	2275 - 1621	**SP** (16° UGR<16)
	BB	**W**	2371 - 1691	**ML** (37° UGR<16)
	GG	**N**	2434 - 1735	**WF** (52° UGR<16)
	DB			
				HONEYCOMB
C00747 HC	**WH**	**M**	2275 - 1191	**SP** (15° UGR<11)
	BB	**W**	2371 - 1242	**ML** (32° UGR<11)
	GG	**N**	2434 - 1274	**MW** (46° UGR<11)
	DB			

Accessories: (pag 507)


IP65 IK07 NEW **DALI**

	Fin	Cct	lm S - lm D	Opt
DALI - 220-240 V AC - 14 W DC - 15,8 W AC				
C00748	**WH**	**M**	2275 - 1621	**SP** (16° UGR<16)
	BB	**W**	2371 - 1691	**ML** (37° UGR<16)
	GG	**N**	2434 - 1735	**WF** (52° UGR<16)
	DB			
				HONEYCOMB
C00749 HC	**WH**	**M**	2275 - 1191	**SP** (15° UGR<11)
	BB	**W**	2371 - 1242	**ML** (32° UGR<11)
	GG	**N**	2434 - 1274	**MW** (46° UGR<11)
	DB			

Accessories: (pag 507)

Portik_Q | V2 | arrayLED






IP65 IK07 NEW

	Fin	Cct	lm S - lm D	Opt
220-240 V AC - 25 W DC - 28 W AC				
C00756	**WH**	**M**	3851 - 2693	**SP** (17° UGR<16)
	BB	**W**	4011 - 2809	**ML** (33° UGR<16)
	GG	**N**	4116 - 2882	**WF** (54° UGR<19)
	DB			
				HONEYCOMB
C00757 HC	**WH**	**M**	3851 - 2019	**SP** (16° UGR<11)
	BB	**W**	4011 - 2105	**ML** (30° UGR<11)
	GG	**N**	4116 - 2160	**MW** (47° UGR<16)
	DB			
220-240 V AC - 32,5 W DC - 36 W AC				
C00758	**WH**	**M**	4777 - 3342	**SP** (17° UGR<16)
	BB	**W**	4976 - 3485	**ML** (33° UGR<16)
	GG	**N**	5106 - 3576	**WF** (54° UGR<19)
	DB			
				HONEYCOMB
C00759 HC	**WH**	**M**	4777 - 2505	**SP** (16° UGR<11)
	BB	**W**	4976 - 2612	**ML** (30° UGR<11)
	GG	**N**	5106 - 2680	**MW** (47° UGR<16)
	DB			
DALI - 220-240 V AC - 32,5 W DC - 36 W AC				**DALI**
C00760	**WH**	**M**	4777 - 3342	**SP** (17° UGR<16)
	BB	**W**	4976 - 3485	**ML** (33° UGR<16)
	GG	**N**	5106 - 3576	**WF** (54° UGR<19)
	DB			
				HONEYCOMB
C00761 HC	**WH**	**M**	4777 - 2505	**SP** (16° UGR<11)
	BB	**W**	4976 - 2612	**ML** (30° UGR<11)
	GG	**N**	5106 - 2680	**MW** (47° UGR<16)
	DB			



PORTIK REDEFINES THE CONCEPT OF ATMOSPHERE BY **GOING BEYOND INSTALLATION BOUNDARIES**



Electronics


BF

99342	**C-E200005**
ON/OFF	DALI/PUSH
1 art.	1 art.
100 x 80 x h 31	125 x 45 x h 30
	55

BZ

89421	**C-E200006**	**C-E200004**
ON/OFF	ON/OFF	DALI/PUSH
1 art.	1 - 2 art.	1 - 2 art.
74 x 65 x h 27	135 x 26 x h 26	125 x 45 x h 30
	35	55

Accessories



IS **C-F100018** Bracket for installation on stretch

suitable for: Portik_R Ø112 mm - Portik_Q 112x112 mm

Finishes

IS Steel




SKIN_S

Aluminium body.
Extra-clear tempered glass diffuser.

Skin_S | powerLED | 220-240 V AC






IK10 IP67

	Cct	lm S - lm D	Opt
6 W DC - 6,7 W AC			
WB **83864**	**M**	798 - 547	**15** (14°)
	W	852 - 582	**30** (32°)
	N	909 - 621	**45** (46°)
9,6 W DC - 11 W AC			
WB **83861**	**M**	1210 - 731	**15** (14°)
	W	1210 - 731	**30** (32°)
	N	1306 - 788	**45** (46°)

Recessed casings: (pag 509)

Skin_S | powerLED | 220-240 V AC





IK08 IP67


	Cct	lm S - lm D	Opt
10 W DC - 11,2 W AC			
WB **83871**	**M**	1330 - 875	**15** (15°)
	W	1420 - 931	**30** (32°)
	N	1515 - 994	**45** (46°)
16,2 W DC - 21 W AC			
WB **83868**	**M**	2016 - 1237	**15** (15°)
	W	2016 - 1237	**30** (32°)
	N	2177 - 1336	**45** (46°)

Recessed casings: (pag 509)



Semi-recessed:
Skin_S


Recessed casings



ABS **83123** L 175 mm
suitable for: Skin_S

ABS **83124** L 229 mm
suitable for: Skin_S

For installation: downlight on brickwork ceiling.



ABS **83125** L 175 mm
suitable for: Skin_S

ABS **83126** L 229 mm
suitable for: Skin_S

For installation: downlight on plasterboard ceiling, downlight on concrete ceiling.

Skin family

Skin_F _FL _Y



552

Skin_WF _WL _WY



534

Finishes	Cct			
WB White/Black	**M**	2700	**N**	4000
	W	3000		



PARKHOTEL EGERNER HÖFE
Rottach-Egern (Germany)
Project: LichtKompetenz
Lighting Designer: Joerg Krewinkel
Photography: Andreas Leder




STADIUM

Polycarbonate body.

Stadium | topLED | 220-240 V AC






IK10 IP65

	Cct	lm S - lm D	Opt
6,4 W DC - 7,8 W AC			
WH **76078**	**M**	1192 - 596	**00** (Diffused)
BB **76079**	**W**	1246 - 623	
	N	1291 - 647	


Stadium | Full light | topLED | 220-240 V AC






IK10 IP65

	Cct	lm S - lm D	Opt
6,4 W DC - 7,8 W AC			
OP **77186**	**M**	1192 - 678	**00** (Diffused)
	W	1246 - 709	
	N	1291 - 734	



White



Black



Opaline
77186 + 83247

Accessories



WH **83247**
BB **83248**

Inclined bracket
for wall installation

Finishes
WH White OP Opaline
BB Black

Cct
M 2700 **N** 4000
W 3000



CUBIT

Aluminium body.

CUBIT: THE PROTAGONISTS OF YOUR PROJECTS



*** White (WH)**



Grey (GG)



Black (BB)



Dark Brown (DB)

CUBIT is an essential luminaire that becomes the protagonist of your lighting project thanks to its extremely clean aesthetics. Its formal simplicity conceals sophisticated, cutting-edge technology in terms of lighting, optics and performance. The lower optical cell is recessed and without front glass in the PRO version; this allows the light to expand at its best without dazzling. The different combinations provided allow the designer to work with a wide range of possibilities, playing with symmetries and openings. CUBIT can illustrate a place by emphasising the distinctive architectural elements of a building, or it can transform an urban landscape by adding luminous signs or patterns on vertical surfaces.

***** The distinctive white finish of the Cubit and Cubit Pro models allows the luminaire to be painted. Colours can be customised, integrating the luminaire into the architectural landscape on which it is fitted.



CELL OPTICS **CUBIT PRO**: RECESSED, EFFICIENT, PERFORMING

Designed for an optimum comfort experience using black cell optics. This solution allows the optical compartment to be set back, thus reducing glare for a more comfortable and improved visual experience. On account of its unique design, this optical system can only be installed facing downwards.

FOUR DIMENSIONS FOR ENDLESS LIGHT EFFECTS



134x134x133 mm



114x114x113 mm



89x89x88 mm

OPTICS **CUBIT** SINGLE EMISSION (COB DIRECT 220-240 V AC)



15	**30**	**60**	**12**	**00**
Spot	Flood	M.W.Flood	E.W.Flood	Diffused

OPTICS **CUBIT** DOUBLE EMISSION (COB DIRECT 220-240 V AC)



15 15+15	**30** 30+30	**60** 60+60	**12** 12+12	**00** 00+00
Spot+ Spot	Flood+ Flood	M.W.Flood+ M.W.Flood	E.W.Flood+ E.W.Flood	Diffused+ Diffused

One or two light outputs (from opposite sides of the cube) and eight different beam openings: Ultra Spot, Spot, Medium Flood, Wide Flood, Extra Wide Flood, Diffused, Elliptic and Asymmetric. The combination of symmetrical and asymmetrical optics increases the possible effects, and thanks to its minimalist form, CUBIT can be positioned freely on the wall.



61x61x60 mm

HOW TO READ OPTICS COMBINATION



15 15+15

Optics code

Optics combination

Cct	lm S - lm D
uble emission - 5,2 W DC - 6,5 W AC	
77423	M 792 - 245
77424	W 850 - 263
77425	N 916 - 284
77426	

15	15+15 (10°÷19°)+(
30	30+30 (20°÷29°)+(
60	30+30 (40°÷49°)+(
12	30+30 (71°÷120°)+(

OPTICS **CUBIT PRO** SINGLE EMISSION



05 U.Spot

15 Spot

30 Flood

60 W.Flood

88 Elliptic

07 Asymmetric

12 E.W.Flood

00 Diffused

Only for 61x61x60 mm

OPTICS **CUBIT PRO** DOUBLE EMISSION



15 15+15 Spot+ Spot

30 30+30 Flood+ Flood

60 60+60 W.Flood+ W.Flood

15 15+05 Spot+ U.Spot

30 30+05 Flood+ U.Spot

60 60+05 W.Flood+ U.Spot

OPTICS **CUBIT PRO** DOUBLE EMISSION



15 07+15 Asymm+ Spot

30 07+30 Asymm+ Flood

60 07+60 Asymm+ W.Flood

30 30+15 Flood+ Spot

60 60+15 W.Flood+ Spot


12 12+12 E.W.Flood+ E.W.Flood

00 00+00 Diffused+ Diffused

Only for 61x61x60 mm

Cubit Pro | powerLED | 220-240 V AC





Optics design:



15 **30** **60** **12** **00**

IK08 IP65


	Cct	lm S - lm D	Opt	
Single emission - 2,6 W DC - 3,2 W AC				
WH **77413**	**M**	396 - 123	**15**	(10°÷ 19°)
BB **77414**	**W**	425 - 132	**30**	(20°÷ 29°)
GG **77415**	**N**	458 - 142	**60**	(40°÷ 49°)
DB **77416**			**12**	(71°÷ 120°)
			00	(Diffused)

IK08 IP65


	Cct	lm S - lm D	Opt	
Double emission - 5,2 W DC - 6,5 W AC				
WH **77418**	**M**	792 - 212	**30**	30+15 (20°÷29°)+(10°÷19°)
BB **77419**	**W**	850 - 228	**60**	60+15 (40°÷49°)+(10°÷19°)
GG **77420**	**N**	916 - 245		
DB **77421**				
WH **77423**	**M**	792 - 245	**15**	15+15 (10°÷19°)+(10°÷19°)
BB **77424**	**W**	850 - 263	**30**	30+30 (20°÷29°)+(20°÷29°)
GG **77425**	**N**	916 - 284	**60**	60+60 (40°÷49°)+(40°÷49°)
DB **77426**			**12**	12+12 (71°÷120°)+(71°÷120°)
			00	00+00 (Diff. + Diff.)

Cubit | arrayLED-Direct | 220-240 V AC





Optics design:



15/30/60 **12** **00**

IK08 IP65 **LED-DIRECT**


	Cct	lm S - lm D	Opt	
Single emission - 7 W AC				
WH **76649**	**W**	865 - 467	**15**	(21°)
BB **76650**	**N**	870 - 468	**30**	(27°)
GG **76651**			**60**	(45°)
DB **76652**				
WH **76634**	**W**	865 - 490	**12**	(82°)
BB **76635**	**N**	870 - 491	**00**	(Diffused)
GG **76636**				
DB **76637**				

IK08 IP65 **LED-DIRECT**

	Cct	lm S - lm D	Opt	
Double emission - 14 W AC				
WH **76654**	**W**	1730 - 938	**15**	15+15 (21°+ 21°)
BB **76655**	**N**	1740 - 940	**30**	30+30 (27°+ 27°)
GG **76656**			**60**	60+60 (45°+ 45°)
DB **76657**				
WH **76639**	**W**	1730 - 980	**12**	12+12 (82°+ 82°)
BB **76640**	**N**	1740 - 981	**00**	00+00 (Diff. + Diff.)
GG **76641**				
DB **76642**				

Cubit Pro | Single emission | arrayLED





Optics design:



05 | Down **Cell**: **15/30/60** | Elliptic **88** Asym.Ww **07**

IK08 IP65

	Cct	Im S - Im D	Opt	
220-240 V AC - 6,7 W DC - 8,7 W AC				
WH **76584**	**M**	849 - 608	**05**	(6°)
BB **76585**	**W**	886 - 635	**15**	(15° Cell)
GG **76586**	**N**	935 - 670	**30**	(22° Cell)
DB **76587**			**60**	(44° Cell)
			88	(22°x 9°)
			07	(Asym. Ww)


IK08 IP65


	Cct	Im S - Im D	Opt	
630mA - 5,5 W DC				
WH **76589**	**M**	643 - 536	**05**	(6°)
BB **76590**	**W**	673 - 559	**15**	(15° Cell)
GG **76591**	**N**	711 - 591	**30**	(22° Cell)
DB **76592**			**60**	(44° Cell)
			88	(22°x 9°)
			07	(Asym. Ww)

Electronics: **BI** (pag 522)


Optic **05** powerLED - Optic **Cell** 15/30/60 only for downlight installation

Cubit Pro | Double emission | arrayLED





Optics design:



Down **Cell**: **15/30/60** | Up: **15/30/60** | Up: **05** | Asym. Ww **07**

IK08 IP65

	Cct	Im S - Im D	Opt	
220-240 V AC - 13,4 W DC - 15,5 W AC				
WH **76614**	**M**	1698 - 1199	**15**	15+15 (15° Cell + 15°)
BB **76615**	**W**	1772 - 1254	**30**	30+30 (22° Cell + 22°)
GG **76616**	**N**	1870 - 1323	**60**	60+60 (44° Cell + 44°)
DB **76617**				
WH **76624**	**M**	1698 - 668	**15**	15+05 (15° Cell + 6°)
BB **76625**	**W**	1772 - 697	**30**	30+05 (22° Cell + 6°)
GG **76626**	**N**	1870 - 736	**60**	60+05 (44° Cell + 6°)
DB **76627**				
WH **77490**	**M**	1698 - 1099	**15**	07+15 (Asym. Ww + 15°)
BB **77491**	**W**	1772 - 1147	**30**	07+30 (Asym. Ww + 22°)
GG **77492**	**N**	1870 - 1211	**60**	07+60 (Asym. Ww + 44°)
DB **77493**				

IK08 IP65


	Cct	Im S - Im D	Opt	
630mA - 11 W DC				
WH **76619**	**M**	1292 - 1059	**15**	15+15 (15° Cell + 15°)
BB **76620**	**W**	1346 - 1108	**30**	30+30 (22° Cell + 30°)
GG **76621**	**N**	1422 - 1169	**60**	60+60 (44° Cell + 44°)
DB **76622**				
WH **76629**	**M**	1292 - 591	**15**	15+05 (15° Cell + 6°)
BB **76630**	**W**	1346 - 617	**30**	30+05 (22° Cell + 6°)
GG **76631**	**N**	1422 - 651	**60**	60+05 (44° Cell + 6°)
DB **76632**				
WH **77495**	**M**	1292 - 971	**15**	07+15 (Asym. Ww + 15°)
BB **77496**	**W**	1346 - 1014	**30**	07+30 (Asym. Ww + 22°)
GG **77497**	**N**	1422 - 1070	**60**	07+60 (Asym. Ww + 44°)
DB **77498**				

Electronics: **BQ** (pag 522)


Optic **05** powerLED - Optic **Cell** 15/30/60 only for downlight installation

Cubit | arrayLED-Direct | 220-240 V AC






Optics design:



15/30/60



12



00

IK08 IP65

LED-DIRECT

	Cct	lm S - lm D	Opt	
Single emission - 10 W AC				
WH **76574**	**W**	1150 - 606	**15**	(16°)
BB **76575**	**N**	1200 - 632	**30**	(27°)
GG **76576**			**60**	(47°)
DB **76577**				
WH **76559**	**W**	1150 - 580	**12**	(81°)
BB **76560**	**N**	1200 - 635	**00**	(Diffused)
GG **76561**				
DB **76562**				

IK08 IP65

LED-DIRECT

	Cct	lm S - lm D	Opt	
Double emission - 20 W AC				
WH **76579**	**W**	2300 - 1220	**15**	15+15 (16°+ 16°)
BB **76580**	**N**	2400 - 1273	**30**	30+30 (27°+ 27°)
GG **76581**			**60**	60+60 (47°+ 47°)
DB **76582**				
WH **76564**	**W**	2300 - 1217	**12**	12+12 (81°+ 81°)
BB **76565**	**N**	2400 - 1269	**00**	00+00 (Diff. + Diff.)
GG **76566**				
DB **76567**				




Finishes


WH White
BB Black
GG Grey
DB Dark Brown

Cct


W 3000
N 4000

Cubit Pro | Single emission | arrayLED | 220-240 V AC





Optics design:




05 | Down **Cell**: **15/30/60** | Elliptic **88** Asym.Ww **07**


IK08 IP65

	Cct	lm S - lm D	Opt
9,3 W DC - 11 W AC			
WH **76321**	**M**	1265 - 816	**05** (6°)
BB **76322**	**W**	1320 - 855	**15** (15° Cell)
GG **76323**	**N**	1354 - 902	**30** (27° Cell)
DB **76324**			**60** (51° Cell)
			88 (25°x 12°)
			07 (Asym. Ww)
6,3 W DC - 7,5 W AC			DALI 2 DALI PUSH
WH **76326**	**M**	925 - 601	**05** (6°)
BB **76327**	**W**	965 - 630	**15** (15° Cell)
GG **76328**	**N**	990 - 664	**30** (27° Cell)
DB **76329**			**60** (51° Cell)
			88 (25°x 12°)
			07 (Asym. Ww)


Optic **05** powerLED - Optic **Cell** 15/30/60 only for downlight installation

Cubit Pro | Double emission | arrayLED | 220-240 V AC





Optics design:



Down **Cell**: **15/30/60** | Up: **15/30/60** | Up: **05** | Asym. Ww **07**


IK08 IP65

	Cct	lm S - lm D	Opt
18,6 W DC - 21,2 W AC			
WH **76351**	**M**	2530 - 1574	**15** 15+15 (15° Cell + 15°)
BB **76352**	**W**	2640 - 1640	**30** 30+30 (27° Cell + 27°)
GG **76353**	**N**	2708 - 1731	**60** 60+60 (51° Cell + 51°)
DB **76354**			
WH **76361**	**M**	2530 - 906	**15** 15+05 (15° Cell + 6°)
BB **76362**	**W**	2640 - 944	**30** 30+05 (27° Cell + 6°)
GG **76363**	**N**	2708 - 996	**60** 60+05 (51° Cell + 6°)
DB **76364**			
WH **77470**	**M**	2530 - 1524	**15** 07+15 (Asym. Ww + 15°)
BB **77471**	**W**	2640 - 1588	**30** 07+30 (Asym. Ww + 27°)
GG **77472**	**N**	2708 - 1675	**60** 07+60 (Asym. Ww + 51°)
DB **77473**			
12,6 W DC - 15 W AC			DALI 2 DALI PUSH
WH **76356**	**M**	1850 - 1159	**15** 15+15 (15° Cell + 15°)
BB **76357**	**W**	1930 - 1208	**30** 30+30 (27° Cell + 27°)
GG **76358**	**N**	1980 - 1275	**60** 60+60 (51° Cell + 51°)
DB **76359**			
WH **76366**	**M**	1850 - 669	**15** 15+05 (15° Cell + 6°)
BB **76367**	**W**	1930 - 697	**30** 30+05 (27° Cell + 6°)
GG **76368**	**N**	1980 - 735	**60** 60+05 (51° Cell + 6°)
DB **76369**			
WH **77475**	**M**	1850 - 1124	**15** 07+15 (Asym. Ww + 15°)
BB **77476**	**W**	1930 - 1171	**30** 07+30 (Asym. Ww + 27°)
GG **77477**	**N**	1980 - 1235	**60** 07+60 (Asym. Ww + 51°)
DB **77478**			


Optic **05** powerLED - Optic **Cell** 15/30/60 only for downlight installation

Cubit | arrayLED-Direct | 220-240 V AC






Optics design:



15/30/60



12



00

IK08 IP65


LED-DIRECT

	Cct	lm S - lm D	Opt
Single emission - 12 W AC			
WH **76311**	**W**	1267 - 809	**15** (15°)
BB **76312**	**N**	1316 - 842	**30** (20°)
GG **76313**			**60** (43°)
DB **76314**			
WH **76296**	**W**	1267 - 730	**12** (81°)
BB **76297**	**N**	1316 - 760	**00** (Diffused)
GG **76298**			
DB **76299**			

IK08 IP65

LED-DIRECT

	Cct	lm S - lm D	Opt
Double emission - 24 W AC			
WH **76316**	**W**	2534 - 1635	**15** 15+15 (15°+ 15°)
BB **76317**	**N**	2632 - 1701	**30** 30+30 (20°+ 20°)
GG **76318**			**60** 60+60 (43°+ 43°)
DB **76319**			
WH **76301**	**W**	2534 - 1460	**12** 12+12 (81°+ 81°)
BB **76302**	**N**	2632 - 1519	**00** 00+00 (Diff. + Diff.)
GG **76303**			
DB **76304**			



Finishes


WH White
BB Black
GG Grey
DB Dark Brown

Cct


W 3000
N 4000

Cubit Pro | Single emission | arrayLED | 220-240 V AC






Optics design:



05



Down **Cell**:
15/30/60



Elliptic **88**
Asym.Ww **07**

IK08 IP65


	Cct	lm S - lm D	Opt	
14 W DC - 17 W AC				
WH **76246**	**M**	1864 - 1292	**05**	(6°)
BB **76247**	**W**	1946 - 1346	**15**	(13° Cell)
GG **76248**	**N**	1995 - 1422	**30**	(20° Cell)
DB **76249**			**60**	(45° Cell)
			88	(26°x 13°)
			07	(Asym. Ww)


DALI 2 DALI PUSH

14 W DC - 17 W AC				
WH **76251**	**M**	1864 - 1292	**05**	(6°)
BB **76252**	**W**	1946 - 1346	**15**	(13° Cell)
GG **76253**	**N**	1995 - 1422	**30**	(20° Cell)
DB **76254**			**60**	(45° Cell)
			88	(26°x 13°)
			07	(Asym. Ww)


Optic **05** powerLED - Optic **Cell** 15/30/60 only for downlight installation

Cubit Pro | Double emission | arrayLED | 220-240 V AC







Optics design:




Down **Cell**:
15/30/60



Up:
15/30/60



Up:
05



Asym. Ww
07

IK08 IP65

	Cct	lm S - lm D	Opt	
28 W DC - 31 W AC				
WH **76276**	**M**	3728 - 2546	**15**	15+15 (13° Cell + 13°)
BB **76277**	**W**	3892 - 2653	**30**	30+30 (20° Cell + 20°)
GG **76278**	**N**	3990 - 2802	**60**	60+60 (45° Cell + 45°)
DB **76279**				
WH **76286**	**M**	3728 - 1565	**15**	15+05 (13° Cell + 6°)
BB **76287**	**W**	3892 - 1482	**30**	30+05 (20° Cell + 6°)
GG **76288**	**N**	3990 - 1565	**60**	60+05 (45° Cell + 6°)
DB **76289**				
WH **77438**	**M**	3728 - 2283	**15**	07+15 (Asym. Ww + 13°)
BB **77439**	**W**	3892 - 2379	**30**	07+30 (Asym. Ww + 20°)
GG **77440**	**N**	3990 - 2512	**60**	07+60 (Asym. Ww + 45°)
DB **77441**				

DALI 2 DALI PUSH

28 W DC - 31 W AC				
WH **76281**	**M**	3728 - 2546	**15**	15+15 (13° Cell + 13°)
BB **76282**	**W**	3892 - 2653	**30**	30+30 (20° Cell + 20°)
GG **76283**	**N**	3990 - 2802	**60**	60+60 (45° Cell + 45°)
DB **76284**				
WH **76291**	**M**	3728 - 1422	**15**	15+05 (13° Cell + 6°)
BB **76292**	**W**	3892 - 1482	**30**	30+05 (20° Cell + 6°)
GG **76293**	**N**	3990 - 1565	**60**	60+05 (45° Cell + 6°)
DB **76294**				
WH **77443**	**M**	3728 - 2283	**15**	07+15 (Asym. Ww + 13°)
BB **77444**	**W**	3892 - 2379	**30**	07+30 (Asym. Ww + 20°)
GG **77445**	**N**	3990 - 2512	**60**	07+60 (Asym. Ww + 45°)
DB **77446**				

Optic **05** powerLED - Optic **Cell** 15/30/60 only for downlight installation

Electronics

BI

C-E200008
ON/OFF
1 - 2 art.
135 x 26 x h 26
35

99186
ON/OFF
2 - 4 art.
117 x 92 x h 38

C-E200002
DALI/PUSH
2 - 4 art.
125 x 45 x h 30
55

BQ

C-E200008
ON/OFF
1 art.
135 x 26 x h 26
35

99186
ON/OFF
1 - 2 art.
117 x 92 x h 38

C-E200002
DALI/PUSH
1 - 2 art.
125 x 45 x h 30
55





LAZIO REGION HEADQUARTER
Roma (Italy)


Photography:
Matteo Canestraro




VEDETTE

Aluminium body.

Vedette_R | powerLED | 220-240 V AC





IK05 IP65


	Cct	lm S - lm D	Opt
Single emission - 4 W DC - 4,5 W AC			
WH **82773**	**M**	490 - 298	**15** (14°)
BB **82774**	**W**	490 - 298	**30** (32°)
GG **82775**	**N**	529 - 301	**45** (44°)
DB **82776**			**00** (Diffused)

IK05 IP65

	Cct	lm S - lm D	Opt
Double emission - 8 W DC - 9 W AC			
WH **82778**	**M**	980 - 596	**15** (14°+ 14°)
BB **82779**	**W**	980 - 596	**30** (32°+ 32°)
GG **82780**	**N**	1058 - 644	**45** (44°+ 44°)
DB **82781**			**00** (Diff. + Diff.)

Vedette_R | arrayLED | 220-240 V AC





IK05 IP65


	Cct	lm S - lm D	Opt
Single emission - 8 W DC - 9 W AC			
WH **82793**	**M**	1041 - 726	**15** (18°)
BB **82794**	**W**	1087 - 754	**30** (36°)
GG **82795**	**N**	1114 - 795	**60** (66°)
DB **82796**			**00** (Diffused)

IK05 IP65

	Cct	lm S - lm D	Opt
Double emission - 16 W DC - 18 W AC			
WH **82798**	**M**	2082 - 1455	**15** (18°+ 18°)
BB **82799**	**W**	2174 - 1512	**30** (36°+ 36°)
GG **82800**	**N**	2228 - 1596	**60** (66°+ 66°)
DB **82801**			**00** (Diff. + Diff.)

Vedette_R | arrayLED | 220-240 V AC






IK05 IP65


	Cct	lm S - lm D	Opt
Single emission - 14 W DC - 15,5 W AC			
WH **82813**	**M**	1676 - 1256	**15** (13°)
BB **82814**	**W**	1750 - 1307	**30** (33°)
GG **82815**	**N**	1794 - 1380	**60** (63°)
DB **82816**			**00** (Diffused)

IK05 IP65

	Cct	lm S - lm D	Opt
Double emission - 28 W DC - 30 W AC			
WH **82818**	**M**	3352 - 2511	**15** (13°+ 13°)
BB **82819**	**W**	3500 - 2623	**30** (33°+ 33°)
GG **82820**	**N**	3588 - 2760	**60** (63°+ 63°)
DB **82821**			**00** (Diff. + Diff.)

Vedette_Q | powerLED | 220-240 V AC






IK05 IP65


	Cct	lm S - lm D	Opt
Single emission - 4 W DC - 4,5 W AC			
WH **82763**	**M**	490 - 298	**15** (14°)
BB **82764**	**W**	490 - 298	**30** (32°)
GG **82765**	**N**	529 - 301	**45** (44°)
DB **82766**			**00** (Diffused)

IK05 IP65

	Cct	lm S - lm D	Opt
Double emission - 8 W DC - 9 W AC			
WH **82768**	**M**	980 - 596	**15** (14°+ 14°)
BB **82769**	**W**	980 - 596	**30** (32°+ 32°)
GG **82770**	**N**	1058 - 644	**45** (44°+ 44°)
DB **82771**			**00** (Diff. + Diff.)

Vedette_Q | arrayLED | 220-240 V AC





IK05 IP65


	Cct	lm S - lm D	Opt
Single emission - 8 W DC - 9 W AC			
WH **82783**	**M**	1041 - 726	**15** (18°)
BB **82784**	**W**	1087 - 754	**30** (36°)
GG **82785**	**N**	1114 - 795	**60** (66°)
DB **82786**			**00** (Diffused)

IK05 IP65

	Cct	lm S - lm D	Opt
Double emission - 16 W DC - 18 W AC			
WH **82788**	**M**	2082 - 1455	**15** (18°+ 18°)
BB **82789**	**W**	2174 - 1512	**30** (36°+ 36°)
GG **82790**	**N**	2228 - 1596	**60** (66°+ 66°)
DB **82791**			**00** (Diff. + Diff.)

Vedette_Q | arrayLED | 220-240 V AC





IK05 IP65

	Cct	lm S - lm D	Opt
Single emission - 14 W DC - 15,5 W AC			
WH **82803**	**M**	1676 - 1256	**15** (13°)
BB **82804**	**W**	1750 - 1307	**30** (33°)
GG **82805**	**N**	1794 - 1380	**60** (63°)
DB **82806**			**00** (Diffused)

IK05 IP65

	Cct	lm S - lm D	Opt
Double emission - 28 W DC - 30 W AC			
WH **82808**	**M**	3352 - 2511	**15** (13°+ 13°)
BB **82809**	**W**	3500 - 2623	**30** (33°+ 33°)
GG **82810**	**N**	3588 - 2760	**60** (63°+ 63°)
DB **82811**			**00** (Diff. + Diff.)

PALAZZO DOGLIO
Cagliari (Italy)

Project: Studio Mei & Pilia Associati


Lighting Designer:
Lighting Design Department

Photography:
Dario Sequi



Vedette_Q | powerLED | 220-240 V AC





IK05 IP65

	Cct	lm S - lm D	Opt
Single emission - Blade - 6 W DC - 7,2 W AC			
WH **97048**	**M**	657 - 75	**05** (4°)
BB **97049**	**W**	699 - 80	
GG **97050**	**N**	747 - 85	
DB **97051**			

IK05 IP65

	Cct	lm S - lm D	Opt
Single emission - Asymmetric - 6 W DC - 7,2 W AC			
WH **81574**	**M**	685 - 532	**07** (Asym. Ww)
BB **81575**	**W**	739 - 554	
GG **81576**	**N**	985 - 585	
DB **81577**			

IK05 IP65

	Cct	lm S - lm D	Opt
Double emission - Blade - 12 W DC - 13 W AC			
WH **97185**	**M**	1314 - 149	**05** (4°+ 4°)
BB **97186**	**W**	1398 - 159	
GG **97187**	**N**	1494 - 169	
DB **97188**			

IK05 IP65

	Cct	lm S - lm D	Opt
Double emission - Blade - 12 W DC - 14,5 W AC			
WH **97052**	**M**	1342 - 491	**56** (60°+ 4°)
BB **97053**	**W**	1486 - 543	
GG **97054**	**N**	1684 - 616	
DB **97055**			


Optic 4° powerLED + 60°arrayLED

IK05 IP65

	Cct	lm S - lm D	Opt
Double emission - Asymmetric - 13,5 W DC - 16,5 W AC			
WH **81578**	**M**	1324 - 1259	**62** (Asym. Ww + 4°)
BB **81579**	**W**	1413 - 1311	**63** (Asym. Ww + 30°)
GG **81580**	**N**	1730 - 1381	**64** (Asym. Ww + 60°)
DB **81581**			


Vedette_Q | powerLED | 220-240 V AC





Vedette_Q | arrayLED | 220-240 V AC





IK05 IP65

	Cct	lm S - lm D	Opt
Single emission - Blade - 24 W DC - 28,8 W AC			
WH **91599**	**M**	2288 - 251	**05** (4°)
BB **91600**	**W**	2288 - 251	
GG **91601**	**N**	2463 - 271	
DB **91602**			

IK05 IP65

	Cct	lm S - lm D	Opt
Single emission - Asymmetric - 14 W DC - 15 W AC			
WH **81582**	**M**	2077 - 841	**07** (Asym. Ww)
BB **81583**	**W**	2165 - 875	
GG **81584**	**N**	2285 - 924	
DB **81585**			

IK05 IP65

	Cct	lm S - lm D	Opt
Double emission - Asymmetric - 28 W DC - 30 W AC			
WH **81586**	**M**	3812 - 2093	**62** (Asym. Ww + 4°)
BB **81587**	**W**	3973 - 2180	**63** (Asym. Ww + 30°)
GG **81588**	**N**	4194 - 2302	**64** (Asym. Ww + 60°)
DB **81589**			

Optic 4° powerLED



LAZIO REGION HEADQUARTER
Roma (Italy)


Photography:
Matteo Canestraro

Finishes

WH White
BB Black
GG Grey
DB Dark Brown

Cct

M 2700
W 3000
N 4000






NAIL

Aluminium body.
Diffuser in polycarbonate.

Nail_W | arrayLED | 220-240 V AC | 6,5 W DC - 8 W AC





IP65

		Cct	lm S - lm D	Opt
WH	**84184**	**M**	552 - 371	**00** (Radial Diffused)
BG	**84185**	**W**	591 - 397	
DB	**84186**	**N**	638 - 429	
GG	**84187**			




Black/Grey (BG)




Dark Brown (DB)



Grey (GG)



*** White (WH)**





Radial optics

Outdoor LED fixture with on-board power supply, equipped with hidden light source which, thanks to optics designed by Linea Light Group in house and made from a single block of methacrylate, creates an extremely low luminance emission with a 360° radial light beam.

*** Paintable finish**

The distinctive white finish of the Nail_W model allows the luminaire to be painted. Colours can be customised, integrating the luminaire into the architectural landscape on which it is fitted.

Finishes

WH White
BG Black/Grey
GG Grey
DB Dark Brown

Cct

M 2700 **N** 4000
W 3000


CEM

Concrete body.



Cem_C | arrayLED | 220-240 V | 6,5 W DC - 8 W AC







IP65

	Cct	lm S - lm D	Opt
CC 64564	M	751 - On req	70 (68°)
	W	770 - On req	
	N	831 - On req	

Cem_W | arrayLED | 220-240 V | 6,5 W DC - 9 W AC






IP65

	Cct	lm S - lm D	Opt
CC 64561	M	849 - On req	00 (Diffused)
	W	876 - On req	
	N	946 - On req	

Cem_W | topLED | 220-240 V | 14 W DC - 16,8 W AC






IP65

	Cct	lm S - lm D	Opt
CC 64562	M	2250 - 852	00 (Diffused)
	W	2350 - 890	
	N	2450 - 907	

Cem_WF | powerLED | 500 mA | 1,5 W DC







C.C. IP65

	Cct	lm S - lm D	Opt
CC 64506	M	199 - On req	00 (Asym. Ww)
	W	213 - On req	
	N	227 - On req	

Electronics: **BC** (pag 533) | Recessed casing (pag 533)

Cem_WF | topLED | 180 mA | 7,5 W DC





C.C. IP65

	Cct	lm S - lm D	Opt
CC 64505	M	967 - 366	00 (Asym. Ww)
	W	1125 - 426	
	N	1175 - 445	

Electronics: **BH** (pag 533) | Recessed casing (pag 533)

Electronics

BC

89422
ON/OFF
1 - 2 art.
74 x 65 x h 27

89423
ON/OFF
2 - 3 art.
74 x 65 x h 27


C-E200007
ON/OFF
3 - 6 art.
135 x 26 x h 26
35

C-E200003
DALI/PUSH
5 - 12 art.
125 x 45 x h 30
55

BH


99716
ON/OFF
1 art.
57 x 38 x h 25

Recessed casings



WH **65002** Concrete casting template

suitable for: Cem_WF 1,5W



WH **65005** Concrete casting template

suitable for: Cem_WF 7,5W

Finishes **Cct**

CC Concrete **M** 2700 **N** 4000
W 3000

SKIN_W

Aluminium body.
Extra-clear tempered glass diffuser.



Skin family

Skin_S

508

Skin_F _FL _Y

552

BEAUTIFUL BY DAY, EFFICIENT IN EVERY SITUATION BY NIGHT

We have expanded and completed the SKIN collection with the new wall-mounted version. The collection's innovative elongated hexagon shape is available in two widths: 160 and 210 mm, and in three light configurations: symmetrical, asymmetrical and diffused. SKIN_W is an extremely versatile product thanks to the different optics and finishes available; its slim shape makes it adaptable to any context. Neutral colours have been chosen to work by assimilation or contrast with the wall surfaces on which they will be installed. SKIN_W is a luminaire that interacts with the surrounding architecture. Combined with the SKIN series, it completes each project, giving it perfect aesthetic uniformity.



Skin_WF
145x160xP51




Skin_WF
145x210xP51

BLEND IN OR STAND OUT: PLAYING WITH FINISHES

SKIN W is available in five neutral finishes: White, Grey, Black Grey, Black and Dark Brown. These colours allow the designer to blend the product in with the surrounding architecture, making it almost invisible to the light, or in contrast, making SKIN W stand out. A solution that offers a dual advantage: it enhances the aesthetics of the luminaire and of its light.



White (WH)



Grey (GG)



Black Grey (BG)



Black (BB)



Dark Brown (DB)

SKIN WALL, LIGHT HOW YOU WANT IT

SKIN W is the wall-mounted version of SKIN. Its compositional matrix is divided into two variants in mono or bi-emission mode. For each version, optics with different lighting effects are provided: with recessed cells, with opal diffuser and linear asymmetric. It has reduced dimensions: small 145x160x51 mm and large 145x210x51; thanks to its slim structure, it can be installed perfectly flush with the wall.



Skin_WF
Single Emission: 7W AC
Optic: Spot, M.Flood, M.W.Flood

Double Emission: 7W+7W AC
Optic: Spot, M.Flood, M.W.Flood



Skin_WL
Single Emission: 8W AC
Optic: Diffused

Double Emission: 8W+8W AC
Optic: Diffused



Skin_WF
Single Emission: 11W AC
Optic: Spot, M.Flood, M.W.Flood

Double Emission: 11W+11W AC
Optic: Spot, M.Flood, M.W.Flood



Skin_WL
Single Emission: 11W AC
Optic: Diffused

Double Emission: 11W+11W AC
Optic: Diffused




Skin_WY
Single Emission: 11W AC
Optic: Asymmetric

Double Emission: 10,5W+10,5W AC
Optic: Asymmetric

Skin_WF | Single emission | powerLED | 220-240 V AC







Up Down


IK06 IP65

	Cct	lm S - lm D	Opt
6,3 W DC - 7 W AC			
WH 76918	M	798 - 574	15 (10°÷ 19°)
BB 76919	W	852 - 613	30 (30°÷ 39°)
BG 76920	N	909 - 654	45 (40°÷ 49°)
GG 76921			
DB 76922			

			DALI 2 PUSH
6,3 W DC - 7 W AC			
WH 76923	M	798 - 574	15 (10°÷ 19°)
BB 76924	W	852 - 613	30 (30°÷ 39°)
BG 76925	N	909 - 654	45 (40°÷ 49°)
GG 76926			
DB 76927			

Skin_WF | Double emission | powerLED | 220-240 V AC







Up Down


IK06 IP65

	Cct	lm S - lm D	Opt
12,6 W DC - 14 W AC			
WH 76938	M	1596 - 1150	15 (10°÷ 19°) + (10°÷ 19°)
BB 76939	W	1704 - 1227	30 (30°÷ 39°) + (30°÷ 39°)
BG 76940	N	1818 - 1310	45 (40°÷ 49°) + (40°÷ 49°)
GG 76941			
DB 76942			

			DALI 2 PUSH
12,6 W DC - 14 W AC			
WH 76943	M	1596 - 1150	15 (10°÷ 19°) + (10°÷ 19°)
BB 76944	W	1704 - 1227	30 (30°÷ 39°) + (30°÷ 39°)
BG 76945	N	1818 - 1310	45 (40°÷ 49°) + (40°÷ 49°)
GG 76946			
DB 76947			

Skin_WL | Single emission | topLED | 220-240 V AC







Up Down


IK06 IP65

	Cct	lm S - lm D	Opt
7,2 W DC - 8 W AC			
WH 76928	M	1038 - 450	00 (Diffused)
BB 76929	W	1085 - 470	
BG 76930	N	1131 - 490	
GG 76931			
DB 76932			

			DALI
7,2 W DC - 8 W AC			
WH 76933	M	1038 - 450	00 (Diffused)
BB 76934	W	1085 - 470	
BG 76935	N	1131 - 490	
GG 76936			
DB 76937			

Skin_WL | Double emission | topLED | 220-240 V AC







Up Down

IK06 IP65

	Cct	lm S - lm D	Opt
14,4 W DC - 16 W AC			
WH 76948	M	2388 - 900	00 (Diff.) + (Diff.)
BB 76949	W	2556 - 940	
BG 76950	N	2724 - 980	
GG 76951			
DB 76952			

			DALI
14,4 W DC - 16 W AC			
WH 76953	M	2388 - 900	00 (Diff.) + (Diff.)
BB 76954	W	2556 - 940	
BG 76955	N	2724 - 980	
GG 76956			
DB 76957			

Finishes

WH White BG Black/Grey DB Dark Brown
BB Black GG Grey

Cct


M 2700 N 4000
W 3000





Skin_WF | Single emission | powerLED | 220-240 V AC









Up Down

IK06 IP65


	Cct	lm S - lm D	Opt
9,9 W DC - 11 W AC			
WH 76958	M	1330 - 846	15 (10°÷ 19°)
BB 76959	W	1420 - 903	30 (30°÷ 39°)
BG 76960	N	1515 - 965	45 (40°÷ 49°)
GG 76961			
DB 76962			

DALI 2 DALI PUSH

9,9 W DC - 11 W AC			
WH 76963	M	1330 - 846	15 (10°÷ 19°)
BB 76964	W	1420 - 903	30 (30°÷ 39°)
BG 76965	N	1515 - 965	45 (40°÷ 49°)
GG 76966			
DB 76967			

Skin_WF | Double emission | powerLED | 220-240 V AC









Up Down

EL * The driver contained in the device complies with IEC 61347-2-13 annex J, and can therefore be powered by centralized power supply systems.

IK06 IP65 *


	Cct	lm S - lm D	Opt
19,8 W DC - 22 W AC			
WH 76978	M	2300 - 1693	15 (10°÷ 19°) + (10°÷ 19°)
BB 76979	W	2490 - 1808	30 (30°÷ 39°) + (30°÷ 39°)
BG 76980	N	2660 - 1929	45 (40°÷ 49°) + (40°÷ 49°)
GG 76981			
DB 76982			

* DALI 2 DALI PUSH

19,8 W DC - 22 W AC			
WH 76983	M	2300 - 1693	15 (10°÷ 19°) + (10°÷ 19°)
BB 76984	W	2490 - 1808	30 (30°÷ 39°) + (30°÷ 39°)
BG 76985	N	2660 - 1929	45 (40°÷ 49°) + (40°÷ 49°)
GG 76986			
DB 76987			

Skin_WL | Single emission | topLED | 220-240 V AC









Up Down

IK06 IP65


	Cct	lm S - lm D	Opt
9,9 W DC - 11 W AC			
WH 76968	M	1384 - 599	00 (Diffused)
BB 76969	W	1446 - 626	
BG 76970	N	1507 - 653	
GG 76971			
DB 76972			

DALI

9,9 W DC - 11 W AC			
WH 76973	M	1384 - 599	00 (Diffused)
BB 76974	W	1446 - 626	
BG 76975	N	1507 - 653	
GG 76976			
DB 76977			

Skin_WL | Double emission | topLED | 220-240 V AC









Up Down

IK06 IP65

	Cct	lm S - lm D	Opt
19,8 W DC - 22 W AC			
WH 76988	M	2769 - 1199	00 (Diff.) + (Diff.)
BB 76989	W	2892 - 1253	
BG 76990	N	3015 - 1306	
GG 76991			
DB 76992			

DALI

19,8 W DC - 22 W AC			
WH 76993	M	2769 - 1199	00 (Diff.) + (Diff.)
BB 76994	W	2892 - 1253	
BG 76995	N	3015 - 1306	
GG 76996			
DB 76997			

Finishes


WH White BG Black/Grey DB Dark Brown
BB Black GG Grey

Cct

M 2700 N 4000
W 3000

Skin_WY | Single emission | powerLED | 220-240 V AC








Up



Down

Skin_WY | Double emission | powerLED | 220-240 V AC







Up



Down

EL * The driver contained in the device complies with IEC 61347-2-13 annex J, and can therefore be powered by centralized power supply systems.

IK06 IP65

	Cct	lm S - lm D	Opt
9,5 W DC - 11 W AC			
WH **76998**	**M**	1533 - 900	**07** (Asy. Ww)
BB **76999**	**W**	1606 - 942	
BG **77000**	**N**	1684 - 988	
GG **77001**			
DB **77002**			

DALI 2 DALI PUSH

9,5 W DC - 11 W AC			
WH **77003**	**M**	1533 - 900	**07** (Asy. Ww)
BB **77004**	**W**	1606 - 942	
BG **77005**	**N**	1684 - 988	
GG **77006**			
DB **77007**			

IK06 IP65 *


	Cct	lm S - lm D	Opt
18,8 W DC - 21 W AC			
WH **77018**	**M**	3066 - 1642	**07** (Asy. Ww) + (Asy. Ww)
BB **77019**	**W**	3213 - 1721	
BG **77020**	**N**	3368 - 1804	
GG **77021**			
DB **77022**			

*** DALI 2 DALI PUSH**

18,8 W DC - 21 W AC			
WH **77023**	**M**	3066 - 1642	**07** (Asy. Ww) + (Asy. Ww)
BB **77024**	**W**	3213 - 1721	
BG **77025**	**N**	3368 - 1804	
GG **77026**			
DB **77027**			

ASYMMETRY MAKES THE DIFFERENCE

In the version with uplight asymmetrical optics, the beam is more open, allowing a greater light diffusion on the ceiling, an effect that is amplified in vaulted rooms; in the downlight version, the beam is narrower and the recessed optics maximise visual comfort, also thanks to the recessed cell optics.







Finishes

WH White BG Black/Grey DB Dark Brown
BB Black GG Grey

Cct

M 2700 **N** 4000
W 3000





LINEAR SYSTEMS

Linear systems range index

Ice-Cut66

Ice-Cut66



547

Thin66

Thin66



549

Skin

Skin_F



556

Skin_FL



556

Skin_Y



556

Paseo

Paseo_L



560-561

Paseo Dark



563

Paseo_X



563

Xenia

Xenia_W

NEW



573-574

Xenia_W Pro

NEW



575

Xenia_A

NEW



578

Xenia_AL

NEW



579

Xenia_A Pro

NEW



580-581

Xenia_A Pro MicroLouvre

NEW



581

Xenia_AF

NEW



582

Xenia_ALF

NEW



583

Xenia_AF Pro

NEW



584-585

Xenia_AF Pro MicroLouvre

NEW



585

Archiline

Archiline_F



594-595

Archiline_FJ



594

Archiline_FL



595

Archiline_A



596-597

Archiline_I



597-599

Archiline_IJ



599

Archiline_W



604-605

Archiline_W Pro



605-606

Mini Tube

Mini Tube



609

Mini Tube IN&OUT



609

Maxi Tube

Maxi Tube



613

Maxi Tube IN&OUT



613

High Protection

High Protection



618

High Protection Wired



618

D-Wave

D-Wave



628

Dirigo

Dirigo_FL2 Complete



632

Dirigo_M2



632

Dirigo_FL1 Complete Steel



633

Dirigo_M1 Steel



633

Dirigo Cut-Off

Dirigo_CUT-OFF Complete



638

Dirigo_CUT-OFF



638

Fylo+

Fylo+ Out Recessed_S



641

Fylo+ Out Recessed_W



641


ICE-CUT66



Translucent polycarbonate body.

Ice-Cut66 | topLED | 24 V DC





	Cct	lm S - lm D	Opt
L 532 mm - 6 W DC			
OP **96740**	**M**	420 - 244	**00** (Diffused)
	W	438 - 265	
	N	478 - 289	

Electronics: **DM** (pag 547) - Accessories & cables: (pag 547)

L 1032 mm - 12 W DC			
OP **96741**	**M**	840 - 488	**00** (Diffused)
	W	875 - 530	
	N	956 - 579	

Electronics: **DN** (pag 547) - Accessories & cables: (pag 547)

L 1532 mm - 18 W DC			
OP **96742**	**M**	1260 - 731	**00** (Diffused)
	W	1313 - 749	
	N	1434 - 868	

Electronics: **DO** (pag 547) - Accessories & cables: (pag 547)

Accessories



IS **98398** 2x Fixing clips

suitable for: Ice-Cut66

Cables

24V DC | Cables



BB **99231** Conn. F.4 pin M8 (L 1m)

suitable for: Ice-Cut66

24V DC | Extension cables



BB **99232** Conn M. + F. 4 pin M8 (L 1m)

suitable for: Ice-Cut66

Electronics

DM

89359	99331	99332	83333	C-E400002
ON/OFF	ON/OFF	0/1-10V	DALI/PUSH	DALI/PUSH
1 - 6 art.	1 - 20 art.	1 - 20 art.	1 - 20 art.	1 - 32 art.
140 x 115 x h 50	158 x 60 x h 35	158 x 60 x h 35	188 x 68 x h 34	188 x 68 x h 34
	70	70	77	77

DN

89359	99331	99332	83333	C-E400002
ON/OFF	ON/OFF	0/1-10V	DALI/PUSH	DALI/PUSH
1 - 3 art.	1 - 9 art.	1 - 9 art.	1 - 9 art.	1 - 15 art.
140 x 115 x h 50	158 x 60 x h 35	158 x 60 x h 35	188 x 68 x h 34	188 x 68 x h 34
	70	70	77	77

DO

89359	99331	99332	83333	C-E400002
ON/OFF	ON/OFF	0/1-10V	DALI/PUSH	DALI/PUSH
1 - 2 art.	1 - 6 art.	1 - 6 art.	1 - 6 art.	1 - 11 art.
140 x 115 x h 50	158 x 60 x h 35	158 x 60 x h 35	188 x 68 x h 34	188 x 68 x h 34
	70	70	77	77


Finishes

BB Anodised Aluminium
IS Steel
OP Opaline


Cct

M 2700
W 3000
N 4000

THIN66







Steel fixing brackets included

C.V. IK10 IP66

			Cct	lm S - lm D	Opt
L 539 mm - 4,8 W DC					
AM	**83885**	M	**M**	425 - 159	**00** (Diffused)
AM	**83889**	M+F	**W**	440 - 165	
			N	480 - 179	

Electronics: **DR** (pag 551) | Accessories & cables: (pag 551)

L 1039 mm - 9,6 W DC					
AM	**83886**	M	**M**	1056 - 317	**00** (Diffused)
AM	**83890**	M+F	**W**	1075 - 330	
			N	1142 - 358	

Electronics: **DS** (pag 551) | Accessories & cables: (pag 551)

L 1539 mm - 14,4 W DC					
AM	**83887**	M	**M**	1275 - 475	**00** (Diffused)
AM	**83891**	M+F	**W**	1320 - 494	
			N	1440 - 537	


Electronics: **DQ** (pag 551) | Accessories & cables: (pag 551)

L 2039 mm - 19,2 W DC					
AM	**83888**	M	**M**	2112 - 634	**00** (Diffused)
AM	**83892**	M+F	**W**	2150 - 659	
			N	2284 - 716	

Electronics: **DO** (pag 551) | Accessories & cables: (pag 551)

Thin66, the linear profile that emits a diffused light that, thanks to its minimalist design, adapts to any type of installation to accentuate architectural details and features whilst emphasising the façades with character and elegance. Anodised aluminium body. Opalescent polyurethane resin coating.





Finishes

AM Anodised Aluminium

Cct

M 2700 **N** 4000
W 3000

BEIJING TONGZHOU HEJING CENTER
Beijing (China)

Studio Lighting Designer:
Brandston Partnership Inc.



Cables

24 V DC | Power cables



BB **99216** Conn. F.4 pin M12 (L 1,5m)
BB **89190** Conn. F.4 pin M12 (L 5m)
suitable for: Thin66

24 V DC | Extension cables



BB **98437** Conn M. + F. 4 pin M12 (L 1m)
BB **98149** Conn M. + F. 4 pin M12 (L 5m)
BB **89188** Conn M. + F. 4 pin M12 (L 10m)
suitable for: Thin66

Accessories



IS **Included** Steel fixing brackets included

suitable for: Thin66

Electronics

DO

89359	**99331**	**99332**	**83333**	**C-E400002**
ON/OFF	ON/OFF	0/1-10V	DALI/PUSH	DALI/PUSH
1 - 2 art.	1 - 6 art.	1 - 6 art.	1 - 6 art.	1 - 11 art.
140 x 115 x h 50	158 x 60 x h 35	158 x 60 x h 35	188 x 68 x h 34	188 x 68 x h 34
	70	70	77	77

DQ

89359	**99331**	**99332**	**83333**	**C-E400002**
ON/OFF	ON/OFF	0/1-10V	DALI/PUSH	DALI/PUSH
1 - 3 art.	1 - 9 art.	1 - 9 art.	1 - 9 art.	1 - 15 art.
140 x 115 x h 50	158 x 60 x h 35	158 x 60 x h 35	188 x 68 x h 34	188 x 68 x h 34
	70	70	77	77

DR

89359	**99331**	**99332**	**83333**
ON/OFF	ON/OFF	0/1-10V	DALI/PUSH
1 - 9 art.	1 - 28 art.	1 - 28 art.	1 - 28 art.
140 x 115 x h 50	158 x 60 x h 35	158 x 60 x h 35	188 x 68 x h 34
	70	70	77

DS

89359	**99331**	**99332**	**83333**	**C-E400002**
ON/OFF	ON/OFF	0/1-10V	DALI/PUSH	DALI/PUSH
1 - 4 art.	1 - 14 art.	1 - 14 art.	1 - 14 art.	1 - 22 art.
140 x 115 x h 50	158 x 60 x h 35	158 x 60 x h 35	188 x 68 x h 34	188 x 68 x h 34
	70	70	77	77

Finishes

BB Black
IS Steel

SKIN

Aluminium body.
Tempered glass diffuser.



Skin family

Skin_S



508

Skin_WF _WL _WY



534



Skin_F

W	6-9,6-10-16,2
mm	**166-220**
Cct	2700-3000-4000
Opt	**Spot-M.Flood M.W.Flood**
Elec.	On/Off
Col.	BD




Skin_F

W	6-9,6-10-16,2
mm	**166-220**
Cct	2700-3000-4000
Opt	**Spot-M.Flood M.W.Flood**
Elec.	On/Off
Col.	BB



Skin_S

W	6-9,6-10-16,2
mm	**166-220**
Cct	2700-3000-4000
Opt	**Spot-M.Flood M.W.Flood**
Elec.	On/Off
Col.	WB



Skin_FL

W	2,1-3,2
mm	**166-220**
Cct	2700-3000-4000
Opt	**Diffused**
Elec.	On/Off
Col.	BB



Skin_Y

W	12,2
mm	**220**
Cct	2700-3000-4000
Opt	**Asymmetric Wallwasher**
Elec.	On/Off
Col.	BB

(pag 508)

An application for each version
Skin comes in various installation configurations: ceiling-mounted, semi-recessed and flush-fit. With two types of outer casing, it is easy to position according to the project requirements with a choice of different light distribution. Skin has an IP67 protection rating and an extremely strong structure with an impact rating of IK10 (166 mm version) and IK08 (220 mm version). The combination of these elements means that Skin is perfect for precise and accurate design requirements.



Ceiling surface:
Skin_Y, Skin_S
Skin_F, Skin_FL



Ceiling recessed:
Skin_Y, Skin_F,
Skin_FL




In-ground:
Skin_Y, Skin_F,
Skin_FL



Wall recessed:
Skin_Y,
Skin_FL


Special outer casings for any type of material
Two types of outer casing have been developed for the installation of Skin, adapted to different types of construction materials and possible configurations. The 83123 and 83124 outer casings have been designed to recess the uplight in a concrete screed and the downlight in brick ceilings. The 83125 and 83126 outer casings have been designed to recess the downlight in false or concrete ceilings, and can be fastened with a special bracket.



For installation
in the version with 5/3 cells:
Uplight on concrete floor.



For installation
in the version with 5/3 cells:
Downlight on brick ceiling.




For installation
in the version with 5/3 cells:
Downlight on false ceiling.
Downlight on concrete ceiling.



Skin_S
M. Flood
(pag 508)




Skin_F
M. Flood



Skin_F
M. Flood



Skin_Y
Asymmetric




Skin_FL
Diffused



TOTAL FLEXIBILITY AND BLENDING IN




Skin takes the concept of flexibility to another level through the innovative template that allows the continuous installation of the individual modules positioned at precisely angled step (one every 10°). Operation is intuitive. The modules can be positioned at an angle of up to 60°, following the project layout, by fixing the template under the outer casing. Different configurations of light fixtures can be combined with this innovative anchoring system, creating eye-catching and innovative lighting scenes. The lights can be applied in any architectural setting, even the most delicate and complex, without the need for major structural interventions. An apse or a historic building can be lit in a uniform, respectful manner, with an aesthetic in keeping with the setting.





A template is included with every outer casing

Thanks to the special template, Skin can be used to create curved lines or perfect circles of lights which adapt and blend into columns and non-linear walls. Continuity is guaranteed by the precision of the installation and the careful study of the optic layout avoids unwanted variations in light intensity. There is a configuration for every setting. On the ceiling or floor, the light produced by Skin fits the context, no matter how complex or delicate, thanks to the different openings (Spot, Medium Flood, Medium Wide Flood, Diffused, Asymmetric). The compact size and unusual elongated hexagonal shape make it easy to simultaneously combine multiple configurations.






Skin lets you have fun with lighting. This collection has been conceived and designed to go beyond standard linear or spot lighting.

Skin_F | powerLED | 220-240 V AC






IK10 IP67

	Cct	lm S - lm D	Opt
6 W DC - 6,7 W AC			
BB **83859**	**M**	798 - 586	**15** (15°)
BD **83860**	**W**	852 - 624	**30** (32°)
	N	909 - 666	**45** (46°)
9,6 W DC - 11 W AC			
BB **83862**	**M**	1210 - 861	**15** (15°)
BD **83863**	**W**	1210 - 861	**30** (33°)
	N	1306 - 930	**45** (47°)

Recessed casing: (pag 557)

Skin_F | powerLED | 220-240 V AC






IK08 IP67

	Cct	lm S - lm D	Opt
10 W DC - 11,2 W AC			
BB **83869**	**M**	1330 - 1030	**15** (15°)
BD **83870**	**W**	1420 - 1097	**30** (33°)
	N	1515 - 1170	**45** (46°)
16,2 W DC - 21 W AC			
BB **83866**	**M**	2016 - 1332	**15** (15°)
BD **83867**	**W**	2016 - 1332	**30** (33°)
	N	2177 - 1439	**45** (47°)

Recessed casing: (pag 557)

Skin_FL | topLED | 220-240 V AC






IK10 IP67

	Cct	lm S - lm D	Opt
2,1 W DC - 2,5 W AC			
BB **83865**	**M**	254 - 59	**00** (Diffused)
	W	266 - 62	
	N	275 - 65	

Recessed casing: (pag 557)

Skin_FL | topLED | 220-240 V AC






IK08 IP67

	Cct	lm S - lm D	Opt
3,2 W DC - 3,8 W AC			
BB **83872**	**M**	381 - 80	**00** (Diffused)
	W	399 - 84	
	N	413 - 88	

Recessed casing: (pag 557)

Skin_Y | powerLED | 220-240 V AC






IK08 IP67

	Cct	lm S - lm D	Opt
12,2 W DC - 14 W AC			
BB **83873**	**M**	1584 - 523	**07** (Asym. Ww)
	W	1700 - 561	
	N	1834 - 606	

Recessed casing: (pag 557)


Recessed casings



ABS **83123** L 175 mm
suitable for:
Skin_F / _FL 166 mm

ABS **83124** L 229 mm
suitable for:
Skin_F / _FL / _Y 220 mm

For installation: uplight on concrete pavement, downlight on brick ceiling.



ABS **83125** L 175 mm
suitable for:
Skin_F / _FL 166 mm

ABS **83126** L 229 mm
suitable for:
Skin_F / _FL / _Y 220 mm

For installation: downlight on false ceiling, downlight on concrete ceiling.

XINSHOUGANG BRIDGE
Beijing (China)

Lighting Project:
The Beijing Municipal Engineering Design Research Institute in collaboration with Zhao Ning (Frontera Lighting Design)

PASEO

Transparent or opalescent polycarbonate body.

Paseo family

Paseo_PIXEL



804

The Paseo range comes with a wide choice of optics, lengths, colour temperatures, and controls. These include DALI and 1-10V, and RGBW DMX and RGB pixel **(Pag. 963)** for dynamic lighting management and spectacular architectural illumination. The housings and numerous accessories mean Paseo can be recessed or fitted to a wall, ceiling or floor.







	Paseo_L / _L Antiglare	**Paseo Dark**	**Paseo_X**
W	6,2-6,6-12-13,1-13,6-19,5-24-31	6,2-12-15	7-8-17-17,3
mm	**512-1152-1452**	**594-1176-1467**	**576-1152**
Cct	2700-3000-4000-RGBW	2700-3000-4000	2700-3000-4000-RGBW
Opt	**M.Flood-Diffused Asymmetric Wallwasher**	**Diffused**	**Spot-Flood-M.Flood M.W.Flood-Elliptic Flood**
Elec.	On/Off-0/1-10V-DALI-DMX	On/Off-0/1-10V-DALI	On/Off-DALI-DMX
Col.	TR OP	BB	TR




Minimal size
The Paseo models are even thinner and more versatile, with width of 24 to 26 millimetres that adapt easily to any design need. Their very small size is combined with simple, minimalist aesthetics.





For cables and power supply/control contact Linea Light support service.

Maximum protection
An electrostatic discharge occurs when, between two bodies that are close or at contact, there occurs a transfer of charges which could at times damage electronics and LED modules. Paseos with incorporated drivers come with an up to 4KV electrostatic discharge (ESD) protection.



Ultrasonic-welded caps offer perfect mechanical resistance and light continuity


Thermoplastic PUR cables with IP67 quick coupling connectors made of M12 with 4 or 5 poles

Steel spring for safe coupling of the Paseo profile to the outer casing

Apparatus equipped TCS® valve, to avoid the formation of humidity in the profile

Paseo_L | topLED | 24 V DC





	Cct	lm S - lm D	Opt
L 512 mm - 6,6 W DC			
TR **97673**	**M**	662 - 507	**20** (37°x 99°)
	W	720 - 552	**07** (Asym. Ww)
	N	749 - 574	
L 512 mm - 6,6 W DC			
OP **81328**	**M**	662 - 330	**00** (Diffused)
	W	720 - 359	
	N	749 - 374	

Electronics: **DM** (pag 567) | Recessed casing, accessories & cables: (pag 564-567)

L 1152 mm - 13,6 W DC			
TR **97674**	**M**	1208 - 931	**20** (34°x 117°)
	W	1313 - 1013	**07** (Asym. Ww)
	N	1365 - 1053	
L 1152 mm - 13,6 W DC			
OP **81329**	**M**	1208 - 624	**00** (Diffused)
	W	1313 - 679	
	N	1365 - 706	


Electronics: **DN** (pag 567) | Recessed casing, accessories & cables: (pag 564-567)

L 1452 mm - 19,5 W DC			
TR **97675**	**M**	1913 - 1474	**20** (34°x 117°)
	W	2079 - 1604	**07** (Asym. Ww)
	N	2162 - 1667	
L 1452 mm - 19,5 W DC			
OP **81330**	**M**	1913 - 988	**00** (Diffused)
	W	2079 - 1075	
	N	2162 - 1117	

Electronics: **DO** (pag 567) | Recessed casing, accessories & cables: (pag 564-567)

Paseo_L | topLED | 220-240 V AC






	Cct	lm S - lm D	Opt
L 512 mm - 6,6 W DC - 7,4 W AC			
TR **96150**	**M**	662 - 507	**20** (37°x 99°)
	W	720 - 552	**07** (Asym. Ww)
	N	749 - 574	
L 512 mm - 6,6 W DC - 7,4 W AC			
OP **81331**	**M**	662 - 330	**00** (Diffused)
	W	720 - 359	
	N	749 - 374	
L 1152 mm - 13,6 W DC - 15,2 W AC			
TR **96151**	**M**	1208 - 931	**20** (34°x 117°)
	W	1313 - 1013	**07** (Asym. Ww)
	N	1365 - 1053	
L 1152 mm - 13,6 W DC - 15,2 W AC			
OP **81332**	**M**	1208 - 624	**00** (Diffused)
	W	1313 - 679	
	N	1365 - 706	
L 1452 mm - 19,5 W DC - 21,8 W AC			
TR **96152**	**M**	1913 - 1474	**20** (34°x 117°)
	W	2079 - 1604	**07** (Asym. Ww)
	N	2162 - 1667	
L 1452 mm - 19,5 W DC - 21,8 W AC			
OP **81333**	**M**	1913 - 988	**00** (Diffused)
	W	2079 - 1075	
	N	2162 - 1117	

Recessed casing, accessories & cables: (pag 564-567)

Paseo_L Anti-glare | topLED | 24 V DC





IK08 IP67 NO-GLARE

	Cct	lm S - lm D	Opt	
L 512 mm - 6,6 W DC				
TR **94021**	**M**	662 - 264	**20**	(37°x 99°)
	W	720 - 288	**07**	(Asym. Ww)
	N	749 - 294		


Electronics: **DM** (pag 567) | Recessed casing, accessories & cables: (pag 564-567)

L 1152 mm - 13,6 W DC				
TR **94022**	**M**	1208 - 496	**20**	(34°x 117°)
	W	1313 - 537	**07**	(Asym. Ww)
	N	1365 - 548		

Electronics: **DN** (pag 567) | Recessed casing, accessories & cables: (pag 564-567)

Paseo_L Anti-glare | topLED | 220-240 V AC






IK08 IP67 NO-GLARE

	Cct	lm S - lm D	Opt	
L 512 mm - 6,2 W DC - 7 W AC				
TR **93994**	**M**	662 - 264	**20**	(37°x 99°)
	W	720 - 288	**07**	(Asym. Ww)
	N	749 - 294		
L 1152 mm - 13,1 W DC - 15 W AC				
TR **93995**	**M**	1208 - 496	**20**	(34°x 117°)
	W	1313 - 537	**07**	(Asym. Ww)
	N	1365 - 548		

Paseo_L | topLED | 24 V DC






IK08 IP67 DMX RDM RGBW

	Cct		Opt	
L 512 mm - 12 W AC				
OP **84055**	**V**	RGBW (3000K)	**00**	(Diffused)
	Q	RGBW (4000K)		
L 1152 mm - 24 W AC				
OP **84056**	**V**	RGBW (3000K)		
	Q	RGBW (4000K)		
L 1452 mm - 31 W AC				
OP **84057**	**V**	RGBW (3000K)		
	Q	RGBW (4000K)		

Electronics: **AM2** (pag 567) | Recessed casing, accessories & cables: (pag 564-567)

Device equipped with Anti-glare profile for reducing direct glaring. The light emission intensity remains unvaried though.

NO-GLARE



Finishes

OP Opaline
TR Transparent

Cct

M 2700 **N** 4000 **Q** RGBW (4000)
W 3000 **V** RGBW (3000)



ATHENS INTERNATIONAL AIRPORT
Athens (Greece)

Project: Alexandros N. Tombazis and Associates | AVW Architecture


Façade Lighting:
Eleftheria Deko & Associates

Structural Design:
Alexandros Athanasiadis & Associates | Kyriaki Kalantzi

Photography:
Gavriil Papadiotis

Paseo Dark | topLED | 48 V DC





Steel fixing brackets included

48V


	Cct	lm S - lm D	Opt
L 594 mm - 6,2 W DC			
BB **84214**	**M**	740 - 262	**00** (Diffused)
	W	760 - 270	
	N	828 - 293	
L 1176 mm - 12 W DC			
BB **84215**	**M**	1480 - 524	
	W	1520 - 540	
	N	1656 - 586	
L 1467 mm - 15 W DC			
BB **84216**	**M**	1850 - 658	
	W	1900 - 677	
	N	2070 - 736	

For cables and power supply/control contact Linea Light support service.

Electronics: **EK** (pag 567) | Accessories & cables: (pag 564-567)

Paseo_X | powerLED | 220-240 V AC






	Cct	lm S - lm D	Opt
L 576 mm - 12 LED - 7 W DC - 7,7 W AC			
TR **96196**	**M**	1128 - 814	**08** (15°x 27°)
	W	1212 - 873	**15** (24°x 32°)
	N	1284 - 925	**30** (30°x 37°)
L 1152 mm - 24 LED - 17,3 W DC - 19,4 W AC			**60** (46°x 51°)
TR **96197**	**M**	2544 - 1836	**25** (28°x 58°)
	W	2736 - 1975	
	N	2904 - 2093	

Recessed casing, accessories & cables: (pag 564-567)

Paseo_X | DALI | powerLED | 220-240 V AC






DALI

	Cct	lm S - lm D	Opt
L 576 mm - 12 LED - 7 W DC - 7,7 W AC			
TR **97256**	**M**	1128 - 814	**08** (15°x 27°)
	W	1212 - 873	**15** (24°x 32°)
	N	1284 - 925	**30** (30°x 37°)
L 1152 mm - 24 LED - 17,3 W DC - 19,4 W AC			**60** (46°x 51°)
TR **97612**	**M**	2256 - 1836	**25** (28°x 58°)
	W	2424 - 1975	
	N	2568 - 2093	

Recessed casing, accessories & cables: (pag 564-567)

Paseo_X | powerLED | 220-240 V AC






DMX RDM RGBW

	Cct	Opt
L 576 mm - 12 LED - 8 W DC - 9 W AC		
TR **84058**	**V** RGBW (3000K)	**25** (28°x 58°)
	Q RGBW (4000K)	
L 1152 mm - 24 LED - 17 W DC - 19 W AC		
TR **84059**	**V** RGBW (3000K)	
	Q RGBW (4000K)	


Electronics: **AM3** (pag 567) | Recessed casing, accessories & cables: (pag 564-567)

Recessed casings

Paseo | Outer casing for floor-mounted recessed installation




Outer casing - Frame




AM 98355 513 mm x Paseo 512 mm
AM 98430 577 mm x Paseo 576 mm
AM 98356 1153 mm x Paseo 1152 mm
AM 98357 1453 mm x Paseo 1452 mm
suitable for: Paseo_L / Paseo_L Anti-glare / Paseo_X / Paseo_PIXEL




Cable gland




AM 98471 513 mm x Paseo 512 mm
AM 98472 577 mm x Paseo 576 mm
AM 98473 1153 mm x Paseo 1152 mm
AM 98474 1453 mm x Paseo 1452 mm
suitable for: Paseo_L / Paseo_L Anti-glare / Paseo_X / Paseo_PIXEL



Installation accessories



98876 2 x Terminal caps for closing the profile




98553 2 x Joining cap between the outer casings with hole for passing cables through

Paseo | Outer casing for floor-mounted or ceiling-mounted flushed installation




Outer casing - Frameless




AM 98467 513 mm x Paseo 512 mm
AM 98468 577 mm x Paseo 576 mm
AM 98469 1153 mm x Paseo 1152 mm
AM 98470 1453 mm x Paseo 1452 mm
suitable for: Paseo_L / Paseo_L Anti-glare / Paseo_X / Paseo_PIXEL




Cable gland




AM 98471 513 mm x Paseo 512 mm
AM 98472 577 mm x Paseo 576 mm
AM 98473 1153 mm x Paseo 1152 mm
AM 98474 1453 mm x Paseo 1452 mm
suitable for: Paseo_L / Paseo_L Anti-glare / Paseo_X / Paseo_PIXEL






Installation accessories





98466 2 x Terminal caps for closing the profile




98554 2 x Joining cap between the outer casings with hole for passing cables through

Paseo | Outer casing for installation on dropped ceiling with springs









AM **98374** 513 mm x Paseo 512 mm
AM **98435** 577 mm x Paseo 576 mm
AM **98375** 1153 mm x Paseo 1152 mm
AM **98376** 1453 mm x Paseo 1452 mm
suitable for: Paseo_L / Paseo_X / Paseo_PIXEL


Installation accessories




98465 2 x Terminal caps for closing the profile

Paseo | Outer casing for flush-mounted installation on dropped ceiling









AM **98367** 513 mm x Paseo 512 mm
AM **98434** 577 mm x Paseo 576 mm
AM **98368** 1153 mm x Paseo 1152 mm
AM **98369** 1453 mm x Paseo 1452 mm
suitable for: Paseo_L / Paseo_X / Paseo_PIXEL


Installation accessories




98464 2 x Terminal caps for closing the profile

Paseo | Outer casing for "3D" ceiling-mounted installation









AM **98836** 513 mm x Paseo 512 mm
AM **98839** 577 mm x Paseo 576 mm
AM **98837** 1153 mm x Paseo 1152 mm
AM **98838** 1453 mm x Paseo 1452 mm
suitable for: Paseo_L / Paseo_X / Paseo_PIXEL

Installation accessories




98840 2 x Terminal caps for closing the profile




98841 2 x Joining cap between the outer casings with hole for passing cables through

Paseo | Outer casing with bracket for wall-mounted installation








AM **98842** 517 mm x Paseo 512 mm
AM **98843** 581 mm x Paseo 576 mm
AM **98844** 1157 mm x Paseo 1152 mm
AM **98845** 1457 mm x Paseo 1452 mm
suitable for: Paseo_L / Paseo_X / Paseo_PIXEL

Installation accessories



Included 2 x Terminal caps for closing the profile


Finishes

AM Anodised Aluminium

Accessories

Paseo | Orientable floor-standing fixing system





TR **98771** 2 x Orientable clips


Pair of fixing clips made of transparent polycarbonate so as not to alter the light emission of Paseo. Orientable accessory, allows to adjust the inclination of Paseo from +90° up to -90°.

suitable for: Paseo_L / Paseo_X / Paseo_PIXEL



Paseo | Extraction key






AM **98475** Extraction key


Paseo extraction key is the tool you need to extract Paseo from the outer casing. Compatible with any type of Paseo outer casing.

suitable for: Paseo_L / Paseo_X / Paseo_PIXEL



Paseo | Fixing base





IS **98772** L 300 - L1 200 mm Paseo 512 - 576 mm
IS **98773** L 950 - L1 850 mm Paseo 1152 - 1452 mm

Possibility of using the independent plate (plate + clip + Paseo) as moveable support without fixing it to a surface (clips 98771 not included).

suitable for: Paseo_L / Paseo_X / Paseo_PIXEL



IS **Included** Steel fixing brackets included

suitable for: Paseo Dark



IS **83162** Support bracket for wall installation

suitable for: Paseo_L / Paseo_X / Paseo Dark / Paseo_PIXEL

Cables

24 V DC 220-240 V AC | Power cables



BB **99216** Conn. F.4 pin M12 (L 1,5m)
BB **89190** Conn. F.4 pin M12 (L 5m)
suitable for: Paseo

DMX | Cables



BB **89186** Conn. M.5 pin M12 + M.3 pin XLR (L 5m)
suitable for: Paseo

DMX | Cables



BB **98493** Conn. M.5 pin M12 + M.5 pin XLR (L 5m)
suitable for: Paseo

24 V DC 220-240 V AC | Extension cables



BB **98437** Conn M. + F. 4 pin M12 (L 1m)
BB **98149** Conn M. + F. 4 pin M12 (L 5m)
BB **89188** Conn M. + F. 4 pin M12 (L 10m)
suitable for: Paseo

1-10 V & DALI | Extension cables



BB **89361** Conn M. + F. 5 pin M12 (L 10m)
suitable for: Paseo

DMX | Cables



BB **89189** Conn. M.5 pin M12 (L 5m)
suitable for: Paseo

DMX | Cables



BB **98494** Conn. M.5 pin M12 + F.3 pin XLR (L 5m)
suitable for: Paseo

1-10 V & DALI | Cables



BB **99879** Conn M. 5 pin M12 (L 5m)
suitable for: Paseo

DMX | Extension cables



BB **98994** Conn. M. / F. 5 pin M12 (L 1m)
BB **98993** Conn. M. / F. 5 pin M12 (L 5m)
BB **89187** Conn. M. / F. 5 pin M12 (L 10m)
suitable for: Paseo



89365 DMX line closure adapter

Pag. 972

Electronics

AM2

Driver CV	Switching	DMX	C-E700026	89365
ON/OFF 24V DC 14W - 240W Pag. 950-951	24V DC 50W - 500W Pag. 945-946	Controllers Pag. 963	DMX/RDM addresser	120 Ohm DMX line closure

AM3

DMX	C-E700026	89365
Controllers Pag. 963	DMX/RDM addresser	120 Ohm DMX line closure

DM

89359	99331	99332	83333	C-E400002
ON/OFF 1 - 6 art. 140 x 115 x h 50	ON/OFF 1 - 20 art. 158 x 60 x h 35 (IP) 70	0/1-10V 1 - 20 art. 158 x 60 x h 35 (IP) 70	DALI/PUSH 1 - 20 art. 188 x 68 x h 34 (IP) 77	DALI/PUSH 1 - 32 art. 188 x 68 x h 34 (IP) 77

DN

89359	99331	99332	83333	C-E400002
ON/OFF 1 - 3 art. 140 x 115 x h 50	ON/OFF 1 - 9 art. 158 x 60 x h 35 (IP) 70	0/1-10V 1 - 9 art. 158 x 60 x h 35 (IP) 70	DALI/PUSH 1 - 9 art. 188 x 68 x h 34 (IP) 77	DALI/PUSH 1 - 15 art. 188 x 68 x h 34 (IP) 77

DO

89359	99331	99332	83333	C-E400002
ON/OFF 1 - 2 art. 140 x 115 x h 50	ON/OFF 1 - 6 art. 158 x 60 x h 35 (IP) 70	0/1-10V 1 - 6 art. 158 x 60 x h 35 (IP) 70	DALI/PUSH 1 - 6 art. 188 x 68 x h 34 (IP) 77	DALI/PUSH 1 - 11 art. 188 x 68 x h 34 (IP) 77

EK

99784	99785	C-E400003	Switching	83177
ON/OFF 150W CV 48V 219 x 63 x h 35 (IP) 80	ON/OFF 240W CV 48V 244 x 71 x h 38 (IP) 81	DALI/PUSH 150W CV 48V 188 x 68 x h 34 (IP) 77	CV 48V Pag. 945-946	Dimmer DMX 312W 97 x 36 x h 62

Finishes

BB Black

XENIA

Xenia family

Xenia_Blade



792

Xenia_PIXEL



806

Xenia is a professional outdoor linear lighting system. Its structure has been completely redesigned, reducing the amount of aluminium for greater sustainability, while maintaining sturdiness and durability. Wall or floor installation options, recessed with flange or frameless, for full flexibility in integrating with the architecture. With a wide optical range and 5 different lengths, Xenia luminaires are ideal for illuminating façades or highlighting architectural details, giving the building a distinctive visual presence. Anodised 6060 aluminium alloy body.














	_W pag 573-574	**_W PRO** pag 575	**_A** pag 578	**_AL** pag 579	**_A PRO** pag 580-581	**_A PRO MicroLouvre** pag 581	**_AF** pag 582	**_ALF** pag 583	**_AF PRO** pag 584-585	**_AF PRO MicroLouvre** pag 585
	Wall		**Recessed - Frame**				**Recessed - Frameless**			
Length	366 -->1530	366 -->1530	359-->1519	359-->1519	160-->1519	359-->1519	359-->1519	359-->1519	160-->1519	359-->1519
Power	6,1 -->27,5	8 -->37,4	6,4 -->27,4	1,7 -->22	4,5 -->37	7,4 -->37	6,4 -->27,4	1,7 -->22	4,5 -->37	7,4 -->37
topLED	2200K 2700K 3000K 4000K RGBW	-	2200K 2700K 3000K 4000K RGBW	2200K 2700K 3000K 4000K RGBW	-	-	2200K 2700K 3000K 4000K RGBW	2200K 2700K 3000K 4000K RGBW	-	-
powerLED	2200K 2700K 3000K 4000K	2200K 2700K 3000K 4000K RGBW	-	-	2200K 2700K 3000K 4000K RGBW	2200K 2700K 3000K 4000K	-	-	2200K 2700K 3000K 4000K RGBW	2200K 2700K 3000K 4000K
Optics	Flood Elliptic Asymm. Ww Diffused	Flood Elliptic Asymm. Ww	Elliptic Asymm. Ww	Diffused	Spot M.Flood W.Flood Elliptic Asymm. Ww	Spot M.Flood W.Flood Elliptic Asymm. Ww	Elliptic Asymm. Ww	Diffused	Spot M.Flood W.Flood Elliptic Asymm. Ww	Spot M.Flood W.Flood Elliptic Asymm. Ww
Finish	AM	AM	AM	AM	AM	AM	AM	AM	AM	AM
Driver	On/Off 0/1-10V DALI	-	On/Off 0/1-10V DALI	On/Off 0/1-10V DALI	On/Off DALI	-	On/Off 0/1-10V DALI	On/Off 0/1-10V DALI	On/Off DALI	-
Driver	On/Off DMX	On/Off DALI DMX	On/Off	On/Off DMX	On/Off DALI DMX	On/Off DALI	On/Off	On/Off DMX	On/Off DALI DMX	On/Off DALI


SMALL DETAILS, BIG DIFFERENCES!

NEW


+40%

EFFICIENCY


COMPARED TO THE PREVIOUS VERSION




XENIA WALL: A RANGE OF ACCESSORIES DESIGNED TO OFFER MAXIMUM INSTALLATION FLEXIBILITY.



Tiltable bracket (C-F400006)



Fixed bracket for surface mounting (C-F400008)




Cantilever bracket (available in various lengths)




MicroLouvre

Xenia_MicroLouvre keeps all the distinctive features of the Xenia family, guaranteeing superior visual comfort. This is made possible by the integration of a special anti-glare grid that divides the light beam into microcells. The extremely thin grid does not compromise the quality or uniformity of the emitted light but effectively reduces glare.



With MicroLouvre



Without MicroLouvre



Scale 1:1

Xenia A / AF recessed


- The Xenia A and AF versions allow the creation of continuous lines of light. The fixtures are designed to be installed in a continuous row, ensuring maximum light uniformity without interruptions.
- The installation is quick and easy thanks to the innovative outer casings; the particular structure allows mounting close to the wall.
- MicroLouvre anti-glare system.
- Size range: 359 mm --> 1519 mm.
- Optical range: Spot, Medium Flood, Wide Flood, Elliptic, Asymmetric Wall Washer, Diffused.
- Maximum durability and reliability in any situation: the Xenia A and AF fixtures have an extremely resistant and robust structure, strong enough to be driven over by vehicles, and boast an IK08 rating for mechanical impact resistance.



Xenia with end caps accessory (83188)

Xenia without end caps accessory (83188)

IK08 IP68






HOTEL PORTRAIT
Milan (Italy)

Lighting Designer:
Alexander Bellman, Gruppo C14

Xenia_W | V2 | topLED | 24 V DC







DW Dynamic White available on request


IP66 NEW

	Fin	Cct	lm S - lm D	Opt
L 366 mm - 6,4 W DC				
C00517	**AM**	**A**	930 - 776	**3F** (27°x 91°)
		M	1085 - 906	**WW** (Asym. Ww)
		W	1133 - 946	**DI** (Diffused)
		N	1199 - 1001	
L 630 mm - 11 W DC				
C00518	**AM**	**A**	1594 - 1330	
		M	1860 - 1552	
		W	1942 - 1621	
		N	2056 - 1715	
L 930 mm - 16,5 W DC				
C00519	**AM**	**A**	2391 - 1995	
		M	2790 - 2328	
		W	2913 - 2431	
		N	3084 - 2572	
L 1230 mm - 22 W DC				
C00520	**AM**	**A**	3188 - 2660	
		M	3720 - 3103	
		W	3884 - 3241	
		N	4112 - 3429	
L 1530 mm - 27,5 W DC				
C00521	**AM**	**A**	3985 - 3325	
		M	4650 - 3879	
		W	4855 - 4051	
		N	5140 - 4287	

Electronics: **AL** (pag 589) | Accessories: (pag 588)

Xenia_W | V2 | topLED | 220-240 V AC





DW Dynamic White available on request


IK07 IP66 NEW

	Fin	Cct	lm S - lm D	Opt
L 366 mm - 6,4 W DC - 7,2 W AC				
C00522	**AM**	**A**	930 - 776	**3F** (27°x 91°)
		M	1085 - 906	**WW** (Asym. Ww)
		W	1133 - 946	**DI** (Diffused)
		N	1199 - 1001	
L 630 mm - 11 W DC - 12,3 W AC				
C00523	**AM**	**A**	1594 - 1330	
		M	1860 - 1552	
		W	1942 - 1621	
		N	2056 - 1715	
L 930 mm - 16,5 W DC - 18,5 W AC				
C00524	**AM**	**A**	2391 - 1995	
		M	2790 - 2328	
		W	2913 - 2431	
		N	3084 - 2572	
L 1230 mm - 22 W DC - 24,6 W AC				
C00525	**AM**	**A**	3188 - 2660	
		M	3720 - 3103	
		W	3884 - 3241	
		N	4112 - 3429	
L 1530 mm - 27,5 W DC - 30,8 W AC				
C00526	**AM**	**A**	3985 - 3325	
		M	4650 - 3879	
		W	4855 - 4051	
		N	5140 - 4287	

Accessories: (pag 588) | Cables: (pag 589)

Xenia_W RGBW DMX/RDM | V2 | topLED | 220-240 V AC





DW Dynamic White available on request

IK07 IP66 NEW DMX RDM RGBW

	Fin	Cct	Opt
L 535 mm - 13 W DC - 13 W AC			
C00527	**AM**	**V** RGBW (3000K)	**3F** (27°x 91°)
		Q RGBW (4000K)	**WW** (Asym. Ww)
			DI (Diffused)
L 1182 mm - 22 W DC - 24 W AC			
C00528	**AM**	**V** RGBW (3000K)	
		Q RGBW (4000K)	

Electronics: **AM13** (pag 589) | Accessories: (pag 588) | Cables: (pag 589)

Finishes


Anodised Aluminium

Cct

A 2200 **W** 3000
M 2700 **N** 4000

Xenia_W | V2 | powerLED | 630 mA








DW Dynamic White available on request

	Fin	Cct	lm S - lm D	Opt
L 366 mm - 3 LED - 6,1 W DC				
C00529	**AM**	**A**	597 - 423	**FL** (29°)
		M	798 - 555	**3F** (29°x 92°)
		W	852 - 595	**EM** (35°x 47°)
		N	909 - 634	**WW** (Asym. Ww)
Electronics: **BI** (pag 589) | Accessories: (pag 588) | Cables: (pag 589)				
L 630 mm - 6 LED - 12,1 W DC				
C00530	**AM**	**A**	1122 - 790	**FL** (29°)
		M	1494 - 1037	**3F** (29°x 92°)
		W	1594 - 1111	**EM** (35°x 47°)
		N	1704 - 1186	**WW** (Asym. Ww)
Electronics: **BQ** (pag 589) | Accessories: (pag 588) | Cables: (pag 589)				
L 930 mm - 9 LED - 17,9 W DC				
C00531	**AM**	**A**	1683 - 1187	**FL** (29°)
		M	2241 - 1558	**3F** (29°x 92°)
		W	2394 - 1670	**EM** (35°x 47°)
		N	2556 - 1782	**WW** (Asym. Ww)
Electronics: **BL** (pag 589) | Accessories: (pag 588) | Cables: (pag 589)				
L 1230 mm - 12 LED - 24,3 W DC				
C00532	**AM**	**A**	2244 - 1583	**FL** (29°)
		M	2988 - 2077	**3F** (29°x 92°)
		W	3192 - 2226	**EM** (35°x 47°)
		N	3408 - 2375	**WW** (Asym. Ww)
Electronics: **BR** (pag 589) | Accessories: (pag 588) | Cables: (pag 589)				

Xenia_W | V2 | powerLED | 220-240 V AC





DW Dynamic White available on request

	Fin	Cct	lm S - lm D	Opt
L 366 mm - 3 LED - 6,1 W DC - 7,8 W AC				
C00534	**AM**	**A**	597 - 423	**FL** (29°)
		M	798 - 555	**3F** (29°x 92°)
		W	852 - 595	**EM** (35°x 47°)
		N	909 - 634	**WW** (Asym. Ww)
L 630 mm - 6 LED - 12,1 W DC - 14,2 W AC				
C00535	**AM**	**A**	1122 - 790	
		M	1494 - 1037	
		W	1594 - 1111	
		N	1704 - 1186	
L 930 mm - 9 LED - 17,9 W DC - 20,4 W AC				
C00536	**AM**	**A**	1683 - 1187	
		M	2241 - 1558	
		W	2394 - 1670	
		N	2556 - 1782	
L 1230 mm - 12 LED - 24,3 W DC - 27,2 W AC				
C00537	**AM**	**A**	2244 - 1583	
		M	2988 - 2077	
		W	3192 - 2226	
		N	3408 - 2375	

Accessories: (pag 588) | Cables: (pag 589)

Finishes


Anodised Aluminium

Cct

A 2200 **W** 3000
M 2700 **N** 4000

Xenia_W PRO | V2 | powerLED | 220-240 V AC





DW Dynamic White available on request


IK07 IP66 NEW

	Fin	Cct	lm S - lm D	Opt
L 366 mm - 6 LED - 8 W DC - 9 W AC				
C00544	**AM**	**A**	828 - 577	**FL** (29°)
		M	1086 - 758	**3F** (29°x 92°)
		W	1164 - 812	**EM** (35°x 47°)
		N	1242 - 866	**WW** (Asym. Ww)
L 630 mm - 12 LED - 15,1 W DC - 17 W AC				
C00545	**AM**	**A**	1656 - 1154	
		M	2172 - 1515	
		W	2328 - 1623	
		N	2484 - 1732	
L 930 mm - 18 LED - 23,1 W DC - 26,2 W AC				
C00546	**AM**	**A**	2250 - 1606	
		M	3024 - 2104	
		W	3240 - 2259	
		N	3456 - 2410	
L 1230 mm - 24 LED - 31,8 W DC - 35,4 W AC				
C00547	**AM**	**A**	3000 - 2142	
		M	4032 - 2810	
		W	4320 - 3012	
		N	4608 - 3214	
L 1530 mm - 30 LED - 37,4 W DC - 44 W AC				
C00548	**AM**	**A**	3750 - 2677	
		M	5040 - 3513	
		W	5400 - 3765	
		N	5760 - 4017	

Accessories: (pag 588) | Cables: (pag 589)

Xenia_W PRO | V2 | DALI | powerLED | 220-240 V AC





DW Dynamic White available on request


IK07 IP66 NEW **DALI**

	Fin	Cct	lm S - lm D	Opt
L 630 mm - 12 LED - 15,1 W DC - 17,1 W AC				
C00550	**AM**	**A**	1656 - 1154	**FL** (29°)
		M	2172 - 1515	**3F** (29°x 92°)
		W	2328 - 1623	**EM** (35°x 47°)
		N	2484 - 1732	**WW** (Asym. Ww)
L 930 mm - 18 LED - 23,1 W DC - 26,2 W AC				
C00551	**AM**	**A**	2250 - 1606	
		M	3024 - 2104	
		W	3240 - 2259	
		N	3456 - 2410	
L 1230 mm - 24 LED - 31,8 W DC - 35,4 W AC				
C00552	**AM**	**A**	3000 - 2142	
		M	4032 - 2810	
		W	4320 - 3012	
		N	4608 - 3214	
L 1530 mm - 30 LED - 37,4 W DC - 44 W AC				
C00553	**AM**	**A**	3750 - 2677	
		M	5040 - 3513	
		W	5400 - 3765	
		N	5760 - 4017	

Accessories: (pag 588) | Cables: (pag 589)

Xenia_W PRO RGBW DMX/RDM | V2 | powerLED | 220-240 V AC





DW Dynamic White available on request

IK07 IP66 NEW DMX RDM RGBW

	Fin	Cct		Opt
L 500 mm - 3x4 LED - 7,3 W DC - 8,5W AC				
C00554	**AM**	**V**	RGBW (3000K)	**EF** (20°÷29°)x(41°÷60°)
		Q	RGBW (4000K)	
L 1182 mm - 8x4 LED - 19,3 W DC - 22,6 W AC				
C00555	**AM**	**V**	RGBW (3000K)	
		Q	RGBW (4000K)	


Electronics: **AM13** (pag 589) | Accessories: (pag 588) | Cables: (pag 589)

Finishes

Anodised Aluminium

Cct

A 2200 **M** 2700 **W** 3000 **N** 4000 **V** RGBW (3000) **Q** RGBW (4000)



NH COLLECTION CITY LIFE MILANO
Milan (Italy)

Architectural project:
Quattroassociati

Lighting Designer:
Esa engineering

Client:
Igefi for Nh Hotel

Photography:
Andrea Martiradonna





HOTEL MAMA SHELTER
Rennes (France)

Project:
Mama Shelter Hotel

Lighting Designer:
Distylight


Architectural project:
DTACC

Photography:
Cyril Folliot



Xenia_A | V2 | topLED | 24 V DC






DW Dynamic White available on request

	Fin	Cct	lm S - lm D	Opt
L 359 mm - 6,4 W DC				
C00556	**AM**	**A**	930 - 565	**3F** (24°x 86°)
		M	1085 - 659	**WW** (Asym. Ww)
		W	1133 - 688	
		N	1199 - 728	
L 619 mm - 11 W DC				
C00557	**AM**	**A**	1594 - 968	
		M	1860 - 1128	
		W	1942 - 1178	
		N	2056 - 1247	
L 919 mm - 16,5 W DC				
C00558	**AM**	**A**	2391 - 1451	
		M	2790 - 1692	
		W	2913 - 1767	
		N	3084 - 1870	
L 1219 mm - 22 W DC				
C00559	**AM**	**A**	3188 - 1935	
		M	3720 - 2256	
		W	3884 - 2356	
		N	4112 - 2493	
L 1519 mm - 27,5 W DC				
C00560	**AM**	**A**	3985 - 2418	
		M	4650 - 2820	
		W	4855 - 2945	
		N	5140 - 3116	

Electronics: **AL** (pag 589) | Recessed casings, accessories & cables: (pag 588/589)

Xenia_A | V2 | topLED | 220-240 V AC






DW Dynamic White available on request

	Fin	Cct	lm S - lm D	Opt
L 359 mm - 6,4 W DC - 7,2 W AC				
C00561	**AM**	**A**	930 - 565	**3F** (24°x 86°)
		M	1085 - 659	**WW** (Asym. Ww)
		W	1133 - 688	
		N	1199 - 728	
L 619 mm - 11 W DC - 12,3 W AC				
C00562	**AM**	**A**	1594 - 968	
		M	1860 - 1128	
		W	1942 - 1178	
		N	2056 - 1247	
L 919 mm - 16,5 W DC - 18,5 W AC				
C00563	**AM**	**A**	2391 - 1451	
		M	2790 - 1692	
		W	2913 - 1767	
		N	3084 - 1870	
L 1219 mm - 22 W DC - 24,6 W AC				
C00564	**AM**	**A**	3188 - 1935	
		M	3720 - 2256	
		W	3884 - 2356	
		N	4112 - 2493	
L 1519 mm - 27,5 W DC - 30,8 W AC				
C00565	**AM**	**A**	3985 - 2418	
		M	4650 - 2820	
		W	4855 - 2945	
		N	5140 - 3116	

Recessed casings, accessories & cables: (pag 588/589)

Xenia_A RGBW DMX/RDM | V2 | topLED | 220-240 V AC






DW Dynamic White available on request

	Fin	Cct	Opt
L 529 mm - 12 W DC - 13 W AC			
C00586	**AM**	**V** RGBW (3000K)	**3F** (24°x 86°)
		Q RGBW (4000K)	**WW** (Asym. Ww)
L 1169 mm - 22 W DC - 24 W AC			
C00587	**AM**	**V** RGBW (3000K)	
		Q RGBW (4000K)	

Electronics: **AM13** (pag 589) | Recessed casings, accessories & cables: (pag 588/589)

Xenia_AL | V2 | topLED | 24 V DC






DW Dynamic White available on request

	Fin	Cct	lm S - lm D	Opt
L 359 mm - 1,7 W DC				
C00566	**AM**	**A**	245 - 67	**DI** (Diffused)
		M	278 - 76	
		W	290 - 80	
		N	307 - 84	
L 619 mm - 3 W DC				
C00567	**AM**	**A**	420 - 115	
		M	478 - 131	
		W	498 - 136	
		N	526 - 144	
L 919 mm - 4,5 W DC				
C00568	**AM**	**A**	630 - 173	
		M	717 - 196	
		W	747 - 204	
		N	789 - 216	
L 1219 mm - 6 W DC				
C00569	**AM**	**A**	840 - 230	
		M	956 - 261	
		W	996 - 272	
		N	1052 - 288	
L 1519 mm - 7,5 W DC				
C00570	**AM**	**A**	1050 - 287	
		M	1195 - 326	
		W	1245 - 340	
		N	1315 - 360	

Electronics: **AL** (pag 589) | Recessed casings, accessories & cables: (pag 588/589)

Xenia_AL | V2 | topLED | 220-240 V AC






DW Dynamic White available on request

	Fin	Cct	lm S - lm D	Opt
L 359 mm - 1,7 W DC - 2,5 W AC				
C00571	**AM**	**A**	245 - 67	**DI** (Diffused)
		M	278 - 76	
		W	290 - 80	
		N	307 - 84	
L 619 mm - 3 W DC - 4 W AC				
C00572	**AM**	**A**	420 - 115	
		M	478 - 131	
		W	498 - 136	
		N	526 - 144	
L 919 mm - 4,5 W DC - 6 W AC				
C00573	**AM**	**A**	630 - 173	
		M	717 - 196	
		W	747 - 204	
		N	789 - 216	
L 1219 mm - 6 W DC - 8 W AC				
C00574	**AM**	**A**	840 - 230	
		M	956 - 261	
		W	996 - 272	
		N	1052 - 288	
L 1519 mm - 7,5 W DC - 10 W AC				
C00575	**AM**	**A**	1050 - 287	
		M	1195 - 326	
		W	1245 - 340	
		N	1315 - 360	

Recessed casings, accessories & cables: (pag 588/589)

Xenia_AL RGBW DMX/RDM | V2 | topLED | 220-240 V AC





DW Dynamic White available on request

	Fin	Cct		Opt
L 529 mm - 12 W DC - 13 W AC				
C00584	**AM**	**V**	RGBW (3000K)	**DI** (Diffused)
		Q	RGBW (4000K)	
L 1169 mm - 22 W DC - 24 W AC				
C00585	**AM**	**V**	RGBW (3000K)	
		Q	RGBW (4000K)	

Electronics: **AM13** (pag 589) | Recessed casings, accessories & cables: (pag 588/589)

Finishes


Anodised Aluminium

Cct

A 2200 **M** 2700 **W** 3000 **N** 4000 **V** RGBW (3000) **Q** RGBW (4000)

Xenia_A PRO | V2 | powerLED | 500 mA





DW Dynamic White available on request

	Fin	Cct	lm S - lm D	Opt
L160 mm - 3 LED - 4,5 W DC				
C00588	**AM**	**A**	453 - 354	**SP** (19°)
		M	597 - 466	**ML** (36°)
		W	639 - 499	**WF** (67°)
		N	681 - 532	**EF** (21°x 42°)
				WW (Asym. Ww)

Electronics: **BW** (pag 589) | Recessed casings, accessories & cables: (pag 588/589)


DW Dynamic White available on request

	Fin	Cct	lm S - lm D	Opt
L 359 mm - 6 LED - 7,4 W DC - 8,3 W AC				
C00589	**AM**	**A**	828 - 631	**SP** (19°)
		M	1086 - 848	**ML** (36°)
		W	1164 - 909	**WF** (67°)
		N	1242 - 970	**EF** (21°x 42°)
L 619 mm - 12 LED - 14,8 W DC - 16,5 W AC				**WW** (Asym. Ww)
C00590	**AM**	**A**	1656 - 1261	
		M	2172 - 1695	
		W	2328 - 1817	
		N	2484 - 1939	
L 919 mm - 18 LED - 22,2 W DC - 24,8 W AC				
C00591	**AM**	**A**	2250 - 1755	
		M	3024 - 2359	
		W	3240 - 2528	
		N	3456 - 2697	
L 1219 mm - 24 LED - 29,6 W DC - 33,2 W AC				
C00592	**AM**	**A**	3000 - 2339	
		M	4032 - 3145	
		W	4320 - 3371	
		N	4608 - 3597	
L 1519 mm - 30 LED - 37 W DC - 41,3 W AC				
C00593	**AM**	**A**	3750 - 2924	
		M	5040 - 3931	
		W	5400 - 4213	
		N	5760 - 4496	

Recessed casings, accessories & cables: (pag 588/589)

Xenia_A PRO | V2 | DALI | powerLED | 220-240 V AC





DW Dynamic White available on request

DALI

	Fin	Cct	lm S - lm D	Opt
L 619 mm - 12 LED - 14,8 W DC - 16,5 W AC				
C00595	**AM**	**A**	1656 - 1261	**SP** (19°)
		M	2172 - 1695	**ML** (36°)
		W	2328 - 1817	**WF** (67°)
		N	2484 - 1939	**EF** (21°x 42°)
L 919 mm - 18 LED - 22,2 W DC - 24,8 W AC				**WW** (Asym. Ww)
C00596	**AM**	**A**	2250 - 1755	
		M	3024 - 2359	
		W	3240 - 2528	
		N	3456 - 2697	
L 1219 mm - 24 LED - 29,6 W DC - 33,2 W AC				
C00597	**AM**	**A**	3000 - 2339	
		M	4032 - 3145	
		W	4320 - 3371	
		N	4608 - 3597	
L 1519 mm - 30 LED - 37 W DC - 41,3 W AC				
C00598	**AM**	**A**	3750 - 2924	
		M	5040 - 3931	
		W	5400 - 4213	
		N	5760 - 4496	

Recessed casings, accessories & cables: (pag 588/589)

Finishes


Anodised Aluminium

Cct

A 2200 **W** 3000
M 2700 **N** 4000

Xenia_A PRO RGBW DMX/RDM | V2 | powerLED | 220-240 V AC





DW Dynamic White available on request


IK08 IP68 NEW DMX RDM +RGBW

	Fin	Cct		Opt
L 529 mm - 3x4 LED - 7,3 W DC - 8,5 W AC				
C00599	**AM**	**V**	RGBW (3000K)	**EF** (21°x 42°)
		Q	RGBW (4000K)	
L 1169 mm - 8x4 LED - 19,3 W DC - 22,6 W AC				
C00600	**AM**	**V**	RGBW (3000K)	**EF** (21°x 42°)
		Q	RGBW (4000K)	

Electronics: **AM13** (pag 589) | Recessed casings, accessories & cables: (pag 588/589)

Xenia_A PRO Micro Louvre | V2 | powerLED | 220-240 V AC





DW Dynamic White available on request


IK08 IP68 NEW

	Fin	Cct	Im S - Im D	Opt
L 359 mm - 6 LED - 7,4 W DC - 8,3 W AC				
C00670	**AM**	**A**	828 - 350	**SP** (10°÷19°)
		M	1086 - 470	**ML** (30°÷39°)
		W	1164 - 504	**WF** (50°÷70°)
		N	1242 - 538	**EF** (20°÷29°)x(41°÷60°)
L 619 mm - 12 LED - 14,8 W DC - 16,5 W AC				**WW** (Asym. Ww)
C00671	**AM**	**A**	1656 - 699	
		M	2172 - 940	
		W	2328 - 1008	
		N	2484 - 1075	
L 919 mm - 18 LED - 22,2 W DC - 24,8 W AC				
C00672	**AM**	**A**	2250 - 973	
		M	3024 - 1308	
		W	3240 - 1402	
		N	3456 - 1496	
L 1219 mm - 24 LED - 29,6 W DC - 33,2 W AC				
C00673	**AM**	**A**	3000 - 1297	
		M	4032 - 1744	
		W	4320 - 1869	
		N	4608 - 1994	
L 1519 mm - 30 LED - 37 W DC - 41,3 W AC				
C00674	**AM**	**A**	3750 - 1622	
		M	5040 - 2180	
		W	5400 - 2336	
		N	5760 - 2493	

Recessed casings, accessories & cables: (pag 588/589)

Xenia_A PRO Micro Louvre | V2 | DALI | powerLED | 220-240 V AC





DW Dynamic White available on request


IK08 IP68 NEW **DALI**

	Fin	Cct	Im S - Im D	Opt
L 619 mm - 12 LED - 14,8 W DC - 16,5 W AC				
C00676	**AM**	**A**	1656 - 699	**SP** (10°÷19°)
		M	2172 - 940	**ML** (30°÷39°)
		W	2328 - 1008	**WF** (50°÷70°)
		N	2484 - 1075	**EF** (20°÷29°)x(41°÷60°)
L 919 mm - 18 LED - 22,2 W DC - 24,8 W AC				**WW** (Asym. Ww)
C00677	**AM**	**A**	2250 - 973	
		M	3024 - 1308	
		W	3240 - 1402	
		N	3456 - 1496	
L 1219 mm - 24 LED - 29,6 W DC - 33,2 W AC				
C00678	**AM**	**A**	3000 - 1297	
		M	4032 - 1744	
		W	4320 - 1869	
		N	4608 - 1994	
L 1519 mm - 30 LED - 37 W DC - 41,3 W AC				
C00679	**AM**	**A**	3750 - 1622	
		M	5040 - 2180	
		W	5400 - 2336	
		N	5760 - 2493	

Recessed casings, accessories & cables: (pag 588/589)

Xenia_AF | V2 | topLED | 24 V DC






DW Dynamic White available on request

	Fin	Cct	lm S - lm D	Opt
L 359 mm - 6,4 W DC				
C00608	**AM**	**A**	930 - 565	**3F** (24°x 86°)
		M	1085 - 659	**WW** (Asym. Ww)
		W	1133 - 688	
		N	1199 - 728	
L 619 mm - 11 W DC				
C00609	**AM**	**A**	1594 - 968	
		M	1860 - 1128	
		W	1942 - 1178	
		N	2056 - 1247	
L 919 mm - 16,5 W DC				
C00610	**AM**	**A**	2391 - 1451	
		M	2790 - 1692	
		W	2913 - 1767	
		N	3084 - 1870	
L 1219 mm - 22 W DC				
C00611	**AM**	**A**	3188 - 1935	
		M	3720 - 2256	
		W	3884 - 2356	
		N	4112 - 2493	
L 1519 mm - 27,5 W DC				
C00612	**AM**	**A**	3985 - 2418	
		M	4650 - 2820	
		W	4855 - 2945	
		N	5140 - 3116	

Electronics: **AL** (pag 589) | Recessed casings, accessories & cables: (pag 588/589)

Xenia_AF | V2 | topLED | 220-240 V AC






DW Dynamic White available on request

	Fin	Cct	lm S - lm D	Opt
L 359 mm - 6,4 W DC - 7,2 W AC				
C00614	**AM**	**A**	930 - 565	**3F** (24°x 86°)
		M	1085 - 659	**WW** (Asym. Ww)
		W	1133 - 688	
		N	1199 - 728	
L 619 mm - 11 W DC - 12,3 W AC				
C00615	**AM**	**A**	1594 - 968	
		M	1860 - 1128	
		W	1942 - 1178	
		N	2056 - 1247	
L 919 mm - 16,5 W DC - 18,5 W AC				
C00616	**AM**	**A**	2391 - 1451	
		M	2790 - 1692	
		W	2913 - 1767	
		N	3084 - 1870	
L 1219 mm - 22 W DC - 24,6 W AC				
C00617	**AM**	**A**	3188 - 1935	
		M	3720 - 2256	
		W	3884 - 2356	
		N	4112 - 2493	
L 1519 mm - 27,5 W DC - 30,8 W AC				
C00618	**AM**	**A**	3985 - 2418	
		M	4650 - 2820	
		W	4855 - 2945	
		N	5140 - 3116	

Recessed casings, accessories & cables: (pag 588/589)

Xenia_AF RGBW DMX/RDM | V2 | topLED | 220-240 V AC






DW Dynamic White available on request

	Fin	Cct	Opt
L 529 mm - 7,3 W DC - 8,5 W AC			
C00650	**AM**	**V** RGBW (3000K)	**3F** (24°x 86°)
		Q RGBW (4000K)	**WW** (Asym. Ww)
L 1169 mm - 19,3 W DC - 22,6 W AC			
C00651	**AM**	**V** RGBW (3000K)	
		Q RGBW (4000K)	

Electronics: **AM13** (pag 589) | Recessed casings, accessories & cables: (pag 588/589)

Xenia_ALF | V2 | topLED | 24 V DC






DW Dynamic White available on request

	Fin	Cct	lm S - lm D	Opt
L 359 mm - 1,7 W DC				
C00619	**AM**	**A**	245 - 67	**DI** (Diffused)
		M	278 - 76	
		W	290 - 80	
		N	307 - 84	
L 619 mm - 3 W DC				
C00620	**AM**	**A**	420 - 115	
		M	478 - 131	
		W	498 - 136	
		N	526 - 144	
L 919 mm - 4,5 W DC				
C00621	**AM**	**A**	630 - 173	
		M	717 - 196	
		W	747 - 204	
		N	789 - 216	
L 1219 mm - 6 W DC				
C00622	**AM**	**A**	840 - 230	
		M	956 - 261	
		W	996 - 272	
		N	1052 - 288	
L 1519 mm - 7,5 W DC				
C00623	**AM**	**A**	1050 - 287	
		M	1195 - 326	
		W	1245 - 340	
		N	1315 - 360	

Electronics: **AL** (pag 589) | Recessed casings, accessories & cables: (pag 588/589)

Xenia_ALF | V2 | topLED | 220-240 V AC






DW Dynamic White available on request

	Fin	Cct	lm S - lm D	Opt
L 359 mm - 1,7 W DC - 2,5 W AC				
C00625	**AM**	**A**	245 - 67	**DI** (Diffused)
		M	278 - 76	
		W	290 - 80	
		N	307 - 84	
L 619 mm - 3 W DC - 4 W AC				
C00626	**AM**	**A**	420 - 115	
		M	478 - 131	
		W	498 - 136	
		N	526 - 144	
L 919 mm - 4,5 W DC - 6 W AC				
C00627	**AM**	**A**	630 - 173	
		M	717 - 196	
		W	747 - 204	
		N	789 - 216	
L 1219 mm - 6 W DC - 8 W AC				
C00628	**AM**	**A**	840 - 230	
		M	956 - 261	
		W	996 - 272	
		N	1052 - 288	
L 1519 mm - 7,5 W DC - 10 W AC				
C00629	**AM**	**A**	1050 - 287	
		M	1195 - 326	
		W	1245 - 340	
		N	1315 - 360	

Recessed casings, accessories & cables: (pag 588/589)

Xenia_ALF RGBW DMX/RDM | V2 | topLED | 220-240 V AC





DW Dynamic White available on request

	Fin	Cct		Opt
L 529 mm - 7,3 W DC - 8,5 W AC				
C00648	**AM**	**V**	RGBW (3000K)	**DI** (Diffused)
		Q	RGBW (4000K)	
L 1169 mm - 19,3 W DC - 22,6 W AC				
C00649	**AM**	**V**	RGBW (3000K)	
		Q	RGBW (4000K)	

Electronics: **AM13** (pag 589) | Recessed casings, accessories & cables: (pag 588/589)

Finishes


Anodised Aluminium

Cct

A 2200 **M** 2700 **W** 3000 **N** 4000 **V** RGBW (3000) **Q** RGBW (4000)

Xenia_AF PRO | V2 | powerLED | 500 mA






DW Dynamic White available on request

Xenia_AF PRO | V2 | powerLED | 220-240 V AC






DW Dynamic White available on request

Xenia_AF PRO | V2 | DALI | powerLED | 220-240 V AC





DW Dynamic White available on request

C.C. IK08 IP68 NEW

	Fin	Cct	lm S - lm D	Opt
L 160 mm - 3 LED - 4,5 W DC				
C00652	**AM**	**A**	453 - 354	**SP** (19°)
		M	597 - 466	**ML** (36°)
		W	639 - 499	**WF** (67°)
		N	681 - 532	**EF** (21°x 42°)
				WW (Asym. Ww)

Electronics: **BW** (pag 589) | Recessed casings, accessories & cables: (pag 588/589)

IK08 IP68 NEW

	Fin	Cct	lm S - lm D	Opt
L 359 mm - 6 LED - 7,4 W DC - 8,3 W AC				
C00653	**AM**	**A**	828 - 631	**SP** (19°)
		M	1086 - 848	**ML** (36°)
		W	1164 - 909	**WF** (67°)
		N	1242 - 970	**EF** (21°x 42°)
L 619 mm - 12 LED - 14,8 W DC - 16,5 W AC				**WW** (Asym. Ww)
C00654	**AM**	**A**	1656 - 1261	
		M	2172 - 1695	
		W	2328 - 1817	
		N	2484 - 1939	
L 919 mm - 18 LED - 22,2 W DC - 24,8 W AC				
C00655	**AM**	**A**	2250 - 1755	
		M	3024 - 2359	
		W	3240 - 2528	
		N	3456 - 2697	
L 1219 mm - 24 LED - 29,6 W DC - 33,2 W AC				
C00656	**AM**	**A**	3000 - 2339	
		M	4032 - 3145	
		W	4320 - 3371	
		N	4608 - 3597	
L 1519 mm - 30 LED - 37 W DC - 41,3 W AC				
C00657	**AM**	**A**	3750 - 2924	
		M	5040 - 3931	
		W	5400 - 4213	
		N	5760 - 4496	

Recessed casings, accessories & cables: (pag 588/589)

IK08 IP68 NEW **DALI**

	Fin	Cct	lm S - lm D	Opt
L 619 mm - 12 LED - 14,8 W DC - 16,5 W AC				
C00659	**AM**	**A**	1656 - 1261	**SP** (19°)
		M	2172 - 1695	**ML** (36°)
		W	2328 - 1817	**WF** (67°)
		N	2484 - 1939	**EF** (21°x 42°)
L 919 mm - 18 LED - 22,2 W DC - 24,8 W AC				**WW** (Asym. Ww)
C00660	**AM**	**A**	2250 - 1755	
		M	3024 - 2359	
		W	3240 - 2528	
		N	3456 - 2697	
L 1219 mm - 24 LED - 29,6 W DC - 33,2 W AC				
C00661	**AM**	**A**	3000 - 2339	
		M	4032 - 3145	
		W	4320 - 3371	
		N	4608 - 3597	
L 1519 mm - 30 LED - 37 W DC - 41,3 W AC				
C00662	**AM**	**A**	3750 - 2924	
		M	5040 - 3931	
		W	5400 - 4213	
		N	5760 - 4496	

Recessed casings, accessories & cables: (pag 588/589)

Finishes


Anodised Aluminium

Cct

A 2200 **W** 3000
M 2700 **N** 4000

Xenia_AF PRO RGBW DMX/RDM | V2 | powerLED | 220-240V AC





DW Dynamic White available on request


IK08 IP68 NEW DMX RDM +RGBW

	Fin	Cct		Opt
L 529 mm - 3x4 LED - 7,3 W DC - 8,5 W AC				
C00668	**AM**	**V**	RGBW (3000K)	**EF** (21°x 42°)
		Q	RGBW (4000K)	
L 1169 mm - 8x4 LED - 19,3 W DC - 22,6 W AC				
C00669	**AM**	**V**	RGBW (3000K)	**EF** (21°x 42°)
		Q	RGBW (4000K)	

Electronics: **AM13** (pag 589) | Recessed casings, accessories & cables: (pag 588/589)

Xenia_AF PRO Micro Louvre | V2 | powerLED | 220-240 V AC





DW Dynamic White available on request


IK08 IP68 NEW

	Fin	Cct	lm S - lm D	Opt
L 359 mm - 6 LED - 7,4 W DC - 8,3 W AC				
C00680	**AM**	**A**	828 - 350	**SP** (10°÷19°)
		M	1086 - 470	**ML** (30°÷39°)
		W	1164 - 504	**WF** (50°÷70°)
		N	1242 - 538	**EF** (20°÷29°)x(41°÷60°)
L 619 mm - 12 LED - 14,8 W DC - 16,5 W AC				**WW** (Asym. Ww)
C00681	**AM**	**A**	1656 - 699	
		M	2172 - 940	
		W	2328 - 1008	
		N	2484 - 1075	
L 919 mm - 18 LED - 22,2 W DC - 24,8 W AC				
C00682	**AM**	**A**	2250 - 973	
		M	3024 - 1308	
		W	3240 - 1402	
		N	3456 - 1496	
L 1219 mm - 24 LED - 29,6 W DC - 33,2 W AC				
C00683	**AM**	**A**	3000 - 1297	
		M	4032 - 1744	
		W	4320 - 1869	
		N	4608 - 1994	
L 1519 mm - 30 LED - 37 W DC - 41,3 W AC				
C00684	**AM**	**A**	3750 - 1622	
		M	5040 - 2180	
		W	5400 - 2336	
		N	5760 - 2493	

Recessed casings, accessories & cables: (pag 588/589)

Xenia_AF PRO Micro Louvre | V2 | DALI | powerLED | 220-240 V AC





DW Dynamic White available on request

IK08 IP68 NEW **DALI**

	Fin	Cct	lm S - lm D	Opt
L 619 mm - 12 LED - 14,8 W DC - 16,5 W AC				
C00686	**AM**	**A**	1656 - 699	**SP** (10°÷19°)
		M	2172 - 940	**ML** (30°÷39°)
		W	2328 - 1008	**WF** (50°÷70°)
		N	2484 - 1075	**EF** (20°÷29°)x(41°÷60°)
L 919 mm - 18 LED - 22,2 W DC - 24,8 W AC				**WW** (Asym. Ww)
C00687	**AM**	**A**	2250 - 973	
		M	3024 - 1308	
		W	3240 - 1402	
		N	3456 - 1496	
L 1219 mm - 24 LED - 29,6 W DC - 33,2 W AC				
C00688	**AM**	**A**	3000 - 1297	
		M	4032 - 1744	
		W	4320 - 1869	
		N	4608 - 1994	
L 1519 mm - 30 LED - 37 W DC - 41,3 W AC				
C00689	**AM**	**A**	3750 - 1622	
		M	5040 - 2180	
		W	5400 - 2336	
		N	5760 - 2493	

Recessed casings, accessories & cables: (pag 588/589)





VIA BROLETTO,
ESA ENGINEERING
Milan (Italy)

Project: Antonio Buonsante

Photography:
Antonio Buonsante

Recessed casings and accessories

Recessed casings



AL **99926** for 160 mm
AL **99912** for 359 mm
AL **99913** for 619 mm
AL **99914** for 919 mm
AL **99915** for 1219 mm
AL **99916** for 1519 mm
suitable for: Xenia_A / _AL / _A Pro
Xenia_AF / _ALF / _AF Pro


AL **99918** for 529 mm
AL **99919** for 1169 mm
suitable for: Xenia_A / _AL / _A Pro RGBW
Xenia_AF / _ALF / _AF Pro RGBW



IS **98949** 2x Fixing brackets 46-67 mm
suitable for: Xenia_W/_W Pro
Xenia_AF / _ALF / _AF Pro
Xenia_AF / _ALF / _AF Pro RGBW



IS **89045** 2x Fixing brackets 90 mm
IS **89046** 2x Fixing brackets 150 mm
IS **89047** 2x Fixing brackets 300 mm
suitable for: Xenia_W/_W Pro




IS **C-F400008** 2x Brackets for surface mounting

suitable for: Xenia_W/_W Pro, Xenia_W RGBW




Xenia_W + Anti-glare
+ Bracket C-F400008



AL **99917** 2x End caps for recessed casing
suitable for: Xenia_AF / _ALF / _AF Pro
Xenia_AF / _ALF / _AF Pro RGBW



AL **83188** 2x End caps
suitable for: Xenia_A / _AL / _A Pro
Xenia_A / _AL / _A Pro RGBW




IS **C-F400006** 2x Fixing brackets

suitable for: Xenia_W/_W Pro, Xenia_AF/_ALF/_AF Pro
Xenia_AF/_ALF/_AF Pro RGBW



IS **99818** Fixing springs for false ceiling


suitable for: Xenia_A / _AL / _A Pro
Xenia_A / _AL / _A Pro RGBW




AL **98782** Anti-glaring - 366 mm
AL **98783** Anti-glaring - 630 mm
AL **98784** Anti-glaring - 930 mm
AL **98785** Anti-glaring - 1230 mm
AL **99778** Anti-glaring - 1530 mm
suitable for: Xenia_W / Xenia_W Pro



AL **98951** Anti-glaring 500 mm
suitable for: Xenia_W PRO RGBW



AL **98953** Anti-glaring 535 mm
suitable for: Xenia_W RGBW



AL **98952** Anti-glaring 1182 mm
suitable for: Xenia_W RGBW
Xenia_W Pro RGBW

Cables

24 V DC / 220-240 V AC | Power cables



BB **99216** Conn. F.4 pin M12 (L 1,5 m)
BB **89190** Conn. F.4 pin M12 (L 5 m)
suitable for: Xenia

24 V DC / 220-240 V AC | Extension cables



BB **98437** Conn M. + F. 4 pin M12 (L 1 m)
BB **98149** Conn M. + F. 4 pin M12 (L 5 m)
BB **89188** Conn M. + F. 4 pin M12 (L 10 m)
suitable for: Xenia

220-240 V AC + DALI | Power cables



BB **C-W200020** Conn. F.4 pin M12 (L 1,5 m)
BB **C-W200021** Conn. F.4 pin M12 (L 5 m)
suitable for: Xenia DALI

220-240 V AC + DMX | Splitter



BB **C-W200018** Start splitter
BB **C-W200019** Continuity splitter
suitable for: Xenia RGBW DMX/RDM

Pag. 972

220-240 V AC + DMX | Power cables



BB **C-W200013** Conn. F.5 pin M12 (L 1,5 m)
BB **C-W200014** Conn. F.5 pin M12 (L 5 m)
suitable for: Xenia RGBW DMX/RDM

220-240 V AC + DMX | Extension cables



BB **C-W200015** Conn M. + F. 5 pin M12 (L 0,5 m)
BB **C-W200016** Conn M. + F. 5 pin M12 (L 1,5 m)
BB **C-W200017** Conn M. + F. 5 pin M12 (L 5 m)
suitable for: Xenia RGBW DMX/RDM

220-240 V AC + DALI | Extension cables



BB **C-W200022** Conn. M+F 4 pin M12 (L 0,5 m)
BB **C-W200023** Conn. M+F 4 pin M12 (L 1,5 m)
BB **83200** Conn. M+F 4 pin M12 (L 5 m)
suitable for: Xenia DALI



BB **C-W400005** DMX line closure adapter

suitable for: Xenia

Pag. 972

Electronics

AL

99374	99331	99332	83333	C-E400002
ON/OFF	ON/OFF	0/1-10V	DALI/PUSH	DALI/PUSH
75W	150W	150W	150W	240W
210 x 49 x h 25	158 x 60 x h 35	158 x 60 x h 35	188 x 68 x h 34	188 x 68 x h 34
56	70	70	77	77

BI

C-E200008	99186	C-E200002
ON/OFF	ON/OFF	DALI/PUSH
1 - 2 art.	2 - 4 art.	2 - 4 art.
135 x 26 x h 26	117 x 92 x h 38	125 x 45 x h 30
35		55

BL

99186	C-E200002
ON/OFF	DALI/PUSH
1 art.	1 art.
117 x 92 x h 38	125 x 45 x h 30
	55

BW

C-E200007	99185	C-E200003
ON/OFF	ON/OFF	DALI/PUSH
1 - 2 art.	2 - 4 art.	2 - 4 art.
135 x 26 x h 26	117 x 92 x h 38	125 x 45 x h 30
35		55

AM13

DMX	C-E700026	C-W400005	C-W200018/C-W200019
Controllers	DMX/RDM addresser	120 Ohm DMX line closure	Splitter ALLinONE Start & Continuity
Pag. 963			Pag. 972

BQ

C-E200008	99186	C-E200002
ON/OFF	ON/OFF	DALI/PUSH
1 art.	1 - 2 art.	1 - 2 art.
135 x 26 x h 26	117 x 92 x h 38	125 x 45 x h 30
35		55

BR

99186	C-E200002
ON/OFF	DALI/PUSH
1 art.	1 art.
117 x 92 x h 38	125 x 45 x h 30
	55


Finishes

BB Black

ARCHILINE

Recessed model materials
Anodised 6060 aluminium alloy or AISI 316L stainless steel flange.
Extra-clear tempered glass or white ceramic varnished
tempered glass diffuser.

Wall/ceiling model materials
Anodised 6060 aluminium alloy or AISI 316L stainless steel body.
Extra-clear tempered glass diffuser.





Archiline_F/_FJ
Frameless

W	12,2-13,2-18,3-19,8-36,5-39,6
mm	**321-511-1001**
Cct	2700-3000-4000
Opt	**Spot-Flood-M.Flood**
	W.Flood-Elliptic
	Asymmetric Wallwasher
Elec.	On/Off-DALI
Col.	**AK**



Archiline_F
Frameless Anti-glaring

	11,2-12,1-18,3-19,8-36,5-39,6
	321-511-1001
	2700-3000-4000
	Spot-Flood
	W.Flood-Elliptic
	On/Off-DALI
	AK



Archiline_F
Frameless RGBW DMX

	13,2-22-44
	321-511-1001
	RGBW
	Spot-Flood
	W.Flood-Elliptic
	Asymmetric Wallwasher
	DMX
	AK



Archiline_FL
Frameless Opaline

	3,6-6-8,4-12-13,6-24
	321-511-1001
	3000-4000-RGBW
	Diffused
	On/Off-DMX
	AK



Archiline_A
Frame Aluminium

	12,2-13,2-18,3-19,8-36,5-39,6-55-59
	371-561-1051-1541
	2700-3000-4000
	Spot-Flood-M.Flood
	W.Flood-Elliptic
	Asymmetric Wallwasher
	On/Off-DALI
	AM



Archiline_A
Frame Aluminium Anti-Glaring

W	11,2-12,1-18,3-19,8-36,5-39,6
mm	**371-561-1051**
Cct	2700-3000-4000
Opt	**Spot-Flood**
	W.Flood-Elliptic
Elec.	On/Off-DALI
Col.	**AM**



Archiline_A
Frame Aluminium RGBW DMX

	13,2-22-44
	371-561-1051
	RGBW
	Spot-Flood
	W.Flood-Elliptic
	Asymmetric Wallwasher
	DMX
	AM



Archiline_I/_IJ
Frame Inox

	12,2-13,2-18,3-19,8-36,5-39,6
	375-565-1055
	2700-3000-4000
	Spot-Flood-M.Flood
	W.Flood-Elliptic
	Asymmetric Wallwasher
	On/Off-DALI
	IS



Archiline_I
Frame Inox Anti-Glaring

	11,2-12,1-18,3-19,8-36,5-39,6
	375-565-1055
	2700-3000-4000
	Spot-Flood
	W.Flood-Elliptic
	On/Off-DALI
	IS



Archiline_I
Frame Inox RGBW DMX

	13,2-22-44
	375-565-1055
	RGBW
	Spot-Flood
	W.Flood-Elliptic
	Asymmetric Wallwasher
	DMX
	IS

State-of-the-art engineering: Archiline_W Pro
The Pro version is the star of the Archiline range, made entirely from dedicated components, including the powerLED diode sources and extremely high-performance integrated drivers. Archiline_W Pro has an efficiency of 140 lm/W, developing a luminous flux of over 11,000 lumens per metre! It is therefore strongly recommended for very high walls, thanks partly to its optics covered with 5-mm extra-clear glass, black screenprinted edges and high-efficiency elliptical, narrow or flood beam. The 06-optic version will project a beam to a height of 50 metres! Available in an ON/OFF or RGBW version with DMX dimmer protocol. In this model, the main tension and DMX signal both pass through the connector.




Archiline_W has an adjustable graduated stainless steel bracket that fixes to a wall or ceiling, and the distance from the wall is also adjustable.



Safety systems
We have developed a variety of corrosion protection technology to maximise the lifespan of our lights.

They also have overtension and electrical discharge protection, TCS® to shield their circuits from moisture, and AquaStop® water protection.



Optics
The Archiline range has optics for every type of design need.
- SPOT and NARROW SPOT for accent lighting
- FLOOD and MEDIUM FLOOD for soft lighting of parts of walls
- ELLIPTIC 20°x50°, which projects an oval beam, ideal for grazing illumination of high and narrow walls
- ASYMMETRIC for a wallwasher effect.


Other features:
- Darklight versions, which section the beam by eliminating the direct component to the exterior and lighting only the wall
- Ability to create continuous lines without affecting the evenness of the light near the ends of each module. In the Archiline_F no-darklight versions, the diodes are arranged so as to maintain the same distance between each one, and between the last ones at each end.

ARCHILINE standard



ARCHILINE darklight





Performance for every need
Each family of lights includes different outputs to meet the largest possible range of requirements. Paseo, Xenia, Archiline and Archiline_W Pro offer a particularly wide selection. It's worth remembering that all Linear Systems can be dimmed using 1-10V, DALI, DMX and RDM protocols, using bidirectional communication to achieve total control of DMX parameters.




SOFITEL BARCELONA SKIPPER
Barcelona (Spain)

Lighting Designer:
Fantastico Lighting Partners

Photography:
Jordi Anguera

Archiline_F | powerLED | 220-240 V AC






5000 kg IK10 IP68

	Cct	lm S - lm D	Opt
L 321 mm - 6 LED			
13,2 W DC - 14,5 W AC			
AK **92127**	**M**	1692 - 916	**08** (18°x13°)
DALI - 12,2 W DC - 13,5 W AC	**W**	1812 - 974	**15** (23°x18°)
AK **81591**	**N**	1932 - 1037	**30** (30°)
			60 (54°)
L 511 mm - 9 LED			**25** (44°x 29°)
19,8 W DC - 22 W AC			**27** (Asym. Ww)
AK **92128**	**M**	2538 - 1481	
DALI - 18,3 W DC - 20,5 W AC	**W**	2718 - 1557	
AK **81592**	**N**	2898 - 1658	
L 1001 mm - 18 LED			
39,6 W DC - 44 W AC			
AK **92129**	**M**	5076 - 2884	
DALI - 36,5 W DC - 41 W AC	**W**	5436 - 3067	
AK **81593**	**N**	5796 - 3265	

Recessed casing: (pag 600) - Cables: (pag 607)

Archiline_F Anti-glare | powerLED | 220-240 V AC






5000 kg IK10 IP68

	Cct	lm S - lm D	Opt
L 321 mm - 11 LED			
12,1 W DC - 13,5 W AC			
AK **92049**	**M**	1716 - 645	**15** (10°÷ 19°)
DALI - 11,2 W DC - 14 W AC	**W**	1837 - 687	**30** (20°÷ 29°)
AK **81594**	**N**	1958 - 730	**60** (50°÷ 70°)
			25 (40°÷ 49°)x(20°÷40°)
L 511 mm - 18 LED			
19,8 W DC - 22 W AC			
AK **92050**	**M**	2808 - 1118	
DALI - 18,3 W DC - 20,5 W AC	**W**	3006 - 1191	
AK **81595**	**N**	3204 - 1264	
L 1001 mm - 36 LED			
39,6 W DC - 43,5 W AC			
AK **92051**	**M**	5616 - 2326	
DALI - 36,5 W DC - 41 W AC	**W**	6012 - 2476	
AK **81596**	**N**	6408 - 2628	

Recessed casing: (pag 600) - Cables: (pag 607)

Archiline_FJ | powerLED | 220-240 V AC





5000 kg IK10 IP68

	Cct	lm S - lm D	Opt
L 321 mm - 6 LED			
13,2 W DC - 14,5 W AC			
AK **82302**	**M**	1692 - 916	**08** (18°x 13°)
DALI - 12,2 W DC - 13,5 W AC	**W**	1812 - 974	**15** (23°x 18°)
AK **82303**	**N**	1932 - 1037	**30** (30°)
			60 (54°)
L 511 mm - 9 LED			**25** (44°x 29°)
19,8 W DC - 22 W AC			**27** (Asym. Ww)
AK **82304**	**M**	2538 - 1482	
DALI - 18,3 W DC - 20,5 W AC	**W**	2718 - 1557	
AK **82305**	**N**	2898 - 1658	
L 1001 mm - 18 LED			
39,6 W DC - 44 W AC			
AK **82306**	**M**	5076 - 2884	
DALI - 36,5 W DC - 41 W AC	**W**	5436 - 3067	
AK **82307**	**N**	5796 - 3265	

Finishes


AK Anodised Black Aluminium

Cct

M 2700 **N** 4000
W 3000

Archiline_F RGBW DMX | powerLED | 220-240 V AC





5000 kg IK10 IP68 DMX RDM RGBW


	Cct	Opt
L 321 mm - 5x4 LED 13,2 W DC - 14,5 W AC		
AK **92083**	**V** RGBW (3000K) **Q** RGBW (4000K)	**15** (10°÷ 19°) **30** (20°÷ 29°) **60** (50°÷ 70°) **25** (40°÷ 49°)x(20°÷40°) **27** (Asym. Ww)
L 511 mm - 5x4 LED 22 W DC - 24,5 W AC		
AK **92084**	**V** RGBW (3000K) **Q** RGBW (4000K)	
L 1001 mm - 10x4 LED 44 W DC - 49 W AC		
AK **92093**	**V** RGBW (3000K) **Q** RGBW (4000K)	

DW Dynamic White available on request

Electronics: **AM4** (pag 607) | Recessed casing: (pag 600) - Cables: (pag 607)

Archiline_FL | topLED | 220-240 V AC






5000 kg IK10 IP68

	Cct	lm S - lm D	Opt
L 321 mm 3,6 W DC - 5 W AC			
AK **92138**	**W** **N**	483 - 95 504 - 103	**00** (Diffused)
L 511 mm 6 W DC - 8,6 W AC			
AK **92139**	**W** **N**	828 - 145 864 - 158	
L 1001 mm 12 W DC - 14,3 W AC			
AK **92142**	**W** **N**	1656 - 290 1728 - 315	

Recessed casing: (pag 600) - Cables: (pag 607)

Archiline_FL RGBW DMX | topLED | 220-240 V AC






5000 kg IK10 IP68 DMX RDM RGBW

	Cct	Opt
L 321 mm 8,4 W DC - 10 W AC		
AK **92143**	**V** RGBW (3000K) **Q** RGBW (4000K)	**00** (Diffused)
L 511 mm 13,6 W DC - 16 W AC		
AK **92144**	**V** RGBW (3000K) **Q** RGBW (4000K)	
L 1001 mm 24 W DC - 25 W AC		
AK **92145**	**V** RGBW (3000K) **Q** RGBW (4000K)	

Electronics: **AM4** (pag 607) | Recessed casing: (pag 600) - Cables: (pag 607)

Archiline_A | powerLED | 220-240 V AC






	Cct	lm S - lm D	Opt
L 371 mm - 6 LED			
13,2 W DC - 14,5 W AC			
AM **92132**	**M**	1692 - 916	**08** (18°x 13°)
DALI - 12,2 W DC - 13,5 W AC	**W**	1812 - 974	**15** (23°x 18°)
AM **81603**	**N**	1932 - 1037	**30** (30°)
			60 (54°)
L 561 mm - 9 LED			**25** (44°x 29°)
19,8 W DC - 22 W AC			**27** (Asym. Ww)
AM **92134**	**M**	2538 - 1481	
DALI - 18,3 W DC - 20,5 W AC	**W**	2718 - 1557	
AM **81604**	**N**	2898 - 1658	
L 1051 mm - 18 LED			
39,6 W DC - 44 W AC			
AM **92136**	**M**	5076 - 2884	
DALI - 36,5 W DC - 41 W AC	**W**	5436 - 3067	
AM **81605**	**N**	5796 - 3265	
L 1541 mm - 27 LED			
59 W DC - 65 W AC			
AM **81590**	**M**	7182 - 4095	
DALI - 55 W DC - 61,4 W AC	**W**	7668 - 4355	
AM **81606**	**N**	8181 - 4660	

Recessed casing: (pag 600) - Cables: (pag 607)

Archiline_A Anti-glare | powerLED | 220-240 V AC





	Cct	lm S - lm D	Opt
L 371 mm - 11 LED			
12,1 W DC - 13,5 W AC			
AM **92052**	**M**	1716 - 645	**15** (10°÷ 19°)
DALI - 11,2 W DC - 12,5 W AC	**W**	1837 - 687	**30** (20°÷ 29°)
AM **81607**	**N**	1958 - 730	**60** (50°÷ 70°)
			25 (40°÷ 49°)x(20°÷40°)
L 561 mm - 18 LED			
19,8 W DC - 22 W AC			
AM **92054**	**M**	2808 - 1118	
DALI - 18,3 W DC - 20,5 W AC	**W**	3006 - 1191	
AM **81608**	**N**	3204 - 1264	
L 1051 mm - 36 LED			
39,6 W DC - 43,5 W AC			
AM **92056**	**M**	5616 - 2326	
DALI - 36,5 W DC - 41 W AC	**W**	6012 - 2476	
AM **81609**	**N**	6408 - 2628	

Recessed casing: (pag 600) - Cables: (pag 607)

Finishes


AM Anodised Aluminium

Cct

M 2700 **N** 4000
W 3000

Archiline_A RGBW DMX | powerLED | 220-240 V AC






	Cct		Opt	
L 371 mm - 3x4 LED				
13,2 W DC - 14,5 W AC				
AM **92100**	**V**	RGBW (3000K)	**15**	(10°÷ 19°)
	Q	RGBW (4000K)	**30**	(20°÷ 29°)
L 561 mm - 5x4 LED			**60**	(50°÷ 70°)
22 W DC - 24,5 W AC			**25**	(40°÷ 49°)x(20°÷40°)
AM **92104**	**V**	RGBW (3000K)	**27**	(Asym. Ww)
	Q	RGBW (4000K)		
L 1051 mm - 10x4 LED				
44 W DC - 49 W AC				
AM **92108**	**V**	RGBW (3000K)		
	Q	RGBW (4000K)		

DW Dynamic White available on request

Electronics: **AM4** (pag 607) | Recessed casing: (pag 600) - Cables: (pag 607)

Archiline_I | powerLED | 220-240 V AC






	Cct	lm S - lm D	Opt	
L 375 mm - 6 LED				
13,2 W DC - 14,5 W AC				
IS **92124**	**M**	1692 - 916	**08**	(18°x 13°)
DALI - 12,2 W DC - 13,5 W AC	**W**	1812 - 974	**15**	(23°x 18°)
IS **81597**	**N**	1932 - 1037	**30**	(30°)
			60	(54°)
L 565 mm - 9 LED			**25**	(44°x 29°)
19,8 W DC - 22 W AC			**27**	(Asym. Ww)
IS **92125**	**M**	2538 - 1481		
DALI - 18,3 W DC - 20,5 W AC	**W**	2718 - 1557		
IS **81598**	**N**	2898 - 1658		
L 1055 mm - 18 LED				
39,6 W DC - 44 W AC				
IS **92126**	**M**	5076 - 2884		
DALI - 36,5 W DC - 41 W AC	**W**	5436 - 3067		
IS **81599**	**N**	5796 - 3265		

Recessed casing: (pag 600) - Cables: (pag 607)

Archiline_I Anti-glare | powerLED | 220-240 V AC






	Cct	lm S - lm D	Opt	
L 375 mm - 11 LED				
12,1 W DC - 13,5 W AC				
IS **92046**	**M**	1716 - 645	**15**	(10°÷ 19°)
DALI - 11,2 W DC - 12,5 W AC	**W**	1837 - 687	**30**	(20°÷ 29°)
IS **81600**	**N**	1958 - 730	**60**	(50°÷ 70°)
			25	(40°÷ 49°)x(20°÷40°)
L 565 mm - 18 LED				
19,8 W DC - 22 W AC				
IS **92047**	**M**	2808 - 1118		
DALI - 18,3 W DC - 20,5 W AC	**W**	3006 - 1191		
IS **81601**	**N**	3204 - 1264		
L 1055 mm - 36 LED				
39,6 W DC - 43,5 W AC				
IS **92048**	**M**	5616 - 2326		
DALI - 36,5 W DC - 41 W AC	**W**	6012 - 2476		
IS **81602**	**N**	6408 - 2628		

Recessed casing: (pag 600) - Cables: (pag 607)



Archiline_IJ | powerLED | 220-240 V AC






	Cct	lm S - lm D	Opt	
L 375 mm - 6 LED				
13,2 W DC - 14,5 W AC				
IS **82308**	**M**	1692 - 916	**08**	(18°x 13°)
DALI - 12,2 W DC - 13,5 W AC	**W**	1812 - 974	**15**	(23°x 18°)
IS **82309**	**N**	1932 - 1037	**30**	(30°)
			60	(54°)
L 565 mm - 9 LED			**25**	(44°x 29°)
19,8 W DC - 22 W AC			**27**	(Asym. Ww)
IS **82310**	**M**	2538 - 1482		
DALI - 18,3 W DC - 20,5 W AC	**W**	2718 - 1557		
IS **82311**	**N**	2898 - 1658		
L 1055 mm - 18 LED				
39,6 W DC - 44 W AC				
IS **82312**	**M**	5076 - 2884		
DALI - 36,5 W DC - 41 W AC	**W**	5436 - 3067		
IS **82313**	**N**	5796 - 3265		

Recessed casing (pag 600) - Cables (pag 607)

Archiline_I RGBW DMX | powerLED | 220-240 V AC






	Cct		Opt	
L 375 mm - 3x4 LED				
13,2 W DC - 14,5 W AC				
IS **92080**	**V**	RGBW (3000K)	**15**	(10°÷ 19°)
	Q	RGBW (4000K)	**30**	(20°÷ 29°)
L 565 mm - 5x4 LED			**60**	(50°÷ 70°)
22 W DC - 24,5 W AC			**25**	(40°÷ 49°)x(20°÷40°)
IS **92081**	**V**	RGBW (3000K)	**27**	(Asym. Ww)
	Q	RGBW (4000K)		
L 1051 mm - 10x4 LED				
44 W DC - 49 W AC				
IS **92082**	**V**	RGBW (3000K)		
	Q	RGBW (4000K)		

DW Dynamic White available on request

Electronics: **AM4** (pag 607) | Recessed casing (pag 600) - Cables (pag 607)

High-quality construction
Archiline bodies are made from extruded 6060 aluminium alloy anodised to 10 microns. These two processes provide superior passive heat dissipation and, most importantly, higher corrosion resistance. The caps are diecast.

New tilting version
The Archiline family expands with the tilting version which rounds out a vast range of solutions and versions. Archiline_IJ and Archiline_FJ use a tilting system that allows adjustment of the optics assembly using a specific ring with 5°/10°/15° steps.




Finishes
IS Steel

Cct
M 2700 **N** 4000 **Q** RGBW (4000)
W 3000 **V** RGBW (3000)

Recessed casings





AK **98724** 322 mm
AK **98725** 513 mm
AK **98726** 1003 mm
suitable for: Archiline_F / _FJ / _FL

Outer casing for floor-mounted recessed installation.


These outer casings allow to create a continuous row of light




Anodisation
Anodisation is carried out in electrochemically controlled conditions, and creates a layer of oxide on the surface of the aluminium. This has excellent levels of adherence, compactness, hardness, and corrosion resistance.

Drive-over capability
The housings of the Archiline_F, FJ and FL versions have tempered glass 12-mm, and will support a weight of up to five tonnes.

Frameless installation


















98671 **ZN** 356 mm
98672 **ZN** 546 mm
98673 **ZN** 1036 mm
99760 **ZN** 1526 mm (only Archiline_A)
suitable for: Archiline_A / _I / _IJ


Outer casing for floor-mounted recessed installation.


Galvanisation
The housings of the Archiline_A, I, IJ and versions are galvanised for improved corrosion resistance and durability.

Installation with Frame












Accessories



ZN **83049** Wall fixing brackets

suitable for: Archiline_F / _FJ / _FL



ZN **98957** Luminaire removing accessory

suitable for: Archiline_F / _FJ / _FL

Finishes
AK Anodised Black Aluminium
ZN Galvanised Steeel

SOFITEL BARCELONA SKIPPER
Barcelona (Spain)

Lighting Designer:
Fantastico Lighting Partners

Photography:
Jordi Anguera







MAUSOLEUM KHOJA AHMED YASAWI
Turkestan (Kazakhstan)


Project: Media Agency Plastdekor LLP


Lighting Designer:
Media agency Plastdekor LLP


Electrical project, project adaptation, supply:
LLP "SOCIETÀ DI INGEGNERIA "KAZGIPRONEFTETRANS",
Media Agency Plastdekor LLP

Archiline_W | powerLED | 220-240 V AC











	Cct	lm S - lm D	Opt
L1 - 320 mm - 6 LED			
13,2 W DC - 14,5 W AC			
AM **92112**	**M**	1692 - 916	**06** (14°)
DALI - 12,2 W DC - 13,5 W AC	**W**	1812 - 974	**15** (23°x 18°)
AM **81610**	**N**	1932 - 1037	**30** (30°)
			60 (54°)
L2 - 620 mm - 11 LED			**25** (44°x 29°)
24,3 W DC - 27 W AC			**27** (Asym. Ww)
AM **92114**	**M**	3102 - 2196	
DALI - 22,3 W DC - 25 W AC	**W**	3322 - 2336	
AM **81611**	**N**	3542 - 2487	
L2 - 920 mm - 17 LED			
37,5 W DC - 41 W AC			
AM **92118**	**M**	4794 - 3094	
DALI - 34,5 W DC - 38,7 W AC	**W**	5134 - 3290	
AM **81612**	**N**	5474 - 3502	
L3 - 1220 mm - 22 LED			
48,5 W DC - 53,5 W AC			
AM **92120**	**M**	6204 - 4004	
DALI - 44,7 W DC - 50 W AC	**W**	6644 - 4258	
AM **81613**	**N**	7084 - 4532	
L3 - 1520 mm - 28 LED			
59 W DC - 65 W AC			
AM **81513**	**M**	7448 - 4803	
DALI - 55 W DC - 61,5 W AC	**W**	7952 - 5468	
AM **81614**	**N**	8484 - 5109	


Accessories & cables: (pag 607)

Archiline_W Anti-glare | powerLED | 220-240 V AC












	Cct	lm S - lm D	Opt
L1 - 320 mm - 11 LED			
12,1 W DC - 13,5 W AC			
AM **92038**	**M**	1716 - 645	**15** (10°÷ 19°)
DALI - 11,2 W DC - 12,5 W AC	**W**	1837 - 687	**30** (20°÷ 29°)
AM **81615**	**N**	1958 - 730	**60** (50°÷ 70°)
			25 (40°÷ 49°)x(20°÷40°)
L2 - 620 mm - 22 LED			
24,3 W DC - 26 W AC			
AM **92040**	**M**	3432 - 1616	
DALI - 22,4 W DC - 25 W AC	**W**	3674 - 1721	
AM **81616**	**N**	3916 - 1826	
L2 - 920 mm - 33 LED			
36,4 W DC - 40 W AC			
AM **92042**	**M**	5148 - 2134	
DALI - 33,6 W DC - 37,5 W AC	**W**	5511 - 2270	
AM **81617**	**N**	5874 - 2409	
L3 - 1220 mm - 44 LED			
48,5 W DC - 53,5 W AC			
AM **92044**	**M**	6864 - 2845	
DALI - 44,8 W DC - 50 W AC	**W**	7348 - 3026	
AM **81618**	**N**	7832 - 3212	


Accessories & cables: (pag 607)

Archiline_W RGBW DMX | powerLED | 220-240 V AC










	Cct		Opt	
L1 - 320 mm - 3x4 LED				
13,2 W DC - 14,5 W AC				
AM **92070**	**V**	RGBW (3000K)	**15**	(10°÷ 19°)
	Q	RGBW (4000K)	**30**	(20°÷ 29°)
L2 - 620 mm - 4x6 LED			**60**	(50°÷ 70°)
26,4 W DC - 29 W AC			**25**	(40°÷ 49°)x(20°÷40°)
AM **92072**	**V**	RGBW (3000K)	**27**	(Asym. Ww)
	Q	RGBW (4000K)		
L2 - 920 mm - 4x9 LED				
39,6 W DC - 43,5 W AC				
AM **92074**	**V**	RGBW (3000K)		
	Q	RGBW (4000K)		
L3 - 1220 mm - 4x12 LED				
52,8 W DC - 58 W AC				
AM **92078**	**V**	RGBW (3000K)		
	Q	RGBW (4000K)		


DW Dynamic White available on request


Electronics: **AM4** (pag 607) | Accessories & cables: (pag 607)

Archiline_W Pro | powerLED | 220-240 V AC











	Cct	lm S - lm D	Opt	
L1 - 356 mm - 6 LED				
32 W DC - 35 W AC				
AM **90458**	**M**	3629 - 2256	**15**	(10°÷ 19°)
	W	3629 - 2338	**30**	(20°÷ 29°)
	N	3917 - 2435	**25**	(40°÷ 49°)x(20°÷40°)
32 W DC - 35 W AC				
AM **81447**	**M**	3629 - 2441	**06**	(7°÷ 9°)
	W	3629 - 2441		
	N	3917 - 2635		
L2 - 515 mm - 9 LED				
46 W DC - 51 W AC				
AM **90460**	**M**	5234 - 3260	**15**	(10°÷ 19°)
	W	5243 - 3638	**30**	(20°÷ 29°)
	N	5660 - 3518	**25**	(40°÷ 49°)x(20°÷40°)
46 W DC - 51 W AC				
AM **81448**	**M**	5234 - 3527	**06**	(7°÷ 9°)
	W	5243 - 3527		
	N	5660 - 3807		
L3 - 1016 mm - 18 LED				
80,5 W DC - 89 W AC				
AM **90461**	**M**	10486 - 6519	**15**	(10°÷ 19°)
	W	10486 - 7175	**30**	(20°÷ 29°)
	N	11320 - 7039	**25**	(40°÷ 49°)x(20°÷40°)
80,5 W DC - 89 W AC				
AM **81449**	**M**	10486 - 7053	**06**	(7°÷ 9°)
	W	10486 - 7053		
	N	11320 - 7615		


Cables: (pag 607)

Archiline_W Pro RGBW DMX | powerLED | 220-240 V AC









	Cct	Opt
L1 - 356 mm - 3x2 LED		
24,6 W DC - 30 W AC		
AM **90459**	**V** RGBW (3000K) **Q** RGBW (4000K)	**15** (10°÷ 19°) **30** (20°÷ 29°) **45** (40°÷ 49°) **25** (40°÷ 49°)x(20°÷40°)
24,6 W DC - 30 W AC		
AM **81450**	**V** RGBW (3000K) **Q** RGBW (4000K)	**06** (7°÷ 9°)
L2 - 515 mm - 3x3 LED		
37 W DC - 44 W AC		
AM **90462**	**V** RGBW (3000K) **Q** RGBW (4000K)	**15** (10°÷ 19°) **30** (20°÷ 29°) **45** (40°÷ 49°) **25** (40°÷ 49°)x(20°÷40°)
37 W DC - 44 W AC		
AM **81451**	**V** RGBW (3000K) **Q** RGBW (4000K)	**06** (7°÷ 9°)
L3 - 1016 mm - 3x6 LED		
74 W DC - 86 W AC		
AM **90463**	**V** RGBW (3000K) **Q** RGBW (4000K)	**15** (10°÷ 19°) **30** (20°÷ 29°) **45** (40°÷ 49°) **25** (40°÷ 49°)x(20°÷40°)
74 W DC - 86 W AC		
AM **81452**	**V** RGBW (3000K) **Q** RGBW (4000K)	**06** (7°÷ 9°)

DW Dynamic White available on request

Electronics: **AM4** (pag 607) | Accessories & cables: (pag 607)

Colour range

LEDs give you access to a wide range of colour temperatures, from warm white (2700 K) to daylight tones (4000 K), for total design versatility. As well as white light, the RGB range offers static or dynamic coloured effects, and the introduction of RGBW, in which white is separate from red, green and blue in the diode, lets you obtain the right mix for your project alongside a very pure white.

Perfect mixing



Finishes	Cct
AM Anodised Aluminium	**V** RGBW (3000) **Q** RGBW (4000)

Electronics

AM4

DMX	C-E700026	98986	98985/99390
Controllers Pag. 963	DMX/RDM addresser	120 Ohm DMX line closure	Splitter ALLinONE Start & Continuity Pag. 972

Cables

On/Off 220-240 V AC | Cables



BB **99057** Conn. F.3 pin (L 2m)

suitable for: Archiline

On/Off 220-240 V AC | Extension cables



BB **98147** Conn. M. / F. 3 pin (L 5m)
BB **98146** Conn. M. / F. 3 pin (L 10m)

suitable for: Archiline

DALI 220-240 V AC | Cables



BB **99826** Conn. F. 5 pin (L 1m)
BB **99822** Conn. F. 5 pin (L 5m)

suitable for: Archiline

DALI 220-240 V AC | Extension cables



BB **99823** Conn. M. / F. 5 pin (L 1m)
BB **99824** Conn. M. / F. 5 pin (L 5m)
BB **99825** Conn. M. / F. 5 pin (L 10m)

suitable for: Archiline

AllinOne DMX 220-240 V AC | Cables



BB **98660** F. 6 pin (L 1m)
BB **98661** F. 6 pin (L 5m)

suitable for: Archiline

AllinOne DMX 220-240 V AC | Extension cables



BB **98662** M. / F. 6 pin (L 1m)
BB **98663** M. / F. 6 pin (L 5m)

suitable for: Archiline



PVC **99390** ALLinONE splitter power/DMX_Continuity splitter
PVC **98985** ALLinONE splitter power/DMX_Start splitter


Pag. 972



BB **98986** ALLinONE splitter power/DMX_DMX line closure adapter

Pag. 972


Accessories



ZN **83049** Wall fixing brackets

suitable for: Archiline_W (not for _W Pro)


Anti-glare flaps



AK **98675**

suitable for:
Archiline_W 620 mm


Anti-glare flaps



AK **98676**

suitable for:
Archiline_W 920 mm


Anti-glare flaps



AK **98677**

suitable for:
Archiline_W 1220 mm

Anti-glare flaps



AK **99748**

suitable for:
Archiline_W 1520 mm

Finishes

AK Anodised Black Aluminium
BB Black


MINI TUBE


Polycarbonate with UV protection. Neoprene cables.



Minimum dimensions
LED tube with minimum dimensions, with a profile just 18 mm in diameter. The reduced dimensions allow easy and functional installations. Applied on the edges, corners or niches of shelving, Mini Tube is perfectly integrated into the setting.


IP65 IK08





Mini Tube | topLED | 220-240 V AC







IK08 IP65 1 m

	Cct	lm S - lm D	Opt
L 331 - 4,5 W DC - 5,2 W AC			
OP **92392**	**W**	586 - 465	**00** (Diffused)
	N	612 - 486	
L 621 - 7,5 W DC - 8,5 W AC			
OP **92393**	**W**	1172 - 929	**00** (Diffused)
	N	1224 - 971	
L 911 - 9 W DC - 10,5 W AC			
OP **92421**	**W**	1354 - 1069	**00** (Diffused)
	N	1414 - 1116	
L 1201 - 12 W DC - 13,5 W AC			
OP **92422**	**W**	2039 - 1626	**00** (Diffused)
	N	2129 - 1698	
L 1491 - 14 W DC - 15,5 W AC			
OP **92423**	**W**	2461 - 1951	**00** (Diffused)
	N	2570 - 2038	
L 1781 - 16,5 W DC - 18 W AC			
OP **92424**	**W**	2883 - 2285	**00** (Diffused)
	N	3012 - 2387	

Accessories (pag 611)

Mini Tube IN&OUT | topLED | 220-240 V AC





IK08 IP65 1 m

	Cct	lm S - lm D	Opt
L 331 - 4,5 W DC - 5,2 W AC			
OP **92384**	**W**	586 - 465	**00** (Diffused)
	N	612 - 486	
L 621 - 7,5 W DC - 8,5 W AC - CRI 80			
OP **92385**	**W**	1172 - 929	**00** (Diffused)
	N	1224 - 971	
L 911 - 9 W DC - 10,5 W AC			
OP **92386**	**W**	1354 - 1069	**00** (Diffused)
	N	1414 - 1116	
L 1201 - 12 W DC - 13,5 W AC			
OP **92387**	**W**	2039 - 1626	**00** (Diffused)
	N	2129 - 1698	
L 1491 - 14 W DC - 15,5 W AC			
OP **92390**	**W**	2461 - 1951	**00** (Diffused)
	N	2570 - 2038	
L 1781 - 16,5 W DC - 18 W AC			
OP **92391**	**W**	2883 - 2285	**00** (Diffused)
	N	3012 - 2387	

Accessories (pag 611)

Finishes

OP Opaline

Cct

W 3000
N 4000


Peso Líquido 700g
Peso Drenado 350g

Accessories



included
Polycarbonate clip springs kit.

suitable for: Mini Tube / Mini Tube IN&OUT



98710
Nickel-plated steel springs kit.

suitable for: Mini Tube / Mini Tube IN&OUT



99229 per meter
Extension cable in neoprene 2x1 mm² ON-OFF.
Example: 99229 x 3 pz = 3 m.


suitable for: Mini Tube / Mini Tube IN&OUT




98729
Quick connector IP68 socket/plug.
2 poles ON-OFF.

suitable for: Mini Tube / Mini Tube IN&OUT

Multiple connection
Fixture available in two variations: version **Mini Tube** with single input cable for installation of a single article or as end-of-line, version **Mini TubeIN&OUT** with double cable input and output cable to be able to create continuous lines of light with the use of specific accessories (Max 600W).







MAXI TUBE

Polycarbonate with UV protection. Neoprene cables.



CRI 90 IP67 DALI


Technical details
Opal or embossed polycarbonate tube with waterproof closing system using side plugs in transparent polycarbonate. The diameter of the tube is 33 mm.



Scale 1:1

Maxi Tube | topLED | 220-240 V AC | 13 W DC - 14,5 W AC






IK08 IP67 1 m

	Cct	lm S - lm D	Opt
CRI 90			
OP 92245	W	1440 - 1154	30 (99°x 85°)
EB 92442	N	1501 - 1226	12 (107°x 129°)
DALI - CRI 90			
OP 84359			
EB 84357			

Accessories (pag 615)

Maxi Tube | topLED | 220-240 V AC | 20 W DC - 22 W AC







IK08 IP67 1 m

	Cct	lm S - lm D	Opt
CRI 90			
OP 92246	W	2318 - 1904	30 (126°x 106°)
EB 92443	N	2478 - 2022	12 (128°x 125°)
DALI - CRI 90			
OP 84363			
EB 84361			

Accessories (pag 615)

Maxi Tube | topLED | 220-240 V AC






IK08 IP67 1 m

	Cct	lm S - lm D	lm S - lm D	Opt
CRI 90				
37W DC - 40,5W AC	W	3974 - 3231	2479 - 2017	30 (137°x 95°)
OP 92247	N	4248 - 3431	2699 - 2196	12 (143°x 118°)
EB 92444				
DALI - CRI 90				
20W DC - 22W AC				
OP 84367				
EB 84365				

Accessories (pag 615)

Maxi Tube IN&OUT | topLED | 220-240 V AC | 13 W DC - 14,5 W AC






IK08 IP67 1 m

	Cct	lm S - lm D	Opt
CRI 90			
OP 92353	W	1440 - 1154	30 (99°x 85°)
EB 92448	N	1501 - 1226	12 (107°x 129°)
DALI - CRI 90			
OP 84371			
EB 84369			

Accessories (pag 615)

Maxi Tube IN&OUT | topLED | 220-240 V AC | 20 W DC - 22 W AC






IK08 IP67 1 m

	Cct	lm S - lm D	Opt
CRI 90			
OP 92356	W	2318 - 1904	30 (126°x 106°)
EB 92449	N	2478 - 2022	12 (128°x 125°)
DALI - CRI 90			
OP 84375			
EB 84373			

Accessories (pag 615)

Maxi Tube IN&OUT | topLED | 220-240 V AC





IK08 IP67 1 m

	Cct	lm S - lm D	lm S - lm D	Opt
CRI 90		37W	20W	
37W DC - 40,5W AC	W	3974 - 3231	2479 - 2017	30 (137°x 95°)
OP 92357	N	4248 - 3431	2699 - 2196	12 (143°x 118°)
EB 92450				
DALI - CRI 90				
20W DC - 22W AC				
OP 84379				
EB 84377				

Accessories (pag 615)

Finishes

OP Opaline
EB Embossed

Cct

W 3000
N 4000



ROZAFA CASTLE
Shkodra (Albania)

Lighting Designer:
Fulvio Baldeschi

Photography:
Pietro Savorelli


Multiple connection
Fixture available in two variations: version **Maxi Tube** with single input cable for installation of a single article or as end-of-line, version **Maxi Tube IN&OUT** with double cable input and output cable to be able to create continuous lines of light with the use of specific accessories (On-Off / DALI max 600W).

Maxi Tube: with single cable




Maxi Tube IN&OUT: with double cable, one input and one output





On-Off / DALI max 600W



Accessories



99226
Fastening kit with nickel-plated steel clips.
Two fastening kits are required for installation.

suitable for: Maxi Tube / Maxi Tube IN&OUT



99227
Fastening kit with nickel-plated steel clips and connector.
Two fastening kits are required for installation.

suitable for: Maxi Tube / Maxi Tube IN&OUT



98695
Fastening kit with safety clasp.
Two fastening kits are required for installation.

suitable for: Maxi Tube / Maxi Tube IN&OUT



C-F100017
Suspension fixing system with 2000 mm long steel cable.
Two fastening kits are required for installation.

suitable for: Maxi Tube / Maxi Tube IN&OUT



99229 per meter
Extension cable in neoprene 2x1 mm^2 ON-OFF.
Example: 99229 x 3 pz = 3 m.

83205 per meter
Extension cable in neoprene 4x1,5 mm^2 DALI.
Example: 83205 x 3 pz = 3 m.

suitable for: Maxi Tube / Maxi Tube IN&OUT



98729
Quick connector IP68 socket/plug.
2 poles ON-OFF.

99768
Quick connector IP68 socket/plug.
5 poles DALI.

suitable for: Maxi Tube / Maxi Tube IN&OUT

HIGH PROTECTION

Body in polycarbonate with UV protection.
Plugs in anodised 6026 aluminium.
Neoprene cables.

High Protection Embossed (EB)



CRI 90 DALI

Construction details
Polycarbonate tube with waterproof closing system using rotating side plugs in 6026 anodised aluminium. Special TCS® valve as protective air vent to prevent the formation of condensation inside the tube, thereby ensuring long life for the lamp. Quick connector system with a range of accessory cables to create continuous lines directly connected to the electrical mains, thanks to the driver included in each bar. LED tube featuring light source made up of latest generation high density SMD Top LEDs mounted on PCB. In the case of embossed internal diffuser with the use of optics in the 30, 12, perfect cleaning of the cone of light is ensured thanks to the special embossing.

High Protection Wired

High Protection



TCS® Valve


Cable exit positions
The orthogonal cable exit from the High Protection tube allows the space between two continuous tubes to be minimised, thereby optimising the continuous line of light effect. The High Protection Wired version has a linear cable exit position along the axis of the tube, through the closing plug.



Connection examples (High Protection)

Single connection

Multiple connection
Max 600W ON/OFF
Max 300W DALI




Insulating terminal plug.



PROTON THERAPY CENTER
Trento (Italy)

High Protection | topLED | 220-240 V AC | 13 W DC - 14,5 W AC






IK08 IP66

	Cct	lm S - lm D	Opt
CRI 90			
EB **94679**	**W**	1440 - 1102	**30** (99°x 85°)
DALI - CRI 90	**N**	1501 - 1148	**12** (107°x 129°)
EB **84402**			

Accessories (pag 619-620)

High Protection | topLED | 220-240 V AC | 20 W DC - 22 W AC






IK08 IP66

	Cct	lm S - lm D	Opt
CRI 90			
EB **94680**	**W**	2318 - 1960	**30** (126°x 106°)
DALI - CRI 90	**N**	2478 - 2096	**12** (128°x 125°)
EB **84405**			

Accessories (pag 619-620)

High Protection | topLED | 220-240 V AC






IK08 IP66

	Cct	lm S - lm D	lm S - lm D	Opt
CRI 90				
37W DC - 40,5W AC	**W**	3974 - 3491	2479 - 2181	**30** (137°x 95°)
EB **94681**	**N**	4248 - 3732	2699 - 2375	**12** (143°x 118°)
DALI - CRI 90				
20W DC - 22W AC				
EB **84408**				

Accessories (pag 619-620)

High Protection Wired | topLED | 220-240 V AC | 13 W DC - 14,5 W AC






1 m IK08 IP66

	Cct	lm S - lm D	Opt
CRI 90			
EB **95465**	**W**	1440 - 1102	**30** (99°x 85°)
DALI - CRI 90	**N**	1501 - 1148	**12** (107°x 129°)
EB **84411**			

Accessories (pag 619-620)

High Protection Wired | topLED | 220-240 V AC | 20 W DC - 22 W AC






1 m IK08 IP66

	Cct	lm S - lm D	Opt
CRI 90			
EB **95466**	**W**	2318 - 1960	**30** (126°x 106°)
DALI - CRI 90	**N**	2478 - 2096	**12** (128°x 125°)
EB **84414**			

Accessories (pag 619-620)

High Protection Wired | topLED | 220-240 V AC





1 m IK08 IP66

	Cct	lm S - lm D	lm S - lm D	Opt
CRI 90				
37W DC - 40,5W AC	**W**	3974 - 3491	2479 - On req	**30** (137°x 95°)
EB **95467**	**N**	4248 - 3732	2699 - On req	**12** (143°x 118°)
DALI - CRI 90				
20W DC - 22W AC				
EB **84417**				

Accessories (pag 619-620)

Accessories



99225
IP66 ON-OFF connection box.

83229
IP66 DALI connection box.

suitable for: High Protection / High Protection Wired



99216 1500 mm
1500 mm long power cable with female quick connector in IP66 (ON-OFF / DALI).

suitable for: High Protection



99217 150 mm
Extension cable with male/female quick connector in IP66 for direct connection between tubes (ON-OFF / DALI).

suitable for: High Protection



99218 1500 mm
Extension cable with male/female quick connector in IP66 for direct connection between tubes (ON-OFF / DALI).

suitable for: High Protection



99229 per meter
Extension cable in neoprene 2x1 mm^2 ON-OFF.
Example: 99229 x 3 pz = 3 m.

83213 per meter
Extension cable in neoprene 4x1 mm^2 DALI.
Example: 83213 x 3 pz = 3 m.

83205 per meter
Extension cable in neoprene 4x1,5 mm^2 DALI.
Example: 83205 x 3 pz = 3 m.

suitable for: High Protection Wired




98729
Quick connector IP68 socket/plug.
2 poles ON-OFF.

99768
Quick connector IP68 socket/plug.
5 poles DALI.

suitable for: High Protection Wired


Accessories

99219

Suspension fixing system with anodised aluminium ring, tightening safety screws, 1200 mm long steel cable, adjustment system for the cable and fixing with screws and anchors. Two fastening kits are required for installation.


suitable for: High Protection / High Protection Wired

C-F100017

Suspension fixing system with 1200 mm long steel cable, adjustment system for the cable and fixing with screws and anchors. Two fastening kits are required for installation.


suitable for: High Protection / High Protection Wired

99221

Male/female fittings in anodised aluminium to join articles, fixing screws and tightening safety screws. To be used only with the suspension fixing kit (code 99219 - indicated above).


suitable for: High Protection

99222

Surface installation system with screw locking and fixing using self-tapping screw and anchor. Made in transparent polycarbonate. Two fastening kits are required for installation.


suitable for: High Protection / High Protection Wired

99220

Clip fixing spring in nickel plated steel, self-tapping screw, anchor and o-ring for safety closing. Two fastening kits are required for installation.


suitable for: High Protection / High Protection Wired

99238

Clip fixing spring in transparent polycarbonate, self-tapping screw, anchor and o-ring for safety closing. Two fastening kits are required for installation.


suitable for: High Protection / High Protection Wired

99224

Corner installation system with pair of side brackets with screw locking and fixing using self-tapping screws and anchors.

suitable for: High Protection

99223

Installation system with pair of side brackets with screw locking and fixing using self-tapping screws and anchors.

suitable for: High Protection

METRO STATION NATIONAL GALLERY
Oslo (Norway)



PARKHAUS ZECHE ZOLLVEREIN
Essen (Germany)

Design and construction supervision:
Dreßler Bau GmbH, Essem Herr Pauli

Lighting Design:
Engineer Büro Paulus Essen, Herr Gräf

Photography:
Linea Light GmbH





RESIDENCE CIVICO 3.9
Treviso (Italy)


Project:
Studio Architetti Associati
Giampietro & Stefano Cinel

Commissioned by:
Fralma Srl

Photography:
TheStudio

D-WAVE

Composite material and metal brackets.




MAXIMUM DESIGN FLEXIBILITY, EVEN IMPOSSIBLE ONES

PATENTED

With D-WAVE we have created the first flexible two-axis lighting system. We have given the impossible a chance. D-WAVE is the new frontier in linear outdoor marker lights. Thanks to the extreme flexibility of the fully recyclable composite material, it can be adapted to any perimeter, even the most complex and winding ones. The internal pass-through compartments, along the entire length, make it possible to insert wiring, for example, and keep it protected. At the front, various flexible linear light sources can be inserted, such as our Rubber 3D and PU_C Plus. Rubber 3D light sources allow you to take full advantage of the double curvature.



Two-axis flexibility
D-WAVE is a system with the highest flexibility and adaptability available on the market. Its cross-section, studied in every detail, allows both zenithal and lateral bending, which allows D-WAVE to overcome any obstacle or embrace any path. The extruded profile, studied in every detail, can have an endless range of customisations thanks to its extreme ductility. The illumination of contemporary architecture, even the most complex and articulated, will always find its correct solution.




Zenithal flexibility



Lateral flexibility (can only be used with Rubber 3D)

A BLADE OF LIGHT THAT SINUOUSLY ILLUMINATES THE GROUND





D-Wave + Rubber 3D Optics white 22W/m | 3000K




D-Wave + Rubber 3D 10W/m | 3000K


BORN FOR THE FUTURE: RECYCLABLE AND CUSTOMISABLE

D-WAVE is a profile designed in every detail to meet all of the designer's needs. The base is designed to accommodate the fastening systems provided: bracket and stake. Two anchoring methods that facilitate installation by adapting to the perimeter to be followed. Engraved on the base is the Recycle 3 logo, which allows the type of material to be recognised for proper recycling.





90° bending radius in just 900 mm
Thanks to its great zenithal flexibility, D-WAVE allows to obtain wide continuous curvatures in the plane. Thanks to the material it is made of, the extruded profile can follow any type of curved perimeter, without interruptions in wiring or light falloff. By combining it with equally flexible and ductile light sources, perfect light continuity is optimised and preserved.




90° angle connection cuts
D-WAVE is available in 2-metre long modules. D-WAVE can be cut anywhere, even at 90° angles, thanks to the special angular joint, and it can be connected in perfect aesthetic and functional continuity. This solution offers two major advantages: work can be carried out with millimetric precision, without losing efficiency, and the brightness can be maintained constant along the entire perimeter.

Floor mounting
Thanks to the quick-release steel bracket, D-WAVE can be mounted on any floor. Positioned at a 50 cm pitch, the bracket ensures firm and continuous anchoring over the entire length of the luminaire.




Ground mounting
For this type of installation, a small steel stake has been provided, which is also adjustable and can be placed at a certain pitch, ensuring continuous and safe anchoring over the entire length of the perimeter.



Quick-release bracket
We have designed a quick-release bracket system. This is ideal in case of maintenance, replacement or relocation of the luminaire. Thanks to the rear lever, the bracket is quickly released from the profile, leaving it free, thus facilitating the planned operations.

All-in-one
D-WAVE is an all-in-one extruded profile that contains the light source in the front channel: Rubber 3D or PU_C Plus, all the wiring required for your project is protected in the rear channel. The duct passing under the light source is used to support the lighting profile inserted. All the technological components that make up the D-WAVE system are housed in a single profile.



Connecting element
We have designed an invisible connecting element that contributes to the maximum aesthetic and functional continuity of D WAVE. The intermediate joint, linear or angular, allows for the continuous passage of cables and light sources without interruptions or falloff.

Anchor brackets
Positioned every 50 cm, they ensure secure and stable installation on any floor or ground and with any zenithal or lateral curvature. The brackets guarantee completely safe installation in any location and in all surface conditions.

Profile leveling thickness
Allows for levelling the D-Wave profile. To be used, for example, if there is too much distance between the two anchoring brackets. (C-F800003).

Closing element
The end element that closes D-WAVE completes the marker light, making it perfectly unified and continuous along the entire length. An essential accessory from a functional and aesthetic point of view. (77408).




2000 mm




Customization on site
The material D-WAVE is made of is easily customisable, whatever colour you need for your projects. Thanks to the special construction material, paint adheres easily to the entire surface (use only paints for plastic materials). Let your creativity run wild with D WAVE!



D-Wave





IK10

2000 mm

BN **77407**

The modules must be completed with light source and power supply.

D-Wave | Flex lights




Rubber 3D pag. 412
Rubber 3D Optics pag. 416
Rubber 3D Pixel pag. 417
PU_C Plus pag. 397

Suggested light unit

Electronics

D-Wave | Driver ON/OFF | 220-240 V AC





C.V. IP67

AL **C-E400001** 100 W - Output 24 V DC

The power supply can be inserted inside the D-Wave profile.


Accessories

D-Wave | Cap



BN **77408** Right-cap accessory
suitable for: D-Wave

D-Wave | Cap



BN **77409** Left-cap accessory
suitable for: D-Wave

D-Wave | Internal 90° corner



BN **77469** Curve for external 90° corner
suitable for: D-Wave

D-Wave | External 90° corner



BN **77412** Curve for internal 90° corner
suitable for: D-Wave

D-Wave | Jointing




BN **77410** Profile jointing accessory
suitable for: D-Wave

D-Wave | Stake




IS **77411** Fixing stake
suitable for: D-Wave

D-Wave | Bracket



IS Mounting bracket
suitable for: D-Wave 4 x included

D-Wave | Profile leveling thickness




PVC **C-F800003** Profile leveling accessory
suitable for: D-Wave

Finishes

BN Brown
AL Aluminium
IS Steel
PVC PVC







DIRIGO

Aluminium or AISI 316L stainless steel body.



RESIDENCE CIVICO 3.9
Castelfranco Veneto - Treviso (Italy)

Project: Studio Architetti Associati Giampietro & Stefano Cinel

Commissioned by: Fralma Srl

Photography: TheStudio

Concept
Invisible during the day. Main actor during the night. Dirigo creates lighting paths through an elegant opposite plans game, hiding the source. Its peculiar profile's section makes the fixture compact and solid, perfectly integrated in all outdoor contexts.




Technology and materials
Dirigo series available in brushed stainless steel AISI 316L or anodyzed extruded aluminum with polyester powder pre-coating antioxide treatment.



Range
Dirigo is available as single module or prepared for continuous line installation.

Single module (L. 1mt)
Sealed and complete source profile, end caps, integrated driver 24V DCo.


Continuous line installation modules
On measure cutting profiles, prepared for continuous line installation up to 5/10m. Led source available with a separated code and on measure cutting. Mechanical connection joints between profiles. Remote driver 24 V DC.



Robust design
The opposing level structure of Dirigo's single profile makes this appliance particularly sturdy and resistant. The absence of raw edges makes it ideal for public and private outdoor applications. Dirigo can be walked on and is extremely safe for users.




Grazing light
The internal Led source gradient was studied for the best lighting distribution, along the pathways.





Dirigo_FL2 Aluminium | Complete Module | topLED | 220-240 V AC






IK09 IP67

	Cct	lm S - lm D	Opt
14,4 W DC - 17 W AC			
DG 64643	W	1425 - 607	00 (Asym. Ww)
GG 64642			
DB 64594			

Dirigo_M2 Aluminium | Master






IK09

DG 64645
GG 64644
DB 64595

To be completed with dedicated installation accessories and with lighting unit

Dirigo_M2 Aluminium | Slave







IK09

	L mm
DG 62400	1000
GG 62401	1000
DB 62402	1000
DG 64647	2000
GG 64646	2000
DB 64597	2000

To be completed with dedicated installation accessories and with lighting unit

Dirigo_M2 Aluminium | IN-corner






IK09

DG 64664
GG 64665
DB 64666

To be completed with dedicated installation accessories and with lighting unit

Dirigo_M2 Aluminium | OUT-corner






IK09

DG 64667
GG 64668
DB 64669

To be completed with dedicated installation accessories and with lighting unit

Dirigo Sealing | End caps






DG 64641	2 x
GG 64640	2 x
DB 64589	2 x
IS 64592	2 x

Dirigo Joining | Joining element






DG 64661	1 x
GG 64663	1 x
DB 64662	1 x
IS 64593	1 x

Dirigo_FL1 Steel | Complete Module | topLED | 220-240 V AC






IK09 IP67

	Cct	lm S - lm D	Opt
9,6 W DC - 12 W AC			
IS **64590**	**W**	865 - 518	**00** (Asym. Ww)

Dirigo_M1 Steel | Master






IK09

IS **64591**

To be completed with dedicated installation accessories and with lighting unit

Dirigo_M1 Steel | Slave







IK09

IS **64648**

To be completed with dedicated installation accessories and with lighting unit

Silicone | 120 LED/m | topLED | CRI 90 | 24 V DC | 9,6 W/m





C.V. CRI 90 IP67 NEW


		Cct	lm S - lm D	Opt	L
C0052		**M**	4040 - 4040	**DI**	**05019** (5 m - 48 W)
		W	4323 - 4323		
		N	4490 - 4490		

Electronics: **AL** (pag 399) | Accessories (pag 398) | Linear profile (pag 400)

Recommended LED strip for **Dirigo_M1 Steel**

PU_C Plus | 140 LED/m | topLED | CRI 90 | 24 V DC | 14,4 W/m






Made in Italy C.V. ICS 3 years warranty IP66 NEW


		Cct	lm S - lm D	Opt	L
C0035		**M**	6900 - 6900	**DI**	**05019** (5 m - 72 W)
		W	7230 - 7230		
		N	7495 - 7495		

Electronics: **AL** (pag 633)

Recommended LED strip for **Dirigo_M2 Aluminium**

Silicone | 168 LED/m | topLED | CRI 90 | 24 V DC | 14,4 W/m





C.V. IP67 NEW

		Cct	lm S - lm D	Opt	L
C0053		**M**	6786 - 6786	**DI**	**05019** (5 m - 72 W)
		W	7127 - 7127		
		N	7189 - 7189		

Electronics: **AL** (pag 633)

Recommended LED strip for **Dirigo_M2 Aluminium**

Electronics

AL


99374	**99331**	**99332**	**83333**	**C-E400002**
ON/OFF	ON/OFF	0/1-10V	DALI/PUSH	DALI/PUSH
75W	150W	150W	150W	240W
210 x 49 x h 25	158 x 60 x h 35	158 x 60 x h 35	188 x 68 x h 34	188 x 68 x h 34
56	70	70	77	77

Finishes

WH White
IS Steel

Cct

M 2700 **N** 4000
W 3000





CAPRICORN BRIDGE
Düsseldorf (Germany)

Design:
Supergelb Architekten

Lighting Designer:
Jack Be Nimble

Photography:
HGEsch Photography

DIRIGO
CUT-OFF




OPTIMISED LIGHT DISTRIBUTION

NEW

BUG Rating U0

Dirigo Cut-Off is a fully modular outdoor lighting system designed to offer a range of customised configurations, which can be adapted to specific project needs. Its structure is entirely made of high-quality aluminium and the three elegant Dark Grey, Dark Brown and Grey finishes allow the system to fit harmoniously into any outdoor context.




Dirigo Cut-Off's special optical compartment ensures targeted light distribution, creating an optimally lit environment and offering greater visual comfort. The system limits light dispersion beyond 90°, thus complying with light pollution regulations. Dirigo Cut-Off is suitable for outdoor lighting in urban and suburban areas and helps create safer and more pleasant environments without compromising the surroundings, preserving the night sky and nature in general.

The two versions, stand-alone or modular to be completed with dedicated accessories, make it possible to create unique and customised lighting solutions.



Create the perfect atmosphere

With Dirigo Cut-Off, it is possible to turn any outdoor space into a unique and comfortable place for the best lighting experience, where design and sustainability go hand in hand.



Grey (GG)





Dark Grey (DG)



Dark Brown (DB)

Dirigo Cut-Off | Complete Module | topLED | 220-240 V AC






IK09 IP67 NEW

	Fin	Cct	lm S - lm D	Opt
7,2 W DC - 9 W AC				
C00222	**DG**	**M**	756 - 345	**WW** (Asym. Ww)
	GG	**W**	802 - 366	
	DB	**N**	914 - 370	

Dirigo Cut-Off | Linear profile






IK09 NEW

		L mm
DG	**C-K400070**	1010
GG	**C-K400071**	1010
DB	**C-K400072**	1010
DG	**C-K400073**	2010
GG	**C-K400074**	2010
DB	**C-K400075**	2010

To be completed with dedicated installation accessories and with lighting unit

Dirigo Cut-Off | IN-corner






IK09 NEW

DG	**C-K400064**	1 x
GG	**C-K400065**	1 x
DB	**C-K400066**	1 x

To be completed with dedicated installation accessories and with lighting unit

Dirigo Cut-Off | OUT-corner







IK09 NEW

DG	**C-K400067**	1 x
GG	**C-K400068**	1 x
DB	**C-K400069**	1 x

To be completed with dedicated installation accessories and with lighting unit

Dirigo Cut-Off | End caps






NEW

DG	**C-K400058**	2 x
GG	**C-K400059**	2 x
DB	**C-K400060**	2 x

Dirigo Cut-Off | Joining element







NEW

DG	**C-K400061**	1 x
GG	**C-K400062**	1 x
DB	**C-K400063**	1 x

PU_C Plus | 140 LED/m | topLED | 24 V DC | 7,2 W/m






	Cct	lm S - lm D	Opt	L
CRI 90				
C0034	**M**	3780 - 3780	**DI**	**05019** (5 m - 36 W)
	W	4010 - 4010		
	N	4568 - 4568		

Electronics: **AL** (pag 639)

Strip suggested for Dirigo Cut-Off (except for Complete Module version)



Electronics

AL

99374	**99331**	**99332**	**83333**	**C-E400002**
ON/OFF	ON/OFF	0/1-10V	DALI/PUSH	DALI/PUSH
75W	150W	150W	150W	240W
210 x 49 x h 25	158 x 60 x h 35	158 x 60 x h 35	188 x 68 x h 34	188 x 68 x h 34
56	70	70	77	77

Finishes

White


Cct

M 2700 **N** 4000
W 3000

FYLO+


Aluminium profile. Quartz powder resin and mixed construction site material.

Installation process
When fully installed, profiles disappear by merging with the surrounding architecture; integrated light concept allows space customization with unusual and precious lighting details.



Fylo+ Out Recessed_S | Recessed light body






	L mm
PR 65036	1000
PR 65037	2000

Accessories: (pag 641)

Fylo+ Out Recessed_W | Recessed light body







	L mm
PR 65039	1000
PR 65040	2000

Accessories: (pag 641)

Silicone | 120 LED/m | topLED | 24 V DC | 9,6 W/m






	Cct	Im S - Im D	Opt	L
CRI 90				
C0052	M	4040 - 4040	DI	05019 (5 m - 48 W)
	W	4323 - 4323		
	N	4490 - 4490		

Electronics: **AL** (pag 641)

Strip suggested for Fylo+ Out article

Accessories


Fylo+ | Opaline diffuser



OP **62757** 1 m
OP **62758** 2 m
OP **65094** Custom
suitable for: Fylo+ Out Recessed_S - Out Recessed_W


By selecting the "Custom" code, it is possible to order at desired diffuser length up to a maximum of 2 m. For example, to request 1.3 m order 1.3 x 65094.

Fylo+ | Sealing caps



PR **65026** 2 x
suitable for: Fylo+ Out Recessed_S

Fylo+ | Template




65035
suitable for: Fylo+ Out Recessed_S

Electronics

AL


99374	99331	99332	83333	C-E400002
ON/OFF	ON/OFF	0/1-10V	DALI/PUSH	DALI/PUSH
75W	150W	150W	150W	240W
210 x 49 x h 25	158 x 60 x h 35	158 x 60 x h 35	188 x 68 x h 34	188 x 68 x h 34
56	70	70	77	77

Fylo+ | Sealing caps



PR **65023** 2 x
suitable for: Fylo+ Out Recessed_W

Fylo+ | Template



POL **65038**
suitable for: Fylo+ Out Recessed_W

Finishes

WH White
PR Primer
OP Opaline
POL Polystyrene

Cct

M 2700 **N** 4000
W 3000





STEP
LIGHTS

RESIDENCE CIVICO 3.9
Castelfranco Veneto (Italy)

Project:
Studio Architetti Associati
Giampietro & Stefano Cinel

Commissioned by:
Fralma Srl

Photography:
TheStudio



Step lights range index

Clip

Clip_Hm

646

Clip_R

647

Clip_X

647

Quara

Quara_RO

650

Quara_R


651

Quara_RI

651

Quara_F

651

Quara_Q

652


Quara_QI

652


Cut


Cut_R

654

Cut_Q

654

Sand

Sand_R

657

Sand_Q

657

Orma

Orma_AJ

659

Orma_IJ

659

Orma_Q

660

Orma_QF

660

Envelope

Envelope_1

666

Envelope_R

666

Envelope_R

666

Envelope_RW

666

Envelope_Q

668


Envelope_QW

668

Envelope_W

668

Step66

Step66

671

Optiwall

Optiwall

674

Optiwall_Pro

674-675

Chim

Chim

676


CLIP

Aluminium body.



Clip_Hm | powerLED | 350 mA | 1 W DC






IK09 IP66

	Cct	lm S - lm D	Opt
WH **82701**	**M**	136 - 40	**07** (Asym. Ww)
GG **82702**	**W**	145 - 42	
DB **82703**	**N**	155 - 45	

Electronics: **BB** (pag 647) | Recessed casings: (pag 647)

Clip_Hm | powerLED | 350 mA | 1 W DC






IK09 IP66

	Cct	lm S - lm D	Opt
IS **82710**	**M**	136 - 35	**07** (Asym. Ww)
	W	145 - 37	
	N	155 - 39	

Electronics: **BB** (pag 647) | Recessed casings: (pag 647)

Clip_R | powerLED | 630 mA | 2 W DC






	Cct	Im S - Im D	Opt
WH 92271	M	233 - 108	70 (Radial Mono-direc.)
GG 92272	W	249 - 115	
IS 92273	N	266 - 123	
	C	266 - 123	
	R-G-B-Y On req		

Electronics: **BD** (pag 647) | Recessed casings: (pag 647)

Clip_R | powerLED | 350 mA | 2 W DC






	Cct	Im S - Im D	Opt
WH 92281	M	272 - 127	70 (Radial Bi-direc.)
GG 92282	W	290 - 135	
IS 92283	N	310 - 144	
	C	330 - 164	
	R-G-B-Y On req		

Electronics: **BX** (pag 647) | Recessed casings: (pag 647)

Clip_X | powerLED | 630 mA | 2 W DC





	Cct	Im S - Im D	Opt
WH 92311	M	233 - 174	70 (Radial 180°)
GG 92312	W	249- 186	
IS 92313	N	266 - 199	
	C	266 - 199	
	R-G-B-Y On req		

Electronics: **BD** (pag 647) | Recessed casings: (pag 647)

Electronics

BB

89419	89421	C-E200006	C-E200004
ON/OFF	ON/OFF	ON/OFF	DALI/PUSH
1 - 2 art.	3 - 6 art.	6 - 12 art.	5 - 12 art.
74 x 65 x h 27	74 x 65 x h 27	135 x 26 x h 26	125 x 45 x h 30
		35	55


BD

89420	C-E200008	99186	C-E200002
ON/OFF	ON/OFF	ON/OFF	DALI/PUSH
1 - 2 art.	3 - 6 art.	6 - 12 art.	5 - 12 art.
74 x 65 x h 27	135 x 26 x h 26	117 x 92 x h 38	125 x 45 x h 30
	35		55

BX


89419	89421	C-E200006	C-E200004
ON/OFF	ON/OFF	ON/OFF	DALI/PUSH
1 art.	2 - 3 art.	3 - 6 art.	3 - 6 art.
74 x 65 x h 27	74 x 65 x h 27	135 x 26 x h 26	125 x 45 x h 30
		35	55

Recessed casings




ABS **99676** Recessed casings

suitable for: Clip_Hm Ø 25 mm



ABS **84336** Recessed casings

suitable for: Clip_Hm Ø 35 / Clip_R / Clip_X Ø 40 mm



ABS **84915** Recessed casings

suitable for: Clip_Hm Ø 35 / Clip_R / Clip_X Ø 40 mm

Finishes

WH White
GG Grey
IS Steel

Cct

M 2700
W 3000
N 4000
C 5000

QUARA

Aluminium or AISI 316L stainless steel body.

Quara family

Quara_R



347-348


Quara_Q




347-348

HIGH DEFINITION LIGHTING

The new circular aperture creating a light beam with extremely well-defined edges complements and completes the Quara series. The perfect shaping of the light on the ground creates striking graphic effects. Thanks to the IP65 protection rating and dedicated finishes, it is the ideal step light for contemporary outdoor settings. Quara RO is available in three diameters: Ø25, Ø40 and Ø70 mm and three colours: White, Grey, Dark and Brown.



White (WH)



Grey (GG)



Dark Brown (DB)


COMPACT, COMFORTABLE, SPECTACULAR

ID Driver on board

A drop of light in a square or round lamp body: Quara, a marker light with an IP65 protection rating which, when installed close to the floor, illuminates and decorates in a classy and tasteful manner thanks to its asymmetrical optics. Available versions (ID) with the power supply integrated to the luminaire body, so it is possible to connect Quara directly to the power line.








Quara_RO | powerLED | 220 mA | 0,7 W DC







	Cct	Im S - Im D	Opt
WH 77395	A	88 - On req	70 (Asym. Ww)
GG 77396	M	94 - On req	
DB 77397	W	101 - On req	
	N	107 - On req	

Electronics: **BA** (pag 652) | Recessed casings: (pag 653)

Quara_RO | powerLED | 350 mA | 1 W DC






	Cct	Im S - Im D	Opt
WH 77391	A	111 - 26	70 (Asym. Ww)
GG 77392	M	145 - 34	
DB 77393	W	154 - 36	
	N	165 - 38	

Electronics: **BB** (pag 652) | Recessed casings: (pag 653)


Quara_RO | powerLED | 350 mA | 1 W DC






	Cct	Im S - Im D	Opt
WH 76745	A	111 - 37	70 (Asym. Ww)
GG 76746	M	145 - 48	
DB 76747	W	154 - 51	
	N	165 - 55	


Electronics: **BB** (pag 652) | Recessed casings: (pag 653)



Quara_RO 1 W DC - 3000K (76745) Assembly height: 40 cm

Quara_R | powerLED | 350 mA | 1 W DC






	Fin	Cct	lm S - lm D	Opt
C00236	WH	M	145 - 14	WW (Asym. Ww)
	GG	W	154 - 14	
	DB	N	165 - 16	
	IS			

Electronics: **BB** (pag 652) | Recessed casings: (pag 653)

Quara_R | powerLED





ID

	Cct	lm S - lm D	Opt
220-240 V AC - 2 W DC - 2,7 W AC			
WH 83579	A	176 - 89	70 (Asym. Ww)
GG 83580	M	233 - 117	
DB 83581	W	249 - 124	
	N	266 - 133	


Accessories: (pag 653)

	Cct	lm S - lm D	Opt
630 mA - 2 W DC			
WH 85543	A	176 - 89	70 (Asym. Ww)
GG 85542	M	233 - 117	
DB 87988	W	249 - 124	
	N	266 - 133	

Electronics: **BD** (pag 652) | Recessed casings: (pag 653)

Quara_R | powerLED | 24 V DC | 1,5 W DC






	Cct	lm S - lm D	Opt
IS 84075	M	188 - 6	07 (Asym. Ww)
DB 84076	W	199 - 7	
BS 84077	N	213 - 8	

Electronics: **DI** (pag 652) | Recessed casings: (pag 653)

Quara_RI | powerLED | 630 mA | 2 W DC






	Cct	lm S - lm D	Opt
IS 92671	A	176 - 63	70 (Asym. Ww)
	M	233 - 84	
	W	249 - 90	
	N	266 - 97	

Electronics: **BD** (pag 652) | Recessed casings: (pag 653)

Quara_F | powerLED | 350 mA | 1 W DC






	Cct	lm S - lm D	Opt
WH 84078	M	145 - 36	70 (Asym. Ww)
	W	154 - 38	
	N	165 - 41	

Electronics: **BB** (pag 652) | Recessed casings: (pag 653)

Quara_F | powerLED | 350 mA | 1 W DC







	Cct	lm S - lm D	Opt
WH 86460	M	145 - 71	70 (Asym. Ww)
	W	154 - 76	
	N	165 - 81	

Electronics: **BB** (pag 652) | Recessed casings: (pag 653)

Quara_Q | powerLED






C.C. IP65

	Fin	Cct	lm S - lm D	Opt
350 mA - 1 W DC				
C00237	**WH**	**M**	145 - 14	**WW** (Asym. Ww)
	GG	**W**	154 - 14	
	DB	**N**	165 - 16	
	IS			

Electronics: **BB** (pag 652) | Recessed casings: (pag 653)

Quara_Q | powerLED





IP65 ID

	Cct	lm S - lm D	Opt
220-240 V AC - 2 W DC - 2,7 W AC			
WH 83583	**A**	176 - 83	**70** (Asym. Ww)
GG 83584	**M**	233 - 116	
DB 83585	**W**	249 - 124	
	N	266 - 133	


Accessories: (pag 653)


C.C. IP65

	Cct	lm S - lm D	Opt
630 mA - 2 W DC			
WH 86563	**A**	176 - 83	**70** (Asym. Ww)
GG 86562	**M**	233 - 116	
DB 87989	**W**	249 - 124	
	N	266 - 133	

Electronics: **BD** (pag 652) | Recessed casings: (pag 653)

Quara_QI | powerLED






C.C. IP65

	Cct	lm S - lm D	Opt
630 mA - 2 W DC			
IS 92672	**A**	176 - 61	**70** (Asym. Ww)
	M	233 - 84	
	W	249 - 90	
	N	266 - 97	

Electronics: **BD** (pag 652) | Recessed casings: (pag 653)

Quara_QI | powerLED





IP65

	Cct	lm S - lm D	Opt
220-240 V AC - 4 W DC - 4,8 W AC			
WH 92238	**A**	352 - 189	**70** (Asym. Ww)
GG 92239	**M**	466 - 267	
DB 92240	**W**	498 - 285	
	N	532 - 305	

Accessories: (pag 653)

Electronics

BA

99307
ON/OFF (IP20)
1 - 2 art.
138 x 22 x h 20
29

83007
ON/OFF (IP20)
3 - 6 art.
138 x 22 x h 20
29

99342
ON/OFF
6 - 12 art.
80 x 100 x h 31

83154
DALI
5 - 14 art.
54 x 121 x h 26
60

BB

89419
ON/OFF
1 - 2 art.
74 x 65 x h 27

89421
ON/OFF
3 - 6 art.
74 x 65 x h 27

C-E200006
ON/OFF
6 - 12 art.
135 x 26 x h 26
35

C-E200004
DALI/PUSH
5 - 12 art.
125 x 45 x h 30
55

BD

89420
ON/OFF
1 - 2 art.
74 x 65 x h 27

C-E200008
ON/OFF
3 - 6 art.
135 x 26 x h 26
35

99186
ON/OFF
6 - 12 art.
117 x 92 x h 38

C-E200002
DALI/PUSH
5 - 12 art.
125 x 45 x h 30
55

DI

89488
ON/OFF
1 - 9 art.
80 x 100 x h 31

89179
ON/OFF
1 - 15 art.
92 x 117 x h 38

89359
ON/OFF
1 - 30 art.
115 x 140 x h 50

99660
Dimmer
DALI - 0/1-10V
149 x 37 x h 31
48


83042
Dimmer DALI/PUSH
0/1-10V
164 x 38 x h 25
45

+ driver 24V DC

99331
150W
1-70 art.
70


99786
240W
1-112 art.
81

Recessed casings




ABS 98950 Recessed casings

suitable for: Quara_RO Ø25 mm, Quara_R Ø25 mm
Quara_Q L25 mm




ABS 84915 Recessed casings

suitable for: Quara_RO Ø40 mm




ABS 84338 Recessed casings

suitable for: Quara_RO Ø70, Quara_R Ø65, Quara_Q L70
Quara_RI Ø70, Quara_QI L70, Quara_F Ø50 mm




ABS 83155 Recessed casings

suitable for: Quara_F Ø29 mm



ABS 84918 Recessed casings

suitable for: Quara_R Ø35 mm



ABS 98050 Recessed casings

suitable for: Quara_QI L126x121 mm



CUT


Aluminium body.





Cut_R | powerLED | 630 mA | 2 W DC







C.C. IP65

	Cct	Im S - Im D	Opt
WH 92513	M	219 - 26	05 (17°)
GG 92514	W	233 - 27	
	N	249 - 29	

Electronics: **BD** (pag 654) | Recessed casings: (pag 654)

Cut_Q | powerLED | 630 mA | 2 W DC





C.C. IP65

	Cct	Im S - Im D	Opt
WH 92558	M	219 - 26	05 (17°)
GG 92559	W	233 - 27	
	N	249 - 29	


Electronics: **BD** (pag 654) | Recessed casings: (pag 654)

Electronics

BD

89420	C-E200008	99186	C-E200002
ON/OFF	ON/OFF	ON/OFF	DALI/PUSH
1 - 2 art.	3 - 6 art.	6 - 12 art.	5 - 12 art.
74 x 65 x h 27	135 x 26 x h 26	117 x 92 x h 38	125 x 45 x h 30
	35		55

Recessed casings



PVC **84338** Recessed casings

suitable for: Cut_R / Cut_Q

ALMAR HOTEL
Jesolo (Italy)

Photography:
Studio Pointer





SAND

Brass body
Opalescent polycarbonate diffuser



Sand_R | powerLED | 350 mA | 1 W DC






	Cct	lm S - lm D	Opt
WH **92260**	**M**	145 - 74	**00** (Diffused)
	W	154 - 78	
	N	165 - 84	
	C	165 - 84	
	B	Blue	
	R-G-Y	On req	

Electronics: **BB** (pag 657) | Recessed casings: (pag 657)

Sand_Q | powerLED | 350 mA | 1 W DC





	Cct	lm S - lm D	Opt
WH **92262**	**M**	145 - 74	**00** (Diffused)
	W	154 - 78	
	N	165 - 84	
	C	165 - 84	
	B	Blue	
	R-G-Y	On req	

Electronics: **BB** (pag 657) | Recessed casings: (pag 657)


PRIVATE RESIDENCE
Venice (Italy)

Electronics

BB


89419	**89421**	**C-E200006**	**C-E200004**
ON/OFF	ON/OFF	ON/OFF	DALI/PUSH
1 - 2 art.	3 - 6 art.	6 - 12 art.	5 - 12 art.
74 x 65 x h 27	74 x 65 x h 27	135 x 26 x h 26	125 x 45 x h 30
		35	55

Recessed casings




ABS **84915** Recessed casings

suitable for: Sand_R / Sand_Q



ABS **84336** Recessed casings

suitable for: Sand_R / Sand_Q



Finishes
WH White

Cct
M 2700 **N** 4000 **B** Blue
W 3000 **C** 5000




ORMA

Aluminium body.
AISI 316L stainless steel flange.

Orma_AJ | Dark Light | arrayLED





Installation with flush flange

Fin	Cct	Im S - Im D	Opt
C.C. - 350 mA - 3 W DC			
C00862 DL **SA**	**M**	482 - 64	**WW** (Asym. Ww)
	W	500 - 67	
	N	526 - 70	


Electronics: **BN** (pag 661) | Recessed casings: (pag 662)

C.V. - 24 V - 3,5 W DC			
C00863 DL **SA**	**M**	482 - 64	**WW** (Asym. Ww)
	W	500 - 67	
	N	526 - 70	

Electronics: **ET** (pag 661) | Recessed casings: (pag 662)

Orma_AJ| Dark Light | arrayLED





Installation with flush flange

Fin	Cct	Im S - Im D	Opt
C.C. - 500 mA - 4,5 W DC			
C00866 DL **SA**	**M**	646 - 89	**WW** (Asym. Ww)
	W	673 - 93	
	N	711 - 98	


Electronics: **BW** (pag 661) | Recessed casings: (pag 662)

C.V. - 24 V - 5 W DC			
C00867 DL **SA**	**M**	646 - 89	**WW** (Asym. Ww)
	W	673 - 93	
	N	711 - 98	

Electronics: **DB** (pag 661) | Recessed casings: (pag 662)

Orma_IJ | Dark Light | powerLED





Installation with placing flange

Fin	Cct	Im S - Im D	Opt
C.C. - 350 mA - 3 W DC			
C00864 DL **SA**	**M**	482 - 64	**WW** (Asym. Ww)
	W	500 - 67	
	N	526 - 70	


Electronics: **BN** (pag 661) | Recessed casings: (pag 662)

C.V. - 24 V - 3,5 W DC			
C00865 DL **SA**	**M**	482 - 64	**WW** (Asym. Ww)
	W	500 - 67	
	N	526 - 70	

Electronics: **ET** (pag 661) | Recessed casings: (pag 662)

Orma_IJ | Dark Light | arrayLED





Installation with placing flange

Fin	Cct	Im S - Im D	Opt
C.C. - 500 mA - 4,5 W DC			
C00868 DL **SA**	**M**	646 - 89	**WW** (Asym. Ww)
	W	673 - 93	
	N	711 - 98	

Electronics: **BW** (pag 661) | Recessed casings: (pag 662)

C.V. - 24 V - 5 W DC			
C00869 DL **SA**	**M**	646 - 89	**WW** (Asym. Ww)
	W	673 - 93	
	N	711 - 98	

Electronics: **DB** (pag 661) | Recessed casings: (pag 662)

Orma family

Orma_C 440-442

Orma_QC 444-445

Orma_I _A 719-727

Orma_F _FO 730-734

Orma_Q _QF 735-741

Orma Blade 793

Finishes

Steel/Aluminium

Cct


M 2700 **N** 4000
W 3000

Accessories

DL Darklight

Orma_QF | Dark Light | arrayLED





Flush installation

2000 kg | IK10 | IP68 | NEW

	Fin	Cct	Im S - Im D	Opt
C.C. - 350 mA - 4 W DC				
C00764 DL	**GA**	**M**	596 - 196	**SP** (10°÷ 19°)
		W	624 - 205	**ML** (30°÷ 39°)
		N	660 - 217	


Electronics: **BE** (pag 661) | Recessed casings: (pag 662)

C.V. - 24 V DC - 5 W DC				
C00765 DL	**GA**	**M**	596 - 196	**SP** (10°÷ 19°)
		W	624 - 205	**ML** (30°÷ 39°)
		N	660 - 217	

Electronics: **DB** (pag 661) | Recessed casings: (pag 662)

Orma_QF | Dark Light | arrayLED





Flush installation

2000 kg | IK10 | IP68 | NEW

	Fin	Cct	Im S - Im D	Opt
C.C. - 220 mA - 8 W DC				
C00769 DL	**GA**	**M**	1088 - 427	**SP** (10°÷ 19°)
		W	1126 - 445	**ML** (30°÷ 39°)
		N	1188 - 457	**WF** (50°÷ 70°)


Electronics: **BF** (pag 661) | Recessed casings: (pag 662)

C.V. - 24 V DC - 9 W DC				
C00770 DL	**GA**	**M**	1088 - 427	**SP** (10°÷ 19°)
		W	1126 - 445	**ML** (30°÷ 39°)
		N	1188 - 457	**WF** (50°÷ 70°)

Electronics: **DC** (pag 661) | Recessed casings: (pag 662)

Orma_Q | Dark Light | arrayLED





Installation with placing flange

2000 kg | IK10 | IP68 | NEW


	Fin	Cct	Im S - Im D	Opt
C.C. - 350 mA - 4 W DC				
C00762 DL	**SA**	**M**	596 - 196	**SP** (10°÷ 19°)
		W	624 - 205	**ML** (30°÷ 39°)
		N	660 - 217	


Electronics: **BE** (pag 661) | Recessed casings: (pag 662)

C.V. - 24 V DC - 5 W DC				
C00763 DL	**SA**	**M**	596 - 196	**SP** (10°÷ 19°)
		W	624 - 205	**ML** (30°÷ 39°)
		N	660 - 217	

Electronics: **DB** (pag 661) | Recessed casings: (pag 662)

Orma_Q | Dark Light | arrayLED





Installation with placing flange

2000 kg | IK10 | IP68 | NEW

	Fin	Cct	Im S - Im D	Opt
C.C. - 220 mA - 8 W DC				
C00767 DL	**SA**	**M**	1088 - 427	**SP** (10°÷ 19°)
		W	1126 - 445	**ML** (30°÷ 39°)
		N	1188 - 457	**WF** (50°÷ 70°)

Electronics: **BF** (pag 661) | Recessed casings: (pag 662)

C.V. - 24 V DC - 9 W DC				
C00768 DL	**SA**	**M**	1088 - 427	**SP** (10°÷ 19°)
		W	1126 - 445	**ML** (30°÷ 39°)
		N	1188 - 457	**WF** (50°÷ 70°)

Electronics: **DC** (pag 661) | Recessed casings: (pag 662)

Electronics

BE

89421	C-E200006	C-E200004
ON/OFF	ON/OFF	DALI/PUSH
1 art.	2 - 3 art.	2 - 3 art.
74 x 65 x h 27	135 x 26 x h 26	125 x 45 x h 30
	35	55

BF

99342	C-E200005
ON/OFF	DALI/PUSH
1 art.	1 art.
100 x 80 x h 31	125 x 45 x h 30
	55

BN

89421	C-E200006	C-E200004
ON/OFF	ON/OFF	DALI/PUSH
1 - 2 art.	2 - 4 art.	2 - 4 art.
74 x 65 x h 27	135 x 26 x h 26	125 x 45 x h 30
	35	55

BW

C-E200007	99185	C-E200003
ON/OFF	ON/OFF	DALI/PUSH
1 - 2 art.	2 - 4 art.	2 - 4 art.
135 x 26 x h 26	117 x 92 x h 38	125 x 45 x h 30
35		55

DB

89488	89179	89359	99660	83042	+ driver 24V DC	
ON/OFF	ON/OFF	ON/OFF	Dimmer	Dimmer DALI/PUSH	99331 150W	99786 240W
1 - 2 art.	1 - 4 art.	1 - 9 art.	DALI - 0/1-10V	0/1-10V	1-21 art.	1-33 art.
80 x 100 x h 31	92 x 117 x h 38	115 x 140 x h 50	149 x 37 x h 31	164 x 38 x h 25	70	81
			48	45		

DC


89179	89359	99331	99660	83042	+ driver 24V DC	
ON/OFF	ON/OFF	ON/OFF	Dimmer	Dimmer DALI/PUSH	99331 150W	99786 240W
1 - 2 art.	1 - 5 art.	1 - 15 art.	DALI - 0/1-10V	0/1-10V	1-11 art.	1-18 art.
92 x 117 x h 38	115 x 140 x h 50	158 x 60 x h 35	149 x 37 x h 31	164 x 38 x h 25	70	81
			48	45		


ET


89488	89179	89359	99660	C-E500023	+ driver 24V DC	
ON/OFF	ON/OFF	ON/OFF	Dimmer	Dimmer DALI/PUSH	99331 150W	99786 240W
1 - 3 art.	1 - 6 art.	1 - 12 art.	DALI - 0/1-10V	0/1-10V	1-38 art.	1-61 art.
80 x 100 x h 31	92 x 117 x h 38	115 x 140 x h 50	149 x 37 x h 31	80 x 40 x h 25	70	81
			48	48		

Dark Light Optics


Optics conceived for wall and floor recessed installation, they allow the creation of perfectly marked and visible luminous paths. Thanks to the tilting system built into the optics compartment (_AJ, _IJ), Orma Dark Light is able to adapt to different installation heights.








Recessed casings




ABS 99650 Recessed casings

suitable for: Orma_AJ Ø54 mm
Orma_IJ Ø64 mm




ABS 99560 Recessed casings with flange

suitable for: Orma_AJ Ø54 mm




ABS 99855 Recessed casings with flange

suitable for: Orma_AJ Ø54 mm




ABS C-C100002 Recessed casings

suitable for: Orma_QF 60x60 mm



ABS 83411 Recessed casings

suitable for: Orma_Q 85x85 mm




ABS 99651 Recessed casings

suitable for: Orma_AJ Ø85 mm
Orma_IJ Ø97 mm




ABS 99563 Recessed casings with flange

suitable for: Orma_AJ Ø85 mm




ABS 99856 Recessed casings with flange

suitable for: Orma_AJ Ø85 mm



ABS C-C100003 Recessed casings

suitable for: Orma_QF 90x90 mm



ABS 83410 Recessed casings

suitable for: Orma_Q 116x116 mm




ENVELOPE

Aluminium body.

Envelope family	Envelope_1	Envelope_2	Envelope_4
			
	351	351	351

ELEGANCE AND QUINTESSENCE



The Envelope family is renewed with new powers, and Envelope_R/RW (24V, 220-240 V) is joined by a new round path marker that appears as a single, compact element, featuring a clean and pared-back look.
The pure geometric forms gently illuminate the space creating a suggestive sense of depth both indoors and outdoors. It is available in four finishes, white, grey, black grey, dark brown, four colour temperatures, 2200K, 2700K, 3000K and 4000K, and powers, 1.5W/2.5W for a softer effect, and 4W for a more incisive effect.

Recessed optics and visual comfort
The recessed source is hidden from view, making it a full cut-off luminaire: the eye sees and appreciates only the clean and comfortable emission; in a slightly asymmetrical position, it directs the beam towards the walking area.

Envelope_R
Ø40



Envelope_R
Ø120




Envelope_RW
Ø132



Envelope_1
40x40



Envelope_Q
120x88



Envelope_W
270x125



Envelope_W
170x168

Simplified installation
The Envelope_Q, _1, _R (Ø40) and _W models can be wall-mounted using the special 503 flush-mounted box; installation is simple and fast, and the screws are completely hidden from view making the luminaire one with the architecture. Envelope_QW, _R (Ø120), _RW and _W, can be fixed directly on the surface, does not involve the use of a flush-mounted box.

Envelope_QW



Installation on surface


Envelope_Q



Installation with recessed casing (standard box mod. 503)

Envelope_R | powerLED | 350 mA






Installation with outer casing

	Cct	Im S - Im D	Opt
1 W DC			
WH 83601	A	111 - 25	07 (Asym. Diffused)
BB 83602	M	145 - 35	
GG 83603	W	154 - 37	
DB 83604	N	165 - 39	
BG 84071			
BS 84072			

Electronics: **BB** (pag 669) | Recessed casings: (pag 669)

Envelope_1 | powerLED | 350 mA







Installation with outer casing

	Cct	Im S - Im D	Opt
1 W DC			
WH 96976	A	111 - 22	07 (Asym. Diffused)
BB 96977	M	145 - 30	
GG 96978	W	154 - 31	
DB 96979	N	165 - 34	
BG 80605			
BS 83613			

Electronics: **BB** (pag 669) | Recessed casings: (pag 669)

Envelope_R | topLED | 24 V DC





Surface installation

	Cct	Im S - Im D	Opt
1,5 W DC			
WH 76104	W	213 - 103	07 (Asym. Diffused)
GG 76105	N	224 - 108	
DB 76107			
BG 76106			


Electronics: **EQ** (pag 669)

4 W DC			
WH 76090	W	468 - 227	07 (Asym. Diffused)
GG 76091	N	490 - 237	
DB 76093			
BG 76092			

Electronics: **DE** (pag 669)

Envelope_RW | topLED | 220-240 V AC





Surface installation or with outer casing

	Cct	Im S - Im D	Opt
1 W DC - 1,6 W AC			
WH 77040	W	181 - 76	07 (Asym. Diffused)
GG 77041	N	189 - 79	
DB 77043			
BG 77042			
2 W DC - 2,5 W AC			
WH 77044	W	370 - 156	07 (Asym. Diffused)
GG 77045	N	390 - 162	
DB 77047			
BG 77046			

Recessed casings: (pag 669)

ID Driver on board

VIDA BEACH RESORT MARASSI AL BAHRAIN
MANAMA (Bahrain)

Lighting Supplier: Huda Lighting

Lighting Designer: UMAYA

Photography: Huda Lighting



ROZAFA CASTLE
SHKODËR (Albania)

Lighting Designer: Fulvio Baldeschi

Photography: Pietro Savorelli



THE CO99 ART BUILDING & OPR GALLERY
Milan (Italy)


Project: Architect Federico Regazzoni

Lighting Designer:
Light+Arch Consultancy,
Architect Giorgio Colombo

Photography:
Marco Reggi

Envelope_Q | topLED | 24 V DC





Installation with outer casing

C.V. IK10 IP66

	Cct	lm S - lm D	Opt
1,5 W DC			
WH **97170**	**W**	213 - 139	**07** (Asym. Diffused)
GG **97172**	**N**	224 - 154	
DB **81342**			
BG **81341**			


Electronics: **EQ** (pag 669) | Recessed casings: (pag 669)

4 W DC			
WH **76098**	**W**	468 - 296	**07** (Asym. Diffused)
GG **76099**	**N**	490 - 310	
DB **76101**			
BG **76100**			

Electronics: **DE** (pag 669) | Recessed casings: (pag 669)

Envelope_QW | topLED | 24 V DC





Surface installation

C.V. IK10 IP66

	Cct	lm S - lm D	Opt
1,5 W DC			
WH **97167**	**W**	213 - 139	**07** (Asym. Diffused)
GG **97169**	**N**	224 - 154	
DB **81340**			
BG **81339**			


Electronics: **EQ** (pag 669)

4 W DC			
WH **76094**	**W**	468 - 296	**07** (Asym. Diffused)
GG **76095**	**N**	490 - 310	
DB **76097**			
BG **76096**			

Electronics: **DE** (pag 669)

Envelope_W | topLED | 220-240 V AC






Surface installation or with outer casing


IK10 IP65

	Cct	lm S - lm D	Opt
6 W DC - 8 W AC			
WH **81343**	**M**	640 - 423	**07** (Asym. Diffused)
GG **81291**	**W**	669 - 444	
DB **81292**	**N**	708 - 472	
BG **81290**			

Recessed casings: (pag 669)

Envelope_W | topLED | 220-240 V AC





Surface installation or with outer casing

IK10 IP65

	Cct	lm S - lm D	Opt
9,5 W DC - 12 W AC			
WH **81344**	**M**	1281 - 780	**07** (Asym. Diffused)
GG **81294**	**W**	1337 - 818	
DB **81295**	**N**	1415 - 869	
BG **81293**			
16 W DC - 18 W AC			
WH **81512**	**M**	1793 - 1091	**07** (Asym. Diffused)
GG **81510**	**W**	1871 - 1140	
DB **81511**	**N**	1980 - 1212	
BG **81509**			

Recessed casings: (pag 669)

Electronics

BB

89419	89421	C-E200006	C-E200004
ON/OFF	ON/OFF	ON/OFF	DALI/PUSH
1 - 2 art.	3 - 6 art.	6 - 12 art.	5 - 12 art.
74 x 65 x h 27	74 x 65 x h 27	135 x 26 x h 26	125 x 45 x h 30
		35	55


EQ

89488	89179	89359	99332	83333
ON/OFF	ON/OFF	ON/OFF	0/1-10V	DALI/PUSH
1 - 8 art.	1 - 14 art.	1 - 28 art.	1 - 90 art.	1 - 90 art.
100 x 80 x h 31	117 x 92 x h 38	140 x 115 x h 50	158 x 60 x h 35	188 x 68 x h 34
			70	77

DE


89488	89179	99331	99332	83333
ON/OFF	ON/OFF	ON/OFF	0/1-10V	DALI/PUSH
1 - 3 art.	1 - 5 art.	1 - 33 art.	1 - 33 art.	1 - 33 art.
100 x 80 x h 31	117 x 92 x h 38	158 x 60 x h 35	158 x 60 x h 35	188 x 68 x h 34
		70	70	77

Recessed casings




ABS 84336 Recessed casing

suitable for: Envelope_R Ø40 mm
Envelope_1 40x40 mm




ABS 84915 Recessed casing

suitable for: Envelope_R Ø40 mm
Envelope_1 40x40 mm




ABS 99745 Recessed casing

suitable for: Envelope_W 270x125 mm



ABS 99744 Recessed casing

suitable for: Envelope_W 170x168 mm



503 98111 Recessed casing
(standard box mod. 503)

suitable for: Envelope_RW Ø132 mm
Envelope_Q 120x88 mm



White (WH)



Grey (GG)



Black Grey (BG)



Dark Brown (DB)









STEP66

Aluminium body.



Step66 full light
Off



Step66 full light
On



Step66

HIGH VISIBILITY AND BRIGHTNESS STEPLIGHT

Step66 Full Light is the new frontier in step lights. The collection has been expanded with a version providing high visibility and brightness thanks to the halo effect of the translucent frame. The use of a removable support makes installation easier and simpler. The asymmetrical optic projects a light beam with perfectly defined contours; the high visibility Step66 Full Light marks out paths and walkways.

Step family


Step IP40



352

Step66 | powerLED





IK08 IP65 NEW

ID

	Cct	lm S - lm D	Opt
220-240 V AC - 1 W DC - 1,5 W AC			
WH **82746**	**A**	111 - 49	**07** (Asym. Ww)
CH **82745**	**M**	136 - 60	
GG **82747**	**W**	145 - 64	
DB **82748**	**N**	155 - 70	
BB **77633**			

Accessories: (pag 671)


C.C. IK08 IP65 NEW

	Cct	lm S - lm D	Opt
350 mA - 1 W DC			
WH **82742**	**A**	111 - 49	**07** (Asym. Ww)
CH **82741**	**M**	136 - 60	
GG **82743**	**W**	145 - 64	
DB **82744**	**N**	155 - 70	
BB **77634**			

Electronics: **BB** (pag 671) | Accessories: (pag 671)

Step66 | Full Light | powerLED





IK08 IP65

ID


	Cct	lm S - lm D	Opt
220-240 V AC - 1 W DC - 1,5 W AC			
OP **76688**	**A**	111 - 49	**07** (Asym. Ww)
	M	136 - 71	
	W	145 - 75	
	N	155 - 80	

Accessories: (pag 671)

C.C. IK08 IP65

	Cct	lm S - lm D	Opt
350 mA - 1 W DC			
OP **76683**	**A**	111 - 49	**07** (Asym. Ww)
	M	136 - 71	
	W	145 - 75	
	N	155 - 80	

Electronics: **BB** (pag 671) | Accessories: (pag 671)



Step66 full light 1,5W AC 3000K (76688)


ID Driver on board

Electronics

BB

89419	89421	C-E200006	C-E200004
ON/OFF	ON/OFF	ON/OFF	DALI/PUSH
1 - 2 art.	3 - 6 art.	6 - 12 art.	5 - 12 art.
74 x 65 x h 27	74 x 65 x h 27	135 x 26 x h 26	125 x 45 x h 30
		35	55

Recessed casings



POL **83181**

suitable for: Step66

Template for concrete casting

Finishes

WH White
CH Chrome
GG Grey
DB Dark Brown
OP Opaline
POL Polystyrene

Cct

A 2200
M 2700
W 3000
N 4000

OPTIWALL

Aluminium body.
PMMA diffuser (PRO).

Optiwall family

Optiwall



356

A CASCADE OF LIGHT IN A FEW MILLIMETRES OF THICKNESS

The OPTIWALL is an innovative marker light with no casing and only 18 mm thick to contain the light sources. Available in two formats, square and rectangular, and four sizes: 70x70, 158x158, 158x84 and 295x84 mm. It is the ideal luminaire for outdoor walkways or stairs, and it is easy to install. The recessed light sources, thanks to the large flat diffuser underneath, diffuse a copious cascade of light on both horizontal and vertical surfaces. OPTIWALL is certified Bug Rating 0.

BUG Rating 0



White (WH)



Black Grey (BG)



Dark Brown (DB)




Grey (GG)

OPTIWALL PRO



Revolutionary step lights

Optiwall Pro revolutionises the path marker concept: it's not so much a wall light as a light window that uses the microincisions of Optilight Technology™ to reduce dazzle to zero. The light isn't just asymmetrically projected onto the ground, but also provides softer and deeper ambient illumination that highlights surrounding features.



Finishes

WH White
GG Grey
DB Dark Brown
BG Black Grey


Cct


M 2700 **N** 4000
W 3000

Step lights

673

Optiwall | topLED | 24 V DC | 1,2 W DC






	Fin	Cct	lm S - lm D	Opt
C01032	**WH**	**A**	126 - 68	**WW** (Asym. Diffused)
	GG	**M**	151 - 81	
	DB	**W**	158 - 85	
	BG	**N**	167 - 90	

Electronics: **EQ** (pag 675)

Optiwall | topLED | 24 V DC | 3,5 W DC






	Cct	lm S - lm D	Opt
WH **77387**	**M**	454 - 340	**07** (Asym. Diffused)
GG **77388**	**W**	474 - 354	
DB **77389**	**N**	502 - 376	
BG **77390**			

Electronics: **DE** (pag 675)

Optiwall | topLED | 24 V DC | 3,5 W DC






	Cct	lm S - lm D	Opt
WH **77383**	**M**	454 - 368	**07** (Asym. Diffused)
GG **77384**	**W**	474 - 382	
DB **77385**	**N**	502 - 406	
BG **77386**			

Electronics: **DE** (pag 675)

Optiwall | topLED | 24 V DC | 7 W DC






	Cct	lm S - lm D	Opt
WH **77370**	**M**	908 - 715	**07** (Asym. Diffused)
GG **77371**	**W**	948 - 744	
DB **77372**	**N**	1004 - 790	
BG **77373**			

Electronics: **DF** (pag 675)

Optiwall_Pro | V2 | topLED | 24 V DC | 3,5 W DC







	Cct	lm S - lm D	Opt
WH **76760**	**M**	454 - 298	**07** (Asym. Diffused)
GG **76761**	**W**	474 - 309	
DB **76762**	**N**	502 - 329	
BG **76763**			

Electronics: **DE** (pag 675)

Optiwall_Pro | V2 | topLED | 24 V DC | 3,5 W DC







	Cct	lm S - lm D	Opt
WH **76764**	**M**	454 - 318	**07** (Asym. Diffused)
GG **76765**	**W**	474 - 331	
DB **76766**	**N**	502 - 352	
BG **76767**			

Electronics: **DE** (pag 675)

*** BUG rating 0**: Only for the finishes Black Grey (BG) and Dark Brown (DB)

Optiwall_Pro | V2 | topLED | 24 V DC | 7 W DC





	Cct	lm S - lm D	Opt
WH **76768**	**M**	908 - 690	**07** (Asym. Diffused)
GG **76769**	**W**	948 - 717	
DB **76770**	**N**	1004 - 763	
BG **76771**			

Electronics: **DF** (pag 675)

Electronics

DE

89488	89179	99331	99332	83333
ON/OFF	ON/OFF	ON/OFF	0/1-10V	DALI/PUSH
1 - 3 art.	1 - 5 art.	1 - 33 art.	1 - 33 art.	1 - 33 art.
100 x 80 x h 31	117 x 92 x h 38	158 x 60 x h 35	158 x 60 x h 35	188 x 68 x h 34
		70	70	77

EQ

89488	89179	89359	99332	83333
ON/OFF	ON/OFF	ON/OFF	0/1-10V	DALI/PUSH
1 - 8 art.	1 - 14 art.	1 - 28 art.	1 - 90 art.	1 - 90 art.
100 x 80 x h 31	117 x 92 x h 38	140 x 115 x h 50	158 x 60 x h 35	188 x 68 x h 34
			70	77

DF

89179	89359	99331	99332	99722
ON/OFF	ON/OFF	ON/OFF	0/1-10V	DALI
1 - 3 art.	1 - 6 art.	1 - 21 art.	1 - 21 art.	1 - 17 art.
117 x 92 x h 38	140 x 115 x h 50	158 x 60 x h 35	158 x 60 x h 35	191 x 63 x h 38
		70	70	73




CHIM

Nylon body.
AISI 316L stainless steel flange.



Chim | powerLED | 220-240 V AC | 4 W DC - 4,8 W AC






IP66

	Cct	lm S - lm D	Opt
IS **92681**	**M**	466 - 300	**12** (Asym. Ww)
	W	498 - 320	
	N	532 - 342	

Recessed casings: (pag 676)

Recessed casings



PVC **98009** Recessed casings

suitable for: Chim L158x113 mm

Finishes **Cct**

IS Steel **M** 2700 **N** 4000
W 3000





FLOOR GRAZING LIGHTS



PRIVATE VILLA
Bassano Del Grappa (Italy)

Project:
Didonè Comacchio Architects

Photography:
Alberto Sinigaglia



Floor Grazing lights range index

Alcor316

Alcor316_R

684

Alcor316_R1

684

Alcor316_R2

685

Alcor316_R4

685

Alcor316_Q1

685

Alcor316_Q2

686

Alcor316_Q4

686

Alcor316_R1 NEW

687

Alcor316_R2 NEW

687

Alcor316_R4 NEW

687

Alcor316_R1

688

Alcor316_R2

688

Alcor316_R4

688

Alcor

Alcor_R

691

Alcor_R1

691

Alcor_R2

691

Alcor_R4

692

Alcor_R NEW

692

Alcor_R1

692

Alcor_R2

693

Alcor_R4

693

Alcor_R1 Blade

694

Alcor_R2 Blade

694

Astropek

Astropek_1

700

Astropek_2

700

Astropek_4


700


Astropek_1 Blade NEW


700


Astropek_2 Blade NEW

700

Astropek NEW

702

Astropek_1 NEW

702

Astropek_2 NEW

702

Astropek_4 NEW

702

Footpad

Footpad_R

707


Footpad_Q

707

ALCOR316

AISI 316L stainless steel body.
Tempered glass diffuser.

Alcor316_Q lighting effect



Alcor316_R lighting effect



SPECTACULAR LIGHTS TO MARK A PATH

Alcor is a range of extremely compact recessed marker lights, with an IP67 protection rating. For ID versions, the power supply is built into the structure, so they can be connected directly to the power line, making installation easier. The body is made of AISI 316 L steel and they have a load capacity of up to 2000 kg. They are available in two shapes, round or square, with a 180° window, narrow window, 2 windows or 4 windows, which allow you to mark a path with fascinating lighting effects.

ID Driver on board








Alcor316_R | powerLED | 500 mA | 1,5 W DC





2000 kg C.C. IK10 IP67


	Cct	lm S - lm D	Opt
IS **97353**	**M**	199 - 38	**18** (Radial Mono-direc.)
BS **83606**	**W**	213 - 40	
	N	227 - 43	

97353 83606

Electronics: **BC** (pag 689) | Recessed casings: (pag 689)

Alcor316_R | powerLED | 220-240 V AC | 2 W DC - 3 W AC






2000 kg IK10 IP67 ID

	Cct	lm S - lm D	Opt
IS **83558**	**M**	233 - 37	**18** (Radial Mono-direc.)
	W	249 - 40	
	N	266 - 43	

Recessed casings: (pag 689)

Alcor316_R1 | powerLED | 500 mA | 1,5 W DC





2000 kg C.C. IK10 IP67


	Cct	lm S - lm D	Opt
IS **97354**	**M**	199 - 12	**18** (Radial Mono-direc.)
BS **83607**	**W**	213 - 13	
	N	227 - 14	

97354 83607

Electronics: **BC** (pag 689) | Recessed casings: (pag 689)

Alcor316_R1 | powerLED | 220-240 V AC | 2 W DC - 3 W AC





2000 kg IK10 IP67 ID


	Cct	lm S - lm D	Opt
IS **83559**	**M**	233 - 13	**18** (Radial Mono-direc.)
	W	249 - 14	
	N	266 - 15	


Recessed casings: (pag 689)

Finishes **Cct**

IS Steel **M** 2700 **N** 4000
BS Brass **W** 3000

Alcor316_R2 | powerLED | 500 mA | 1,5 W DC





2000 kg | C.C. | IK10 | IP67


	Cct	lm S - lm D	Opt
IS 97355	M	199 - 28	18 (Radial Bi-direc.)
BS 83608	W	213 - 29	
	N	227 - 30	

97355 83608

Electronics: **BC** (pag 689) | Recessed casings: (pag 689)

Alcor316_R2 | powerLED | 220-240 V AC | 2 W DC - 3 W AC






2000 kg | IK10 | IP67 | ID

	Cct	lm S - lm D	Opt
IS 83560	M	233 - 27	18 (Radial Bi-direc.)
	W	249 - 29	
	N	266 - 30	

Recessed casings: (pag 689)

Alcor316_R4 | powerLED | 500 mA | 1,5 W DC





2000 kg | C.C. | IK10 | IP67


	Cct	lm S - lm D	Opt
IS 97356	M	199 - 50	18 (Radial Multi-direc.)
BS 83609	W	213 - 57	
	N	227 - 61	

97356 83609

Electronics: **BC** (pag 689) | Recessed casings: (pag 689)

Alcor316_R4 | powerLED | 220-240 V AC | 2 W DC - 3 W AC






2000 kg | IK10 | IP67 | ID

	Cct	lm S - lm D	Opt
IS 83561	M	233 - 53	18 (Radial Multi-direc.)
	W	249 - 57	
	N	266 - 61	

Recessed casings: (pag 689)

Alcor316_Q1 | powerLED | 500 mA | 1,5 W DC






2000 kg | C.C. | IK10 | IP67


	Cct	lm S - lm D	Opt
IS 81736	M	199 - 20	18 (Radial Mono-direc.)
BS 83610	W	213 - 22	
	N	227 - 23	

81736 83610

Electronics: **BC** (pag 689) | Recessed casings: (pag 689)

Alcor316_Q1 | powerLED | 220-240 V AC | 2 W DC - 3 W AC






2000 kg | IK10 | IP67 | ID

	Cct	lm S - lm D	Opt
IS 83562	M	233 - 21	18 (Radial Mono-direc.)
	W	249 - 23	
	N	266 - 24	

Recessed casings: (pag 689)

Alcor316_Q2 | powerLED | 500 mA | 1,5 W DC






2000 kg


	Cct	lm S - lm D	Opt
IS **81750**	**M**	199 - 40	**18** (Radial Bi-direc.)
BS **83611**	**W**	213 - 43	
	N	227 - 46	

81750 83611

Electronics: **BC** (pag 689) | Recessed casings: (pag 689)

Alcor316_Q2 | powerLED | 220-240 V AC | 2 W DC - 3 W AC





2000 kg


ID

	Cct	lm S - lm D	Opt
IS **83563**	**M**	233 - 40	**18** (Radial Bi-direc.)
	W	249 - 43	
	N	266 - 46	

Recessed casings: (pag 689)

Alcor316_Q4 | powerLED | 500 mA | 1,5 W DC





2000 kg


	Cct	lm S - lm D	Opt
IS **81751**	**M**	199 - 79	**18** (Radial Multi-direc.)
BS **83612**	**W**	213 - 85	
	N	227 - 91	

81751 83612

Electronics: **BC** (pag 689) | Recessed casings: (pag 689)

Alcor316_Q4 | powerLED | 220-240 V AC | 2 W DC - 3 W AC





2000 kg

ID

	Cct	lm S - lm D	Opt
IS **83564**	**M**	233 - 79	**18** (Radial Multi-direc.)
	W	249 - 85	
	N	266 - 91	

Recessed casings: (pag 689)

Finishes


IS Steel
BS Brass

Cct

M 2700 **N** 4000
W 3000

Alcor316_R1 | powerLED | 500 mA | 4,5 W DC






1500 kg C.C. IK10 IP67 NEW

	Fin	Cct	Im S - Im D	Opt
C00324	**IS**	**M**	535 - 33	**RU** (Radial Mono-direc.)
		W	575 - 36	
		N	620 - 38	

Electronics: **BW** (pag 689) | Recessed casings: (pag 689)

Alcor316_R1 | powerLED | 220-240 V | 4,5 W DC - 5,6 W AC






1500 kg IK10 IP67 NEW

	Fin	Cct	Im S - Im D	Opt
C00327	**IS**	**M**	535 - 33	**RU** (Radial Mono-direc.)
		W	575 - 36	
		N	620 - 38	

Recessed casings: (pag 689)

Alcor316_R2 | powerLED | 500 mA | 4,5 W DC






1500 kg C.C. IK10 IP67 NEW

	Fin	Cct	Im S - Im D	Opt
C00325	**IS**	**M**	535 - 66	**RB** (Radial Bi-direc.)
		W	575 - 72	
		N	620 - 78	

Electronics: **BW** (pag 689) | Recessed casings: (pag 689)

Alcor316_R2 | powerLED | 220-240 V | 4,5 W DC - 5,6 W AC







1500 kg IK10 IP67 NEW

	Fin	Cct	Im S - Im D	Opt
C00328	**IS**	**M**	535 - 66	**RB** (Radial Bi-direc.)
		W	575 - 72	
		N	620 - 78	

Recessed casings: (pag 689)

Alcor316_R4 | powerLED | 500 mA | 4,5 W DC






1500 kg C.C. IK10 IP67 NEW

	Fin	Cct	Im S - Im D	Opt
C00326	**IS**	**M**	535 - 79	**RM** (Radial Multi-direc.)
		W	575 - 85	
		N	620 - 92	

Electronics: **BW** (pag 689) | Recessed casings: (pag 689)

Alcor316_R4 | powerLED | 220-240 V | 4,5 W DC - 5,6 W AC






1500 kg IK10 IP67 NEW

	Fin	Cct	Im S - Im D	Opt
C00329	**IS**	**M**	535 - 79	**RM** (Radial Multi-direc.)
		W	575 - 85	
		N	620 - 92	

Recessed casings: (pag 689)

Alcor316_R1 | arrayLED | 350 mA - 6,3 W DC







2500 kg | C.C. | IK10 | IP67

	Fin	Cct	Im S - Im D	Opt
C00718	**SE**	**M**	925 - 49	**RU** (Radial Mono-direc.)
		W	965 - 52	
		N	990 - 53	

Electronics: **BZ** (pag 689) | Recessed casings: (pag 689)

Alcor316_R1 | arrayLED | 220-240 V AC | 4,5 W DC - 6,3 W AC






2500 kg | IK10 | IP67

	Fin	Cct	Im S - Im D	Opt
C00715	**SE**	**M**	646 - 39	**RU** (Radial Mono-direc.)
		W	673 - 42	
		N	711 - 43	

Recessed casings: (pag 689)

Alcor316_R2 | arrayLED | 350 mA - 6,3 W DC






2500 kg | C.C. | IK10 | IP67

	Fin	Cct	Im S - Im D	Opt
C00719	**SE**	**M**	925 - 98	**RB** (Radial Bi-direc.)
		W	965 - 104	
		N	990 - 105	

Electronics: **BZ** (pag 689) | Recessed casings: (pag 689)

Alcor316_R2 | arrayLED | 220-240 V AC | 4,5 W DC - 6,3 W AC






2500 kg | IK10 | IP67

	Fin	Cct	Im S - Im D	Opt
C00716	**SE**	**M**	646 - 78	**RB** (Radial Bi-direc.)
		W	673 - 83	
		N	711 - 86	

Recessed casings: (pag 689)

Alcor316_R4 | arrayLED | 350 mA - 6,3 W DC






2500 kg | C.C. | IK10 | IP67

	Fin	Cct	Im S - Im D	Opt
C00720	**SE**	**M**	925 - 139	**RM** (Radial Multi-direc.)
		W	965 - 145	
		N	990 - 149	

Electronics: **BZ** (pag 689) | Recessed casings: (pag 689)

Alcor316_R4 | arrayLED | 220-240 V AC | 4,5 W DC - 6,3 W AC





2500 kg | IK10 | IP67

	Fin	Cct	Im S - Im D	Opt
C00717	**SE**	**M**	646 - 105	**RM** (Radial Multi-direc.)
		W	673 - 110	
		N	711 - 115	

Recessed casings: (pag 689)

Finishes

Stainless Steel

Cct

M 2700 **N** 4000
W 3000

Recessed casings



ABS 84918 Recessed casings

suitable for: Alcor316_R/R1/R2/R4 - Ø40 h28/65
Alcor316_Q1/Q2/Q4 - L40x40 h28/65



ABS 84341 Recessed casings

suitable for: Alcor316_R1/R2/R4- Ø120 h102



ABS 84936 Recessed casings

suitable for: Alcor316_R1/R2/R4 - Ø70 h82



ABS 84935 Recessed casings

suitable for: Alcor316_R1/R2/R4 - Ø70 h126

Electronics

BC

89422	89423	C-E200007	C-E200003
ON/OFF	ON/OFF	ON/OFF	DALI/PUSH
1 - 2 art.	2 - 3 art.	3 - 6 art.	5 - 12 art.
74 x 65 x h 27	74 x 65 x h 27	135 x 26 x h 26	125 x 45 x h 30
		35	55

BW


C-E200007	99185	C-E200003
ON/OFF	ON/OFF	DALI/PUSH
1 - 2 art.	2 - 4 art.	2 - 4 art.
135 x 26 x h 26	117 x 92 x h 38	125 x 45 x h 30
35		55

BZ

89421	C-E200006	C-E200004
ON/OFF	ON/OFF	DALI/PUSH
1 art.	1 - 2 art.	1 - 2 art.
74 x 65 x h 27	135 x 26 x h 26	125 x 45 x h 30
	35	55

ALCOR

Aluminium body.
Tempered glass diffuser.




Alcor lighting effect



Alcor_R | V2 | powerLED | 500 mA | 4,5 W DC






1500 kg | C.C. | IK10 | IP67

	Cct	lm S - lm D	Opt
GG 76862	M	535 - 79	18 (Radial Mono-direc.)
	W	575 - 84	
	N	620 - 91	

Electronics: **BW** (pag 695) | Recessed casings: (pag 695)

Alcor_R | V2 | powerLED | 220-240 V AC | 4,5 W DC - 5,6 W AC






1500 kg | IK10 | IP67

	Cct	lm S - lm D	Opt
GG 76866	M	535 - 79	18 (Radial Mono-direc.)
	W	575 - 84	
	N	620 - 91	

Recessed casings: (pag 695)

Alcor_R1 | V2 | powerLED | 500 mA | 4,5 W DC






1500 kg | C.C. | IK10 | IP67

	Cct	lm S - lm D	Opt
GG 76863	M	535 - 51	18 (Radial Mono-direc.)
	W	575 - 55	
	N	620 - 59	

Electronics: **BW** (pag 695) | Recessed casings: (pag 695)

Alcor_R1 | V2 | powerLED | 220-240 V AC | 4,5 W DC - 5,6 W AC






1500 kg | IK10 | IP67

	Cct	lm S - lm D	Opt
GG 76867	M	535 - 51	18 (Radial Mono-direc.)
	W	575 - 55	
	N	620 - 59	

Recessed casings: (pag 695)

Alcor_R2 | V2 | powerLED | 500 mA | 4,5 W DC






1500 kg | C.C. | IK10 | IP67

	Cct	lm S - lm D	Opt
GG 76864	M	535 - 101	18 (Radial Bi-direc.)
	W	575 - 109	
	N	620 - 117	

Electronics: **BW** (pag 695) | Recessed casings: (pag 695)

Alcor_R2 | V2 | powerLED | 220-240 V AC | 4,5 W DC - 5,6 W AC







1500 kg | IK10 | IP67

	Cct	lm S - lm D	Opt
GG 76868	M	535 - 101	18 (Radial Bi-direc.)
	W	575 - 109	
	N	620 - 117	

Recessed casings: (pag 695)

Alcor_R4 | V2 | powerLED | 500 mA | 4,5 W DC






1500 kg | III | C.C. | IK10 | IP67

	Cct	lm S - lm D	Opt
GG 76865	M	535 - 120	18 (Radial Multi-direc.)
	W	575 - 128	
	N	620 - 138	

Electronics: **BW** (pag 695) | Recessed casings: (pag 695)

Alcor_R4 | V2 | powerLED | 220-240 V AC | 4,5 W DC - 5,6 W AC






1500 kg | IK10 | IP67

	Cct	lm S - lm D	Opt
GG 76869	M	535 - 120	18 (Radial Multi-direc.)
	W	575 - 128	
	N	620 - 138	

Recessed casings: (pag 695)

Alcor_R | arrayLED | 350 mA | 6,3 W DC






III | C.C. | IK10 | IP67 | NEW

	Cct	lm S - lm D	Opt
GG 76689	M	925 - 118	18 (Radial Mono-direc.)
	W	965 - 124	
	N	990 - 127	

Electronics: **BZ** (pag 695) | Recessed casings: (pag 695)

Alcor_R | arrayLED | 220-240 V AC | 6,3 W DC 8,2 W AC






IK10 | IP67 | NEW

	Cct	lm S - lm D	Opt
GG 76693	M	925 - 118	18 (Radial Mono-direc.)
	W	965 - 124	
	N	990 - 127	

Recessed casings: (pag 695)

Alcor_R1 | arrayLED | 350 mA | 6,3 W DC






2500 kg | III | C.C. | IK10 | IP67

	Cct	lm S - lm D	Opt
GG 76690	M	925 - 73	18 (Radial Mono-direc.)
	W	965 - 76	
	N	990 - 78	

Electronics: **BZ** (pag 695) | Recessed casings: (pag 695)

Alcor_R1 | V2 | arrayLED | 220-240 V AC | 6,3 W DC 8,2 W AC





2500 kg | IK10 | IP67


	Cct	lm S - lm D	Opt
GG 76694	M	925 - 73	18 (Radial Mono-direc.)
	W	965 - 76	
	N	990 - 78	


Recessed casings: (pag 695)

Finishes **Cct**

GG Grey **M** 2700 **N** 4000
W 3000

Alcor_R2 | arrayLED | 350 mA | 6,3 W DC







2500 kg

	Cct	lm S - lm D	Opt
GG **76691**	**M**	925 - 145	**18** (Radial Bi-direc.)
	W	965 - 151	
	N	990 - 155	

Electronics: **BZ** (pag 695) | Recessed casings: (pag 695)

Alcor_R2 | V2 | arrayLED | 220-240 V AC | 6,3 W DC 8,2 W AC







2500 kg

	Cct	lm S - lm D	Opt
GG **76695**	**M**	925 - 145	**18** (Radial Bi-direc.)
	W	965 - 151	
	N	990 - 155	

Recessed casings: (pag 695)

Alcor_R4 | arrayLED | 350 mA | 6,3 W DC







2500 kg

	Cct	lm S - lm D	Opt
GG **76692**	**M**	925 - 138	**18** (Radial Multi-direc.)
	W	965 - 144	
	N	990 - 147	

Electronics: **BZ** (pag 695) | Recessed casings: (pag 695)

Alcor_R4 | V2 | arrayLED | 220-240 V AC | 6,3 W DC 8,2 W AC






2500 kg

	Cct	lm S - lm D	Opt
GG **76696**	**M**	925 - 138	**18** (Radial Multi-direc.)
	W	965 - 144	
	N	990 - 147	

Recessed casings: (pag 695)

Alcor_R1 Blade | powerLED | 220-240 V | 2 W DC - 2,5 W AC






2500 kg IK10 IP67 05 12

	Cct	lm S - lm D	Opt
GG **83523**	**M**	233 - 46	**05** (Narrow Mono-direc.)
	W	249 - 50	**12** (Radial Mono-direc.)
	N	266 - 53	

Recessed casings: (pag 695)

Alcor_R1 Blade | powerLED | 220-240 V | 4 W DC - 4,5 W AC







2500 kg IK10 IP67 05 12

	Cct	lm S - lm D	Opt
GG **82639**	**M**	490 - 94	**05** (Narrow Mono-direc.)
	W	490 - 94	**12** (Radial Mono-direc.)
	N	529 - 101	

Recessed casings: (pag 695)

Alcor_R2 Blade | powerLED | 220-240 V | 4 W DC - 4,5 W AC







2500 kg IK10 IP67 05 12

	Cct	lm S - lm D	Opt
GG **83521**	**M**	438 - 101	**05** (Narrow Bi-direc.)
	W	466 - 107	**12** (Radial Bi-direc.)
	N	498 - 114	

Recessed casings: (pag 695)

Alcor_R2 Blade | powerLED | 220-240 V | 8 W DC - 9 W AC






2500 kg IK10 IP67 05 12

	Cct	lm S - lm D	Opt
GG **82640**	**M**	980 - 188	**05** (Narrow Bi-direc.)
	W	980 - 188	**12** (Radial Bi-direc.)
	N	1058 - 203	

Recessed casings: (pag 695)

Recessed casings



ABS **84936** Recessed casings

suitable for: Alcor_R/R1/R2/R4 - Ø70 h65



ABS **84935** Recessed casings

suitable for: Alcor_R/R1/R2/R4 - Ø70 h106



ABS **98121** Recessed casings

suitable for: Alcor_R/R1/R2/R4 - Ø120 h112



ABS **84900** Recessed casings

suitable for: Alcor_R1/R2 Blade - Ø120 h120

Electronics

BZ

89421
ON/OFF
1 art.
74 x 65 x h 27

C-E200006
ON/OFF
1 - 2 art.
135 x 26 x h 26
35

C-E200004
DALI/PUSH
1 - 2 art.
125 x 45 x h 30
55

BW

C-E200007
ON/OFF
1 - 2 art.
135 x 26 x h 26
35

99185
ON/OFF
2 - 4 art.
117 x 92 x h 38

C-E200003
DALI/PUSH
2 - 4 art.
125 x 45 x h 30
55

VIDA BEACH RESORT MARASSI AL BAHRAIN
MANAMA (Bahrain)





ASTROPEK

Aluminium body.
Tempered glass diffuser.



Astropek Blade lighting effect



Astropek lighting effect




ONE, TWO OR FOUR: SUITABLE FOR ANY PATH

Astropek has been revamped to expand its installation potential. Thanks to the special base, it can be placed in even the most sensitive and complex settings, such as historical town centres. The innovative truncated, tapered base makes it easier and faster to position while the cabling does not require an outer casing. The fixture can be connected directly to the mains power supply and is designed with a LED light source for high-efficiency and brightness. Astropek can be driven on and withstand weights of up to 2,500 kg. It is available with one, two or four emission uplights.




Astropek_1



Astropek



Astropek_2



Astropek_4

Astropek_1 | powerLED




2000 kg | III | C.C. | IK10 | IP67

Fin	Cct	lm S - lm D	Opt
500 mA - 4,5 W DC			
C00270 GG	**M**	535 - 51	**RU** (Radial Mono-direc.)
	W	575 - 55	
	N	620 - 59	

Electronics: **BW** (pag 703)

Astropek_2 | powerLED




2000 kg | III | C.C. | IK10 | IP67

Fin	Cct	lm S - lm D	Opt
500 mA - 4,5 W DC			
C00279 GG	**M**	535 - 101	**RB** (Radial Bi-direc.)
	W	575 - 109	
	N	620 - 117	

Electronics: **BW** (pag 703)

Astropek_4 | powerLED




2000 kg | III | C.C. | IK10 | IP67

Fin	Cct	lm S - lm D	Opt
500 mA - 4,5 W DC			
C00300 GG	**M**	535 - 120	**RM** (Radial Multi-direc.)
	W	575 - 128	
	N	620 - 138	

Electronics: **BW** (pag 703)

Astropek_1 Blade | V2 | powerLED



2500 kg | III | C.C. | IK10 | IP67 | NEW | 05 | 12

Cct	lm S - lm D	Opt
630 mA - 2 W DC		
GG **83524**	**M** 233 - 51	**05** (Narrow Mono-direc.)
	W 249 - 54	**12** (Radial Mono-direc.)
	N 266 - 58	

Electronics: **BD** (pag 703)

350 mA - 4 W DC		
GG **82637**	**M** 490 - 95	**05** (Narrow Mono-direc.)
	W 490 - 95	**12** (Radial Mono-direc.)
	N 529 - 102	

Electronics: **BE** (pag 703)

Astropek_2 Blade | V2 | powerLED



2500 kg | III | C.C. | IK10 | IP67 | NEW | 05 | 12

Cct	lm S - lm D	Opt
630 mA - 4 W DC		
GG **83522**	**M** 466 - 102	**05** (Narrow Bi-direc.)
	W 498 - 108	**12** (Radial Bi-direc.)
	N 532 - 115	

Electronics: **BP** (pag 703)


350 mA - 8 W DC		
GG **82638**	**M** 980 - 189	**05** (Narrow Bi-direc.)
	W 980 - 189	**12** (Radial Bi-direc.)
	N 1058 - 204	

Electronics: **BY** (pag 703)



Astropek | V2 | arrayLED-direct | 220-240 V AC






IK10 IP67 NEW **LED-DIRECT**

	Cct	lm S - lm D	Opt
7 W AC			
GG **76697**	**W**	865 - 116	**12** (Radial Mono-direc.)
	N	870 - 117	

Astropek_1 | V2 | arrayLED-direct | 220-240 V AC






2500 kg IK10 IP67 NEW **LED-DIRECT**

	Cct	lm S - lm D	Opt
7 W AC			
GG **76698**	**W**	865 - 74	**12** (Radial Mono-direc.)
	N	870 - 75	

Astropek_2 | V2 | arrayLED-direct | 220-240 V AC






2500 kg IK10 IP67 NEW **LED-DIRECT**

	Cct	lm S - lm D	Opt
7 W AC			
GG **76699**	**W**	865 - 148	**12** (Radial Bi-direc.)
	N	870 - 149	

Astropek_4 | V2 | arrayLED-direct | 220-240 V AC





2500 kg IK10 IP67 NEW **LED-DIRECT**

	Cct	lm S - lm D	Opt
7 W AC			
GG **76700**	**W**	865 - 158	**12** (Radial Multi-direc.)
	N	870 - 159	



Electronics

BD

89420
ON/OFF
1 - 2 art.
74 x 65 x h 27

C-E200008
ON/OFF
3 - 6 art.
135 x 26 x h 26
35

99186
ON/OFF
6 - 12 art.
117 x 92 x h 38

C-E200002
DALI/PUSH
5 - 12 art.
125 x 45 x h 30
55

BP

89420
ON/OFF
1 art.
74 x 65 x h 27

C-E200008
ON/OFF
2 - 3 art.
135 x 26 x h 26
35

99186
ON/OFF
3 - 6 art.
117 x 92 x h 38

C-E200002
DALI/PUSH
3 - 6 art.
125 x 45 x h 30
55

BY

C-E200006
ON/OFF
1 art.
135 x 26 x h 26
35

C-E200004
DALI/PUSH
1 art.
125 x 45 x h 30
55

BE

89421
ON/OFF
1 art.
74 x 65 x h 27

C-E200006
ON/OFF
2 - 3 art.
135 x 26 x h 26
35

C-E200004
DALI/PUSH
2 - 3 art.
125 x 45 x h 30
55

BW

C-E200007
ON/OFF
1 - 2 art.
135 x 26 x h 26
35

99185
ON/OFF
2 - 4 art.
117 x 92 x h 38

C-E200003
DALI/PUSH
2 - 4 art.
125 x 45 x h 30
55


FOOTPAD



FOOTPAD IS THE ULTRA-FLAT SURFACE MARKER LIGHT WITH 360° LIGHTING

A series of IP67 floor-mounted luminaires, characterised by an ultra-flat AISI 316 stainless steel structure, with a projection of just 20 mm. Available in two shapes and two electrifications, it is designed for 360° grazing lighting above the ground, suitable for illuminating passageways and at the same time creating striking lighting effects. Footpad is installed directly on the surface without the need for casings; the strong and reliable materials guarantee an IK10 impact resistance rating.






Footpad 5W (77451W00)



Footpad_R | V2 | arrayLED





2000 kg | IK10 | IP67

	Cct	lm S - lm D	Opt
C.C. - 500 mA - 4,5 W DC			
SE **77453**	**M**	646 - 200	**00** (Radial Diffused)
	W	673 - 208	
	N	711 - 220	

Electronics: **BW** (pag 707)


C.V. - 24 V DC - 5 W DC

SE **77451**	**M**	646 - 200	**00** (Radial Diffused)
	W	673 - 208	
	N	711 - 220	

Electronics: **DB** (pag 707)

Footpad_Q | V2 | arrayLED





2000 kg | IK10 | IP67


	Cct	lm S - lm D	Opt
C.C. - 500 mA - 4,5 W DC			
SE **77454**	**M**	646 - 201	**00** (Radial Diffused)
	W	673 - 209	
	N	711 - 221	

Electronics: **BW** (pag 707)

C.V. - 24 V DC - 5 W DC

SE **77452**	**M**	646 - 201	**00** (Radial Diffused)
	W	673 - 209	
	N	711 - 221	

Electronics: **DB** (pag 707)



* Distance to be maintained before cable bending

Position of installation hole for cable and cable gland

The Footpad_R and Footpad_Q models are secured to the floor using special tamper resistant screws



Electronics

DB

89488	89179	89359	99660	83042	+ driver 24V DC	
					99331	99786
ON/OFF	ON/OFF	ON/OFF	Dimmer	Dimmer DALI/PUSH	150W	240W
1 - 2 art.	1 - 4 art.	1 - 9 art.	DALI - 0/1-10V	0/1-10V	1-21 art.	1-33 art.
80 x 100 x h 31	92 x 117 x h 38	115 x 140 x h 50	149 x 37 x h 31	164 x 38 x h 25		
48			48	45	70	81

BW

C-E200007	99185	C-E200003
ON/OFF	ON/OFF	DALI/PUSH
1 - 2 art.	2 - 4 art.	2 - 4 art.
135 x 26 x h 26	117 x 92 x h 38	125 x 45 x h 30
35		55

Finishes

SE Stainless Steel

Cct

M 2700 **N** 4000
W 3000




INGROUND

RESIDENTIAL HOME
Empordà (Spain)

Interior Design: A&P Interiorismo
(Loles Armengol y Eva Pallarés)

Project:
Studio Gama

Lighting Designer:
Vié Il·Luminació
(@vieluxbcn) Anna Vié

Photography:
Jordi Anguera



Inground range index

Beret

Beret_R

714

Beret_X

714

Beret_2R

714

Beret_Q

715

Beret_2Q

715

Orma

Orma_I

719-722

Orma_IJ

719-723

Orma_IL

719-723

Orma_A

724-726

Orma_AJ

724-727

Orma_AL

724-727

Orma_F

730-733

Orma_FJ

731-733

Orma_FL

730-733

Orma_FO

734

Orma_Q
NEW

735-736

Orma_QJ

735-736

Orma_QL
NEW

735-737

Orma_QF
NEW

738-740

Orma_QFJ

739-740

Orma_QFL
NEW

738-741

Suelo

Suelo_R
NEW

751-758

Suelo_R Pro

751-756

Suelo_RJ
NEW

753, 759

Suelo_RJ Pro

756

Suelo_RF
NEW

760

Suelo_RFJ
NEW

761

Suelo_RX
NEW

765-772

Suelo_RX Pro

764-767

Suelo_RXJ
NEW

767-772

Suelo_RXF
NEW

770-773

Suelo_RXFJ
NEW

771-773

Suelo_Brass

774

Suelo316

Suelo316_R
NEW

779

Suelo316_RJ
NEW

779

Suelo316_RX
NEW

779-780

Suelo316_RXJ
NEW

780

Suelo316_RXF
NEW

781

Suelo316_RXFJ
NEW

781

BERET

Brass or aluminium body.
Brass or steel flange.







ADAPTABLE IN ANY CONTEXT

Beret is an extremely compact recessed up-light, with an IP67 protection rating. For ID versions, the power supply is integrated into the structure and can be connected directly to the power line. It is available in two shapes, round and square, with a flange of just 35 mm, and in six different finishes: white, grey, chrome, brushed nickel, AISI 316 L steel and natural brass, to offer unprecedented compositional possibilities and five types of distribution angles.

"Steel" version (IS): body and flange made of AISI 316 L steel.

ID Driver on board






Beret_X Anti-glaring Brass (BS)



Beret_R | powerLED | 350 mA | 1 W DC







	Cct	Im S - Im D	Opt
WH 92065	M	145 - 87	15 (21°)
GG 92061	W	154 - 98	30 (26°)
CH 92066	N	165 - 105	60 (57°)
NK 92067			00 (Diffused)
IS 92068			
BS 81469			

Electronics: **BB** (pag 715) | Recessed casing: (pag 714)

Beret_X Anti-glaring | powerLED | 350 mA | 1 W DC






	Cct	Im S - Im D	Opt
WH 97800	M	145 - 34	15 (21°)
GG 97801	W	154 - 37	30 (26°)
CH 97797	N	165 - 39	60 (57°)
NK 97798			
IS 97799			
BS 81471			

Electronics: **BB** (pag 715) | Recessed casing: (pag 714)

Beret_2R | powerLED | 630 mA 2 W DC | 1000 mA 3 W DC






	Fin	Cct	Im S - Im D 2 W	Im S - Im D 3 W	Opt
C01052	CH	M	233 - 132	417 - 238	SP (10°)
	NK	W	249 - 141	432 - 246	FL (21°)
	IS	N	266 - 150	642 - 264	ML (32°)
	BS				WF (57°)
					DI (Diffused)

Electronics: 2W IP67 **BD** - 3W IP40 **FQ** (pag 715) | Recessed casing: (pag 714)

Beret_2R | powerLED | 220-240 V AC | 1,6 W DC - 3 W AC






	Cct	Im S - Im D	Opt
WH 83568	M	233 - 132	08 (10°)
GG 83569	W	249 - 149	15 (21°)
CH 83565	N	266 - 159	30 (26°)
NK 83566			60 (57°)
IS 83567			00 (Diffused)
BS 83570			


Recessed casing: (pag 714)

Recessed casings




ABS **84336** Recessed casings

suitable for: Beret_R /_X Ø35 h28
Beret_Q 35x35 h28



ABS **84918** Recessed casings

suitable for: Beret_2R Ø35 h44/74
Beret_2Q 35x35 h44/74




ABS **84915** Recessed casings

suitable for: Beret_R /_X Ø35 h28
Beret_Q 35x35 h28

Beret_Q | powerLED | 350 mA | 1 W DC






	Cct	Im S - Im D	Opt
WH 92088	M	145 - 87	15 (21°)
GG 92092	W	154 - 98	30 (26°)
CH 92069	N	165 - 105	60 (57°)
NK 92076			00 (Diffused)
IS 92077			

Electronics: **BB** (pag 715) | Recessed casing: (pag 714)

Beret_2Q | powerLED | 630 mA 2 W DC | 1000 mA 3 W DC






	Fin	Cct	Im S - Im D 2 W	Im S - Im D 3 W	Opt
C01054	CH	M	233 - 132	417 - 238	SP (10°)
	NK	W	249 - 141	432 - 246	FL (21°)
	IS	N	266 - 150	642 - 264	ML (32°)
					WF (57°)
					DI (Diffused)

Electronics: 2W IP67 **BD** - 3W IP40 **FQ** (pag 715) | Recessed casing: (pag 714)

Beret_2Q | powerLED | 630 mA 2 W DC | 1000 mA 3 W DC






	Fin	Cct	Im S - Im D 2 W	Im S - Im D 3 W	Opt
C01053	CH	M	233 - 132	417 - 238	SP (10°)
	NK	W	249 - 141	432 - 246	FL (21°)
	IS	N	266 - 150	642 - 264	ML (32°)
					WF (57°)
					DI (Diffused)

Electronics: 2W IP67 **BD** - 3W IP40 **FQ** (pag 715) | Recessed casing: (pag 714)

Beret_2Q | powerLED | 220-240 V AC | 1,6 W DC - 3 W AC





	Cct	Im S - Im D	Opt
WH 83708	M	233 - 132	08 (10°)
GG 83709	W	249 - 149	15 (21°)
CH 83705	N	266 - 159	30 (26°)
NK 83706			60 (57°)
IS 83707			00 (Diffused)
BS 83710			

Recessed casing: (pag 714)

Electronics

BB

89419	89421	C-E200006	C-E200004
ON/OFF	ON/OFF	ON/OFF	DALI/PUSH
1 - 2 art.	3 - 6 art.	6 - 12 art.	5 - 12 art.
74 x 65 x h 27	74 x 65 x h 27	135 x 26 x h 26	125 x 45 x h 30
		35	55

FQ IP40

C-E100046	C-E100047	C-E100033	C-E100034
ON/OFF	DALI	ON/OFF	DALI/PUSH
1 - 6 art.	1 - 3 art.	4 - 12 art.	4 - 12 art.
130 x 38 x h 28	140 x 36 x h 20	138 x 44 x h 23	138 x 44 x h 23
48	40	50	50

BD IP67

89420	C-E200008	99186	C-E200002
ON/OFF	ON/OFF	ON/OFF	DALI/PUSH
1 - 2 art.	3 - 6 art.	6 - 12 art.	5 - 12 art.
74 x 65 x h 27	135 x 26 x h 26	117 x 92 x h 38	125 x 45 x h 30
	35		55

Finishes

WH White CH Chrome IS Steel
GG Grey NK Nickel BS Brass

Cct

M 2700 **N** 4000
W 3000

ORMA

Aluminium body. AISI 316L stainless steel flange.
Extra-clear tempered glass diffuser.




ALL THE TECHNOLOGY COMBINED IN 51 MILLIMETRES

Vast range
Orma is a complete recess-mounted family with compact sizes, and sturdy, reliable materials with high grades of protection: temporary IK10 and IP68, ideal for tight installation spaces. In addition to the embossed steel flange, the range is enriched by the new Brass finish. The recess-mounted steel flange is completed by the brand new version with an all-glass front flush with the floor and a path-marker with concentric optics. The swinging versions can also be easily and quickly directed using a flat screwdriver on the specific screw, without having to open the lamp body and consequently taking the risk of compromising the waterproof seal. Orma was conceived with a unique application versatility which provides the designer with a vast range of possible shapes, finish and optics combinations. Flush, all-glass or in metal, Orma can adapt to any setting, even the most unusual one.



ORMA & ORMA_Q ADJUSTABLE

Which can be easily adjusted using a slotted screwdriver on the relevant screw, the optic group can be angled from -20°/+20°






Orma family

Orma_C _CJ	Orma_QC _QCJ	Orma_AJ _IJ	Orma_Q _QF	Orma Blade_AB _IB
				
440-442	444-445	659	660	793

Installation with swing flange (I / Q collection)



_I / _IJ Pag 719-722

W 4-5-7-8-9-11,5-12-13
mm **Ø 64-97-138**

_IL Pag 719-723

W 1-1,5-2-3-4-5-7
mm **Ø 64-97-138**

_IB Blade Pag 789

W 8-9
mm **Ø 97**



_Q / _QJ Pag 735-736

W 4-5-8-9
mm ☐ **85-116**

Opt **N.Spot-Spot-Flood-M.Flood M.W.Flood-W.Flood Elliptic Flood-Diffused**
Cct 2700-3000-4000-RGBW
Acc. HC-DL
Elec. On/Off-0/1-10V-DALI-DMX
Col. SA BM

_QL Pag 735-737


W 1,5-2-2,5-3
mm ☐ **85-116**

Opt **Diffused**
Cct 2700-3000-4000-RGBW
Acc.
Elec. On/Off-0/1-10V-DALI
Col. SA

_Q Blade Pag 790

W 8-9
mm ☐ **116**

Opt **Blade**
Cct 2700-3000-4000-RGBW
Acc.
Elec. On/Off-0/1-10V-DALI
Col. SA



Installation with flush flange (A collection)



_A / _AJ Pag 724-727

W 4-5-8-9-12-13
mm **Ø 54-85-125**
Opt **Spot-Flood-M.Flood M.W.Flood-W.Flood**
Cct 2700-3000-4000-RGBW
Acc. HC-DL
Elec. On/Off-DALI/PUSH-DMX
Col. SA

_AL Pag 724-727

W 1-1,5-2-3-4-4,5
mm **Ø 54-85-125**
Opt **Diffused**
Cct 2700-3000-4000
Acc. HC-DL
Elec. On/Off-0/1-10V-DALI
Col. SA

_AB Blade Pag 789

W 8-9
mm **Ø 85**
Opt **Blade**
Cct 2700-3000-4000
Acc.
Elec. On/Off-0/1-10V-DALI
Col. SA



Frameless installation (F / QF collection)



_F / _FJ Pag 730-733


W 1-1,5-4-5-8-9-12-13
mm **Ø 22,5-56-87-127**
Opt **Spot-Flood-M.Flood M.W.Flood-W.Flood**
Cct 2700-3000-4000-RGBW
Acc. HC-DL
Elec. On/Off-0/1-10V-DALI
Col. GA

_FL Pag 730-733

W 1-1,5-2-3-4-5
mm **Ø 22,5-56-87-127**
Opt **Diffused**
Cct 2700-3000-4000-RGBW
Acc.
Elec. On/Off-0/1-10V-DALI
Col. GA

_FO Pag 734

W 1-1,5-2-3-4-5
mm **Ø 42-56-87-127**
Opt **Diffused**
Cct 2700-3000-4000
Acc.
Elec. On/Off-DALI/PUSH
Col. WH BB GG



_QF / _QFJ Pag 738-740

W 2-2,5-4-5-8-9
mm ☐ **36-60-90**
Opt **Spot-Flood-M.Flood M.W.Flood-W.Flood**
Cct 2700-3000-4000-RGBW
Acc. HC-DL
Elec. On/Off-0/1-10V-DALI
Col. GA

_QFL Pag 738-741

W 1-1,5-2-2,5-3
mm ☐ **36-60-90**
Opt **Diffused**
Cct 2700-3000-4000-RGBW
Acc.
Elec. On/Off-0/1-10V-DALI
Col. GA


_QF Blade Pag 790

W 8-9
mm ☐ **90**
Opt **Blade**
Cct 2700-3000-4000-RGBW
Acc.
Elec. On/Off-0/1-10V-DALI
Col. GA



Orma_I | powerLED





2000 kg

		Cct	Im S - Im D	Opt
C.C. - 350 mA - 4 W DC				
SA **80582**		**M**	490 - 270	**15** (22°)
		W	490 - 270	**30** (29°)
		N	529 - 292	**60** (49°)
				25 (17°x 38°)
SA **80583**	HC	**M**	490 - 186	**15** (20°)
		W	490 - 186	**30** (25°)
		N	529 - 201	**60** (37°)
SA **80584**	DL	**M**	490 - 193	**15** (22°)
		W	490 - 193	**30** (30°)
		N	529 - 208	**60** (55°)


Electronics: **BE** (pag 744) | Recessed casing: (pag 742-743)

C.V. - 24 V DC - 5 W DC				
SA **80585**		**M**	490 - 270	**15** (22°)
		W	490 - 270	**30** (29°)
		N	529 - 292	**60** (49°)
				25
SA **80586**	HC	**M**	490 - 186	**15** (20°)
		W	490 - 186	**30** (25°)
		N	529 - 201	**60** (37°)
SA **80587**	DL	**M**	490 - 193	**15** (22°)
		W	490 - 193	**30** (30°)
		N	529 - 208	**60** (55°)

Electronics: **DB** (pag 744) | Recessed casing: (pag 742-743)

Orma_IJ | powerLED





2000 kg


		Cct	Im S - Im D	Opt
C.C. - 350 mA - 4 W DC				
SA **81199**		**M**	490 - 270	**15** (22°)
BM **82521**		**W**	490 - 270	**30** (29°)
		N	529 - 292	**60** (49°)


Electronics: **BE** (pag 744) | Recessed casing: (pag 742-743)

C.V. - 24 V DC - 5 W DC				
SA **81200**		**M**	490 - 270	**15** (22°)
BM **82522**		**W**	490 - 270	**30** (29°)
		N	529 - 292	**60** (49°)

Electronics: **DB** (pag 744) | Recessed casing: (pag 742-743)

Orma_IL | powerLED





2000 kg


		Cct	Im S - Im D	Opt
C.C. - 350 mA - 1 W DC				
SA **81211**		**M**	145 - 17	**00** (Diffused)
		W	154 - 19	
		N	165 - 21	


Electronics: **BB** (pag 744) | Recessed casing: (pag 742-743)

C.V. - 24 V DC - 1,5 W DC				
SA **81212**		**M**	145 - 17	**00** (Diffused)
		W	154 - 19	
		N	165 - 21	

Electronics: **DI** (pag 744) | Recessed casing: (pag 742-743)

Orma_I | arrayLED





		Cct	Im S - Im D	Opt
C.C. - 220 mA - 8 W DC				
SA **80588**		**M**	1132 - 893	**15** (15°)
		W	1182 - 933	**30** (32°)
		N	1212 - 956	**60** (61°)
SA **80589**	HC	**M**	1132 - 644	**15** (15°)
		W	1182 - 673	**30** (27°)
		N	1212 - 690	**60** (49°)
SA **80590**	DL	**M**	1132 - 598	**15** (16°)
		W	1182 - 624	**30** (29°)
		N	1212 - 640	**60** (53°)

Electronics: **BF** (pag 744) | Recessed casing: (pag 742-743)


		Cct	Im S - Im D	Opt
C.V. - 24 V DC - 9 W DC				
SA **81172**		**M**	1265 - 998	**15** (15°)
		W	1320 - 1041	**30** (32°)
		N	1354 - 1068	**60** (61°)
SA **81173**	HC	**M**	1265 - 719	**15** (15°)
		W	1320 - 750	**30** (27°)
		N	1354 - 769	**60** (49°)
SA **81174**	DL	**M**	1265 - 668	**15** (16°)
		W	1320 - 697	**30** (29°)
		N	1354 - 715	**60** (53°)


Electronics: **DC** (pag 744) | Recessed casing: (pag 742-743)

	Cct	Opt
powerLED - C.C. - 630 mA - 8 W DC		
SA **81321**	**V** RGBW (3000 K)	**06** (7°÷ 9°)
	Q RGBW (4000 K)	**15** (10°÷ 19°)
		45 (40°÷ 49°)
		00 (Diffused)

Electronics: **CF** (pag 744) | Recessed casing and cables: (pag 742-744)

Orma_I | arrayLED-Direct | 220-240 V AC





LED-DIRECT


		Cct	Im S - Im D	Opt
7 W AC				
SA **76080**		**W**	865 - 560	**15** (18°)
		N	870 - 561	**30** (33°)
				60 (56°)


Recessed casing: (pag 742-743)



Orma_I 220 V-240 V (direct)
The Orma family has evolved, presenting a luminaire with an extremely small fixture, just 51 millimetres thick, which can be directly connected to the mains without the need for external power sources, allowing easier and faster installation. Its performance remains unaltered as do the materials used, all sturdy and reliable.

Orma_IJ | arrayLED






		Cct	lm S - lm D	Opt
C.C. - 220 mA - 8 W DC				
SA **81201**		**M**	1132 - 892	**15** (15°)
BM **82523**		**W**	1182 - 930	**30** (32°)
		N	1212 - 955	**60** (61°)
SA **82456**	HC	**M**	1132 - 644	**15** (15°)
BM **82934**	HC	**W**	1182 - 671	**30** (27°)
		N	1212 - 689	**60** (49°)


Electronics: **BF** (pag 744) | Recessed casing: (pag 742-743)

C.V. - 24 V DC - 9 W DC				
SA **81202**		**M**	1265 - 993	**15** (15°)
BM **82524**		**W**	1320 - 1036	**30** (32°)
		N	1354 - 1068	**60** (61°)
SA **82457**	HC	**M**	1265 - 714	**15** (15°)
BM **82935**	HC	**W**	1320 - 744	**30** (27°)
		N	1354 - 767	**60** (49°)

Electronics: **DC** (pag 744) | Recessed casing: (pag 742-743)

Orma_IL | powerLED





		Cct	lm S - lm D	Opt
C.C. - 630 mA - 2 W DC				
SA **81213**		**M**	233 - 23	**00** (Diffused)
		W	249 - 25	
		N	266 - 27	


Electronics: **BD** (pag 744) | Recessed casing: (pag 742-743)

C.V. - 24 V DC - 3 W DC				
SA **81214**		**M**	233 - 23	**00** (Diffused)
		W	249 - 25	
		N	266 - 27	

Electronics: **DL** (pag 744) | Recessed casing: (pag 742-743)

Orma_IL | arrayLED-Direct | 220-240 V AC





LED-DIRECT

		Cct	lm S - lm D	Opt
7 W AC				
SA **76081**		**W**	865 - 106	**00** (Diffused)
		N	870 - 107	

Recessed casing: (pag 742-743)

Finishes

SA Steel/Aluminium
BM Brass/Aluminium

Cct


M 2700 **N** 4000
W 3000

Accessories

HC Honeycomb

Orma_I | arrayLED





IK10 IP68

		Cct	lm S - lm D	Opt
C.C. - 350 mA - 12 W DC				
SA	**81175**	**M**	2015 - 1612	**15** (14°)
		W	2100 - 1680	**30** (31°)
		N	2156 - 1725	**60** (60°)
SA	**81176** HC	**M**	2015 - 1146	**15** (14°)
		W	2100 - 1195	**30** (28°)
		N	2156 - 1227	**60** (49°)
SA	**81177** DL	**M**	2015 - 1277	**15** (14°)
		W	2100 - 1331	**30** (30°)
		N	2156 - 1367	**60** (52°)


Electronics: **BG** (pag 744) | Recessed casing: (pag 742-743)

C.V. - 24 V DC - 13 W DC				
SA	**81178**	**M**	1876 - 1501	**15** (14°)
		W	1959 - 1567	**30** (31°)
		N	2010 - 1608	**60** (60°)
SA	**81179** HC	**M**	1876 - 1067	**15** (14°)
		W	1959 - 1115	**30** (28°)
		N	2010 - 1144	**60** (49°)
SA	**81180** DL	**M**	1876 - 1189	**15** (14°)
		W	1959 - 1242	**30** (30°)
		N	2010 - 1274	**60** (52°)

Electronics: **DD** (pag 744) | Recessed casing: (pag 742-743)

Orma_I | arrayLED-Direct | 220-240 V AC





IK10 IP68 **LED-DIRECT**

		Cct	lm S - lm D	Opt
11,5 W AC				
SA	**76082**	**W**	1267 - 821	**15** (17°)
		N	1316 - 854	**30** (25°)
				60 (53°)

Recessed casing: (pag 742-743)

Orma_I 220 V-240 V (direct)
The Orma family has evolved, presenting a luminaire with an extremely small fixture, just 51 millimetres thick, which can be directly connected to the mains without the need for external power sources, allowing easier and faster installation. Its performance remains unaltered as do the materials used, all sturdy and reliable.



Inground


Finishes
SA Steel/Aluminium

Cct
M 2700 **N** 4000
W 3000

Accessories
HC Honeycomb
DL Darklight

Orma_IJ | arrayLED





		Cct	lm S - lm D	Opt
C.C. - 350 mA - 12 W DC				
SA **81203**		**M**	2015 - 1540	**15** (22°)
BM **82525**		**W**	2100 - 1607	**30** (34°)
		N	2156 - 1650	**60** (61°)
SA **82458**	HC	**M**	2015 - 1093	**15** (20°)
		W	2100 - 1141	**30** (27°)
		N	2156 - 1171	**60** (48°)


Electronics: **BG** (pag 744) | Recessed casing: (pag 742-743)

		Cct	lm S - lm D	Opt
C.V. - 24 V DC - 13 W DC				
SA **81204**		**M**	1876 - 1432	**15** (22°)
BM **82526**		**W**	1959 - 1495	**30** (34°)
		N	2010 - 1535	**60** (61°)
SA **82459**	HC	**M**	1876 - 1017	**15** (20°)
		W	1959 - 1062	**30** (27°)
		N	2010 - 1089	**60** (48°)

Electronics: **DD** (pag 744) | Recessed casing: (pag 742-743)

Orma_IL | powerLED





		Cct	lm S - lm D	Opt
C.C. - 350 mA - 4 W DC				
SA **81215**		**M**	490 - 89	**00** (Diffused)
		W	490 - 89	
		N	529 - 96	


Electronics: **BE** (pag 744) | Recessed casing: (pag 742-743)

		Cct	lm S - lm D	Opt
C.V. - 24 V DC - 5 W DC				
SA **81216**		**M**	490 - 89	**00** (Diffused)
		W	490 - 89	
		N	529 - 96	

Electronics: **DB** (pag 744) | Recessed casing: (pag 742-743)

Orma_IL | arrayLED-Direct | 220-240 V AC





LED-DIRECT

		Cct	lm S - lm D	Opt
7 W AC				
SA **76083**		**W**	865 - 208	**00** (Diffused)
		N	870 - 209	

Recessed casing: (pag 742-743)


Finishes
SA Steel/Aluminium
BM Brass/Aluminium

Cct
M 2700 **N** 4000
W 3000

Accessories
HC Honeycomb

Orma_A | powerLED






		Cct	lm S - lm D	Opt	
C.C. - 350 mA - 4 W DC					
SA **81181**		**M**	490 - 270	**15**	(22°)
		W	490 - 270	**30**	(29°)
		N	529 - 292	**60**	(49°)
				25	(17°x 38°)
SA **81182**	HC	**M**	490 - 186	**15**	(20°)
		W	490 - 186	**30**	(25°)
		N	529 - 201	**60**	(37°)
SA **81183**	DL	**M**	490 - 193	**15**	(22°)
		W	490 - 193	**30**	(30°)
		N	529 - 208	**60**	(55°)


Electronics: **BE** (pag 744) | Recessed casing: (pag 742-743)

C.V. - 24 V DC - 5 W DC					
SA **81184**		**M**	490 - 270	**15**	(22°)
		W	490 - 270	**30**	(29°)
		N	529 - 292	**60**	(49°)
				25	
SA **81185**	HC	**M**	490 - 186	**15**	(20°)
		W	490 - 186	**30**	(25°)
		N	529 - 201	**60**	(37°)
SA **81186**	DL	**M**	490 - 193	**15**	(22°)
		W	490 - 193	**30**	(30°)
		N	529 - 208	**60**	(55°)

Electronics: **DB** (pag 744) | Recessed casing: (pag 742-743)

Orma_AJ | powerLED






		Cct	lm S - lm D	Opt	
C.C. - 350 mA - 4 W DC					
SA **81205**		**M**	490 - 270	**15**	(22°)
		W	490 - 270	**30**	(29°)
		N	529 - 292	**60**	(49°)


Electronics: **BE** (pag 744) | Recessed casing: (pag 742-743)

C.V. - 24 V DC - 5 W DC					
SA **81206**		**M**	490 - 270	**15**	(22°)
		W	490 - 270	**30**	(29°)
		N	529 - 292	**60**	(49°)

Electronics: **DB** (pag 744) | Recessed casing: (pag 742-743)

Orma_AL | powerLED





		Cct	lm S - lm D	Opt	
C.C. - 350 mA - 1 W DC					
SA **81217**		**M**	145 - 17	**00**	(Diffused)
		W	154 - 19		
		N	165 - 21		


Electronics: **BB** (pag 744) | Recessed casing: (pag 742-743)

C.V. - 24 V DC - 1,5 W DC					
SA **81218**		**M**	145 - 17	**00**	(Diffused)
		W	154 - 19		
		N	165 - 21		

Electronics: **DI** (pag 744) | Recessed casing: (pag 742-743)

Orma_A | arrayLED





		Cct	lm S - lm D	Opt
C.C. - 220 mA - 8 W DC				
SA **81187**		**M**	1132 - 893	**15** (15°)
		W	1182 - 933	**30** (31°)
		N	1212 - 956	**60** (61°)
SA **81188**	HC	**M**	1132 - 644	**15** (15°)
		W	1182 - 673	**30** (27°)
		N	1212 - 690	**60** (49°)
SA **81189**	DL	**M**	1132 - 598	**15** (16°)
		W	1182 - 624	**30** (29°)
		N	1212 - 640	**60** (53°)

Electronics: **BF** (pag 744) | Recessed casing: (pag 742-743)

		Cct	lm S - lm D	Opt
C.V. - 24 V DC - 9 W DC				
SA **81190**		**M**	1265 - 998	**15** (15°)
		W	1320 - 1041	**30** (31°)
		N	1354 - 1068	**60** (61°)
SA **81191**	HC	**M**	1265 - 719	**15** (15°)
		W	1320 - 750	**30** (27°)
		N	1354 - 769	**60** (49°)
SA **81192**	DL	**M**	1265 - 668	**15** (16°)
		W	1320 - 697	**30** (29°)
		N	1354 - 715	**60** (53°)


Electronics: **DC** (pag 744) | Recessed casing: (pag 742-743)

		Cct	Opt
powerLED - C.C. - 630 mA - 8 W DC			
SA **81322**		**V** RGBW (3000 K)	**06** (7°÷ 9°)
		Q RGBW (4000 K)	**15** (10°÷ 19°)
			45 (40°÷ 49°)
			00 (Diffused)

Electronics: **CF** (pag 744) | Recessed casing and cables: (pag 742-744)

Orma_AJ | arrayLED





		Cct	lm S - lm D	Opt
C.C. - 220 mA - 8 W DC				
SA **81207**		**M**	1132 - 893	**15** (15°)
		W	1182 - 933	**30** (32°)
		N	1212 - 956	**60** (61°)
SA **82460**	HC	**M**	1132 - 644	**15** (15°)
		W	1182 - 673	**30** (27°)
		N	1212 - 690	**60** (49°)


Electronics: **BF** (pag 744) | Recessed casing: (pag 742-743)

		Cct	lm S - lm D	Opt
C.V. - 24 V DC - 9 W DC				
SA **81208**		**M**	1265 - 998	**15** (15°)
		W	1320 - 1041	**30** (32°)
		N	1354 - 1068	**60** (61°)
SA **82461**	HC	**M**	1265 - 719	**15** (15°)
		W	1320 - 750	**30** (32°)
		N	1354 - 769	**60** (61°)

Electronics: **DC** (pag 744) | Recessed casing: (pag 742-743)

Orma_AL | powerLED





		Cct	lm S - lm D	Opt
C.C. - 630 mA - 2 W DC				
SA **81219**		**M**	233 - 23	**00** (Diffused)
		W	249 - 25	
		N	266 - 27	

Electronics: **BD** (pag 744) | Recessed casing: (pag 742-743)


C.V. - 24 V DC - 3 W DC

SA **81220**		**M**	233 - 23	**00** (Diffused)
		W	249 - 25	
		N	266 - 27	

Electronics: **DL** (pag 744) | Recessed casing: (pag 742-743)

Orma_A | arrayLED





		Cct	lm S - lm D	Opt
C.C. - 350 mA - 12 W DC				
SA **81193**		**M**	2015 - 1612	**15** (14°)
		W	2100 - 1680	**30** (31°)
		N	2156 - 1725	**60** (61°)
SA **81194**	HC	**M**	2015 - 1146	**15** (14°)
		W	2100 - 1195	**30** (28°)
		N	2156 - 1227	**60** (49°)
SA **81195**	DL	**M**	2015 - 1277	**15** (14°)
		W	2100 - 1331	**30** (30°)
		N	2156 - 1367	**60** (52°)

Electronics: **BG** (pag 744) | Recessed casing: (pag 742-743)


C.V. - 24 V DC - 13 W DC

SA **81196**		**M**	1876 - 1501	**15** (14°)
		W	1959 - 1567	**30** (31°)
		N	2010 - 1608	**60** (60°)
SA **81197**	HC	**M**	1876 - 1067	**15** (14°)
		W	1959 - 1115	**30** (28°)
		N	2010 - 1144	**60** (49°)
SA **81198**	DL	**M**	1876 - 1189	**15** (14°)
		W	1959 - 1242	**30** (30°)
		N	2010 - 1274	**60** (52°)

Electronics: **DD** (pag 744) | Recessed casing: (pag 742-743)

Orma_AJ | arrayLED





		Cct	lm S - lm D	Opt
C.C. - 350 mA - 12 W DC				
SA **81209**		**M**	2015 - 1540	**15** (22°)
		W	2100 - 1606	**30** (34°)
		N	2156 - 1650	**60** (61°)
SA **82462**	HC	**M**	2015 - 1093	**15** (20°)
		W	2100 - 1141	**30** (27°)
		N	2156 - 1171	**60** (48°)


Electronics: **BG** (pag 744) | Recessed casing: (pag 742-743)

		Cct	lm S - lm D	Opt
C.V. - 24 V DC - 13 W DC				
SA **81210**		**M**	1876 - 1432	**15** (22°)
		W	1959 - 1495	**30** (34°)
		N	2010 - 1535	**60** (61°)
SA **82463**	HC	**M**	1876 - 1017	**15** (20°)
		W	1959 - 1062	**30** (27°)
		N	2010 - 1089	**60** (48°)

Electronics: **DD** (pag 744) | Recessed casing: (pag 742-743)

Orma_AL | powerLED





		Cct	lm S - lm D	Opt
C.C. - 350 mA - 4 W DC				
SA **81221**		**M**	490 - 89	**00** (Diffused)
		W	490 - 89	
		N	529 - 96	


Electronics: **BE** (pag 744) | Recessed casing: (pag 742-743)

		Cct	lm S - lm D	Opt
C.V. - 24 V DC - 4,5 W DC				
SA **81222**		**M**	490 - 89	**00** (Diffused)
		W	490 - 89	
		N	529 - 96	

Electronics: **DB** (pag 744) | Recessed casing: (pag 742-743)

LIGHT TO ENHANCE FORMS

At nightfall, the shadows and chiaroscuro created by artificial lighting can be deliberately manipulated to give depth and meaning to the whole complex, or to 'bring out' the anatomy of statuesque bodies from the darkness, emphasising their physicality through the appropriate play of light and shadow. The enhancement of the forms and characteristics of statues and symbolic monuments can only be achieved through an in-depth analysis of the material they are made of, their interaction with the general/environmental lighting, and the desired scenic effect.



CABEZA PARQUE NORTE
Madrid (Spain)

Sculptor and lighting project:
Arturo Berned

Photography:
Marek Jarosz



ARIA RETREAT & SPA
Cima di Porlezza, Como (Italy)

Architectural design:
R4M Engineering

Lighting design:
Architect Giorgio Colombo,
Light+Arch Consultancy


Construction:
Quadrio Gaetano Costruzioni S.p.a.


Contract & Custom Lighting:
Bespoke Lighting Solutions

Photo: Andrea Martiradonna



Orma_F | powerLED






2000 kg

	Cct	Im S - Im D	Opt
C.C. - 350 mA - 1 W DC			
GA **82697**	**M**	145 - 72	**20** (26°)
	W	154 - 76	**35** (45°)
	N	165 - 82	

Electronics: **BB** (pag 744) | Recessed casing: (pag 742-743)

Orma_FL | powerLED






2000 kg

	Cct	Im S - Im D	Opt
C.C. - 350 mA - 1 W DC			
GA **82699**	**M**	145 - 13	**00** (Diffused)
	W	154 - 14	
	N	165 - 15	

Electronics: **BB** (pag 744) | Recessed casing: (pag 742-743)

Orma_F | powerLED






2000 kg

	Cct	Im S - Im D	Opt
C.V. - 24 V DC - 1,5 W DC			
GA **82698**	**M**	145 - 72	**20** (26°)
	W	154 - 76	**35** (45°)
	N	165 - 82	

Electronics: **DI** (pag 744) | Recessed casing: (pag 742-743)

Orma_FL | powerLED






2000 kg

	Cct	Im S - Im D	Opt
C.V. - 24 V DC - 1,5 W DC			
GA **82700**	**M**	145 - 13	**00** (Diffused)
	W	154 - 14	
	N	165 - 15	

Electronics: **DI** (pag 744) | Recessed casing: (pag 742-743)

Orma_F | powerLED





2000 kg

		Cct	Im S - Im D	Opt
C.C. - 350 mA - 4 W DC				
GA **82657**		**M**	490 - 287	**15** (16°)
GA **82658**	HC	**W**	490 - 287	**30** (30°)
GA **82659**	DL	**N**	529 - 309	**60** (55°)


Electronics: **BE** (pag 744) | Recessed casing: (pag 742-743)

C.V. - 24 V DC - 5 W DC				
GA **82660**		**M**	490 - 287	**15** (16°)
GA **82661**	HC	**W**	490 - 287	**30** (30°)
GA **82662**	DL	**N**	529 - 309	**60** (55°)

Electronics: **DB** (pag 744) | Recessed casing: (pag 742-743)

Orma_FJ | powerLED





2000 kg

		Cct	Im S - Im D	Opt
C.C. - 350 mA - 4 W DC				
GA **82663**		**M**	490 - 287	**15** (16°)
		W	490 - 287	**30** (30°)
		N	529 - 309	**60** (55°)


Electronics: **BE** (pag 744) | Recessed casing: (pag 742-743)

C.V. - 24 V DC - 5 W DC				
GA **82664**		**M**	490 - 287	**15** (16°)
		W	490 - 287	**30** (30°)
		N	529 - 309	**60** (55°)

Electronics: **DB** (pag 744) | Recessed casing: (pag 742-743)

Orma_FL | powerLED





2000 kg

		Cct	Im S - Im D	Opt
C.C. - 350 mA - 1 W DC				
GA **82667**		**M**	145 - 17	**00** (Diffused)
		W	154 - 19	
		N	165 - 21	


Electronics: **BB** (pag 744) | Recessed casing: (pag 742-743)

C.V. - 24 V DC - 1,5 W DC				
GA **82668**		**M**	145 - 17	**00** (Diffused)
		W	154 - 19	
		N	165 - 21	

Electronics: **DI** (pag 744) | Recessed casing: (pag 742-743)

Orma_F | arrayLED





		Cct	lm S - lm D	Opt
C.C. - 220 mA - 8 W DC				
GA **82669**		**M**	1132 - 717	**15** (17°)
GA **82670**	HC	**W**	1182 - 748	**30** (30°)
GA **82671**	DL	**N**	1212 - 767	**60** (60°)


Electronics: **BF** (pag 744) | Recessed casing: (pag 742-743)

C.V. - 24 V DC - 9 W DC				
GA **82672**		**M**	1265 - 730	**15** (17°)
GA **82673**	HC	**W**	1320 - 761	**30** (30°)
GA **82674**	DL	**N**	1354 - 780	**60** (60°)

Electronics: **DC** (pag 744) | Recessed casing: (pag 742-743)

Orma_FJ | arrayLED






		Cct	lm S - lm D	Opt
C.C. - 220 mA - 8 W DC				
GA **82675**		**M**	1132 - 717	**15** (17°)
GA **82676**	HC	**W**	1182 - 748	**30** (30°)
		N	1212 - 767	**60** (60°)


Electronics: **BF** (pag 744) | Recessed casing: (pag 742-743)

C.V. - 24 V DC - 9 W DC				
GA **82677**		**M**	1265 - 730	**15** (17°)
GA **82678**	HC	**W**	1320 - 761	**30** (30°)
		N	1354 - 780	**60** (60°)

Electronics: **DC** (pag 744) | Recessed casing: (pag 742-743)

Orma_FL | powerLED





		Cct	lm S - lm D	Opt
C.C. - 630 mA - 2 W DC				
GA **82681**		**M**	233 - 23	**00** (Diffused)
		W	249 - 24	
		N	266 - 26	


Electronics: **BD** (pag 744) | Recessed casing: (pag 742-743)

C.V. - 24 V DC - 3 W DC				
GA **82682**		**M**	233 - 23	**00** (Diffused)
		W	249 - 24	
		N	266 - 26	

Electronics: **DL** (pag 744) | Recessed casing: (pag 742-743)

Orma_F | arrayLED





		Cct	lm S - lm D	Opt
C.C. - 350 mA - 12 W DC				
GA **82683**		**M**	2015 - 1596	**15** (12°)
GA **82684**	HC	**W**	2100 - 1663	**30** (31°)
GA **82685**	DL	**N**	2156 - 1708	**60** (57°)


Electronics: **BG** (pag 744) | Recessed casing: (pag 742-743)

C.V. - 24 V DC - 13 W DC				
GA **82686**		**M**	1876 - 1486	**15** (12°)
GA **82687**	HC	**W**	1959 - 1552	**30** (31°)
GA **82688**	DL	**N**	2010 - 1592	**60** (57°)

Electronics: **DD** (pag 744) | Recessed casing: (pag 742-743)

Orma_FJ | arrayLED





		Cct	lm S - lm D	Opt
C.C. - 350 mA - 12 W DC				
GA **82689**		**M**	2015 - 1407	**15** (22°)
GA **82690**	HC	**W**	2100 - 1468	**30** (30°)
		N	2156 - 1505	**60** (58°)


Electronics: **BG** (pag 744) | Recessed casing: (pag 742-743)

C.V. - 24 V DC - 13 W DC				
GA **82691**		**M**	1876 - 1308	**15** (22°)
GA **82692**	HC	**W**	1959 - 1366	**30** (30°)
		N	2010 - 1400	**60** (58°)

Electronics: **DD** (pag 744) | Recessed casing: (pag 742-743)

Orma_FL | powerLED






		Cct	lm S - lm D	Opt
C.C. - 350 mA - 4 W DC				
GA **82695**		**M**	490 - 50	**00** (Diffused)
		W	490 - 50	
		N	529 - 54	


Electronics: **BE** (pag 744) | Recessed casing: (pag 742-743)

C.V. - 24 V DC - 5 W DC				
GA **82696**		**M**	490 - 50	**00** (Diffused)
		W	490 - 50	
		N	529 - 54	

Electronics: **DB** (pag 744) | Recessed casing: (pag 742-743)

Orma_FO | topLED





2000 kg | III | IK09 | IP67


	Cct	Im S - Im D	Opt
C.V. - 24 V DC - 1,8 W DC			
WH **95474**	**M**	54 - 6	**00** (Diffused)
BB **95475**	**W**	60 - 7	
GG **95476**	**N**	63 - 8	

Electronics: **EU** (pag 744) | Recessed casing: (pag 742-743)

With installation on outer casing 98292, cable outlet is straight, not 90° lateral.

Orma_FO | powerLED





2000 kg | III | IK10 | IP68


	Cct	Im S - Im D	Opt
C.C. - 350 mA - 1 W DC			
BB **82665**	**M**	145 - 6	**00** (Diffused)
	W	154 - 7	
	N	165 - 8	


Electronics: **BB** (pag 744) | Recessed casing: (pag 742-743)

C.V. - 24 V DC - 1,5 W DC			
BB **82666**	**M**	145 - 6	**00** (Diffused)
	W	154 - 7	
	N	165 - 8	

Electronics: **DI** (pag 744) | Recessed casing: (pag 742-743)

Orma_FO | powerLED





III | IK10 | IP68

	Cct	Im S - Im D	Opt
C.C. - 630 mA - 2 W DC			
BB **82679**	**M**	233 - 13	**00** (Diffused)
	W	249 - 14	
	N	266 - 15	


Electronics: **BD** (pag 744) | Recessed casing: (pag 742-743)

C.V. - 24 V DC - 3 W DC			
BB **82680**	**M**	233 - 13	**00** (Diffused)
	W	249 - 14	
	N	266 - 15	

Electronics: **DL** (pag 744) | Recessed casing: (pag 742-743)

Orma_FO | powerLED





III | IK10 | IP68


	Cct	Im S - Im D	Opt
C.C. - 350 mA - 4 W DC			
BB **82693**	**M**	490 - 34	**00** (Diffused)
	W	490 - 34	
	N	529 - 37	


Electronics: **BE** (pag 744) | Recessed casing: (pag 742-743)

C.V. - 24 V DC - 5 W DC			
BB **82694**	**M**	490 - 34	**00** (Diffused)
	W	490 - 34	
	N	529 - 37	

Electronics: **DB** (pag 744) | Recessed casing: (pag 742-743)

Orma_Q | arrayLED





2000 kg


		Cct	lm S - lm D	Opt
C.C. - 350 mA - 4 W DC				
SA **77284**		**M**	596 - 299	**15** (19°)
SA **77286**	HC	**W**	624 - 313	**30** (30°)
		N	660 - 330	**60** (52°)


Electronics: **BE** (pag 744) | Recessed casing: (pag 742-743)

C.V. - 24 V DC - 5 W DC				
SA **77290**		**M**	596 - 299	**15** (19°)
SA **77292**	HC	**W**	624 - 313	**30** (30°)
		N	660 - 330	**60** (52°)

Electronics: **DB** (pag 744) | Recessed casing: (pag 742-743)

Orma_QJ | arrayLED





2000 kg

		Cct	lm S - lm D	Opt
C.C. - 350 mA - 4 W DC				
SA **77294**		**M**	596 - 299	**15** (19°)
SA **77296**	HC	**W**	624 - 313	**30** (30°)
		N	660 - 330	**60** (52°)


Electronics: **BE** (pag 744) | Recessed casing: (pag 742-743)

C.V. - 24 V DC - 5 W DC				
SA **77298**		**M**	596 - 299	**15** (19°)
SA **77300**	HC	**W**	624 - 313	**30** (30°)
		N	660 - 330	**60** (52°)

Electronics: **DB** (pag 744) | Recessed casing: (pag 742-743)

Orma_QL | powerLED





2000 kg


		Cct	lm S - lm D	Opt
C.C. - 500 mA - 1,5 W DC				
SA **77282**		**M**	199 - 21	**00** (Diffused)
		W	213 - 23	
		N	227 - 25	


Electronics: **BC** (pag 744) | Recessed casing: (pag 742-743)

C.V. - 24 V DC - 3 W DC				
SA **77288**		**M**	199 - 21	**00** (Diffused)
		W	213 - 23	
		N	227 - 25	

Electronics: **DL** (pag 744) | Recessed casing: (pag 742-743)

Orma_Q | arrayLED





2000 kg | III | IK10 | IP68


		Cct	lm S - lm D	Opt
C.C. - 220 mA - 8 W DC				
SA **77304**		**M**	1132 - 720	**15** (18°)
SA **77306**	HC	**W**	1182 - 751	**30** (26°)
		N	1212 - 770	**60** (58°)


Electronics: **BF** (pag 744) | Recessed casing: (pag 742-743)

C.V. - 24 V DC - 9 W DC				
SA **77310**		**M**	1265 - 804	**15** (18°)
SA **77312**	HC	**W**	1320 - 839	**30** (26°)
		N	1354 - 860	**60** (58°)

Electronics: **DC** (pag 744) | Recessed casing: (pag 742-743)

Orma_Q | powerLED | RGBW







2000 kg | III | IK10 | IP68 | NEW

	Fin	Cct		Opt
C.C - 630 mA - 8 W DC				
C00969	SA	**V**	RGBW (3000 K)	**NS** (7°÷ 9°)
		Q	RGBW (4000 K)	**SP** (10°÷ 19°)
				MW (40°÷ 49°)

Electronics: **CF** (pag 744) | Recessed casing: (pag 742-743)

Orma_Q | arrayLED-Direct | 220-240 V AC





2000 kg | IK10 | IP68 | NEW


LED-DIRECT

	Fin	Cct	lm S - lm D	Opt
7 W AC				
C00971	SA	**W**	865 - 316	**SP** (18°)
		N	870 - 317	**FL** (26°)
				MW (44°)

Recessed casing: (pag 742-743)

Orma_QJ | arrayLED





2000 kg | III | IK10 | IP68

		Cct	lm S - lm D	Opt
C.C. - 220 mA - 8 W DC				
SA **77314**		**M**	1132 - 720	**15** (18°)
SA **77316**	HC	**W**	1182 - 751	**30** (26°)
		N	1212 - 770	**60** (58°)


Electronics: **BF** (pag 744) | Recessed casing: (pag 742-743)

C.V. - 24 V DC - 9 W DC				
SA **77318**		**M**	1265 - 804	**15** (18°)
SA **77320**	HC	**W**	1320 - 839	**30** (26°)
		N	1354 - 860	**60** (58°)

Electronics: **DC** (pag 744) | Recessed casing: (pag 742-743)

Orma_QL | powerLED





2000 kg

	Cct	lm S - lm D	Opt
C.C. - 630 mA - 2 W DC			
SA **77302**	**M**	249 - 44	**00** (Diffused)
	W	266 - 45	
	N	284 - 47	

Electronics: **BD** (pag 744) | Recessed casing: (pag 742-743)

C.V. - 24 V DC - 2,5 W DC

SA **77308**	**M**	249 - 44	**00** (Diffused)
	W	266 - 45	
	N	284 - 47	

Electronics: **DL** (pag 744) | Recessed casing: (pag 742-743)

2000 kg

	Fin	Cct		Opt
C.C - 350 mA - 4 W DC				
C01034	**SA**	**V**	RGBW (3000 K)	**DI** (Diffused)
		Q	RGBW (4000 K)	


Electronics: **CD** (pag 744) | Recessed casing: (pag 742-743)



Finishes	Cct					
SA Steel/Aluminium	**M**	2700	**N**	4000	**Q**	RGBW (4000)
	W	3000	**V**	RGBW (3000)		

Orma_QF | powerLED | 220-240 V AC






2000 kg IK06 IP68 ID

	Cct	lm S - lm D	Opt
2 W DC - 3 W AC			
GA **77281**	**M**	233 - 133	**15** (23°)
	W	249 - 145	**30** (32°)
	N	266 - 155	**60** (41°)

Recessed casing: (pag 742-743)

Orma_QF | powerLED





2000 kg III IK06 IP68


	Cct	lm S - lm D	Opt
C.C. - 600 mA - 2 W DC			
GA **77279**	**M**	233 - 133	**15** (23°)
	W	249 - 145	**30** (32°)
	N	266 - 155	**60** (41°)


Electronics: **BD** (pag 744) | Recessed casing: (pag 742-743)

C.V. - 24 V DC - 3 W DC			
GA **77280**	**M**	233 - 133	**15** (23°)
	W	249 - 145	**30** (32°)
	N	266 - 155	**60** (41°)

Electronics: **DL** (pag 744) | Recessed casing: (pag 742-743)

Orma_QFL | powerLED





Orma_QFL 1,5W
OFF

Orma_QFL 1,5W
ON

2000 kg IK06 IP68 ID

	Cct	lm S - lm D	Opt
220-240 V AC - 1 W DC - 1,5 W AC			
GA **77278**	**M**	145 - 20	**00** (Diffused)
	W	154 - 21	
	N	165 - 22	

Recessed casing: (pag 742-743)

2000 kg III IK06 IP68

	Cct	lm S - lm D	Opt
C.C. - 350 mA - 1 W DC			
GA **77276**	**M**	145 - 20	**00** (Diffused)
	W	154 - 21	
	N	165 - 22	


Electronics: **BB** (pag 744) | Recessed casing: (pag 742-743)


C.V. - 24 V DC - 1,5 W DC			
GA **77277**	**M**	145 - 20	**00** (Diffused)
	W	154 - 21	
	N	165 - 22	

Electronics: **DI** (pag 744) | Recessed casing: (pag 742-743)

ID Driver on board

Orma_QF | arrayLED





2000 kg


		Cct	lm S - lm D	Opt
C.C. - 350 mA - 4 W DC				
GA **77285**		**M**	596 - 299	**15** (19°)
GA **77287**	HC	**W**	624 - 313	**30** (30°)
		N	660 - 330	**60** (52°)


Electronics: **BE** (pag 744) | Recessed casing: (pag 742-743)

C.V. - 24 V DC - 5 W DC				
GA **77291**		**M**	596 - 299	**15** (19°)
GA **77293**	HC	**W**	624 - 313	**30** (30°)
		N	660 - 330	**60** (52°)

Electronics: **DB** (pag 744) | Recessed casing: (pag 742-743)

Orma_QFJ | arrayLED





2000 kg

		Cct	lm S - lm D	Opt
C.C. - 350 mA - 4 W DC				
GA **77295**		**M**	596 - 299	**15** (19°)
GA **77297**	HC	**W**	624 - 313	**30** (30°)
		N	660 - 330	**60** (52°)


Electronics: **BE** (pag 744) | Recessed casing: (pag 742-743)

C.V. - 24 V DC - 5 W DC				
GA **77299**		**M**	596 - 299	**15** (19°)
GA **77301**	HC	**W**	624 - 313	**30** (30°)
		N	660 - 330	**60** (52°)

Electronics: **DB** (pag 744) | Recessed casing: (pag 742-743)

Orma_QFL | powerLED





2000 kg


		Cct	lm S - lm D	Opt
C.C. - 500 mA - 1,5 W DC				
GA **77283**		**M**	199 - 21	**00** (Diffused)
		W	213 - 23	
		N	227 - 25	


Electronics: **BC** (pag 744) | Recessed casing: (pag 742-743)

C.V. - 24 V DC - 3 W DC				
GA **77289**		**M**	199 - 21	**00** (Diffused)
		W	213 - 23	
		N	227 - 25	

Electronics: **DL** (pag 744) | Recessed casing: (pag 742-743)

Orma_QF | arrayLED





2000 kg


		Cct	lm S - lm D	Opt
C.C. - 220 mA - 8 W DC				
GA **77305**		**M**	1132 - 720	**15** (18°)
GA **77307**	HC	**W**	1182 - 751	**30** (26°)
		N	1212 - 770	**60** (58°)


Electronics: **BF** (pag 744) | Recessed casing: (pag 742-743)

C.V. - 24 V DC - 9 W DC				
GA **77311**		**M**	1265 - 720	**15** (18°)
GA **77313**	HC	**W**	1320 - 751	**30** (26°)
		N	1354 - 770	**60** (58°)

Electronics: **DC** (pag 744) | Recessed casing: (pag 742-743)

Orma_QF | powerLED | RGBW







2000 kg NEW

	Fin	Cct	Opt
C.C. - 630 mA - 8 W DC			
C00968	GA	**V** RGBW (3000 K)	**NS** (7°÷ 9°)
		Q RGBW (4000 K)	**SP** (10°÷ 19°)
			MW (40°÷ 49°)

Electronics: **CF** (pag 744) | Recessed casing: (pag 742-743)

Orma_QF | arrayLED-Direct | 220-240 V AC







2000 kg NEW **LED-DIRECT**

	Fin	Cct	lm S - lm D	Opt
7 W AC				
C00970	GA	**W**	865 - 316	**SP** (18°)
		N	870 - 317	**FL** (26°)
				MW (44°)

Recessed casing: (pag 742-743)

Orma_QFJ | arrayLED





2000 kg

		Cct	lm S - lm D	Opt
C.C. - 220 mA - 8 W DC				
GA **77315**		**M**	1132 - 720	**15** (18°)
GA **77317**	HC	**W**	1182 - 751	**30** (26°)
		N	1212 - 770	**60** (58°)

Electronics: **BF** (pag 744) | Recessed casing: (pag 742-743)

C.V. - 24 V DC - 9 W DC				
GA **77319**		**M**	1265 - 720	**15** (18°)
GA **77321**	HC	**W**	1320 - 751	**30** (26°)
		N	1354 - 770	**60** (58°)

Electronics: **DC** (pag 744) | Recessed casing: (pag 742-743)

Finishes


GA Glass/Aluminium

Cct

M 2700 **N** 4000 **Q** RGBW (4000)
W 3000 **V** RGBW (3000)

Orma_QFL | powerLED





2000 kg

	Cct	Im S - Im D	Opt
C.C. - 630 mA - 2 W DC			
GA **77303**	**M**	249 - 44	**00** (Diffused)
	W	266 - 45	
	N	284 - 47	

Electronics: **BD** (pag 744) | Recessed casing: (pag 742-743)

	Cct	Im S - Im D	Opt
C.V. - 24 V DC - 2,5 W DC			
GA **77309**	**M**	249 - 44	**00** (Diffused)
	W	266 - 45	
	N	284 - 47	

Electronics: **DL** (pag 744) | Recessed casing: (pag 742-743)

2000 kg NEW

	Fin	Cct	Opt
C.C. 350 mA - 4 W DC			
C01033	**GA**	**V** RGBW (3000 K)	**DI** (Diffused)
		Q RGBW (4000 K)	

Electronics: **CD** (pag 744) | Recessed casing: (pag 742-743)




Finishes

GA Glass/Aluminium

Cct


M 2700 **N** 4000 **Q** RGBW (4000)
W 3000 **V** RGBW (3000)

Recessed casings (F / FO collection)



ABS 99925 Coring recessed casings

suitable for: Orma_F /_FL Ø22,5 h59
Orma_F /_FL Ø22,5 h85




ABS 99923 Coring recessed casings

suitable for: Orma_F /_FJ /_FL /_FO Ø87 h60



ABS 98292 Recessed casings

suitable for: Orma_FO Ø42 h65



ABS 83036 Recessed casings

suitable for: Orma_F /_FL Ø22,5 h59




ABS 83038 Recessed casings

suitable for: Orma_F /_FJ /_FL /_FO Ø56 h61




ABS 83040 Recessed casings

suitable for: Orma_F /_FJ /_FL /_FO Ø127 h65




ABS 99922 Coring recessed casings

suitable for: Orma_F /_FJ /_FL /_FO Ø56 h61




ABS 99924 Coring recessed casings

suitable for: Orma_F /_FJ /_FL /_FO Ø127 h65



ZN 98291 Recessed casings

suitable for: Orma_FO Ø42 h65



ABS 83037 Recessed casings

suitable for: Orma_F /_FL Ø22,5 h85



ABS 83039 Recessed casings

suitable for: Orma_F /_FJ /_FL /_FO Ø87 h60




PVC 83235 Suction cup

suitable for: for all Orma (**NOT FOR** Orma_F Ø22,5 / Orma_FL / Orma_QFL / Orma_FO / Orma_QF 36x36)

PVC C-K400101 Suction cup


suitable for: for Orma_FL Ø87 / Orma_FL Ø127 / Orma_QFL 60x60 / Orma_QFL 90x90

Recessed casings (Q / QF collection)




ABS 83411 Recessed casings

suitable for: Orma_Q /_QJ /_QL 85x85




ABS C-C100001 Recessed casings

suitable for: Orma_QF /_QFL 36x36




ABS C-C100003 Recessed casings

suitable for: Orma_QF /_QFJ /_QFL 90x90



ABS 83410 Recessed casings

suitable for: Orma_Q /_QJ /_QL 116x116



ABS C-C100002 Recessed casings

suitable for: Orma_QF /_QFJ /_QFL 60x60



PVC 83235 Suction cup

suitable for: for all Orma (**NOT FOR** Orma_F Ø22,5 / Orma_FL / Orma_QFL / Orma_FO / Orma_QF 36x36)

PVC C-K400101 Suction cup

suitable for: for Orma_FL Ø87 / Orma_FL Ø127 / Orma_QFL 60x60 / Orma_QFL 90x90

Recessed casings (A / I collection)



ABS 99650 Recessed casings

suitable for: Orma_I /_IJ /_IL Ø64 h48
Orma_A /_AJ /_AL Ø54 h48




ABS 99652 Recessed casings

suitable for: Orma_I /_IJ /_IL Ø138 h53
Orma_A /_AJ /_AL Ø125 h50




ABS 99563 Recessed casings

suitable for: Orma_A /_AJ /_AL Ø85 h50



ABS 99855 Recessed casings

suitable for: Orma_A /_AJ /_AL Ø54 h48




ABS 99857 Recessed casings

suitable for: Orma_A /_AJ /_AL Ø125 h50



ABS 99651 Recessed casings

suitable for: Orma_I /_IJ /_IL Ø97 h53
Orma_A /_AJ /_AL Ø85 h50




ABS 99560 Recessed casings

suitable for: Orma_A /_AJ /_AL Ø54 h48



ABS 99564 Recessed casings

suitable for: Orma_A /_AJ /_AL Ø125 h50





ABS 99856 Recessed casings


suitable for: Orma_A /_AJ /_AL Ø85 h50

INSTALLATION

Installation in a few quick steps **(Recessed casing 99563 + Orma AJ 81207W15)**







Electronics

BB

89419	89421	C-E200006	C-E200004
ON/OFF	ON/OFF	ON/OFF	DALI/PUSH
1 - 2 art.	3 - 6 art.	6 - 12 art.	5 - 12 art.
74 x 65 x h 27	74 x 65 x h 27	135 x 26 x h 26	125 x 45 x h 30
		35	55

BC

89422	89423	C-E200007	C-E200003
ON/OFF	ON/OFF	ON/OFF	DALI/PUSH
1 - 2 art.	2 - 3 art.	3 - 6 art.	5 - 12 art.
74 x 65 x h 27	74 x 65 x h 27	135 x 26 x h 26	125 x 45 x h 30
		35	55

BD

89420	C-E200008	99186	C-E200002
ON/OFF	ON/OFF	ON/OFF	DALI/PUSH
1 - 2 art.	3 - 6 art.	6 - 12 art.	5 - 12 art.
74 x 65 x h 27	135 x 26 x h 26	117 x 92 x h 38	125 x 45 x h 30
	35		55

BE

89421	C-E200006	C-E200004
ON/OFF	ON/OFF	DALI/PUSH
1 art.	2 - 3 art.	2 - 3 art.
74 x 65 x h 27	135 x 26 x h 26	125 x 45 x h 30
	35	55

BF

99342	C-E200005
ON/OFF	DALI/PUSH
1 art.	1 art.
100 x 80 x h 31	125 x 45 x h 30
	55

BG

C-E200006	C-E200004
ON/OFF	DALI/PUSH
1 art.	1 art.
135 x 26 x h 26	125 x 45 x h 30
35	55

CD

C-E700003+C-W600001	C-E500014	DMX	Driver CV	Switching
Dimmer RF	Dimmer DMX	Controllers	CV 48V	CV 48V
6 - 12 art.	6 - 12 art.			
175 x 45 x h 27	107 x 96 x h 39	Pag. 963	Pag. 950-951	Pag. 945-946
52				

CF

C-E700003+C-W600001	C-E500011	DMX	Driver CV	Switching
Dimmer RF	Dimmer DMX	Controllers	CV 48V	CV 48V
6 - 12 art.	6 - 12 art.			
175 x 45 x h 27	107 x 96 x h 39	Pag. 963	Pag. 950-951	Pag. 945-946
52				

DB

89488	89179	89359	99660	83042	+ driver 24V DC	
ON/OFF	ON/OFF	ON/OFF	Dimmer	Dimmer DALI/PUSH	99331 150W	99786 240W
1 - 2 art.	1 - 4 art.	1 - 9 art.	DALI - 0/1-10V	0/1-10V	1-21 art.	1-33 art.
80 x 100 x h 31	92 x 117 x h 38	115 x 140 x h 50	149 x 37 x h 31	164 x 38 x h 25		
			48	45	70	81

DC

89179	89359	99331	99660	83042	+ driver 24V DC	
ON/OFF	ON/OFF	ON/OFF	Dimmer	Dimmer DALI/PUSH	99331 150W	99786 240W
1 - 2 art.	1 - 5 art.	1 - 15 art.	DALI - 0/1-10V	0/1-10V	1-11 art.	1-18 art.
92 x 117 x h 38	115 x 140 x h 50	158 x 60 x h 35	149 x 37 x h 31	164 x 38 x h 25		
			48	45	70	81

DD

89179	89359	99331	99660	83042	+ driver 24V DC	
ON/OFF	ON/OFF	ON/OFF	Dimmer	Dimmer DALI/PUSH	99331 150W	99786 240W
1 art.	1 - 3 art.	1 - 10 art.	DALI - 0/1-10V	0/1-10V	1-8 art.	1-12 art.
92 x 117 x h 38	115 x 140 x h 50	158 x 60 x h 35	149 x 37 x h 31	164 x 38 x h 25		
			48	45	70	81

DI

89488	89179	89359	99660	83042	+ driver 24V DC	
ON/OFF	ON/OFF	ON/OFF	Dimmer	Dimmer DALI/PUSH	99331 150W	99786 240W
1 - 9 art.	1 - 15 art.	1 - 30 art.	DALI - 0/1-10V	0/1-10V	1-70 art.	1-112 art.
80 x 100 x h 31	92 x 117 x h 38	115 x 140 x h 50	149 x 37 x h 31	164 x 38 x h 25		
			48	45	70	81

DL

89488	89179	89359	99660	83042	+ driver 24V DC	
ON/OFF	ON/OFF	ON/OFF	Dimmer	Dimmer DALI/PUSH	99331 150W	99786 240W
1 - 4 art.	1 - 7 art.	1 - 14 art.	DALI - 0/1-10V	0/1-10V	1-35 art.	1-56 art.
80 x 100 x h 31	92 x 117 x h 38	115 x 140 x h 50	149 x 37 x h 31	164 x 38 x h 25		
			48	45	70	81

EU

89488	89179	89359	99332	83333
ON/OFF	ON/OFF	ON/OFF	0/1-10V	DALI/PUSH
1 - 7 art.	1 - 12 art.	1 - 28 art.	1 - 75 art.	1 - 75 art.
80 x 100 x h 31	92 x 117 x h 38	115 x 140 x h 50	150 x 60 x h 35	188 x 68 x h 34
			70	77

Cables

24 V DC / 220-240 V AC | Cable with F-connector



BB **99216** Conn. F.4 pin M12 (L 1 m)
BB **89190** Conn. F.4 pin M12 (L 5 m)
suitable for: Orma RGBW

24 V DC / 220-240 V AC | Cable with M-connector



BB **98476** Conn. M.4 pin M12 (L 1 m)
BB **98477** Conn. M.4 pin M12 (L 5 m)
suitable for: Orma RGBW

24 V DC 220-240V AC | Extension cable with M+F connectors



BB **98437** Conn M. + F. 4 pin M12 (L 1 m)
BB **98149** Conn M. + F. 4 pin M12 (L 5 m)
BB **89188** Conn M. + F. 4 pin M12 (L 10 m)
suitable for: Orma RGBW



SUELO

Aluminium body, brass body.
AISI 316L stainless steel flange.



THE RANGE

The Suelo family offers a variety of solutions for every design need: fixed and swivel versions, small-flanged flush-mount uplights, and dimmer units using the DALI protocol. There are pro models with recessed optics and RGBW sources, and beam control filters. All models have exclusive AquaStop® protection systems, and there are versions with 24-volt cable converters.
Suelo can be used with a honeycomb filter, which screens secondary light and reduces dazzle, maintaining a high-quality diffuse light. A darklight filter directs the illumination onto one part of the wall by sectioning one part of the beam, and prevents dazzle even close to the source.
For full beam control and a drastically reduced dazzle risk, choose the Suelo PRO versions, in which the recessed source increases the screening angle, totally skimming off the secondary flow to give a cleaner, more concentrated and efficient light.

Aesthetic frame, without visible screws (R collection)



_R
W 2
mm **Ø 30**
Pag 751

_R Pro
W 2-3
mm **Ø 35**
Pag 751

_R / _RJ
_R Pro
W 2-3-4,5-5
mm **Ø 64**
Pag 752-753

_R / _RJ
_R Pro / _RJ Pro
W 2-3-8-9
mm **Ø 92**
Pag 754-756

_R
_RJ
W 12,6-13-16-19-25
mm **Ø 185**
Pag 758-759
Installation with placing flange

_RF
_RFJ
W 12,6-13-16-19-25
mm **Ø 180**
Pag 760-761
Installation with flush flange

Frame with security screws (RX collection)



_RX Pro
W 2-3
mm **Ø 50**
Pag 764

_RX / _RX Pro
_RXJ Pro
W 2-3-8-9-13
mm **Ø 112 - Ø 170 (Ww)**
Pag 765-767

_RX
_RXJ
W 12,6-13-16-19-25
mm **Ø 185 - Ø 232 (Ww)**
Pag 768-769
Installation with placing flange

_RXF
_RXFJ
W 12,6-13-16-19-25
mm **Ø 180**
Pag 770-771
Installation with flush flange

_RX
_RXJ
W 37-44,2
mm **Ø 315**
Pag 772
Installation with placing flange

_RXF
_RXFJ
W 37-44,2
mm **Ø 308**
Pag 773
Installation with flush flange

Frame with security screws (Brass collection)



_Brass
W 8
mm **Ø 120**
Pag 774

Safety systems
We have developed specific safety systems to protect the uplights against corrosion and make them very durable. They also incorporate overvoltage and electrostatic discharge protection, and systems to protect the integrity of the circuits from moisture and internal condensation (AquaStop) formation.

Suelo Ø 315 mm / Ø 308 mm
The evolution of the Suelo family includes a 315 / 308 mm diameter, 44,2 W version that improves it in terms of performance. In addition to the optics range that sets all Suelo units apart, the RX / RF version is characterised by extremely easy installation through the use of the recessed casing designed to be able adjust the inclination of the horizontal axis and, without accessing the inside of the optics chamber, the vertical axis. Suelo was also designed to house the power supply and control unit inside the body of the product, which guarantees a high grade of protection.



Suelo_RXJ/RXFJ Standard



Suelo_RXJ/RXFJ Optics 06


Suelo_RXJ/RXFJ Dark light


Suelo_RXJ/RXFJ Honeycomb

Standard and Pro optics
Linea Light Group recessed lights have an optionally deeper-positioned source than the standard version. The increased screening angle offers greater visual comfort.


Standard version


Pro version



NO-GLARE


Darklight (DL)
The darklight filter attenuates the light so that it shines only on a specific area of the surface. This accessory sections the beam so that only a part of it shines on the wall, and prevents dazzle even close to the source.






Honeycomb (HC)
The hexagonal microcells making up the mesh of the Honeycomb filter help to screen the light beam, reducing dazzle while leaving the light quality unaltered.





With Darklight



With Honeycomb



Without Darklight



Without Honeycomb




HAKKA INDENTURE MUSEUM
Beijing (China)
Project: DnA Design and Architecture




Suelo_R | powerLED





Suelo_R Pro | powerLED





	Fin	Cct	lm S - lm D 2 W	lm S - lm D 3 W	Opt
C.C. - 630 mA 2 W DC - 1000 mA 3 W DC					
C01049	**CH**	**M**	233 - 149	417 - 238	**SP** (10°)
		W	249 - 159	432 - 246	**FL** (21°)
		N	266 - 170	642 - 264	**ML** (32°)
					WF (57°)
					XF (91°)
					DI (Diffused)

Electronics: 2W IP67 **BD** - 3W IP40 **FQ** (pag 775) | Recessed casing: (pag 776)

2500 kg

	Fin	Cct	lm S - lm D 2 W	lm S - lm D 3 W	Opt
C.C. - 630 mA 2 W DC - 1000 mA 3 W DC					
C01050	**SA**	**M**	233 - 138	417 - 219	**FL** (22°)
	BM	**W**	249 - 170	432 - 227	**ML** (31°)
		N	266 - 181	642 - 242	**WF** (54°)
					1S (16°x 36°)
					DI (Diffused)
C.C. - 630 mA 2 W DC - 1000 mA 3 W DC					
C01135 HC	**SA**	**M**	233 - 86	417 - 137	**SP** (19°)
	BM	**W**	249 - 92	432 - 142	**FL** (25°)
		N	266 - 98	642 - 152	**MW** (45°)

Electronics: 2W IP67 **BD** - 3W IP40 **FQ** (pag 775) | Recessed casing: (pag 776)


C.V. 24 V DC - 3 W DC				
SA 80441	**M**	233 - 121	**15**	(22°)
BM 82531	**W**	249 - 138	**30**	(28°)
	N	266 - 148	**60**	(54°)
			88	(16°x 36°)
			00	(Diffused)
C.V. 24 V DC - 3 W DC				
SA 80442 HC	**M**	233 - 76	**15**	(19°)
BM 82532 HC	**W**	249 - 86	**30**	(25°)
	N	266 - 92	**60**	(45°)

Electronics: **DL** (pag 775) | Recessed casing: (pag 776)

Scale 1:1

(SA)

(BM)



Finishes

CH Chrome
SA Steel/Aluminium
BM Brass/Aluminium

Cct


M 2700 **N** 4000
W 3000

Accessories

HC Honeycomb

Suelo_R | powerLED





2500 kg IK09 IP68 NEW

	Fin	Cct	lm S - lm D	Opt
C.C. - 630 mA - 2 W DC				
C00074	**SA**	**M**	174 - 158	**US** (4°)
	BM	**W**	177 - 161	
		N	201 - 183	

Electronics: **BD** (pag 775) | Recessed casing: (pag 776)

C.V. - 24 V DC - 3 W DC				
C00103	**SA**	**M**	174 - 158	**US** (4°)
	BM	**W**	177 - 161	
		N	201 - 183	

Electronics: **DL** (pag 775) | Recessed casing: (pag 776)

2500 kg IK09 IP68

		Cct	lm S - lm D	Opt
C.C. - 500 mA - 4,5 W DC				
SA **76207**		**M**	646 - 345	**20** (20°)
		W	673 - 359	**30** (27°)
		N	711 - 379	**60** (53°)
				88 (23°x 54°)
				00 (Diffused)
C.C. - 500 mA - 4,5 W DC				
SA **76209**	HC	**M**	646 - 219	**20** (20°)
		W	673 - 228	**30** (24°)
		N	711 - 241	**60** (39°)


Electronics: **BW** (pag 775) | Recessed casing: (pag 776)

C.V. - 24 V DC - 5 W DC				
SA **76210**		**M**	646 - 345	**20** (20°)
		W	673 - 359	**30** (27°)
		N	711 - 379	**60** (53°)
				88 (23°x 54°)
				00 (Diffused)
C.V. - 24 V DC - 5 W DC				
SA **76212**	HC	**M**	646 - 219	**20** (20°)
		W	673 - 228	**30** (24°)
		N	711 - 241	**60** (39°)

Electronics: **DB** (pag 775) | Recessed casing: (pag 776)

Suelo_R | powerLED





2500 kg IK09 IP68

		Cct	lm S - lm D	Opt
C.C. - 500 mA - 4,5 W DC				
SA **76208**		**M**	646 - 348	**07** (Asym. Ww)
		W	673 - 363	
		N	711 - 383	


Electronics: **BW** (pag 775) | Recessed casing: (pag 776)

C.V. - 24 V DC - 5 W DC				
SA **76211**		**M**	646 - 348	**07** (Asym. Ww)
		W	673 - 363	
		N	711 - 383	

Electronics: **DB** (pag 775) | Recessed casing: (pag 776)

Suelo_R | powerLED | 220-240 V AC






2500 kg IK09 IP68 NEW

	Fin	Cct	lm S - lm D	Opt
2 W DC - 2,5 W AC				
C00083	**SA**	**M**	174 - 158	**US** (4°)
	BM	**W**	177 - 161	
		N	201 - 183	

Recessed casing: (pag 776)

Suelo_R | powerLED | 220-240 V AC






2500 kg IK09 IP68

		Cct	lm S - lm D	Opt
4,5 W DC - 5,9 W AC				
SA	**76213**	**M**	646 - 345	**20** (20°)
		W	673 - 359	**30** (27°)
		N	711 - 379	**60** (53°)
				88 (23°x 54°)
				00 (Diffused)
4,5 W DC - 5,9 W AC				
SA	**76214** HC	**M**	646 - 219	**20** (20°)
		W	673 - 228	**30** (24°)
		N	711 - 241	**60** (39°)

Recessed casing: (pag 776)

Suelo_R Pro | powerLED





2500 kg IK09 IP68


		Cct	lm S - lm D	Opt
C.C. - 500 mA - 4,5 W DC				
SA	**76215**	**M**	646 - 227	**20** (20°)
SA	**76216** HC	**W**	673 - 236	**30** (26°)
SA	**76217** DL	**N**	711 - 250	**50** (43°)


Electronics: **BW** (pag 775) | Recessed casing: (pag 776)

C.V. - 24 V DC - 5 W DC				
SA	**76218**	**M**	646 - 227	**20** (20°)
SA	**76219** HC	**W**	673 - 236	**30** (26°)
SA	**76220** DL	**N**	711 - 250	**50** (43°)

Electronics: **DB** (pag 775) | Recessed casing: (pag 776)

Suelo_RJ | powerLED





2500 kg IK09 IP68

		Cct	lm S - lm D	Opt
C.C. - 500 mA - 4,5 W DC				
SA	**76221**	**M**	646 - 345	**20** (20°)
BM	**76222**	**W**	673 - 359	**30** (26°)
		N	711 - 379	**60** (53°)


Electronics: **BW** (pag 775) | Recessed casing: (pag 776)

C.V. - 24 V DC - 5W DC				
SA	**76223**	**M**	646 - 345	**20** (20°)
BM	**76224**	**W**	673 - 359	**30** (26°)
		N	711 - 379	**60** (53°)

Electronics: **DB** (pag 775) | Recessed casing: (pag 776)

Suelo_RJ | powerLED | 220-240 V AC






2500 kg IK09 IP68


		Cct	lm S - lm D	Opt
4,5 W DC - 5,9 W AC				
SA	**76225**	**M**	646 - 345	**20** (20°)
		W	673 - 359	**30** (26°)
		N	711 - 379	**60** (53°)

Recessed casing: (pag 776)

Finishes		Cct		Accessories	
SA	Steel/Aluminium	**M** 2700	**N** 4000	HC	Honeycomb
BM	Brass/Aluminium	**W** 3000		DL	Darklight

Suelo_R | powerLED





2500 kg

	Fin	Cct	lm S - lm D	Opt
C.C. - 630 mA - 2 W DC				
C00075	**SA**	**M**	174 - 149	**HS** (3°)
	BM	**W**	177 - 152	
		N	201 - 172	

Electronics: **BD** (pag 775) | Recessed casing: (pag 776)

C.V. - 24 V DC - 3 W DC				
C00112	**SA**	**M**	174 - 149	**HS** (3°)
	BM	**W**	177 - 152	
		N	201 - 172	

Electronics: **DL** (pag 775) | Recessed casing: (pag 776)

2500 kg


		Cct	lm S - lm D	Opt
C.C. - 630 mA - 8 W DC				
SA **80546**		**M**	877 - 613	**06** (9°)
		W	945 - 618	
		N	1013 - 663	
C.C. - 220 mA - 8 W DC				
SA **76701**		**M**	1041 - 891	**15** (15°)
		W	1087 - 931	**30** (26°)
		N	1114 - 953	**60** (50°)
				88 (15°x 47°)
				00 (Diffused)
				07 (Asym. Ww)
C.C. - 630 mA - 8 W DC				
SA **80547**	HC	**M**	877 - 470	**06** (9°)
		W	945 - 472	
		N	1013 - 507	
C.C. - 220 mA - 8 W DC				
SA **76702**	HC	**M**	1041 - 694	**15** (14°)
		W	1087 - 725	**30** (24°)
		N	1114 - 743	**60** (43°)


Electronics: 630 mA **BU** - 220 mA **BF** (pag 775) | Recessed casing: (pag 776)

C.V. - 24 V DC - 9 W DC				
SA **80550**		**M**	877 - 613	**06** (9°)
		W	945 - 618	
		N	1013 - 663	
C.V. - 24 V DC - 9 W DC				
SA **76703**		**M**	1265 - 891	**15** (15°)
		W	1320 - 931	**30** (26°)
		N	1354 - 954	**60** (50°)
				88 (15°x 47°)
				00 (Diffused)
				07 (Asym. Ww)
C.V. - 24 V DC - 9 W DC				
SA **80551**	HC	**M**	877 - 470	**06** (9°)
		W	945 - 472	
		N	1013 - 507	
C.V. - 24 V DC - 9 W DC				
SA **76704**	HC	**M**	1265 - 694	**15** (14°)
		W	1320 - 725	**30** (24°)
		N	1354 - 743	**60** (43°)

Electronics: **DC** (pag 775) | Recessed casing: (pag 776)

Suelo_R | powerLED | RGBW







2500 kg

	Cct	Opt
C.C - 630 mA - 8 W DC		
SA **81717**	**V** RGBW (3000 K)	**06** (7°÷ 9°)
	Q RGBW (4000 K)	**15** (10°÷ 19°)
		45 (40°÷ 49°)

Electronics: **CF** (pag 775) | Recessed casing: (pag 776)

Suelo_R | powerLED | 220-240 V AC







2500 kg

	Fin	Cct	lm S - lm D	Opt
2 W DC - 2,5 W AC				
C00115	**SA**	**M**	174 - 149	**HS** (3°)
	BM	**W**	177 - 152	
		N	201 - 172	

Recessed casing: (pag 776)

Suelo_R | powerLED | 220-240 V AC





2500 kg

	Cct	lm S - lm D	Opt
8 W DC - 9 W AC			
SA **80554**	**M**	877 - 613	**06** (9°)
	W	945 - 614	
	N	1013 - 663	
SA **76203**	**M**	1041 - 891	**15** (15°)
	W	1087 - 931	**30** (26°)
	N	1114 - 954	**60** (50°)
			88 (15°x 47°)
			00 (Diffused)
			07 (Asym. Ww)
8 W DC - 9 W AC			
SA **80555** HC	**M**	877 - 470	**06** (9°)
	W	945 - 471	
	N	1013 - 507	
SA **76717** HC	**M**	1041 - 694	**15** (14°)
	W	1087 - 725	**30** (24°)
	N	1114 - 743	**60** (43°)


Recessed casing: (pag 776)




Suelo_R Pro Brass (BM) **Suelo_R Pro Steel (SA)**

Finishes	Cct				Accessories		Inground
SA Steel/Aluminium	**M** 2700	**N** 4000	**Q** RGBW (4000)		HC Honeycomb		755
BM Brass/Aluminium	**W** 3000	**V** RGBW (3000)					

Suelo_R Pro | powerLED





2500 kg


	Cct	Im S - Im D	Opt
C.C. - 630 mA - 8 W DC			
SA **80558**	**M**	877 - 579	**06** (6°)
SA **80559** HC	**W**	945 - 580	
SA **80560** DL	**N**	1013 - 621	
C.C. - 220 mA - 8 W DC			
SA **76709**	**M**	1041 - 868	**15** (15°)
SA **76710** HC	**W**	1087 - 906	**30** (26°)
	N	1114 - 929	**60** (50°)


Electronics: 630 mA **BU** - 220 mA **BF** (pag 775) | Recessed casing: (pag 776)

	Cct	Im S - Im D	Opt
C.V. - 24 V DC - 9 W DC			
SA **80564**	**M**	877 - 579	**06** (6°)
SA **80565** HC	**W**	945 - 580	
SA **80566** DL	**N**	1013 - 621	
C.V. - 24 V DC - 9 W DC			
SA **76711**	**M**	1265 - 868	**15** (15°)
SA **76712** HC	**W**	1320 - 906	**30** (26°)
	N	1354 - 929	**60** (50°)

Electronics: **DC** (pag 775) | Recessed casing: (pag 776)

Suelo_R Pro | powerLED | 220-240 V AC







2500 kg

	Cct	Im S - Im D	Opt
8 W DC - 9 W AC			
SA **80570**	**M**	877 - 579	**06** (6°)
BM **82535**	**W**	945 - 580	
SA **80571** HC	**N**	1013 - 621	
BM **82536** HC			
8 W DC - 9 W AC			
SA **76204**	**M**	1041 - 868	**15** (15°)
BM **76718**	**W**	1087 - 906	**30** (26°)
SA **76719** HC	**N**	1114 - 929	**60** (50°)
BM **76720** HC			

Recessed casing: (pag 776)

Suelo_RJ Pro | powerLED





2500 kg


	Cct	Im S - Im D	Opt
C.C. - 630 mA - 8 W DC			
SA **80576**	**M**	760 - 558	**20** (20°)
	W	760 - 558	**30** (30°)
	N	821 - 603	**60** (60°)


Electronics: **BU** (pag 775) | Recessed casing: (pag 776)

	Cct	Im S - Im D	Opt
C.V. - 24 V DC - 9 W DC			
SA **80578**	**M**	760 - 558	**20** (20°)
	W	760 - 558	**30** (30°)
	N	821 - 603	**60** (60°)

Electronics: **DC** (pag 775) | Recessed casing: (pag 776)

Suelo_RJ Pro | powerLED | 220-240 V AC





2500 kg

	Cct	Im S - Im D	Opt
8 W DC - 9 W AC			
SA **80580**	**M**	760 - 558	**20** (20°)
	W	760 - 558	**30** (30°)
	N	821 - 603	**60** (60°)

Recessed casing: (pag 776)

FRANTOIO CENTUMBRIE
Agello, Perugia (Italy)

Architectural design:
Architect Gianmarco Balucani

System and lighting design:
Prait, Simone Suriani


Designer:
Miriam Cinaglia

Photography:
Matteo Canestraro



Suelo_R | arrayLED | 220-240 V AC





Installation with placing flange


5000 kg IK10 IP68 NEW

		Cct	lm S - lm D	Opt
13 W DC - 15 W AC				
SA **77117**		**M**	1676 - 1325	**10** (10°)
SA **77118**	HC	**W**	1750 - 1381	
SA **77119**	DL	**N**	1794 - 1421	
DALI				
SA **77126**				
SA **77127**	HC			
SA **77128**	DL			
16 W DC - 18 W AC				
SA **77114**		**M**	2528 - 1718	**15** (16°)
SA **77115**	HC	**W**	2634 - 1790	**30** (37°)
SA **77116**	DL	**N**	2704 - 1844	**50** (53°)
DALI				
SA **77123**				
SA **77124**	HC			
SA **77125**	DL			
19 W DC - 22 W AC				
SA **77111**		**M**	2773 - 2117	**15** (16°)
SA **77112**	HC	**W**	2889 - 2205	**30** (37°)
SA **77113**	DL	**N**	2966 - 2230	**50** (53°)
DALI				
SA **77120**				
SA **77121**	HC			
SA **77122**	DL			

Recessed casing & accessories: (pag 776-777)

Suelo_R | arrayLED | RGBW | 24/48 V DC







RGBW Connector

Installation with placing flange


5000 kg III IK10 IP68 NEW DMX RDM RGBW

	Fin	Cct	Opt
C.V. - 12,6 W DC			
C00602	SA	**H** RGBW (2700 K)	**SP** (10°÷ 19°)
		V RGBW (3000 K)	**ML** (30°÷ 39°)
		Q RGBW (4000 K)	**WF** (50°÷ 70°)


Electronics: **AM12** (pag 775) | Recessed casing: (pag 776)


C.V. - 25 W DC			
C00921	SA	**H** RGBW (2700 K)	**SP** (10°÷ 19°)
		V RGBW (3000 K)	**ML** (30°÷ 39°)
		Q RGBW (4000 K)	**WF** (50°÷ 70°)

Electronics: **AM12** (pag 775) | Recessed casing: (pag 776)



Suelo_RJ | arrayLED | 220-240 V AC





Installation with placing flange


5000 kg IK10 IP68 NEW

		Cct	lm S - lm D	Opt
13 W DC - 15 W AC				
SA **77133**		**M**	1676 - 1289	**10** (11°)
SA **77134**	HC	**W**	1750 - 1344	
DALI		**N**	1794 - 1383	
SA **77139**				
SA **77140**	HC			
16 W DC - 18 W AC				
SA **77131**		**M**	2528 - 1633	**15** (16°)
SA **77132**	HC	**W**	2634 - 1702	**30** (37°)
DALI		**N**	2704 - 1753	**50** (52°)
SA **77137**				
SA **77138**	HC			
19 W DC - 22 W AC				
SA **77129**		**M**	2773 - 2013	**15** (16°)
SA **77130**	HC	**W**	2889 - 2097	**30** (37°)
DALI		**N**	2966 - 2121	**50** (52°)
SA **77135**				
SA **77136**	HC			

Recessed casing & accessories: (pag 776-777)

Suelo_RJ | arrayLED | RGBW | 24/48 V DC







RGBW Connector

Installation with placing flange


5000 kg III IK10 IP68 NEW DMX RDM RGBW

	Fin	Cct		Opt
C.V. - 12,6 W DC				
C00603	SA	**H**	RGBW (2700 K)	**SP** (10°÷ 19°)
		V	RGBW (3000 K)	**ML** (30°÷ 39°)
		Q	RGBW (4000 K)	**WF** (50°÷ 70°)

Electronics: **AM12** (pag 775) | Recessed casing: (pag 776)

C.V. - 25 W DC				
C00923	SA	**H**	RGBW (2700 K)	**SP** (10°÷ 19°)
		V	RGBW (3000 K)	**ML** (30°÷ 39°)
		Q	RGBW (4000 K)	**WF** (50°÷ 70°)

Electronics: **AM12** (pag 775) | Recessed casing: (pag 776)



Finishes

SA Steel/Aluminium

Cct


M 2700 **N** 4000 **V** RGBW (3000)
W 3000 **H** RGBW (2700) **Q** RGBW (4000)

Accessories

HC Honeycomb

Suelo_RF | arrayLED | 220-240 V AC





Installation with flush flange


5000 kg IK10 IP68 NEW

		Cct	lm S - lm D	Opt
13 W DC - 15 W AC				
SA **77147**		**M**	1676 - 1325	**10** (10°)
SA **77148**	HC	**W**	1750 - 1381	
SA **77149**	DL	**N**	1794 - 1421	
DALI				
SA **77156**				
SA **77157**	HC			
SA **77158**	DL			
16 W DC - 18 W AC				
SA **77144**		**M**	2528 - 1718	**15** (16°)
SA **77145**	HC	**W**	2634 - 1790	**30** (37°)
SA **77146**	DL	**N**	2704 - 1844	**50** (53°)
DALI				
SA **77153**				
SA **77154**	HC			
SA **77155**	DL			
19 W DC - 22 W AC				
SA **77141**		**M**	2773 - 2117	**15** (16°)
SA **77142**	HC	**W**	2889 - 2205	**30** (37°)
SA **77143**	DL	**N**	2966 - 2230	**50** (53°)
DALI				
SA **77150**				
SA **77151**	HC			
SA **77152**	DL			

Recessed casing & accessories: (pag 776-777)

Suelo_RF | arrayLED | RGBW | 24/48 V DC







RGBW Connector

Installation with flush flange


5000 kg III IK10 IP68 NEW DMX RDM RGBW

	Fin	Cct	Opt
C.V. - 12,6 W DC			
C00605	SA	**H** RGBW (2700 K)	**SP** (10°÷ 19°)
		V RGBW (3000 K)	**ML** (30°÷ 39°)
		Q RGBW (4000 K)	**WF** (50°÷ 70°)


Electronics: **AM12** (pag 775) | Recessed casing: (pag 776)


C.V. - 25 W DC			
C00925	SA	**H** RGBW (2700 K)	**SP** (10°÷ 19°)
		V RGBW (3000 K)	**ML** (30°÷ 39°)
		Q RGBW (4000 K)	**WF** (50°÷ 70°)

Electronics: **AM12** (pag 775) | Recessed casing: (pag 776)



Suelo_RFJ | arrayLED | 220-240 V AC





Installation with flush flange


5000 kg IK10 IP68 NEW

		Cct	lm S - lm D	Opt
13 W DC - 15 W AC				
SA **77163**		**M**	1676 - 1289	**10** (11°)
SA **77164**	HC	**W**	1750 - 1344	
DALI		**N**	1794 - 1383	
SA **77169**				
SA **77170**	HC			
16 W DC - 18 W AC				
SA **77161**		**M**	2528 - 1633	**15** (16°)
SA **77162**	HC	**W**	2634 - 1702	**30** (37°)
DALI		**N**	2704 - 1753	**50** (52°)
SA **77167**				
SA **77168**	HC			
19 W DC - 22 W AC				
SA **77159**		**M**	2773 - 2013	**15** (16°)
SA **77160**	HC	**W**	2889 - 2097	**30** (37°)
DALI		**N**	2966 - 2121	**50** (52°)
SA **77165**				
SA **77166**	HC			

Recessed casing & accessories: (pag 776-777)

Suelo_RFJ | arrayLED | RGBW | 24/48 V DC







RGBW Connector

Installation with flush flange


5000 kg III IK10 IP68 NEW DMX RDM RGBW

	Fin	Cct		Opt
C.V. - 12,6 W DC				
C00607	SA	**H**	RGBW (2700 K)	**SP** (10°÷ 19°)
		V	RGBW (3000 K)	**ML** (30°÷ 39°)
		Q	RGBW (4000 K)	**WF** (50°÷ 70°)

Electronics: **AM12** (pag 775) | Recessed casing: (pag 776)

C.V. - 25 W DC				
C00927	SA	**H**	RGBW (2700 K)	**SP** (10°÷ 19°)
		V	RGBW (3000 K)	**ML** (30°÷ 39°)
		Q	RGBW (4000 K)	**WF** (50°÷ 70°)

Electronics: **AM12** (pag 775) | Recessed casing: (pag 776)





Finishes	Cct				Accessories	Inground
SA Steel/Aluminium	**M** 2700	**N** 4000	**V** RGBW (3000)	HC Honeycomb		
	W 3000	**H** RGBW (2700)	**Q** RGBW (4000)			



PALAZZO DELL'EMICICLO
L'Aquila (Italy)


REGIONALE
CONSIGLIO REGIONALE





2500 kg

	Fin		Cct	lm S - lm D 2 W	lm S - lm D 3 W	Opt
C.C. - 630 mA 2 W DC - 1000 mA 3 W DC						
C01051	**SA**		**M**	233 - 121	417 - 219	**FL** (22°)
	BM		**W**	249 - 138	432 - 227	**ML** (31°)
			N	266 - 148	642 - 242	**WF** (54°)
						DI (Diffused)
C.C. - 630 mA 2 W DC - 1000 mA 3 W DC						
C01136 HC	**SA**		**M**	233 - 76	417 - 137	**SP** (19°)
	BM		**W**	249 - 86	432 - 142	**FL** (25°)
			N	266 - 92	642 - 152	**MW** (45°)

Electronics: 2W IP67 **BD** - 3W IP40 **FQ** (pag 775) | Recessed casing: (pag 776)


		Cct		Opt
C.V. - 24 V DC - 3 W DC				
SA **80437**		**M**	233 - 121	**15** (22°)
BM **82540**		**W**	249 - 138	**30** (31°)
		N	266 - 148	**60** (54°)
				00 (Diffused)
C.V. - 24 V DC - 3 W DC				
SA **80438**	HC	**M**	233 - 76	**15** (19°)
BM **82541**	HC	**W**	249 - 86	**30** (25°)
		N	266 - 92	**60** (45°)


Electronics: **DL** (pag 775) | Recessed casing: (pag 776)

IT IS THE MOST ADVERSE CONDITIONS THAT ENHANCE AN EXTRAORDINARY PRODUCT



Suelo_RX | powerLED





2500 kg NEW


	Fin	Cct	lm S - lm D	Opt
C.C. - 630 mA - 2 W DC				
C00113	**SA**	**M**	174 - 149	**HS** (3°)
	BM	**W**	177 - 152	
		N	201 - 172	


Electronics: **BD** (pag 775) | Recessed casing: (pag 776)

C.V. - 24 V DC - 3 W DC				
C00114	**SA**	**M**	174 - 149	**HS** (3°)
	BM	**W**	177 - 152	
		N	201 - 172	

Electronics: **DL** (pag 775) | Recessed casing: (pag 776)

Suelo_RX | powerLED





2500 kg

		Cct	lm S - lm D	Opt
C.C. - 630 mA - 8 W DC				
SA **80548**		**M**	877 - 613	**06** (9°)
		W	945 - 618	
		N	1013 - 663	
C.C. - 220 mA - 8 W DC				
SA **76705**		**M**	1041 - 891	**15** (15°)
		W	1087 - 931	**30** (26°)
		N	1114 - 953	**60** (50°)
				88 (15°x 47°)
				00 (Diffused)
				07 (Asym. Ww)
C.C. - 630 mA - 8 W DC				
SA **80549**	HC	**M**	877 - 470	**06** (9°)
		W	945 - 470	
		N	1013 - 507	
C.C. - 220 mA - 8 W DC				
SA **76706**	HC	**M**	1041 - 694	**15** (14°)
		W	1087 - 725	**30** (24°)
		N	1114 - 743	**60** (43°)

Electronics: 630 mA **BU** - 220 mA **BF** (pag 775) | Recessed casing: (pag 776)

C.V. - 24 V DC - 9W DC				
SA **80552**		**M**	877 - 613	**06** (9°)
		W	945 - 618	
		N	1013 - 663	
C.V. - 24 V DC - 9W DC				
SA **76707**		**M**	1265 - 891	**15** (15°)
		W	1320 - 931	**30** (26°)
		N	1354 - 954	**60** (50°)
				88 (15°x 47°)
				00 (Diffused)
				07 (Asym. Ww)
C.V. - 24 V DC - 9W DC				
SA **80553**	HC	**M**	877 - 470	**06** (9°)
		W	945 - 472	
		N	1013 - 507	
C.V. - 24 V DC - 9W DC				
SA **76708**	HC	**M**	1265 - 694	**15** (14°)
		W	1320 - 725	**30** (24°)
		N	1354 - 743	**60** (43°)

Electronics: **DC** (pag 775) | Recessed casing: (pag 776)

2500 kg RGBW

		Cct	Opt
C.C. - 630 mA - 8 W DC			
SA **81718**		**V** RGBW (3000 K)	**06** (7°÷ 9°)
		Q RGBW (4000 K)	**15** (10°÷ 19°)
			45 (40°÷ 49°)

Electronics: **CF** (pag 775) | Recessed casing: (pag 776)

Finishes

SA Steel/Aluminium
BM Brass/Aluminium

Cct


M 2700 **N** 4000 **Q** RGBW (4000)
W 3000 **V** RGBW (3000)

Accessories

HC Honeycomb

Suelo_RX | powerLED | 220-240 V AC






2500 kg IK10 IP68 NEW

	Fin	Cct	lm S - lm D	Opt
2 W DC - 2,5 W AC				
C00116	**SA**	**M**	174 - 149	**HS** (3°)
	BM	**W**	177 - 152	
		N	201 - 172	

Recessed casing: (pag 776)

Suelo_RX | powerLED | 198-264V AC







2500 kg IK10 IP68

		Cct	lm S - lm D	Opt
8 W DC - 9 W AC				
SA	**80556**	**M**	877 - 613	**06** (9°)
		W	945 - 614	
		N	1013 - 663	
8 W DC - 9 W AC				
SA	**76205**	**M**	1041 - 891	**15** (15°)
		W	1087 - 931	**30** (26°)
		N	1114 - 954	**60** (50°)
				88 (15°x 47°)
				00 (Diffused)
				07 (Asym. Ww)
8 W DC - 9 W AC				
SA	**80557** HC	**M**	877 - 470	**06** (9°)
		W	945 - 471	
		N	1013 - 507	
8 W DC - 9 W AC				
SA	**76721** HC	**M**	1041 - 694	**15** (14°)
		W	1087 - 725	**30** (24°)
		N	1114 - 743	**60** (43°)

Recessed casing: (pag 776)

Suelo_RX Pro | powerLED





2500 kg III IK10 IP68


		Cct	lm S - lm D	Opt
C.C. - 630 mA - 8 W DC				
SA	**80561**	**M**	877 - 579	**06** (6°)
SA	**80562** HC	**W**	945 - 580	
SA	**80563** DL	**N**	1013 - 621	
C.C. - 220 mA - 8 W DC				
SA	**76713**	**M**	1041 - 868	**15** (15°)
SA	**76714** HC	**W**	1087 - 906	**30** (26°)
		N	1114 - 929	**60** (50°)


Electronics: 630 mA **BU** - 220 mA **BF** (pag 775) | Recessed casing: (pag 776)

		Cct	lm S - lm D	Opt
C.V. - 24 V DC - 9 W DC				
SA	**80567**	**M**	877 - 579	**06** (6°)
SA	**80568** HC	**W**	945 - 580	
SA	**80569** DL	**N**	1013 - 621	
C.V. - 24 V DC - 9 W DC				
SA	**76715**	**M**	1265 - 868	**15** (15°)
SA	**76716** HC	**W**	1320 - 906	**30** (26°)
		N	1354 - 929	**60** (50°)

Electronics: **DC** (pag 775) | Recessed casing: (pag 776)

Suelo_RX Pro | powerLED | 220-240 V AC







2500 kg IK10 IP68

	Cct	lm S - lm D	Opt
8 W DC - 9 W AC			
SA **80573**	**M**	877 - 579	**06** (6°)
BM **82542**	**W**	945 - 580	
SA **80574** HC	**N**	1013 - 621	
BM **82543** HC			
8 W DC - 9 W AC			
SA **76206**	**M**	1041 - 868	**15** (15°)
BM **76722**	**W**	1087 - 906	**30** (26°)
SA **76723** HC	**N**	1114 - 929	**60** (50°)
BM **76724** HC			

Recessed casing: (pag 776)

Suelo_RXJ | powerLED





2500 kg IK10 IP68


	Cct	lm S - lm D	Opt
C.C. - 630 mA - 8 W DC			
SA **80577**	**M**	760 - 558	**20** (20°)
	W	760 - 558	**30** (30°)
	N	821 - 603	**60** (60°)


Electronics: **BU** (pag 775) | Recessed casing: (pag 776)

C.V. - 24 V DC - 9 W DC			
SA **80579**	**M**	760 - 558	**20** (20°)
	W	760 - 558	**30** (30°)
	N	821 - 603	**60** (60°)

Electronics: **DC** (pag 775) | Recessed casing: (pag 776)

Suelo_RXJ | powerLED | 220-240 V AC







2500 kg IK10 IP68

	Cct	lm S - lm D	Opt
8 W DC - 9 W AC			
SA **80581**	**M**	760 - 558	**20** (20°)
BM **82545**	**W**	760 - 558	**30** (30°)
	N	821 - 603	**60** (60°)

Recessed casing: (pag 776)

Suelo_RX Pro | Ww | arrayLED | 220-240 V AC







2500 kg IK10 IP68

	Cct	lm S - lm D	Opt
13 W DC - 15 W AC			
SA **80612**	**M**	1743 - 1185	**07** (Asymmetric Ww)
BM **82547**	**W**	1863 - 1266	
DALI	**N**	1863 - 1266	
SA **81110**			

Recessed casing: (pag 776)

Suelo_RX | arrayLED | 220-240 V AC






Installation with placing flange


5000 kg IK10 IP68 NEW

		Cct	lm S - lm D	Opt
13 W DC - 15 W AC				
SA **76122**		**M**	1676 - 1325	**10** (10°)
SA **76123**	HC	**W**	1750 - 1381	
SA **76124**	DL	**N**	1794 - 1421	
DALI				
SA **76131**				
SA **76132**	HC			
SA **76133**	DL			
16 W DC - 18 W AC				
SA **76119**		**M**	2528 - 1718	**15** (16°)
SA **76120**	HC	**W**	2634 - 1790	**30** (37°)
SA **76121**	DL	**N**	2704 - 1844	**50** (53°)
DALI				
SA **76128**				
SA **76129**	HC			
SA **76130**	DL			
19 W DC - 22 W AC				
SA **76116**		**M**	2773 - 2117	**15** (16°)
SA **76117**	HC	**W**	2889 - 2205	**30** (37°)
SA **76118**	DL	**N**	2966 - 2230	**50** (53°)
DALI				
SA **76125**				
SA **76126**	HC			
SA **76127**	DL			

Recessed casing & accessories: (pag 776-777)

Suelo_RX | arrayLED | RGBW | 24/48 V DC







RGBW Connector

Installation with placing flange

5000 kg III IK10 IP68 NEW DMX RDM RGBW


	Fin	Cct	Opt
C.V. - 12,6 W DC			
C00601	SA	**H** RGBW (2700 K)	**SP** (10°÷ 19°)
		V RGBW (3000 K)	**ML** (30°÷ 39°)
		Q RGBW (4000 K)	**WF** (50°÷ 70°)


Electronics: **AM12** (pag 775) | Recessed casing: (pag 776)

	Fin	Cct	Opt
C.V. - 25 W DC			
C00920	SA	**H** RGBW (2700 K)	**SP** (10°÷ 19°)
		V RGBW (3000 K)	**ML** (30°÷ 39°)
		Q RGBW (4000 K)	**WF** (50°÷ 70°)

Electronics: **AM12** (pag 775) | Recessed casing: (pag 776)

Suelo_RX | Ww | arrayLED | 220-240 V AC






Installation with placing flange


2500 kg IK10 IP68

	Cct	lm S - lm D	Opt
25 W DC - 27 W AC			
SA **80616**	**M**	3167 - 1408	**07** (Asymmetric Ww)
DALI	**W**	3401 - 1467	
SA **81734**	**N**	3667 - 1548	

Recessed casing: (pag 776)

Suelo_RXJ | arrayLED | 220-240 V AC






Installation with placing flange


5000 kg IK10 IP68 NEW

		Cct	lm S - lm D	Opt
13 W DC - 15 W AC				
SA **76138**		**M**	1676 - 1289	**10** (11°)
SA **76139**	HC	**W**	1750 - 1344	
DALI		**N**	1794 - 1383	
SA **76144**				
SA **76145**	HC			
16 W DC - 18 W AC				
SA **76136**		**M**	2528 - 1633	**15** (16°)
SA **76137**	HC	**W**	2634 - 1702	**30** (37°)
DALI		**N**	2704 - 1753	**50** (52°)
SA **76142**				
SA **76143**	HC			
19 W DC - 22 W AC				
SA **76134**		**M**	2773 - 2013	**15** (16°)
SA **76135**	HC	**W**	2889 - 2097	**30** (37°)
DALI		**N**	2966 - 2121	**50** (52°)
SA **76140**				
SA **76141**	HC			

Recessed casing & accessories: (pag 776-777)

Suelo_RXJ | arrayLED | RGBW | 24/48 V DC







RGBW Connector

Installation with placing flange


5000 kg III IK10 IP68 NEW DMX RDM RGBW

	Fin	Cct	Opt
C.V. - 12,6 W DC			
C00576	SA	**H** RGBW (2700 K)	**SP** (10°÷ 19°)
		V RGBW (3000 K)	**ML** (30°÷ 39°)
		Q RGBW (4000 K)	**WF** (50°÷ 70°)

Electronics: **AM12** (pag 775) | Recessed casing: (pag 776)


C.V. - 25 W DC			
C00922	SA	**H** RGBW (2700 K)	**SP** (10°÷ 19°)
		V RGBW (3000 K)	**ML** (30°÷ 39°)
		Q RGBW (4000 K)	**WF** (50°÷ 70°)


Electronics: **AM12** (pag 775) | Recessed casing: (pag 776)



Finishes	Cct				Accessories	Inground
SA Steel/Aluminium	**M** 2700	**N** 4000	**V** RGBW (3000)	HC Honeycomb		
	W 3000	**H** RGBW (2700)	**Q** RGBW (4000)			

Suelo_RXF | arrayLED | 220-240 V AC






Installation with flush flange


5000 kg IK10 IP68 NEW

		Cct	lm S - lm D	Opt
13 W DC - 15 W AC				
SA **76152**		**M**	1676 - 1325	**10** (10°)
SA **76153**	HC	**W**	1750 - 1381	
SA **76154**	DL	**N**	1794 - 1421	
DALI				
SA **76161**				
SA **76162**	HC			
SA **76163**	DL			
16 W DC - 18 W AC				
SA **76149**		**M**	2528 - 1718	**15** (16°)
SA **76150**	HC	**W**	2634 - 1790	**30** (37°)
SA **76151**	DL	**N**	2704 - 1844	**50** (53°)
DALI				
SA **76158**				
SA **76159**	HC			
SA **76160**	DL			
19 W DC - 22 W AC				
SA **76146**		**M**	2773 - 2117	**15** (16°)
SA **76147**	HC	**W**	2889 - 2205	**30** (37°)
SA **76148**	DL	**N**	2966 - 2230	**50** (53°)
DALI				
SA **76155**				
SA **76156**	HC			
SA **76157**	DL			

Recessed casing & accessories: (pag 776-777)

Suelo_RXF | arrayLED | RGBW | 24/48 V DC







RGBW Connector

Installation with flush flange


5000 kg III IK10 IP68 NEW DMX RDM RGBW

	Fin	Cct	Opt
C.V. - 12,6 W DC			
C00604	SA	**H** RGBW (2700 K)	**SP** (10°÷ 19°)
		V RGBW (3000 K)	**ML** (30°÷ 39°)
		Q RGBW (4000 K)	**WF** (50°÷ 70°)

Electronics: **AM12** (pag 775) | Recessed casing: (pag 776)


C.V. - 25 W DC			
C00924	SA	**H** RGBW (2700 K)	**SP** (10°÷ 19°)
		V RGBW (3000 K)	**ML** (30°÷ 39°)
		Q RGBW (4000 K)	**WF** (50°÷ 70°)

Electronics: **AM12** (pag 775) | Recessed casing: (pag 776)



Suelo_RXFJ | arrayLED | 220-240 V AC





Installation with flush flange


5000 kg | IK10 | IP68 | NEW

		Cct	lm S - lm D	Opt
13 W DC - 15 W AC				
SA **76168**		**M**	1676 - 1289	**10** (11°)
SA **76169**	HC	**W**	1750 - 1344	
DALI		**N**	1794 - 1383	
SA **76174**				
SA **76175**	HC			
16 W DC - 18 W AC				
SA **76166**		**M**	2528 - 1633	**15** (16°)
SA **76167**	HC	**W**	2634 - 1702	**30** (37°)
DALI		**N**	2704 - 1753	**50** (52°)
SA **76172**				
SA **76173**	HC			
19 W DC - 22 W AC				
SA **76164**		**M**	2773 - 2013	**15** (16°)
SA **76165**	HC	**W**	2889 - 2097	**30** (37°)
DALI		**N**	2966 - 2121	**50** (52°)
SA **76170**				
SA **76171**	HC			

Recessed casing & accessories: (pag 776-777)

Suelo_RXFJ | arrayLED | RGBW | 24/48 V DC







RGBW Connector

Installation with flush flange


5000 kg | III | IK10 | IP68 | NEW | DMX RDM | RGBW

	Fin	Cct	Opt
C.V. - 12,6 W DC			
C00606	SA	**H** RGBW (2700 K)	**SP** (10°÷ 19°)
		V RGBW (3000 K)	**ML** (30°÷ 39°)
		Q RGBW (4000 K)	**WF** (50°÷ 70°)

Electronics: **AM12** (pag 775) | Recessed casing: (pag 776)


C.V. - 25 W DC			
C00926	SA	**H** RGBW (2700 K)	**SP** (10°÷ 19°)
		V RGBW (3000 K)	**ML** (30°÷ 39°)
		Q RGBW (4000 K)	**WF** (50°÷ 70°)


Electronics: **AM12** (pag 775) | Recessed casing: (pag 776)



Finishes	Cct				Accessories	
SA Steel/Aluminium	**M** 2700	**N** 4000	**V** RGBW (3000)		HC Honeycomb	
	W 3000	**H** RGBW (2700)	**Q** RGBW (4000)			

Suelo_RX | arrayLED | 220-240 V AC





Installation with placing flange

5000 kg


		Cct	lm S - lm D	Opt
44,2 W DC - 48,2 W AC				
SA **83925**		**M**	6832 - 4374	**15** (19°)
DALI		**W**	7045 - 4505	**30** (25°)
SA **83928**		**N**	7305 - 4678	**50** (61°)
SA **83926**	HC	**M**	6832 - 3391	**15** (17°)
DALI		**W**	7045 - 3489	**30** (23°)
SA **83929**	HC	**N**	7305 - 3617	**50** (47°)
SA **83927**	DL	**M**	6832 - 2993	**15** (17°)
DALI		**W**	7045 - 3082	**30** (22°)
SA **83930**	DL	**N**	7305 - 3202	
SA **83937**		**M**	4849 - 3209	**06** (7°)
DALI		**W**	4849 - 3209	
SA **83938**		**N**	5235 - 3465	


5000 kg

	Cct	Opt
RGBW - 37W DC - 41W AC		
SA **83941**	**V** RGBW (3000 K)	**15** (10°÷ 19°)
		30 (30°÷ 39°)
		50 (50°÷ 70°)


Electronics: **AM4** (pag 775) | Recessed casing, extension cables: (pag 776-777)

Suelo_RXJ | arrayLED | 220-240 V AC





Installation with placing flange



5000 kg


		Cct	lm S - lm D	Opt
44,2 W DC - 48,2 W AC				
SA **82713**		**M**	6832 - 4374	**15** (19°)
DALI		**W**	7045 - 4505	**30** (25°)
SA **82716**		**N**	7305 - 4678	**50** (61°)
SA **82714**	HC	**M**	6832 - 3391	**15** (17°)
DALI		**W**	7045 - 3489	**30** (23°)
SA **82717**	HC	**N**	7305 - 3617	**50** (47°)
SA **82715**	DL	**M**	6832 - 2993	**15** (17°)
DALI		**W**	7045 - 3082	**30** (22°)
SA **82718**	DL	**N**	7305 - 3202	
SA **82719**		**M**	4849 - 3209	**06** (7°)
DALI		**W**	4849 - 3209	
SA **82720**		**N**	5235 - 3465	


5000 kg

	Cct	Opt
RGBW - 37W DC - 41W AC		
SA **82723**	**V** RGBW (3000 K)	**15** (10°÷ 19°)
		30 (30°÷ 39°)
		50 (50°÷ 70°)

Electronics: **AM4** (pag 775) | Recessed casing, extension cables: (pag 776-777)

Suelo_RXF | arrayLED | 220-240 V AC





Installation with flush flange

5000 kg


		Cct	lm S - lm D	Opt
44,2 W DC - 48,2 W AC				
SA **83931**		**M**	6832 - 4374	**15** (19°)
DALI		**W**	7045 - 4505	**30** (25°)
SA **83934**		**N**	7305 - 4678	**50** (61°)
SA **83932**	HC	**M**	6832 - 3391	**15** (17°)
DALI		**W**	7045 - 3489	**30** (23°)
SA **83935**	HC	**N**	7305 - 3617	**50** (47°)
SA **83933**	DL	**M**	6832 - 2993	**15** (17°)
DALI		**W**	7045 - 3082	**30** (22°)
SA **83936**	DL	**N**	7305 - 3202	
SA **83939**		**M**	4849 - 3209	**06** (7°)
DALI		**W**	4849 - 3209	
SA **83940**		**N**	5235 - 3465	


5000 kg

	Cct	Opt
RGBW - 37W DC - 41W AC		
SA **83942**	**V** RGBW (3000 K)	**15** (10°÷ 19°)
		30 (30°÷ 39°)
		50 (50°÷ 70°)


Electronics: **AM4** (pag 775) | Recessed casing, extension cables: (pag 776-777)

Suelo_RXFJ | arrayLED | 220-240 V AC





Installation with flush flange



5000 kg


		Cct	lm S - lm D	Opt
44,2 W DC - 48,2 W AC				
SA **83776**		**M**	6832 - 4374	**15** (19°)
DALI		**W**	7045 - 4505	**30** (25°)
SA **83779**		**N**	7305 - 4678	**50** (61°)
SA **83777**	HC	**M**	6832 - 3391	**15** (17°)
DALI		**W**	7045 - 3489	**30** (23°)
SA **83780**	HC	**N**	7305 - 3617	**50** (47°)
SA **83778**	DL	**M**	6832 - 2993	**15** (17°)
DALI		**W**	7045 - 3082	**30** (22°)
SA **83781**	DL	**N**	7305 - 3202	
SA **82721**		**M**	4849 - 3209	**06** (7°)
DALI		**W**	4849 - 3209	
SA **82722**		**N**	5235 - 3465	


5000 kg

	Cct	Opt
RGBW - 37W DC - 41W AC		
SA **82724**	**V** RGBW (3000 K)	**15** (10°÷ 19°)
		30 (30°÷ 39°)
		50 (50°÷ 70°)

Electronics: **AM4** (pag 775) | Recessed casing, extension cables: (pag 776-777)

Suelo_Brass | powerLED | 220-240 V AC





2000 kg

IK09 IP68

		Cct	lm S - lm D	Opt
8 W DC - 9 W AC				
BS **82266**		**M**	1132 - On Req	**06** (12°)
		W	1182 - On Req	
		N	1212 - On Req	
BS **82267**		**M**	1132 - On Req	**15** (15°)
		W	1182 - On Req	**35** (25°)
		N	1212 - On Req	**60** (48°)
BS **82268**	HC	**M**	1132 - On Req	**06** (11°)
		W	1182 - On Req	
		N	1212 - On Req	
BS **82269**	HC	**M**	1132 - On Req	**15** (14°)
		W	1182 - On Req	**35** (22°)
		N	1212 - On Req	**60** (39°)

Recessed casing: (pag 776)



Electronics

AM4

DMX
Controllers
Pag. 963

C-E700026
DMX/RDM addresser

98986
120 Ohm DMX line closure

98985/99390
Splitter ALLinONE Start & Continuity
Pag. 972

BD IP67

89420
ON/OFF
1 - 2 art.
74 x 65 x h 27

C-E200008
ON/OFF
3 - 6 art.
135 x 26 x h 26
35

99186
ON/OFF
6 - 12 art.
117 x 92 x h 38

C-E200002
DALI/PUSH
5 - 12 art.
125 x 45 x h 30
55

BU

C-E200008
ON/OFF
1 art.
135 x 26 x h 26
35

99186
ON/OFF
2 - 3 art.
117 x 92 x h 38

C-E200002
DALI/PUSH
2 - 3 art.
125 x 45 x h 30
55

CF

C-E700003+C-W600001
Dimmer RF
6 - 12 art.
175 x 45 x h 27
52

C-E500011
Dimmer DMX
6 - 12 art.
107 x 96 x h 39

DMX
Controllers
Pag. 963

Driver CV
CV 48V
Pag. 950-951

Switching
CV 48V
Pag. 945-946

DC

89179
ON/OFF
1 - 2 art.
92 x 117 x h 38

89359
ON/OFF
1 - 5 art.
115 x 140 x h 50

99331
ON/OFF
1 - 15 art.
158 x 60 x h 35

99660
Dimmer
DALI - 0/1-10V
149 x 37 x h 31
48

83042
Dimmer DALI/PUSH
0/1-10V
164 x 38 x h 25
45

+ driver 24V DC

99331 150W
1-11 art.
70

99786 240W
1-18 art.
81

FQ IP40

C-E100046
ON/OFF
1 - 6 art.
130 x 38 x h 28
48

C-E100047
DALI
1 - 3 art.
140 x 36 x h 20
40

C-E100033
ON/OFF
4 - 12 art.
138 x 44 x h 23
50

C-E100034
DALI/PUSH
4 - 12 art.
138 x 44 x h 23
50

AM12

99784
ON/OFF
150W CV 48V
219 x 63 x h 35
80

DMX
Controllers
Pag. 963

C-E700026
DMX/RDM addresser

C-W400004
IN&OUT ALLinONE

98985/99390
Splitter ALLinONE Start & Continuity
Pag. 972

98986
120 Ohm DMX line closure

BF

99342
ON/OFF
1 art.
100 x 80 x h 31

C-E200005
DALI/PUSH
1 art.
125 x 45 x h 30
55

BW

C-E200007
ON/OFF
1 - 2 art.
135 x 26 x h 26
35

99185
ON/OFF
2 - 4 art.
117 x 92 x h 38

C-E200003
DALI/PUSH
2 - 4 art.
125 x 45 x h 30
55

DB

89488
ON/OFF
1 - 2 art.
80 x 100 x h 31

89179
ON/OFF
1 - 4 art.
92 x 117 x h 38

89359
ON/OFF
1 - 9 art.
115 x 140 x h 50

99660
Dimmer
DALI - 0/1-10V
149 x 37 x h 31
48

83042
Dimmer DALI/PUSH
0/1-10V
164 x 38 x h 25
45

+ driver 24V DC

99331 150W
1-21 art.
70

99786 240W
1-33 art.
81

DL

89488
ON/OFF
1 - 4 art.
80 x 100 x h 31

89179
ON/OFF
1 - 7 art.
92 x 117 x h 38

89359
ON/OFF
1 - 14 art.
115 x 140 x h 50

99660
Dimmer
DALI - 0/1-10V
149 x 37 x h 31
48

83042
Dimmer DALI/PUSH
0/1-10V
164 x 38 x h 25
45

+ driver 24V DC

99331 150W
1-35 art.
70

99786 240W
1-56 art.
81

Recessed casings (R collection)




ABS 84918 Recessed casings

suitable for: Suelo_R Ø30 h44




ABS 84936 Recessed casings

suitable for: Suelo_R Ø64 h64
Suelo_RJ Ø64 h64




ABS 99680 Recessed casings

suitable for: Suelo_R /_R Pro /_RJ Pro Ø92 h112



ABS 83328 * Recessed casings

suitable for: Suelo_R /_RJ Ø185 h186
Suelo_RF /_RFJ Ø180 h186
*To be completed with: 83329 or 83331.




ABS 99684 Recessed casings

suitable for: Suelo_R Pro Ø35 h67



ABS 84935 Recessed casings

suitable for: Suelo_R /_R Pro /_RJ Ø64 h129



ABS 99681 Recessed casings


suitable for: Suelo_R /_R Pro /_RJ Pro Ø92 h152

Recessed casings (RX collection)



ABS 99685 Recessed casings

suitable for: Suelo_RX Pro Ø50 h67



ABS 98122 Recessed casings

suitable for: Suelo_RX /_RX Pro /_RXJ Ø112 h152




ABS 83096 * Recessed casings

suitable for: Suelo_RX /_RXJ Ø315 h216,5
Suelo_RXF /_RXFJ Ø308 h216,5
*To be completed with: 83097 or 83098.




PVC 99794 Recessed casings

suitable for: Suelo_RX Ww Ø232 h167




ABS 98121 Recessed casings

suitable for: Suelo_RX /_RX Pro /_RXJ Ø112 h112



ABS 83328 * Recessed casings

suitable for: Suelo_RX /_RXJ Ø185 h186
Suelo_RXF /_RXFJ Ø180 h186
*To be completed with: 83329 or 83331.



ABS 84932 Recessed casings

suitable for: Suelo_RX Pro Ww Ø170 h204


Recessed casings (Brass collection)



ABS 84900 Recessed casings


suitable for: Suelo_Brass Ø120 h119

Accessories and extension cables




POL 83097 Template for installation with placing flange

suitable for: 83096




POL 83098 Template for installation with flush flange

suitable for: 83096




ZN 93099 Caseback

suitable for: 83096




ZN 83330 Caseback

suitable for: 83328



POL 83331 Template for installation with placing flange

suitable for: 83328



POL 83329 Template for installation with flush flange

suitable for: 83328



AllinOne DMX 190-250V AC

BB 98662 M. / F. 6 pin (L 1 m)

BB 98663 M. / F. 6 pin (L 5 m)

suitable for: Suelo RGBW 12,6W / 25 W / 37W



AllinOne DMX 190-250V AC

BB 98660 F. 6 pin (L 1m)

BB 98661 F. 6 pin (L 5m)

suitable for: Suelo RGBW 12,6W / 25 W / 37W



PVC 98985 ALLinONE splitter power/DMX_Start splitter

suitable for: Suelo RGBW 12,6W / 25 W / 37W

Pag. 972



PVC 99390 ALLinONE splitter power/DMX_Continuity splitter

suitable for: Suelo RGBW 12,6W / 25 W / 37W

Pag. 972



BB C-W400004 T-shaped connector for parallel connection

suitable for: Suelo_RGBW 12,6W / 25W



BB 98986 ALLinONE splitter power/DMX _ DMX line closure adapter

suitable for: Suelo RGBW 12,6W / 37W

Pag. 972



FRANTOIO CENTUMBRIE
Agello, Perugia (Italy)

Architectural design:
Architect Gianmarco Balucani

System and lighting design:
Prait, Simone Suriani

Designer:
Miriam Cinaglia

Photography:
Matteo Canestraro


SUELO316

AISI 316L stainless steel body.
AISI 316L stainless steel flange.






Which can be easily adjusted using a slotted screwdriver on the relevant screw, the optic group can be angled from -30°/+30°.



Suelo316_R | powerLED | 350 mA | 1 W DC






2500 kg | C.C. | IK09 | IP68

	Cct	lm S - lm D	Opt
SE 80432	M	145 - 105	20 (26°)
	W	154 - 112	35 (37°)
	N	165 - 120	

Electronics: **BB** (pag 783) | Recessed casing: (pag 783)

Suelo316_R | arrayLED | 350 mA | 3 W DC






2500 kg | C.C. | IK08 | IP68 | NEW

	Cct	lm S - lm D	Opt
SE 76036	M	482 - 377	15 (15°)
	W	500 - 391	30 (23°)
	N	526 - 411	45 (35°)

Electronics: **BN** (pag 783) | Recessed casing: (pag 783)

Suelo316_R | arrayLED | 220-240 V AC | 3 W DC - 3,5 W AC






2500 kg | C.C. | IK08 | IP68 | NEW

	Cct	lm S - lm D	Opt
SE 76038	M	482 - 377	15 (15°)
	W	500 - 391	30 (23°)
	N	526 - 411	45 (35°)

Recessed casing: (pag 783)

Suelo316_RJ | arrayLED | 350 mA | 3 W DC






2500 kg | C.C. | IK08 | IP68 | NEW

	Cct	lm S - lm D	Opt
SE 76037	M	482 - 280	15 (19°)
	W	500 - 291	30 (28°)
	N	526 - 306	45 (55°)

Electronics: **BN** (pag 783) | Recessed casing: (pag 783)

Suelo316_RJ | arrayLED | 220-240 V AC | 3 W DC - 3,5 W AC






2500 kg | C.C. | IK08 | IP68 | NEW

	Cct	lm S - lm D	Opt
SE 76039	M	482 - 280	15 (19°)
	W	500 - 291	30 (28°)
	N	526 - 306	45 (55°)

Recessed casing: (pag 783)

Suelo316_RX | powerLED | 220-240 V AC | 2 W DC - 3 W AC





2500 kg | IK09 | IP67 | ID


	Cct	lm S - lm D	Opt
SE 83588	M	233 - 131	08 (10°)
	W	249 - 149	15 (21°)
	N	266 - 159	30 (26°)
			60 (57°)
			00 (Diffused)


Recessed casing: (pag 783)

ID Driver on board

Finishes	Cct			
SE Stainless Steel	**M**	2700	**N**	4000
	W	3000		

Suelo316_RX | arrayLED | 220 mA | 7,2 W DC






3000 kg | C.C. | IK10 | IP68 | NEW

	Cct	lm S - lm D	Opt
SE **76040**	**M**	1080 - 705	**15** (16°)
	W	1126 - 736	**30** (28°)
	N	1188 - 754	**60** (60°)

Electronics: **BF** (pag 783) | Recessed casing: (pag 783)

Suelo316_RX | arrayLED | 220-240 V AC | 5,4 W DC - 7W AC







3000 kg | IK10 | IP68 | NEW

	Cct	lm S - lm D	Opt
SE **76042**	**M**	773 - 545	**15** (16°)
	W	806 - 569	**30** (28°)
	N	851 - 584	**60** (60°)

Recessed casing: (pag 783)

Suelo316_RXJ | arrayLED | 220 mA | 7,2 W DC







3000 kg | C.C. | IK10 | IP68 | NEW

	Cct	lm S - lm D	Opt
SE **76041**	**M**	1080 - 685	**15** (22°)
	W	1126 - 715	**30** (38°)
	N	1188 - 733	**60** (66°)

Electronics: **BF** (pag 783) | Recessed casing: (pag 783)

Suelo316_RXJ | arrayLED | 220-240 V AC | 5,4 W DC - 7W AC







3000 kg | IK10 | IP68 | NEW

	Cct	lm S - lm D	Opt
SE **76043**	**M**	773 - 530	**15** (22°)
	W	806 - 553	**30** (38°)
	N	851 - 567	**60** (66°)

Recessed casing: (pag 783)

Suelo316_RX | arrayLED | 220-240 V AC | 16,2 W DC - 18 W AC






3000 kg | IK10 | IP68 | NEW

	Cct	lm S - lm D	Opt
SE **76048**	**M**	2304 - 1725	**15** (15°)
	W	2401 - 1797	**30** (35°)
DALI	**N**	2535 - 1845	**60** (50°)
SE **76074**			

Recessed casing: (pag 783)

Suelo316_RXJ | arrayLED | 220-240 V AC | 16,2 W DC - 18 W AC





3000 kg | IK10 | IP68 | NEW

	Cct	lm S - lm D	Opt
SE **76049**	**M**	2304 - 1884	**15** (21°)
	W	2401 - 1963	**30** (32°)
DALI	**N**	2535 - 2015	**60** (53°)
SE **76075**			

Recessed casing: (pag 783)





Installation with placing flange (R / RJ / RX / RXJ)

Finishes **Cct**

SE Stainless Steel **M** 2700 **N** 4000 **W** 3000

Suelo316_RXF | arrayLED | 220 mA | 7,2 W DC






3000 kg | C.C. | IK10 | IP68 | NEW

	Cct	lm S - lm D	Opt
SE 76044	M	1080 - 705	15 (16°)
	W	1126 - 736	30 (28°)
	N	1188 - 754	60 (60°)

Electronics: **BF** (pag 783) | Recessed casing: (pag 783)

Suelo316_RXF | arrayLED | 220-240 V AC | 5,4 W DC - 7W AC






3000 kg | C.C. | IK10 | IP68 | NEW

	Cct	lm S - lm D	Opt
SE 76046	M	773 - 545	15 (16°)
	W	806 - 569	30 (28°)
	N	851 - 584	60 (60°)

Recessed casing: (pag 783)

Suelo316_RXFJ | arrayLED | 220 mA | 7,2 W DC






3000 kg | C.C. | IK10 | IP68 | NEW

	Cct	lm S - lm D	Opt
SE 76045	M	1080 - 685	15 (22°)
	W	1126 - 715	30 (38°)
	N	1188 - 733	60 (66°)

Electronics: **BF** (pag 783) | Recessed casing: (pag 783)

Suelo316_RXFJ | arrayLED | 220-240 V AC | 5,4 W DC - 7 W AC






3000 kg | C.C. | IK10 | IP68 | NEW

	Cct	lm S - lm D	Opt
SE 76047	M	773 - 530	15 (22°)
	W	806 - 553	30 (38°)
	N	851 - 567	60 (66°)

Recessed casing: (pag 783)

Suelo316_RXF | arrayLED | 220-240 V AC | 16,2 W DC - 18 W AC






3000 kg | IK10 | IP68 | NEW

	Cct	lm S - lm D	Opt
SE 76050	M	2304 - 1725	15 (15°)
	W	2401 - 1797	30 (35°)
DALI	N	2535 - 1845	60 (50°)
SE 76076			

Recessed casing: (pag 783)

Suelo316_RXFJ | arrayLED | 220-240 V AC | 16,2 W DC - 18 W AC






3000 kg | IK10 | IP68 | NEW

	Cct	lm S - lm D	Opt
SE 76051	M	2304 - 1884	15 (21°)
	W	2401 - 1963	30 (32°)
DALI	N	2535 - 2015	60 (53°)
SE 76077			

Recessed casing: (pag 783)



Installation with flush flange (RXF / RXFJ)

Finishes

SE Stainless Steel

Cct

M 2700 **N** 4000
W 3000



Electronics

BB

89419	89421	C-E200006	C-E200004
ON/OFF	ON/OFF	ON/OFF	DALI/PUSH
1 - 2 art.	3 - 6 art.	6 - 12 art.	5 - 12 art.
74 x 65 x h 27	74 x 65 x h 27	135 x 26 x h 26	125 x 45 x h 30
		35	55

BN

89421	C-E200006	C-E200004
ON/OFF	ON/OFF	DALI/PUSH
1 - 2 art.	2 - 4 art.	2 - 4 art.
74 x 65 x h 27	135 x 26 x h 26	125 x 45 x h 30
	35	55

BF

99342	C-E200005
ON/OFF	DALI/PUSH
1 art.	1 art.
100 x 80 x h 31	125 x 45 x h 30
	55

Recessed casings R collection



ABS 99676 Recessed casings for installation with placing flange

suitable for: Suelo316_R Ø25 h51



ABS 84936 Recessed casings for installation with placing flange


suitable for: Suelo316_R Ø64 h80
Suelo316_RJ Ø64 h80



ABS 84935 Recessed casings for installation with placing flange


suitable for: Suelo316_R Ø64 h123
Suelo316_RJ Ø64 h123

Recessed casings RX / RXF collection



ABS 99685 Recessed casings for installation with placing flange

suitable for: Suelo316_RX Ø50 h73



ABS C-C100018 Recessed casings for installation with placing flange

suitable for: Suelo316_RX /_RXJ Ø120 h89
Suelo316_RX /_RXJ Ø120 h132



ABS 98134 Recessed casings for installation with flush flange

suitable for: Suelo316_RXF /_RXFJ Ø110 h88
Suelo316_RXF /_RXFJ Ø110 h131




ABS 98133 Recessed casings for installation with placing flange or flush flange

suitable for: Suelo316_RX /_RXJ Ø160 h144
Suelo316_RXF /_RXFJ Ø150 h144

Accessories


Connector 2 ways



PVC 84893 IP68 min. 2x0,5 mm^2
max. 2x2,5 mm^2

suitable for: Suelo316

Connector 4 ways



PVC 84894 IP68
max. 4x1,5 mm^2

suitable for: Suelo316



EFFECT LIGHTS



RADISSON HOTEL
Milan (Italy)

Lighting design project:
Deerns

Architectural project:
Studio Marco Piva

Photography:
Andrea Martiradonna



Effect lights range index

Orma

Orma_IB
NEW

789

Orma_AB
NEW

789

Orma_Q
NEW

790

Orma_QF
NEW

790

Xenia

Xenia_A_Blade
NEW

793

Xenia_AF_Blade
NEW

793

Arcada

Arcada

797

Arcada Pro

797

Myia

Myia


799

Loop66

Loop66

801

Pixie

Pixie_PIXEL

803

Paseo

Paseo_PIXEL

805

Paseo_PIXEL Dark

805

Xenia

Xenia_PIXEL

807


ORMA
BLADE


Aluminium body. AISI 316L stainless steel flange.
Extra-clear tempered glass diffuser.





Orma_IB | Blade | powerLED





	Cct	Im S - Im D	Opt
C.C. - 630 mA - 8 W DC			
SA **83644**	**M**	854 - 217	**18** (10°x 131° W.Grazing)
	W	854 - 217	
	N	922 - 234	

Electronics: **BU** (pag 790) | Recessed casings: (pag 791)


C.V. - 24 V DC - 9 W DC			
SA **83645**	**M**	854 - 217	**18** (10°x 131° W.Grazing)
	W	854 - 217	
	N	922 - 234	


Electronics: **DC** (pag 790) | Recessed casings: (pag 791)

	Fin	Cct		Opt
RGBW C.C. - 630 mA - 8 W DC				
C00982	**SA**	**H**	RGBW (2700 K)	**3N** (10°x 131° W.Grazing)
		V	RGBW (3000 K)	
		Q	RGBW (4000 K)	

Electronics: **CF** (pag 790) | Recessed casings & Cables: (pag 791)

Orma_AB | Blade | powerLED





	Cct	Im S - Im D	Opt
C.C. - 630 mA - 8 W DC			
SA **83642**	**M**	854 - 217	**18** (10°x 131° W.Grazing)
	W	854 - 217	
	N	922 - 234	

Electronics: **BU** (pag 790) | Recessed casings: (pag 791)

C.V. - 24 V DC - 9 W DC			
SA **83643**	**M**	854 - 217	**18** (10°x 131° W.Grazing)
	W	854 - 217	
	N	922 - 234	

Electronics: **DC** (pag 790) | Recessed casings: (pag 791)

	Fin	Cct		Opt
RGBW C.C. - 630 mA - 8 W DC				
C00981	**SA**	**H**	RGBW (2700 K)	**3N** (10°x 131° W.Grazing)
		V	RGBW (3000 K)	
		Q	RGBW (4000 K)	

Electronics: **CF** (pag 790) | Recessed casings & Cables: (pag 791)

Orma family

Orma_C _QC



440-445

Orma_IJ _AJ _Q_QF



659-660

Orma_I _A



719-727

Orma_F _FO



730-734

Orma_Q _QF



735-741



Finishes


SA Steel Aluminium


Cct

M 2700 **N** 4000 **V** RGBW 3000
W 3000 **H** RGBW 2700 **Q** RGBW 4000

Effect lights

Orma_Q | Blade | powerLED





2000 kg

	Fin	Cct	lm S - lm D	Opt
C.C. - 630 mA - 8 W DC				
C00966	**SA**	**M**	854 - 217	**3N** (10°x 131° W.Grazing)
		W	854 - 217	
		N	922 - 234	

Electronics: **BU** (pag 790) | Recessed casings: (pag 791)

C.V. - 24 V - 9 W DC				
C00967	**SA**	**M**	854 - 217	**3N** (10°x 131° W.Grazing)
		W	854 - 217	
		N	922 - 234	


Electronics: **DC** (pag 790) | Recessed casings: (pag 791)


2000 kg

	Fin	Cct	Opt
RGBW C.C. - 630 mA - 8 W DC			
C00980	**SA**	**H** RGBW (2700 K)	**3N** (10°x 131° W.Grazing)
		V RGBW (3000 K)	
		Q RGBW (4000 K)	

Electronics: **CF** (pag 790) | Recessed casings & Cables: (pag 791)

Orma_QF | Blade | powerLED





2000 kg

	Fin	Cct	lm S - lm D	Opt
C.C. - 630 mA - 8 W DC				
C00964	**GA**	**M**	854 - 217	**3N** (10°x 131° W.Grazing)
		W	854 - 217	
		N	922 - 234	

Electronics: **BU** (pag 790) | Recessed casings: (pag 791)

C.V. - 24 V - 9 W DC				
C00965	**GA**	**M**	854 - 217	**3N** (10°x 131° W.Grazing)
		W	854 - 217	
		N	922 - 234	

Electronics: **DC** (pag 790) | Recessed casings: (pag 791)

2000 kg

	Fin	Cct	Opt
RGBW C.C. - 630 mA - 8 W DC			
C00978	**GA**	**H** RGBW (2700 K)	**3N** (10°x 131° W.Grazing)
		V RGBW (3000 K)	
		Q RGBW (4000 K)	

Electronics: **CF** (pag 790) | Recessed casings & Cables: (pag 791)

Electronics

BU

C-E200008	99186	C-E200002
ON/OFF	ON/OFF	DALI/PUSH
1 art.	2 - 3 art.	2 - 3 art.
135 x 26 x h 26	117 x 92 x h 38	125 x 45 x h 30
35		55

DC

89179	89359	99331	99660	83042	+ driver 24V DC	
ON/OFF	ON/OFF	ON/OFF	Dimmer	Dimmer DALI/PUSH	99331 150W	99786 240W
1 - 2 art.	1 - 5 art.	1 - 15 art.	DALI - 0/1-10V	0/1-10V	1-11 art.	1-18 art.
92 x 117 x h 38	115 x 140 x h 50	158 x 60 x h 35	149 x 37 x h 31	164 x 38 x h 25		
			48	45	70	81

CF

C-E700003+C-W600001	C-E500011	DMX	Driver CV	Switching
Dimmer RF	Dimmer DMX	Controllers	CV 48V	CV 48V
6 - 12 art.	6 - 12 art.			
175 x 45 x h 27	107 x 96 x h 39	Pag. 963	Pag. 950-951	Pag. 945-946
52				



Cables

24 V DC / 220-240 V AC | Cable with F-connector



BB **99216** Conn. F.4 pin M12 (L 1 m)
BB **89190** Conn. F.4 pin M12 (L 5 m)
suitable for: Orma RGBW

24 V DC / 220-240 V AC | Cable with M-connector



BB **98476** Conn. M.4 pin M12 (L 1 m)
BB **98477** Conn. M.4 pin M12 (L 5 m)
suitable for: Orma RGBW

24 V DC 220-240 V AC | Extension cable with M+F connectors




BB **98437** Conn M. + F. 4 pin M12 (L 1 m)
BB **98149** Conn M. + F. 4 pin M12 (L 5 m)
BB **89188** Conn M. + F. 4 pin M12 (L 10 m)
suitable for: Orma RGBW

Recessed casings




ABS **99651** Recessed casings
suitable for: Orma_IB / Orma_AB




ABS **C-C100003** Recessed casings
suitable for: Orma_QF 90x90



ABS **99563** Recessed casings with anti-vandalism flange.
suitable for: Orma_AB



ABS **83410** Recessed casings
suitable for: Orma_Q 116x116



ABS **99856** Recessed casings with anti-vandalism flange.
suitable for: Orma_AB



PVC **83235** Suction cup
suitable for: for all Orma

XENIA
BLADE

Aluminium body.



Xenia family



568



Xenia_A_Blade with frame




Xenia_AF_Blade frameless



Xenia_A_Blade | V2 | powerLED





Fin	Cct	lm S - lm D	Opt
500 mA - 6 W DC			
C00690 **AM**	**A**	568 - 222	**3N** (9°x 150° W.Grazing)
	M	604 - 237	
	W	688 - 269	
	N	736 - 288	


Electronics: **BO** (pag 793) | Recessed casings & Accessories: (pag 793)

Fin	Cct	Opt
RGBW - 350 mA - 8 W DC		
C01036 **AM**	**H** RGBW (2700 K)	**3N** (9°x 150° W.Grazing)
	V RGBW (3000 K)	
	Q RGBW (4000 K)	

Electronics: **GB** (pag 793) | Recessed casings & Accessories: (pag 793)

Xenia_AF_Blade | V2 | powerLED





Fin	Cct	lm S - lm D	Opt
500 mA - 6 W DC			
C00691 **AM**	**A**	568 - 222	**3N** (9°x 150° W.Grazing)
	M	604 - 237	
	W	688 - 269	
	N	736 - 288	

Electronics: **BO** (pag 793) | Recessed casings & Accessories: (pag 793)

Fin	Cct	Opt
RGBW - 350 mA - 8 W DC		
C01037 **AM**	**H** RGBW (2700 K)	**3N** (9°x 150° W.Grazing)
	V RGBW (3000 K)	
	Q RGBW (4000 K)	

Electronics: **GB** (pag 793) | Recessed casings & Accessories: (pag 793)

Electronics

BO

C-E200007	99185	C-E200003
ON/OFF 1 art. 135 x 26 x h 26 35	ON/OFF 2 - 3 art. 117 x 92 x h 38	DALI/PUSH 2 - 3 art. 125 x 45 x h 30 55

GB

C-E700003+C-W600001	C-E500014	DMX	Driver CV	Switching
Dimmer RF 3 - 6 art. 175 x 45 x h 27 52	Dimmer DMX 3 - 6 art. 107 x 96 x h 39	Controllers Pag. 963	CV 48V Pag. 950-951	CV 48V Pag. 945-946

Recessed casings & Accessories



AM **99933** Recessed casing 205 mm

suitable for: Xenia_A_Blade
Xenia_AF_Blade



IS **99818** 2 x Fixing springs for false ceiling

suitable for: Xenia_A_Blade



AM **99917** 2 x End caps for recessed casing

suitable for: Xenia_AF_Blade




AM **83188** 2 x Line sealing caps

suitable for: Xenia_A_Blade



IS **98949** 2 x Fixing brackets 46-67 mm

suitable for: Xenia_AF_Blade



IS **C-F400006** 2 x Fixing brackets

suitable for: Xenia_AF_Blade

Finishes	Cct								Effect lights
Anodised Aluminium	**A**	2200	**W**	3000	**H**	RGBW 2700	**Q**	RGBW 4000	
IS Steel	**M**	2700	**N**	4000	**V**	RGBW 3000			



ARIA RETREAT & SPA
Cima di Porlezza, Como (Italy)

Architectural design:
R4M Engineering

Lighting design:
Architect Giorgio Colombo,
Light+Arch Consultancy

Construction:
Quadrio Gaetano Costruzioni S.p.a.

Contract & Custom Lighting:
Bespoke Lighting Solutions

Photo: Andrea Martiradonna




ARCADA

Aluminium body/polycarbonate (Pro).



Arcada | powerLED





IP65 IK08

	Cct	lm S - lm D	Opt
220-240 V AC - 4 W DC - 6 W AC			
WH **95454**	**M**	544 - 394	**18** (18°x 140° W.Grazing)
BB **95612**	**W**	580 - 424	
GG **95619**	**N**	620 - 450	

III C.C. IP65 IK08

	Cct	lm S - lm D	Opt
630 mA - 8 W DC			
WH **95458**	**M**	876 - 636	**18** (18°x 140° W.Grazing)
BB **95616**	**W**	932 - 678	
GG **95623**	**N**	996 - 724	


Electronics: **BU** (pag 797)


III C.C. IP65 IK08 RGB

	Cct		Opt
RGB - 220 mA - 8 W DC			
WH **95749**	**Z**	RGB	**18** (18°x 140° W.Grazing)
BB **95750**			
GG **95751**			

Electronics: **GA** (pag 797)

Arcada Pro | powerLED





IP65 IK08

	Cct	lm S - lm D	Opt
220-240 V AC - 4 W DC - 6 W AC			
WH **84283**	**M**	440 - 102	**18** (4°x 134° W.Grazing)
BB **84284**	**W**	500 - 115	
GG **84285**	**N**	536 - 124	

III C.C. IP65 IK08 RGBW

	Cct		Opt
RGBW - 350 mA - 4 W DC			
WH **84286**	**V**	RGBW (3000 K)	**18** (4°x 134° W.Grazing)
BB **84287**	**Q**	RGBW (4000 K)	
GG **84288**			

Electronics: **CD** (pag 797)





Electronics

BU

C-E200008	99186	C-E200002
ON/OFF	ON/OFF	DALI/PUSH
1 art.	2 - 3 art.	2 - 3 art.
135 x 26 x h 26	117 x 92 x h 38	125 x 45 x h 30
35		55

CD

C-E700003+C-W600001	C-E500014	DMX	Driver CV	Switching
Dimmer RF	Dimmer DMX	Controllers	CV 48V	CV 48V
6 - 12 art.	6 - 12 art.			
175 x 45 x h 27	107 x 96 x h 39	Pag. 963	Pag. 950-951	Pag. 945-946
52				

GA

C-E700003+C-W600001	C-E500015	DMX	Driver CV	Switching
Dimmer RF	Dimmer DMX	Controllers	CV 48V	CV 48V
2 - 3 art.	2 - 3 art.			
175 x 45 x h 27	107 x 96 x h 39	Pag. 963	Pag. 951	Pag. 945-946
52				

Finishes

WH White GG Grey
BB Black

Cct

M 2700 **N** 4000 **Q** RGBW 4000
W 3000 **V** RGBW 3000 **Z** RGB


Effect lights


MYIA

Aluminium body.



Myia | powerLED | 220-240 V AC | 8,4 W DC - 10,5 W AC





IP65 IK05

		Cct	lm S - lm D	Opt
WH	**91596**	**M**	854 - 311	**90** (14°x 85° Wall Grazing)
BB	**91597**	**W**	854 - 311	
GG	**91598**	**N**	922 - 335	



Finishes

WH White GG Grey
BB Black

Cct

M 2700 **N** 4000
W 3000


Effect lights




LOOP66

Aluminium body.


Loop66 | powerLED | 220-240 V AC | 23 W DC - 25 W AC





IP65 IK05

		Cct	lm S - lm D	Opt
WH	**97065**	**M**	2628 - 365	**05** (5°)
BB	**97066**	**W**	2796 - 387	
GG	**97067**	**N**	2988 - 415	
DB	**97357**			



Finishes

WH White
BB Black
GG Grey
DB Dark Brown

Cct

M 2700 **N** 4000
W 3000

Effect lights

801


PIXIE
PIXEL

Powder-coated, open-pore-anodised aluminium body.
Opalescent PMMA diffuser.



Pixie_PIXEL | topLED | 48V DC | 3,5 W DC





C.V. 48V IP67 IK07

	Cct	Opt
GG 83841	Q RGBW (4000 K)	00 (Diffused)

Accessories and cables: (pag 803)

For cables and power supply/control contact Linea Light support service.

Cables

AllinOne SPI 48 V DC | Cables



BB **83201** Conn. M. 4 pin M12 (L 2,5m)
BB **83202** Conn. F. 4 pin M12 (L 2,5m)
suitable for: Pixie_PIXEL

AllinOne SPI 48 V DC | Extension cables



BB **83199** Conn. M+F 4 pin M12 (L 1m)
BB **83200** Conn. M+F 4 pin M12 (L 5m)
suitable for: Pixie_PIXEL

Accessories




IS **98659** 2 xn Fixing bracket
suitable for: Pixie_PIXEL




IS **98654** Fixing bracket
suitable for: Pixie_PIXEL



IS **98655** Fixing bracket
suitable for: Pixie_PIXEL



IS **98653** Swivel fixing bracket
suitable for: Pixie_PIXEL





PALAZZO VECCHIO
Florence (Italy)

Project: Zanon Architetti Associati

Customer:
F - Light in collaboration with
MUSE Firenze (Florence MUSEUMS)

Photo&Video:
Lungimirante Productions

Finishes	Cct	Effect lights
BB Black IS Steel GG Grey	Q RGBW 4000	

PASEO
PIXEL

Polycarbonate body.


Paseo family **Paseo**



558


Paseo_PIXEL | topLED | 24V DC





Paseo_PIXEL Dark | topLED | 48V DC





RGBW Pixel available on request

C.V. IP67 IK08 DMX RDM

	Cct		Opt	
L 576 - 9,5 W DC				
OP **81337**	**Z**	RGB	**00**	(Diffused)
L 1152 - 19,5 W DC				
OP **81338**	**Z**	RGB	**00**	(Diffused)

Recessed casing, accessories & cables: (pag 564-567)

For cables and power supply/control contact Linea Light support service.

C.V. 48V IP67 IK08 DMX RDM

	Cct		Opt	
L 594 - 9,5 W DC				
BB **84217**	**Z**	RGB	**00**	(Diffused)
L 1176 - 19,5 W DC				
BB **84218**	**Z**	RGB	**00**	(Diffused)


Accessories: (pag 805)

For cables and power supply/control contact Linea Light support service.

RGB Pixel

Paseo_PIXEL RGB
Lighting performance & engineering

The i-LèD Paseo PIXEL RGB linea system redefines the surrounding landscape through the creation of dynamic lighting effects. Every single RGB LED can be controlled individually, the available versions are: 576mm/594mm with 32 RGB full-color LEDs, or 1152mm/1176mm with 64 RGB full-color LEDs.



Accessories



IS **Included** Steel fixing brackets included

suitable for: Paseo_PIXEL Dark



IS **83162** Support bracket for wall installation

suitable for: Paseo_PIXEL / Paseo_PIXEL Dark

Finishes
BB Black
IS Steel
OP Opaline

Cct
Z RGB

Effect lights

XENIA
PIXEL


Anodised 6060 aluminium alloy body.



568

Xenia_PIXEL | topLED | 48 V DC | 9,5 W DC





C.V. 48V IP65 IK08 DMX RDM RGB PIXEL


		Cct		Opt	
AM	**82596**	**Z**	RGB	**00**	(Diffused)

Accessories: (pag 807)

For cables and power supply/control contact Linea Light support service.

Xenia_PIXEL | topLED | 48 V DC | 19 W DC





C.V. 48V IP65 IK08 DMX RDM RGB PIXEL

		Cct		Opt	
AM	**82597**	**Z**	RGB	**00**	(Diffused)

Accessories: (pag 807)

For cables and power supply/control contact Linea Light support service.

Accessories



IS **98949** x2 Fixing brackets 46-67 mm


suitable for: Xenia_PIXEL

IS **89045** x2 Fixing brackets 90 mm
IS **89046** x2 Fixing brackets 150 mm
IS **89047** x2 Fixing brackets 300 mm

suitable for: Xenia_PIXEL

AM **83190** Anti-glaring 595 mm
AM **83191** Anti-glaring 1170 mm

suitable for: Xenia_PIXEL



Finishes

AM Anodised Aluminium
IS Steel

Cct

Z RGB



BOLLARDS

PRIVATE VILLA
Castelfranco Veneto, Treviso (Italy)

Architectural design:
Studio Architetti Associati
Giampietro & Stefano Cinel

Photography:
TheStudio



Bollards range index

Lino

Lino



813

Blum

Blum



815

Blum Projector

NEW



815

Blum



816

Blum Spike

NEW



816

Blum Flower




817

Rolling Sky

Rolling Sky


NEW



820

Rolling Sky

NEW



820

Bond Pro

Bond Pro



825

Buzzer

Buzzer



832-835

Buzzer Pro

NEW



832-835

Ryo

Ryo



837

Apache

Apache



839

Peak

Peak



841

LINO



ARIA RETREAT & SPA
Cima di Porlezza, Como (Italy)

Architectural design:
R4M Engineering

Lighting design:
Architect Giorgio Colombo,
Light+Arch Consultancy


Construction:
Quadrio Gaetano Costruzioni S.p.a.

Contract & Custom Lighting:
Bespoke Lighting Solutions

Photo: Andrea Martiradonna

Lino | V2 | powerLED | 24 V DC | 1 W DC





5 m


	Cct	lm S - lm D	Opt
SE **83763**	**M**	98 - 66	**00** (Diffused)
	W	106 - 71	
	N	112 - 75	

Electronics: **DG** (pag 813)

Electronics

DG

89488	**89179**	**89359**	**99332**	**83333**
ON/OFF	ON/OFF	ON/OFF	0/1-10V	DALI/PUSH
1 - 13 art.	1 - 22 art.	1 - 45 art.	1 - 135 art.	1 - 135 art.
100 x 80 x h 31	117 x 92 x h 38	140 x 115 x h 50	150 x 60 x h 35	188 x 68 x h 34
			70	77





Stainless steel body.
Extra-clear glass diffuser.

Finishes	Cct
SE Stainless Steel	**M** 2700 **N** 4000
	W 3000

BLUM

PVC/Aluminium body.
PMMA diffuser.



ARIA RETREAT & SPA
Cima di Porlezza, Como (Italy)

Architectural design:
R4M Engineering

Lighting design:
Architect Giorgio Colombo,
Light+Arch Consultancy


Construction:
Quadrio Gaetano Costruzioni S.p.a.

Contract & Custom Lighting:
Bespoke Lighting Solutions

Photo: Andrea Martiradonna

Blum | powerLED | 220-240 V AC | 1,5 W DC - 1,8 W AC






IK08 IP65

	Cct	lm S - lm D	Opt
1 x powerLED			
BN **83875**	**A**	150 - 97	**20** (25°)
	M	170 - 109	**00** (99°)
	W	181 - 116	
	N	203 - 130	

Accessories: (pag 817)

Blum | powerLED | 220-240 V AC | 4,5 W DC - 5,4 W AC






IK08 IP65

	Cct	lm S - lm D	Opt
3 x powerLED			
BN **83879**	**A**	450 - 290	**20** (25°)
	M	510 - 328	**00** (99°)
	W	543 - 349	
	N	609 - 392	

Accessories: (pag 817)

Blum Projector | powerLED | 220-240 V AC | 4,5 W DC - 5,5 W AC






IK08 IP65 NEW

	Fin	Cct	lm S - lm D	Opt
1 x powerLED				
C00004	BN	**A**	542 - 417	**SP** (10°÷ 19°)
		M	646 - 500	**FL** (20°÷ 29°)
		W	673 - 520	**WF** (50°÷ 70°)
		N	711 - 549	

Accessories: (pag 817)

Blum Projector | powerLED | 500 mA | 4,5 W DC






C.C. IK08 IP65 NEW

	Fin	Cct	lm S - lm D	Opt
1 x powerLED				
C00006	BN	**A**	542 - 417	**SP** (10°÷ 19°)
		M	646 - 500	**FL** (20°÷ 29°)
		W	673 - 520	**WF** (50°÷ 70°)
		N	711 - 549	

Electronics: **BW** (pag 817) | Accessories: (pag 817)

Blum Projector | powerLED | 220-240 V AC | 12,2 W DC - 14,2 W AC





IK08 IP65 NEW

	Fin	Cct	lm S - lm D	Opt
3 x powerLED				
C00005	BN	**A**	1494 - 1149	**SP** (10°÷ 19°)
		M	1772 - 1365	**FL** (20°÷ 29°)
		W	1848 - 1424	**WF** (50°÷ 70°)
		N	1950 - 1504	

Accessories: (pag 817)



Blum (83875W20)



Blum Projector (C00004BNWFL)


Finishes


BN Brown

Cct

A 2200 **W** 3000
M 2700 **N** 4000

Blum | powerLED | 220-240 V AC | 1,5 W DC - 1,8 W AC






IK08 IP65

	Cct	lm S - lm D	Opt
1 x powerLED			
BN **83876**	**A**	150 - 44	**00** (Diffused)
	M	170 - 49	
	W	181 - 53	
	N	203 - 59	

Accessories: (pag 817)

Blum | powerLED | 220-240 V AC | 4,5 W DC - 5,4 W AC







IK08 IP65

	Cct	lm S - lm D	Opt
3 x powerLED			
BN **83880**	**A**	450 - 131	**00** (Diffused)
	M	510 - 149	
	W	543 - 158	
	N	609 - 178	

Accessories: (pag 817)

Blum Spike | powerLED | 220-240 V AC | 1,5 W DC - 1,8 W AC







IK08 IP65 NEW

	Fin	Cct	lm S - lm D	Opt
1 x powerLED				
C00001	**BN**	**A**	151 - 38	**DI** (Diffused)
		M	199 - 50	
		W	213 - 54	
		N	227 - 57	

Accessories: (pag 817)

Blum Spike | powerLED | 500 mA | 1,5 W DC







C.C. IK08 IP65 NEW

	Fin	Cct	lm S - lm D	Opt
1 x powerLED				
C00003	**BN**	**A**	151 - 38	**DI** (Diffused)
		M	199 - 50	
		W	213 - 54	
		N	227 - 57	

Electronics: **BC** (pag 817) | Accessories: (pag 817)

Blum Spike | powerLED | 220-240 V AC | 4,5 W DC - 5,4 W AC







IK08 IP65 NEW

	Fin	Cct	lm S - lm D	Opt
3 x powerLED				
C00002	**BN**	**A**	453 - 114	**DI** (Diffused)
		M	597 - 150	
		W	639 - 162	
		N	681 - 171	

Accessories: (pag 817)



Blum (83876)



Blum Spike (C00001)




Blum Flower (83877)



Blum Flower (83878)

Blum Flower | powerLED | 220-240 V AC | 1,5 W DC - 1,8 W AC






IK08 IP65

	Cct	lm S - lm D	Opt
1 x powerLED			
BN **83877**	**A**	150 - On req	**00** (Diffused)
	M	170 - On req	
	W	181 - On req	
	N	203 - On req	

Accessories: (pag 817)

Blum Flower | powerLED | 220-240 V AC | 4,5 W DC - 5,4 W AC






IK08 IP65

	Cct	lm S - lm D	Opt
3 x powerLED			
BN **83881**	**A**	450 - On req	**00** (Diffused)
	M	510 - On req	
	W	543 - On req	
	N	609 - On req	

Accessories: (pag 817)

Blum Flower | powerLED | 220-240 V AC | 1,5 W DC - 1,8 W AC






IK08 IP65

	Cct	lm S - lm D	Opt
1 x powerLED			
BN **83878**	**A**	150 - On req	**00** (Diffused)
	M	170 - On req	
	W	181 - On req	
	N	203 - On req	

Accessories: (pag 817)

Blum Flower | powerLED | 220-240 V AC | 4,5 W DC - 5,4 W AC





IK08 IP65

	Cct	lm S - lm D	Opt
3 x powerLED			
BN **83882**	**A**	450 - On req	**00** (Diffused)
	M	510 - On req	
	W	543 - On req	
	N	609 - On req	

Accessories: (pag 817)

Accessories




TR **83884** Open flower

suitable for: Blum Flower



TR **83883** Closed flower

suitable for: Blum Flower



PLC **14931** Peg

suitable for: Blum / Blum Projector / Blum Spike Blum Flower

Electronics

BC

89422	**89423**	**C-E200007**	**C-E200003**
ON/OFF	ON/OFF	ON/OFF	DALI/PUSH
1 - 2 art.	2 - 3 art.	3 - 6 art.	5 - 12 art.
74 x 65 x h 27	74 x 65 x h 27	135 x 26 x h 26	125 x 45 x h 30
		35	55

BW

C-E200007	**99185**	**C-E200003**
ON/OFF	ON/OFF	DALI/PUSH
1 - 2 art.	2 - 4 art.	2 - 4 art.
135 x 26 x h 26	117 x 92 x h 38	125 x 45 x h 30
35		55

Finishes

BN Brown
TR Transparent
PLC Polycarbonate

Cct

A 2200 **W** 3000
M 2700 **N** 4000

ROLLING SKY



RADIANT ELEGANCE FOR A UNIQUE ATMOSPHERE

A collection of outdoor lamps characterized by neutral and elegant shapes. The light projected on the surface creates unique effects, transforming outdoor spaces into suggestive and welcoming environments. The transparency of the material allows for a homogeneous light distribution, offering unparalleled visual comfort. The versatility of Rolling Sky is emphasized by the possibility of composing the diffusers with the light units, allowing the light to be customized and adapted to the needs of the project.




Ø300 - H340 Ø400 - H435 Ø500 - H535



Ø290 - H335 Ø383 - H437 Ø490 - H535

MODULAR SHAPES AND COLOURS




Light module
Dark brown (DB) or Black (BB)

Transparent aesthetic element
Sphere or Amphora

PVC/Aluminium body, PMMA diffuser.

Rolling Sky | topLED | 220-240 V AC | 9 W DC - 10 W AC






IK07 IP65 NEW

	Cct	lm S - lm D	Opt
BB 77099	M	1316 - 300	00 (Asym. 360°)
DB 77100	W	1385 - 322	

suitable for: (Sphere Ø300) **C-D100001** - (Amphora Ø290) **C-D100004**

Rolling Sky | topLED | 220-240 V AC | 15 W DC - 17 W AC






IK07 IP65 NEW

	Cct	lm S - lm D	Opt
BB 77101	M	1987 - 470	00 (Asym. 360°)
DB 77102	W	2136 - 505	

suitable for: (Sphere Ø400) **C-D100002** - (Amphora Ø383) **C-D100005**

Rolling Sky | topLED | 220-240 V AC | 20 W DC - 22 W AC






IK07 IP65 NEW

	Cct	lm S - lm D	Opt
BB 77103	M	2643 - 547	00 (Asym. 360°)
DB 77104	W	2842 - 588	

suitable for: (Sphere Ø500) **C-D100003** - (Sphere Ø490) **C-D100006**

Rolling Sky | Sphere






IK07 NEW

TR C-D100001	A= Ø300	B= H300 | C= Ø139
TR C-D100002	A= Ø400	B= H395 | C= Ø179
TR C-D100003	A= Ø500	B= H495 | C= Ø219

Rolling Sky | Amphora





IK07 NEW

TR C-D100004	A= Ø290	B= H295 | C= Ø139
TR C-D100005	A= Ø383	B= H397 | C= Ø179
TR C-D100006	A= Ø490	B= H495 | C= Ø219



INSTALLATION POSSIBILITIES

Grass



Floor



Ceiling



Wall




Accessories





PLC 14931 Peg

suitable for: Rolling Sky















BOND PRO

Polyester powder-coated aluminium body and
protective surface treatment or stainless steel body.
Opalescent white polyethylene diffuser.



Bond_PRO | topLED | 220-240 V AC | 10,8 W DC - 12 W AC






IK07 IP65

	Cct	lm S - lm D	Opt
L 210			
BB **81098**	**W**	1350 - 580	**00** (Asym. 360°)
DB **81099**	**N**	1460 - 627	
SE **81100**			
GG **81097**			

Accessories: (pag 825)

Bond_PRO | topLED | 220-240 V AC | 10,8 W DC - 12 W AC






IK07 IP65

	Cct	lm S - lm D	Opt
L 510			
BB **81102**	**W**	1350 - 580	**00** (Asym. 360°)
DB **81103**	**N**	1460 - 627	
SE **81104**			
GG **81101**			
L 810			
BB **81106**	**W**	1350 - 580	**00** (Asym. 360°)
DB **81107**	**N**	1460 - 627	
SE **81108**			
GG **81105**			


Accessories: (pag 825)



Ergonomic design

The light source in the top of the bollard is screened by the circular flange to create a total cutoff, so that the light is never invasive and fits perfectly with its environment.
The light emitted illuminates the portion of the area below.
The Bond PRO range offers three different sizes that allow the product to be declined in a variety of application contexts.

Accessories



PLC **14931** Peg

suitable for: Bond_PRO

Finishes

BB Black DB Dark Brown
GG Grey SE Stainless Steel

Cct

W 3000
N 4000



BUZZER

826

A NEW BOLLARD THAT REVOLUTIONISES THE CONCEPT OF VISUAL COMFORT WITH WRAPAROUND LIGHTING AND NO SHADOW AREAS

Buzzer is the new bollard designed to illuminate routes, whether pedestrian or vehicle, and contemporary landscape projects. Available in five heights and four diameters, it is a flexible outdoor device, ideal for meeting all the designer's requirements. The light source, located entirely under the head, ensure Buzzer's excellent anti-glare, visual comfort. The bollard illuminates on the ground with 2 openings (180°) or a single opening (360°) with no upward dispersion. Thanks to its special optics, it offers a wide light diffusion all around it with no shadow areas at the base. Buzzer comes in four neutral finishes which are perfect for outdoor installation: White, Grey, Black Grey, Dark Brown and Green (for models ø130 mm and ø136 mm). Available in four temperature colours: 2200K, 2700K, 3000K and 4000K.

Materials
Die-cast aluminium body with powder coating.

Buzzer family

Buzzer Pro



850



Black Grey (BG) **Grey (GG)** **Dark Brown (DB)**

360° OPTICAL COMPARTMENT





360° light

180° OPTICAL COMPARTMENT






180° light

RANGE


Ø70

Ø120



Ø136

H87	H400	H700	H900	H78	H145	H410
Buzzer 7 W On-Off Led-Direct	**Buzzer** 7 W On-Off Led-Direct	**Buzzer** 7 W On-Off Led-Direct	**Buzzer** 7 W On-Off Led-Direct		**Buzzer** 7 W On-Off Led-Direct	**Buzzer** 10 W On-Off Led-Direct
Buzzer Pro 8,5 W On-Off	**Buzzer Pro** 8,5 W On-Off	**Buzzer Pro** 8,5 W On-Off	**Buzzer Pro** 8,5 W On-Off	**Buzzer Pro** 8,5 W On-Off	**Buzzer Pro** 6,5 W On-Off - DALI 7,1 W On-Off	**Buzzer Pro** 11 W On-Off 11 W DALI 2
Optic 360° - 180°	**Optic** 360° - 180°	**Optic** 360° - 180°	**Optic** 360° - 180°	**Optic** 360° - 180°	**Optic** 360° - 180°	**Optic** 360° - 180°



H710

Buzzer
10 W On-Off
Led-Direct

Buzzer Pro
11 W On-Off
11 W DALI 2

Optic
360° - 180°

H910

Buzzer
10 W On-Off
Led-Direct

Buzzer Pro
11 W On-Off
11 W DALI 2

Optic
360° - 180°

H400

Buzzer Pro
20,5 W On-Off
20,5 W DALI 2

Optic
360° - 180°

H700

Buzzer Pro
20,5 W On-Off
20,5 W DALI 2

Optic
360° - 180°

H900

Buzzer Pro
20,5 W On-Off
20,5 W DALI 2


Optic
360° - 180°





Buzzer | arrayLED-direct | 220-240 V AC





IK10 IP65 BUG Rating 0


LED-DIRECT

	Cct	lm S - lm D	Opt
L 400 - 7 W AC			
BG **76874**	**W**	865 - 137	**00** (Asym. 360°)
GG **76875**	**N**	870 - 138	**18** (Asym. 180°)
DB **76876**			
L 700 - 7 W AC			
BG **76878**	**W**	865 - 137	**00** (Asym. 360°)
GG **76879**	**N**	870 - 138	**18** (Asym. 180°)
DB **76880**			
L 900 - 7 W AC			
BG **76882**	**W**	865 - 137	**00** (Asym. 360°)
GG **76883**	**N**	870 - 138	**18** (Asym. 180°)
DB **76884**			

Accessories: (pag 835)

Buzzer Pro | arrayLED | 220-240 V AC






IK10 IP65 BUG Rating 0

	Fin	Cct	lm S - lm D	Opt
L 400 - 6,5 W DC - 8,5 W AC				
C00007	BG	**A**	746 - 129	**RD** (Asym. 360°)
	GG	**M**	925 - 152	**SR** (Asym. 180°)
	DB	**W**	965 - 159	
		N	990 - 169	
L 700 - 6,5 W DC - 8,5 W AC				
C00008	BG	**A**	746 - 129	**RD** (Asym. 360°)
	GG	**M**	925 - 152	**SR** (Asym. 180°)
	DB	**W**	965 - 159	
		N	990 - 169	
L 900 - 6,5 W DC - 8,5 W AC				
C00009	BG	**A**	746 - 129	**RD** (Asym. 360°)
	GG	**M**	925 - 152	**SR** (Asym. 180°)
	DB	**W**	965 - 159	
		N	990 - 169	

Accessories: (pag 835)

Buzzer | arrayLED-direct | 220-240 V AC





IK09 IP65


LED-DIRECT

	Cct	lm S - lm D	Opt
7 W AC			
BG **76886**	**W**	865 - 220	**00** (Asym. 360°)
GG **76887**	**N**	870 - 221	**18** (Asym. 180°)
DB **76888**			

Accessories: (pag 835)

Buzzer Pro | arrayLED





III IK09 IP65

	Fin	Cct	lm S - lm D	Opt
C.C. - 350 mA - 6,5 W DC				
C00017	BG	**A**	746 - 213	**RD** (Asym. 360°)
	GG	**M**	925 - 251	**SR** (Asym. 180°)
	DB	**W**	965 - 262	
		N	990 - 278	

Electronics: **BZ** (pag 835) | Accessories: (pag 835)


IK09 IP65

	Fin	Cct	lm S - lm D	Opt
220-240 V AC - 5,4 W DC - 7,1 W AC				
C00018	BG	**A**	746 - 213	**RD** (Asym. 360°)
	GG	**M**	925 - 251	**SR** (Asym. 180°)
	DB	**W**	965 - 262	
		N	990 - 278	

Accessories: (pag 835)

Buzzer | arrayLED-direct | 220-240 V AC






IK09 IP65 BUG Rating 0 *

LED-DIRECT

		Cct	lm S - lm D	Opt
L 410 - 10 W AC				
BG	**76890**	**W**	1065 - 255	**00** (Asym. 360°)
GG	**76891**	**N**	1105 - 264	**18** (Asym. 180°) *
DB	**76892**			
L 710 - 10 W AC				
BG	**76894**	**W**	1065 - 255	**00** (Asym. 360°)
GG	**76895**	**N**	1105 - 264	**18** (Asym. 180°) *
DB	**76896**			
L 910 - 10 W AC				
BG	**76898**	**W**	1065 - 255	**00** (Asym. 360°)
GG	**76899**	**N**	1105 - 264	**18** (Asym. 180°) *
DB	**76900**			

Buzzer Pro | arrayLED | 220-240 V AC






IK09 IP65 BUG Rating 0

	Fin		Cct	lm S - lm D	Opt
L 410 - 9,3 W DC - 11 W AC					
C00011	**BG**	BG	**A**	1011 - 270	**RD** (Asym. 360°)
	GG	GG	**M**	1265 - 318	**SR** (Asym. 180°)
DALI	**DB**	DB	**W**	1320 - 332	
C00014			**N**	1354 - 351	
L 710 - 9,3 W DC - 11 W AC					
C00012	**BG**	BG	**A**	1011 - 270	**RD** (Asym. 360°)
	GG	GG	**M**	1265 - 318	**SR** (Asym. 180°)
DALI	**DB**	DB	**W**	1320 - 332	
C00015			**N**	1354 - 351	
L 910 - 9,3 W DC - 11 W AC					
C00013	**BG**	BG	**A**	1011 - 270	**RD** (Asym. 360°)
	GG	GG	**M**	1265 - 318	**SR** (Asym. 180°)
DALI	**DB**	DB	**W**	1320 - 332	
C00016			**N**	1354 - 351	

Accessories: (pag 835)

Buzzer Pro | arrayLED | 220-240 V AC






IK09 IP65 NEW

	Fin		Cct	lm S - lm D	Opt
L 400 - 18 W DC - 20,5 W AC					
C00022	**BG**	BG	**A**	2559 - 658	**RD** (Asym. 360°)
	GG	GG	**M**	2907 - 750	**SR** (Asym. 180°)
DALI	**DB**	DB	**W**	3027 - 781	
C00019			**N**	3106 - 824	
L 700 - 18 W DC - 20,5 W AC					
C00023	**BG**	BG	**A**	2559 - 658	**RD** (Asym. 360°)
	GG	GG	**M**	2907 - 750	**SR** (Asym. 180°)
DALI	**DB**	DB	**W**	3027 - 781	
C00020			**N**	3106 - 824	
L 900 - 18 W DC - 20,5 W AC					
C00024	**BG**	BG	**A**	2559 - 658	**RD** (Asym. 360°)
	GG	GG	**M**	2907 - 750	**SR** (Asym. 180°)
DALI	**DB**	DB	**W**	3027 - 781	
C00021			**N**	3106 - 824	

Accessories: (pag 835)

Buzzer Pro | arrayLED | 220-240 V AC






IK09 IP65 NEW

	Fin		Cct	lm S - lm D	Opt
7,2 W DC - 8,5 W AC					
C00714	**WH**		**A**	838 - 163	**RD** (Asym. 360°)
	BG		**M**	1041 - 203	
	GG		**W**	1087 - 211	
	DB		**N**	1114 - 218	
	GR				

Accessories: (pag 835)

Buzzer Pro | arrayLED | 220-240 V AC






IK09 IP65 NEW


	Fin		Cct	lm S - lm D	Opt
7,2 W DC - 8,5 W AC					
C00713	**WH**		**A**	838 - 63	**SR** (Asym. 180°)
	BG		**M**	1041 - 78	
	GG		**W**	1087 - 82	
	DB		**N**	1114 - 84	
	GR				

Accessories: (pag 835)



Buzzer | Kit relamping | arrayLED-direct | 220-240 V AC





IK10 IP65 BUG Rating 0


LED-DIRECT

	Cct	lm S - lm D	Opt
7 W AC			
BG **77187**	**W**	865 - 137	**00** (Asym. 360°)
GG **77188**	**N**	870 - 138	**18** (Asym. 180°)
DB **77189**			

Accessories: (pag 835)

Buzzer Pro | Kit relamping | arrayLED | 220-240 V AC





IK10 IP65 BUG Rating 0

	Fin	Cct	lm S - lm D	Opt
6,5 W DC - 8,5 W AC				
C00010	BG	**A**	746 - 129	**RD** (Asym. 360°)
	GG	**M**	925 - 152	**SR** (Asym. 180°)
	DB	**W**	965 - 159	
		N	990 - 169	

Accessories: (pag 835)

RELAMPING KIT

For poles with a diameter of 60 mm external, 56 mm internal




Step 01
Removal of old mounted fixture

Step 02
Connection of the relamping kit with the waterproof connector (included)


Step 03
Press-fit insertion of the relamping kit

Accessories & Electronics



PLC **14931** Peg

suitable for: Buzzer Ø110 (only for h 145)
Buzzer Pro Ø110 (only for h 145) - Buzzer Pro Ø130
Buzzer Pro Ø136



IS **W-F500001** Steel peg 300 mm

suitable for: Buzzer Ø70 - Buzzer Pro Ø70



IS **W-F900001** Tie rods Ø110
IS **W-F900002** Tie rods Ø180

suitable for: Buzzer Ø110 (not for h 145)
Buzzer Pro Ø110 (not for h 145) - Buzzer Pro Ø180

BZ

89421	**C-E200006**	**C-E200004**
ON/OFF	ON/OFF	DALI/PUSH
1 art.	1 - 2 art.	1 - 2 art.
74 x 65 x h 27	135 x 26 x h 26	125 x 45 x h 30
	35	55

Finishes
BG Black Grey
GG Grey
DB Dark Brown
IS Steel
PLC Polycarbonate

Cct
A 2200 **W** 3000
M 2700 **N** 4000




RYO

Polyester powder-coated aluminium
body and protective surface treatment.
Transparent polycarbonate diffuser.

Ryo | arrayLED | 220-240 V AC | 4,2 W DC - 5,2 W AC






IK09 IP66

	Cct	lm S - lm D	Opt
L 250			
GG **64761**	**M**	669 - 341	**00** (Asym. Diffused)
BG **64759**	**W**	699 - 356	
DB **64760**	**N**	717 - 365	

Accessories: (pag 837)

Ryo | arrayLED | 220-240 V AC | 9 W DC - 10 W AC






IK09 IP66

	Cct	lm S - lm D	Opt
L 820			
GG **64734**	**M**	1265 - 644	**00** (Asym. Diffused)
BG **64721**	**W**	1320 - 673	
DB **64726**	**N**	1354 - 690	
L 1120			
GG **64736**	**M**	1265 - 644	**00** (Asym. Diffused)
BG **64723**	**W**	1320 - 673	
DB **64728**	**N**	1354 - 690	

Accessories: (pag 837)

Ryo | arrayLED | 220-240 V AC | 8,4 W DC - 10 W AC






IK09 IP66

	Cct	lm S - lm D	Opt
L 250			
GG **64764**	**M**	1265 - 681	**00** (Double Asym. Diffused)
BG **64762**	**W**	1320 - 712	
DB **64763**	**N**	1354 - 730	

Accessories: (pag 837)

Ryo | arrayLED | 220-240 V AC | 18 W DC - 20 W AC






IK09 IP66

	Cct	lm S - lm D	Opt
L 820			
GG **64735**	**M**	2530 - 1288	**00** (Double Asym. Diffused)
BG **64722**	**W**	2640 - 1346	
DB **64727**	**N**	2708 - 1381	
L 1120			
GG **64737**	**M**	2530 - 1288	**00** (Double Asym. Diffused)
BG **64724**	**W**	2640 - 1346	
DB **64729**	**N**	2708 - 1381	

Accessories: (pag 837)



Accessories



IS **64758** Tie rods

suitable for: Ryo

Finishes

BG Black Grey
GG Grey
DB Dark Brown
IS Steel

Cct

M 2700 **N** 4000
W 3000




APACHE

Aluminium body with polyester powder coating and protective surface pre-treatment.
Polycarbonate diffuser.

Apache | topLED | 220-240 V AC





IK09 IP66


	Cct	lm S - lm D	Opt
L 550 - 7 W DC - 9 W AC			
BG **64252**	**M**	992 - 447	**00** (Asym. Ww)
GY **64253**	**W**	1034 - 466	
DB **64254**	**N**	1087 - 489	
L 850 - 8,5 W DC - 10 W AC			
BG **64256**	**M**	1198 - 539	**00** (Asym. Ww)
GY **64257**	**W**	1249 - 561	
DB **64258**	**N**	1313 - 589	

Accessories: (pag 839)



Black Grey (BG) **Grey-Black (GY)**

Accessories



IS **64210** Tie rods

suitable for: Apache

Finishes

BG Black Grey
GY Grey/Black
DB Dark Brown
IS Steel

Cct


M 2700 **N** 4000
W 3000


PEAK

Polyester powder-coated aluminium body
with protective surface treatment.
Extra-clear glass diffuser.



Peak | arrayLED | 220-240 V AC







IK05 IP66

	Cct	lm S - lm D	Opt
L 350 - 6,5 W DC - 9 W AC			
GG **64794**	**M**	948 - 552	**07** (Asym. Ww)
BG **64795**	**W**	990 - 576	
DB **64796**	**N**	1015 - 591	
L 750 - 9,5 W DC - 11 W AC			
GG **64791**	**M**	1265 - 822	**07** (Asym. Ww)
BG **64792**	**W**	1320 - 847	
DB **64793**	**N**	1354 - 869	

Accessories: (pag 841)

Peak | arrayLED | 220-240 V AC





IK07 IP66

	Cct	lm S - lm D	Opt
9,5 W DC - 11 W AC			
GG **64788**	**M**	1265 - 822	**07** (Asym. Ww)
BG **64789**	**W**	1320 - 847	
DB **64790**	**N**	1354 - 869	
DALI - 9,5 W DC - 11 W AC			**DALI**
GG **65403**	**M**	1265 - 822	**07** (Asym. Ww)
BG **65404**	**W**	1320 - 847	
DB **65405**	**N**	1354 - 869	

Accessories: (pag 841)



Optics design

The peculiar optical group conformation provides a lighting emission only on bollard front, eliminating every secondary light dispersion on the back. The light emission is deep, clear and defined.


Peak family

Peak-Maxi



848

Accessories



IS **65082** Tie rods

suitable for: Peak 6,5W / Peak 9,5W

Finishes

BG Black Grey
GG Grey
DB Dark Brown
IS Steel

Cct

M 2700 **N** 4000
W 3000




URBAN
LIGHTS

RESIDENCE CIVICO 3.9
Castelfranco Veneto - Treviso (Italy)

Project: Studio Architetti Associati
Giampietro & Stefano Cinel

Commissioned by:
Fralma Srl

Photography:
The Studio



Urban lights range index

Stalk

Stalk



847

Peak

Peak-Maxi



849

Peak-Maxi_L



849

Peak-Maxi_DL



849

Buzzer

Buzzer Pro



851

Parker

Parker



853-854

Parker PC



854

Ledweg


Ledweg



857

Voyager

Voyager



859

Poles, arms & fixing accessories

Poles



860-861

Arms & fixing accessories



862-865




STALK

Polyester powder-coated aluminium body
with protective surface treatment.
Opalescent white polyethylene diffuser.

Stalk | topLED | 220-240 V AC | 20 W DC - 21 W AC






IK08 IP65

	Cct	lm S - lm D	Opt
GG **63445**	**M**	2210 - 757	**00** (Diffused)
DB **63446**	**W**	2314 - 792	
	N	2460 - 841	

Accessories: (pag 847)



Accessories



IS **53890** Tie rods

suitable for: Stalk

Finishes

GG Grey
DB Dark Brown
IS Steel

Cct

M 2700 **N** 4000
W 3000


PEAK

Polyester powder-coated aluminium body
with protective surface treatment.
Extra-clear glass diffuser.



Peak-Maxi | powerLED | 220-240 V AC | 34 W DC - 38 W AC





IK08 IP66

	Fin	Cct	lm S - lm D	Opt
C00379	**GG**	**M**	4776 - 3887	**PK** (Park)
	BG	**W**	5112 - 4163	**ST** (Street)
	DB	**N**	5448 - 4438	

Accessories: (pag 849)


IK08 IP66 **DALI**

	Fin	Cct	lm S - lm D	Opt
DALI				
C00380	**GG**	**M**	4776 - 3887	**PK** (Park)
	BG	**W**	5112 - 4163	**ST** (Street)
	DB	**N**	5448 - 4438	

Accessories: (pag 849)

Peak-Maxi_L | powerLED | 220-240 V AC | 51 W DC - 56 W AC





IK08 IP66

	Fin	Cct	lm S - lm D	Opt
C00381	**GG**	**M**	7164 - 5831	**PK** (Park)
	BG	**W**	7668 - 6243	**ST** (Street)
	DB	**N**	8172 - 6656	

Accessories: (pag 849)


IK08 IP66 **DALI**

	Fin	Cct	lm S - lm D	Opt
DALI				
C00384	**GG**	**M**	7164 - 5831	**PK** (Park)
	BG	**W**	7668 - 6243	**ST** (Street)
	DB	**N**	8172 - 6656	

Accessories: (pag 849)

Peak-Maxi_DL | powerLED | 220-240 V AC | 102 W DC - 112 W AC





IK08 IP66

	Fin	Cct	lm S - lm D	Opt
C00382	**GG**	**M**	14328 - 11662	**PK** (Park)
	BG	**W**	15336 - 12486	**ST** (Street)
	DB	**N**	16344 - 13312	

Accessories: (pag 849)

IK08 IP66 **DALI**

	Fin	Cct	lm S - lm D	Opt
DALI				
C00385	**GG**	**M**	14328 - 11662	**PK** (Park)
	BG	**W**	15336 - 12486	**ST** (Street)
	DB	**N**	16344 - 13312	

Accessories: (pag 849)


Peak family

Peak




840

Accessories



GG **65076** Fixing base
BG **65077** Fixing base
DB **65075** Fixing base
suitable for: Peak Maxi / Peak Maxi L / Peak Maxi DL



IS **65078** Fixing base
suitable for: Peak Maxi / Peak Maxi L / Peak Maxi DL

Finishes

BG Black Grey
GG Grey
DB Dark Brown
IS Steel

Cct

M 2700 **N** 4000
W 3000




BUZZER

Die-cast aluminium body
with powder coating

Buzzer Pro | arrayLED | 220-240 V AC





IK09 IP65 NEW

	Fin		Cct	lm S - lm D	Opt
L 2300 - 18 W DC - 20,5 W AC					
C00991	**GG**		**A**	2559 - 864	**RD** (Asym. 360°)
	BG		**M**	2907 - 982	
DALI	**DB**		**W**	3027 - 1023	
C00992			**N**	3106 - 1049	

Accessories: (pag 851)

Accessories



IS **W-F900002** Tie rods Ø180

suitable for: Buzzer Pro Ø190


Buzzer Pro, with a height of 2300 mm, is the new urban pole designed to illuminate pedestrian or vehicular paths and contemporary landscape projects. The light source, positioned completely underneath the head, gives Buzzer a very high anti-glare visual comfort. The device illuminates the ground with a 360° opening without upward dispersion, and thanks to its special optical group, it offers broad light diffusion around it without shadow zones at the base. Buzzer Pro is presented in three neutral finishes, perfect for any outdoor setting: Grey, Black Grey, and Dark Brown. Four colour temperatures are available: 2200K, 2700K, 3000K, and 4000K.

Buzzer family

Buzzer



826



Buzzer Pro 20,5 W AC (H 2300 mm)
Code: C00991BGNRD



Finishes

BG Black Grey
GG Grey
DB Dark Brown
IS Steel

Cct

A 2200 **W** 3000
M 2700 **N** 4000


PARKER

Body in die-cast aluminium ENAB-46100.
Extra-clear tempered glass diffuser.



Parker | powerLED | 220-240 V AC






0,5 m | 0,02 | 0,07

	Cct	lm S - lm D	Opt
12 x powerLED - 20 W DC - 22 W AC			
AT **77379**	**A**	2108 - 1545	**72** (Street)
	W	2988 - 2192	**73** (Urban)
Autocontrol System	**N**	3852 - 2810	**79** (Park)
AT **77378**			
24 x powerLED - 33 W DC - 36 W AC			
AT **77381**	**A**	3309 - 2561	**72** (Street)
	W	4883 - 3631	**73** (Urban)
Autocontrol System	**N**	6283 - 4656	**79** (Park)
AT **77380**			
12 x powerLED - 37 W DC - 40 W AC			
AT **77382**	**A**	3258 - 2287	**72** (Street)
	W	4746 - 3244	**73** (Urban)
	N	6107 - 4158	**79** (Park)

Accessories: (pag 854) | Poles: (pag 860) | Arms & fixing accessories: (pag 862)

Parker | powerLED | 220-240 V AC





1 m | 0,03 | 0,1

	Cct	lm S - lm D	Opt
24 x powerLED - 41,5 W DC - 44 W AC			
AT **84466**	**A**	4217 - 3255	**72** (Street)
LY **84467**	**W**	5976 - 4609	**73** (Urban)
Autocontrol System	**N**	7534 - 5812	**79** (Park)
AT **84468**			
LY **84469**			
36 x powerLED - 52 W DC - 55 W AC			
AT **84470**	**A**	5434 - 4163	**72** (Street)
LY **84471**	**W**	7768 - 5895	**73** (Urban)
Autocontrol System	**N**	9643 - 7473	**79** (Park)
AT **84472**			
LY **84473**			
36 x powerLED - 63 W DC - 66 W AC			
AT **84474**	**A**	6326 - 4880	**72** (Street)
LY **84475**	**W**	8964 - 6911	**73** (Urban)
Autocontrol System	**N**	11300 - 8714	**79** (Park)
AT **84476**			
LY **84477**			
36 x powerLED - 71,5 W DC - 75 W AC			
AT **84478**	**A**	6957 - 5393	**72** (Street)
LY **84479**	**W**	9925 - 7636	**73** (Urban)
Autocontrol System	**N**	12491 - 9629	**79** (Park)
AT **84480**			
LY **84481**			
36 x powerLED - 84 W DC - 90 W AC			
AT **84567**	**A**	7920 - 6218	**72** (Street)
LY **84568**	**W**	11448 - 8804	**73** (Urban)
Autocontrol System	**N**	14400 - 11102	**79** (Park)
AT **84569**			
LY **84570**			

Accessories: (pag 854) | Poles: (pag 860) | Arms & fixing accessories: (pag 862)


Autocontrol system
The Autocontrol system makes it so that autonomous street lights are able to automatically adjust the luminous flow based on the selected programming depending on the technical lighting needs. The system works in combination with a timer or a twilight switch upstream of the system which determines the daily hours of operation. Generally, the operating time is divided into 5 time slots, proportional in percentage to the duration of the night. This time is stored by the power supply and used to determine the hours of operation in the various time slots of the following day.

Finishes
AT Anthracite
LY Light Grey

Cct
A 2200 **N** 4000
W 3000


Parker PC | Pedestrian | powerLED | 220-240 V AC





Parker | powerLED | 220-240 V AC







Autocontrol system
The Autocontrol system makes it so that autonomous street lights are able to automatically adjust the luminous flow based on the selected programming depending on the technical lighting needs. The system works in combination with a timer or a twilight switch upstream of the system which determines the daily hours of operation. Generally, the operating time is divided into 5 time slots, proportional in percentage to the duration of the night. This time is stored by the power supply and used to determine the hours of operation in the various time slots of the following day.



	Cct	lm S - lm D	Opt
8 x powerLED - 53 W DC - 58 W AC			
AT **92370**	**A**	5655 - 4321	**78** (Pedestrian Crossing)
LY **92371**	**W**	7949 - 5226	
	N	8523 - 6504	
	C	8523 - 6504	

Accessories: (pag 854) | Poles: (pag 860) | Arms & fixing accessories: (pag 862)



	Cct	lm S - lm D	Opt
48 x powerLED - 91 W DC - 100 W AC			
AT **84506**	**A**	9001 - 7504	**72** (Street)
LY **84507**	**W**	12820 - 10737	**73** (Urban)
Autocontrol System	**N**	16134 - 13505	**79** (Park)
AT **84508**			
LY **84509**			
60 x powerLED - 110 W DC - 120 W AC			
AT **84510**	**A**	10898 - 9079	**72** (Street)
LY **84511**	**W**	15496 - 12992	**73** (Urban)
Autocontrol System	**N**	19501 - 16341	**79** (Park)
AT **84512**			
LY **84513**			
72 x powerLED - 133 W DC - 145 W AC			
AT **84514**	**A**	13077 - 9886	**72** (Street)
LY **84515**	**W**	18595 - 14034	**73** (Urban)
Autocontrol System	**N**	23401 - 17653	**79** (Park)
AT **84516**			
LY **84517**			
96 x powerLED - 149 W DC - 160 W AC			
AT **84518**	**A**	15219 - 11429	**72** (Street)
LY **84519**	**W**	21504 - 16224	**73** (Urban)
Autocontrol System	**N**	27060 - 20408	**79** (Park)
AT **84520**			
LY **84521**			

Accessories: (pag 854) | Poles: (pag 860) | Arms & fixing accessories: (pag 862)

Accessories



AL **83404** Wall fixing bracket

suitable for: Parker 22W, 36W, 40W



PVC **99229** Extension cables in neoprene (per meter) 2x1 mm. Example: 99229 x 3 pz = 3 m


suitable for: Parker



PVC **98729** Quick connector ON-OFF IP68 socket/plug (2 poles)

suitable for: Parker

Head adjustment



90° positioning



15° positioning




180° positioning

LEDWEG

Body in die-cast aluminium ENAB-46100.
Extra-clear tempered glass diffuser.







1 m 0,03 0,06

	Cct	lm S - lm D	Opt	
4 x powerLED - 31 W DC - 35 W AC				
AT **92157**	**A**	3118 - 1898	**71**	(Bike)
LY **92162**	**W**	4371 - 2669	**72**	(Street)
	N	4686 - 2862	**73**	(Urban)
	C	4686 - 2862	**79**	(Park)
5 x powerLED- 35 W DC - 40 W AC				
AT **92163**	**A**	3534 - 2165	**71**	(Bike)
LY **92166**	**W**	4968 - 3043	**72**	(Street)
Autocontrol System	**N**	5327 - 3262	**73**	(Urban)
AT **92518**	**C**	5327 - 3262	**79**	(Park)
LY **92525**				
6 x powerLED - 42 W DC - 46 W AC				
AT **92167**	**A**	4241 - 2545	**71**	(Bike)
LY **92168**	**W**	5962 - 3576	**72**	(Street)
Autocontrol System	**N**	6392 - 3834	**73**	(Urban)
AT **92526**	**C**	6392 - 3834	**79**	(Park)
LY **92527**				


Poles: (pag 860) | Arms & fixing accessories: (pag 862)

Autocontrol system
The Autocontrol system makes it so that autonomous street lights are able to automatically adjust the luminous flow based on the selected programming depending on the technical lighting needs. The system works in combination with a timer or a twilight switch upstream of the system which determines the daily hours of operation. Generally, the operating time is divided into 5 time slots, proportional in percentage to the duration of the night. This time is stored by the power supply and used to determine the hours of operation in the various time slots of the following day.



Finishes
AT Anthracite
LY Light Grey

Cct
A 2200 **N** 4000
W 3000 **C** 5000




VOYAGER

Body in die-cast aluminium ENAB-46100.
Extra-clear tempered glass or sand-blasted glass diffuser.

Voyager | powerLED | 220-240 V AC






1 m | OVP | ESD | IP66 | IK08 | 0,03 | 0,14

	Cct	lm S - lm D	Opt
3 x powerLED - 23 W DC - 26 W AC			
AT **93188**	**A**	2339 - 1448	**71** (Bike)
LY **93189**	**W**	3278 - 2031	**72** (Street)
	N	3515 - 2177	**73** (Urban)
	C	3515 - 2177	**79** (Park)
5 x powerLED - 35 W DC - 40 W AC			
AT **93184**	**A**	3534 - 2194	**71** (Bike)
LY **93185**	**W**	4968 - 3077	**72** (Street)
Autocontrol System	**N**	5327 - 3299	**73** (Urban)
AT **93332**	**C**	5327 - 3299	**79** (Park)
LY **93336**			
7 x powerLED - 49 W DC - 54 W AC			
AT **93174**	**A**	4948 - 3080	**71** (Bike)
LY **93181**	**W**	6955 - 4321	**72** (Street)
Autocontrol System	**N**	7457 - 4632	**73** (Urban)
AT **93312**	**C**	9588 - 5963	**79** (Park)
LY **93313**			

Poles: (pag 860) | Arms & fixing accessories: (pag 862)

Voyager | powerLED | 220-240 V AC






1 m | OVP | ESD | IP66 | IK08 | 0,03 | 0,14

	Cct	lm S - lm D	Opt
9 x powerLED - 64 W DC - 71 W AC			
AT **93170**	**A**	6361 - 4905	**00** (Asym. 360°)
LY **93171**	**W**	8942 - 6902	
Autocontrol System	**N**	9588 - 7398	
AT **93293**	**C**	9588 - 7398	
LY **93294**			

Poles: (pag 860) | Arms & fixing accessories: (pag 862)

Voyager | topLED | 220-240 V AC





1 m | OVP | ESD | IP66 | IK08 | 0,03 | 0,14

	Cct	lm S - lm D	Opt
216 x topLED - 50 W DC - 55 W AC			
AT **80909**	**A**	7182 - 3209	**00** (Diffused)
LY **80910**	**W**	8672 - 4022	
Autocontrol System	**N**	8996 - 4427	
AT **80913**	**C**	8996 - 4565	
LY **80914**			
216 x topLED - 63 W DC - 70 W AC			
AT **80953**	**A**	8510 - 4070	**00** (Diffused)
LY **80954**	**W**	10303 - 5521	
Autocontrol System	**N**	10670 - 5839	
AT **80955**	**C**	10670 - 6131	
LY **80956**			

Poles: (pag 860) | Arms & fixing accessories: (pag 862)

Autocontrol system
The Autocontrol system makes it so that autonomous street lights are able to automatically adjust the luminous flow based on the selected programming depending on the technical lighting needs. The system works in combination with a timer or a twilight switch upstream of the system which determines the daily hours of operation. Generally, the operating time is divided into 5 time slots, proportional in percentage to the duration of the night. This time is stored by the power supply and used to determine the hours of operation in the various time slots of the following day.

Finishes
AT Anthracite
LY Light Grey

Cct
A 2200 **N** 4000
W 3000 **C** 5000

TECHNICAL CHARACTERISTICS

The calculations with the relative design loads are carried out in accordance with:
- Presidential Decree 07/01/1956 No. 164 "Regulations for the prevention of injuries in the workplace."
- Law No. 1086 of 05/11/71: "Regulations on works by reinforced, normal and prestressed concrete and in metallic structure."
- CNR - UNI 10011/88: "Steel construction: instructions for calculation, execution, commissioning and maintenance."
- CNR10022/84: "Cold formed sections. Instructions for use in building."
- "UNI - ENV " 1993-1-1(2004 - Eurocode 3, Design of concrete structures Part 1- 1: General regulations-General rules and rules for buildings.
- Ministerial Decree 14/01/08 Technical standards for construction.
- Ministerial Circular No. 617 of 02/02/09 "Instructions for the application of the Technical Standards for construction pursuant to Ministerial Decree 14 January 2008.
- "UNI-ENV 1991-2-4 (1997), Eurocode 1, Basis of design and actions on structures" For the entire sector of poles 20 m tall or shorter (straight poles) and equal to or shorter than 18 m (poles with arm), in the European Union, the harmonized UNI-EN standards are applied correlated with the "European Directive Council of 21 December 1988 relative to the reconciliation of the legislative, Regulatory and administrative provisions of the member States concerning construction products EEC 89/106."
- The lamp towers are constructed in observance of DPR 547 "Standards for prevention of accidents" and DPR 459 "Regulation for the implementation of the 89/392/EEC, 91/368/EEC, 93/44/EEC and 93/68/ directives.
- EEC concerning the reconciliation of legislation by the member States relative to machines.

	MATERIAL	UNI EN 40/2 DIMENSIONAL TOLERANCES	PROTECTION
TAPERED AND CYLINDRICAL POLES	**Steel:** S235 JRH - UNI EN 10219 (Fe 360B) **R:** 360 - 490 N/mm² **R and H:** 235 N/mm² **A:** 20 %	**External diameter:** ± 1 % **Thickness:** ± 10 % **Straightness:** ± 0.3 % of the total length Length: ± 0.5 %	Hot galvanising in accordance with UNI EN ISO 1461
CONICAL POLES, CURVED BY SHEET METAL	**Steel:** S235 JRH - UNI EN 10219 (Fe 360B) **R:** 360 - 490 N/mm² **R and H:** 235 N/mm² **A:** 20 %	**External diameter:** ± 1 % **Shape:** ± 3 % from the diameter **Thickness:** ± 10 % **Straightness:** ± 0.3 % of the total length **Length:** ± 0.5 %	Hot galvanising in accordance with UNI EN ISO 1461
TAPERED AND CONICAL POLES, HOT ROLLED	**Steel:** S275 JOH - UNI EN 10219 (Fe 340) (S235 JOH - UNI EN 10219 on request) **R:** 410 - 560 N/mm² (360 - 490 N/mm² on request) **R and H:** 275 N/mm² (360 - 490 N/mm² on request) **A:** 20 %	**External diameter:** ± 3 % **Thickness:** ± 0.3 % **Straightness:** ± 0.3 % of the total length **Length:** ± 50 mm	Hot galvanising in accordance with UNI EN ISO 1461

R = unit tensile strength load
R and H = unit yield load
A = elongation

Processing
- Poles top street lamp connecting shaft.
- Slot for terminal block.
- Incoming cables slot.
- Earth connection.

On Request:
- Base plate with anchoring holes.
- Reinforcing sleeve in welded steel.

Finishes
- Hot galvanising by immersion in melted zinc bath.
- Processing carried out in accordance with UNI EN 40/4 standards.
- Powder coating.
- Hydrocarbonising of the external buried part.
- Anti-corrosion sleeve to the section of coupling in membrane.

On Request:
- On request, different colouring from the unified RAL range.

Standard

Galvanized Steel (ZN)
The poles are made entirely in galvanised steel.



On request

Light grey (LY)
RAL 7035




On request

Anthracite (AT)
RAL 7016



Conical poles in galvanised steel or painted








	L mm	Hft mm	I mm	D mm	d mm	Kg	Eyelet mm
ZN **98150**	3500	3000	500	95	60	21	38x132
AT **83450**	3500	3000	500	95	60	21	38x132
ZN **98151**	4500	4000	500	105	60	28	38x132
AT **83451**	4500	4000	500	105	60	28	38x132
ZN **98152**	5500	5000	500	115	60	37	38x132
AT **83453**	5500	5000	500	115	60	37	38x132
ZN **98153**	6800	6000	800	128	60	48	46x186
AT **83452**	6800	6000	800	128	60	48	46x186
ZN **98154**	7800	7000	800	138	60	58	46x186
AT **83447**	7800	7000	800	138	60	58	46x186
ZN **98155**	8800	8000	800	148	60	81	46x186
ZN **98156**	9800	9000	800	158	60	81	46x186
ZN **98157**	10800	10000	800	168	60	93	46x186
ZN **98158**	6800	6000	800	128	60	63	46x186
ZN **98159**	7800	7000	800	138	60	77	46x186
ZN **98160**	8800	8000	800	148	60	91	46x186
ZN **98161**	9800	9000	800	158	60	107	46x186
AT **83448**	9800	9000	800	158	60	107	46x186
ZN **98162**	10800	10000	800	168	60	123	46x186

Cylindrical poles in galvanised steel








	L mm	Hft mm	I mm	D mm	d mm	Kg	Eyelet mm
ZN **98163**	5500	5000	500	102	102	44	38x132
ZN **98164**	7000	6000	1000	102	102	64	46x186

Tapered poles in galvanised steel








	L mm	Hft mm	I mm	D mm	d mm	Kg	Eyelet mm
ZN **99166**	5500	5000	500	89	60	31	38x132
ZN **99167**	6800	6000	800	114	60	53	46x186
ZN **99168**	6800	6000	800	127	60	58	46x186
ZN **99169**	7800	7000	800	114	60	61	46x186
ZN **99170**	7800	7000	800	127	60	66	46x186
ZN **99171**	6800	6000	800	114	60	63	46x186
ZN **99172**	6800	6000	800	152	60	80	46x186
ZN **99173**	7800	7000	800	127	60	75	46x186
ZN **98174**	7800	7000	800	139	60	79	46x186
ZN **98175**	7800	7000	800	152	60	89	46x186
ZN **98176**	7800	7000	800	168	60	104	46x186
ZN **98165**	7800	7000	1000	127	102	103	46x186
ZN **98177**	8800	8000	800	168	60	104	46x186
ZN **98178**	8800	8000	800	193	102	131	46x186
ZN **98179**	9800	9000	800	193	102	143	46x186
ZN **98180**	10800	10000	800	193	102	155	46x186
ZN **98181**	12800	12000	800	193	102	182	46x186


Finishes

ZN Galvanised Steel
AT Anthracite

Arms & fixing accessories

Round arm Ø 60mm






	L mm	T mm	Kg
AT **98182**	1000	700	8
LY **98749**	1000	700	8

To fasten the round arm Ø 60mm on the cylindrical pole, apply two couplers.

Single coupler for round arm






	Ø A mm	Ø B mm	Kg
AT **98184**	102	60	0,8
LY **98750**	102	60	0,8

Single coupler for round arm Ø 60mm (for cylindrical pole).

Double coupler for round arm






	Ø A mm	Ø B mm	Kg
AT **98186**	102	60	1,5
LY **98751**	102	60	1,5

Double coupler for round arm Ø 60mm (for cylindrical pole).

Triple coupler for round arm







	Ø A mm	Ø B mm	Kg
AT **98188**	102	60	2,2
LY **98752**	102	60	2,2

Triple coupler for round arm Ø 60mm (for cylindrical pole).

Wall-mount bracket for round arm






	L mm	Ø mm	Kg
ZN **98288**	250	70	4,5

Wall-mount bracket for round arm Ø 60mm.

Single folded arm





	L mm	T mm	Kg
ZN **98214**	500	1500	8,5


Single folded arm Ø 60mm for conical, tapered pole.

Finishes

ZN Galvanised Steel LY Light Grey
AT Anthracite

Double folded arm







		L mm	T mm	Kg
ZN	**98215**	500	3000	17

Double folded arm Ø 60mm for conical, tapered pole.

Single arm bracket







		L mm	T mm	Kg
ZN	**98216**	500	1500	8,5

Single arm bracket Ø 60mm for conical, tapered pole.

Double arm bracket






		L mm	T mm	Kg
ZN	**98217**	500	3000	17

Double arm bracket Ø 60mm for conical, tapered pole.

Reducer for conical Ø 70 mm







		Ø A mm	Ø B mm	Kg
AT	**98742**	80	60	0,8
LY	**98743**	80	60	0,8
ZN	**On req**	80	60	0,8

Reducer for conical or tapered pole Ø 70mm.

Reducer for conical Ø 89 mm







		Ø A mm	Ø B mm	Kg
AT	**98744**	102	60	1
LY	**98745**	102	60	1
ZN	**On req**	102	60	1

Reducer for conical or tapered pole Ø 89mm.

Reducer for conical Ø 120 mm





		Ø A mm	Ø B mm	Kg
AT	**98746**	114	60	1,1
LY	**98747**	114	60	1,1
ZN	**On req**	114	60	1,1


Reducer for conical or tapered pole Ø 120mm.

Finishes

ZN Galvanised Steel LY Light Grey
AT Anthracite

Cover for pole hand hole.






		L mm	T mm	Kg
AT	98192	132	38	0,09
AT	98194	186	45	0,15
LY	83075	132	38	0,09
LY	83076	186	45	0,15
ZN	On req	132	38	0,09
ZN	On req	186	45	0,15


Terminal block for hand hole (2 poli - 10 A)






		L mm	T mm
PVC	98193	132	38
PVC	98195	186	45


Cross arm Ø 60mm for conical or tapered pole






		L mm	T mm	Ø mm	Kg
ZN	98196	500	70	60	3
ZN	98197	1000	70	60	5


15° arm for wall mounting






		L mm	Ø mm	Kg
ZN	98198	250	60	3,5
AT	83449	250	60	3,5


Square-section cross arm Ø 100mm for conical or tapered pole






		L mm	Ø mm	Ø mm	Kg
ZN	98199	500	100	100	20

Single 15° angled arm Ø 60mm






		L mm	T mm	Ø mm	Kg
AT	98210	250	250	60	4,5
LY	98209	250	250	60	4,5
ZN	98208	250	250	60	4,5


Single 15° angled arm Ø 60mm for conical or tapered pole.

Finishes

ZN Galvanised Steel LY Light Grey
AT Anthracite

Double 15° angled arm Ø 60mm






	L mm	T mm	Ø mm	Kg
AT **98213**	250	250	60	5,4
LY **98212**	250	250	60	5,4
ZN **98211**	250	250	60	5,4

Double 15° angled arm Ø 60mm for conical or tapered pole.

Examples of installations with accessories



Finishes

ZN Galvanised Steel LY Light Grey
AT Anthracite




UNDER
WATER

FOUR SEASONS HOTEL, ARION
Athens (Greece)

Lighting designer:
Thomas Gravanis (Studio L+DG Lighting Architects)

Photography:
Gavriil Papadiotis



Underwater range index

Sub

Sub_R



873

Sub_Q



873

Suelo

Suelo_R



875

Suelo_RX Pro



875

MK68

MK68_RF



884-885

MK68_R



886-887

MK68_RW

NEW



888

MK68_RP



890-891

MK68_RF



894-895

Rubber 3D Protection

Rubber 3D Protection

NEW



900

MK68 Linear

MK68_LR



907

MK68_LQ



907

Rodix


Rodix



911

Private villa in Voula | Athens, Greece

A modern building, where light becomes dynamic in furnishings and function. A mosaic infinity pool stretches along two sides of the villa. Linea Light Group's MK68_RF and Suelo_RX Pro submerged lights guarantee an amazing performance even under water. The high IP rating is determined by the tempered glass and waterproof structure made of AISI 316L stainless steel.










SUB

AISI 316L stainless steel body.



Sub_R | powerLED






1 m | III | C.C. | IK10 | IP68

	Cct	lm S - lm D	Opt	
C.C. - 500 mA - 1,5 W DC				
SE **97315**	**M**	199 - 150	**15**	(21°)
	W	213 - 161	**30**	(27°)
	N	227 - 171	**60**	(61°)
			00	(Diffused)

Electronics: **BC** (pag 873) | Recessed casing (pag 873)

Sub_Q | powerLED





1 m | III | C.C. | IK10 | IP68

	Cct	lm S - lm D	Opt	
C.C. - 500 mA - 1,5 W DC				
SE **97317**	**M**	199 - 150	**15**	(21°)
	W	213 - 161	**30**	(27°)
	N	227 - 171	**60**	(61°)
			00	(Diffused)

Electronics: **BC** (pag 873) | Recessed casing (pag 873)

Electronics

BC 500 mA


89422	**89423**	**C-E200007**	**C-E200003**
ON/OFF	ON/OFF	ON/OFF	DALI/PUSH
1 - 2 art.	2 - 3 art.	3 - 6 art.	5 - 12 art.
74 x 65 x h 27	74 x 65 x h 27	135 x 26 x h 26	125 x 45 x h 30
		35	55

Recessed casing



ABS **98148** Recessed casing IP68

suitable for: Sub_R - Sub_Q



ABS **98060** Recessed casing

suitable for: Sub_R - Sub_Q

Finishes	**Cct**			
SE Stainless Steel	**M** 2700	**N** 4000	**Underwater**	
	W 3000			


SUELO

AISI 316L stainless steel body.



Suelo_R | powerLED






IK09 IP68 C.C. 1 m

	Cct	lm S - lm D	Opt
350 mA - 1 W DC			
SE **80432**	**M**	145 - 105	**20** (26°)
	W	154 - 112	**35** (37°)
	N	165 - 120	

Electronics: **BB** (pag 875) | Recessed casing (pag 875)

Suelo_RX Pro | powerLED





IK10 IP68 C.C. 5 m

	Cct	lm S - lm D	Opt
630 mA - 2 W DC			
SE **93114**	**W**	233 - 188	**08** (11°)
	N	249 - 200	**15** (21°)
			30 (27°)
			60 (61°)
			12 (113°)
			00 (Diffused)

Electronics: **BD** (pag 875) | Recessed casing (pag 875)

IK10 IP68 C.C. 5 m

	Cct		Opt
RGB - 220 mA - 2,1 W DC			
SE **94151**	**Z**	RGB	**60** (61°)
			12 (113°)

Electronics: **CC** (pag 875) | Recessed casing (pag 875)

For cables and power supply/control contact Linea Light support service.

Electronics

BB 350 mA

89419	89421	C-E200006	C-E200004
ON/OFF	ON/OFF	ON/OFF	DALI/PUSH
1 - 2 art.	3 - 6 art.	6 - 12 art.	5 - 12 art.
74 x 65 x h 27	74 x 65 x h 27	135 x 26 x h 26	125 x 45 x h 30
		35	55


BD 630 mA

89420	C-E200008	99186	C-E200002
ON/OFF	ON/OFF	ON/OFF	DALI/PUSH
1 - 2 art.	3 - 6 art.	6 - 12 art.	5 - 12 art.
74 x 65 x h 27	135 x 26 x h 26	117 x 92 x h 38	125 x 45 x h 30
	35		55

CC 48 V

C-E700003+C-W600001	C-E500015	DMX	Driver CV	Switching
Dimmer RF	Dimmer DMX	Controllers	CV 48V	CV 48V
6 - 12 art.	6 - 12 art.			
175 x 45 x h 27	107 x 96 x h 39		Pag. 950-951	Pag. 945-946
52		Pag. 963		

Recessed casings



ABS **99678** Recessed casing IP68

suitable for: Suelo_R



ABS **84945** Outer casing IP68 with side outlet

suitable for: Suelo_RX Pro



ABS **84990** Outer casing IP68 with central outlet

suitable for: Suelo_RX Pro

Finishes	Cct			
SE Stainless Steel	**M** 2700	**N** 4000		
	W 3000	**Z** RGB		

MK68

AISI 316L stainless steel body.



MK68 GOES DOWN AS FAR AS 25 METRES

MK68 is the innovative, IP68 submersible recess-mount, ideal for creating underwater scenes. The waterproof recessed casing allows wall or floor positioning. The special AISI 316L stainless steel structure gives the projector capacity to withstand a depth up to 25 metres.

Flange in electro-polished AISI 316L stainless steel*

* Electro-polishing is an electrochemical process that selectively removes the surface layer of the component, thus reducing the surface roughness and, therefore, any micro irregularities. In addition to the aesthetic factor, this process increases the resistance to corrosion of the material and simplifies the maintenance and cleaning process.

Body in AISI 316L stainless steel

Extra-clear tempered glass



Scale 1:1

A COMPLETE RANGE FOR ALL INSTALLATION CONTEXTS

MK68 has an understated design featuring a precision electro-polished AISI 316 steel frame, which is flat for structures covered in tiles or mosaics, or rounded for structures with a waterproofing cover or sheet, flared for surface mounting. The extra-clear tempered glass diffuser with white silk screen-printed edges making it virtually invisible once submerged. The many benefits include the “anti-suction” system which protects from infiltration, Flood, Medium Flood, Medium Wide Flood, Diffused, Elliptic and Asymmetric downlights for optimal distribution of light and mix flux with the possibility of combining and independently controlling different optics. All the models have white 3000K or 4000K or RGBW light sources to create stunning scenarios.

MK68_RF



26W (6Led) 18W RGBW (6Led) 38W (9Led) 25W RGBW (9Led)	14W 13W RGBW	4,5W 4W RGBW
Ø 230 mm *	**Ø 148 mm ***	**Ø 108 mm ***

MK68_R



26W (6Led) 18W RGBW (6Led) 38W (9Led) 25W RGBW (9Led)	14W 13W RGBW
Ø 226 mm *	**Ø 145 mm ***

MK68_RP



26W (6Led) 18W RGBW (6Led) 38W (9Led) 25W RGBW (9Led)	6W 6W RGBW 14W 13W RGBW	4W
Ø 214 mm *	**Ø 134 mm ***	**Ø 55 mm**

MK68_RW



26W (6Led) 18W RGBW (6Led)	14W 13W RGBW
Ø 262 mm *	**Ø 160 mm ***

*** The light fixture can only be installed underwater**

INSTALLATION OPTIONS

Installation on concrete casting with tile or mosaic covering

MK68 RF only with outer casing 83140, 83141, 83142




Installation on concrete casting with sheet covering

MK68 R with outer casing 83197, 83198



Installation on concrete casting with waterproofing cover

MK68 R with outer casing 83141, 83142





PROFESSIONAL OPTICS

The MK68 optic groups have been developed to adapt to any lighting requirement and to different depths.
There are three types of symmetrical optics, Flood and Medium Wide Flood, Diffused, plus two asymmetrical versions.



Diffused **(00/DI)**



Flood **(20/FL)**
Elliptic Medium Flood **(25/EM)**
Medium Wide Flood **(40/MW)**



Asymmetric Wall Washer **(07/WW)**

MIX FLUX OPTICS

In addition to the fixed optics, there are two new types called Mix Flux for the 6 and 9 LED versions: Asymmetric + Wall-Washer and Asymmetric + Flood which, thanks to DALI and DMX protocols, can be controlled independently, increasing the designer's creative possibilities.


Realistic light effects with devices installed in water.

Lamp height from tank floor: 1 m

Flood **(20/FL)** - Elliptic Medium Flood **(25/EM)**


Asymmetric Wall Washer **(07/WW)**






MIX FLUX 31/X1


Optic Asymmetric Wall Washer **(07/WW)** + Optic Elliptic Medium Flood **(25/EM)**






MIX FLUX 32/X2


Optic Asymmetric **(07/WW)** + Optic Flood **(20/FL)**






MIX FLUX 31/X1 *


Optic Asymmetric Wall Washer **(07/WW)**






MIX FLUX 31/X1 *


Optic Elliptic Medium Flood **(25/EM)**






MIX FLUX 32/X2 *


Optic Asymmetric Wall Washer **(07/WW)**





MIX FLUX 32/X2 *


Optic Flood **(20/FL)**




* Independent optics control is not available in the RGBW version.

MK68_RF | powerLED





Recessed casing



ABS **83140** Outer casing IP68 for tiles or mosaics

The light fixture can only be installed underwater

IK10 IP68

		Fin	Cct	Im S - Im D	Opt
C.V. - 12 V DC - 4,5 W DC					
cable 2 m	**84031**		**W**	575 - 473	**20** (21°)
			N	620 - 510	**40** (41°)
					07 (Asym.Ww)
					25 (24°x 49°)
					00 (Diffused)
cable 5 m	**C00316**	**SE**	**W**	575 - 473	**FL** (21°)
cable 15 m	**C00319**		**N**	620 - 510	**MW** (41°)
cable 30 m	**C00322**				**WW** (Asym.Ww)
					EM (24°x 49°)
					DI (Diffused)

Electronics: **ED** (pag 896)


IK10 IP68

		Fin	Cct		Opt
RGBW - C.C. - 350 mA - 4 W DC					
cable 2 m	**84032**		**V**	RGBW (3000 K)	**20** (21°)
			Q	RGBW (4000 K)	**40** (41°)
					07 (Asym.Ww)
					25 (24°x 49°)
					00 (Diffused)
cable 5 m	**C00323**	**SE**	**V**	RGBW (3000 K)	**FL** (21°)
cable 15 m	**C00330**		**Q**	RGBW (4000 K)	**MW** (41°)
					WW (Asym.Ww)
					EM (24°x 49°)
					DI (Diffused)

Electronics: **CP1 12V - CP2 24V** (pag 896)

MK68_RF | powerLED





Recessed casing



ABS **83141** Outer casing IP68 for tiles or mosaics

The light fixture can only be installed underwater
*** The cable cannot be shortened below 30 m**

IK10 IP68

		Fin	Cct	Im S - Im D	Opt
C.V. - 12 V DC - 14 W DC					
cable 5 m	**84033**		**W**	1521 - 1199	**20** (20°÷ 29°)
			N	1640 - 1296	**40** (40°÷ 49°)
					07 (Asym.Ww)
					25 (30°÷39°x41°÷60°)
					00 (Diffused)
cable 15 m	**C00305**	**SE**	**W**	1521 - 1199	**FL** (20°÷ 29°)
cable 30 m	**C00076**		**N**	1640 - 1296	**MW** (40°÷ 49°)
cable 60 m *	**C00077**				**WW** (Asym.Ww)
					EM (30°÷39°x41°÷60°)
					DI (Diffused)

Electronics: **EC** (pag 896)


IK10 IP68

		Fin	Cct		Opt
RGBW - C.C. - 350 mA - 13 W DC					
cable 5 m	**84034**		**V**	RGBW (3000 K)	**20** (20°÷ 29°)
			Q	RGBW (4000 K)	**40** (40°÷ 49°)
					07 (Asym.Ww)
					25 (30°÷39°x41°÷60°)
					00 (Diffused)


Electronics: **CQ1 12V - CQ2 24V** (pag 896)

MK68_RF | powerLED





Recessed casing



ABS **83142** Outer casing IP68 for tiles or mosaics

The light fixture can only be installed underwater

IK10 IP68

	Fin	Cct	Im S - Im D	Opt
C.V. - 12 V DC - 26 W DC				
cable 5 m **84037**		**W**	3042 - 2553	**20** (20°÷ 29°)
		N	3281 - 2754	**40** (40°÷ 49°)
				07 (Asym.Ww)
				25 (30°÷39°x41°÷60°)
				31 (Asym+Ellip.)
				32 (Asym+Flood)
				00 (Diffused)
cable 15 m **C00307**	**SE**	**W**	3042 - 2553	**FL** (20°÷ 29°)
cable 30 m **C00078**		**N**	3281 - 2754	**MW** (40°÷ 49°)
				WW (Asym.Ww)
				EM (30°÷39°x41°÷60°)
				X1 (Asym+Ellip.)
				X2 (Asym+Flood)
				DI (Diffused)

Electronics: **EB** (pag 896)


IK10 IP68 RGBW

	Fin	Cct		Opt
RGBW - C.C. - 500 mA - 18 W DC				
cable 5 m **84039**		**V**	RGBW (3000 K)	**20** (20°÷ 29°)
		Q	RGBW (4000 K)	**40** (40°÷ 49°)
				07 (Asym.Ww)
				25 (30°÷39°x41°÷60°)
				31 (Asym+Ellip.)
				32 (Asym+Flood)
				00 (Diffused)


Electronics: **CR1 12V - CR2 24V** (pag 896)

MK68_RF | powerLED





Recessed casing



ABS **83142** Outer casing IP68 for tiles or mosaics

The light fixture can only be installed underwater

IK10 IP68

	Fin	Cct	Im S - Im D	Opt
C.V. - 12 V DC - 38 W DC				
cable 5 m **84038**		**W**	4563 - 3341	**20** (20°÷ 29°)
		N	4921 - 3604	**40** (40°÷ 49°)
				07 (Asym.Ww)
				25 (30°÷39°x41°÷60°)
				31 (Asym+Ellip.)
				32 (Asym+Flood)
				00 (Diffused)
cable 20 m **C00079**	**SE**	**W**	4563 - 3341	**FL** (20°÷ 29°)
		N	4921 - 3604	**MW** (40°÷ 49°)
				WW (Asym.Ww)
				EM (30°÷39°x41°÷60°)
				X1 (Asym+Ellip.)
				X2 (Asym+Flood)
				DI (Diffused)

Electronics: **EA** (pag 896)


IK10 IP68 RGBW

	Fin	Cct		Opt
RGBW - C.C. - 700 mA - 25 W DC				
cable 5 m **84040**		**V**	RGBW (3000 K)	**20** (20°÷ 29°)
		Q	RGBW (4000 K)	**40** (40°÷ 49°)
				07 (Asym.Ww)
				25 (30°÷39°x41°÷60°)
				31 (Asym+Ellip.)
				32 (Asym+Flood)
				00 (Diffused)

Electronics: **CS1 12V - CS2 24V** (pag 896)

MK68_R | powerLED





Recessed casing



ABS **83197** Outer casing IP68 (sheet)
ABS **83141** Outer casing IP68 (waterproofing)

The light fixture can only be installed underwater
*** The cable cannot be shortened below 30 m**

IK10 IP68

	Fin	Cct	Im S - Im D	Opt
C.V. - 12 V DC - 14 W DC				
cable 5 m **84035**		**W**	1521 - 1199	**20** (20°÷ 29°)
		N	1640 - 1296	**40** (40°÷ 49°)
				07 (Asym.Ww)
				25 (30°÷39°x41°÷60°)
				00 (Diffused)
cable 15 m **C00308**	**SE**	**W**	1521 - 1199	**FL** (20°÷ 29°)
cable 30 m **C00080**		**N**	1640 - 1296	**MW** (40°÷ 49°)
cable 60 m * **C00081**				**WW** (Asym.Ww)
				EM (30°÷39°x41°÷60°)
				DI (Diffused)

Electronics: **EC** (pag 896)


IK10 IP68 +RGBW

	Fin	Cct		Opt
RGBW - C.C. - 350 mA - 13 W DC				
cable 5 m **84036**		**V**	RGBW (3000 K)	**20** (20°÷ 29°)
		Q	RGBW (4000 K)	**40** (40°÷ 49°)
				07 (Asym.Ww)
				25 (30°÷39°x41°÷60°)
				00 (Diffused)

Electronics: **CQ1 12V - CQ2 24V** (pag 896)

MK68_R | powerLED





Recessed casing



ABS **83198** Outer casing IP68 (sheet)
ABS **83142** Outer casing IP68 (waterproofing)

The light fixture can only be installed underwater

IK10 IP68

	Fin	Cct	Im S - Im D	Opt
C.V. - 12 V DC - 26 W DC				
cable 5 m **84041**		**W**	3042 - 2553	**20** (20°÷ 29°)
		N	3281 - 2754	**40** (40°÷ 49°)
				07 (Asym.Ww)
				25 (30°÷39°x41°÷60°)
				31 (Asym+Ellip.)
				32 (Asym+Flood)
				00 (Diffused)
cable 15 m **C00309**	**SE**	**W**	3042 - 2553	**FL** (20°÷ 29°)
cable 30 m **C00082**		**N**	3281 - 2754	**MW** (40°÷ 49°)
				WW (Asym.Ww)
				EM (30°÷39°x41°÷60°)
				X1 (Asym+Ellip.)
				X2 (Asym+Flood)
				DI (Diffused)

Electronics: **EB** (pag 896)


IK10 IP68 +RGBW

	Fin	Cct		Opt
RGBW - C.C. - 500 mA - 18 W DC				
cable 5 m **84043**		**V**	RGBW (3000 K)	**20** (20°÷ 29°)
		Q	RGBW (4000 K)	**40** (40°÷ 49°)
				07 (Asym.Ww)
				25 (30°÷39°x41°÷60°)
				31 (Asym+Ellip.)
				32 (Asym+Flood)
				00 (Diffused)


Electronics: **CR1 12V - CR2 24V** (pag 896)

MK68_R | powerLED





Recessed casing



ABS **83198** Outer casing IP68 (sheet)
ABS **83142** Outer casing IP68 (waterproofing)

The light fixture can only be installed underwater

IK10 IP68

		Fin	Cct	Im S - Im D	Opt	
C.V. - 12 V DC - 38 W DC						
cable 5 m	**84042**		**W**	4563 - 3341	**20**	(20°÷ 29°)
			N	4921 - 3604	**40**	(40°÷ 49°)
					07	(Asym.Ww)
					25	(30°÷39°x41°÷60°)
					31	(Asym+Ellip.)
					32	(Asym+Flood)
					00	(Diffused)
cable 20 m	**C00084**	**SE**	**W**	4563 - 3341	**FL**	(20°÷ 29°)
cable 30 m	**C00310**		**N**	4921 - 3604	**MW**	(40°÷ 49°)
					WW	(Asym.Ww)
					EM	(30°÷39°x41°÷60°)
					X1	(Asym+Ellip.)
					X2	(Asym+Flood)
					DI	(Diffused)

Electronics: **EA** (pag 896)

IK10 IP68 +RGBW

		Fin	Cct		Opt	
RGBW - C.C. - 700 mA - 25 W DC						
cable 5 m	**84044**		**V**	RGBW (3000 K)	**20**	(20°÷ 29°)
			Q	RGBW (4000 K)	**40**	(40°÷ 49°)
					07	(Asym.Ww)
					25	(30°÷39°x41°÷60°)
					31	(Asym+Ellip.)
					32	(Asym+Flood)
					00	(Diffused)

Electronics: **CS1 12V - CS2 24V** (pag 896)

INSTALLATION FLEXIBILITY

Easy installation thanks to versions with cables up to 60 m.




Finishes
Stainless Steel

Cct
W 3000 **V** RGBW 3000
N 4000 **Q** RGBW 4000

Underwater

MK68_RW | powerLED





The light fixture can only be installed underwater

IK10 IP68 NEW

		Fin	Cct	Im S - Im D	Opt
C.V. - 12 V DC - 14 W DC					
cable 5 m	**C00497**	**SE**	**W**	1521 - 1199	**FL** (20°÷ 29°)
cable 20 m	**C00498**		**N**	1640 - 1296	**MW** (40°÷ 49°)
					WW (Asym.Ww)
					EM (30°÷39°x41°÷60°)
					DI (Diffused)

Electronics: **EA** (pag 896)


IK10 IP68 NEW RGBW

		Fin	Cct		Opt
RGBW - C.C. - 350 mA - 13 W DC					
cable 5 m	**C00705**	**SE**	**V**	RGBW (3000 K)	**FL** (20°÷ 29°)
cable 20 m	**C00706**		**Q**	RGBW (4000 K)	**MW** (40°÷ 49°)
					WW (Asym.Ww)
					EM (30°÷39°x41°÷60°)
					DI (Diffused)

Electronics: **CQ1 12V - CQ2 24V** (pag 896)

MK68_RW | powerLED





The light fixture can only be installed underwater

IK10 IP68 NEW


		Fin	Cct	Im S - Im D	Opt
C.V. - 12 V DC - 26 W DC					
cable 5 m	**C00499**	**SE**	**W**	3042 - 2553	**FL** (20°÷ 29°)
cable 15 m	**C00500**		**N**	3281 - 2754	**MW** (40°÷ 49°)
					WW (Asym.Ww)
					EM (30°÷39°x41°÷60°)
					X1 (Asym+Ellip.)
					X2 (Asym+Flood)
					DI (Diffused)

Electronics: **EC** (pag 896)

IK10 IP68 NEW RGBW

		Fin	Cct		Opt
RGBW - C.C. - 500 mA - 18 W DC					
cable 5 m	**C00707**	**SE**	**V**	RGBW (3000 K)	**FL** (20°÷ 29°)
cable 15 m	**C00708**		**Q**	RGBW (4000 K)	**MW** (40°÷ 49°)
					WW (Asym.Ww)
					EM (30°÷39°x41°÷60°)
					X1 (Asym+Ellip.)
					X2 (Asym+Flood)
					DI (Diffused)

Electronics: **CR1 12V - CR2 24V** (pag 896)



Fixing bracket included

MK68 RW
The MK68 family expands installation options with the MK68_RW series. These new luminaires offer versatile surface-mounted solutions, ideal for the lighting refurbishment of older underwater fixtures.

Finishes

Stainless Steel

Cct

W 3000 **V** RGBW 3000
N 4000 **Q** RGBW 4000




SACMI
Imola (Italy)

Architectural Project:
A2 Studio Gasparri e Ricci Bitti
Architetti Associati

Photography:
Lorenzo Rinella

MK68_RP | powerLED






IK10 IP68

	Fin	Cct	Im S - Im D	Opt
350 mA - 4 W DC				
cable 5 m **80314**		**W**	490 - 360	**15** (15°)
		N	529 - 389	**30** (28°)
				60 (59°)

Electronics: **BE** (pag 896)

MK68_RP | powerLED





The light fixture can only be installed underwater
*** The cable cannot be shortened below 30 m**

IK10 IP68

	Fin	Cct	Im S - Im D	Opt
C.V. - 12 V DC - 6 W DC				
cable 5 m **84193**		**W**	945 - 745	**20** (20°÷ 29°)
		N	1019 - 805	**40** (40°÷ 49°)
				25 (30°÷39°x41°÷60°)
				00 (Diffused)
cable 15 m **C00314**	**SE**	**W**	945 - 745	**FL** (20°÷ 29°)
cable 30 m **C00108**		**N**	1019 - 805	**MW** (40°÷ 49°)
cable 60 m ***** **C00109**				**EM** (30°÷39°x41°÷60°)
				DI (Diffused)

Electronics: **EL** (pag 896)

C.V. - 12 V DC - 14 W DC				
cable 5 m **84025**		**W**	1521 - 1199	**20** (20°÷ 29°)
		N	1640 - 1296	**40** (40°÷ 49°)
				25 (30°÷39°x41°÷60°)
				00 (Diffused)
cable 15 m **C00315**	**SE**	**W**	1521 - 1199	**FL** (20°÷ 29°)
cable 30 m **C00110**		**N**	1640 - 1296	**MW** (40°÷ 49°)
cable 60 m ***** **C00111**				**EM** (30°÷39°x41°÷60°)
				DI (Diffused)

Electronics: **EC** (pag 896)

IK10 IP68

	Fin	Cct		Opt
RGBW - C.C. - 220 mA - 6 W DC				
cable 5 m **84194**		**V**	RGBW (3000 K)	**20** (20°÷ 29°)
		Q	RGBW (4000 K)	**40** (40°÷ 49°)
				25 (30°÷39°x41°÷60°)
				00 (Diffused)

Electronics: **CT1 12V - CT2 24V** (pag 896)

RGBW - C.C. - 350 mA - 13 W DC			
cable 5 m **84026**	**V**	RGBW (3000 K)	
	Q	RGBW (4000 K)	

Electronics: **CQ1 12V - CQ2 24V** (pag 896)

Finishes


Stainless Steel

Cct

W 3000 **V** RGBW 3000
N 4000 **Q** RGBW 4000

MK68_RP | powerLED





The light fixture can only be installed underwater

IK10 IP68

		Fin	Cct	Im S - Im D	Opt
C.V. - 12 V DC - 26 W DC					
cable 5 m	**84027**		**W**	3042 - 2553	**20** (20°÷ 29°)
			N	3281 - 2754	**40** (40°÷ 49°)
					25 (30°÷39°x41°÷60°)
					00 (Diffused)
cable 15 m	**C00313**	**SE**	**W**	3042 - 2553	**FL** (20°÷ 29°)
cable 30 m	**C00106**		**N**	3281 - 2754	**MW** (40°÷ 49°)
					EM (30°÷39°x41°÷60°)
					DI (Diffused)

Electronics: **EB** (pag 896)


IK10 IP68

		Fin	Cct		Opt
RGBW - C.C. - 500 mA - 18 W DC					
cable 5 m	**84029**		**V**	RGBW (3000 K)	**20** (20°÷ 29°)
			Q	RGBW (4000 K)	**40** (40°÷ 49°)
					25 (30°÷39°x41°÷60°)
					00 (Diffused)

Electronics: **CR1 12V - CR2 24V** (pag 896)

MK68_RP | powerLED





The light fixture can only be installed underwater

IK10 IP68

		Fin	Cct	Im S - Im D	Opt
C.V. - 12 V DC - 38 W DC					
cable 5 m	**84028**		**W**	4563 - 3341	**20** (20°÷ 29°)
			N	4921 - 3605	**40** (40°÷ 49°)
					25 (30°÷39°x41°÷60°)
					00 (Diffused)
cable 20 m	**C00107**	**SE**	**W**	4563 - 3341	**FL** (20°÷ 29°)
			N	4921 - 3605	**MW** (40°÷ 49°)
					EM (30°÷39°x41°÷60°)
					DI (Diffused)

Electronics: **EA** (pag 896)

IK10 IP68

		Fin	Cct		Opt
RGBW - C.C. - 700 mA - 25 W DC					
cable 5 m	**84030**		**V**	RGBW (3000 K)	**20** (20°÷ 29°)
			Q	RGBW (4000 K)	**40** (40°÷ 49°)
					25 (30°÷39°x41°÷60°)
					00 (Diffused)

Electronics: **CS1 12V - CS2 24V** (pag 896)

REPLACING WITHOUT CHANGING


The new relamping systems have been designed to make the most of all the MK68 technology even in pre-installed outer casings from the previous Admiral collection. A bonus when installing because no structural changes to the swimming pool are required.


To ensure that the lights work correctly, make sure that the outer casting is perfectly sealed (watertight) and replace the previous electronics with the version dedicated to MK68 light fixtures



Relamping kit for outer casing 84937

For installed outer casing, code 84937 Ø131mm (IP68) use the specific adaptor 83223 with MK68_R Ø145 mm (code. 84035 - 84036 - C00308 - C00080 - C00081).





Outer casing IP68 (cod. 84937)

Admiral (cod. 97631, 93495, 97641, 97647, 93503)

Pre-installed outer casing IP68 (cod. 84937)


New adapter (cod. 83223)

MK68_R*

*** The light fixture can only be installed underwater**

MK68_RF Ø205 mm for outer casing 84938

For installed outer casing, code 84938 Ø190mm (IP68) use the new dedicated device Nautlius_RF Ø205 mm (code 76737 - 76738 - C00311 - C00085 - C00086).



Outer casing IP68 (cod. 84938)


Admiral (cod. 97632, 93637, 97643, 97648, 93505)

Pre-installed outer casing IP68 (cod. 84938)

New MK68_RF * Ø 205 3 LED

MK68_RF Ø300 mm for outer casing 84939

For installed outer casing, code 84939 Ø283mm (IP68) use the new dedicated device Nautlius_RF Ø300 mm (code 76733 - 76734 - C00312 - C00104 - 76735 - 76736 - C00105).



Outer casing IP68 (cod. 84939)

Admiral (cod. 97638, 93498, 97691, 97651, 93506)


Pre-installed outer casing IP68 (cod. 84939)

New MK68_RF * Ø 300 6 LED Ø 300 9 LED

*** The light fixture can only be installed underwater**

MK68_RF | powerLED





The light fixture can only be installed underwater
*** The cable cannot be shortened below 30 m**

IK10 IP68

		Fin	Cct	Im S - Im D	Opt
C.V. - 12 V DC - 14 W DC					
cable 5 m	**76737**		**W**	1521 - 1199	**20** (20°÷ 29°)
			N	1640 - 1296	**40** (40°÷ 49°)
					07 (Asym.Ww)
					25 (30°÷39°x41°÷60°)
					00 (Diffused)
cable 15 m	**C00311**	**SE**	**W**	1521 - 1199	**FL** (20°÷ 29°)
cable 30 m	**C00085**		**N**	1640 - 1296	**MW** (40°÷ 49°)
cable 60 m *	**C00086**				**WW** (Asym.Ww)
					EM (30°÷39°x41°÷60°)
					DI (Diffused)

Electronics: **EC** (pag 896)

IK10 IP68


		Fin	Cct		Opt
RGBW - C.C. - 350 mA - 13 W DC					
cable 5 m	**76738**		**V**	RGBW (3000 K)	**20** (20°÷ 29°)
			Q	RGBW (4000 K)	**40** (40°÷ 49°)
					07 (Asym.Ww)
					25 (30°÷39°x41°÷60°)
					00 (Diffused)

Electronics: **CQ1 12V - CQ2 24V** (pag 896)

Please note: for installation only on outer casing:
84938 Ø190 mm

MK68_RF | powerLED





The light fixture can only be installed underwater

IK10 IP68

		Fin	Cct	Im S - Im D	Opt
C.V. - 12 V DC - 26 W DC					
cable 5 m	**76733**		**W**	3042 - 2553	**20** (20°÷ 29°)
			N	3281 - 2754	**40** (40°÷ 49°)
					07 (Asym.Ww)
					25 (30°÷39°x41°÷60°)
					31 (Asym+Ellip.)
					32 (Asym+Flood)
					00 (Diffused)
cable 15 m	**C00312**	**SE**	**W**	3042 - 2553	**FL** (20°÷ 29°)
cable 30 m	**C00104**		**N**	3281 - 2754	**MW** (40°÷ 49°)
					WW (Asym.Ww)
					EM (30°÷39°x41°÷60°)
					X1 (Asym+Ellip.)
					X2 (Asym+Flood)
					DI (Diffused)

Electronics: **EB** (pag 896)

IK10 IP68

		Fin	Cct		Opt
RGBW - C.C. - 500 mA - 18 W DC					
cable 5 m	**76734**		**V**	RGBW (3000 K)	**20** (20°÷ 29°)
			Q	RGBW (4000 K)	**40** (40°÷ 49°)
					07 (Asym.Ww)
					25 (30°÷39°x41°÷60°)
					31 (Asym+Ellip.)
					32 (Asym+Flood)
					00 (Diffused)

Electronics: **CR1 12V - CR2 24V** (pag 896)


Please note: for installation only on outer casing:
84939 Ø283 mm

Finishes
Stainless Steel

Cct
W 3000 **V** RGBW 3000
N 4000 **Q** RGBW 4000

MK68_RF | powerLED





The light fixture can only be installed underwater
*** The cable cannot be shortened below 30 m**

IK10 IP68

		Fin	Cct	Im S - Im D	Opt
C.V. - 12 V DC - 38 W DC					
cable 5 m	**76735**		**W**	4563 - 3341	**20** (20°÷ 29°)
			N	4921 - 3604	**40** (40°÷ 49°)
					07 (Asym.Ww)
					25 (30°÷39°x41°÷60°)
					31 (Asym+Ellip.)
					32 (Asym+Flood)
					00 (Diffused)
cable 20 m	**C00105**	**SE**	**W**	4563 - 3341	**FL** (20°÷ 29°)
			N	4921 - 3604	**MW** (40°÷ 49°)
					WW (Asym.Ww)
					EM (30°÷39°x41°÷60°)
					X1 (Asym+Ellip.)
					X2 (Asym+Flood)
					DI (Diffused)

Electronics: **EA** (pag 896)

IK10 IP68

		Fin	Cct		Opt
RGBW - C.C. - 700 mA - 25 W DC					
cable 5 m	**76736**		**V**	RGBW (3000 K)	**20** (20°÷ 29°)
			Q	RGBW (4000 K)	**40** (40°÷ 49°)
					07 (Asym.Ww)
					25 (30°÷39°x41°÷60°)
					31 (Asym+Ellip.)
					32 (Asym+Flood)
					00 (Diffused)

Electronics: **CS1 12V - CS2 24V** (pag 896)

Please note: for installation only on outer casing:
84939 Ø283 mm



RESIDENCE IN EKALI
Attica (Greece)
Project: IFI Group

Finishes	Cct			
Stainless Steel	**W**	3000	**V**	RGBW 3000
	N	4000	**Q**	RGBW 4000

Electronics

BE 350 mA

89421
ON/OFF
1 art.
74 x 65 x h 27

C-E200006
ON/OFF
2 - 3 art.
135 x 26 x h 26
35

C-E200004
DALI/PUSH
2 - 3 art.
125 x 45 x h 30
55

CP2 24V

C-E700003+C-W600001
Dimmer RF
3 - 6 art.
175 x 45 x h 27
52

C-E500014
Dimmer DMX
3 - 6 art.
107 x 96 x h 39

DMX
Controllers
Pag. 963

99331
Driver CV 24V
150W DC
158 x 60 x h 35
70

CQ2 24V

C-E700003+C-W600001
Dimmer RF
3 - 6 art.
175 x 45 x h 27
52

C-E500014
Dimmer DMX
3 - 6 art.
107 x 96 x h 39

DMX
Controllers
Pag. 963

99331
Driver CV 24V
150W DC
158 x 60 x h 35
70

CR2 24V

C-E700003+C-W600001
Dimmer RF
1 - 2 art.
175 x 45 x h 27
52

C-E500012
Dimmer DMX
1 - 2 art.
107 x 96 x h 39

DMX
Controllers
Pag. 963

99331
Driver CV 24V
150W DC
158 x 60 x h 35
70

CS2 24V

C-E700003+C-W600001
Dimmer RF
1 - 2 art.
175 x 45 x h 27
52

C-E500003
Dimmer DMX
1 - 2 art.
107 x 96 x h 39

DMX
Controllers
Pag. 963

99331
Driver CV 24V
150W DC
158 x 60 x h 35
70

CT2 24V

C-E700003+C-W600001
Dimmer RF
1 - 2 art.
175 x 45 x h 27
52

C-E500015
Dimmer DMX
1 - 2 art.
107 x 96 x h 39

DMX
Controllers
Pag. 963

99331
Driver CV 24V
150W DC
158 x 60 x h 35
70

EB 12V

83010
ON/OFF
1 - 2 art.
163 x 43 x h 32
54

83013
ON/OFF
1 - 5 art.
191 x 63 x h 38
74

83012
DALI
1 - 2 art.
150 x 53 x h 35
29

83015
DALI
1 - 4 art.
191 x 63 x h 38
29

ED 12V

83010
ON/OFF
1 - 12 art.
163 x 43 x h 32
54

83013
ON/OFF
1 - 32 art.
191 x 63 x h 38
74

83012
DALI
1 - 12 art.
150 x 53 x h 35
29

83015
DALI
1 - 25 art.
191 x 63 x h 38
29

CP1 12V

C-E700003+C-W600001
Dimmer RF
3 art.
175 x 45 x h 27
52

83187
Dimmer DMX
2 - 3 art.
97 x 71 x h 62

DMX
Controllers
Pag. 963

83010
Driver CV 12V
60W DC
163 x 43 x h 32
54

CQ1 12V

C-E700003+C-W600001
Dimmer RF
1 art.
175 x 45 x h 27
52

83187
Dimmer DMX
1 art.
97 x 71 x h 62

DMX
Controllers
Pag. 963

83010
Driver CV 12V
60W DC
163 x 43 x h 32
54

CR1 12V

C-E700003+C-W600001
Dimmer RF
1 art.
175 x 45 x h 27
52

83187
Dimmer DMX
1 art.
97 x 71 x h 62

DMX
Controllers
Pag. 963

83010
Driver CV 12V
60W DC
163 x 43 x h 32
54

CS1 12V

C-E700003+C-W600001
Dimmer RF
1 art.
175 x 45 x h 27
52

83187
Dimmer DMX
1 art.
97 x 71 x h 62

DMX
Controllers
Pag. 963

83010
Driver CV 12V
60W DC
163 x 43 x h 32
54

CT1 12V

C-E700003+C-W600001
Dimmer RF
1 art.
175 x 45 x h 27
52

83187
Dimmer DMX
1 art.
97 x 71 x h 62

DMX
Controllers
Pag. 963

83010
Driver CV 12V
60W DC
163 x 43 x h 32
54

EA 12V

83010
ON/OFF
1 art.
163 x 43 x h 32
54

83013
ON/OFF
1 - 3 art.
191 x 63 x h 38
74

83012
DALI
1 art.
150 x 53 x h 35
29

83015
DALI
1 - 3 art.
191 x 63 x h 38
29

EC 12V

83010
ON/OFF
1 - 4 art.
163 x 43 x h 32
54

83013
ON/OFF
1 - 10 art.
191 x 63 x h 38
74

83012
DALI
1 - 4 art.
150 x 53 x h 35
29

83015
DALI
1 - 8 art.
191 x 63 x h 38
29

EL 12V

83010
ON/OFF
1 - 9 art.
163 x 43 x h 32
54

83013
ON/OFF
1 - 24 art.
191 x 63 x h 38
74

83012
DALI
1 - 9 art.
150 x 53 x h 35
29

83015
DALI
1 - 19 art.
191 x 63 x h 38
29

DMX: for power supply/control contact Linea Light support service



HOTEL DE RUSSIE
Rome (Italy)

Project: Zanon Architetti Associati

Design and L.D.: architect Pietro Paolo Lateano

Green design: Sofia Varoli Piazza

Specialised technical lighting consultancy: architects Carolina De Camillis and Riccardo Fibbi

Photography: Matteo Canestraro


RUBBER 3D PROTECTION



IP68 3m


IP68 and permanent submersion

Rubber 3D PROtection is certified with a grade of IP68, therefore it lends itself well to permanent installations, submerged up to 3 metres, in environments such as pools, fountains, vertical waterfalls, modern showers and similar, at the same time guaranteeing maximum flexibility. In addition, the waterproof power cable allows protection from the water. An amazing 5 metres long, much longer than the average if we consider similar products already available on the market, the cable allows placement of the power supply unit in a separate site, helping the installer and facilitating subsequent maintenance and/or any replacements.





IP69

IP69 is a classification of the German DIN 40050-9 standard that extends the standard IP classification, developed for sectors where supplementary protection against high pressures and high temperatures is needed. Rubber 3D PROtection has passed the IP69 test: once installed in a pool or other environments that require periodic cleaning through the use of a pressure washer, Rubber PROtection withstands jets of high-pressure or hot water aimed directly on the product, without needing to be removed and subsequently repositioned. This is a considerable advantage that lets you avoid maintenance operations which would otherwise be compulsory and need to be repeated over time. IP69 is an additional classification that comes alongside the IP68 standard set forth by the IEC60529 system. Rubber 3D PROtection is certified for both grades of protection.



Rubber 3D PROtection | V3 | LED strip | 24 V DC





10 m | max 3 m

	Cct	Im S/m - Im D/m	Opt	L
CRI 90 - 9,6 W/m				
C0012	**M**	998 - On req	**DI**	**01004** (1 m - 10 W)
	W	1096 - On req		**05004** (5 m - 50 W)
	T	1158 - On req		**10004** (10 m - 100 W)
	N	1206 - On req		


Electronics: **AL** (pag 900) | Accessories (pag 902-903)

10 m | max 3 m

	Cct		Opt	L
CRI 90 - 15 W/m				
C0012	**V**	RBGW (3000 K)	**DI**	**01004** (1 m - 15 W)
				05004 (5 m - 75 W)

For power supply/control contact
Linea Light support service

Electronics: **AM7** (pag 900) | Accessories (pag 902-903)



Electronics

AL | 24 V DC Mono Color

99374	**99331**	**99332**	**83333**	**C-E400002**
ON/OFF	ON/OFF	0/1-10V	DALI/PUSH	DALI/PUSH
75W	150W	150W	150W	240W
210 x 49 x h 25	158 x 60 x h 35	158 x 60 x h 35	188 x 68 x h 34	188 x 68 x h 34
56	70	70	77	77

AM7 | 24 V DC RGBW

C-E700002+C-W600001	**99331**	**C-E700005**	**DMX**	**99331**
Dimmer RF	CV 24V	Dimmer DMX	Controllers	CV 24V
	150 W			150 W
52 x 52 x h 26	158 x 60 x h 35		Pag. 963	158 x 60 x h 35
53	70			70


Finishes **Cct**

White **M** 2700 **T** 3500 **V** RGBW (3000)
W 3000 **N** 4000




Accessories: Rubber 3D PROtection

Linear profile




ASA **C-K100002** 1000 mm - 18 mm - 19 mm
ASA **C-K100001** 2000 mm - 18 mm - 19 mm
suitable for: Rubber 3D PROtection

Linear profile with cable run



ASA **C-K100005** 1000 mm - 39 mm - 19 mm
ASA **C-K100004** 2000 mm - 39 mm - 19 mm
suitable for: Rubber 3D PROtection


Clip



ASA **C-K100003** 50 mm - 18 mm - 19 mm

suitable for: Rubber 3D PROtection


Clip with cable run



ASA **C-K100006** 50 mm - 39 mm - 19 mm

suitable for: Rubber 3D PROtection


Recessed casing + cable gland



PVC **C-C300001** 300 mm - Ø36 mm


suitable for: Rubber 3D PROtection

Rubber profile drilling template



AM **C-V200005** 25 mm - 20 mm - 34 mm
hole Ø 13,2
suitable for: Linear profile Rubber 3D PROtection


Rubber preparation kit



WH **99521** 1100 mm - 40 mm - 23 mm
Niche template

suitable for: Rubber 3D PROtection


Accessory for corrugated preparation



WH **C-K400165** 50 mm - 40 mm - 23 mm
To be combined with Rubber preparation kit 99521

suitable for: Rubber 3D PROtection


Rubber preparation kit



WH **C-K400170** 1010 mm - 40 mm - 27 mm
Niche template


suitable for: Rubber 3D PROtection

Accessory for corrugated preparation or C-C300001



WH **C-K400171** 50 mm - 40 mm - 27 mm
To be combined with Rubber preparation kit C-K400170

suitable for: Rubber 3D PROtection



ASA: Acrylonitrile Styrene Acrylate (thermoplastic material)

Underwater

Finishes

WH White
AM Anodised Aluminium

Accessories

Connector 2 ways



PVC **98990** IP68 min. 2x0,25 mm2
IP68 max. 2x1,0 mm2

suitable for: Rubber 3D PROtection (not suitable RGBW)


Connector 2 ways



PVC **C-W300001** IP68 with GEL 5x1.5 mm2

suitable for: Rubber 3D PROtectionRGBW

Connector



PVC **89548** IP68 with GEL
max. 4x1,5 mm2

suitable for: Rubber 3D PROtection (not suitable RGBW)

Double-sided tape




PVC **99520** 33 m

suitable for: Rubber 3D PROtection

Connector 2 ways C-W300001






MK68
LINEAR
904




MK68 LINEAR TAKES A LEAP FORWARD

MK68 Linear is an adjustable underwater luminaire with IP68 protection rating, designed to create special light effects in swimming pools, water baths or fountains. The revolutionary ZeroAir system definitively prevents the development of humidity inside the product. Available in two sizes with round or square section, two power ratings and with a new Flood optic. The fixture is in polycarbonate with closing elements in AISI 316L stainless steel, and the special structure ensures MK68 Linear is able to resist up to 25 metres in depth.


VERSATILE IN EVERY SITUATION

MK68_LQ:
82650N30
Tank size:
(L x P) 2,5 x 7 m
Tank depth:
0,5 m
Lamp height from tank floor:
0,4 m




ZEROAIR SYSTEM:
LONG LIFE FOR MK68 LINEAR





Thanks to the experience gained in the design of immersion fixtures, Linea Light Group has realized a special system called ZeroAir, which definitively solves the formation of moisture inside the product, so as to preserve the LED circuit from the generation of condensation.



PATENT PENDING

A MEDIUM FLOOD (30) OPTIC TO GO DEEP

MK68 Linear retains its excellent technical features and is enhanced with a new Medium Flood optic, 30° for the version with round section, and 39° for the version with square section.

COMPARISON BETWEEN NEW MEDIUM FLOOD 30 OPTIC AND EXTRA WIDE FLOOD 36 OPTIC



Optic **30**




Optic **36**





MK68_LR | topLED | 12 V DC





5 m

		Cct	lm S - lm D	Opt	
L 694 mm - 11 W DC					
TR	**82642**	**W**	1470 - 1331	**30**	(30°x 90°)
		N	1538 - 1392	**36**	(114°x 111°)
		C	1538 - 1392		
OP	**82646**	**W**	1470 - 1161	**00**	(Diffused)
		N	1538 - 1215		
		C	1538 - 1215		

Electronics: **EI** (pag 909) | Recessed casing (pag 909)

L 1290 mm - 20 W DC					
TR	**82644**	**W**	2940 - 2662	**30**	(30°x 90°)
		N	3078 - 2784	**36**	(114°x 111°)
		C	3078 - 2784		
OP	**82648**	**W**	2940 - 2323	**00**	(Diffused)
		N	3078 - 2430		
		C	3078 - 2430		

Electronics: **EJ** (pag 909) | Recessed casing & Accessories (pag 909)

MK68_LQ | topLED | 12 V DC





5 m

		Cct	lm S - lm D	Opt	
L 694 mm - 11 W DC					
TR	**82650**	**W**	1470 - 1243	**30**	(39°x 90°)
		N	1538 - 1300	**36**	(108°x 102°)
		C	1538 - 1300		
OP	**82654**	**W**	1470 - 1010	**00**	(Diffused)
		N	1538 - 1056		
		C	1538 - 1056		

Electronics: **EI** (pag 909) | Recessed casing (pag 909)

L 1290 mm - 20 W DC					
TR	**82652**	**W**	2940 - 2486	**30**	(39°x 90°)
		N	3076 - 2600	**36**	(108°x 102°)
		C	3076 - 2600		
OP	**82656**	**W**	2940 - 2019	**00**	(Diffused)
		N	3076 - 2112		
		C	3076 - 2112		

Electronics: **EJ** (pag 909) | Recessed casing & Accessories (pag 909)

NO FLEX

MK68 Linear is completed by a new accessory specifically for the 1290mm length. Available for the round and square section, when positioned centrally, it prevents the device from flexing when it is installed under a waterfall, for example. The accessory is included in the MK68_LR 82644, 82648 and MK68_LQ 82652, 82656 models.






Central support bracket included for
MK68_LR code 82644 – 82648



Central support bracket included for
MK68_LQ code 82652 – 82656



4-SPA
Catania (Italy)

Electronics

EI 12 V


83010	83013	83012	83015
ON/OFF	ON/OFF	DALI	DALI
1 - 5 art.	1 - 10 art.	1 - 5 art.	1 - 10 art.
163 x 43 x h 32	191 x 63 x h 38	150 x 53 x h 35	191 x 63 x h 38
54	74	29	29

EJ 12 V

83010	83013	83012	83015
ON/OFF	ON/OFF	DALI	DALI
1 - 3 art.	1 - 6 art.	1 - 3 art.	1 - 6 art.
163 x 43 x h 32	191 x 63 x h 38	150 x 53 x h 35	191 x 63 x h 38
54	74	29	29

Recessed casings & Accessories

Connector gel 2 ways



PVC 98991 IP68 max. 3x1.5 mm2

suitable for: MK68_LR - MK68_LQ


Connector 2 ways



PVC 84893 IP68 min. 2x0,5 mm2 max. 2x2,5 mm2

suitable for: MK68_LR - MK68_LQ


Accessories



IS 83020 Brackets x 2

suitable for: MK68_LR - MK68_LQ

Recessed casing



IS 83022 L 739 mm (suitable for L 694)

IS 83023 L 1335 mm (suitable for L 1290)

suitable for: MK68_LR - MK68_LQ




Cable extension on request:
MK68 Linear 694 mm: 22 metres of cable extension in total
MK68 Linear 1290 mm: 12 metres of cable extension in total

MK68 LINEAR FITS SEAMLESSLY INTO THE STRUCTURE WITH THE NEW OUTER CASING

The outer casing in AISI 316L stainless steel allows an additional recessed installation option for MK68 Linear. Designers now have an extra solution to create special underwater light effects in swimming pools, pools or fountains. The integrated bracket has been designed to allow easy installation and removal of the device, especially during maintenance and cleaning operations. The outer casing is available for the MK68_LR and MK68_LQ models with the 694 mm and 1290 mm length.





Finishes

IS Steel

Underwater


RODIX

AISI 316L stainless steel body.



Rodix | powerLED | 12 V DC





5 m

	Cct	lm S - lm D	Opt	
L 350 mm - 6 LEDs - 14 W DC				
SE **84212**	**M**	1596 - 905	**15**	(Asym. + 23°)
	W	1704 - 967	**30**	(Asym. + 30°)
	N	1818 - 1036	**60**	(Asym. + 40°)
			25	(Asym. + 30°x40°)

Electronics: **EN** (pag 911) | Recessed casing (pag 911)

L 600 mm - 12 LEDs - 28 W DC				
SE **84213**	**M**	3192 - 1813	**15**	(Asym. + 23°)
	W	3408 - 1937	**30**	(Asym. + 30°)
	N	3636 - 2075	**60**	(Asym. + 40°)
			25	(Asym. + 30°x40°)

Electronics: **EM** (pag 911) | Recessed casing (pag 911)



Cable extension on request:
Rodix 350 mm: 20 metres of cable extension in total
Rodix 600 mm: 10 metres of cable extension in total

Electronics

EM 12 V


83010	83013	83012	83015
ON/OFF	ON/OFF	DALI	DALI
1 art.	1 - 3 art.	1 art.	1 - 3 art.
163 x 43 x h 32	191 x 63 x h 38	150 x 53 x h 35	191 x 63 x h 38
54	74	29	29

EN 12 V

83010	83013	83012	83015
ON/OFF	ON/OFF	DALI	DALI
1 - 4 art.	1 - 7 art.	1 - 4 art.	1 - 7 art.
163 x 43 x h 32	191 x 63 x h 38	150 x 53 x h 35	191 x 63 x h 38
54	74	29	29


Recessed casings & Accessories

Connector gel 2 ways



PVC **98991** IP68 max. 3x1.5 mm2

suitable for: Rodix L 350 mm - Rodix L 600 mm



IS **83160** Recessed casing


suitable for: Rodix L 350 mm

Connector 2 ways



PVC **84893** IP68 min. 2x0,5 mm2
max. 2x2,5 mm2

suitable for: Rodix L 350 mm - Rodix L 600 mm



IS **83161** Recessed casing

suitable for: Rodix L 600 mm

Finishes	Cct			
SE Stainless Steel	**M**	2700	**N**	4000
	W	3000		



INDUSTRIAL LIGHTS





CANTINA PODVERSIC DAMIJAN
Gorizia (Italy)

Lighting Design:
Architect Massimiliano Zanon

Photography:
TheStudio

Industrial lights range index

Multilamp

Multilamp



917

Raptor

Raptor



920

Alix

Alix

NEW



923

Alix Pro

NEW



923

Alux

Alux



926

Alux Pro



926

Atix

Atix




929



MULTILAMP


Construction details

Light fixture with made in 6060 anodised black or RAL9003 White painted extruded aluminium. Side plugs in painted steel (black or white to match the projector body). Optics assembly in UV ray stabilised polycarbonate that also acts as a protective screen. Tightening screws and brackets in AISI 316 steel.



Multilamp | topLED | 220-240 V AC | 63 W DC - 70 W AC






2 m

	Cct	lm S - lm D	Opt
WH **90443**	**W**	10180 - 8394	**30** (43°)
BB **90442**	**N**	10638 - 8772	**90** (84°)
DALI	**C**	11201 - 9237	**12** (104°)
WH **90445**			
BB **90444**			
TWIL			
BB **90473**			

Accessories: (pag 917)

Configuration with code **98758**



Metallic cage to protect against impact. With protection, compliant with standards EN13964 (annex D) and DIN 57710-13.

IK08 → IK10





Suspension configuration with code **98748**

Surface configuration with code **98748**



Accessories

Steel clip



IS **98748**

suitable for:
Multilamp 70W (2 x **98748**)

Steel clip bracket for dual installation, hanging or surface mounted (chains not included).

Adjustable bracket



IS **98755** 70W

suitable for: Multilamp

Adjustable bracket in steel with screws and safety pins for wall or ceiling installation.

Hanging bracket




IS **98754**

suitable for:
Multilamp 70W (2 x **98754**)

Steel bracket for ceiling installation (chains not included).

Protective cage




IS **98758**

suitable for:
Multilamp 70W (1 x **98758**)

Protective metal cage, ideal for increasing the impact resistance of the device.

Flush frame




WH **98761** L 308 mm
BB **98764** L 308 mm

suitable for: Multilamp

Protective metallic cage, ideal for increasing the impact resistance of the fixture.

Flush frame



WH **99585**
BB **99484**

suitable for: Multilamp

Frame in painted aluminium for direct recessed installation with screws.

Finishes
WH White IS Steel
BB Black

Cct
W 3000 **C** 6500
N 4000

RAPTOR



DESIGNED FOR WORK

By providing excellent light quality and high lighting performance, is the ideal solution for industrial and commercial lighting. Thanks to its high mechanical strength and ease of installation, it is suitable for large production and logistics spaces.

Strength and performance in any setting
Raptor has been revamped and upgraded. The new light has a single high-performance die-cast aluminium body with low copper content, a structural material that ensures good anti-corrosion properties and excellent thermal performance. The diffuser of extra-clear tempered glass can be installed in harsh environments with exposure to chemicals, acids, halides, solvents, grease and oil.



Single die-cast aluminium body with low copper content.

4 mm thick extra-clear tempered glass


Integrated antenna (Twil versions)

3 COB Led
130W
150W

4 COB Led
180W

OPTIC ELLIPTIC (88)


Versions with optic 88 have a double attachment fastening system. This means that the light fixtures can be suspended by chains while maintaining the direction of the light beam. The clear glass diffuser is tempered with a ridged pattern.





Raptor | arrayLED | 220-240 V AC






	Cct	lm S - lm D	Opt
119 W DC - 130 W AC			
AL **77090**	**W**	16404 - 13127	**30** (35° UGR<19)
DALI	**N**	16832 - 13820	**60** (66° UGR<22)
AL **77091**	**C**	17031 - 14097	**90** (94°)
Twil			**12** (107°)
AL **77092**			**88** (34°x60°)
138 W DC - 150 W AC			
AL **77093**	**W**	20916 - 15969	**30** (35° UGR<19)
DALI	**N**	21687 - 16812	**60** (66° UGR<22)
AL **77094**	**C**	21933 - 17149	**90** (94°)
Twil			**12** (107°)
AL **77095**			**88** (34°x60°)


Raptor | arrayLED | 220-240 V AC





	Cct	lm S - lm D	Opt
165 W DC - 180 W AC			
AL **77096**	**W**	25744 - 19605	**30** (35° UGR<19)
DALI	**N**	26693 - 20641	**60** (66° UGR<22)
AL **77097**	**C**	26997 - 21054	**90** (94°)
Twil			**12** (107°)
AL **77098**			**88** (34°x60°)

GROUND LIGHTING WITH OPTICS: MEDIUM FLOOD, WIDE FLOOD, EXTRA WIDE FLOOD



Finishes

AL Aluminium

Cct

W 3000 **C** 5000
N 4000



ROTOCART HQ
Treviso (Italy)
Photography: Quasar


ALIX

Body in polycarbonate with UV protection.




Alix | topLED | 220-240 V AC





Alix PRO | topLED | 220-240 V AC





IK08 IP66 NEW

	Fin	Cct	lm S - lm D	Opt
L 1240 - 27 W DC - 30 W AC				
C00908	**GG**	**N**	3900 - On req	**DI** (Diffused)
L 1640 - 42 W DC - 47 W AC				
C00909	**GG**	**N**	6100 - On req	**DI** (Diffused)

IK10 IP69K NEW

	Fin	Cct	lm S - lm D	Opt
L 1213 - 30 W DC - 32 W AC				
C00910	**GG**	**N**	4000 - On req	**DI** (Diffused)
DALI - 30 W DC - 32 W AC				
C00911	**GG**	**N**	4000 - On req	**DI** (Diffused)
L 1493 - 46 W DC - 51 W AC				
C00912	**GG**	**N**	6000 - On req	**DI** (Diffused)
DALI - 46 W DC - 51 W AC				
C00913	**GG**	**N**	6100 - On req	**DI** (Diffused)

CIRCULAR PRODUCT:

100%
RECYCLED

The Alix luminaire body is 100% recyclable, and the electronic components can be easily separated to facilitate recycling at the end of its service life.

The connection of Alix and Alix Pro luminaires **is quick and easy**, without the need for tools.



IP69K DALI

Alix PRO

IP69K is a classification that extends the protection classification system against the ingress of solids and liquids. IP69K was developed for areas where additional protection against high pressures and high temperatures is required.
Typical applications requiring this classification involve mobile environments or machinery such as in the food industry, where equipment is cleaned intensively every day with high-pressure water, steam and aggressive detergents.

Thanks to a special switch, Alix luminaires **can be adapted** to the requirements of any project:

C00908 Step 1 = 30W (3900 lm) → Step 2 = 20W (2500 lm)
C00909 Step 1 = 47W (6100 lm) → Step 2 = 33W (4300 lm)



Accessories




SE **INCLUDED**

Steel clip bracket for dual installation, hanging or surface mounted (chains not included).

suitable for: Alix / Alix PRO





Finishes
GG Grey
SE Stainless Steel

Cct
N 4000

ALUX

Body in anodised extruded aluminium.
Extra-clear tempered glass or
polycarbonate diffuser.

Construction details
Waterproof structure made in anodised extruded aluminium, polycarbonate or impact-resistant toughened glass cover. Driver built into the lamp body with direct connection to the mains power via neoprene cable.




Alux




Alux Pro


Resistance to corrosion (Side cap Alux Pro)
An electrochemical open-pore anodising pretreatment is carried out on the base allow to guarantee resistance to the corrosion typical in environments where aggressive substances are in the air. The TCS® valve is built into the closing plug of the profile for transpiration.



Alux Pro 100 W
TWIL version




High-performance optics
The high precision optics used perfectly convey the emission of the primary light cone, significantly decreasing the light of the secondary cone. By using Medium Flood or Wide Flood optics, the result is a particularly intense and uniform light, without reflections.



Alux | topLED | 220-240 V AC





EL

* The driver contained in the device complies with IEC 61347-2-13 annex J, and can therefore be powered by centralized power supply systems.

IK07 Glass, IK10 Poly, IP65, *

	Cct	lm S - lm D	Opt	
L 627 mm - 24 W DC - 27 W AC				
GA **84418**	**W**	3852 - 2929	**30**	(23°x 46°)
LA **84421**	**N**	4029 - 3060	**60**	(48°x 64°)
DALI	**C**	4029 - 3060	**12**	(118°)
GA **84424**			**00**	(Diffused)
LA **84427**			**69**	(74°x 120°)
L 1212 mm - 49 W DC - 54 W AC				
GA **84419**	**W**	7704 - 5859	**30**	(23°x 46°)
LA **84422**	**N**	8057 - 6127	**60**	(48°x 64°)
DALI	**C**	8057 - 6127	**12**	(118°)
GA **84425**			**00**	(Diffused)
LA **84428**			**69**	(74°x 120°)
L 1505 mm - 60 W DC - 64 W AC				
GA **84420**	**W**	9340 - 7125	**30**	(23°x 46°)
LA **84423**	**N**	9768 - 7444	**60**	(48°x 64°)
DALI	**C**	9768 - 7444	**12**	(118°)
GA **84426**			**00**	(Diffused)
LA **84429**			**69**	(74°x 120°)


IK07 Glass, IK10 Poly, IP65, EM

	Cct	lm S - lm D	Opt	
L 1227 mm - EMERGENCY - 49 W DC - 54 W AC				
GA **84430**	**W**	7704 - 5858	**30**	(23°x 46°)
LA **84431**	**N**	8057 - 6127	**60**	(48°x 64°)
	C	8057 - 6127	**12**	(118°)
			00	(Diffused)
			69	(74°x 120°)

Emergency: 1 Hours - 5W DC - lm D: (W) 768, (N) 813 (C) 813
Accessories (pag 927)

Alux Pro | topLED | 220-240 V AC





IK06, IP65

	Cct	lm S - lm D	Opt	
L 454 - 35 W DC - 40 W AC				
GA **81774**	**W**	5390 - 4912	**30**	(32°)
DALI	**N**	5635 - 5137	**60**	(53°)
GA **81775**			**12**	(120°)
			00	(Diffused)
			69	(76°x 121°)
L 844 - 65 W DC - 70 W AC				
GA **81776**	**W**	10055 - 9208	**30**	(32°)
DALI	**N**	10538 - 9618	**60**	(53°)
GA **81777**			**12**	(120°)
			00	(Diffused)
			69	(76°x 121°)
L 1234 - 90 W DC - 100 W AC				
GA **81778**	**W**	13891 - 12672	**30**	(32°)
DALI	**N**	14558 - 13265	**60**	(53°)
GA **81779**			**12**	(120°)
Twil**			**00**	(Diffused)
GA **76010**			**69**	(76°x 121°)

**Only Indoor | Accessories (pag 927)

Finishes

GA Glass/Aluminium
LA Polycarbonate/Aluminium

Cct

W 3000 **C** 5700
N 4000



Accessories



BB 84863 Extension cables in neoprene ON-OFF (per meter) 3x1mm2. Example: 84863 x 3 pz = 3m



BB 99737 Quick connector ON-OFF IP68 2 ways (3 poles).



BB 83239 Extension cables in neoprene DALI (per meter) 5x2,5mm2. Example: 83239 x 3 pz = 3m

Finishes

BB Black

ATIX


The ATEX explosion-proof watertight appliances, designed with latest-generation technological materials are suitable for lighting areas with atmospheres at risk of explosion.



Places of use

- Mining sites
- Petrochemical industries
- Service stations
- Electrical power plants
- Chemical industries
- Pharmaceutical industries
- Food industries






IK08 IP66 EX 2,22

	Cct	Im S - Im D	Opt
L 1587 mm - 36 W DC - 38 W AC			
YY **93282**	**N**	6590 - 6045	**12** (69°x 179°)

Body in compressed fibreglass reinforced with RAL 1003 yellow polyester. Transparent diffuser in ridged polycarbonate with UV protection. Stainless steel locking clip.





ATEX explosion proof

The Atex articles are designed with extremely high quality tested materials to guarantee adequate resistance and function. They are, therefore, perfectly suited for use in EX areas in accordance with directive ATEX 2014/34 / EU.

Version suitable for EX zone: **2,22**

II 3 G Ex nA IIC T6 Gc
II 3 D Ex t IIIC T85 °C Dc

Accessories



SE **INCLUDED**


Steel clip bracket for dual installation, hanging or surface mounted (chains not included).

Finishes

YY Yellow
SE Stainless Steel

Cct

N 4000


FL202
C2048
R2007
R2006
C2037
C2045
C2041
C2039
C2029
C2030
R4527
R4521
R4522
C5422
C5411
C5413
R5405
C5412
C5417
R5409
C5423
C5425
X540

ELEC TRONICS

TWIL | pag 932
Bluetooth Silvair | pag 935
Casambi | pag 936

INDOOR

CC On/Off Driver | pag 937
CC Triac Driver | pag 939
CC 0/1-10V Driver | pag 940
CC DALI Driver | pag 941
CV-CC 0/1-10V & DALI Converter | pag 944
CV On/Off Driver | pag 944
CV On/Off Switching | pag 945
CV Triac Driver | pag 946
CV DALI Driver | pag 946
CV 0/1-10V, DALI & PUSH Dimmer | pag 947

OUTDOOR

CC On/Off Driver | pag 948
CC 0/1-10V Driver | pag 949
CC DALI Driver | pag 949
CV On/Off Driver | pag 950
CC-CV On/Off Converter | pag 952
CV 0/1-10V Driver | pag 952
CV DALI Driver | pag 952

MASTER & CONTROLLER


Master Triac | pag 954
Master DALI | pag 954
Dimmer CC radio frequency | pag 957
Dimmer CV radio frequency | pag 957
Dimmer CV SPI | pag 958
Dimmer CC & CV DALI DT8 | pag 959
Dimmer CC & CV DALI DT6 | pag 960
Signal Converter DMX/DALI | pag 961
Dimmer CC DMX | pag 961
Dimmer CV DMX | pag 962
Master DMX | pag 963
Master Pixel/SPI | pag 964

EMERGENCY

Emergency light kit | pag 968

Tanqueray | C.C. Driver TWIL






	Range	Output	Input	Eff.	PF	Surge
C-E100006	11W DC	300mA 9-37V	220-240V AC	80%	0.84	4 kV
C-E100035	12W DC	350mA 9-37V	220-240V AC	80%	0.84	4 kV
C-E100007	16W DC	450mA 9-37V	220-240V AC	84%	0.91	4 kV
C-E100036	18W DC	500mA 9-37V	220-240V AC	84%	0.91	4 kV
C-E100037	23W DC	630mA 9-37V	220-240V AC	86%	0.94	4kV
C-E100008	25W DC	700mA 9-37V	220-240V AC	86%	0.94	4kV
C-E100009	35W DC	950mA 9-37V	220-240V AC	88%	0.97	4kV

Driver with Twil technology characterised by a constant current output which makes it ideal for any independent application from 11W to 35W.

JRose | C.V. driver TWIL 2 outputs 24/48 V DC






	Range	Output	Input	Surge
C-E500001	2ch. x (1-96W stripLED/ch.)	2xch 4A 24V	220-240V AC	1 kV
	2ch. x (1- 72W stripLED/ch.)	2xch 3A 48V		

Converter with Twil technology for strip LEDs, characterised by two 24/48 VDC outputs. It also features a simplified DALI interface to send commands via broadcast (DAPC broadcast).

Adamus | Controller TWIL-DALI | Stand-Alone






	Output	Input	Network standard	
C-E700007	DALI 100mA	220-240V AC	IEEE 802.11 a/b/g/n	MiWi IEEE 802.15.4

Controller for DALI driver via TWIL ecosystem. With this device, it is possible to include drivers with a DALI interface (up to 32 drivers) in the TWIL network, centralising the control and monitoring of the devices. It is possible to automate control by means of the TWIL sensors and time events. Compatible with D4i drivers for power and energy monitoring. Built-in DALI bus power supply.

Adamus-T | Controller TWIL-DALI | Track






	Type	Output	Input	Network standard	
C-E700031	WH	DALI 100mA	220-240V AC	IEEE 802.11 a/b/g/n	MiWi IEEE 802.15.4
C-E700008	BB	DALI 100mA	220-240V AC	IEEE 802.11 a/b/g/n	MiWi IEEE 802.15.4

TWIL-DALI controller for devices with DALI protocol installed on a three-phase track. The controller can manage up to 32 devices and each gateway can manage up to 80 Adamus-T Controllers.

Giniu | PIR+LUX Sensor






	Type	Network standard		Input
83236	GG	IEEE 802.11 a/b/g/n	MiWi IEEE 802.15.4	220-240V AC

Giniu is a multi-purpose wireless sensor equipped with light and motion detection devices. The two sensors can be individually deactivated and adjusted, allowing for three different detection modes. (LUX-sensor, MOTION-sensor, and BI-sensor).

Accessories: (pag 934)

Giniu-PRO | PIR+LUX Sensor MICROWAVE






	Type	Network standard		Input
C-E900005	GG	IEEE 802.11 a/b/g/n	MiWi IEEE 802.15.4	220-240V AC

Wireless multifunctional sensor equipped with a motion and brightness detection device. The two sensors can be individually deactivated and adjusted, allowing for three different detection modes. (LUX-sensor, MOTION-sensor, and BI-sensor). This sensor works horizontally with a detection range of up to 10 m and it is designed for harsh indoor environments (shock resistance, presence of dust, etc.). It can also be placed behind non-metallic covers (e.g. glass and plastic).

Accessories: (pag 934)

Giniu-PRO-D | Distance FMCW sensor





IP40 NEW


	Type	Network standard		Input
C-E900006	GG	IEEE 802.11 a/b/g/n	MiWi IEEE 802.15.4	220-240V AC

The sensor is equipped with a powerful and reliable microwave distance sensor based on the FMCV (Frequency Modulated Continuous Wave) system, which can detect the distance (on the vertical and horizontal axis) of one or more items of various sizes up to a maximum of 20 metres. By monitoring the variations in the detected measurements, it is possible to determine the movement of obstacles in the work area or accurately measure levels of solids, liquids and granular materials. Not only can it be interfaced with Twil devices, but it is also possible to connect it to generic loads via a normally closed or normally open contact. The contact can also be connected to a DALI interface.

Accessories: (pag 934)

Twil Gateway







III IP40

	Type	Network standard	
83237	BB	IEEE 802.11 a/b/g/n	MiWi IEEE 802.15.4

Connection to mobile devices is done via the Twil Gateway, which converts Wireless signals into MiWi signals. In this way, Twil technology can be used on all IT networks. If the existing IT network cannot be used, the Gateway Hotspot function can be used to generate an autonomous and independent Wireless network. WARNING: a Twil Gateway can control up to 80 devices with Twil technology. As general indications we can provide the following maximum distances between Twil Gateway and Twil device: Maximum radius of 50m around the Twil Gateway

Push Twil







IP40 NEW

	Type	Network standard		Input
C-E700006	GG	IEEE 802.11 a/b/g/n	MiWi IEEE 802.15.4	220-240V AC

Industrial push-button panel thanks to which Twil lamps and sensors can be physically controlled; it consists of 4 push-buttons that can call up to 8 different lighting scenarios that can be programmed via APP. The Switch is ideal for managing lighting quickly, especially in small installations. The device works connected to the Wi-Fi router and transmits commands to the gateways, which communicate with the associated Twil devices.

Push Converter






IP40 NEW

	Type	Network standard		Input
C-E700009	GG	IEEE 802.11 a/b/g/n	MiWi IEEE 802.15.4	220-240V AC

It is a signal converter for commercial push-buttons that is installed inside the 503 box. Thanks to the smart converter, it is possible to manage scenarios, which can be programmed via APP, without having to change the aesthetics of the existing buttons.

TP-Link EX530v | Wireless router






III IP40 NEW

	Type	Network standard	Radio-frequency	Port
C-E700029	WH	IEEE 802.11 a/b/g/n/ac	2.4 & 5GHz	USB 3.0, gigabit Ethernet

Simultaneous dual band (2.4 + 5 GHz), able to offer a stronger connection with a wider frequency range.

TP-Link | Extender






III IP40

	Type	Network standard	Radio-frequency	Supply
99472	WH	IEEE 802.11 a/b/g/n/ac	2.4 & 5GHz	PoE (power over Ethernet) 802.af or driver

The latest-generation Access Points (802.11ac standard) ensure superior wireless performance and high coverage on 2.4GHz and 5GHz networks. TP-link extender can be used to extend the range of the Wireless signal generated by the TP-Link EX530v router, for installations in areas with very large spaces, where adequate coverage of the Wireless signal is required.

SERVICES

Linea Light Group makes an assistance service available for the realisation of complex projects where Twil light connection technology will be used. A specialised team follows the development of the installation step by step right from the initial phases, guaranteeing the operation of the luminaires by means of function tests and the pre-addressing of the luminaires.



Twil sensors accessories



98659 2 x Couple of side fixing bracket

suitable for: Twil sensor



98658 Fixing hidden bracket

suitable for: Twil sensor



98657 Fixing bracket

suitable for: Twil sensor




98656 Fixing adjustable bracket

suitable for: Twil sensor

Bluetooth Silvair

Hendriks | Driver Bluetooth mesh






C.C. IP40 NEW

	Range	Output	Input	Eff.	PF	Surge
83104	11W DC	300mA 9-37V	220-240V AC	80%	0.84	4 kV
C-E100041	12W DC	350mA 9-37V	220-240V AC	80%	0.84	4 kV
83105	16W DC	450mA 9-37V	220-240V AC	84%	0.91	4 kV
C-E100042	18W DC	500mA 9-37V	220-240V AC	84%	0.91	4kV
C-E100043	23W DC	630mA 9-37V	220-240V AC	86%	0.94	4 kV
83106	25W DC	700mA 9-37V	220-240V AC	86%	0.94	4 kV
83107	35W DC	950mA 9-37V	220-240V AC	88%	0.97	4 kV

Qualified Bluetooth mesh driver featuring a constant current output which makes it ideal for any independent application from 12W to 35W.

Cherokee | Controller Bluetooth mesh 2 outputs 24/48 V DC





C.V. IP40


	Range	Output	Input	Surge
83189	2ch. x (1- 96W stripLED/ch.)	2xch 4A 24V	220-240 V AC	2kV
	2ch. x (1- 72W stripLED/ch.)	2xch 3A 48V	220-240 V AC	

Bluetooth mesh qualified controller featuring two 24/48VDC outputs. Suitable for controlling drivers with 0/1-10V interface. Power metre feature on the primary, measuring power consumption and energy consumed during the entire life cycle of the article. The range of the signal reaches 30 metres as the crow flies and 10 metres in an enclosed environment.

Easyfit | Switch Bluetooth




83017





83226




IP20

	Type	Frequency	Range
83017	WH	Radio Frequency 2.4 GHz	2 button
83226	WH	Radio Frequency 2.4 GHz	4 button

Switch that transmits its status based on Bluetooth low energy technology. No power supply required. The signal range is 10 m in an enclosed environment.

Mura | Sensor Bluetooth mesh





C.V. IP20

	Type	Frequency	Control
83016	WH	Radio Frequency 2.4 GHz	DALI
83225	WH	Radio Frequency 2.4 GHz	1-10V

Bluetooth mesh qualified sensor suitable for controlling DALI or 1/10V drivers with additional DALI or 1/10V bus power supply. The sensor is a LUX/PIR type. Maximum installation height 3 metres. The signal range is 10 m in an enclosed environment.




99309
DALI Power Supply
for **83016**



99658
1-10V Power Supply
for **83225**

Stormshield BT | DALI driver 24V






IP67

	Range	Output	Input	Eff.	PF	Surge
83228	1-120 W DC stripLED	5A 24V	220-240V AC	90%	0.9	2 kV

Driver with qualified Bluetooth mesh. Self-restoring protection against overtemperature, overloads, open circuits and short circuits along the output line. The signal range is 10 m in an enclosed environment.

G500 BT | Gateway Bluetooth mesh






IP20


	Signal output	Signal input	Connector	Power input
83227	Bluetooth 5	Ethernet	CLAMP RJ45	12 V DC

Bluetooth 5 mesh Gateway, TCP/IP, IPv4. Possibility to configure via web page.

Casambi

Leddip | Casambi LED driver






C.C. IP20 NEW

	Range	Output	Input	Eff.	PF	Surge
C-E100019	1.8-10.5W DC	200mA 9-52V	220-240VAC	85%	0.96	2 kV
	2.7-15.5W DC	300mA 9-52V				
	3-18W DC powerLEDs	350mA 9-52V				
	3.6-20W DC arrayLED	400mA 9-52V				
	4.5-26W DC arrayLED	500mA 9-52V				
	5.4-26W DC arrayLED	600mA 9-43V				
	6-26W DC arrayLED	700mA 9-37V				

Multiple power supply equipped with dip-switches for the output current section from 150 to 700 mA. Casambi LED driver. Dimming from 1-100 %. Flicker-free.

Ledmin | Casambi CC 4ch





Made in Italy C.C. IP10 NEW


	Range	Output	Input
C-E500020	4ch. x (2.1-8,4W DC/ch.)	350mA 6-24V	12-24V DC
C-E500021	4ch. x (3-12 W DC/ch)	500mA 6-24V	12-24V DC

	24V DC switching
99371	Peta 50 W
84700	Peta 75 W
99374	Reson 75 W
99331	Reson 150 W

4-channel dimmer with CASAMBI module allows for the control of all types of LEDs: white, dynamic white, RGB and RGBW.

Ledmin | Casambi CV 4ch





Made in Italy C.V. IP10 NEW


	Range	Output	Input
C-E500022	4ch. x (60W DC/ch.)	2.5A 24V	12-24V DC

	24V DC switching
99371	Peta 50 W
84700	Peta 75 W
99374	Reson 75 W
99331	Reson 150 W

4-channel dimmer with CASAMBI module allows for the control of all types of LEDs: white, dynamic white, RGB and RGBW.

BasicDIM | Wireless passive module






IP20 NEW

	Type	Signal Output	Input	Connector
C-E700012	WH	DALI	15-16V DC	CLAMP

The passive wireless module is a BT DALI converter compatible with Casambi, with 4 freely configurable button inputs. The module is powered via the DALI bus, so no additional mains power supply is required.

Ledmin | Converter Casambi DMX





IP10 NEW

	Type	Signal Output	Input	Connector
C-E700021	WH	DMX	12-48V DC	CLAMP

Signal converter from Casambi to DMX. Configurable via Casambi APP.


83009

Power supply

INDOOR | CC On/Off Driver

Bit | On/Off Driver






C.C. IP40

	Range	Output	Input	Eff.	PF	Surge
99243	6.5W DC arrayLED	700mA 10V	220-240V AC	80%	0.6	0.5 kV
99370	10W DC arrayLED	300mA 36V	220-240V AC	80%	0.6	0.5 kV

Protection self-resetting against overheating, overloading, open circuits and short-circuits along the output line.

Slim | On/Off Driver






C.C. IP40

	Range	Output	Input	Eff.	PF	Surge
99307	0.7-1.5W DC powerLEDs	220mA 3-7V	220-240V AC	80%	0.6	4 kV
89144	1-2W DC powerLEDs 1-2.5W DC topLED	350mA 3-7V	220-240V AC	80%	0.6	4 kV
89145	3-6W DC powerLEDs 3.5-7W DC topLED	350mA 9-18V	220-240V AC	80%	0.6	4 kV
99195	1.5-3W DC powerLEDs	500mA 3-7V	220-240V AC	80%	0.6	4 kV
89146	3-5W DC powerLEDs	500mA 6-10V	220-240V AC	80%	0.6	4 kV
89147	2-4W DC powerLEDs	630mA 3-7V	220-240V AC	80%	0.6	4 kV

Smartwave™: excellent efficiency, a long operating life, surge protection and high PF. Protection self-resetting against overheating, overloading, open circuits and short-circuits along the output line.

Slim-12 | On/Off Driver






C.C. IP40

	Range	Output	Input	Eff.	PF	Surge
83007	2-5W DC powerLEDs	220mA 9-18V	220-240V AC	80%	0.9	2 kV
99375	6-12W DC powerLEDs	350mA 17-40V	220-240V AC	80%	0.9	2 kV
99377	4.5-10W DC powerLEDs	500mA 9-18V	220-240V AC	80%	0.9	2 kV
99376	6-12W DC powerLEDs	630mA 9-18V	220-240V AC	80%	0.9	2 kV

Smartwave™: excellent efficiency, a long operating life, surge protection and high PF. Protection self-resetting against overheating, overloading, open circuits and short-circuits along the output line.

K18 | On/Off Driver






	Range	Output	Input	Eff.	PF	Surge
C-E100046	3-20W DC powerLEDs	1050mA 21V	220-240V AC	85%	0.6	2 kV

Protection self-resetting against overheating, overloading, open circuits and short-circuits along the output line.

Simon | On/Off Driver







Easy Plug connector included for codes **99260, 99740**

	Range	Output	Input	Eff.	PF	Surge	
99198	8W DC arrayLED 3-7W DC powerLEDs 8W DC topLED	220mA 17-40V	220-240V AC	89%	0.9	4 kV	
99126	13.5W DC topLED 6-12W DC powerLEDs	350mA 17-40V	220-240V AC	89%	0.9	4 kV	
99128	4.5-9W DC powerLEDs	500mA 9-20V	220-240V AC	89%	0.9	4 kV	
99129	6-12W DC powerLEDs	630mA 9-20V	220-240V AC	89%	0.9	4 kV	
99734	8W DC arrayLED 11W DC arrayLED 15W DC arrayLED	220mA 12-37V 300mA 12-37V 400mA 12-37V	220-240V AC	82%	0.96	2 kV	
99735	6W DC powerLEDs 6.5-7W DC arrayLED 10W DC powerLEDs	500mA 9-12V 700mA 9-12V 800mA 9-12V	220-240V AC	74%	0.96	2 kV	
99260	13W DC topLED	350mA 17-40V	220-240V AC	89%	0.9	4 kV	
99740	8W DC arrayLED 11W DC arrayLED 15W DC arrayLED	220mA 12-37V 300mA 12-37V 400mA 12-37V	220-240V AC	82%	0.96	2 kV	

Smartwave™: excellent efficiency, a long operating life, surge protection and high PF. Protection against overheating, overloading, open circuits and short-circuits along the output line. For codes 99734, 99735 and 99740, the current is selected via the jumper.

Emy | On/Off Driver






	Range	Output	Input	Eff.	PF	Surge
C-E100045	40W DC	1050mA 40V	220-240V AC	88%	0.9	3 kV

Protection self-resetting against overheating, overloading, open circuits and short-circuits along the output line.

Leon | On/Off Driver






Easy Plug connector included for codes **99261, 99112, 99093, 99146.**

	Range	Output	Input	Eff.	PF	Surge
99106	9-18W DC powerLEDs 19W DC topLED	500mA 39V	220-240V AC	91%	0.95	4 kV
99105	12-24W DC powerLEDs	630mA 39V	220-240V AC	91%	0.95	4 kV
99147	25W DC arrayLED	700mA 37V	220-240V AC	91%	0.95	4 kV
99135	30W DC arrayLED 30W DC topLED	840mA 39V	220-240V AC	91%	0.95	4 kV
99239	35W DC arrayLED	950mA 37V	220-240V AC	89%	0.95	4 kV
99261	23W DC topLED	630mA 39V	220-240V AC	91%	0.95	4 kV
99112	25W DC arrayLED	700mA 37V	220-240V AC	91%	0.95	4 kV
99093	30W DC arrayLED 30W DC topLED	840mA 39V	220-240V AC	91%	0.95	4 kV
99146	35W DC arrayLED	950mA 37V	220-240V AC	89%	0.95	4 kV

Smartwave™: excellent efficiency, a long operating life, surge protection and high PF.
Protection against overheating, overloading, open circuits and short-circuits along the output line.

K44 | On/Off Driver






C.C. IP20 NEW

	Range	Output	Input	Eff.	PF	Surge
C-E100033	10/40W DC	300/1050mA 9-45V	220-240V AC	88%	0.95	2 kV

Multi-current driver from 300 to 1050 mA, in 50 mA steps. Self-resetting protection against overheating, overloading, open circuit and short-circuits along the output line.

K53 | On/Off Driver





C.C. IP20 NEW


	Range	Output	Input	Eff.	PF	Surge
C-E100048 / C-E100049	18-50W DC arrayLED	500-1200mA 2.5-44V DC 1250mA 2.5-42V DC 1300mA 2.5-40V DC 1350mA 2.5-39V DC 1400mA 2.5-38V DC	220-240 V AC	89%	≥0.95	1 kV

Multi-current driver from 500 to 1400 mA, in 1 mA steps, settable via smartphone APP NFC. Self-resetting protection against overheating, overloading, open circuit and short-circuits along the output line.

Easy Plug connector included for code **C-E100049.**

Wade | On/Off Driver






C.C. IP20

	Range	Output	Input	Eff.	PF	Surge
99717	70W DC topLED	1.75A 37V	220-240V AC	88%	0.97	5 kV
99718	90W DC topLED	2.25A 37V	220-240V AC	88%	0.97	5 kV

Protection against overheating, overloading, open circuits and short-circuits along the output line.

VoltEdge | On/Off Driver





C.C. IP20


	Range	Output	Input	Eff.	PF	Surge
83122	38 W DC powerLEDs 46 W DC powerLEDs	600mA 60V 600mA 72V	220-240V AC	90%	0.95	2 kV

Protection against overheating, overloading, open circuits and short-circuits along the output line.

INDOOR | CC Triac Driver

Edge | Triac Multi Current





C.C. IP20


	Range	Output	Input	Eff.	PF	Surge
99141	1-12 W DC powerLEDs 1.5-18 W DC powerLEDs 2-24 W DC powerLEDs 25 W DC arrayLED	350mA 39V 500mA 39V 550mA 39V 700mA 37V	220-240V AC	85%	0.97	1 kV

Adjustment via Phase Cut or TRIAC Dimmer. Operation also at 24V DC, maximum 22W. Selection of output current intensity via dip-switch. Protection against over-temperature, short circuits, overloading and mains overvoltages.

98436
Cable and connector

WT | Triac Multi Current





C.C. IP20

	Range	Output	Input	Eff.	PF	Surge
99360	8 W arrayLED 13 W arrayLED 25 W arrayLED	250mA 37V 350mA 37V 700mA 37V	200-240V AC	88%	0.9	1 kV


Adjustment via Phase Cut or TRIAC Dimmer. Selection of output current intensity via dip-switch. Protection self-resetting against overheating, overloading, open circuits and short-circuits along the output line.

98436
Cable and connector

INDOOR | CC 0/1-10V Driver

Multipower PRO | 0/1-10V PUSH Multi Current






	Range	Output	Input	Eff.	PF	Surge
83143	68 W DC powerLEDs	550mA 108V	99-264V AC	92%	0.95	4 kV

Multipower driver supplied with dip-switch for the selection of the output current. Protections: against overheating and short circuits, against mains voltage spikes, against overloads. Light regulation 0/1 - 100 % by means of PUSH function, 0/1...10 V interface (I=1 mA) or 100 Kohm potentiometer. Possibility to use PUSH function to 4/5 drivers without sync cable. Maximum length of the cable, from push button to last driver, must be max. 15 m.

Slim_PRO | 0/1-10V Driver






	Range	Output	Input	Eff.	PF	Surge
C-E100010	4 W DC	350mA 9-12V	220-240V AC	73%	0.45	2 kV
C-E100004	6 W DC	500mA 6-12V	220-240V AC	72%	0.5	2 kV

Settings via 0/1-10V interface or potentiometer. Self-resetting protection against overheating, overloading, open circuit and short-circuits along the output line.

Simon | 0/1-10V Multi Current








Easy Plug connector included for codes **99739.**

	Range	Output	Input	Eff.	PF	Surge
99732 / 99739	8 W DC arrayLED	220mA 12-37V	220-240V AC	82%	0.96	2 kV
	11 W DC arrayLED	300mA 12-37V				
	15 W DC arrayLED	400mA 12-37V				
99733	6 W DC powerLEDs	500mA 9-12V	220-240V AC	82%	0.96	2 kV
	6,5 W - 8,5 W DC arrayLED	700mA 9-12V				
	10 W DC powerLEDs	800mA 9-12V				

Selection of output current intensity via jumper. Settings via 0/1-10V interface or potentiometer. Protection self-resetting against overheating, overloading, open circuits and short-circuits along the output line.

Boson | 0/1-10V N/O button Multi Current








Easy Plug connector included for codes **99262.**

	Range	Output	Input	Eff.	PF	Surge
99115	1-15 W DC powerLEDs	350mA 45V	220-240V AC	87%	0.6	4 kV
	15 W DC arrayLED	350mA 39V				
	1.5-18 W DC powerLEDs	500mA 39V				
	19 W DC arrayLED	500mA 39V				
	2-20 W DC powerLEDs	630mA 33V				
99262	13 W DC arrayLED	350mA 37V	220-240V AC	87%	0.6	4 kV
	18 W DC arrayLED	500mA 37V				
	20 W DC arrayLED	630mA 33V				

Selection of output current intensity via dedicated terminal. Settings via interface, or 0/1-10V potentiometer, or N/A button. Possibility of connecting up to 50 drivers (via the Sync bus). Protection self-resetting against overheating, overloading, open circuits and short-circuits along the output line.

WT | 0/1-10V Multi Current








98436
Cable and connector

INDOOR | CC DALI Driver

Slim_PRO | DALI2 Push and Simply Dim Multi Current






	Range	Output	Input	Eff.	PF	Surge
C-E100011	4 W DC	350mA 9-12V	220-240V AC	73%	0.45	2 kV
C-E100005	6 W DC	500mA 6-12V	220-240V AC	72%	0.5	2 kV

Settings via DALI interface or Simply Dim. Optimisation of the DALI transmission signal. Protection self-resetting against overheating, overloading, open circuits and short-circuits along the output line.

Slim_PRO HE | DALI2 Push and Simply Dim Multi Current






	Range	Output	Input	Eff.	PF	Surge
C-E100012	8.5-9.5 W DC	700mA 12-13V	220-240V AC	89%	0.5	4 kV
C-E100013	10-11 W DC	800mA 12-13V	220-240V AC	89%	0.5	4 kV

Settings via DALI interface or Simply Dim. Optimisation of the DALI transmission signal. Protection self-resetting against overheating, overloading, open circuits and short-circuits along the output line.

Simon_PRO | DALI2 Push and Simply Dim Multi Current








Easy Plug connector included
for codes **C-E100032.**

	Range	Output	Input	Eff.	PF	Surge
83322 /	2.4-7.4 W DC	200mA 12-36V	220-240V AC	76%	0.91	2 kV
C-E100032	3-9 W DC	250mA 12-36V	220-240V AC	78%	0.94	2 kV
	3.5-11W DC	300mA 12-36V	220-240V AC	80%	0.97	2 kV
	4-13 W DC	350mA 12-36V	220-240V AC	81%	0.97	2 kV
	5-15W DC	400mA 12-36V	220-240V AC	82%	0.98	2 kV
83323	4.5-6 W DC	500mA 9-12V	220-240V AC	72%	0.86	2 kV
	6-8.5 W DC	700mA 9-12V	220-240V AC	73%	0.94	2 kV
	7-9.5 W DC	800mA 9-12V	220-240V AC	74%	0.97	2 kV

Settings via DALI interface or Simply Dim. Optimisation of the DALI transmission signal. Selection of current intensity via dedicated terminal. Protection self-resetting against overheating, overloading, open circuits and short-circuits along the output line.

K18 | DALI2 Push Multi Current






	Range	Output	Input	Eff.	PF	Surge
C-E100047	3-10 W DC	900mA 3-11V	220-240V AC	76%	0.93	1 kV

Settings via DALI2 or PUSH interface. Self-resetting protection against overheating, overloading, open circuit and short-circuits along the output line.

Argo_PRO | DALI2 Push and Simply Dim Multi Current








Easy Plug connector included for codes **C-E100030, C-E00031.**

	Range	Output	Input	Eff.	PF	Surge
C-E100001 / C-E100030	6-15 W DC	400mA 15-36V	220-240V AC	76%	0.93	2 kV
	6.5-16.5W DC	450mA 15-36V	220-240V AC	78%	0.93	2 kV
	7.5-18.5W DC	500mA 15-36V	220-240V AC	80%	0.93	2 kV
	8-20W DC	550mA 15-36V	220-240V AC	81%	0.93	2 kV
	9-22W DC	600mA 15-36V	220-240V AC	85%	0.93	2 kV
C-E100016 / C-E100031	10.5-26 W DC	700mA 15-36V	220-240V AC	85%	0.93	2 kV

Settings via DALI interface or Simply Dim. Optimisation of the DALI transmission signal. Selection of current intensity via dedicated terminal. Protection self-resetting against overheating, overloading, open circuits and short-circuits along the output line.

Argo | DALI Push and Simply Dim Multi Current








Easy Plug connector included for codes **99330.**

	Range	Output	Input	Eff.	PF	Surge
99345 / 99330	6-25W DC arrayLED	700mA 9-37V	220-240V AC	85%	0.95	4 kV
	7.5-30W DC arrayLED	840mA 9-37V				
	9-35W DC arrayLED	950mA 9-37V				

Settings via DALI interface or Simply Dim. Optimisation of the DALI transmission signal. Selection of current intensity via dedicated terminal. Protection self-resetting against overheating, overloading, open circuits and short-circuits along the output line.

Emy | DALI2 PUSH Driver






	Range	Output	Input	Eff.	PF	Surge
99971.02	40W DC	1050 mA 40V	190-240V AC	87%	0.97	2 kV

Settings via DALI2 or PUSH interface. Self-resetting protection against overheating, overloading, open circuit and short-circuits along the output line.

K44 | DALI2 PUSH Driver






	Range	Output	Input	Eff.	PF	Surge
C-E100034	10/40W DC	300/1050mA 9-45V	220-240V AC	88%	0.95	2 kV

Settings via DALI2 or PUSH interface. Multi-current from 300 to 1050mA, in 50mA steps. Self-resetting protection against overheating, overloading, open circuit and short-circuits along the output line.

Dynamic Drive | DRIVER DALI 2 DT8 2CH







	Range	Output	Input	Eff.	PF	Surge
83159	14-35W DC arrayLED	700mA 37V	220-240V AC	88%	0.9	1 kV

Settings via the DALI interface. Driver for Dinamic White DT8. Dimming level from 0/1-100%.

LumiTune | DRIVER DALI 2 DT8 2CH






	Range	Output	Input	Eff.	PF	Surge
83058	10W DC arrayLED	350mA 39V	120-250V AC	87%	0.9	2 kV
83059	20W DC arrayLED	600mA 39V	120-250V AC	87%	0.9	2 kV
83060	30W DC arrayLED	840mA 39V	120-250V AC	87%	0.9	2 kV
83061	45W DC arrayLED	1250mA 39V	120-250V AC	87%	0.9	2 kV

Settings via the DALI interface. Driver for Dinamic White DT8. dimming level from 0/1-100%.

Planck | DALI Multi Current






98436
Cable and connector

	Range	Output	Input	Eff.	PF	Surge
99373	1-12W DC arrayLED	350mA 34V	220-240V AC	84%	0.9	0,5 kV
	1.5-12W DC powerLED	500mA 24V				
	1.5-12W DC powerLED	600mA 20V				

Recommended for 6W, 8W or two 6W series items. Settings via the DALI interface. Optimisation of the DALI transmission signal. Selection of output current intensity via dip-switch. Protection self-resetting against overheating, overloading, open circuits and short-circuits along the output line.

WT | DALI Multi Current






98436
Cable and connector

	Range	Output	Input	Eff.	PF	Surge
99362	8 W DC arrayLED	250mA 37V	220-240V AC	88%	>0.9	1 kV
	13 W DC arrayLED	350mA 37V				
	25 W DC arrayLED	700mA 37V				

Settings via the DALI interface. Optimisation of the DALI transmission signal. Selection of output current intensity via dip-switch. Protection self-resetting against overheating, overloading, open circuits and short-circuits along the output line.

Multipower | DALI 2 Push 0/1-10V Multi Current






Easy Plug connector
included for codes **83066.**

	Range	Output	Input	Eff.	PF	Surge
83008 / 83066	4-18W DC powerLEDs	350mA 53V	99~264V AC	92%	0.96	4 kV
	6-26W DC powerLEDs	500mA 53V				
	8-31W DC powerLEDs	600mA 53V				
	15W DC arrayLED	400mA 37V				
	25W DC arrayLED	700mA 37V				
	30W DC arrayLED	850mA 37V				
	35W DC arrayLED	950mA 37V				
	45W DC arrayLED	1200mA 37V				

Multipower driver supplied with dip-switch for the selection of the output current. Protections: against overheating and short circuits, against mains voltage spikes, against overloads. RIPPLE FREE ≤ 3%. On request BIS certification. Light regulation 0/1 - 100 % by means of PUSH function, 0/1...10 V interface (I=1 mA) or 100 Kohm potentiometer and DALI. Possibility to use PUSH function to 4/5 drivers without sync cable. Maximum length of the cable, from push button to last driver, must be max. 15 m.

Multipower PRO | DALI2 0/1-10V PUSH Multi Current






	Range	Output	Input	Eff.	PF	Surge
83120	38 W DC powerLEDs	600mA 60 V	99-264V AC	92%	0.95	4 kV
	46 W DC powerLEDs	600mA 72V				

Multipower driver supplied with dip-switch for the selection of the output current. Protections: against overheating and short circuits, against mains voltage spikes, against overloads.
RIPPLE FREE ≤ 3%. On request BIS certification. Light regulation 0/1 - 100% by means of PUSH function, 0/1...10 V interface (I=1 mA) or 100 Kohm potentiometer and DALI. Possibility to use PUSH function to 4/5 drivers without sync cable. Maximum length of the cable, from push button to last driver, must be max. 15 m.

Omnidali | DALI2 Multi Current






	Range	Output	Input	Eff.	PF	Surge
83121	68 W DC powerLEDs	550mA 108 V	99-264V AC	92%	0.98	6 kV

Protections: against overheating and short circuits, against mains voltage spikes, against overloads. Light regulation 0/1 - 100 % by means of DALI.

INDOOR | CV-CC 0/1-10V & DALI Converter

Slim | 0/1-10V Converter






	Range	Output	Input	Eff.
99708	1.6 W powerLEDs	350mA 3-18V	24V DC	95%
99709	1.5-9 W powerLEDs	500mA 3-18V	24V DC	95%
99710	2-12 W powerLEDs	630mA 3-18V	24V DC	95%

Converter 0/1-10V. Settings via 0/1-10V interface or potentiometer. Protection self-resetting against overheating, overloading, open circuits and short-circuits along the output line.

Slim | DALI Converter






	Range	Output	Input	Eff.
99711	1.6 W powerLEDs	350mA 3-18V	24V DC	95%
99712	1.5-9 W powerLEDs	500mA 3-18V	24V DC	95%
99713	2-12 W powerLEDs	630mA 3-18V	24V DC	95%

DALI converter. Settings via the DALI interface. Protection self-resetting against overheating, overloading, open circuits and short-circuits along the output line.


Example:
Slim 0/1-10V Converter
or Slim DALI Converter



INDOOR | CV On/Off Driver

Slim | On/Off Driver






	Range	Output	Input	Eff.	PF	Surge
89408	1-5W DC stripLED 1-5W DC topLED	200mA 24V	220-240V AC	80%	0.6	4 kV

Suitable for powering LED strips, 5 mm LEDs and constant voltage LED top. Protection self-resetting against open circuits and short-circuits along the output line.

Fusion | On/Off Driver






	Range	Output	Input	Eff.	PF	Surge
84829	1-24W DC stripLED 1-24W DC topLED	1A 24V	220-240V AC	88%	0.6	2 kV

Suitable for powering LED strips, 5 mm LEDs and constant voltage LED top. Protection self-resetting against open circuits and short-circuits along the output line.

Reson_75 | On/Off Driver






	Range	Output	Input	Eff.	PF	Surge
99374	1-75 W DC stripLED 1-75 W DC topLED	3.125A 24V	220-240V AC	91%	0.96	4 kV

Suitable for powering LED strips, 5 mm LEDs and constant voltage LED top. Protection self-resetting against open circuits and short-circuits along the output line. High efficiency, long operating life and high PF.

Velar | On/Off Driver






	Range	Output	Input	Eff.	PF	Surge
C-E300009	1-75 W DC stripLED 1-75 W DC topLED	1.550A 48V	220-240V AC	90%	0.96	4 kV
C-E300010	1-150 W DC stripLED 1-150 W DC topLED	3.125A 48V	220-240V AC	91%	0.97	4 kV

Suitable for powering LED strips and constant voltage LED top. Protection self-resetting against open circuits and short-circuits along the output line. High efficiency, long operating life and high PF.

INDOOR | CV On/Off Switching

Peta | Switching Driver 50 W DC






	Type	Output	Input	Cooling	PF
99371	Peta	2.2A 24V	88-264V AC	Natural Convection	No PFC

Protection self-resetting against open circuits and short-circuits along the output line.

Peta / Exa | Switching Driver 75 W DC






	Type	Output	Input	Cooling	PF
84700	Peta	3.2A 24V	88-264V AC	Natural Convection	No PFC

Protection self-resetting against open circuits and short-circuits along the output line.

Peta | Switching Driver 100 W DC






	Type	Output	Input	Cooling	PF
99372	Peta	4.5A 24V	88-264V AC	Natural Convection	No PFC

Protection self-resetting against open circuits and short-circuits along the output line.

Peta / Exa | Switching Driver 150 W DC






	Type	Output	Input	Cooling	PF
84701	Peta	6.5A 24V	88-264V AC	Natural Convection	No PFC

Protection self-resetting against open circuits and short-circuits along the output line.

Peta / Exa | Switching Driver 200 W DC






	Type	Output	Input	Cooling	PF
99682	Peta	8.4A 24V	88-264V AC	Natural Convection	0.95

Protection self-resetting against open circuits and short-circuits along the output line.

Peta / Exa | Switching Driver 320 W DC






C.V.

	Type	Output	Input	Cooling	PF
99683	Peta	13.4A 24V	88-264V AC	Forced Convection	0.95
99725	Exa	6.7A 48V	88-264V AC	Forced Convection	0.95

Protection self-resetting against open circuits and short-circuits along the output line.

Peta | Switching Driver 500 W DC






C.V.

	Type	Output	Input	Cooling	PF
84787	Peta	21A 24V	88-264V AC	Forced Convection	0.95

Protection self-resetting against open circuits and short-circuits along the output line.

Exa | Switching Driver 500 W DC





C.V.


	Type	Output	Input	Cooling	PF
84626	Exa	10A 48V	88-264V AC	Forced Convection	0.95

Protection self-resetting against open circuits and short-circuits along the output line.

INDOOR | CV Triac Driver

Triac | Driver TRIAC PUSH





C.V. IP20 NEW


	Range	Output	Input	Eff.	PF	Surge
C-E300001	1-150W DC	6.25A 24V	220-240V AC	91%	0.99	2 kV

24V constant voltage LED driver, supports Leading edge (Triac), Trailing edge (ELV) or Push DIM from 1% to 100%. Flicker-Free.

INDOOR | CV DALI Driver

DALIFlat Push | Driver DALI PUSH





C.V. IP20


	Range	Output	Input	Eff.	PF	Surge
83062	150W DC	6.25A 24V	220-240V AC	94%	0.99	1 kV

Set-up via the DALI interface. 24V constant voltage LED driver dimmable from 1 to 100% via DALI or PUSH interface. Flicker-Free.

INDOOR | CV 0/1-10V, DALI & PUSH Dimmer

Bode | DALI 0/1-10V dimmer







	Range	Output	Input	Eff.
99074	3ch. x (1-72 W DC stripLED/ch.) 3ch. x (1-72 W DC topLED/ch.)	3A 24V/ch.	24V DC	95%
99660	1-216 W DC stripLED 1-216 W DC topLED	9A 24V	24V DC	95%

Suitable for powering LED strips and 5 mm constant voltage LED tops. Adjustment via DALI, 0/1-10V interface or potentiometer.

Bird Mini | DALI PUSH 0/1-10V dimmer







	Range	Output	Input
83041	1-72 W DC stripLED 1-144 W DC stripLED 1-288 W DC stripLED	6A 12V 6A 24V 6A 48V	12V DC 24V DC 48V DC

Suitable for powering 12/24/48V constant voltage products. Adjustment via DALI, PUSH 1-10V interface.

Bird Maxi | DALI PUSH 0/1-10V dimmer






	Range	Output	Input
83042	1-144 W DC stripLED 1-288 W DC stripLED 1-576 W DC stripLED	12A 12V 12A 24V 12A 48V	12V DC 24V DC 48V DC

Suitable for powering 12/24V constant voltage products. Adjustment via DALI, PUSH 0/1-10V interface or potentiometer.

L400 | DALI PUSH 0/1-10V dimmer






	Range	Output	Input
C-E500023	1-144 W DC stripLED 1-288 W DC stripLED 1-576 W DC stripLED	12A 12V 12A 24V 12A 48V	12V DC 24V DC 48V DC

Suitable for powering 12/24V constant voltage products. Adjustment via DALI, PUSH 0/1-10V interface or potentiometer.

OUTDOOR | CC On/Off Driver

Mini_Penny | On/Off Driver






	Range	Output	Input	Eff.	PF	Surge
89148	1-2 W DC powerLEDs	350mA 6.6V	220-240V AC	80%	0.6	0.5 kV
89149	3-6 W DC powerLEDs	350mA 20V	220-240V AC	80%	0.6	0.5 kV
89150	3-4.5 W DC powerLEDs	500mA 10V	220-240V AC	80%	0.6	0.5 kV
89151	2-4 W DC powerLEDs	630mA 6.6V	220-240V AC	80%	0.6	0.5 kV

Protection self-resetting against overheating, overloading, open circuits and short-circuits along the output line.

Mini_Aqualed | On/Off Driver






	Range	Output	Input	Eff.	PF	Surge
89419	1-2.5 W DC powerLEDs	350mA 7V	220-240V AC	55%	0.45	0.5 kV
89421	3.5-6.5 W DC powerLEDs	350mA 18V	220-240V AC	75%	0.55	0.5 kV
89422	1.5-3.5 W DC powerLEDs	500mA 7V	220-240V AC	65%	0.5	0.5 kV
89423	3-5 W DC powerLEDs	500mA 10V	220-240V AC	75%	0.5	0.5 kV
89420	2-4.5 W DC powerLEDs	630mA 7V	220-240V AC	70%	0.5	0.5 kV

Protection self-resetting against overheating, overloading, open circuits and short-circuits along the output line.

Penny_Q | On/Off Driver






	Range	Output	Input	Eff.	PF	Surge
99716	7.5 W DC topLED	180mA 40V	220-240V AC	76%	0.6	4 kV

Smartwave™: excellent efficiency, a long operating life, surge protection and high PF.
Protection against overheating, overloading, open circuits and short-circuits along the output line.

Penny | On/Off Driver






	Range	Output	Input	Eff.	PF	Surge
99177	6-12 W DC powerLEDs	350mA 39V	220-240V AC	84%	0.96	4 kV
99176	4.5-9 W DC powerLEDs	500mA 20V	220-240V AC	84%	0.96	4 kV
99175	6-12 W DC powerLEDs	630mA 20V	220-240V AC	84%	0.96	4 kV

Smartwave™: excellent efficiency, a long operating life, surge protection and high PF.
Protection against overheating, overloading, open circuits and short-circuits along the output line.

Aqualed | On/Off Driver






	Range	Output	Input	Eff.	PF	Surge
99342	3.8-8.4W DC powerLEDs	220mA 39V	220-240V AC	84%	0.6	4 kV

Protection self-resetting against overheating, overloading, open circuits and short-circuits along the output line.

Aqualed_SLIM | On/Off Driver






	Range	Output	Input	Eff.	PF	Surge
C-E200006	6-12.5 W DC powerLEDs	350mA 17-36V	220-240V AC	>80%	0.9	2 kV
C-E200007	4.5-10W DC powerLEDs	500mA 9-20V	220-240V AC	>80%	0.9	2 kV
C-E200008	6-12.5W DC powerLEDs	630mA 9-20V	220-240V AC	>80%	0.9	2 kV

Self-resetting protection against overheating, overloading, open circuit and short-circuits along the output line.

Maxi_Aqualed | On/Off Driver






	Range	Output	Input	Eff.	PF	Surge
99185	20 W DC arrayLED 9-18 W DC powerLEDs	500mA 39V	198~264V AC	91%	0.95	4 kV
99340	20 W DC arrayLED	580mA 37V	198~264V AC	91%	0.95	4 kV
99186	20 W DC arrayLED 12-24 W DC powerLEDs	630mA 39V	198~264V AC	91%	0.95	4 kV
99269	30 W DC arrayLED	840mA 37V	198~264V AC	91%	0.95	4 kV

Smartwave™: excellent efficiency, a long operating life, surge protection and high PF.
Protection against overheating, overloading, open circuits and short-circuits along the output line.

OUTDOOR | CC 0/1-10V Driver

Stormshield | 0/1-10V Driver







98436
Cable and connector


	Range	Output	Input	Eff.	PF	Surge
99726	70 W DC topLED	1.8A 37V	100-250V AC	93%	0.9	4 kV
99728	90 W DC topLED	2.28A 37V	100-250V AC	93%	0.9	4 kV

Settings via 0/1-10 V interface or potentiometer. Protection self-resetting against overheating, overloading, open circuits and short-circuits along the output line.

OUTDOOR | CC DALI Driver

Aqualed_PRO | DALI2 PUSH Driver






	Range	Output	Input	Eff.	PF	Surge
C-E200005	4-9W DC powerLEDs	250mA 15-36V	220-240V AC	>85%	0.93	2 kV
C-E200004	5-12.5 W DC powerLEDs	350mA 15-36V	220-240V AC	>85%	0.93	2 kV
C-E200003	7.5-18W DC powerLEDs	500mA 15-36V	220-240V AC	>85%	0.93	2 kV
C-E200002	9-21.5W DC powerLEDs	600mA 15-36V	220-240V AC	>85%	0.93	2 kV
C-E200001	10.5-25W DC powerLEDs	700mA 15-36V	220-240V AC	>85%	0.93	2 kV

Settings via DALI interface or Simply Dim. Optimisation of the DALI transmission signal. Protection self-resetting against overheating, overloading, open circuits and short-circuits along the output line.

Stormshield | DALI Driver






	Range	Output	Input	Eff.	PF	Surge
83194	54 W DC topLED	1.45A 36V	100-305V AC	89%	0.9	4 kV
83195	75 W DC topLED	2.1A 36V	100-305V AC	89%	0.9	4 kV

Settings via the DALI interface. Protection self-resetting against overheating, overloading, open circuits and short-circuits along the output line.

Stormshield | DALI Driver






	Range	Output	Input	Eff.	PF	Surge
99727	70 W DC topLED	1.8A 37V	120-277V AC	93%	0.9	2 kV
99729	90 W DC topLED	2.28A 37V	120-277V AC	93%	0.9	2 kV

Settings via the DALI interface. Protection self-resetting against overheating, overloading, open circuits and short-circuits along the output line.

Stormshield | DALI Driver






C.C. | DALI | IP67


	Range	Output	Input	Eff.	PF	Surge
83196	157W DC topLED	4.35A 42V	100-305V AC	92%	0.9	4 kV

Settings via the DALI interface. Protection self-resetting against overheating, overloading, open circuits and short-circuits along the output line.

OUTDOOR | CV On/Off Driver

Stormshield | On/Off Driver 12V







C.V. | IP67

	Range	Output	Input	Eff.	PF	Surge
83010	1-60W DC	5A 12V	90-264V AC	83%	-	3 kV

Suitable for MK68, MK68 Linear. Protection self-resetting against the open circuit and short-circuit along the output line.

Stormshield | On/Off Driver 12V







C.V. | IP67

	Range	Output	Input	Eff.	PF	Surge
83013	120W DC	10A 12V	180-305V AC	87%	-	3 kV

Suitable for MK68, MK68 Linear. Protection self-resetting against the open circuit and short-circuit along the output line.

Aqualed | On/Off Driver 24V






Made in Italy | C.V. | IP67

	Range	Output	Input	Eff.	PF	Surge
89488	1-14.4 W DC stripLED 1-14.4 W DC topLED	600mA 24V	220-240V AC	80%	0.6	0.5 kV

Suitable for powering LED strips, 5 mm LEDs and constant voltage LED top. Protection self-resetting against open circuits and short-circuits along the output line.

Lingotto | On/Off Driver 24V







C.V. | IP67

	Range	Output	Input	Eff.	PF	Surge
83009	1-18 W DC stripLED 1-18 W DC topLED	750mA 24V	220-240V AC	82%	0.6	3 kV

Suitable for powering LED strips, 5 mm LEDs and constant voltage LED top. Protection self-resetting against open circuits and short-circuits along the output line.

Maxi_Aqualed | On/Off Driver 24V






Made in Italy | C.V. | IP67

	Range	Output	Input	Eff.	PF	Surge
89179	1-24 W DC stripLED 1-24 W DC topLED	1A 24V	220-240V AC	88%	0.6	2 kV

Suitable for powering LED strips, 5 mm LEDs and constant voltage LED top. Protection self-resetting against open circuits and short-circuits along the output line.

Giant_Aqualed | On/Off Driver 24V






	Range	Output	Input	Eff.	PF	Surge
89359	1-48 W DC stripLED 1-48 W DC topLED	2A 24V	220-240V AC	89%	0.6	1 kV

Suitable for powering LED strips, 5 mm LEDs and constant voltage LED top. Protection self-resetting against open circuits and short-circuits along the output line.

Reson_150 | On/Off Driver 24V






	Range	Output	Input	Eff.	PF	Surge
99331	1-150 W DC stripLED 1-150 W DC topLED	6.25A 24V	220-240V AC	95%	0.98	5 kV

Suitable for powering LED strips, 5 mm LEDs and constant voltage LED top. Protection self-resetting against open circuits and short-circuits along the output line. High efficiency, long operating life and high PF.

Stormshield | On/Off Driver 24 V






	Range	Output	Input	Eff.	PF	Surge
99786	1-240 W DC stripLED 1-240 W DC topLED	10A 24V	220-240V AC	92%	0.95	6 kV

Suitable for powering LED strips, 5 mm LEDs and constant voltage LED top. Protection self-resetting against the open circuit and the short-circuit along the output line.

Stormshield | On/Off Driver 48 V






	Range	Output	Input	Eff.	PF	Surge
99784	1-150 W DC	3.13A 48V	180-295V AC	91%	0.95	6 kV

Suitable for powering LED strips, 5 mm LEDs and constant voltage LED top. Protection self-resetting against the open circuit and the short-circuit along the output line.

Stormshield | On/Off Driver 48 V






	Range	Output	Input	Eff.	PF	Surge
99785	1-240 W DC	5A 48V	220-240V AC	92%	0.95	2 kV

Suitable for powering LED strips, 5 mm LEDs and constant voltage LED top. Protection self-resetting against the open circuit and the short-circuit along the output line.

OUTDOOR | CC-CV On/Off Converter

Round | On/Off Converter





C.C. IP65


	Range	Output	Input	Eff.
89175	1-3 W DC powerLEDs	350mA 12V	12V DC	95%
	1-6 W DC powerLEDs	350mA 24V	24V DC	95%
89176	1.5-4.5 W DC powerLEDs	500mA 12V	12V DC	95%
	1.5-9 W DC powerLEDs	500mA 24V	24V DC	95%
89177	2-6 W DC powerLEDs	630mA 12V	12V DC	95%
	2-12 W DC powerLEDs	630mA 24V	24V DC	95%

Protection against overheating, overloading, open circuits and short-circuits along the output line.

OUTDOOR | CV 0/1-10V Driver

Reson_150 | 0/1-10V Driver 24 V





C.V. 1-10V IP65


	Range	Output	Input	Eff.	PF	Surge
99332	1-150 W DC stripLED 1-150 W DC topLED	6.25A 24V	220-240V AC	95%	0.98	5 kV

Suitable for powering LED strips, 5 mm LEDs and constant voltage LED top. Protection self-resetting against open circuits and short-circuits along the output line. High efficiency, long operating life and high PF. Adjustment via 0/1-10V interface or potentiometer.

OUTDOOR | CV DALI Driver

Stormshield | DALI Driver 12V






C.V. DALI IP67

	Range	Output	Input	Eff.	PF	Surge
83015	120W DC	10A 12V	90-305V AC	88%	0.9	2 kV

Settings via the DALI interface. Protection self-resetting against overheating, overloading, open circuits and short-circuits along the output line.

Stormshield | DALI Driver 12V






C.V. DALI IP67

	Range	Output	Input	Eff.	PF	Surge
83012	60W DC	5A 12V	90-305V AC	86%	0.9	2 kV

Settings via the DALI interface. Protection self-resetting against overheating, overloading, open circuits and short-circuits along the output line.

Stormshield | DALI Driver 24 V






C.V. DALI IP67

	Range	Output	Input	Eff.	PF	Surge
99722	1-120 W DC stripLED	5A 24V	220-240V AC	90%	0.9	2 kV

Settings via the DALI interface. Protection self-resetting against overheating, overloading, open circuits and short-circuits along the output line.

Power | DALI2 PUSH driver 24V






	Range	Output	Input	Eff.	PF	Surge
83333	1-150 W DC stripLED	6.3A 24V	90-305V AC	90%	0.9	6 kV

Settings via DALI2 or PUSH interface. Optimisation of the DALI transmission signal. Suitable for powering LED strips, 5 mm LEDs and constant voltage LED top. Protection self-resetting against overheating, overloading, open circuits and short-circuits along the output line.

Power | DALI2 PUSH driver 24V






	Range	Output	Input	Eff.	PF	Surge
C-E400002	1-240 W DC stripLED	10A 24V	90-305V AC	90%	0.9	6 kV

Settings via DALI2 or PUSH interface. Optimisation of the DALI transmission signal. Suitable for powering LED strips, 5 mm LEDs and constant voltage LED top. Protection self-resetting against overheating, overloading, open circuits and short-circuits along the output line.

Power | DALI2 PUSH driver 48V






	Range	Output	Input	Eff.	PF	Surge
C-E400003	1-150 W DC stripLED	3.2A 48V	90-305V AC	90%	0.9	6 kV

Settings via DALI2 or PUSH interface. Optimisation of the DALI transmission signal. Suitable for powering strip LEDs and top LEDs at constant 48V voltage. Self-resetting protection against overheating, overloading, open circuit and short-circuits along the output line.

Master Triac

Phasecon | TRIAC controller





C.V. IP20


	Comand	Output	Input	Connector
KIT0027	Push DIM	350W	220-240V AC	CLAMP

Phase Cut Dimmer, via N/A button. Rotating selectors for the choice of dimming and ascent and descent time. AUTO configuration that enables the dimming of any type of 230V AC lamp.

Master DALI

Dali_PS1 | DALI power Supply







C.V. DALI IP20

	Type	Signal Output	Input	Connector
99309	TR	DALI 15-16V DC	220-240V AC	CLAMP

Power supply for 200 mA DALI BUS, for DALI devices, or control modules without own power supply.

Dali_PS2 | DALI power Supply







C.V. DALI IP20

	Type	Signal Output	Input	Connector
99310	WH	DALI 15-16V DC	220-240V AC	CLAMP

Power supply for 240 mA DALI BUS, for DALI devices, or control modules without own power supply. Power supply suitable for mounting on 35 mm Omega DIN rail.

Dali_PS3 | DALI power Supply






C.V. DALI2 IP20 NEW

	Type	Signal Output	Input	Connector
C-E300002	WH	DALI 15-16V DC	220-240V AC	CLAMP

Power supply for 70 mA DALI BUS, for DALI devices, or control modules without own power supply.

Dali_USB | DALI Controller






DALI IP20

	Type	Signal Output	Input	Connector
99308	TR	DALI	4.5-5V DC	CLAMP USB

PC/DALI interface. It allows the PC to interface with the DALI system and to address individual drivers, managing scenes and groups. The system must be integrated with the free "MasterCONFIGURATOR" software. Powered by DALI cable and USB interface.

Dali_XC | DALI Controller






DALI IP20

	Type	Signal Output	Input	Connector
99311	WH	DALI	15-16V DC	CLAMP

4 independent inputs for N/O contacts/buttons. Operating mode adjustable via 2 rotary switches. Possibility of connecting multiple DALI MSensors in a group and on the DALI line. Power supply via DALI cable. Connection cables, with a length of 25 cm, depending on the colours of the terminal, included.

SceneCOM EVO | DALI2






IP20

	Type	Signal Output	Input	Connector
83146	WH	3 DALI lines	220-240V AC	CLAMP

DALI2 control unit. Maximum number of DALI drivers that can be connected 192. 3 DALI outputs. Web interface for programming. Schedules and programmable calendar functions

XC G2 | DALI2






IP20

	Type	Signal Output	Input	Connector
83147	WH	DALI	15-16V DC	CLAMP

To be used with 83146. 4 independent inputs for contacts and N/O buttons. Possibility of connecting several XC G2s on the DALI line. Power supply via DALI cable. Connection cables with a length of 25cm according to the colors of the terminal.

OptiTouch | Display 4" DALI2





83009 Power supply


IP20 NEW

	Type	Signal Output	Input	Connector
C-E700019	WH	DALI	24V DC	CLAMP

Multifunctional 4" capacitive touch screen for DALI and DALI-2 systems. Addressing and configuration via user interface, customisable thanks to the many widgets. Tunable RGB and white colour management. Scenario recall and saving.

OptiTouch | Display 7" DALI2





83009 Power supply


IP20 NEW

	Type	Signal Output	Input	Connector
C-E700020	WH	DALI	24V DC	CLAMP

Multifunctional 7" capacitive touch screen for DALI and DALI-2 systems. Addressing and configuration via user interface, customisable thanks to the many widgets. Tunable RGB and white colour management. Scenario recall and saving. Group configuration. Circadian daylight curves. Weekly programs and sequences.

OptiTimer | DALI Real Time Clock






IP20 NEW

	Type	Signal Output	Input	Connector
C-E700024	WH	DALI	DALI	CLAMP

DALI real-time clock. The time can be set and queried via DALI. Scheduler function - up to 28 items. Easy programming configuration via DALI Cockpit software and the DALI USB interface. The DALI RTC module does not need to be connected to the mains. It is powered directly via the DALI signal line. Internal battery, by default the clock is set to the local time (GMT+1).

BasicDIM DGC | Digital Controller






IP20

	Type	Signal Output	Input	Connector
83115	WH	DALI/DSI	220-240V AC	CLAMP

2 brodcast control outputs for 10 + 10 DALI \ DSI drivers. Possibility of programming via TLC FULL programmer 83118 or via free “MasterCONFIGURATOR” sosftware.

BasicDIM DGC | Sensor 5DPI 14rc





IP20

	Type	Signal Output	Input	Connector
83116	WH	DALI/DSI	15-16V DC	CLAMP

LUX \ PIR sensor, maximum 4 sensors connected to a 83115 digital controller. Possibility of programming via TLC FULL programmer 83118 or via free “MasterCONFIGURATOR” sosftware.

BasicDIM DGC | Full Programmer



IP20

	L x W x H
83118	130x56x15

Programming remote control for 83115 and 83116. Programming functions: brightness levels and delay time for switching on and off, possibility to deactivate LUX or \ and PIR sensor.

BasicDIM DGC | Easy Programmer



IP20


	L x W x H
83119	86.5x40.5x72

Remote control for 83115 and 83116 management. On, Off and Dimming functionality. Activation of automatic lighting control (LUX).

Dimmer CC radio frequecy

Smart_PRO CC | RF remote





RF Remote



C-W600001
RF Remote

RF remote control functions:
- on/off
- dimming
- speed

	Range	Output	Input
C-E700003	4ch. x (4.6-9.2 W powerLED/ch.)	220mA 21-42V	48V DC
	4ch. x (6.5-12.5 W powerLED/ch.)	300mA 21-42V	
	4ch. x (7-14.5 W arrayLED/ch.)	350mA 21-42V	
	4ch. x (8.4-17 W powerLED/ch.)	400mA 21-42V	
	4ch. x (10.5-21 W powerLED/ch.)	500mA 21-42V	
	4ch. x (13-26 W powerLED/ch.)	630mA 21-42V	
	4ch. x (14.5-29.5 W arrayLED/ch.)	700mA 21-42V	
	4ch. x (17.5-35 W arrayLED/ch.)	840mA 21-42V	
	4ch. x (20-40W arrayLED/ch.)	950mA 21-42V	
	4ch. x (21-42W arrayLED/ch)	1000mA 21-42V	
	4ch. x (2.5-4 W powerLED/ch.)	220mA 12-18V	24V DC
	4ch. x (4-6 W powerLED/ch.)	350mA 12-18V	
	4ch. x (6-9 W powerLED/ch.)	500mA 12-18V	
	4ch. x (11-17 W powerLED/ch.)	630mA 12-18V	
	4ch. x (3 W powerLED/ch.)	350mA 6-9V	12V DC
	4ch. x (4.5 W powerLED/ch.)	500mA 6-9V	
	4ch. x (6 W powerLED/ch.)	700mA 6-9V	

	24V DC
99371	Peta 50 W Switching
84700	Peta 75 W Switching
99374	Reson 75 W Driver


	48V DC
99784	Mean 150 W Switching IP65
99785	Mean 240 W Switching IP65

Dimming via radio frequency remote control, single N/A button or wi-fi network (Tuya smart APP). Device with 4 channels, the first dip switch dedicated for current selection and the second dip switch dedicated for configuration: MONO, DYNAMIC, RGB, RGBW. Protection against overheating, overloading, open circuits and short-circuits along the output line.

Dimmer CV radio frequecy

Smart_PRO CV | RF remote





RF Remote



C-W600001
RF Remote

RF remote control functions:
- on/off
- dimming
- speed

	Range	Output	Input
C-E700002	MONO stripLED	3A x 4ch. 12-24-48V	12-24-48V DC
	DYNAMIC stripLED	3A x 4ch. 12-24-48V	12-24-48V DC
	RGB/RGBW stripLED	3A x 4ch. 12-24-48V	12-24-48V DC

	24V DC
99371	Peta 50 W Switching
84700	Peta 75 W Switching
99374	Reson 75 W Driver

	24V DC
99331	Reson 150 W Driver
99786	Mean 240 W Switching


	48V DC
99784	Mean 150 W Switching IP65
99785	Mean 240 W Switching IP65

Dimming via radio frequency remote control, single N/A button or wi-fi network (Tuya smart APP). Device with 4 channels and dedicated dip switch for configuration: MONO, DYNAMIC, RGB, RGBW. Protection against overheating, overloading, open circuits and short-circuits along the output line.

Dimmer CV SPI

Smart SPI | Controller SPI





IP20 NEW

	Range	Output	Input
C-E700001	Rubber Pixel RGBW	4out SPI 512ch	12-24V DC

Four SPI outputs, up to a maximum of 128 pixels (16 metres) per output. Front panel with control buttons, can also be used with the RF remote control to select mode, programs and speed. With memory function that saves the last status when switched off. Programs: 7 static effect modes, 127 automatic cycle modes. Master and Slave function via shielded wire 84865.

RF Remote




RF remote control functions:
- on/off
- dimming
- speed

C-W600001

Smart SPI | Controller SPI + RF Remote






IP20 NEW

	Range	Output	Input
C-E700004	Rubber Pixel RGBW	4 out SPI 512ch	12-24V DC

Four SPI outputs, up to a maximum of 128 pixels (16 metres) per output. Front panel with control buttons, can also be used with the RF remote control to select mode, programs and speed. With memory function that saves the last status when switched off. Programs: 7 static effect modes, 127 automatic cycle modes. Master and Slave function via shielded wire 84865.

DiGidot C4 | Controller Art-Net to SPI





IP20 NEW


	Range	Output	Input
82852	Rubber Pixel RGBW	4 out SPI 2048ch	5-24V DC
82853	Rubber Pixel RGBW	4 out SPI 4096ch	5-24V DC

SPI controller with Art-Net, sANC or DMX input. Four SPI outputs. 82852 up to a maximum of 128 pixels (16 metres) per output. 82856 up to a maximum of 256 pixels (32 metres) per output. Built in Ethernet switch with 2 ports. Configuration via dedicated web page.

83009 Power supply

DiGidot | PxLNet-Transmitter





IP20 NEW


	Range	Output	Input
82856	Rubber Pixel RGBW	4 out PxLNet RJ45	5-48V DC

SPI to PxLNet converter. Four inputs and four outputs. Maximum CAT-5 E cable length 250 metres per output.

83009 Power supply

PixRubber | Controller DMX SPI





NEW


	Range	IP	Output	Input
C-E700011	Rubber Pixel RGBW	IP 40	1 out SPI 1024ch	24V DC
C-E700010	Rubber Pixel RGBW	IP 65		

SPI controller with DMX or DMX2048 input. Single SPI output. Possibility of connecting up to a maximum of 128 pixels (16 metres) with standard DMX master. Up to a maximum of 256 pixels (32 metres) with ILèD DMX2048 master. Configuration via dmx/rdm C-E700026 addresser.

Dimmer CC & CV DALI DT8

Optidimm RGBW | DALI 4ch DT8





IP20 NEW

	Range	Output	Input
C-E500007	4ch x 3/6/12W	250mA	12/24/48V DC
C-E500008	4ch x 4/8/16W	350mA	12/24/48V DC
C-E500009	4ch x 6/12/24W	500mA	12/24/48V DC
C-E500010	4ch x 8/16/33W	700mA	12/24/48V DC

	12V DC switching
83010	Mean 60 W
83013	Mean 120 W


	24V DC switching
99371	Peta 50 W
84700	Peta 75 W
99374	Reson 75 W
99331	Reson 150 W

	48V DC switching
99784	Mean 150 W
99785	Mean 240 W

Suitable for powering 12/24/48V constant current products. Adjustment via DALI DT8 interface. Four output channels. Dimming, RGB, RGBW functions.

Optidimm DW | DALI 4ch DT8





IP20 NEW

	Range	Output	Input
C-E500004	4ch x 4/8/16W	350mA	12/24/48V DC
C-E500005	4ch x 6/12/24W	500mA	12/24/48V DC
C-E500006	4ch x 8/16/33W	700mA	12/24/48V DC

	12V DC switching
83010	Mean 60 W
83013	Mean 120 W


	24V DC switching
99371	Peta 50 W
84700	Peta 75 W
99374	Reson 75 W
99331	Reson 150 W

	48V DC switching
99784	Mean 150 W
99785	Mean 240 W

Suitable for powering 12/24/48V constant current products. Adjustment via DALI DT8 interface. Four output channels. Dimming, dynamic white functions.

Optidimm CV | DALI RGBW DW DT8





C.V. IP10 NEW

	Range	Type	Output	Input
C-E700015	1-96 W DC	Dynamic white	8A 12V	12V DC
	1-192W DC		8A 24V	24V DC
	1-384 W DC		8A 48V	48V DC
C-E700017	1-96 W DC	RGB/RGBW	8A 12V	12V DC
	1-192W DC		8A 24V	24V DC
	1-384 W DC		8A 48V	48V DC


	24V DC switching
99786	Mean 240 W

	48V DC switching
99784	Mean 150 W
99785	Mean 240 W

Suitable for powering 12/24/48V constant voltage products. Version for Dynamic white and RGB/RGBW. Adjustment via DALI DT8 and PUSH interface.

Optidimm CV | DALI RGBW DW DT8





C.V. IP10 NEW

	Range	Type	Output	Input
C-E700016	1-120 W DC	Dynamic white	10A 12V	12V DC
	1-240W DC		10A 24V	24V DC
	1-480 W DC		10A 48V	48V DC
C-E700018	1-120 W DC	RGB/RGBW	10A 12V	12V DC
	1-240W DC		10A 24V	24V DC
	1-480 W DC		10A 48V	48V DC

	24V DC switching
99786	Mean 240 W


	48V DC switching
99784	Mean 150 W
99785	Mean 240 W

Suitable for powering 12/24/48V constant voltage products. Version for Dynamic white and RGB/RGBW. Adjustment via DALI DT8 and PUSH interface.

Dimmer CC & CV DALI DT6

Lumiquad PRO | DALI 4ch DT6





C.C. | 1-10V | DALI | IP10 | NEW

	Range	Output	Input
C-E500017	4ch x 3/6/12W	250mA	12/24/48V DC
	4ch x 4/8/16W	350mA	12/24/48V DC
	4ch x 6/12/24W	500mA	12/24/48V DC
	4ch x 8/16/33W	700mA	12/24/48V DC

	12V DC switching
83010	Mean 60 W
83013	Mean 120 W


	24V DC switching
99371	Peta 50 W
84700	Peta 75 W
99374	Reson 75 W
99331	Reson 150 W

	48V DC switching
99784	Mean 150 W
99785	Mean 240 W

Suitable for powering 12/24/48V constant current products. Adjustment via DALI DT6, PUSH interface, 0/1-10V interface and potentiometer. Four output channels. Warm tune, dynamic white, RGB, RGBW dimming functions. DALI address and current settable via rotary switch or via DALI.

Lumiquad | Mono CV DALI 1ch DT6





Made in Italy | C.V. | 1-10V | DALI | IP10 | NEW

	Range	Output	Input
C-E500016	1-78 W DC	6.5A 12V	12V DC
	1-156 W DC	6.5A 24V	24V DC
	1-312 W DC	6.5A 48V	48V DC


	24V DC switching
99374	Reson 75 W
99331	Reson 150 W

	48V DC switching
99784	Mean 150 W
99785	Mean 240 W

Suitable for powering 12/24/48V constant voltage products. Adjustment via DALI DT6, PUSH interface, 0/1-10V interface. Four output channels. Warm tune, dynamic white, RGB, RGBW dimming functions. DALI address settable via rotary switch or via DALI.

Lumiquad mini | CV DALI 4ch DT6





Made in Italy | C.V. | DALI | IP20 | NEW

	Range	Output	Input
C-E500019	4ch. x (1-30 W DC/ch.)	2.5A 12V/ch	12V DC
	4ch. x (1-60 W DC/ch)	2.5A 24V/ch	24V DC


	24V DC switching
99374	Reson 75 W
99331	Reson 150 W

Suitable for powering 12/24 V constant voltage products. Compatible with DALI DT6 protocol. DALI address selectable via dip-switch or via DALI. Four output channels. Warm tune, dynamic white, RGB, RGBW dimming functions.

Signal Converter DMX/DALI

Dualgate | Converter SIGNAL





	Type	Signal Input	Signal Output	Power input	Connector
C-E700022	WH	DALI	DMX	12-48V DC	CLAMP
C-E700023	WH	DMX	DALI	12-48V DC	CLAMP


Signal converter from DALI to DMX or from DMX to DALI.

83009 Power supply

Dimmer CC DMX

Real-T_PRO | CC DMX/RDMX 4ch







84865
DMX cable

	Range	Output	Input	Eff.
C-E500015	4ch. x (1-5 W powerLEDs/ch.)	220mA 4-22V	24V DC	84%
	4ch. x (1.5-10 W powerLEDs/ch.)	220mA 7-45V	48V DC	85%
C-E500014	4ch. x (1.5-7.5 W powerLEDs/ch.)	350mA 4-22V	24V DC	86%
	4ch. x (2.5-16 W powerLEDs/ch.)	350mA 7-45V	48V DC	88%
C-E500013	4ch. x (3-18 W arrayLED/ch.)	400mA 7-45V	48V DC	89%
C-E500012	4ch. x (2-11 W powerLEDs/ch.)	500mA 4-22V	24V DC	89%
	4ch. x (3.5-22.5 W powerLEDs/ch.)	500mA 7-45V	48V DC	91%
C-E500011	4ch. x (2.5-14 W powerLEDs/ch.)	630mA 4-22V	24V DC	90%
	4ch. x (4.5-28.5 W powerLEDs/ch.)	630mA 7-45V	48V DC	92%
C-E500003	4ch. x (5-31.5 W arrayLED/ch.)	700mA 7-45V	48V DC	93%


	24V DC switching
99371	Peta 50 W
84700	Peta 75 W
99374	Reson 75 W
99331	Reson 150 W

	48V DC switching
99784	Mean 150 W
99785	Mean 240 W

Suitable for powering constant current products. Adjustment via DMX interface. Four output channels. DMS address settable via NFC and dedicated APP or via DMX/RDM. With I-LèD 83192 master, self-addressing function.

Lumiquad PRO | DMX/RDM 4ch







84865
DMX cable

	Range	Output	Input
83187	4ch x 3/6/12W	250mA	12/24/48V DC
	4ch x 4/8/16W	350mA	12/24/48V DC
	4ch x 6/12/24W	500mA	12/24/48V DC
	4ch x 8/16/33W	700mA	12/24/48V DC

	12V DC switching
83010	Mean 60 W
83013	Mean 120 W

	48V DC switching
99784	Mean 150 W
99785	Mean 240 W


	24V DC switching
99371	Peta 50 W
84700	Peta 75 W
99374	Reson 75 W
99331	Reson 150 W

Suitable for powering MK68 RGBW products. Regulation via DMX interface, PUSH, 0/1-10V interface and potentiometer. Four output channels. Dimming functions warm tune, dynamic white, RGB, RGBW. Current and dmx address settable via rotay switch or via DMX/RDM.

Dimmer CV DMX

Spectrum_PRO | CV DMX/RDM 4ch







84865
Cable

Made in Italy | 100 | | III | C.V. | NFC | DMX RDM | IP40 | NEW


	Range	Output	Input	Eff.
C-E500002	4ch. x (1-72 W stripLED/ch.) 4ch. x (1-72 W topLED/ch.)	3A 24V/ch	24V DC	95%

	24V DC switching
99371	Peta 50 W
84700	Peta 75 W
99374	Reson 75 W
99331	Reson 150 W

Suitable for powering constant voltage products. Adjustment via DMX interface. Four output channels. DMS address settable via NFC and dedicated APP or via DMX/RDM. With I-LèD 83192 master, self-addressing function.

Lumiquad | Mono CV DMX/RDM 1ch







84865
Cable

Made in Italy | III | C.V. | 1-10V | DMX RDM | IP10

	Range	Output	Input	Eff.
83177	1-78 W DC 1-156 W DC 1-312 W DC	6.5A 12V 6.5A 24V 6.5A 48V	12V DC 24V DC 48V DC	95% 95% 95%


	24V DC switching
99371	Peta 50 W
84700	Peta 75 W
99374	Reson 75 W
99331	Reson 150 W

	48V DC switching
99784	Mean 150 W
99785	Mean 240 W

Suitable for powering 12/24/48V constant voltage products. Regulation via DMX interface, PUSH, 0/1-10V interface or potentiometer. Single output channel.

Lumiquad PRO CV | DMX/RDM 4ch







84865
Cable

Made in Italy | III | C.V. | 1-10V | DMX RDM | IP10

	Range	Output	Input	Eff.
83178	4ch (1-60W DC/ch) 4ch (1-120W DC/ch) 4ch (1-240W DC/ch)	5A 12V/ch 5A 24V/ch 5A 48V/ch	12V DC 24V DC 48V DC	95% 95% 95%


	24V DC switching
99371	Peta 50 W
84700	Peta 75 W
99374	Reson 75 W
99331	Reson 150 W

	48V DC switching
99784	Mean 150 W
99785	Mean 240 W

Suitable for powering 12/24/48V constant voltage products. Regulation via DMX interface, PUSH, 0/1-10V interface. Four output channels. Warm tune, dynamic white, RGB, RGBW dimming functions.

Lumiquad mini | CV DMX/RDM 4ch







84865
Cable

Made in Italy | III | C.V. | DMX RDM | IP10 | NEW

	Range	Output	Input
C-E700005	4ch. x (1-30 W DC/ch.) 4ch. x (1-60 W DC/ch)	2.5A 12V/ch 2.5A 24V/ch	12V DC 24V DC


	24V DC switching
99371	Peta 50 W
84700	Peta 75 W
99374	Reson 75 W
99331	Reson 150 W

Suitable for powering strip LEDs and 5 mm LEDs, also RGB. DMX address selectable via dip-switch or via DALI. Compatible with USITT DMX 512-A protocol. Four output channels. Warm tune, dynamic white, RGB, RGBW dimming functions.

Master DMX

Stick_GU2 | DMX Controller







99184
Power supply



84865
DMX cable



98140
Outer casing




	Type	Signal Output	Input	Connector
99045	WH	DMX	5.5-6V DC	CLAMP micro USB
99046	BB	DMX	5.5-6V DC	CLAMP micro USB

Mode selector: Color, Scene and Dimmer. Ability to handle 128ch (0.25 DMX Universe). Selector of up to 24 scenes with selection between dynamic or static. Arrows allow changing active scene. During the execution of a program, the dimmer function can be used to vary the intensity. In colour mode, it is possible to recall a series of pre-set static colours. All functions can be configured by hardware manager (enable/disable the different modes, select starting scenario, etc.).

Stick_DE3 | DMX Controller







99184
Power supply



84865
DMX cable



98140
Outer casing




	Type	Signal Output	Input	Connector
99234	WH	DMX	5.5-6V DC	CLAMP RJ45 mini USB
99235	BB	DMX	5.5-6V DC	CLAMP RJ45 mini USB

Ability to handle 512ch (1 DMX Universe), extendable up to 1024ch (2 DMX Universes). Zone selector to simultaneously activate up to 10 scenes. Dimmer to adjust light intensity and saturation. Selector of up to 500 scenes with the possibility of choosing between dynamic or static. Possibility of increasing or reducing the speed of dynamic scenes and colour effects. Color selector pad allowing RGB values to be entered. Control option via local WiFi network (after Ethernet connection) with free Arcolis Remote App.

Slesa_U11 | DMX Controller







83244
Power supply



89186
5 m extension
M 5 pin M12
M 3 pin XLR



84869
Connector
M 3 pin XLR



84865
DMX cable




	Signal Output	Input	Connector
83243	DMX	5.5-6V DC	RJ45 XLR 3 Pin F. USB C

Ability to manage 1024ch (2 DMX universes) stand-alone, extendable up to 2048ch (4 DMX universes) with connected PC. Selector of up to 99 scenes with selection between dynamic or static. Arrows allow changing active scene. 5 zone selector. Control option via local WiFi network (after Ethernet connection) with free Arcolis Remote App.

Dina DR1 | DMX Controller







83145
Included




	Signal Output	Input	Connector
83144	6 uni DMX/RDM	12V DC	CLAMP Ethernet RJ45 USB typeC

Ability to manage 3072ch (6 DMX Universes) standalone, 128 DALI drivers (2 DALI BUS, DALI BUS power supply required). Selector of up to 2000 scenes with choice of dynamic or static. Arrows allow changing active scene. 20 zone selector. Control option via local WiFi network (after Ethernet connection) with free Arcolis Remote App. Allows deployment via Cloud for remote management (Internet access required).

Master Pixel/SPI

Pixie_PIXEL box | ArtNet DMX/RDM controller for Pixie_PIXEL





	Signal Output	Signal Input	Connector	Power input
83220	Pixie cable	DMX512/RDM	5 Pin F.	48 V DC

Required to drive PIXEL Pixies. Programmable via RDM. Electrically isolates the PIXEL Pixie line from the DMX/RDM line to avoid disturbance propagation.



98493
5 m extension
M 5 pin M12
M 5 pin XLR



89187
M. / F.
5pin M12



83199
M. / F. 4 pin



84865
DMX cable




99785
48V



89365
DMX Line
closure

Paseo_PIXEL box | ArtNet DMX/RDM controller for Paseo_PIXEL





	Signal Output	Signal Input	Connector	Power input
99388	4 Paseo cable	DMX512/RDM ETHERNET (Artnet, sACN)	5 Pin M12	220-240 V AC

Required to drive Paseo_PIXEL in high pixel-density mode. Bridge RDM for the programming of Paseo_PIXEL. Supports 16 DMX universes via ARTNET or sACN protocol. Generate the RS-485 signal required by Paseo_PIXEL.



98493
5 m extension
M 5 pin M12
M 5 pin XLR




84865
DMX cable



99346
Connector
M 5 pin XLR

Pix2048 | Start PIXEL box






	Type	Signal Output	Signal Input	Connector	Power input
83193	BB	DMX 2048	DMX 512 / RDM	CLAMP	24 - 48V DC

Non isolated control interface for RGB/RGBW article with digital control. Recommended for Xenia_PIXEL and Paseo_PIXEL_Dark or for Linea Light items only. Maximum distance from the ArtNet node 50 meters. Control via DMX/RDM C-E700026 addresser.

DMXTrack | ArtNet DMX Recorder






	Signal Output	Input	Connector
99575	16 Uni ArtNet	12-40 V DC	RJ45
99576	32 Uni ArtNet	12-40 V DC	RJ45
99577	64 Uni ArtNet	12-40 V DC	RJ45

ArtNet DMX stand alone recorder of ArtNet DMX sequences. It can be accessed from a mobile device or web browser to adjust the recording and triggering settings.

Pixtwo | Converter ArtNet DMX/RDM





83009
Power supply



84865
DMX cable


C.V. DMX RDM IP10

	Signal Output	Signal Input	Connector	Power input
83192	2 x DMX-RDM	ETHERNET (Artnet4 protocol)	CLAMP RJ45	12-24 V DC

ArtNet-DMX RDM signal converter. Possibility to configure via web page.

Line isolator DMX | RDM BOOST DMX





99658
Power supply



84865
DMX cable


DMX RDM IP10

	Signal Output	Signal Input	Connector	Power input
99657	Bus DMX512	Bus DMX512	CLAMP	12V DC

The Line isolator galvanically isolates the DMX512/RDM input with the output. Through RDM it is possible to set the personality and therefore the type of operation.

Dmxhub | 6OUT DMX/RDM







99658
Power supply



84865
DMX cable



89189
5 m cable
M 5 pin M12



98985
ALLinONE splitter
signal/power


DMX RDM IP20

	Signal Output	Signal Input	Connector	Input
99386	6 DMX512/RDM	DMX512/RDM	CLAMP	9-24V DC

The DMX-512 Splitter takes the DMX input signal and sends it back to the 6 DMX output ports. The splitter can also function as a signal amplifier, because each port supports another 300-metre long connection. This splitter complies with the RDM protocol for bi-directional communication on DMX. Fixture suitable for mounting on 35mm Omega DIN rail.

Dmxhub PRO | 6OUT DMX/RDM







99658
Power supply



84865
DMX cable



89185
5 m cable
M 5 pin M12



98985
ALLinONE splitter
signal/power


DMX RDM IP20

	Signal Output	Signal Input	Connector	Input
83148	6 DMX 512/RDM	DMX 512/RDM	CLAMP	10-48 VDC

The DMX-512 Splitter takes the DMX input signal and sends it back to the 6 DMX output ports. The splitter can also function as a signal amplifier, because each port supports another 300-metre long connection. This splitter complies with the RDM protocol for bi-directional communication on DMX. Fixture suitable for mounting on 35mm Omega DIN rail.

Titan | ArtNet DMX Controller





	LxPxH mm	Signal Output	Signal Input	Connector	Power Input
99381	140x63x38	2 DMX512	Ethernet RJ45	XLR 5 Pin F.	220-240V AC
99382	138x93x38	4 DMX512	Ethernet RJ45	XLR 5 Pin F.	220-240V AC
99383	483x137x44	8 DMX512	Ethernet RJ45	XLR 5 Pin F.	220-240V AC
99384	483x137x44	16 DMX512	Ethernet RJ45	XLR 5 Pin F.	220-240V AC

The ArtNet protocol is received via Ethernet. Generate the DMX512 signal. Perfect synchronisation between universes. Configurable via web page.



98493
5 m extension
M 5 pin M12
M 5 pin XLR



99346
Connector
M 5 pin XLR




84865
DMX cable



89189
5 m cable
M 5 pin M12

DMX USB PRO | DMX/RDM Addresser





	Signal Output	Signal Input	Connector	Power Input
C-E700026	1 DMX512	USBtype A	XLR 5 Pin F.	USB 5V

ENTTEC software included. Required to program DMX/RDM devices. Test the correct operation of the installation. It is possible to use the two DMX universes and the stand-alone mode for small installations (1024 pixels).



89186
5 m extension
M 5 pin M12
M 3 pin XLR



98493
5 m extension
M 5 pin M12
M 5 pin XLR



99346
Connector
M 5 pin XLR



84865
DMX cable



89189
5 m cable
M 5 pin M12

Dmxrack | ArtNet Converter




	Signal Output	Signal Input	Connector	Type	Power Input
83149	4 UNI	ArtNet	RJ45 XLR3	Box	220-240V AC
83150	4 UNI	ArtNet	RJ45 XLR3	Rack	
83151	8 UNI	ArtNet	RJ45 XLR3	Rack	

Art-Net and sACN to DMX converter for 4 and 8 independent universes. 4 and 8 individually optically isolated DMX ports. Graphic display and encoder knob for easy configuration and accurate status information. Web interface for status observation, settings adjustment and firmware updates. Neutrik powerCON input and output.



83152
Plug Power DMXnode

SunsetX | ArtNet DMX controller recorder



83009
Power supply

Key | Madrix 5



	Type	Signal Output
81828	entry	8 DMX Universe
81829	basic	32 DMX Universe
81830	professional	128 DMX Universe
81831	ultimate	512 DMX Universe

Licence for Madrix software to enable the ArtNet output signal. The MADRIX® 5 software is the lighting instrument preferred by professionals in the sector, lighting designers.

WS | WorkStation HP



IP20

	Power Input
81835	220-240 vAC

MHD | Monitor



IP20

	Power Input	
81836	220-240 vAC	24 pollici HDMI

HPE | Ethernet Switch




IP20 NEW

	Signal Output	Power Input
83388	8 RJ45	220-240 vAC
83389	24 RJ45	220-240 vAC

Emergency

Emergency light kit | Emergency







Switchable (on/off) in the presence of mains via switch on SL input (switched line). Automatic reset following battery and/or LED lamp replacement. Electronic multi-level charging system. Supplied with 3,000 mAh battery pack.

	Range	Output	Input	Eff.	PF	Surge
99355	Universal	6-60V 40-400mA	220-240V AC	86%	0.5	4 kV

Frequency	50-60 Hz
Nominal input current	40 mA (30 A inrush current with cold start)
Outout voltage (without load)	6-60V
TA Operating temperature	-25 +50 °C
Max casing temperature TC	70 °C
Control interface	Switch Line, Rest mode
Protections	Overtemperature, overload, overvoltage, short-circuit, open circus
Charge current	200 mA
Emergency output current	400-40 mA
Emergency power	2,4W
Emergency output current	20 h
Reference norms	IEC 61347-2-7:2011, IEC 61347-2-7:2011/AMD1:2017, IEC 61347-1:2015, IEC 61347-1:2015/AMD1:2017, EN 61347-1:2015, EN 61347-2-7:2012+A1:2019, EN 55015:2013/ A1:2015, EN61547:2009, EN 61000-3-2: 2014 EN 61000-3-3: 2013







The installation of the emergency kit is quick and simple: the Emergency unit only needs to be connected to the LED driver as shown in the diagram.

*the driver is not included in the Emergency kit/the Emergency kit can be connected to all the original drivers of the LED device.

Emergency light kit | Emergency






- Maintained or non maintained operation
- Suitable for electronic driver, dimmable electronic driver
- Adjustable version dip-switch, constant current or constant voltage to power LED to LED modules
- Connected to power supplies with maximum output voltage and current 90V and 2A
- Automatic operation
- High temperature NiCd batteries
- Charge indicator with FROR led cable
- Protection device against extensive discharge
- MAT4 DALI self diagnosis system with external module
- Charging device with supply is reinforced insulation able to recharge the battery normally after the test in clause 22.3 of the IEC 61347-2-7:2007.
- Supplied with 3,000 mAh battery pack.

EM C.C. IP20

	Range	Output	Input	PF
KIT0014	Universal C.C. Universal C.V.	9-57V 350-60mA 24V 2000mA	220-240V AC	0.5

Frequency	50-60 Hz
Nominal input current	20 mA
Outout voltage (without load)	9-57V C.C. / 24V C.V.
TA Operating temperature	0 +50 °C
Max casing temperature TC	70 °C
Control interface	Switch Line, Rest mode
Protections	Overtemperature, overload, overvoltage, short-circuit, open circus
Emergency output current	350-60 mA C.C. / 2000mA C.V.
Emergency power	3,4W
Recharging time	24 h
Reference norms	EN61347-2-13, EN61347-2-7, EN61547, EN55015, EN60598-2-22, EN61000-3-2



The installation of the emergency kit is quick and simple: the Emergency unit only needs to be connected to the LED driver as shown in the diagram.

*the driver is not included in the Emergency kit/the Emergency kit can be connected to all the original drivers of the LED device.

Cables

	application	type	voltage	insulation	Ø	nomenclature	sec. mm	cable colour	core colour	cable gland	temperature
84874	indoor	RGB	low	PVC + PVC	7 mm	--	6 x 0,75	●	○●●●●●	PG7	--
99237	outdoor	MONO	low	FEP + PCP	5,3 mm	--	2 x 0,5	●	●●	--	70-90°C
84888	outdoor	MONO	low	GUM	6,5 mm	--	2 x 1	●	●●	PG7	--
84875	outdoor	MONO	low	GUM + PCP	8,3 mm	H07RN8-F	2 x 1	●	●●	PG9	60-90°C
84892	indoor outdoor	MONO	low	FEP + FEP	1,9 x 3,3 mm	--	2 x 0,5	●●	●●	--	180°C
99353	outdoor	--	high	GUM + PCP	6,2 mm	H05RN-F	2 x 0,75	●	●●	PG7	60-90°C
99229	outdoor	--	high	GUM + PCP	6,5 mm	H05RN-F	2 x 1	●	●●	PG7	60-90°C
84887	outdoor	--	high	GUM + PCP	7,2 mm	H05RN-F	3 x 1	●	●●●	PG7	60-90°C
99002	outdoor underwater	MONO	low	NEOPRENE	5,3 mm	--	2 x 0,5	●	●●	--	70-90°C
84876	outdoor underwater	MONO	low	NEOPRENE	6,5 mm	--	3 x 1	●	●●●	PG9	--
84864	outdoor underwater	RGB	low	NEOPRENE	9,6 mm	--	7 x 1	●	○●●●●●●	PG9	--


Extension cables

The conductor cables to utilize for installing our outdoor fixtures has to be NEOPRENE H07 that respond to technical requests of EN60598 sez. 5.2.2:

- temperature of use 90°C
- Type of conductor red copper wire
- Execution tension 450/750V
- Nomenclature H07RN-F
- Conforming of the normative CEI 20-19
- Conforming on the requests of directive B.T.73/23CEE e 93/68CEE

The cable is suitable for humid and dry outdoor ambient; Water resist, on erosion, on frequent flexions. The cable resist on temperature up to –25°C without any superficial crackles; is necessary to protect it anyway even on surface that is use for pathways or drive over in order to prevent curving at 30°.


	application	voltage	insulation	sec. mm	length mm	colour	temperature
84866	indoor	low	PVC	3 x 0,5	1500	●●●	90°C
84867	indoor	low	PVC	3 x 0,5	3000	●●●	90°C
84872	indoor	low	PVC	3 x 0,5	1500	●●●	90°C
84873	indoor	low	PVC	3 x 0,5	1500	●○●	90°C



Junction boxs | DMX accessories

Junction box | connector gel 2 ways






	Connectors	External Ø of the cabl
98989	IP68 2x0,75 mm²	Ø 4,8 ~ Ø 6 mm

Junction box | connector 2 ways






	Connectors	External Ø of the cable
98990	IP68 min. 2x0,25 mm² max. 2x1,0 mm²	Ø 3 ~ Ø 8 mm

Junction box | connector gel 2 ways






	Connectors	External Ø of the cabl
98991	IP68 max. 3x1.5 mm²	Ø 5,5 ~ Ø 10 mm

Junction box | connector 2 ways






	Connectors	External Ø of the cable
84893	IP68 min. 2x0,5 mm² max. 2x2.5 mm²	Ø 7 ~ Ø 13,5 mm

Junction box | connector gel 4 ways





	Connectors	External Ø of the cable
84894	IP68 max. 4x1,5 mm²	Ø 6,5 ~ Ø 12 mm

Cables | DMX



	L m	Connectors	Sec. Ø
84895	1	F 3 pin XLR	2 x 0,25 mm² + shield
84994	5		

Extension cables | DMX




	L m	Connectors	Sec. Ø
84871	1	M + F 3 pin XLR	2 x 0,25 mm² + shield
84885	5		


Connectors | DMX




	L m	Connectors	Sec. Ø
84869	3 M	XLR	
84870	3 F		
99346	5 M		
99379	5 F		









DMX accessories

Cable | DMX



price / m	sec. Ø	
order: x m / 84865	2 x 0,25 mm² + shield	**84865**

Connector | DMX line closure adapter



*accessory to be installed obligatorily at the end of each continuous row of appliances.

suitable for	input	output	
*Paseo RGBW	Bus DMX 512	120 Ohm	**89365**
*Paseo_PIXEL RGB			
*Xenia 2.0 RGBW			
*Pixie_PIXEL_box			

Connector | ALLinONE DMX line closure adapter



*accessory to be installed obligatorily at the end of each continuous row of appliances.

suitable for	input	output	
*Archiline RGBW	Bus DMX 512	120 Ohm	**98986**
*Prolamp RGBW			

Connector | ALLinONE DMX line closure adapter



*accessory to be installed obligatorily at the end of each continuous row of appliances.


suitable for	input	output	
*Xenia RGBW	Bus DMX 512	120 Ohm	**C-W400005**


Connector splitter | ALLinONE splitter power/DMX



Start splitter


suitable for	input	output	
Archiline RGBW Prolamp RGBW	1 3x1,5 mm² (for power supply) 2 2x0,25 mm² (for DMX) +shield	3 ALLinONE F 3x1,5 mm² + 2x0,2 mm² +shield	**98985**
Xenia RGBW	1 2x1 mm² (for power supply) 2 2x0,25 mm² (for DMX) +shield	3 ALLinONE F 2x1 mm² + 2x0,2 mm² +shield	**C-W200018**





Continuity splitter A

suitable for	input	output	
Archiline RGBW Prolamp RGBW	1 ALLinONE M 3x1,5 mm² + 2x0,2 mm² +shiel 2 3x1,5 mm² (for power supply)	3 ALLinONE F 3x1,5 mm² + 2x0,2 mm² +shield	**99390**
Xenia RGBW	1 ALLinONE M 2x1 mm² + 2x0,2 mm² +shiel 2 2x1 mm² (for power supply)	3 ALLinONE F 2x1 mm² + 2 x 0,2 mm² +shield	**C-W200019**





MONTEFELTRO OFFICE VILLAGE
Milan (Italy)

Project:
Stefano Giubileo, Gregg Brodarick,
Andrea Bianchi, Fabio Crespi

Photography:
Marco Reggi

SYMBOLS
FINISHES
OPTICS
INDEX



Alphabetical Effects Range

Optic code	Optic range	Optic Description
0H	(40°÷49°) x <20° Wall Grazing	Elliptic Medium Wide Flood
1F	(20°÷29°) x (20°÷40°) Wall Grazing	Elliptic Flood
1H	(40°÷49°) x (20°÷40°) Wall Grazing	Elliptic Medium Wide Flood
1S	(10°÷19°) x (20°÷40°) Wall Grazing	Elliptic Spot
3F	(20°÷29°) x >60° Wall Grazing	Elliptic Flood
3N	≤ 9° x >60° Wall Grazing	Elliptic Narrow Spot
AE	Zoom Elliptic	Adjustable Focus Elliptic
AF	1°- 60° Zoom Spot	Adjustable Focus
AW	Adj. Ww	Adjustable Wall Washer
BK	Bike (bike paths, narrow streets)	Bike
BW	Batwing (Double Asymmetric)	Batwing
DD	Diffused + Diffused	Double Diffused
DI	≥ 121°	Diffused
DZ	Diffused (Up) + No Optic	Diffused + No Optic
EF	(20°÷29°) x (41°÷60°) Wall Grazing	Elliptic Flood
EM	(30°÷39°) x (41°÷60°) Wall Grazing	Elliptic Medium Flood
ES	(10°÷19°) x (41°÷60°) Wall Grazing	Elliptic Spot
FL	20°÷ 29°	Flood
HS	1°÷ 3°	Hyper Spot
ML	30°÷ 39°	Medium Flood
MW	40°÷ 49°	Medium Wide Flood
NS	7°÷ 9°	Narrow Spot
PD	Pedestrian Crossing	Pedestrian
PK	Park (wide areas, parking lots)	Park
RB	Radial Bi-direc.	Radial Bi-directional emission
RD	Asym. 360°	Asymmetric 360°
RM	Radial Multi-direc.	Radial Multidirectional emission
RU	Radial Mono-direc.	Radial Mono-directional emission
SB	Suburban (suburban roads)	Suburban
SP	10°÷19°	Spot
SR	Asym. 180°	Asymmetric 180°
ST	Street (wide streets)	Street
UR	Urban (urban streets)	Urban
US	4°÷ 6°	Ultra Spot
WF	50°÷ 70°	Wide Flood
WW	Asym. Ww	Asymmetric Wallwasher
X1	Asym.+ Elliptic	MixFlux Asymmetric + Elliptic
X2	Asym. + Flood	MixFlux Asymmetric + Flood
XF	71°÷ 120°	Extra Wide Flood
ZZ	No Optics	No Optics

Effects Range

Optic range	Optic code	Optic Description
Floodlight effects		
1°÷ 3°	HS	Hyper Spot
4°÷ 6°	US	Ultra Spot
7°÷ 9°	NS	Narrow Spot
10°÷ 19°	SP	Spot
20°÷ 29°	FL	Flood
30°÷ 39°	ML	Medium Flood
40°÷ 49°	MW	Medium Wide Flood
50°÷ 70°	WF	Wide Flood
71°÷ 120°	XF	Extra Wide Flood
≥ 121°	DI	Diffused
1°- 60° Zoom Spot	AF	Adjustable Focus
Wall Grazing effects		
≤ 9° x >60°	3N	Elliptic Narrow Spot
(10°÷19°) x (41°÷60°)	ES	Elliptic Spot
(10°÷19°) x (20°÷40°)	1S	Elliptic Spot
(20°÷29°) x (41°÷60°)	EF	Elliptic Flood
(20°÷29°) x >60°	3F	Elliptic Flood
(20°÷29°) x (20°÷40°)	1F	Elliptic Flood
(30°÷39°) x (41°÷60°)	EM	Elliptic Medium Flood
(40°÷49°) x <20°	0H	Elliptic Medium Wide Flood
(40°÷49°) x (20°÷40°)	1H	Elliptic Medium Wide Flood
Zoom Elliptic	AE	Adjustable Focus Elliptic
Asymmetrical effects		
Adj. Ww	AW	Adjustable Wall Washer
Asym. + Flood	X2	MixFlux Asymmetric + Flood
Asym. 180°	SR	Asymmetric 180°
Asym. 360°	RD	Asymmetric 360°
Asym. Ww	WW	Asymmetric Wallwasher
Asym.+ Elliptic	X1	MixFlux Asymmetric + Elliptic
Batwing	BW	Batwing (Double Asymmetric)
Multi-effects		
Bike (bike paths, narrow streets)	BK	Bike
Diffused (Up) + No Optic	DZ	Diffused + No Optic
Diffused + Diffused	DD	Double Diffused
No Optics	ZZ	No Optics
Park (wide areas, parking lots)	PK	Park
Pedestrian Crossing	PD	Pedestrian
Radial Bi-direc.	RB	Radial Bi-directional emission
Radial Mono-direc.	RU	Radial Mono-directional emission
Radial Multi-direc.	RM	Radial Multidirectional emission
Street (wide streets)	ST	Street
Suburban (suburban roads)	SB	Suburban
Urban (urban streets)	UR	Urban

Suffixes

Example composition:

Suelo_**RFJ** = **R** + **F** + **J**

Round — Frameless — Adjustable

A	Aluminium
A (Orma)	Round Flush Frame
AB (Orma)	Round Flush Frame Blade
AL (Orma)	Round Flush Frame Opaline
AL	Aluminium Opaline
BC	Base Ceiling
BS	Base Surface
C	Ceiling
CD	Ceiling Direct
CI	Ceiling Internal
D	Double

EX	Extractable
F	Frameless
FL	Frameless Opaline
FO	Frameless Circular
I	Inox
I (Orma)	Round with Frame
IB (Orma)	Round with Frame Blade
IL (Orma)	Round with Frame Opaline
IL	Inox Opaline
J	Adjustable
L	Linear Module

M	Modular
O	Circular
P	Pendant
PD	Pendant Direct
PI	Pendant Internal
PU	Pendant Up
Q	Square
PRO	Professional
R	Round
RDX	Round Double + Screws
RF	Round Frameless

RP (MK68)	Round Projectors
RX	Round + Screws
S	Surface
SP	Spot Projector
T	Track
W	Wall
Ww	Wall Washer
X (Paseo)	PowerLED
Y	Asymmetric

How to read symbols


Indoor installation


Outdoor installation


Wall mounting


Ground mounting


Ceiling mounting


Wall or ground mounting


Ceiling or wall mounting


Ceiling, wall or groung mounting



Protection index (IEC 60529) against foreign bodies and water



Product designed to withstand temporary immersions



Optical compartment protecion index



Protection index (IEC 62262) against external mechanical impacts


Walkable device


Carriageable device


Stainless steel


Circular installation hole


Square installation hole


Directional light beam


Tilting light beam


Power supply cable included



Device suitable to be mounted on furniture



Device suitable to be mounted on normally flammable surfaces (EN 60598)



Device with built-in thermal protection


Driver included


Driver not included


Class I - IEC protection class


Class II - IEC protection class



Class III - IEC protection class



Over Voltage Protection


Smartwave™



Constant Current



Constant Voltage



Dimming On Board
Integrated potentiometer



1-10 V



Digital Addressable Lighting Interface



Digital Addressable Lighting Interface



Digital Addressable Lighting Interface



PointToPoint DALI. Dimmering on single item


Technology Wi-Fi i-Led



RDM, DMX 512


Casambi


Matter


Infrared



Radio frequency remote control


P.I.R. Sensor


Light + Motion sensor


Power supply with safety transformer


Independent power supply



Thermally protected power supply


Reinforced insulation



Unified Glare Rating



BUG Rating


Integrated antenna


External antenna


The power supply does not switch into the installation hole



Electrostatic discharge protection



Over Voltage Protection



Version suitable for ATEX 2,22 areas



High Efficiency



Internal Driver
Micro driver on-board




The driver contained in the device complies with IEC 61347-2-13 annex J




Emergency version

The connection diagrams for electronics articles are included in the technical documentation.

Finishes




White | RAL 9003 embossed



Black | RAL 9005 embossed




Gray Black | RAL 7021 embossed



Anodised Black



Anthracite grey | RAL 7016



Grey | RAL 9006 embossed



Light grey | RAL 7035




Satin finish



Cement



Aluminium



Anodised aluminium



Steel




Brushed nickel



Chrome



Transparent PMMA



Opaline PMMA



Brushed gold



Brushed copper




Gold



Brass



Copper




Burnished



Bronze



Brown



Dark Brown



Signal Yellow | RAL 1003



Green | RAL 6031



Sand

Codes index

Code	Page
14931	487
	817
	821
	825
	835
53890	847
60830	107
62400	632
62401	632
62402	632
62460	305
62757	641
62758	641
62900	336
	337
63300	320
	321
63301	320
	321
63302	320
	321
63445	847
63446	847
63772	209
63773	209
63778	208
63779	208
63782	209
63783	209
64010	196
	210
64011	196
	210
64012	196
	210
64013	196
	210
64020	196
	210
64021	196
	210
64022	196
	210
64023	196
	210
64030	196
	210
64031	196
	210
64032	196
	210
64033	196
	210
64038	196
	210
64039	196
	210
64060	196
	211
64061	196
	211
64062	196
	211
64063	196
	211
64066	196
	211
64067	196
	211
64068	196
	211
64069	196
	211
64179	197
	212
64189	197
	212
64210	839
64252	839
64253	839
64254	839
64256	839
64257	839
64258	839
64505	533
64506	533
64522	487
64523	487
64530	487
64531	487
64532	487
64533	487
64534	487
64536	487
64537	487
64538	487
64539	487
64546	107
64547	107
64548	107
64549	107
64550	107
64551	107
64561	533
64562	533
64564	533
64575	197
	212
64578	196
	210
64589	632
64590	633
64591	633
64592	632
64593	632
64594	632
64595	632
64597	632
64630	107
64631	107
64639	320
	321
64640	632
64641	632
64642	632
64643	632
64644	632
64645	632
64646	632
64647	632
64648	633
64649	320
	321
64660	320
	321
64661	632
64662	632
64663	632
64664	632
64665	632
64666	632
64667	632
64668	632
64669	632
64670	197
	212
64721	837
64722	837
64723	837
64724	837
64726	837
64727	837
64728	837
64729	837
64734	837
64735	837
64736	837
64737	837
64758	837
64759	837
64760	837
64761	837
64762	837
64763	837
64764	837
64788	841
64789	841
64790	841
64791	841
64792	841
64793	841
64794	841
64795	841
64796	841
65002	533
65003	336
65004	336
65005	533
65006	336
65007	336
65008	337
65009	336
65010	336
65011	337
65012	336
65013	336
65014	337
65015	337
65016	337
65018	337
65019	337
65021	337
65022	337
65023	641
65024	337
65025	337
65026	641
65027	336
65028	336
65035	641
65036	641
65037	641
65038	641
65039	641
65040	641
65054	336
	337
65055	336
	337
65075	849
65076	849
65077	849
65078	849
65082	841
65094	641
65097	337
65142	196
	210
65180	336
65181	336
65182	336
	337
65183	336
	337
65184	336
	337
65190	227
65191	227
65192	227
65193	227
65324	196
	210
65326	196
	210
65336	196
	211
65338	196
	211
65403	841
65404	841
65405	841
65412	196
	211
65413	196
	211
65438	305
65439	305
65440	305
65441	305
76010	926
76036	779
76037	779
76038	779
76039	779
76040	780
76041	780
76042	780
76043	780
76044	781
76045	781
76046	781
76047	781
76048	780
76049	780
76050	781
76051	781
76052	147
76053	147
76054	147
76055	147
76056	147
76057	147
76074	780
76075	780
76076	781
76077	781
76078	511
76079	511
76080	720
76081	721
76082	722
76083	723
76084	233
76085	233
76086	233
76087	233
76088	233
76089	233
76090	666
76091	666
76092	666
76093	666
76094	668
76095	668
76096	668
76097	668
76098	668
76099	668
76100	668
76101	668
76102	232
76103	232
76104	666
76105	666
76106	666
76107	666
76116	768
76117	768
76118	768
76119	768
76120	768
76121	768
76122	768
76123	768
76124	768
76125	768
76126	768
76127	768
76128	768
76129	768
76130	768
76131	768
76132	768
76133	768
76134	769
76135	769
76136	769
76137	769
76138	769
76139	769
76140	769
76141	769
76142	769
76143	769
76144	769
76145	769
76146	770
76147	770
76148	770
76149	770
76150	770
76151	770
76152	770
76153	770
76154	770
76155	770
76156	770
76157	770
76158	770
76159	770
76160	770
76161	770
76162	770
76163	770
76164	771
76165	771
76166	771
76167	771
76168	771
76169	771
76170	771
76171	771
76172	771
76173	771
76174	771
76175	771
76180	441
76181	442
76182	473
76183	473
76184	473
76185	473
76203	755
76204	756
76205	766
76206	767
76207	752
76208	752
76209	752
76210	752
76211	752
76212	752
76213	753
76214	753
76215	753
76216	753
76217	753
76218	753
76219	753
76220	753
76221	753
76222	753
76223	753
76224	753
76225	753
76246	521
76247	521
76248	521
76249	521
76251	521
76252	521
76253	521
76254	521
76276	521
76277	521
76278	521
76279	521
76281	521
76282	521
76283	521
76284	521
76286	521
76287	521
76288	521
76289	521
76291	521
76292	521
76293	521
76294	521
76296	520
76297	520
76298	520
76299	520
76301	520
76302	520
76303	520
76304	520
76311	520
76312	520
76313	520
76314	520
76316	520
76317	520
76318	520
76319	520
76321	519
76322	519
76323	519
76324	519
76326	519
76327	519
76328	519
76329	519
76351	519
76352	519
76353	519
76354	519
76356	519
76357	519
76358	519
76359	519
76361	519
76362	519
76363	519
76364	519
76366	519
76367	519
76368	519
76369	519
76372	276
76373	276
76374	276
76375	276
76376	276
76377	276
76378	276
76379	276
76380	276
76381	276
76382	276
76383	276
76384	276
76385	276
76386	276
76387	276
76396	276
76397	276
76398	276
76399	276
76400	276
76401	276
76402	276
76403	276
76404	276
76405	276
76406	276
76407	276
76408	276

Codes index

Code	Page	Code	Page	Code	Page	Code	Page	Code	Page	Code	Page	Code	Page	Code	Page
76409	276	**76636**	516	**76722**	767	**76812**	453	**76890**	833	**76970**	540	**77077**	160	**77150**	760
76410	276	**76637**	516	**76723**	767	**76814**	452	**76891**	833	**76971**	540	**77078**	160	**77151**	760
76411	276	**76639**	516	**76724**	767	**76815**	452	**76892**	833	**76972**	540	**77079**	160	**77152**	760
76420	278	**76640**	516	**76733**	894	**76817**	451	**76894**	833	**76973**	540	**77080**	160	**77153**	760
76421	278	**76641**	516	**76734**	894	**76818**	451	**76895**	833	**76974**	540	**77081**	160	**77154**	760
76422	278	**76642**	516	**76735**	895	**76820**	453	**76896**	833	**76975**	540	**77082**	160	**77155**	760
76423	278	**76649**	516	**76736**	895	**76821**	453	**76898**	833	**76976**	540	**77083**	160	**77156**	760
76424	278	**76650**	516	**76737**	894	**76822**	452	**76899**	833	**76977**	540	**77090**	920	**77157**	760
76425	278	**76651**	516	**76738**	894	**76823**	452	**76900**	833	**76978**	540	**77091**	920	**77158**	760
76426	278	**76652**	516	**76739**	180	**76824**	451	**76918**	537	**76979**	540	**77092**	920	**77159**	761
76427	278	**76654**	516	**76740**	180	**76825**	451	**76919**	537	**76980**	540	**77093**	920	**77160**	761
76428	278	**76655**	516	**76741**	180	**76826**	453	**76920**	537	**76981**	540	**77094**	920	**77161**	761
76429	278	**76656**	516	**76742**	180	**76827**	453	**76921**	537	**76982**	540	**77095**	920	**77162**	761
76430	278	**76657**	516	**76743**	180	**76828**	452	**76922**	537	**76983**	540	**77096**	920	**77163**	761
76431	278	**76659**	146	**76744**	180	**76829**	452	**76923**	537	**76984**	540	**77097**	920	**77164**	761
76432	278	**76660**	146	**76745**	650	**76830**	451	**76924**	537	**76985**	540	**77098**	920	**77165**	761
76433	278	**76661**	146	**76746**	650	**76831**	451	**76925**	537	**76986**	540	**77099**	820	**77166**	761
76434	278	**76662**	146	**76747**	650	**76832**	453	**76926**	537	**76987**	540	**77100**	820	**77167**	761
76435	278	**76663**	146	**76760**	674	**76833**	453	**76927**	537	**76988**	540	**77101**	820	**77168**	761
76559	518	**76664**	146	**76761**	674	**76835**	452	**76928**	537	**76989**	540	**77102**	820	**77169**	761
76560	518	**76665**	146	**76762**	674	**76836**	452	**76929**	537	**76990**	540	**77103**	820	**77170**	761
76561	518	**76666**	146	**76763**	674	**76838**	451	**76930**	537	**76991**	540	**77104**	820	**77186**	511
76562	518	**76667**	146	**76764**	674	**76839**	451	**76931**	537	**76992**	540	**77111**	758	**77187**	835
76564	518	**76668**	146	**76765**	674	**76841**	453	**76932**	537	**76993**	540	**77112**	758	**77188**	835
76565	518	**76669**	146	**76766**	674	**76842**	453	**76933**	537	**76994**	540	**77113**	758	**77189**	835
76566	518	**76670**	146	**76767**	674	**76844**	452	**76934**	537	**76995**	540	**77114**	758	**77276**	738
76567	518	**76683**	671	**76768**	675	**76845**	452	**76935**	537	**76996**	540	**77115**	758	**77277**	738
76574	518	**76688**	671	**76769**	675	**76847**	451	**76936**	537	**76997**	540	**77116**	758	**77278**	738
76575	518	**76689**	692	**76770**	675	**76848**	451	**76937**	537	**76998**	541	**77117**	758	**77279**	738
76576	518	**76690**	692	**76771**	675	**76850**	453	**76938**	537	**76999**	541	**77118**	758	**77280**	738
76577	518	**76691**	693	**76772**	453	**76851**	453	**76939**	537	**77000**	541	**77119**	758	**77281**	738
76579	518	**76692**	693	**76773**	453	**76852**	452	**76940**	537	**77001**	541	**77120**	758	**77282**	735
76580	518	**76693**	692	**76775**	452	**76853**	452	**76941**	537	**77002**	541	**77121**	758	**77283**	739
76581	518	**76694**	692	**76776**	452	**76854**	451	**76942**	537	**77003**	541	**77122**	758	**77284**	735
76582	518	**76695**	693	**76778**	451	**76855**	451	**76943**	537	**77004**	541	**77123**	758	**77285**	739
76584	517	**76696**	693	**76779**	451	**76856**	453	**76944**	537	**77005**	541	**77124**	758	**77286**	735
76585	517	**76697**	702	**76781**	453	**76857**	453	**76945**	537	**77006**	541	**77125**	758	**77287**	739
76586	517	**76698**	702	**76782**	453	**76858**	452	**76946**	537	**77007**	541	**77126**	758	**77288**	735
76587	517	**76699**	702	**76784**	452	**76859**	452	**76947**	537	**77018**	541	**77127**	758	**77289**	739
76589	517	**76700**	702	**76785**	452	**76860**	451	**76948**	537	**77019**	541	**77128**	758	**77290**	735
76590	517	**76701**	754	**76787**	451	**76861**	451	**76949**	537	**77020**	541	**77129**	759	**77291**	739
76591	517	**76702**	754	**76788**	451	**76862**	691	**76950**	537	**77021**	541	**77130**	759	**77292**	735
76592	517	**76703**	754	**76790**	453	**76863**	691	**76951**	537	**77022**	541	**77131**	759	**77293**	739
76614	517	**76704**	754	**76791**	453	**76864**	691	**76952**	537	**77023**	541	**77132**	759	**77294**	735
76615	517	**76705**	765	**76792**	452	**76865**	692	**76953**	537	**77024**	541	**77133**	759	**77295**	739
76616	517	**76706**	765	**76793**	452	**76866**	691	**76954**	537	**77025**	541	**77134**	759	**77296**	735
76617	517	**76707**	765	**76794**	451	**76867**	691	**76955**	537	**77026**	541	**77135**	759	**77297**	739
76619	517	**76708**	765	**76795**	451	**76868**	691	**76956**	537	**77027**	541	**77136**	759	**77298**	735
76620	517	**76709**	756	**76796**	453	**76869**	692	**76957**	537	**77040**	666	**77137**	759	**77299**	739
76621	517	**76710**	756	**76797**	453	**76874**	832	**76958**	540	**77041**	666	**77138**	759	**77300**	735
76622	517	**76711**	756	**76798**	452	**76875**	832	**76959**	540	**77042**	666	**77139**	759	**77301**	739
76624	517	**76712**	756	**76799**	452	**76876**	832	**76960**	540	**77043**	666	**77140**	759	**77302**	737
76625	517	**76713**	766	**76800**	451	**76878**	832	**76961**	540	**77044**	666	**77141**	760	**77303**	741
76626	517	**76714**	766	**76801**	451	**76879**	832	**76962**	540	**77045**	666	**77142**	760	**77304**	736
76627	517	**76715**	766	**76802**	453	**76880**	832	**76963**	540	**77046**	666	**77143**	760	**77305**	740
76629	517	**76716**	766	**76803**	453	**76882**	832	**76964**	540	**77047**	666	**77144**	760	**77306**	736
76630	517	**76717**	755	**76805**	452	**76883**	832	**76965**	540	**77072**	160	**77145**	760	**77307**	740
76631	517	**76718**	756	**76806**	452	**76884**	832	**76966**	540	**77073**	160	**77146**	760	**77308**	737
76632	517	**76719**	756	**76808**	451	**76886**	832	**76967**	540	**77074**	160	**77147**	760	**77309**	741
76634	516	**76720**	756	**76809**	451	**76887**	832	**76968**	540	**77075**	160	**77148**	760	**77310**	736
76635	516	**76721**	766	**76811**	453	**76888**	832	**76969**	540	**77076**	160	**77149**	760	**77311**	740

Codes index

Code	Page	Code	Page	Code	Page	Code	Page	Code	Page	Code	Page	Code	Page	Code	Page
77312	736	**77373**	674	**77475**	519	**77583**	260	**80490**	75	**80704**	95	**81024**	170	**81101**	825
77313	740	**77378**	853	**77476**	519	**77584**	260	**80491**	75	**80751**	91	**81025**	170	**81102**	825
77314	736	**77379**	853	**77477**	519	**77585**	260	**80546**	754	**80753**	91	**81026**	170	**81103**	825
77315	740	**77380**	853	**77478**	519	**77586**	260	**80547**	754	**80758**	92	**81033**	169	**81104**	825
77316	736	**77381**	853	**77490**	517	**77587**	260	**80548**	765	**80760**	92		170	**81105**	825
77317	740	**77382**	853	**77491**	517	**77588**	260	**80549**	765	**80799**	95	**81034**	170	**81106**	825
77318	736	**77383**	674	**77492**	517	**77589**	261	**80550**	754	**80800**	95	**81036**	169	**81107**	825
77319	740	**77384**	674	**77493**	517	**77590**	261	**80551**	754	**80801**	95		170	**81108**	825
77320	736	**77385**	674	**77495**	517	**77591**	261	**80552**	765	**80807**	95	**81037**	170	**81110**	767
77321	740	**77386**	674	**77496**	517	**77592**	261	**80553**	765	**80808**	95	**81039**	170	**81122**	74
77322	48	**77387**	674	**77497**	517	**77593**	261	**80554**	755	**80809**	95	**81040**	170	**81123**	74
77323	48	**77388**	674	**77498**	517	**77594**	262	**80555**	755	**80831**	97	**81042**	169	**81172**	720
77324	48	**77389**	674	**77534**	46	**77595**	262	**80556**	766	**80832**	97		170	**81173**	720
77325	48	**77390**	674	**77535**	46	**77596**	262	**80557**	766	**80833**	97	**81043**	170	**81174**	720
77326	48	**77391**	650	**77536**	46	**77597**	262	**80558**	756	**80839**	97	**81045**	169	**81175**	722
77327	48	**77392**	650	**77537**	46	**77604**	464	**80559**	756	**80840**	97		170	**81176**	722
77328	48	**77393**	650	**77538**	46	**77605**	464	**80560**	756	**80841**	97	**81046**	170	**81177**	722
77329	48	**77395**	650	**77539**	46	**77606**	464	**80561**	766	**80863**	96	**81048**	169	**81178**	722
77330	46	**77396**	650	**77540**	46	**77607**	464	**80562**	766	**80864**	96		170	**81179**	722
77331	46	**77397**	650	**77541**	46	**77608**	464	**80563**	766	**80865**	96	**81049**	170	**81180**	722
77332	46	**77407**	628	**77542**	48	**77609**	473	**80564**	756	**80871**	96	**81051**	169	**81181**	724
77333	46	**77408**	628	**77543**	48	**77611**	473	**80565**	756	**80872**	96		170	**81182**	724
77334	46	**77409**	628	**77544**	48	**77612**	473	**80566**	756	**80873**	96	**81052**	170	**81183**	724
77335	46	**77410**	628	**77545**	48	**77613**	481	**80567**	766	**80895**	98	**81054**	169	**81184**	724
77336	46	**77411**	628	**77546**	48	**77614**	481	**80568**	766	**80896**	98		170	**81185**	724
77337	46	**77412**	628	**77547**	48	**77615**	481	**80569**	766	**80897**	98	**81055**	170	**81186**	724
77338	50	**77413**	516	**77548**	48	**77618**	469	**80570**	756	**80903**	98	**81057**	169	**81187**	725
77339	50	**77414**	516	**77549**	48	**77619**	180	**80571**	756	**80904**	98		170	**81188**	725
77340	50	**77415**	516	**77550**	50	**77620**	180	**80573**	767	**80905**	98	**81058**	170	**81189**	725
77341	50	**77416**	516	**77551**	50	**77621**	180	**80574**	767	**80909**	859	**81060**	169	**81190**	725
77342	50	**77418**	516	**77552**	50	**77633**	671	**80576**	756	**80910**	859		170	**81191**	725
77343	50	**77419**	516	**77553**	50	**77634**	671	**80577**	767	**80913**	859	**81061**	170	**81192**	725
77344	50	**77420**	516	**77554**	50	**80029**	87	**80578**	756	**80914**	859	**81063**	169	**81193**	726
77345	50	**77421**	516	**77555**	50	**80030**	87	**80579**	767	**80953**	859		170	**81194**	726
77346	48	**77423**	515	**77556**	50	**80033**	87	**80580**	756	**80954**	859	**81064**	170	**81195**	726
77347	48		516	**77557**	50	**80034**	87	**80581**	767	**80955**	859	**81066**	169	**81196**	726
77348	48	**77424**	515	**77558**	46	**80035**	87	**80582**	719	**80956**	859		170	**81197**	726
77349	48		516	**77559**	46	**80036**	87	**80583**	719	**80990**	170	**81067**	170	**81198**	726
77350	48	**77425**	515	**77560**	46	**80039**	87	**80584**	719	**80991**	170	**81069**	170	**81199**	719
77351	48		516	**77561**	46	**80040**	87	**80585**	719	**80992**	170	**81070**	170	**81200**	719
77352	48	**77426**	515	**77562**	46	**80065**	88	**80586**	719	**80993**	170	**81072**	170	**81201**	721
77353	48		516	**77563**	46	**80066**	88	**80587**	719	**80994**	170	**81073**	170	**81202**	721
77354	46	**77438**	521	**77564**	46	**80069**	88	**80588**	720	**80995**	170	**81075**	170	**81203**	723
77355	46	**77439**	521	**77565**	46	**80070**	88	**80589**	720	**80999**	169	**81076**	170	**81204**	723
77356	46	**77440**	521	**77566**	48	**80314**	890	**80590**	720		170	**81078**	170	**81205**	724
77357	46	**77441**	521	**77567**	48	**80338**	123	**80595**	91	**81000**	170	**81079**	170	**81206**	724
77358	46	**77443**	521	**77568**	48	**80354**	98	**80596**	91	**81002**	170	**81081**	170	**81207**	725
77359	46	**77444**	521	**77569**	48	**80355**	98	**80603**	91	**81003**	170	**81082**	170	**81208**	725
77360	46	**77445**	521	**77570**	48	**80356**	98	**80604**	91	**81005**	171	**81084**	171	**81209**	727
77361	46	**77446**	521	**77571**	48	**80362**	98	**80605**	666	**81006**	170	**81085**	171	**81210**	727
77362	50	**77451**	707	**77572**	48	**80363**	98	**80612**	767	**81007**	170	**81086**	170	**81211**	719
77363	50	**77452**	707	**77573**	48	**80364**	98	**80616**	768	**81008**	170	**81087**	170	**81212**	719
77364	50	**77453**	707	**77574**	50	**80370**	96	**80644**	92	**81009**	170	**81088**	170	**81213**	721
77365	50	**77454**	707	**77575**	50	**80371**	96	**80645**	92	**81012**	170	**81091**	171	**81214**	721
77366	50	**77466**	305	**77576**	50	**80372**	96	**80648**	92	**81013**	170	**81093**	171	**81215**	723
77367	50	**77468**	305	**77577**	50	**80432**	779	**80649**	92	**81014**	170	**81094**	171	**81216**	723
77368	50	**77469**	628	**77578**	50		875	**80660**	97	**81015**	170	**81095**	171	**81217**	724
77369	50	**77470**	519	**77579**	50	**80437**	764	**80661**	97	**81018**	170	**81097**	825	**81218**	724
77370	674	**77471**	519	**77580**	50	**80438**	764	**80672**	95	**81019**	170	**81098**	825	**81219**	726
77371	674	**77472**	519	**77581**	50	**80441**	751	**80673**	95	**81021**	170	**81099**	825	**81220**	726
77372	674	**77473**	519	**77582**	260	**80442**	751	**80690**	97	**81022**	170	**81100**	825	**81221**	727

Codes index

Code	Page	Code	Page	Code	Page	Code	Page	Code	Page	Code	Page	Code	Page	Code	Page
81222	727	**81413**	266	**81605**	596	**81779**	926	**82075**	112	**82360**	236	**82463**	727	**82666**	734
81223	440	**81414**	266	**81606**	596	**81784**	469	**82077**	112	**82361**	236	**82469**	73	**82667**	731
81224	440	**81416**	266	**81607**	596	**81785**	469	**82105**	143	**82362**	236	**82470**	73	**82668**	731
81226	440	**81417**	266	**81608**	596	**81786**	469	**82106**	143	**82363**	236	**82473**	114	**82669**	732
81227	440	**81418**	256	**81609**	596	**81787**	469	**82107**	144	**82364**	236	**82474**	114	**82670**	732
81229	441	**81419**	256	**81610**	604	**81788**	464	**82108**	144	**82365**	236	**82477**	115	**82671**	732
81230	441	**81420**	256	**81611**	604	**81789**	464	**82109**	144	**82366**	236	**82478**	115	**82672**	732
81232	441	**81421**	256	**81612**	604	**81790**	464	**82110**	144	**82367**	236	**82521**	719	**82673**	732
81233	441	**81422**	257	**81613**	604	**81791**	464	**82114**	147	**82368**	236	**82522**	719	**82674**	732
81235	442	**81423**	257	**81614**	604	**81808**	140	**82121**	147	**82369**	236	**82523**	721	**82675**	732
81236	442	**81424**	266	**81615**	604	**81809**	140	**82122**	147	**82370**	236	**82524**	721	**82676**	732
81238	442	**81425**	257	**81616**	604	**81810**	140	**82198**	430	**82383**	178	**82525**	723	**82677**	732
81239	442	**81426**	256	**81617**	604	**81811**	140	**82199**	430	**82384**	178	**82526**	723	**82678**	732
81241	440	**81427**	257	**81618**	604	**81812**	140	**82202**	430	**82385**	178	**82531**	751	**82679**	734
81242	440	**81430**	256	**81625**	138	**81813**	140	**82227**	139	**82386**	178	**82532**	751	**82680**	734
81243	441	**81447**	605	**81626**	138	**81828**	967	**82228**	139	**82389**	178	**82535**	756	**82681**	732
81244	441	**81448**	605	**81627**	138	**81829**	967	**82229**	141	**82390**	178	**82536**	756	**82682**	732
81245	442	**81449**	605	**81628**	138	**81830**	967	**82230**	141	**82391**	178	**82540**	764	**82683**	733
81246	442	**81450**	606	**81629**	138	**81831**	967	**82231**	142	**82392**	178	**82541**	764	**82684**	733
81258	81	**81451**	606	**81630**	138	**81835**	967	**82232**	142	**82395**	178	**82542**	767	**82685**	733
81259	81	**81452**	606	**81631**	140	**81836**	967	**82251**	158	**82396**	178	**82543**	767	**82686**	733
81262	82	**81469**	714	**81632**	140	**81838**	449	**82252**	158	**82397**	178	**82545**	767	**82687**	733
81263	82	**81471**	714	**81633**	140	**81839**	449	**82253**	158	**82398**	178	**82547**	767	**82688**	733
81274	74	**81473**	481	**81634**	140	**81840**	449	**82254**	158	**82406**	139	**82596**	807	**82689**	733
81275	74	**81474**	481	**81635**	140	**81877**	504	**82258**	222	**82407**	139	**82597**	807	**82690**	733
81278	75	**81509**	668	**81636**	140	**81878**	504	**82259**	222	**82408**	139	**82600**	108	**82691**	733
81279	75	**81510**	668	**81637**	142	**81879**	504	**82260**	222	**82409**	139	**82601**	108	**82692**	733
81282	74	**81511**	668	**81638**	142	**81880**	504	**82261**	222	**82410**	141	**82602**	108	**82693**	734
81283	74	**81512**	668	**81639**	142	**81885**	504	**82262**	222	**82411**	141	**82603**	227	**82694**	734
81286	75	**81513**	604	**81640**	142	**81886**	504	**82263**	222	**82412**	141	**82604**	227	**82695**	733
81287	75	**81574**	528	**81641**	142	**81887**	504	**82266**	774	**82413**	141	**82605**	227	**82696**	733
81290	668	**81575**	528	**81642**	142	**81888**	504	**82267**	774	**82414**	142	**82606**	227	**82697**	730
81291	668	**81576**	528	**81661**	128	**81893**	449	**82268**	774	**82415**	142	**82607**	138	**82698**	730
81292	668	**81577**	528	**81662**	128	**81894**	449	**82269**	774	**82416**	142	**82608**	138	**82699**	730
81293	668	**81578**	528	**81663**	128	**81895**	449	**82270**	490	**82417**	142	**82609**	138	**82700**	730
81294	668	**81579**	528	**81664**	128	**81916**	449	**82271**	490	**82422**	143	**82610**	138	**82701**	646
81295	668	**81580**	528	**81665**	128	**81917**	449	**82272**	490	**82423**	143	**82611**	138	**82702**	646
81321	720	**81581**	528	**81666**	128	**81918**	449	**82273**	490	**82424**	493	**82612**	138	**82703**	646
81322	725	**81582**	529	**81667**	129	**81946**	489	**82274**	490	**82425**	493	**82631**	180	**82710**	646
81328	560	**81583**	529	**81668**	129	**81949**	489	**82275**	490	**82426**	493	**82632**	180	**82713**	772
81329	560	**81584**	529	**81669**	129	**81954**	138	**82286**	490	**82438**	143	**82637**	700	**82714**	772
81330	560	**81585**	529	**81670**	129	**81955**	138	**82287**	490	**82439**	143	**82638**	700	**82715**	772
81331	560	**81586**	529	**81671**	129	**81987**	143	**82302**	594	**82440**	144	**82639**	694	**82716**	772
81332	560	**81587**	529	**81672**	129	**81988**	143	**82303**	594	**82441**	144	**82640**	694	**82717**	772
81333	560	**81588**	529	**81717**	755	**81989**	143	**82304**	594	**82444**	143	**82642**	907	**82718**	772
81337	805	**81589**	529	**81718**	765	**81990**	143	**82305**	594	**82445**	143	**82644**	907	**82719**	772
81338	805	**81590**	596	**81734**	768	**81991**	144	**82306**	594	**82446**	144	**82646**	907	**82720**	772
81339	668	**81591**	594	**81736**	685	**81992**	144	**82307**	594	**82447**	144	**82648**	907	**82721**	773
81340	668	**81592**	594	**81750**	686	**81995**	237	**82308**	599	**82448**	144	**82650**	907	**82722**	773
81341	668	**81593**	594	**81751**	686	**81996**	237	**82309**	599	**82449**	144	**82652**	907	**82723**	772
81342	668	**81594**	594	**81752**	142	**81997**	237	**82310**	599	**82452**	441	**82654**	907	**82724**	773
81343	668	**81595**	594	**81753**	142	**81998**	237	**82311**	599	**82453**	441	**82656**	907	**82728**	173
81344	668	**81596**	594	**81754**	142	**81999**	237	**82312**	599	**82454**	442	**82657**	731	**82729**	173
81371	504	**81597**	597	**81755**	142	**82000**	237	**82313**	599	**82455**	442	**82658**	731	**82730**	173
81372	504	**81598**	597	**81756**	142	**82003**	237	**82353**	236	**82456**	721	**82659**	731	**82731**	172
81373	504	**81599**	597	**81757**	142	**82004**	237	**82354**	236	**82457**	721	**82660**	731	**82732**	172
81374	504	**81600**	597	**81774**	926	**82005**	237	**82355**	236	**82458**	723	**82661**	731	**82733**	172
81410	256	**81601**	597	**81775**	926	**82006**	237	**82356**	236	**82459**	723	**82662**	731	**82734**	172
	263	**81602**	597	**81776**	926	**82007**	237	**82357**	236	**82460**	725	**82663**	731	**82735**	172
81411	256	**81603**	596	**81777**	926	**82008**	237	**82358**	236	**82461**	725	**82664**	731	**82736**	172
	263	**81604**	596	**81778**	926	**82072**	147	**82359**	236	**82462**	727	**82665**	734	**82737**	128

Codes index

Code	Page	Code	Page	Code	Page	Code	Page	Code	Page	Code	Page	Code	Page	Code	Page
82738	128	**82813**	525	**83008**	943	**83107**	935	**83193**	964	**83267**	282	**83347**	161		742
82739	128	**82814**	525	**83009**	937	**83108**	295	**83194**	949	**83269**	282	**83348**	161	**83412**	256
82740	128	**82815**	525		950		296	**83195**	949	**83270**	282	**83349**	161		263
82741	671	**82816**	525		955		297	**83196**	950	**83271**	280	**83350**	161	**83413**	256
82742	671	**82818**	525		958	**83109**	295	**83197**	886	**83272**	280	**83351**	430		263
82743	671	**82819**	525		961		296	**83198**	886	**83273**	280	**83352**	430	**83414**	256
82744	671	**82820**	525		965		297		887	**83274**	280	**83356**	305		263
82745	671	**82821**	525		966	**83115**	956	**83199**	803	**83275**	280	**83357**	305	**83415**	266
82746	671	**82823**	225	**83010**	950	**83116**	956		964	**83276**	280	**83359**	459	**83416**	266
82747	671	**82825**	225		959	**83118**	956	**83200**	589	**83277**	280	**83361**	57	**83417**	266
82748	671	**82827**	225		960	**83119**	956		803	**83278**	280	**83362**	57	**83418**	256
82749	225	**82829**	225		961	**83120**	943	**83201**	803	**83279**	280	**83363**	57	**83419**	256
82751	225	**82834**	225	**83012**	952	**83121**	943	**83202**	803	**83280**	280	**83364**	57	**83420**	256
82753	209	**82836**	225	**83013**	950	**83122**	939	**83205**	615	**83281**	280	**83365**	57	**83421**	256
82754	209	**82838**	225		959	**83123**	509		619	**83282**	280	**83366**	57	**83422**	257
82755	209	**82840**	225		960		557	**83211**	495	**83283**	281	**83367**	58	**83423**	257
82756	209	**82842**	225		961	**83124**	509	**83212**	495	**83284**	281	**83368**	58	**83424**	257
82757	209	**82844**	225	**83015**	952		557	**83213**	243	**83285**	281	**83369**	58	**83425**	257
82758	209	**82846**	430	**83016**	935	**83125**	509		619	**83286**	281	**83370**	58	**83426**	257
82759	209	**82847**	430	**83017**	935		557	**83215**	495	**83287**	281	**83371**	58	**83427**	257
82760	209	**82850**	417	**83020**	909	**83126**	509	**83216**	495	**83288**	281	**83372**	58	**83428**	266
82763	526		433	**83022**	909		557	**83217**	495	**83291**	281	**83373**	57	**83429**	266
82764	526	**82851**	417	**83023**	909	**83129**	404	**83218**	495	**83292**	281	**83374**	57	**83430**	266
82765	526		433	**83030**	495	**83132**	404	**83220**	964	**83293**	281	**83375**	57	**83431**	266
82766	526	**82852**	958	**83031**	495		405	**83221**	296	**83294**	281	**83376**	57	**83447**	861
82768	526	**82853**	958	**83034**	430		407		297	**83295**	281	**83377**	57	**83448**	861
82769	526	**82856**	958	**83035**	491	**83133**	404	**83222**	296	**83296**	281	**83378**	57	**83449**	864
82770	526	**82857**	417	**83036**	742	**83140**	884		297	**83297**	284	**83379**	58	**83450**	861
82771	526	**82877**	87	**83037**	742	**83141**	884	**83224**	407	**83298**	284	**83380**	58	**83451**	861
82773	525	**82878**	87	**83038**	742		886	**83225**	935	**83305**	284	**83381**	58	**83452**	861
82774	525	**82881**	87	**83039**	742	**83142**	885	**83226**	935	**83306**	284	**83382**	58	**83453**	861
82775	525	**82882**	87	**83040**	742		886	**83227**	936	**83309**	277		71	**83521**	694
82776	525	**82902**	178	**83041**	947		887	**83228**	936	**83310**	277	**83383**	58	**83522**	700
82778	525	**82903**	178	**83042**	266	**83143**	940	**83229**	619	**83311**	277		71	**83523**	694
82779	525	**82905**	178		282	**83144**	963	**83235**	742	**83312**	277	**83384**	58	**83524**	700
82780	525	**82906**	178		947	**83145**	963		791	**83313**	277		71	**83558**	684
82781	525	**82908**	178	**83049**	600	**83146**	955	**83236**	932	**83314**	277	**83387**	417	**83559**	684
82783	526	**82909**	178	**83051**	181	**83147**	955	**83237**	933	**83316**	277	**83388**	967	**83560**	685
82784	526	**82912**	180	**83052**	181	**83148**	965	**83239**	927	**83317**	277	**83389**	967	**83561**	685
82785	526	**82914**	260	**83054**	181	**83149**	966	**83242**	181	**83318**	277	**83390**	58	**83562**	685
82786	526	**82916**	260	**83055**	181	**83150**	966	**83243**	963	**83319**	277	**83391**	58	**83563**	686
82788	526	**82918**	260	**83058**	942	**83151**	966	**83244**	963	**83322**	941	**83392**	58	**83564**	686
82789	526	**82920**	260	**83059**	942	**83152**	966	**83245**	471	**83323**	941	**83393**	58	**83565**	714
82790	526	**82922**	262	**83060**	942	**83153**	263	**83246**	474	**83328**	453	**83394**	58	**83566**	714
82791	526	**82926**	261	**83061**	942	**83155**	653	**83247**	511		776	**83395**	58	**83567**	714
82793	525	**82928**	261	**83062**	946	**83159**	942	**83248**	511	**83329**	777	**83396**	398	**83568**	714
82794	525	**82930**	261	**83064**	76	**83160**	911	**83249**	171	**83330**	453	**83397**	398	**83569**	714
82795	525	**82932**	261	**83065**	58	**83161**	911	**83250**	171		777	**83398**	398	**83570**	714
82796	525	**82934**	721		76	**83162**	566	**83254**	281	**83331**	453	**83399**	398	**83571**	481
82798	525	**82935**	721	**83066**	943		805	**83255**	281		777	**83400**	398	**83572**	481
82799	525	**82940**	108	**83067**	328	**83177**	962	**83256**	282	**83333**	953	**83401**	398	**83573**	481
82800	525	**82941**	108	**83068**	329	**83178**	962	**83257**	282	**83336**	170	**83402**	398	**83574**	481
82801	525	**82942**	108	**83069**	328	**83181**	671	**83258**	282	**83337**	170	**83403**	398	**83575**	481
82803	526	**82944**	261	**83075**	864	**83186**	265	**83259**	282	**83338**	170	**83404**	854	**83576**	481
82804	526	**82946**	259	**83076**	864	**83187**	961	**83260**	282	**83339**	170	**83407**	305	**83577**	481
82805	526	**82947**	259	**83096**	776	**83188**	588	**83261**	282	**83340**	170	**83408**	305	**83579**	651
82806	526	**82948**	259	**83097**	777		793	**83262**	282	**83341**	170	**83409**	305	**83580**	651
82808	526	**82949**	259	**83098**	777	**83189**	935	**83263**	282	**83342**	161	**83410**	662	**83581**	651
82809	526	**82950**	259	**83104**	935	**83190**	807	**83264**	282	**83343**	161		742	**83583**	652
82810	526	**82951**	259	**83105**	935	**83191**	807	**83265**	282	**83344**	161		791	**83584**	652
82811	526	**83007**	937	**83106**	935	**83192**	965	**83266**	282	**83345**	161	**83411**	662	**83585**	652

Codes index

Code	Page
83588	779
83601	666
83602	666
83603	666
83604	666
83606	684
83607	684
83608	685
83609	685
83610	685
83611	686
83612	686
83613	666
83642	789
83643	789
83644	789
83645	789
83651	327
83652	327
83653	327
83654	327
83655	327
83656	328
83705	715
83706	715
83707	715
83708	715
83709	715
83710	715
83712	296
83713	296
83714	296
83715	296
83716	296
83717	296
83718	296
83719	296
83720	298
83721	298
83722	298
83723	298
83724	298
83725	299
83726	299
83727	299
83728	299
83729	299
83730	298
83731	298
83732	298
83733	296
	297
83736	296
83737	296
83738	296
83739	296
83740	296
83741	296
83742	296
83743	296
83744	298
83745	298
83746	298
83747	298
83748	298
83749	299
83750	299
83751	299
83752	299
83753	299
83754	298
83755	298
83756	298
83757	296
	297
83763	813
83766	80
83767	80
83770	80
83771	80
83774	80
83775	80
83776	773
83777	773
83778	773
83779	773
83780	773
83781	773
83791	297
83792	297
83793	297
83794	297
83795	297
83796	297
83797	297
83798	297
83799	139
83800	139
83801	139
83802	139
83803	139
83804	139
83805	140
83806	140
83807	140
83808	140
83809	140
83810	140
83811	142
83812	142
83815	297
83816	297
83817	297
83818	297
83819	297
83820	297
83821	297
83822	297
83823	142
83824	142
83825	142
83826	142
83827	143
83828	143
83829	143
83830	143
83831	143
83832	143
83833	143
83834	143
83835	144
83836	144
83839	144
83840	144
83841	803
83859	556
83860	556
83861	509
83862	556
83863	556
83864	509
83865	556
83866	556
83867	556
83868	509
83869	556
83870	556
83871	509
83872	556
83873	556
83875	815
83876	816
83877	817
83878	817
83879	815
83880	816
83881	817
83882	817
83883	817
83884	817
83885	549
83886	549
83887	549
83888	549
83889	549
83890	549
83891	549
83892	549
83899	147
83900	147
83921	158
83922	158
83923	158
83924	158
83925	772
83926	772
83927	772
83928	772
83929	772
83930	772
83931	773
83932	773
83933	773
83934	773
83935	773
83936	773
83937	772
83938	772
83939	773
83940	773
83941	772
83942	773
83943	260
83944	260
83945	260
83946	262
83947	262
83948	262
83952	264
83953	264
83954	264
83955	264
83956	265
83957	265
83958	265
83959	265
83960	264
83961	264
83962	264
83963	264
83964	264
83968	260
83969	260
83970	260
83971	260
83972	260
83973	260
83974	260
83975	262
83976	262
83977	262
83978	262
83979	261
83980	261
83981	261
83982	261
83983	261
83987	259
83988	259
83989	259
83990	259
83991	259
83992	259
83993	264
83994	264
83995	264
83996	264
83997	265
83998	265
83999	265
84000	265
84001	264
84002	264
84003	264
84004	264
84005	264
84010	256
84011	256
84012	263
84013	263
84014	263
84015	263
84016	256
	263
84017	257
84018	266
84023	121
84024	121
84025	890
84026	890
84027	891
84028	891
84029	891
84030	891
84031	884
84032	884
84033	884
84034	884
84035	886
84036	886
84037	885
84038	885
84039	885
84040	885
84041	886
84042	887
84043	886
84044	887
84055	561
84056	561
84057	561
84058	563
84059	563
84068	490
84069	490
84070	490
84071	666
84072	666
84073	263
84074	263
84075	651
84076	651
84077	651
84078	651
84083	79
84084	79
84085	79
84086	79
84087	80
84088	80
84089	80
84090	80
84091	80
84092	80
84093	80
84094	80
84095	83
84096	83
84097	83
84098	83
84099	83
84100	83
84101	83
84102	83
84103	83
84104	83
84105	83
84106	83
84107	81
84108	81
84109	82
84110	82
84111	95
84112	95
84113	95
84115	95
84116	95
84117	95
84119	95
84120	95
84121	95
84123	95
84124	95
84125	95
84127	97
84128	97
84129	97
84131	97
84132	97
84133	97
84135	97
84136	97
84137	97
84139	97
84140	97
84141	97
84143	96
84144	96
84145	96
84147	96
84148	96
84149	96
84151	98
84152	98
84153	98
84155	98
84156	98
84157	98
84159	128
84160	128
84161	129
84162	129
84163	129
84164	129
84165	138
84166	138
84167	140
84168	140
84169	222
84170	222
84171	222
84184	531
84185	531
84186	531
84187	531
84193	890
84194	890
84199	112
84200	112
84203	112
84204	112
84212	911
84213	911
84214	563
84215	563
84216	563
84217	805
84218	805
84233	464
84234	464
84235	464
84236	464
84237	464
84238	464
84239	464
84240	464
84241	473
84242	473
84243	473
84244	473
84270	222
84271	222
84272	222
84273	222
84274	222
84275	222
84276	222
84277	222
84278	222
84283	797
84284	797
84285	797
84286	797
84287	797
84288	797
84335	345
	367
	377
84336	345
	351
	369
	371
	647
	657
	669
	714
84337	355
84338	348
	653
	654
84341	689
84349	355
84357	613
84359	613
84361	613
84363	613
84365	613
84367	613
84369	613
84371	613
84373	613
84375	613
84377	613
84379	613
84382	242
84385	242
84388	242
84393	242
84396	242
84399	242
84402	618
84405	618
84408	618
84411	618
84414	618
84417	618
84418	926
84419	926
84420	926
84421	926
84422	926
84423	926
84424	926
84425	926
84426	926
84427	926
84428	926
84429	926
84430	926
84431	926
84432	494
84433	494
84434	495
84435	494
84436	494
84437	495
84438	494
84439	494
84440	495
84441	490
84442	490
84443	490
84446	404
84466	853
84467	853
84468	853
84469	853
84470	853

Codes index

Code	Page
84471	853
84472	853
84473	853
84474	853
84475	853
84476	853
84477	853
84478	853
84479	853
84480	853
84481	853
84506	854
84507	854
84508	854
84509	854
84510	854
84511	854
84512	854
84513	854
84514	854
84515	854
84516	854
84517	854
84518	854
84519	854
84520	854
84521	854
84527	473
84528	473
84529	473
84530	473
84537	477
84538	477
84539	477
84540	477
84541	477
84542	477
84543	477
84544	477
84545	477
84546	477
84547	477
84548	477
84549	478
84550	478
84551	478
84552	478
84553	478
84554	478
84555	478
84556	478
84557	478
84558	478
84559	478
84560	478
84561	481
84562	481
84563	481
84564	481
84565	481
84566	481
84567	853
84568	853
84569	853
84570	853
84575	232
84576	232
84577	232
84578	232
84579	232
84580	232
84581	233
84582	233
84583	233
84584	233
84585	233
84586	233
84587	233
84588	233
84589	233
84626	946
84700	936
	945
	957
	959
	960
	961
	962
84701	945
84787	946
84829	944
84863	927
84864	970
84865	961
	962
	963
	964
	965
	966
	971
	972
84866	970
84867	970
84869	963
	971
84870	971
84871	971
84872	970
84873	970
84874	970
84875	970
84876	970
84885	971
84887	970
84888	970
84890	478
	481
	485
84892	970
84893	783
	909
	911
	971
84894	783
	971
84895	971
84900	695
	776
84901	369
	371
	377
84902	373
84915	345
	371
	647
	653
	657
	669
84916	363
	367
	377
84917	363
	367
	377
84918	653
	689
	714
	776
84932	776
84935	689
	695
	776
	783
84936	689
	695
	776
	783
84945	875
84952	343
84954	377
84955	369
84956	369
84990	875
84994	971
84995	343
85001	365
85002	365
85335	363
85542	651
85543	651
86460	651
86562	652
86563	652
86612	370
86613	370
86614	371
86615	371
86674	370
86675	371
86707	365
86708	365
87340	375
87988	651
87989	652
88417	365
88568	370
88569	371
89045	588
	807
89046	588
	807
89047	588
	807
89144	937
89145	937
89146	937
89147	937
89148	948
89149	948
89150	948
89151	948
89175	952
89176	952
89177	952
89179	950
89186	567
	963
	966
89187	567
	964
89188	551
	567
	589
	744
	791
89189	567
	965
	966
89190	551
	567
	589
	744
	791
89223	398
89359	951
89361	567
89365	567
	964
	972
89371	471
	474
89373	58
	67
	76
	115
	446
89374	58
	67
	76
	115
	446
89408	944
89419	948
89420	948
89421	948
89422	948
89423	948
89488	950
89548	433
	903
90403	481
90404	481
90442	917
90443	917
90444	917
90445	917
90458	605
90459	606
90460	605
90461	605
90462	606
90463	606
90473	917
90519	464
90520	464
90521	464
90522	464
90660	75
90661	75
90662	73
90663	73
90666	75
90667	75
90670	73
90671	73
90672	75
90673	75
90674	73
90675	73
90678	75
90679	75
90682	73
90683	73
90762	79
90763	79
90766	79
90767	79
90770	83
90771	83
90774	83
90775	83
90776	79
90777	79
90780	79
90781	79
90784	83
90785	83
90788	83
90789	83
90790	80
90791	80
90794	80
90795	80
90798	83
90799	83
90802	83
90803	83
90830	81
90831	81
90834	81
90835	81
90838	84
90839	84
90842	84
90843	84
90846	81
90847	81
90850	81
90851	81
90854	84
90855	84
90858	84
90859	84
90862	81
90863	81
90866	81
90867	81
90870	84
90871	84
90874	84
90875	84
90903	327
90905	327
90905E	327
90907	327
90909	327
90911	327
90913	327
90915	327
90917	327
90919	328
90921	328
90923	328
90925	328
90927	328
90929	328
90931	328
90933	328
90935	328
90943	329
90944	329
90945	329
90946	329
90950	328
90952	328
91352	365
91366	363
91596	799
91597	799
91598	799
91599	529
91600	529
91601	529
91602	529
91749	95
91750	95
91751	95
91753	97
91754	97
91755	97
92023	331
92025	331
92038	604
92040	604
92042	604
92044	604
92046	597
92047	597
92048	597
92049	594
92050	594
92051	594
92052	596
92054	596
92056	596
92061	714
92065	714
92066	714
92067	714
92068	714
92069	715
92070	605
92072	605
92074	605
92076	715
92077	715
92078	605
92080	599
92081	599
92082	599
92083	595
92084	595
92088	715
92092	715
92093	595
92100	597
92104	597
92108	597
92112	604
92114	604
92118	604
92120	604
92124	597
92125	597
92126	597
92127	594
92128	594
92129	594
92132	596
92134	596
92136	596
92138	595
92139	595
92142	595
92143	595
92144	595
92145	595
92157	857
92162	857
92163	857
92166	857
92167	857
92168	857
92238	652
92239	652
92240	652
92245	613
92246	613
92247	613
92260	657
92262	657
92271	647
92272	647
92273	647
92281	647
92282	647
92283	647
92311	647
92312	647
92313	647
92353	613
92356	613
92357	613
92370	854
92371	854
92384	609
92385	609
92386	609
92387	609
92390	609
92391	609
92392	609
92393	609
92421	609
92422	609
92423	609
92424	609
92442	613
92443	613
92444	613
92448	613
92449	613
92450	613
92513	654
92514	654
92518	857
92525	857
92526	857
92527	857
92558	654
92559	654
92671	651
92672	652
92681	676
93099	777
93114	875
93170	859
93171	859

Codes index

Code	Page
93174	859
93181	859
93184	859
93185	859
93188	859
93189	859
93282	929
93293	859
93294	859
93312	859
93313	859
93332	859
93336	859
93450	96
93451	96
93452	96
93994	561
93995	561
94021	561
94022	561
94110	331
94115	331
94151	875
94679	618
94680	618
94681	618
94908	242
94909	242
94910	242
94911	242
94912	242
94913	242
95068	464
95126	464
95141	464
95330	464
95454	797
95458	797
95465	618
95466	618
95467	618
95474	734
95475	734
95476	734
95612	797
95616	797
95619	797
95623	797
95749	797
95750	797
95751	797
96150	560
96151	560
96152	560
96196	563
96197	563
96740	547
96741	547
96742	547
96976	666
96977	666
96978	666
96979	666
97048	528
97049	528
97050	528
97051	528
97052	528
97053	528
97054	528
97055	528
97065	801
97066	801
97067	801
97071	481
97072	481
97073	481
97167	668
97169	668
97170	668
97172	668
97185	528
97186	528
97187	528
97188	528
97256	563
97315	873
97317	873
97353	684
97354	684
97355	685
97356	685
97357	801
97612	563
97673	560
97674	560
97675	560
97797	714
97798	714
97799	714
97800	714
97801	714
98009	676
98049	369
98050	653
98060	873
98111	669
98112	478
	481
	485
98121	695
	776
98122	776
98133	783
98134	783
98140	963
98146	491
	607
98147	491
	607
98148	873
98149	551
	567
	589
	744
	791
98150	861
98151	861
98152	861
98153	861
98154	861
98155	861
98156	861
98157	861
98158	861
98159	861
98160	861
98161	861
98162	861
98163	861
98164	861
98165	861
98174	861
98175	861
98176	861
98177	861
98178	861
98179	861
98180	861
98181	861
98182	862
98184	862
98186	862
98188	862
98192	864
98193	864
98194	864
98195	864
98196	864
98197	864
98198	864
98199	864
98208	864
98209	864
98210	864
98211	865
98212	865
98213	865
98214	862
98215	863
98216	863
98217	863
98288	862
98291	742
98292	742
98355	564
98356	564
98357	564
98367	565
98368	565
98369	565
98374	565
98375	565
98376	565
98395	407
98398	547
98418	407
98419	407
98420	407
98428	225
98430	564
98434	565
98435	565
98436	103
98437	551
	567
	589
	744
	791
98464	565
98465	565
98466	564
98467	564
98468	564
98469	564
98470	564
98471	564
98472	564
98473	564
98474	564
98475	566
98476	744
	791
98477	744
	791
98493	567
	964
	966
98494	567
98499	93
98500	93
98513	481
98527	93
98528	93
98529	93
98530	93
98531	93
98532	93
98533	93
98534	93
98535	93
98536	93
98537	93
98538	93
98549	471
	485
98550	471
98553	564
98554	564
98588	181
98589	181
98624	459
	471
	474
98653	803
98654	803
98655	803
98656	934
98657	934
98658	934
98659	803
	934
98660	491
	607
	777
98661	491
	607
	777
98662	470
	491
	607
	777
98663	470
	491
	607
	777
98669	459
	474
98671	600
98672	600
98673	600
98675	607
98676	607
98677	607
98695	615
98699	332
98710	611
98713	332
98716	332
98724	600
98725	600
98726	600
98729	243
	611
	615
	619
	854
98742	863
98743	863
98744	863
98745	863
98746	863
98747	863
98748	917
98749	862
98750	862
98751	862
98752	862
98754	917
98755	917
98758	917
98761	917
98764	917
98771	566
98772	566
98773	566
98781	332
98782	588
98783	588
98784	588
98785	588
98836	565
98837	565
98838	565
98839	565
98840	565
98841	565
98842	565
98843	565
98844	565
98845	565
98876	564
98878	332
98879	332
98885	407
98886	407
98887	407
98888	407
98890	407
98891	404
98892	404
98895	405
98896	405
98897	406
98898	406
98899	406
98900	406
98901	406
98902	406
98904	407
98906	406
98907	406
98912	407
98913	407
98914	407
98915	407
98916	406
98917	406
98918	406
98921	406
98922	406
98925	404
98928	404
98931	404
	405
98941	404
	405
	407
98942	404
	405
	407
98943	404
	405
	407
98944	404
	405
98949	588
	793
	807
98950	348
	653
98951	588
98952	588
98953	588
98954	404
98956	407
98957	600
98964	398
98965	405
98985	470
	491
	607
	777
	965
	972
98986	470
	491
	607
	777
	972
98989	971
98990	433
	903
	971
98991	909
	911
	971
98993	567
98994	567
99002	970
99045	963
99046	963
99057	491
	607
99074	947
99093	938
99105	938
99106	938
99112	938
99115	940
99126	938
99128	938
99129	938
99135	938
99141	939
99146	938
99147	938
99166	861
99167	861
99168	861
99169	861
99170	861
99171	861
99172	861
99173	861
99175	948
99176	948
99177	948
99184	963
99185	949
99186	949
99195	937
99198	938
99216	551
	567
	589
	619
	744
	791
99217	619
99218	619
99219	620
99220	620
99221	620
99222	620
99223	620
99224	620
99225	243
	619
99226	243
	615
99227	243
	615
99228	243
99229	243
	611
	615
	619
	854
	970
99231	547
99232	547
99234	963
99235	963
99237	970
99238	620
99239	938
99243	937
99260	938
99261	938
99262	940
99269	949
99307	937
99308	954
99309	935
	954
99310	954
99311	954
99330	942
99331	936
	951
	957
	959
	960
	961
	962
99332	952
99340	949

Codes index

Code	Page
99342	948
99345	942
99346	964
	966
	971
99353	970
99355	968
99360	939
99361	940
99362	943
99370	937
99371	936
	945
	957
	959
	960
	961
	962
99372	945
99373	943
99374	936
	944
	957
	959
	960
	961
	962
99375	937
99376	937
99377	937
99379	971
99381	966
99382	966
99383	966
99384	966
99386	965
99388	964
99390	470
	491
	607
	777
	972
99391	491
99392	491
99472	933
99479	130
99484	917
99485	123
99486	123
99487	123
99488	123
99489	123
99490	123
99497	124
99498	124
99499	124
99500	124
99501	124
99502	124
99510	130
99519	417
99520	433
	903
99521	432
	902
99538	430
99539	430
99549	430
99550	125
99552	125
99554	125
99556	245
99560	662
	743
99563	662
	743
	791
99564	743
99574	491
99575	964
99576	964
99577	964
99584	245
99585	917
99650	662
	743
99651	662
	743
	791
99652	743
99657	965
99658	935
	965
99660	947
99673	453
99676	647
	783
99678	875
99680	776
99681	776
99682	945
99683	946
99684	776
99685	776
	783
99688	417
	433
99689	417
	433
99708	944
99709	944
99710	944
99711	944
99712	944
99713	944
99716	948
99717	939
99718	939
99722	952
99725	946
99726	949
99727	949
99728	949
99729	949
99732	940
99733	940
99734	938
99735	938
99737	927
99739	940
99740	938
99744	669
99745	669
99748	607
99749	446
99750	446
99760	600
99768	243
	615
	619
99773	150
	238
99774	150
	238
99775	150
	238
99776	150
	238
99777	150
	238
99778	588
99779	130
	150
	174
	183
	212
	238
99780	130
	150
	174
	183
	212
	238
99781	130
	150
	174
	183
	212
	238
99782	130
	150
	174
	183
	212
	238
99783	130
	150
	174
	183
	212
	238
99784	282
	951
	957
	959
	960
	961
	962
99785	282
	951
	957
	959
	960
	961
	962
99786	951
	957
	959
99794	776
99795	130
	174
	183
99796	130
	174
	183
99797	130
	174
	183
99798	130
	174
	183
99799	130
	174
	183
99802	471
99805	150
	238
99806	150
	238
99807	150
	238
99808	130
	150
	174
	183
99809	130
	150
	174
	183
99810	130
	150
	174
	183
99818	588
	793
99819	474
99822	607
99823	607
99824	607
99825	607
99826	607
99827	130
	150
	174
	183
	212
	238
99828	130
	150
	174
	183
	212
	238
99829	130
	150
	174
	183
	212
	238
99841	130
	161
	174
	183
99842	130
	174
	183
99843	130
	174
	183
99844	130
	174
	183
99848	76
99849	58
	76
99850	353
99853	150
99855	662
	743
99856	662
	743
	791
99857	743
99879	567
99888	115
99889	115
99890	115
99891	115
99892	115
99893	115
99898	245
99899	115
99900	115
99901	115
99902	115
99903	115
99904	115
99912	588
99913	588
99914	588
99915	588
99916	588
99917	588
	793
99918	588
99919	588
99922	742
99923	742
99924	742
99925	742
99926	588
99927	173
99928	173
99929	173
99933	793
99936	181
99938	181
99941	181
99943	181
99946	181
99948	181
99951	181
99953	181
99971.02	942
99983	404
C0010	416
C0011	416
C0012	418
	900
C0013	412
C0014	412
C0015	412
C0016	413
C0017	412
C0018	397
C0019	397
C0020	278
	424
C0021	392
C0022	392
C0023	394
C0024	394
C0025	397
C0026	397
C0027	392
	393
C0028	394
C0029	392
C0030	394
C0031	394
C0033	390
C0034	639
C0035	633
C0036	390
C0037	393
C0039	392
C0040	394
C0041	390
C0042	390
C0043	390
C0044	390
C0045	391
C0046	391
C0047	391
C0048	391
C0049	391
C0050	391
C0051	396
C0052	396
	641
C0053	396
	633
C0054	396
C0055	396
C0056	417
C0057	411
C00001	816
C00002	816
C00003	816
C00004	815
C00005	815
C00006	815
C00007	832
C00008	832
C00009	832
C00010	835
C00011	833
C00012	833
C00013	833
C00014	833
C00015	833
C00016	833
C00017	832
C00018	832
C00019	833
C00020	833
C00021	833
C00022	833
C00023	833
C00024	833
C00040	74
C00045	74
C00046	73
C00047	73
C00048	87
C00049	87
C00050	88
C00051	88
C00052	79
C00053	79
C00054	82
C00055	82
C00058	91
C00059	91
C00063	74
C00064	73
C00065	295
C00066	295
C00067	295
C00068	295
C00069	295
C00070	295
C00071	295
C00072	295
C00074	752
C00075	754
C00076	884
C00077	884
C00078	885
C00079	885
C00080	886
C00081	886
C00082	886
C00083	753
C00084	887
C00085	894
C00086	894
C00103	752
C00104	894
C00105	895
C00106	891
C00107	891
C00108	890
C00109	890
C00110	890
C00111	890
C00112	754
C00113	765
C00114	765
C00115	755
C00116	766
C00117	87
C00118	88
C00119	79
C00120	82
C00121	91
C00140	484
C00141	484
C00142	484
C00143	484
C00144	54
C00145	54
C00146	54
C00147	54
C00148	106
C00149	106
C00150	106
C00151	106
C00152	106
C00153	106
C00154	484
C00155	484
C00156	484
C00157	484
C00158	484
C00159	484
C00160	484
C00161	484
C00162	54
C00163	54
C00164	54
C00165	54
C00170	294
C00171	294
C00172	294
C00173	294
C00174	114

Codes index

Code	Page	Code	Page	Code	Page	Code	Page	Code	Page	Code	Page	Code	Page	Code	Page
C00175	114	**C00260**	51	**C00336**	308	**C00425**	206	**C00532**	574	**C00604**	770	**C00666**	193	**C00734**	218
C00176	115	**C00261**	363	**C00337**	308	**C00426**	206	**C00534**	574	**C00605**	760	**C00667**	193	**C00735**	218
C00177	116	**C00263**	365	**C00338**	308	**C00427**	206	**C00535**	574	**C00606**	771	**C00668**	585	**C00736**	218
C00178	116	**C00264**	365	**C00339**	308	**C00428**	207	**C00536**	574	**C00607**	761	**C00669**	585	**C00737**	218
C00179	116	**C00267**	365	**C00340**	308	**C00429**	207	**C00537**	574	**C00608**	582	**C00670**	581	**C00738**	194
C00180	116	**C00268**	365	**C00341**	312	**C00430**	207	**C00544**	575	**C00609**	582	**C00671**	581	**C00739**	194
C00181	117	**C00269**	370	**C00342**	312	**C00431**	207	**C00545**	575	**C00610**	582	**C00672**	581	**C00740**	218
C00182	117	**C00270**	700	**C00343**	312	**C00432**	156	**C00546**	575	**C00611**	582	**C00673**	581	**C00741**	218
C00183	117	**C00271**	51	**C00344**	312	**C00433**	156	**C00547**	575	**C00612**	582	**C00674**	581	**C00742**	218
C00184	117	**C00272**	51	**C00345**	312	**C00434**	156	**C00548**	575	**C00613**	47	**C00676**	581	**C00743**	218
C00187	306	**C00273**	370	**C00346**	313	**C00435**	156	**C00550**	575	**C00614**	582	**C00677**	581	**C00744**	218
C00188	306	**C00275**	371	**C00347**	313	**C00436**	156	**C00551**	575	**C00615**	582	**C00678**	581	**C00745**	218
C00189	306	**C00276**	371	**C00348**	313	**C00437**	208	**C00552**	575	**C00616**	582	**C00679**	581	**C00746**	505
C00190	306	**C00278**	369	**C00349**	313	**C00438**	156	**C00553**	575	**C00617**	582	**C00680**	585	**C00747**	505
C00191	306	**C00279**	700	**C00350**	313	**C00439**	208	**C00554**	575	**C00618**	582	**C00681**	585	**C00748**	505
C00197	102	**C00280**	369	**C00351**	444	**C00440**	156	**C00555**	575	**C00619**	583	**C00682**	585	**C00749**	505
C00198	102	**C00281**	369	**C00352**	444	**C00441**	156	**C00556**	578	**C00620**	583	**C00683**	585	**C00754**	50
C00199	52	**C00282**	373	**C00354**	444	**C00442**	208	**C00557**	578	**C00621**	583	**C00684**	585	**C00755**	46
C00200	102	**C00283**	375	**C00355**	444	**C00443**	156	**C00558**	578	**C00622**	583	**C00686**	585	**C00756**	505
C00201	102	**C00284**	375	**C00357**	444	**C00446**	156	**C00559**	578	**C00623**	583	**C00687**	585	**C00757**	505
C00202	102	**C00292**	375	**C00358**	444	**C00448**	156	**C00560**	578	**C00624**	47	**C00688**	585	**C00758**	505
C00203	52	**C00293**	375	**C00359**	444	**C00449**	156	**C00561**	578	**C00625**	583	**C00689**	585	**C00759**	505
C00204	102	**C00294**	375	**C00360**	444	**C00467**	503	**C00562**	578	**C00626**	583	**C00690**	793	**C00760**	505
C00205	52	**C00295**	376	**C00361**	445	**C00468**	503	**C00563**	578	**C00627**	583	**C00691**	793	**C00761**	505
C00206	52	**C00296**	376	**C00362**	445	**C00470**	165	**C00564**	578	**C00628**	583	**C00692**	68	**C00762**	660
C00207	107	**C00297**	376	**C00364**	445	**C00471**	503	**C00565**	578	**C00629**	583	**C00693**	68	**C00763**	660
C00208	107	**C00298**	376	**C00365**	445	**C00472**	165	**C00566**	579	**C00630**	47	**C00694**	68	**C00764**	660
C00217	52	**C00299**	376	**C00367**	445	**C00473**	158	**C00567**	579	**C00631**	47	**C00695**	69	**C00765**	660
C00218	52	**C00300**	700	**C00368**	445	**C00474**	158	**C00568**	579	**C00632**	49	**C00696**	69	**C00767**	660
C00219	52	**C00301**	379	**C00369**	445	**C00475**	158	**C00569**	579	**C00633**	49	**C00697**	52	**C00768**	660
C00220	52	**C00303**	379	**C00370**	445	**C00476**	158	**C00570**	579	**C00634**	49	**C00698**	52	**C00769**	660
C00221	201	**C00305**	884	**C00371**	54	**C00477**	343	**C00571**	579	**C00635**	49	**C00699**	52	**C00770**	660
C00222	638	**C00307**	885	**C00372**	54	**C00478**	343	**C00572**	579	**C00636**	51	**C00700**	52	**C00771**	66
C00223	201	**C00308**	886	**C00373**	55	**C00480**	503	**C00573**	579	**C00637**	51	**C00701**	53	**C00773**	484
C00224	201	**C00309**	886	**C00374**	55	**C00481**	503	**C00574**	579	**C00638**	51	**C00702**	53	**C00774**	484
C00225	201	**C00310**	887	**C00375**	54	**C00482**	503	**C00575**	579	**C00639**	51	**C00703**	53	**C00775**	484
C00227	351	**C00311**	894	**C00376**	54	**C00483**	503	**C00576**	769	**C00640**	47	**C00704**	53	**C00776**	484
C00228	351	**C00312**	894	**C00377**	55	**C00484**	503	**C00579**	66	**C00641**	47	**C00705**	888	**C00777**	466
C00229	351	**C00313**	891	**C00378**	55	**C00487**	467	**C00580**	66	**C00642**	47	**C00706**	888	**C00778**	466
C00230	345	**C00314**	890	**C00379**	849	**C00488**	467	**C00581**	66	**C00643**	47	**C00707**	888	**C00779**	466
C00231	345	**C00315**	890	**C00380**	849	**C00489**	466	**C00582**	67	**C00644**	49	**C00708**	888	**C00780**	466
C00232	345	**C00316**	884	**C00381**	849	**C00490**	466	**C00583**	67	**C00645**	49	**C00709**	473	**C00781**	467
C00233	345	**C00317**	232	**C00382**	849	**C00497**	888	**C00584**	579	**C00646**	49	**C00710**	473	**C00783**	68
C00236	347	**C00318**	232	**C00384**	849	**C00498**	888	**C00585**	579	**C00647**	49	**C00711**	473	**C00786**	66
	651	**C00319**	884	**C00385**	849	**C00499**	888	**C00586**	578	**C00648**	583	**C00712**	473	**C00787**	68
C00237	347	**C00320**	232	**C00400**	124	**C00500**	888	**C00587**	578	**C00649**	583	**C00713**	834	**C00788**	320
	652	**C00321**	232	**C00403**	201	**C00517**	573	**C00588**	580	**C00650**	582	**C00714**	834	**C00789**	320
C00238	347	**C00322**	884	**C00404**	201	**C00518**	573	**C00589**	580	**C00651**	582	**C00715**	688	**C00790**	320
C00239	347	**C00323**	884	**C00405**	119	**C00519**	573	**C00590**	580	**C00652**	584	**C00716**	688	**C00791**	320
C00240	347	**C00324**	687	**C00406**	119	**C00520**	573	**C00591**	580	**C00653**	584	**C00717**	688	**C00792**	320
C00241	347	**C00325**	687	**C00407**	119	**C00521**	573	**C00592**	580	**C00654**	584	**C00718**	688	**C00793**	320
C00244	355	**C00326**	687	**C00408**	119	**C00522**	573	**C00593**	580	**C00655**	584	**C00719**	688	**C00794**	316
C00245	355	**C00327**	687	**C00409**	119	**C00523**	573	**C00595**	580	**C00656**	584	**C00720**	688	**C00795**	316
C00246	355	**C00328**	687	**C00410**	203	**C00524**	573	**C00596**	580	**C00657**	584	**C00726**	504	**C00796**	316
C00247	307	**C00329**	687	**C00411**	203	**C00525**	573	**C00597**	580	**C00659**	584	**C00727**	504	**C00797**	321
C00248	307	**C00330**	884	**C00412**	203	**C00526**	573	**C00598**	580	**C00660**	584	**C00728**	504	**C00798**	321
C00249	307	**C00331**	311	**C00413**	204	**C00527**	573	**C00599**	581	**C00661**	584	**C00729**	504	**C00799**	321
C00250	307	**C00332**	311	**C00414**	204	**C00528**	573	**C00600**	581	**C00662**	584	**C00730**	218	**C00800**	321
C00251	307	**C00333**	311	**C00415**	204	**C00529**	574	**C00601**	768	**C00663**	193	**C00731**	218	**C00801**	321
C00258	51	**C00334**	311	**C00416**	204	**C00530**	574	**C00602**	758	**C00664**	193	**C00732**	218	**C00802**	321
C00259	363	**C00335**	311	**C00424**	206	**C00531**	574	**C00603**	759	**C00665**	193	**C00733**	218	**C00803**	317

Codes index

Code	Page
C00804	317
C00805	317
C00806	320
C00807	320
C00808	316
C00809	321
C00810	321
C00811	317
C00812	468
C00813	468
C00814	468
C00815	468
C00816	468
C00817	468
C00818	468
C00819	468
C00820	468
C00821	221
C00822	221
C00823	221
C00824	221
C00825	221
C00826	221
C00827	320
C00828	320
C00829	320
C00830	320
C00831	320
C00832	320
C00833	320
C00834	320
C00835	316
C00836	316
C00837	316
C00838	316
C00839	321
C00840	321
C00841	321
C00842	321
C00843	321
C00844	321
C00845	321
C00846	321
C00847	317
C00848	317
C00850	317
C00853	317
C00854	203
C00855	203
C00856	203
C00857	469
C00858	469
C00859	469
C00860	469
C00862	659
C00863	659
C00864	659
C00865	659
C00866	659
C00867	659
C00868	659
C00869	659
C00874	469
C00875	469
C00876	469
C00877	469
C00878	167
C00879	167
C00880	167
C00881	167
C00904	163
C00905	163
C00908	923
C00909	923
C00910	923
C00911	923
C00912	923
C00913	923
C00920	768
C00921	758
C00922	769
C00923	759
C00924	770
C00925	760
C00926	771
C00927	761
C00934	74
C00935	74
C00938	75
C00939	75
C00943	353
C00964	790
C00965	790
C00966	790
C00967	790
C00968	740
C00969	736
C00970	740
C00971	736
C00972	445
C00974	489
C00975	489
C00978	790
C00980	790
C00981	789
C00982	789
C00991	851
C00992	851
C00993	155
C00994	155
C00995	155
C00996	155
C00997	155
C00998	155
C00999	155
C01000	155
C01029	233
C01030	233
C01031	233
C01032	357
C01033	741
C01034	737
C01036	793
C01037	793
C01038	87
C01039	88
C01040	88
C01041	79
C01042	79
C01043	81
C01044	81
C01045	379
C01046	379
C01047	459
C01048	459
C01049	751
C01050	751
C01051	764
C01052	714
C01053	715
C01054	715
C01055	191
C01056	191
C01057	191
C01058	191
C01059	192
C01060	192
C01061	192
C01062	192
C01063	192
C01130	245
C01131	245
C01132	245
C01133	172
C01134	178
C01135	751
C01136	764
C01241	82
C01242	82
C01243	84
C01244	84
C01245	91
C-C100001	742
C-C100002	662
	742
C-C100003	662
	742
	791
C-C100004	58
C-C100005	93
C-C100006	69
	93
	112
C-C100007	58
C-C100008	69
C-C100009	69
C-C100010	69
C-C100011	69
C-C100012	69
C-C100013	69
C-C100015	446
C-C100016	67
	446
C-C100017	67
	446
C-C100018	783
C-C100020	67
C-C300001	432
	902
C-C600001	311
	312
	313
C-D100001	820
C-D100002	820
C-D100003	820
C-D100004	820
C-D100005	820
C-D100006	820
C-E100001	942
C-E100004	940
C-E100005	941
C-E100006	932
C-E100007	932
C-E100008	932
C-E100009	932
C-E100010	940
C-E100011	941
C-E100012	941
C-E100013	941
C-E100016	942
C-E100019	936
C-E100030	942
C-E100031	942
C-E100032	941
C-E100033	939
C-E100034	942
C-E100035	932
C-E100036	932
C-E100037	932
C-E100041	935
C-E100042	935
C-E100043	935
C-E100045	938
C-E100046	938
C-E100047	941
C-E100048	939
C-E100049	939
C-E200001	949
C-E200002	949
C-E200003	949
C-E200004	949
C-E200005	949
C-E200006	948
C-E200007	948
C-E200008	948
C-E300001	946
C-E300002	954
C-E300007	171
	431
C-E300008	171
	431
C-E300009	945
C-E300010	945
C-E400001	628
C-E400002	953
C-E400003	953
C-E500001	932
C-E500002	962
C-E500003	961
C-E500004	959
C-E500005	959
C-E500006	959
C-E500007	959
C-E500008	959
C-E500009	959
C-E500010	959
C-E500011	961
C-E500012	961
C-E500013	961
C-E500014	961
C-E500015	961
C-E500016	960
C-E500017	960
C-E500019	960
C-E500020	936
C-E500021	936
C-E500022	936
C-E500023	947
C-E700001	958
C-E700002	957
C-E700003	957
C-E700004	958
C-E700005	962
C-E700006	933
C-E700007	932
C-E700008	150
	160
	165
	932
C-E700009	933
C-E700010	958
C-E700011	958
C-E700012	937
C-E700015	959
C-E700016	959
C-E700017	959
C-E700018	959
C-E700019	955
C-E700020	955
C-E700021	937
C-E700022	961
C-E700023	961
C-E700024	955
C-E700026	966
C-E700027	966
C-E700028	966
C-E700029	933
C-E700031	150
	160
	165
	932
C-E900001	299
C-E900002	299
C-E900003	299
C-E900004	299
C-E900005	932
C-E900006	933
C-F100003	320
	321
C-F100017	615
	620
C-F100018	507
C-F300001	284
	426
C-F300002	284
	426
C-F300003	284
	426
C-F300004	284
	426
C-F300005	285
	426
C-F300006	285
	426
C-F300007	285
	426
C-F300008	285
	426
C-F300009	284
	426
C-F300010	284
	426
C-F300011	196
	210
C-F300012	196
	210
C-F300013	196
	210
C-F300014	196
	210
C-F300015	196
	210
C-F300016	196
	210
C-F300017	196
	210
C-F300018	196
	210
C-F300019	196
	210
C-F300020	196
	210
C-F300021	196
	211
C-F300022	196
	211
C-F300027	196
	211
C-F300029	196
	211
C-F300030	196
	211
C-F300031	196
	211
C-F300032	196
	211
C-F300033	196
	211
C-F300034	196
	211
C-F300035	196
	211
C-F300036	196
	211
C-F300037	196
	211
C-F300038	196
	211
C-F300039	196
	211
C-F300040	196
	211
C-F300041	196
	211
C-F300042	208
C-F300043	208
C-F300044	208
C-F300045	208
C-F300054	196
	210
C-F300055	196
	210
C-F300056	196
	210
C-F300057	196
	210
C-F400001	430
C-F400002	430
C-F400003	430
C-F400004	430
C-F400005	284
	426
C-F400006	588
	793
C-F400007	316
	317
C-F400008	588
C-F500001	478
	481
	485
C-F500002	459
	471
	474
C-F500003	459
	471
	474
C-F500004	430
C-F500005	430
C-F600002	71
C-F800003	628
C-K100001	432
	902
C-K100002	432
	902
C-K100003	432
	902
C-K100004	432
	902
C-K100005	432
	902
C-K100006	432
	902
C-K100007	430
C-K100008	430
C-K100009	430
C-K100010	430
C-K100011	430
C-K100015	405
C-K100016	405
C-K100017	404
	405
C-K100018	404
	405
C-K100019	407
C-K100020	407
C-K100021	171
	431
C-K100022	171
	431
C-K100025	406
C-K100026	405
C-K100027	405
C-K100028	407
C-K100029	407
C-K100032	430
C-K200001	404
C-K200002	404
C-K200003	405
C-K200004	405
C-K200005	404
	405
C-K200007	404
	405
C-K200009	406
C-K400001	295
C-K400002	295
C-K400004	295
C-K400005	295
C-K400007	295
C-K400008	295
C-K400010	296
	297
C-K400011	296
	297
C-K400013	296
	297
C-K400014	296
	297
C-K400016	295
C-K400017	295
C-K400018	295
C-K400019	295
C-K400020	295
C-K400021	295
C-K400022	296
	297
C-K400023	296

Codes index

Code	Page
	297
C-K400024	296
	297
C-K400025	296
	297
C-K400026	294
C-K400027	294
C-K400028	57
C-K400029	57
C-K400030	294
C-K400031	294
C-K400032	57
C-K400033	57
C-K400034	57
C-K400035	57
C-K400036	294
C-K400037	294
C-K400038	57
C-K400039	57
C-K400040	57
C-K400041	57
C-K400042	57
C-K400043	57
C-K400044	58
C-K400045	58
C-K400046	57
C-K400047	57
C-K400048	57
C-K400049	57
C-K400050	57
C-K400051	57
C-K400052	58
C-K400053	58
C-K400054	58
C-K400055	58
C-K400056	294
C-K400057	294
C-K400058	638
C-K400059	638
C-K400060	638
C-K400061	638
C-K400062	638
C-K400063	638
C-K400064	638
C-K400065	638
C-K400066	638
C-K400067	638
C-K400068	638
C-K400069	638
C-K400070	638
C-K400071	638
C-K400072	638
C-K400073	638
C-K400074	638
C-K400075	638
C-K400076	424
C-K400077	424
C-K400080	424
C-K400081	57
C-K400082	57
C-K400083	57
C-K400084	57
C-K400085	57
C-K400086	57
C-K400087	57
C-K400088	57
C-K400089	57
C-K400090	57
C-K400091	57
C-K400092	57
C-K400093	57
C-K400094	57
C-K400095	57
C-K400096	57
C-K400097	57
C-K400098	57
C-K400099	57
C-K400100	57
C-K400101	742
C-K400102	57
C-K400103	57
C-K400104	57
C-K400105	57
C-K400106	57
C-K400107	57
C-K400108	57
C-K400109	57
C-K400110	57
C-K400111	57
C-K400112	57
C-K400113	57
C-K400114	57
C-K400115	57
C-K400116	57
C-K400117	57
C-K400118	57
C-K400119	57
C-K400120	57
C-K400121	57
C-K400122	57
C-K400123	57
C-K400124	57
C-K400125	57
C-K400126	57
C-K400127	57
C-K400128	57
C-K400129	57
C-K400130	57
C-K400131	57
C-K400132	71
C-K400134	71
C-K400135	71
C-K400136	71
C-K400138	71
C-K400139	71
C-K400140	71
C-K400141	71
C-K400144	71
C-K400145	71
C-K400146	71
C-K400147	71
C-K400148	71
C-K400165	432
	902
C-K400168	430
C-K400169	430
C-K400170	432
	902
C-K400171	432
	902
C-U100001	404
	405
C-U100002	161
C-U100003	161
C-U100004	161
C-U200002	306
	311
	316
	320
C-U200003	306
	311
	316
	320
C-U200004	306
	311
	316
	320
C-U200006	306
	311
	316
	320
C-U200007	306
	311
	316
	320
C-U200008	307
	312
	317
	321
C-U200009	307
	312
	317
	321
C-U200010	307
	312
	317
	321
C-U200012	307
	312
	317
	321
C-U200013	307
	312
	317
	321
C-U200014	307
	312
	317
	321
C-U200015	307
	312
	317
	321
C-U200016	308
	313
C-U200017	308
	313
C-U200018	308
	313
C-U200020	308
	313
C-U200021	308
	313
C-U200022	308
	313
C-U200023	308
	313
C-U200026	320
C-U200027	320
C-U300007	125
	161
	212
	238
C-U300008	125
	161
	212
	238
C-U300009	125
	161
	212
	238
C-U300010	125
	161
C-U300011	125
C-U300012	161
C-U300013	130
	150
	161
	174
	183
C-U300014	130
	150
	161
	174
	183
C-U300015	130
	150
	161
	174
	183
	212
	238
C-U300016	130
	150
	161
	174
	183
	212
	238
C-U300017	130
	150
	161
	174
	183
	212
	238
C-U300018	474
C-U300019	71
C-U300020	71
C-U300021	71
C-U300022	71
C-U300023	471
C-U300024	471
C-U300025	471
C-U300026	471
C-U300027	471
C-U300028	471
C-U300029	125
	130
	150
	161
	174
	183
	212
	238
C-U300030	125
	130
	150
	161
	174
	183
	212
	238
C-U300031	125
	130
	150
	161
	174
	183
	212
	238
C-U300032	471
C-U300033	471
C-U300034	130
	161
	174
	183
C-U300035	71
C-U300036	71
C-U300037	71
C-U300038	71
C-U300039	71
C-U300040	71
C-U300041	71
C-U300042	71
C-U300043	161
C-U300044	161
C-U300045	161
C-U300046	161
C-U300047	161
C-U500008	281
C-U500009	281
C-U500010	280
C-U500011	280
C-U500012	280
C-U500013	280
C-V200001	306
C-V200003	307
C-V200004	308
C-V200005	430
	432
	902
C-V200006	311
C-V200007	312
C-V200008	313
C-V400002	398
C-V400004	306
C-V400006	311
C-V400008	307
C-V400010	312
C-V400012	308
C-V400014	313
C-V400015	316
	320
C-V400016	316
	320
C-V400017	317
	321
C-V400018	317
	321
C-V400019	404
C-V400020	404
C-V400021	405
C-V400022	405
C-V400023	404
	405
C-V400024	404
C-V400025	405
C-V400026	405
C-V400027	404
C-V400029	404
C-V400031	405
C-V400033	405
C-V400035	405
C-V400036	405
C-V400037	407
C-V400038	407
C-V400041	406
C-W200001	433
C-W200002	433
C-W200003	433
C-W200004	433
C-W200005	433
C-W200006	433
C-W200007	433
C-W200009	433
C-W200011	433
C-W200013	589
C-W200014	589
C-W200015	589
C-W200016	589
C-W200017	589
C-W200018	589
	972
C-W200019	589
	972
C-W200020	589
C-W200021	589
C-W200022	589
C-W200023	589
C-W300001	433
	903
C-W400001	398
C-W400002	398
C-W400003	398
C-W400004	777
C-W400005	589
	972
C-W500001	284
	426
C-W600001	957
	958
KIT0014	969
KIT0027	954
W-F500001	835
W-F900001	835
W-F900002	835
	851
W-U300001	459

Printed in Italy
October 2024

Credits
Matteo Lavazza Seranto Photography Studio
Imagine Computer Graphics
Nerokubo
Orygine

Mural illustration
Emanuele Nicoletti Serra

Thanks to
Martino Lorenzon for artwork on page 148

and

LAMINAM
SUPERIOR NATURAL SURFACES

The drawings, the measurements, the materials and the colours in this catalogue are understood to be indicative. In the interest of the clientele, the company reserves the right to modify the models at any time and without any obligation of advance notice.

"Linea Light Group" reserves the right, without any advance notice, to change the characteristics of their products, as well as the availability of the same at any time. No product, relative technical data, illustrations and information in the catalogue are binding for **"Linea Light Group"**. **"Linea Light Group"** will not be held liable for any illustration, text and/or translation errors. More product characteristics are contained in the relative technical data sheets and instruction sheets. This catalogue is protected by copyright (law 22/04/1941 No. 633 and law 14/12/1942 No. 1485: this prohibits any reproduction, total or even partial). All values indicated in the catalogue are measured values. There is a +/- 10% tolerance for the flow, CCT and power data.


FSC
www.fsc.org
MISTO
A sostegno della gestione forestale responsabile
FSC® C112256


Printed with Saphira Eco
HEIDELBERG

Addresses

Linea Light HQ Italy
Via Europa, 14
31028 Vazzola TV
Italy

+39 0438 444826
info@linealight.com

Linea Light HUB Milano
Via Giovanni Boccaccio, 15/A
20123 Milano MI
Italy

+39 02 36750915
milano@linealight.com

Linea Light Nord-Est
Via Medoaco 4
c/o Hope Center
35135 Padova PD
Italy
+39 049 7969440
nordest@linealight.com

Linea Light Roma
Via La Spezia, 34
00182 Roma
Italy

+39 06 68589134
info@linealightroma.com

Linea Light UK
Suite205 The business design center
52 Upper Street Islington
N10QH London
United Kingdom
+44 0203 6371983
info@linealight.co.uk

Linea Light France
ZA 12A rue des Artisans
68700 Cernay
France

+33 389 75 52 23
info@linealight.fr

Linea Light Deutschland
Aktienstraße 214
45473 Mülheim an der Ruhr
Germany

+49 208 299979-0
service@linealight.de

Linea Light Greece
538 Vouliagmenis Ave.
17456 Alimos Athens
Greece

+30 210 9940559
g.virinis@linealight.com

Linea Light Spain
C/ Longares, 48
28022 Madrid
Spain

+34 912534773
gestion@linealight.com

Linea Light USA - Inter Lux
3741 Commerce Drive - Suites 306-308
MD21227 Baltimore
USA

+1 410 381 1497
answers@inter-lux.com

Linea Light GCC
P.O. Box 125902
Jumeirah Lake Towers JBC2
35th Floor Office 04
Dubai UAE
+971 4 4218275
info@linealight.ae

Linea Light Asia - Pacific
No. 7, Nanyi Huayuan Road,
Industry Avenue, 528478 Xiaolan Town,
Zhongshan City, Guangdong Province
China
+86 760 87618355
info@linealight.com.cn

Linea Light Singapore
21 Kaki Bukit Place, 5th Fl.
416199 Singapore
Singapore

+65 6908 5758
info.sg@linealight.com

linealight.com



LIGHT UP NEW IDEAS!

linealight.com